



## Categories of Digital Investigation Analysis Techniques Based On The Computer History Model

*By*

**Brian Carrier, Eugene Spafford**

*Presented At*

The Digital Forensic Research Conference

**DFRWS 2006 USA** Lafayette, IN (Aug 14<sup>th</sup> - 16<sup>th</sup>)

DFRWS is dedicated to the sharing of knowledge and ideas about digital forensics research. Ever since it organized the first open workshop devoted to digital forensics in 2001, DFRWS continues to bring academics and practitioners together in an informal environment. As a non-profit, volunteer organization, DFRWS sponsors technical working groups, annual conferences and challenges to help drive the direction of research and development.

**<http://dfrws.org>**

# Categories of Digital Investigation Analysis Techniques Based on the Computer History Model

Brian D. Carrier  
and  
Eugene H. Spafford



# DFRWS 2004 Frameworks

- More like process models
- But, there is no unique process for an investigation
- Number of phases were subjective (including ours...)
- Completeness cannot be shown
- Useful for teaching, but not as useful for research and development



# The New Approach

1. Define an investigation model based on a standard computation model.
  - i.e. mathematical model
2. Define analysis technique categories based on the investigation model.




# Finite State Machine

- Finite State Machine (FSM)
  - Set of possible states:  $Q$
  - Set of possible event symbols:  $\Sigma$
  - State change function:  $\delta$ 
$$Q \times \Sigma \rightarrow Q$$
- We assume that a computer **CAN** be represented by a FSM
  - Reduction is not performed during an investigation
  - FSM used for hardware / software independence



# Basic Event Visualization



# Computer History

- A computer's history contains the sequence of its previous states and events
- A digital investigation is a process to answer questions about previous and current states and events.
  - Starts with one or more known states
  - Makes inferences about the others
  - Searches the known and inferred states and events
- If you know the history, you can answer any question.



# Computer History Model

- Goal is to mathematically represent the computer's history.
- Define a set  $T$  with the times that the history exists.
- Map times in set  $T$  to the states in  $Q$  and events in  $\Sigma$  that occurred.

$$h_{ps}: T \rightarrow Q$$

$$h_{pe}: T \rightarrow \Sigma$$





# Dynamic FSM


- Problem: The set of possible states and events at 2 times can be different in real systems. Why?



# Dynamic FSM

- Problem: The set of possible states and events at 2 times can be different in real systems. Why?
- Sets  $Q$  and  $\Sigma$  can change based on:
  - The devices that were connected.
  - The possible states for each device
    - Number of addresses
    - Domain of each address
  - The possible events for each device





# Summary (thus far)

- We assume a computer CAN be represented as a FSM.
- FSM must be dynamic and account for removable devices.
- We can represent the primitive history of the computer as a mapping from times to the FSM.



# Complex Systems

- Modern computers operate at “complex” levels
- Complex states: Defined by virtual storage locations that map and transform to primitive and lower-level storage locations.
  - Files, process memory, data structures...
- Complex events: A single event that causes multiple lower-level events to occur.
  - User-level events, buttons, system calls..
- A history exists for complex states and events



# Dynamic Complex Systems

- Number of possible complex events and states is based on:
  - The primitive devices connected
  - The programs on each device
  - The capabilities of each program
- A file exists only if programs on the computer supports the file system....
- We can map between the different layers (file type rules, event decomposition...)



# Summary (thus far)

- The computer history model can represent complex states and events.
- Complex capabilities are based on the devices and programs that exist.
- There is (at least) one mapping between the primitive and complex histories.



# Analysis Technique Categories

- If the computer history is known, we can answer any question.
- Our Hypothesis: The techniques required to define the computer history model are the same as required for a digital investigation.





# Category Overview

- Eight categories and each defines specific variables (27 variables total)
- Organizing into eight is intuitive, but not required
  - There is still subjectivity
- Each category has at least one class of techniques defined based on model and practice
  - Classes may increase over time



# History Duration Category (#1)

- Defines the set  $T$  of times when the computer has a history.
- When did the computer first exist?
  - Did the computer exist during the timeframe being investigated?
- Examples:
  - Manufactured date
  - OS Install date
  - Earliest MAC time



# Primitive Storage Capabilities Category (#2)

- Defines the possible states of the system at each time.
  - Which storage devices existed.
  - The possible states of each device.
  - When each device was connected.
- Examples:
  - Hard disk spec or query commands
  - Logs that record connected devices



# Primitive Event Capabilities Category (#3)




- Defines the possible events that could have occurred at each time.
  - The event devices that existed.
  - The possible events and state change functions for each event device.
  - When each device was connected.
- Examples:
  - Processor spec or query commands
  - Logs that record connected devices



# Primitive State and Event Definition Category (#4)

- Defines the states and events that are believed to have occurred
  - Observed states
  - Event and state reconstruction
  - Event and state construction
  - Sampling
  - Capabilities
- Can use one technique for defining a state or event and others for testing.





# Layers of Abstraction

## Definition Category (#5)

- Defines the layers of event abstractions
- Nearly impossible to determine
  - Requires knowledge about development process over lifetime of programs on system
  - Multiple equivalent layers exist
- In practice, make assumptions:
  - User-level events
  - File systems



# Complex Storage Capabilities Category (#6)

- Defines the possible complex storage states
  - Identify the programs that exist at each time (in theory)
  - Identify the complex storage types for each time.
- Examples:
  - Reverse engineer stored data
  - Static / dynamic analysis of programs
  - Program specifications





# Complex Event Capabilities Category (#7)


- Defines the possible complex events at each time.
  - Identify the programs that exist at each time (in theory)
  - Identify the complex events defined by each program
- Examples:
  - Static / dynamic analysis of programs
  - Program specifications



# Complex State and Event Definition Category (#8)

- Defines complex states and events that are believed to have occurred.
- Make inferences about previous events and states.
- Examples:
  - Event and state abstraction
  - Event and state materialization
  - Event and state reconstruction
  - Event and state construction





# Summary

- Previous frameworks / classifications not based on mathematical models.
- This work defined an investigation model based on a standard computation model.
- Categories of techniques can be shown to be complete, but structure is still subjective.
- The difference between previous frameworks is how they organize these categories.



# Questions?

Brian Carrier

[carrier@digital-evidence.org](mailto:carrier@digital-evidence.org)

Eugene Spafford

[spaf@cerias.purdue.edu](mailto:spaf@cerias.purdue.edu)



[www.cerias.purdue.edu](http://www.cerias.purdue.edu)