



## XIRAF - Ultimate Forensic Querying

*By*

**Wouter Alink, Raoul Bhoedjang, Peter Boncz and Arjen de Vries**

*Presented At*

The Digital Forensic Research Conference

**DFRWS 2006 USA** Lafayette, IN (Aug 14<sup>th</sup> - 16<sup>th</sup>)

DFRWS is dedicated to the sharing of knowledge and ideas about digital forensics research. Ever since it organized the first open workshop devoted to digital forensics in 2001, DFRWS continues to bring academics and practitioners together in an informal environment. As a non-profit, volunteer organization, DFRWS sponsors technical working groups, annual conferences and challenges to help drive the direction of research and development.

**<http://dfrws.org>**

# XIRAF

## Ultimate Forensic Querying

DFRWS - August 15, 2006

Wouter Alink, Raoul Bhoedjang  
Netherlands Forensic Institute

Peter Boncz, Arjen de Vries  
Centrum voor Wiskunde en Informatica



# Introduction

## XIRAF

*“An XML Information Retrieval  
Approach to Digital Forensics”*

Collect, manage, and query information  
extracted from digital evidence

## Outline

- Problem statement
- XIRAF approach
- XIRAF architecture
- Forensic application areas
- Initial experiments
- Conclusion

# Typical investigation steps

1. Media capture
2. Feature extraction
3. Analysis
4. Reporting


## Problem identification

- Large amounts of data
  - Investigation restricted by deadlines
  - Too much information to track manually
- Diversity of data and tools
  - Many different formats
  - Many stand-alone forensic tools

## Approach

- Clean separation between feature extraction and analysis
- A single, XML-based output format for tools
- XML database technology to analyze extracted features
- Use of existing forensic analysis tools

# XIRAF architecture






# Tool wrapper

```
<photo>
  <camera>Canon</camera>
  <taken-on>
    <date>15-12-2005</date>
  </taken-on>
</photo>
```

```
//file[mime="image/jpeg"]
```


- metadata (features/traces)
- new view of the original data




## Tool repository

- Feature extraction tools
- Gain knowledge about an 'object':
  - volume
  - file-system
  - image
  - email
- Some of the wrapped tools:
  - file-system dissector
  - windows registry analyzer
  - EXIF-data parser
  - carving tool
  - IE-history parser
  - Hashing tool


# XIRAF architecture




# Feature extraction framework



# Feature extraction framework




# Feature extraction



```
<case name="testcase">
  <image path="/casedata/HD-A.img"/>
    <image path="/casedata/HD-B.e01"/>
      <image path="/casedata/HD-C.e01"/>
        </case>
```


```
  <image path="/casedata/HD-C.e01">
    <volume label="MP3"/>
  </image>
</case>
```

# XIRAF architecture





# Virtual BLOB and XML




```
<case name="testcase">
  <image name="Phone data" start="70000" end="74999"/>
  <image name="sizedata/HD-B.img" start="20000" end="29999"/>
  <image name="sizedata/HD-C.e01" start="30000" end="59999"/>
</case>
<modified><date>2006-08-15T09:10:00</date></modified>
</file>
...
<volume type="FAT" start="1000" end="19999"/>
<volume type="NTFS" start="35000" end="39999"/>
```



## Storage subsystem

- Virtual BLOB mapping
  - evidence files
  - alternative representations
- Single XML document
  - extracted features
  - references to layout

# XIRAF architecture



## XQuery language

- Database language:
  - large XML documents
  - sorting/grouping/selecting/(updating)
- Example: timeline
  - different tools produce date-elements

```
for $i in doc("case.xml")//date
order by $i
where $i > $lowerbound
      and $i < $upperbound
return $i
```

## Forensic application areas

- search for keywords, MD5s, URLs

```
for $i in doc("case.xml")//file
for $j in doc("CP-hashes.xml")//md5
where $i/md5 = $j
return <file> { $i/@name } </file>
```

```
let $word_list :=
    doc("terrorism-words.xml")//word
for $i in doc("case.xml")//*
where some $j in $word_list
    satisfies blob-contains($i,$j)
return element { name($i) } { $i/@* }
```

## Benefits

- Exploit exhaustive runs of tools
- Use knowledge from previous investigations
- Integrated data schema
- Added functionality:
  - XQuery extensions to relate XML to Virtual BLOB content

## XIRAF Query Page

Project: **javaPatrick**  
Number of files: 89017  
Number of folders: 4471

Please select an object of interest:

### Limiting Results

The item should:

☐ contain the keyword

☒ contain  date between

and

☒ contain

☒ contain


with key

☒ contain a

with keyword (optional):


[back to project page](#) | [explain page](#)

```
let $d := doc("case.xml")
for $i in $d//%object_of_interest%
where $i/descendant::%contains%[so-contains(%keyword_1%)]
and $i/ancestor::%contained%[so-contains(%keyword_2%)]
and (some $j in $i//%date%//date
satisfies $j >= %lowerbound% and $j < %upperbound%)
return element { name($i) } { $i/@* }
```





# XIRAF architecture



## Initial Experiments

- Evidence: 2 hard disks
  - (2 x 120GB)
- ~200MB XML
  - ~2.5M elements
- Recognized ~90000 files
  - file-systems / unallocated space
- ~500000 timestamps
  - file-system, registry, EXIF, .LNK, log-entry, cookie, etc



## Conclusion

- Separation of feature extraction and analysis seems a viable approach
- Integrated querying of multiple tools becomes possible

## Status & Future Work

- Prototype implementation (Java/Python)
- Make system production-ready
- More tools, query patterns
- Connect XIRAF to existing knowledge-bases

## More information

- [xiraf-info@holmes.nl](mailto:xiraf-info@holmes.nl)
- <http://www.forensischinstituut.nl/>
- <http://monetdb.cwi.nl/>