



Privacy-Preserving Email Forensics

By

Frederik Armknecht, Andreas Dewald and Michael Gruhn

Presented At

The Digital Forensic Research Conference

DFRWS 2015 USA Philadelphia, PA (Aug 9th - 13th)

DFRWS is dedicated to the sharing of knowledge and ideas about digital forensics research. Ever since it organized the first open workshop devoted to digital forensics in 2001, DFRWS continues to bring academics and practitioners together in an informal environment. As a non-profit, volunteer organization, DFRWS sponsors technical working groups, annual conferences and challenges to help drive the direction of research and development.

<http://dfrws.org>

Privacy-Preserving Email Forensics (PPEF)

Frederik Armknecht (University of Mannheim), Andreas Dewald (Friedrich-Alexander University)

Sven Kälber (Speaker, Friedrich-Alexander University)




- Idea, motivation & contributions
- The big picture / overall scheme design
- Own implementation details
 - Protection mechanism
 - Extraction mechanism
- Cryptographic building blocks
- Practical implementation and evaluation
- Summary & conclusion
- Limitations & future work


- Privacy protection of employees in (large-scale) digital forensic investigations
- Revealing of only case relevant information
 - Achieved through strong cryptographic standards
- Operation principle:
 1. Extraction of mailboxes
 2. Encryption of all emails by applying our introduced scheme
 3. Hand over of only encrypted mailboxes to third-party investigators
 4. Decryption of individual emails only possible on t matching keywords

- Private use of corporate e-mail accounts
 - Private e-mails typically contain private and very sensitive data
 - This information is often highly protected by local data protection laws
 - Typically case irrelevant information in private e-mails
- Today's approaches and tools are often limited to filtering, which is not enforced
 - Investigators might read private e-mails by accident or on purpose
- Case „United States v. Carey“ (1999)
- Problems of leaving the e-mails at the company's IT
 - Leaks search queries of investigators
 - Is costly and time consuming because of the high degree of interaction needed
 - Trust issues


- Novel approach for privacy-preserving email forensics allowing for **non-interactive** threshold keyword search on **encrypted** emails
- Proof-of-concept implementation in Python and as a Autopsy v3 plug-in
- An evaluation of the practical applicability in terms of:
 - en- / decryption runtime performance
 - introduced storage overhead
 - brute-force / dictionary attack vulnerability



Decryption success



Decryption fail



- Encryption of e-mails (protection mechanism):
 - Each e-mail plaintext **P** is encrypted to a cyphertext **C** with an individual secret key **k** .
 - **k** gets split up in shares and might later be reconstructed
 - Support for blacklisting of commonly used words (e.g. „the“)
 - Support for whitelisting of investigation keywords (e.g. „fraud“)
- Decryption of e-mails (extraction mechanism):
 - Only possible when the e-mail in question contains at least **t** keywords.
 - Investigator learns nothing about the secret key of other e-mails upon successfully decrypting one e-mail.
 - Investigator learns nothing about the content of the mail if **$t-1$ or less keywords** match the content of the e-mail.

1. Encryption function:

- AES-128 in CBC mode used for the encryption of individual e-mails
- Add characteristic padding p as the first block to be decrypted (*e.g.* $[0, \dots, 0]$)

2. Shamir's Secret Sharing

- Used for splitting the secret key k into shares
- Details follow on the next slide


3. Mapping

- Hash function: SHA-256 part of the mapping function
- Further tweaks for efficiency reasons


- **Functionality:**
 - Input: Two integers $t \leq n$, a secret k
 - Output: n shares $k \downarrow 1, \dots, k \downarrow n$
- **Security**
 - Given at least t shares, one can reconstruct the secret
 - If less than t shares are known, reconstruction not possible
- **Realization**
 - Polynomial interpolation of a polynomial of degree $t-1$

Working Principle

- Input: Two integers $t \leq n$, Secret k
- Choose polynomial $p(x)$ of degree $t-1$
- Compute shares: $(x_1, y_1), \dots, (x_n, y_n)$ (here: $n=12$) with $y_i = p(x_i)$
- Reconstruction from t shares:
 - Interpolate $p(x)$
 - Compute $k = p(x_0)$



The Mapping Function



- Task: Map 256-bit hash values to 256-bit shares $(x \downarrow i, y \downarrow i)$
- Approach:
 - Interpret hash values as $(x \downarrow i, z \downarrow i)$ (128-bit + 128-bit)
 - Use the values $x \downarrow i$ to compute shares $(x \downarrow i, y \downarrow i) = (x \downarrow i, p(x \downarrow i))$
 - Find mapping $g(x)$ such that $g(x \downarrow i) = y \downarrow i \text{ XOR } z \downarrow i$
 - Function $G(h \downarrow i) = G(x \downarrow i, z \downarrow i) = (x \downarrow i, g(x \downarrow i) \text{ XOR } z \downarrow i) \rightarrow (x \downarrow i, y \downarrow i)$
- Getting the mapping:
 - Core idea: compute polynomial $g(x)$ such that $g(x \downarrow i) = y \downarrow i \text{ XOR } z \downarrow i$
 - Problem: requires to interpolate polynomial of degree $n \rightarrow$ effort is $O(n^3)$, too slow
 - Idea: Split range of x into l subsets, e.g. determined by the l last bits
 - Interpolate polynomials $g \downarrow j(x)$ for each subset
 - Effort: interpolate l polynomials, each of degree $\approx n/l$
 - Overall effort: $l \cdot (n/l)^3 = n^3 / l^2$

1. Python en- / decrytion of mailboxes


Supported mailbox formats:

mbox

pst

MH (RFC 822)

Maildir




```
C:\Windows\system32\cmd.exe


C:\ppef>python ppef_gen.py pst MailArchive.pst MailArchive.ppef 3 blacklist.txt
1/4
2/4
3/4
...
C:\ppef>
```

2. PPEF plugin for Autopsy v3


PPEF Autopsy plug-in



PPEF Autopsy plug-in



PPEF Autopsy plug-in



PPEF Autopsy plug-in

TestCase - NetBeans Platform 7.3.1

File View Tools Window Help

Close Case + Add Data Source Generate Report

PPEF Search hosting localhost userdir Keyword Lists Search...

Directory Listing

LogicalFileSet1

Table Thumbnail

Name	Location	Modified Time	Change Time	Access Time
Mailarchive.ppef	/LogicalFileSet1/Mailarchive.ppef	0000-00-00 00:00:00	0000-00-00 00:00:00	0000-00-00 00:00:00


1 Results

Hex Strings Metadata Results Text Media

Page: 1 of 303 Page Go to Page:

```
0x00002840: 4F E4 D1 A2 DF 5F 2B 53 13 AE 37 A5 E6 5E EC ED O.....+S...7..^..
0x00002850: 40 02 C8 1C D4 56 67 8C FE A2 C7 D9 52 A9 34 D7 @....Vg.....R.4.
0x00002860: 2A 24 98 CB FD A1 E1 73 49 88 56 B5 31 03 0A 67 *$.....sI.V.1..g
0x00002870: 07 47 8A 37 59 27 EA 97 CE 37 02 66 FF DD B0 EC .G.7Y'....7.f....
0x00002880: 8C 17 67 C4 F5 E3 6E 70 55 F0 51 44 8D 1B 06 AB .g...npU.QD....
0x00002890: EB 39 B7 B7 DC E0 AD 19 D4 80 96 C5 0B 10 5B 7D .9.....[.
0x000028a0: BB 0C 93 29 5B 1F 15 1E 9F DC 5B 04 3D A6 EA B6 ...)[.....[.=...
0x000028b0: CA E3 69 E7 53 C8 41 FC EB FF C2 5C 6F 5C 71 54 .i.S.A.....\o\qT
0x000028c0: 7C B8 86 2A 3F DE 78 63 AE 6B 08 1A F4 CD 24 55 |...*?xc.k...$U
0x000028d0: E9 64 FC 30 28 D7 E1 47 42 E0 18 0C 1F CC 24 DC .d.0(...GB.....$.
0x000028e0: 2A DF E3 AF AB 6C 53 22 9E 6B 4C C9 13 7A F8 E5 +...1S".kL.z...
0x000028f0: D8 3F 83 58 11 E6 29 54 C5 EF C8 33 94 FA 42 C4 .?.X...)T...3..B.
0x00002900: B7 45 84 13 20 9C E3 C4 F7 CC 20 6A 17 17 F7 ED .E.....j....
0x00002910: 0D 5A 12 9E 83 D7 81 1B 1A 5F B0 5B C8 3E 2B 43 .Z.....[.>+C
```

PPEF Autopsy plug-in



TestCase - NetBeans Platform 7.3.1

File View Tools Window Help

Close Case Add Data Source Generate Report

PPEF Search hosting localhost userdir Keyword Lists Search...

Directory Listing

Default 2 Results

E-Mail From	E-Mail To	E-Mail CC	Date Received	Subject	Source File
	""users@		2001-12-05 2...	RE: Help with	ppef_SearchResult
	<users@		2001-12-05 2...	Re: Help with	ppef_SearchResult

Hex Strings Metadata Results Text Media

Result: 1 of 2 Result

virtual hosting

The data set used in our evaluation consists of 5 different mailboxes:

- *Apache* – httpd user mailing list (75724 e-mails)
- *Work* – personal work e-mails (1590 e-mails)
- *A, B, C* – private e-mail accounts (511, 349, 83 e-mails)

Evaluations:

1. Encryption runtime performance
2. Encryption storage overhead
3. Search / decryption runtime performance
4. Brute-force attack performance

- Time (in seconds) to encrypt the corresponding emails of each account
- Average encryption rate: 13.5 emails/sec
 - Encryption of large mailboxes might take several hours (< 2h for 75724 e-mails) , but only needs to be done once!

	Apache [s]	Work	A	B	C
Min	0.004	0.005	0.005	0.005	0.005
Max	31.745	1.403	1.932	1.117	0.460
Avg	0.082	0.136	0.122	0.110	0.173
Med	0.072	0.115	0.101	0.074	0.150
σ	0.133	0.120	0.132	0.153	0.071
Σ	6243.511	217.242	62.842	38.535	14.367

- Encryption with AES does not add much storage overhead (33 – 48 bytes per mail)
- Main storage overhead factor is the mapping function (on average 582.4 bytes per mail)
- Average storage overhead: 5.2 %

	Apache	Work	A	B	C
Size Raw [KB]	376,551	418,680	16,386	47,486	6,676
Size PPEF [KB]	418,870	420,418	16,885	47,821	6,806
Overhead	11.2 %	0.4 %	3.0 %	0.7 %	1.9 %

- Time (in seconds) to search each e-mail for 3 keywords and decrypt matching e-mails
- Average search and decryption rate: 98 mails/sec
 - Searches on large mailboxes take time (< 15min) but are still feasible

	Apache [s]	Work	A	B	C
Min	0.0090	0.0096	0.0098	0.0097	0.0098
Max	0.0598	0.1645	0.0139	0.1508	0.0148
Avg	0.0115	0.0137	0.0114	0.0123	0.0117
Med	0.0115	0.0117	0.0113	0.0113	0.0116
σ	0.0007	0.0103	0.0007	0.0086	0.0009
Σ	876.8591	21.7977	5.8650	4.2982	0.9750

- Brute-force attacks to decrypt the whole mailbox ($\pi=0.99$) or a random half of the mailbox ($\pi=0.5$)
- Using 4 different vocabularies
 - Oxford English Dictionary (171,476 words)
 - 50 % of the Oxford English Dictionary (85,738 words)
 - Vocabulary in daily speech edu. person (20,000 words)
 - Vocabulary of uneducated person (10,000 words)

π	N	Apache	Work	A	B	C
0.99	171,476	$1.15 \cdot 10^8$	$3.26 \cdot 10^5$	$1.23 \cdot 10^5$	$1.17 \cdot 10^5$	5,373.15
0.50	171,476	$1.73 \cdot 10^7$	49,072.84	18,565.34	17,638.94	808.74
0.99	85,738	$1.44 \cdot 10^7$	40,753.36	15,418.00	14,648.51	671.63
0.50	85,738	$2.17 \cdot 10^6$	6,133.99	2,320.64	2,204.82	101.09
0.99	20,000	$1.83 \cdot 10^5$	517.23	195.68	185.91	8.52
0.50	20,000	27,510.37	77.85	29.45	27.98	1.28
0.99	10,000	22,843.44	64.64	24.46	23.24	1.07
0.50	10,000	3,438.28	9.73	3.68	3.50	0.16

- We proposed a novel approach for privacy-preserving email forensics allowing for **non-interactive** threshold keyword search on **encrypted** e-mails.
- We developed a **prototype-implementation** in Python and an **Autopsy plug-in** that supports multiple well-known mailbox formats.
- We **evaluated the practical applicability** in terms of en- / decryption performance, storage overhead and brute-force vulnerability.
 - Sufficiently large mailboxes are well protected against dictionary (brute-force) attacks

Limitations:

- Scheme based on keyword searches, therefore prone to spelling errors
- No wildcard operator or regular expression possible that allows for more advanced search queries
- Brute-force / dictionary attacks possible

Future work:

- Support for wildcard usage within the search keywords

Thank you for your attention!

Speaker:

Sven Kälber - sven.kaelber@cs.fau.de

Authors:

Frederik Armknecht – armknecht@uni-mannheim.de

Andreas Dewald – andreas.dewald@fau.de

TestCase - NetBeans Platform 7.3.1

File View Tools Window Help

Close Case Add Data Source Generate Report

PPEF Search Keyword Lists Search...

Directory Listing

LogicalFileSet1 1 Results

Table Thumbnail

Name	Location	Modified Time	Change Time	Access Time
Mailarchive.ppef	/LogicalFileSet1/Mailarchive.ppef	0000-00-00 00:00:00	0000-00-00 00:00:00	0000-00-00 00:00:00

!!!

Hex Strings Metadata Results Text Media

Page: 1 of 303 Page Go to Page:

```

0x00002840: 4F E4 D1 A2 DF 5F 2B 53 13 AE 37 A5 E6 5E EC ED 0.....+S..7..^..
0x00002850: 40 02 C8 1C D4 56 67 8C FE A2 C7 D9 52 A9 34 D7 @....Vg....R.4.
0x00002860: 2A 24 98 CB FD A1 E1 73 49 88 56 B5 31 03 0A 67 *$......sI.V.1..g
0x00002870: 07 47 8A 37 59 27 EA 97 CE 37 02 66 FF DD B0 EC .G.7Y'...7.f....
0x00002880: 8C 17 67 C4 F5 E3 6E 70 55 F0 51 44 8D 1B 06 AB ..g...npU.QD....
0x00002890: EB 39 B7 B7 DC E0 AD 19 D4 80 96 C5 0B 10 5B 7D .9.....[]
0x000028a0: BB 0C 93 29 5B 1F 15 1E 9F DC 5B 04 3D A6 EA B6 ...)[.....[.=...
0x000028b0: CA E3 69 E7 53 C8 41 FC EB FF C2 5C 6F 5C 71 54 ..i.S.A....\o\qT
0x000028c0: 7C B8 86 2A 3F DE 78 63 AE 6B 08 1A F4 CD 24 55 |..*?.xc.k....$U
0x000028d0: E9 64 FC 30 28 D7 E1 47 42 E0 18 0C 1F CC 24 DC .d.0(..GB.....$.
0x000028e0: 2A DF E3 AF AB 6C 53 22 9E 6B 4C C9 13 7A F8 E5 *......lS".kL..z..
0x000028f0: D8 3F 83 58 11 E6 29 54 C5 EF C8 33 94 FA 42 C4 .?X...)T...3..B.
0x00002900: B7 45 84 13 20 9C E3 C4 F7 CC 20 6A 17 17 F7 ED .E.. .... j....
0x00002910: 0D 5A 12 9E 83 D7 81 1B 1A 5F B0 5B C8 3E 2B 43 .Z....._.[.>+C

```

!!!

- Task: Map 256-bit hash values to 256-bit key shares
- Approach
 - Interpret hash values as (128 bit + 128 bit)
 - Use the values to compute key shares
 - Find a mapping such that
 - Function
- Getting the Mapping
 - Core idea: compute polynomial such that
 - Problem: requires to interpolate polynomial of degree n effort is in $\mathcal{O}(n^2)$, too
 - Idea: Split range of \mathcal{H} into subsets, e.g., determined by the first k bits
 - Interpolate polynomials for each subset
 - Effort: interpolate polynomials, each of degree k
 - Overall effort: