

## WORK ORDER

MASPL						
<b>Name:</b> : J.S. TECHNOLOGIES, NO 2, II FLOUR, ARS AVENUE, DTDC COURIER UPSTAIR, SURAMANGALAM MAIN ROAD, SALEM-636005  <b>Billing Address:</b> : NO 2, II FLOUR, ARS AVENUE, DTDC COURIER UPSTAIR, SURAMANGALAM MAIN ROAD, SALEM-636005  <b>Shipping Address:</b> : NO 2, II FLOUR, ARS AVENUE, DTDC COURIER UPSTAIR, SURAMANGALAM MAIN ROAD, SALEM-636005		<b>P.O No.</b> : JS-02  <b>Date</b> : 30/10/2021		<b>W.O No.</b> : WO-2122-OCT-236  <b>Date</b> : 30/10/2021		
Sr.No	Item Description	Qty	Module Details / Rate	Discount	GST	Total
1	<b>THERMOWELL</b> Part No:TW 21 / 1000 MM BARSTOCK THERMOWELL, TYPE: FLANGED MAKE: AAVAD CONSTRUCTION: BARSTOCK SHANK DIA: 21 MM BORE: 10 MM SHANK MATERIAL: SS 316 TOTAL LENGTH: 1000 MM PROCESS CONNECTION: 25 NB ASA 150# RF, FIXED FLANGE, SS316, INSTRUMATE CONNECTION: 1/2" BSP F"	2	5,350	35	18	8,207
2	<b>K TYPE THERMOCOUPLE SENSOR</b> Part No:AKWS - 8 X 1000 MM TYPE: K (CR/AL) MAKE: AAVAD MODEL : AKWS CONFIGURATION: SIMPLEX NO. OF WIRE IN SIMPLEX:2 TOTAL NO.OF WIRES: 2 MATERIAL OF CONSTRUCTION : SS 316 INSULATION : COMPACTED MGO INSULATION PROCESS CONNECTION: BSP PROCESS CONNECTION SIZE : 1/2 " (M) ADJUSTABLE PROTECTION HEAD: DIE-CAST ALUMINUM HEAD WITH THREADED CAP & CHAIN HEAD PROTECTION CLASS :IP-65 HEAD CABLE ENTRY CONNECTION : ¾ "ET NO. OF CABLE ENTRY : SINGLE TERMINAL BLOCK : NICKEL PLATED CERAMIC TERMINAL BLOCK OD: 8 MM LENGTH: 1000 MM	0	1,294	0	18	0

3	Part No:TW 21 / 750 MM BARSTOCK THERMOWELL, TYPE: FLANGED MAKE: AAVAD CONSTRUCTION: BARSTOCK SHANK DÍA: 21 MM BORE: 10 MM SHANK MATERIAL: SS 316 TOTAL LENGTH: 750 MM PROCESS CONNECTION: 25 NB ASA 150# RF, FIXED FLANGE, SS316, INSTRUMATE CONNECTION: 1/2" BSP F"	2	4,375	35	18	6,711
4	<b>K TYPE THERMOCOUPLE SENSOR</b> Part No:AKWS - 6 X 815 MM TYPE: K (CR/AL) MAKE: AAVAD MODEL : AKWS CONFIGURATION: SIMPLEX TOTAL NO.OF WIRES: 2 MATERIAL OF CONSTRUCTION : SS 316 INSULATION : COMPACTED MGO INSULATION PROCESS CONNECTION: BSP PROCESS CONNECTION SIZE : 1/2 " (M) ADJUSTABLE PROTECTION HEAD: DIE-CAST ALUMINUM HEAD WITH THREADED CAP & CHAIN HEAD PROTECTION CLASS :IP-65 HEAD CABLE ENTRY CONNECTION : ¾ "ET NO. OF CABLE ENTRY : SINGLE TERMINAL BLOCK : NICKEL PLATED CERAMIC TERMINAL BLOCK OD: 6 MM LENGTH: 815 MM	2	1,086	35	18	1,666
5	<b>K TYPE THERMOCOUPLE SENSOR</b> Part No:AKWS - 6 x 500 MM TYPE: K (CR/AL) MAKE: AAVAD MODEL : AKWS CONFIGURATION: SIMPLEX TOTAL NO.OF WIRES: 2 MATERIAL OF CONSTRUCTION : SS 316 INSULATION : COMPACTED MGO INSULATION PROCESS CONNECTION: BSP PROCESS CONNECTION SIZE : 1/2 " (M) ADJUSTABLE PROTECTION HEAD: DIE-CAST ALUMINUM HEAD WITH THREADED CAP & CHAIN HEAD PROTECTION CLASS :IP-65 HEAD CABLE ENTRY CONNECTION : ¾ "ET NO. OF CABLE ENTRY : SINGLE TERMINAL BLOCK : NICKEL PLATED CERAMIC TERMINAL BLOCK OD: 6 MM LENGTH: 500 MM	2	724	35	18	1,111

6	<b>J TYPE THERMOCOUPLE SENSOR</b> Part No:AJWS - 6 X 500 MM TYPE: J (IR/CO) MAKE: AAVAD MODEL : AJWS CONFIGURATION: SIMPLEX TOTAL NO.OF WIRES: 2 MATERIAL OF CONSTRUCTION : SS 316 INSULATION : COMPACTED MGO INSULATION PROCESS CONNECTION: BSP PROCESS CONNECTION SIZE : 1/2 " (M) ADJUSTABLE PROTECTION HEAD: DIE-CAST ALUMINUM HEAD WITH THREADED CAP & CHAIN HEAD PROTECTION CLASS :IP-65 HEAD CABLE ENTRY CONNECTION : ¾ "ET NO. OF CABLE ENTRY : SINGLE TERMINAL BLOCK : NICKEL PLATED CERAMIC TERMINAL BLOCK OD: 6 MM LENGTH: 500 MM	3	710	35	18	1,634
7	<b>K TYPE THERMOCOUPLE SENSOR</b> Part No:AKWS - 6 X 350 MM TYPE: K (CR/AL) MAKE: AAVAD MODEL : AKWS CONFIGURATION: SIMPLEX TOTAL NO.OF WIRES: 2 MATERIAL OF CONSTRUCTION : SS 316 INSULATION : COMPACTED MGO INSULATION PROCESS CONNECTION: BSP PROCESS CONNECTION SIZE : 1/2 " (M) ADJUSTABLE PROTECTION HEAD: DIE-CAST ALUMINUM HEAD WITH THREADED CAP & CHAIN HEAD PROTECTION CLASS :IP-65 HEAD CABLE ENTRY CONNECTION : ¾ "ET NO. OF CABLE ENTRY : SINGLE TERMINAL BLOCK : NICKEL PLATED CERAMIC TERMINAL BLOCK OD: 6 MM LENGTH: 350 MM	2	646	35	18	991

8	<b>J TYPE THERMOCOUPLE SENSOR</b> Part No:AJWS - 6 X 350 MM TYPE: J (IR/CO) MAKE: AAVAD MODEL : AJWS CONFIGURATION: SIMPLEX TOTAL NO.OF WIRES: 2 MATERIAL OF CONSTRUCTION : SS 316 INSULATION : COMPACTED MGO INSULATION PROCESS CONNECTION: BSP PROCESS CONNECTION SIZE : 1/2 " (M) ADJUSTABLE PROTECTION HEAD: DIE-CAST ALUMINUM HEAD WITH THREADED CAP & CHAIN HEAD PROTECTION CLASS :IP-65 HEAD CABLE ENTRY CONNECTION : ¾ “ET NO. OF CABLE ENTRY : SINGLE TERMINAL BLOCK : NICKEL PLATED CERAMIC TERMINAL BLOCK OD: 6 MM LENGTH: 350 MM	0	635	0	18	0
	<b>P &amp; F</b>		0		0	0
	<b>Freight</b>		0		0	0
				<b>Total:</b>		<b>20319.36</b>
	<b>Twenty Thousands Three Hundred and Nineteen Rupees Only</b>			<b>Grand Total:</b>		<b>20319.36</b>
<b>Delivery Time /</b> : <b>Date</b>		<b>Delivery by</b> :				
		<b>Courier</b> : <b>Name</b>		<b>Docket No.</b> :		
<b>Prepared by</b> : AMITPATEL		<b>Tested by</b> : AMITPATEL		<b>Remarks</b> :		

NG

PS

Account

Store

Production