

## WORK ORDER

MASPL						
<b>Name:</b> : AMOPHIL CHEMICALS PRIVATE LIMITED, 124/33 A-B, GIDC ESTATE, NANDESARI - VADODARA - 391340, GUJARAT  <b>Billing Address:</b> : 124/33 A-B, GIDC ESTATE, NANDESARI - VADODARA - 391340, GUJARAT  <b>Shipping Address:</b> : 124/33 A-B, GIDC ESTATE, NANDESARI - VADODARA - 391340, GUJARAT		<b>P.O No.</b> : 635  <b>Date</b> : 03/11/2021	<b>W.O No.</b> : WO-2122-NOV-249  <b>Date</b> : 09/11/2021			
Sr.No	Item Description	Qty	Module Details / Rate	Discount	GST	Total
1	Part No:APFS-6*300 MM RTD SENSOR TYPE: PT-100 MAKE: AAVAD MODEL : APFS CONFIGURATION: SIMPLEX NO. OF WIRE IN SIMPLEX:3 TOTAL NO.OF WIRES: 3 TEMPERATURE RANGE : -50 TO 400 DEGREE C MATERIAL OF CONSTRUCTION : SS 316 INSULATION : COMPACTED MGO INSULATION PROCESS CONNECTION: NPT PROCESS CONNECTION SIZE : 1/2 " (M) ADJUSTABLE PROTECTION HEAD: DIE-CAST ALUMINUM FLAMEPROOF HEAD WITH THREADED CAP & CHAIN HEAD PROTECTION CLASS :IP-67 HEAD CABLE ENTRY CONNECTION : 1/2 " NPT NO. OF CABLE ENTRY : SINGLE TERMINAL BLOCK : NICKEL PLATED CERAMIC TERMINAL BLOCK OD: 6 MM LENGTH: 300 MM	3	897	0	18	3,175

2	Part No:APFS-6*1900 MM RTD SENSOR TYPE: PT-100 MAKE: AAVAD MODEL : APFS CONFIGURATION: SIMPLEX NO. OF WIRE IN SIMPLEX:3 TOTAL NO.OF WIRES: 3 TEMPERATURE RANGE : -50 TO 400 DEGREE C MATERIAL OF CONSTRUCTION : SS 316 INSULATION : COMPACTED MGO INSULATION PROCESS CONNECTION: NPT PROCESS CONNECTION SIZE : 1/2 " (M) ADJUSTABLE PROTECTION HEAD: DIE-CAST ALUMINUM FLAMEPROOF HEAD WITH THREADED CAP & CHAIN HEAD PROTECTION CLASS :IP-67 HEAD CABLE ENTRY CONNECTION : 1/2 " NPT NO. OF CABLE ENTRY : SINGLE TERMINAL BLOCK : NICKEL PLATED CERAMIC TERMINAL BLOCK OD: 6 MM LENGTH: 1900 MM	3	1,720	0	18	6,089
3	<b>FLAMEPROOF INDICATOR</b> Part No:AFI-098-RTD-199.9 C INPUT : RTD PT-100, 3 WIRE , FACTORY SET PROGRAMMABLE RANGE : -199.9 TO 199.9 & -200 TO 600 DEG C (JUMPER SELECTABLE) DISPLAY : 3x1/2 DIGIT 7 SEGMENT 0.56" BRIGHT RED LED DISPLAY CALIBRATION: ZERO AND SPAN ADJUSTABLE BY TRIMPOTS ACCURACY: $\pm 0.25\%$ OF FS $\pm$ 1 COUNT RESPONSE TIME: LESS THAN 1 SEC. POWER SUPPLY: 110 OR 230 VAC, 50 HZ (FACTORY SET FOR ANY ONE) NO. OF CABLE ENTRY: TWO AMBIENT TEMPERATURE: 0 TO 55° C HUMIDITY: UP TO 95% NONE CONDENSING ENCLOSURE: FLAME PROOF ENCLOSURE (CMRI CERTIFIED)	3	2,170	0	18	7,682
	<b>P &amp; F</b>		0		0	0

	Freight		0		0	0
				Total:	16945.98	
	Sixteen Thousands Nine Hundred and Forty Six Rupees Only			Grand Total:	16945.98	
Delivery Time / Date		Delivery by				
		Courier Name		Docket No.		
Prepared by : MANISHPRAJAPATI		Tested by : MANISHPRAJAPATI		Remarks : FREIGHT : NILL DELIVERY : 1-2 WEEK		

NG

PS

Account

Store

Prodution