

WORK ORDER

MASPL						
Name: : TORRENT POWER LIMITED, SABARMATI THERMAL POWER STATION, SABARMATI, AHMEDABAD-380005, Billing Address: : SABARMATI THERMAL POWER STATION, SABARMATI, AHMEDABAD-380005, Shipping Address: : SABARMATI THERMAL POWER STATION, SABARMATI, AHMEDABAD-380005,		P.O No. : fro inq. Date : 06/08/2021		W.O No. : WO-2122-AUG-191 Date : 06/08/2021		
Sr.No	Item Description	Qty	Module Details / Rate	Discount	GST	Total
1	DIRECT CABLE RTD (PT-100) SENSOR Part No:APED RTD SENSOR TYPE: PT-100 MAKE: AAVAD MODEL : APED CONFIGURATION: DUPLEX NO. OF WIRE IN SIMPLEX:3 TOTAL NO.OF WIRES: 3+3 ACCURACY : CLASS A TEMPERATURE RANGE : -50 TO 400 DEGREE C MATERIAL OF CONSTRUCTION : SS 316 PROCESS CONNECTION SIZE : 3/4 " (M) ADJUSTABLE CABLE LENGTH: 5MTR CABLE TYPE: TF/TF SENSOR LENGTH: SUITABLE TO THERMOWELL SENSOR OD: 6MM THERMOWELL THERMOWELL U LENGTH: 75 MM THERMOWELL OD : 15 MM ID : 9 MM INSTRUMENT CONNECTION : 3/4 " BSP (F) PROCESS CONNECTION: 3/4 " BSP (M)	1	2,284	14	18	2,318

2	DIRECT CABLE RTD (PT-100) SENSOR Part No:APED-75 RTD SENSOR TYPE: PT-100 MAKE: AAVAD MODEL : APED CONFIGURATION: DUPLEX NO. OF WIRE IN SIMPLEX:3 TOTAL NO.OF WIRES: 3+3 ACCURACY : CLASS A TEMPERATURE RANGE : -50 TO 400 DEGREE C MATERIAL OF CONSTRUCTION : SS 316 PROCESS CONNECTION SIZE : 3/4 " (M) ADJUSTABLE CABLE LENGTH: 5MTR CABLE TYPE: TF/TF SENSOR LENGTH: SUITABLE TO THERMOWELL SENSOR OD: 6MM THERMOWELL THERMOWELL U LENGTH: 393 MM THERMOWELL OD : 15 MM ID : 9 MM INSTRUMENT CONNECTION : 3/4 " BSP (F) PROCESS CONNECTION: 3/4 " BSP (M)	1	3,096	14	18	3,142
3	DIRECT CABLE RTD (PT-100) SENSOR Part No:APED RTD SENSOR TYPE: PT-100 MAKE: AAVAD MODEL : APED CONFIGURATION: DUPLEX NO. OF WIRE IN SIMPLEX:3 TOTAL NO.OF WIRES: 3+3 ACCURACY : CLASS A TEMPERATURE RANGE : -50 TO 400 DEGREE C MATERIAL OF CONSTRUCTION : SS 316 PROCESS CONNECTION SIZE : 3/4 " (M) ADJUSTABLE CABLE LENGTH: 5MTR CABLE TYPE: TF/TF SENSOR LENGTH: SUITABLE TO THERMOWELL SENSOR OD: 6MM THERMOWELL THERMOWELL U LENGTH: 88 MM THERMOWELL OD : 15 MM ID : 9 MM INSTRUMENT CONNECTION : 3/4 " BSP (F) PROCESS CONNECTION: 3/4 " BSP (M)	1	2,320	14	18	2,354

4	DIRECT CABLE RTD (PT-100) SENSOR Part No:APED RTD SENSOR TYPE: PT-100 MAKE: AAVAD MODEL : APED CONFIGURATION: DUPLEX NO. OF WIRE IN SIMPLEX:3 TOTAL NO.OF WIRES: 3+3 ACCURACY : CLASS A TEMPERATURE RANGE : -50 TO 400 DEGREE C MATERIAL OF CONSTRUCTION : SS 316 PROCESS CONNECTION SIZE : 3/4 " (M) ADJUSTABLE CABLE LENGTH: 5MTR CABLE TYPE: TF/TF SENSOR LENGTH: SUITABLE TO THERMOWELL SENSOR OD: 6MM THERMOWELL THERMOWELL U LENGTH: 255 MM THERMOWELL OD : 15 MM ID : 9 MM INSTRUMENT CONNECTION : 3/4 " BSP (F) PROCESS CONNECTION: 3/4 " BSP (M)	1	2,737	14	18	2,778
5	DIRECT CABLE RTD (PT-100) SENSOR Part No:APED RTD SENSOR TYPE: PT-100 MAKE: AAVAD MODEL : APED CONFIGURATION: DUPLEX NO. OF WIRE IN SIMPLEX:3 TOTAL NO.OF WIRES: 3+3 ACCURACY : CLASS A TEMPERATURE RANGE : -50 TO 400 DEGREE C MATERIAL OF CONSTRUCTION : SS 316 PROCESS CONNECTION SIZE : 3/4 " (M) ADJUSTABLE CABLE LENGTH: 5MTR CABLE TYPE: TF/TF SENSOR LENGTH: SUITABLE TO THERMOWELL SENSOR OD: 6MM THERMOWELL THERMOWELL U LENGTH: 48 MM THERMOWELL OD : 15 MM ID : 9 MM INSTRUMENT CONNECTION : 3/4 " BSP (F) PROCESS CONNECTION: 3/4 " BSP (M)	1	2,219	20	18	2,095
	P & F		0		0	0
	Freight		0		0	0
				Total:		12686.21

