

## WORK ORDER

MASPL						
<b>Name:</b> : MARUTI ENTERPRISE, PLOT NO - 5639/G, NR. SHALAMANDIR BUS STOP, VINZOL CROSSING ROAD, PHASE II, G.I.D.C., VATVA, AHMEDABAD 380026  <b>Billing Address:</b> : PLOT NO - 5639/G, NR. SHALAMANDIR BUS STOP, VINZOL CROSSING ROAD, PHASE II, G.I.D.C., VATVA, AHMEDABAD 380026  <b>Shipping Address:</b> : PLOT NO - 5639/G, NR. SHALAMANDIR BUS STOP, VINZOL CROSSING ROAD, PHASE II, G.I.D.C., VATVA, AHMEDABAD 380026		<b>P.O No.</b> : fro inq.  <b>Date</b> : 17/08/2021	<b>W.O No.</b> : WO-2122-AUG-201  <b>Date</b> : 17/08/2021			
Sr.No	Item Description	Qty	Module Details / Rate	Discount	GST	Total
1	<b>RTD (PT-100) SENSOR</b> Part No:APWD RTD SENSOR TYPE: PT-100 MAKE: AAVAD MODEL : APWD CONFIGURATION: DUPLEX NO. OF WIRE IN SIMPLEX:3 TOTAL NO.OF WIRES: 3+3 ACCURACY : CLASS A TEMPERATURE RANGE : -50 TO 400 DEGREE C MATERIAL OF CONSTRUCTION : SS 316 INSULATION : COMPACTED MGO INSULATION PROCESS CONNECTION: BSP PROCESS CONNECTION SIZE : 1/2 " NPT (M) ADJUSTABLE PROTECTION HEAD: DIE-CAST ALUMINUM HEAD WITH THREADED CAP & CHAIN HEAD PROTECTION CLASS :IP-65 HEAD CABLE ENTRY CONNECTION : ¾ "ET NO. OF CABLE ENTRY : SINGLE TERMINAL BLOCK : NICKEL PLATED CERAMIC TERMINAL BLOCK OD: 6 MM LENGTH: 350 MM	7	780	0	18	6,443

2	<b>RTD (PT-100) SENSOR</b> Part No:APWD RTD SENSOR TYPE: PT-100 MAKE: AAVAD MODEL : APWD CONFIGURATION: DUPLEX NO. OF WIRE IN SIMPLEX:3 TOTAL NO.OF WIRES: 3+3 ACCURACY : CLASS A TEMPERATURE RANGE : -50 TO 400 DEGREE C MATERIAL OF CONSTRUCTION : SS 316 INSULATION : COMPACTED MGO INSULATION PROCESS CONNECTION: BSP PROCESS CONNECTION SIZE : 1/2 " NPT (M) ADJUSTABLE PROTECTION HEAD: DIE-CAST ALUMINUM HEAD WITH THREADED CAP & CHAIN HEAD PROTECTION CLASS :IP-65 HEAD CABLE ENTRY CONNECTION : ¾ "ET NO. OF CABLE ENTRY : SINGLE TERMINAL BLOCK : NICKEL PLATED CERAMIC TERMINAL BLOCK OD: 8 MM LENGTH: 350 MM	7	780	0	18	6,443
3	<b>DIRECT CABLE RTD (PT-100) SENSOR, GSP</b> Part No:APES- 6 X 100 RTD SENSOR TYPE: PT-100 MAKE: AAVAD MODEL : APES CONFIGURATION: SIMPLEX NO. OF WIRE IN SIMPLEX:3 TOTAL NO.OF WIRES: 3 ACCURACY : CLASS A TEMPERATURE RANGE : -50 TO 400 DEGREE C MATERIAL OF CONSTRUCTION : SS 316 INSULATION : COMPACTED MGO INSULATION PROCESS CONNECTION: BSP PROCESS CONNECTION SIZE : 1/2 " (M) ADJUSTABLE CABLE LENGTH: 10 MTR CABLE TYPE: TF/TF/SS SENSOR LENGTH: 300 MM SENSOR OD: 8 MM	25	550	0	18	16,225

4	<b>K TYPE THERMOCOUPLE SENSOR</b> Part No:AKWD THERMOCOUPLE SENSOR TYPE: K (CR/AL) MAKE: AAVAD MODEL : AKWD CONFIGURATION: DUPLEX NO. OF WIRE IN SIMPLEX:2 TOTAL NO.OF WIRES: 2+2 ACCURACY : +/- 0.75 % TEMPERATURE RANGE : -50 TO 600 DEGREE C MATERIAL OF CONSTRUCTION : SS 316 INSULATION : COMPACTED MGO INSULATION PROCESS CONNECTION: BSP PROCESS CONNECTION SIZE : 1/2 " (M) ADJUSTABLE PROTECTION HEAD: DIE-CAST ALUMINUM HEAD WITH THREADED CAP & CHAIN HEAD PROTECTION CLASS :IP-65 HEAD CABLE ENTRY CONNECTION : ¾ "ET NO. OF CABLE ENTRY : SINGLE TERMINAL BLOCK : NICKEL PLATED CERAMIC TERMINAL BLOCK OD: 8 MM LENGTH: 750 MM	7	1,300	0	18	10,738
	<b>P &amp; F</b>		0		0	0
	<b>Freight</b>		0		0	0
				<b>Total:</b>		<b>39848.6</b>
	<b>Thirty Nine Thousands Eight Hundred and Forty Nine Rupees Only</b>			<b>Grand Total:</b>		<b>39848.6</b>
<b>Delivery Time / Date</b>		<b>Delivery by</b>				
		<b>Courier Name</b>		<b>Docket No.</b>		
<b>Prepared by</b> : VINAYSHRIMALI		<b>Tested by</b> : VINAYSHRIMALI		<b>Remarks</b>		

NG

PS

Account

Store

Prodution