

Toshniwal Domestic Water Meter



Name: Multi-Jet Dry Type Vane

Model: LXSC 15 \sim 40 DN : 15 \sim 40 mm

ISO 4064 Class B

WORKING CONDITION:

a) Water temperature : < 40°C
b) Water pressure : < 1MPa

MAXIMUM PERMISSIBLE ERROR:

- a) In the lower zone from qmin inclusive up to but excluding qt is \pm 5%
- b) In the upper zone from qt inclusive up to and including qs is $\pm 2\%$

NOTE:

Technical data conform to international Standard ISO4064 Class B


APPLICATIONS:

Measuring the volume of cold portable water passing through the pipline. Hot water meter upto 90°C also available upon request.

FEATURES:

Dry type,magnetic drive,numerical cylinder drum and pointer indication,easy and long term clear reading,frost resistance,long working life,etc...

B D D



MAIN TECHNICAL DATA*

Model	Size (mm)	Class	MAX Flow	Normal Flow	qt Transitional Flow	qmin Min. Flow	Min. Reading	Max. Reading			
			m³/h		m³/h		m ³				
LXSC-15	15	В	3	1.5	120	30	0.0001	999999			
LXSC-20	20	В	5	2.5	200	50	0.0001	999999			
LXSC-25	25	В	7	3.5	280	70	0.0001	999999			
LXSC-32	32	В	12	6.0	480	120	0.0001	999999			
LXSC-40	40	В	20	10	800	200	0.001	999999			

DIMENSION AND WEIGHT*

Model	Size	Length	Width	Height	Connecting Thread D	Weight kg	
			mm				
LXLC-15	15	165	99	104	G 3/4B	1.5	
LXLC-20	20	190	106	114	G1B	1.7	
LXLC-25	25	260/225	103	114	G1 1/4B	2.6/2.4	
LXLC-32	32	260/230	104	114	G1 1/2B	2.8/2.7	
LXLC-40	40	300/245	124	147	G2B	5.1/4.8	

*Specifications are subjected to changes without notice

Toshniwal Brothers (Hyd) Pvt. Ltd.

267 Kilpuak Garden Road, Chennai - 600 010, India **Phone:** + 91 44 2644 8983 / 5626 **Fax:** + 91 44 2644 1820 **Web:** www.toshniwal.net / **Email:** sales@toshniwal.net