

WORK ORDER

: 25/05/2021

Date

MASPL

Name: : MAKCUR LIFESCIENCE

PRIVATE LTD, SURVEY NO

:46/4-7,VILLAGE ZAK, NARODA-DEHGAM ROAD ,TAL. DEHGAM, DIST. GANDHINAGAR - 382330,

Billing : SURVEY NO

Address: :46/4-7, VILLAGE ZAK,

NARODA-DEHGAM ROAD ,TAL. DEHGAM, DIST. GANDHINAGAR - 382330,

Shipping: SURVEY NO

Address: :46/4-7, VILLAGE ZAK,

NARODA-DEHGAM ROAD ,TAL. DEHGAM, DIST. GANDHINAGAR - 382330, **P.O No.** : fro inq. **W.O No.** : WO-2122-MAY-50

Date : 25/05/2021

	GANDHINAGAR - 382330,						
Sr.No	Item Description	1	Qty	Module Deta / Rate	Discount	GST	Total
1	RTD (PT-100) SENSOR Part No:APWS RTD SENSOR TYPE: PT-100 MAKE: AAVAD MODEL : APWS CONFIGURATION: SIMPLEX NO. OF WIRE IN SIMPLEX:3 TOTAL NO.OF WIRES: 3 ACCURACY: CLASS A TEMPERATURE RANGE: -50 TO C MATERIAL OF CONSTRUCTION: SS 316 INSULATION PROTECTION HEAD: DIE-CAST AI HEAD WITH THREADED CAP & CHAIN HEAD PROTECTION CLASS :IP-65 HEAD CABLE ENTRY CONNECTION NO. OF CABLE ENTRY: SINGLE TERMINAL BLOCK: NICKEL PLAT CERAMIC TERMINAL BLOCK OD: 6 MM LENGTH: 105 MM TOTAL STEM LENGTH - 105 MM TC BOTTOM LOCATION - 50 MM FROTIP STEM DIA - 6 MM TRICLOVER OD SIZE - 25 MM	LUMINUM N : ¾ "ET	5	889	10	18	4,721

RTD (PT-100) SENSOR Part No:APWD RTD SENSOR TYPE: PT-100 MAKE: AAVAD MODEL: APWD CONFIGURATION: DUPLEX NO. OF WIRE IN SIMPLEX:3 TOTAL NO.OF WIRES: 3+3 ACCURACY: CLASS A TEMPERATURE RANGE: -50 TO 400 DEGREE C MATERIAL OF CONSTRUCTION: SS 316 INSULATION: COMPACTED MGO INSULATION PROTECTION HEAD: DIE-CAST ALUMINUM HEAD WITH THREADED CAP & CHAIN HEAD PROTECTION CLASS:IP-65 HEAD CABLE ENTRY CONNECTION: 3/4 "ET NO. OF CABLE ENTRY: SINGLE TERMINAL BLOCK: NICKEL PLATED CERAMIC TERMINAL BLOCK OD: 6 MM LENGTH: 105 MM TOTAL STEM LENGTH - 105 MM TO BOTTOM LOCATION - 50 MM FROM SENSOR TIP STEM DIA - 6 MM TRICLOVER OD SIZE - 25 MM	5	1,129	10	18	5,995
Part No:TG01 BI-METAL TEMPERATURE GAUGE MAKE: AAVAD DIAL SIZE: 63MM RANGE: 0 TO 200?C CONFIGURATION: BI-METAL STRIP CASE & BEZEL: SS 304, BAYONET TYPE STEM OD × LENGTH: 8× 60 MM DIAL: ALUMINIUM, BLACK MARKINGS ON WHITE BACKGROUND POINTER: ALUMINIUM, BLACK WINDOW: PLAIN GLASS ACCURACY: +/- 1.6% OF FSD OVER-RANGE PROTECTION: 130% OF FSD CONNECTION: 1/2" BSP (M) MOUNTING: DIRECT BOTTOM MOUNTING RATE: 735/-EACH FOR DIRECT BOTTOM MOUNTING RATE: 455/-EACH FOR DIRECT BACK MOUNTING	1	735	0	18	867
P & F		0		0	0
Freight		0		0	0

						Total:	11582.88
	Eleven Thousands Five Hundred and Eighty Three Rupees Only					Grand Total:	11582.88
Delivery Time / : Date			Delivery by :				
			Courier : Name		Docket No. :		
Prepa	red by	: VINAYSHRIMALI	Tested by	: VINAYSHRIMALI	Remarks	:	

NG PS Account Store Prodution