

## **WORK ORDER**

MASPL

: LOUIS DREYFUS Name:

COMMODITIES INDIA PVT.LIMITED,

SURVEY NO- 310-2-B, NEAR BHIMASAR RLWY STATION, VILL:

BHIMASAR, TA: ANJAR, DIST: KUTCH, GUJARAT

INDIA

Billing Address

: SURVEY NO- 310-2-B, NEAR BHIMASAR RLWY

STATION, VILL:

BHIMASAR, TA: ANJAR, DIST: KUTCH, GUJÁRAT /

INDIA

Shippin : SURVEY NO- 310-2-B, NEAR BHIMASAR RLWY

Address STATION, VILL:

BHIMASAR, TA: ANJAR, DIST: KUTCH, GUJÁRAT /

INDIA

	P.O No.	: PO-IN03-210110-0	<b>W.O No.</b> : WO-2122-JUN-108
	Date	: 19/06/2021	<b>Date</b> : 19/06/2021
/			

Sr.No	Item Description	Qty	Module D / Rat	Details te	Discount	GST	Total	
1		1	410 0		0	18	484	
	Part No:							
	RTD SENSOR							
	MAKE:AAVAD							
	CONFIGURATION: SIMPLEX 2 WIRE							
	MOC: SS316							
	LENGTH:65							
	MM							
	OD:6MM							
	PROCESS							
	CONNECTION:1/2"BSP MALE ADJUSTABLE							
	WITH 2							
	METER TF/TF/SS CABLE							

2		2	8,200	0	18	19,352
_	Part No:	_	0,200	J	10	13,332
	8 CHANNEL FIXED INPUT SCANNER					
	INPUT: RTD					
	PT-100					
	SIZE : 96 X 96					
	DISPLAY: 4 DIGITS					
	0.56" RED LED FOR PV AND 2					
	DIGITS					
	0.56" RED LED FOR CH. NO.					
	ACCURACY: 0.25% OF					
	FULL SCALE ?1 COUNT THROUGHOUT THE					
	RANGE.					
	CALIBRATION:BY ZERO & SPAN ADJUSTMENT					
	BY					
	SOFTWARE FROM FRONT PANEL					
	KEYBOARD.					
	POWER:230V AC?10% OR 110V AC?10%,					
	50HZ					
	(FACTORY SETTING)					
	POWER					
	CONSUMPTION: LESS THAN 10 VA CONTROL:BY FOUR KEYS					
	ON FRONT PANEL					
	INDEX, INCREMENT, DECREMENT AND					
	ENTER.					
	ENVIRONMENT CONDITION:0-50 ?C					
	AND					
	HUMIDITY UP TO 95%					
	NON-CONDENSING					

3			1	26,600		0	18	31,388		
	Part No:							·		
	ELECTROMAGNETIC FLOWMETER									
	MODEL:AMAG?R									
	SERVICE :ETP									
	CONDUCTIVITY : ≥ 10									
	MS/CM									
	OUTPUT: 4?20 MA ISOLATED,RS - 485 ,PULSE									
	DISPLAY: LCD 16X4 LINE WITH 5 METER									
	CABLE 9 DIGIT TOTALIZED									
	FLOW									
	ACCURACY: +/? 0.5 % OF READING									
	REPEATIBILITY: +/?1%									
	PROCESS TEMPERATURE: 0 C? 150 °C									
	PROCESS PRESSURE: MAX : 10 KG/CM2									
	INTERNAL : PTFE									
	LINNING ELECTRODE MOC : HASTALLOY C									
	POWER SUPPLY : 230 V AC RESPONSE TIME									
	: 0.3 SEC PROCESS CONNECTION : ASA 150 FLANGE MS	D								
	OPERATING TEMPERATURE : 55 C									
	ELECTRONICS HOUSING: DIE CAST ALUMINUM,									
	IP 65									
	EMPTY PIPE DETECTION:									
	YES BACK LIGHT LCD: YES									
	VELOCIY:0.3 TO									
	10 M/S MEASURING UNIT :									
	SELECTABLE									
	KG/H,M3/H,L/H,L/M,L/S,KG/M,KG/S LINE									
	SIZE: 50 MM									
4	Part No:		2	4,000		0	18	9,440		
	panel with internal wiring									
	P & F			0			0	0		
	Freight			0			0	0		
							Total:	60663.8		
Sixty Thousands Six Hundred and Sixty Four Rupees Only					Grand	Grand Total: 60663.8				
Deliv Date		Delivery by :								
			ourier : Docket No. :							
Prepared by : JIGNASHAGADHAVI Tested by : JIGNASHAGADHAVI Remarks :										