

## **WORK ORDER**

: 26/07/2021

MASPL

Date

Name: : GMM PFAUDLER LIMITED,

VITHAL UDYOGNAGAR, ANAND - SOJITRA ROAD, KARAMSAD- 388325, GUJARAT, INDIA

**Billing**: VITHAL UDYOGNAGAR, **Address:** ANAND - SOJITRA ROAD,

KARAMSAD- 388325, GUJARAT, INDIA

**Shipping**: VITHAL UDYOGNAGAR, **Address**: ANAND - SOJITRA ROAD,

KARAMSAD- 388325, GUJARAT, INDIA **P.O No.** : fro inq. **W.O No.** : WO-2122-JUL-172

**Date** : 26/07/2021

Sr.No	Item Description	Qty	Module Details / Rate	Discount	GST	Total
1		1	710	0	18	838
	Part No:INDUSTRIAL PRESSURE GAUGE					
	MAKE: AAVAD					
	DIAL					
	SIZE: 63 MM RANGE: 0 TO 60					
	KG/CM2					
	CASE & BEZEL:					
	SS 304, BAYONET TYPE					
	SOCKET: SS					
	304					
	MOVEMENT: SS					
	304					
	SENSING MATERIAL: SS 316,					
	BOURDON TUBE <b>DIAL</b> : ALUMINIUM,					
	BLACK MARKINGS ON WHITE					
	BACKGROUND					
	POINTER: ALUMINIUM,					
	BLACK					
	WINDOW: ACRYLIC					
	GLASS					
	ACCURACY: +/- 1.0% OF					
	FSD OVER-RANGE PROTECTION: 130%					
	OF FSD					
	CONNECTION: 1/4" NPT					
	(M), SS 316					
	MOUNTING:					
	DIRECT BOTTOM MOUNTING					
	JOINT:					
	ARGON WELDING					
	GLYCERINE FILLED:					
	YES					

2	RTD (PT-100) SENSOR Part No:ENSYORS-0123 TYPE: PT-100 MAKE: AAVAD MODEL: APFD CONFIGURATION: DUPLEX TOTAL NO. OF WIRES: 3+3 ACCURACY: CLASS A TEMPERATURE RANGE: -50 TO 250 DEGREE C MATERIAL OF CONSTRUCTION: SS 316 INSULATION: COMPACTED MGO INSULATION PROCESS CONNECTION: NPT PROCESS CONNECTION SIZE: 1/4 " (M) PROTECTION HEAD: DIE-CAST ALUMINUM FLAMEPROOF HEAD WITH THREADED CAP & CHAIN HEAD PROTECTION CLASS: IP-67, T 6 HEAD CABLE ENTRY CONNECTION: 1/2 " NPT NO. OF CABLE ENTRY: DOUBLE TERMINAL BLOCK: NICKEL PLATED CERAMIC TERMINAL BLOCK OD: 6 MM LENGTH: 150 MM WITH HEAD MOUNTED TEMPERATURE TRANSMITTER INPUT: RTD OUTPUT: 4 -20 MA (2 WIRE) CALIBRATION RANGE: -10 TO 220 DEGREE C	1	2,850	0	18	3,363
---	---	---	-------	---	----	-------

3	Down No ENGVODO 0124	1	2,700	0	18	3,186
	Part No:ENSYORS-0124 TYPE: PT-100					
	MAKE: AAVAD					
	MODEL:					
	APFD					
	CONFIGURATION: DUPLEX TOTAL NO. OF					
	WIRES: 3+3					
	ACCURACY: CLASS A					
	TEMPERATURE					
	RANGE : -50 TO 250 DEGREE C					
	MATERIAL OF CONSTRUCTION : SS 316					
	INSULATION : COMPACTED MGO					
	INSULATION					
	PROCESS CONNECTION:					
	NPT PROCESS CONNECTION SIZE : 1/4 ''					
	(M)					
	PROTECTION HEAD: DIE-CAST ALUMINUM					
	FLAMEPROOF					
	HEAD WITH THREADED CAP & CHAIN HEAD PROTECTION CLASS:					
	IP-67, T 6					
	HEAD CABLE ENTRY CONNECTION: 1/2					
	" NPT					
	NO. OF CABLE ENTRY : DOUBLE					
	TERMINAL BLOCK : NICKEL PLATED					
	CERAMIC TERMINAL BLOCK					
	OD: 6 MM					
	LENGTH: 110 MM					
	WITH					
	HEAD MOUNTED TEMPERATURE					
	TRANSMITTER					
	INPUT :RTD OUTPUT: 4 -20 MA					
	(2 WIRE)					
	CALIBRATION RANGE: -10 TO 220 DEGREE					
	С					

			IValli	<b>-</b>						
			Cour			Docket N	cket No. :			
Delivery Time / : Date		Deliv	ery by		:					
Ten Thousands Three Hundred and Ninety Six Rupees Only					G	rand Total:	10395.8			
							Total:	10395.8		
Freight					0		0	0		
P & F					0		0	0		
TYPE: PT-1 MAKE: AAV MODEL: APFD CONFIGURA TOTAL NO. WIRES: 3+: ACCURACY: TEMPERATU RANGE: -5 MATERIAL ( CONSTRUC' INSULATION INSULATION PROCESS C (M) PROTECTIO FLAMEPROC HEAD WITH PROTECTIO IP-67, T 6 HEAD CABL " NPT NO. OF CAI DOUBLE TERMINAL I CERAMIC T OD: 6 MM LENGTH: 75 MM WITH HEAD MOU TRANSMITT INPUT: RTD OUTPUT: 4 (2 WIRE)	ATION: DUPLE OF 3 CLASS A JRE 0 TO 250 DE OF TION: SS 31 N: COMPACT N CONNECTION: CONNECTION N HEAD: DIE OF I THREADED N CLASS: LE ENTRY CO BLE ENTRY: BLOCK: NICI ERMINAL BLO NTED TEMPE ER O -20 MA	EGREE C  16 TED MGO  SIZE: 1/4 ''  E-CAST ALUMIN  CAP & CHAIN  NNECTION: 1/	HEAD	1	2,550		) 18	3,009		