

FLAMEPROOF RTD SENSOR



➤ TECHNICAL SPECIFICATION :

RTD (PT-100) SENSOR	
MAKE	AAVAD
MODEL	APFD
SENSOR TYPE	RTD (PT-100)
CONFIGURATION	3 – WIRE (DUPLEX)
TOTAL NO. OF WIRES	3 + 3
ACCURACY	CLASS A
TEMPERATURE RANGE	-50 TO 400 DEGREE C
MATERIAL OF CONSTRUCTION	SS 316
INSULATION	COMPACTED MGO INSULATION
PROTECTION HEAD	DIE-CAST ALUMINUM FLAMEPROOF HEAD WITH THREADED CAP & CHAIN
HEAD PROTECTION CLASS	IP-67
CERAMIC TERMINAL BLOCK	NICKEL PLATED CERAMIC TERMINAL BLOCK
HEAD CABLE ENTRY CONNECTION	1/2 " NPT
NO. OF CABLE ENTRY	DOUBLE
ABOVE THREAD OD	12 MM
LENGTH	45 MM
TIP OD	8 MM
TIP LENGTH WITH THREAD	45 MM

AAVAD INSTRUMENT

216-217, Sangath Mall - 1, Opp. Engineering College, Chandkheda, Motera, Ahmedabad - 380005, Gujarat, India.

E : aavad@aavadinstrument.com **W :** www.aavadinstrument.com **Ph :** +91-972-772-2823, 079-40095342.

GSTIN : 24AHZPG7088C1ZY | **PAN No. :** AHZPG7088C | **MSME No. :** GJ01A0024728

Bank : Kotak Mahindra Bank LTD | **A/c Name :** Aavad Instrument | **A/C No. :** 141117509 | **IFSC Code :** KKBK0000839

TEMPERATURE - PRESSURE - FLOW - LEVEL - PROCESS CONTROL