

WORK ORDER

MASPL : MAKEVALE ACRYLICS PVT P.O No. : 14PO2192 W.O No.: WO-2122-OCT-227 Name: LIMITED, : 23/10/2021 Date : 23/10/2021 Date BLOCK NO. 372-373-374/1 & 2, AT & PO, VILLAGE MOKHI, TALUKA SAVLI, VADODARA - 391780, GUJARAT, INDIA Billing : BLOCK NO. Address 372-373-374/1 & 2, AT & PO, VILLAGE MOKHI, TALUKA SAVLI, VADODARA - 391780, GUJARAT, INDIA Shippin : BLOCK NO. 372-373-374/1 & 2, AT & Address PO, VILLAGE MOKHI, TALUKA SAVLI,

VADODARA - 391780, GUJARAT, INDIA

| Sr.No | Item Description | Qty | Module Details / Rate | Discount | GST | Total |
|-------|--|-----|--------------------------|----------|-----|--------|
| 1 | Part No:RANGE: 0 TO 7KG/CM2 INDUSTRIAL PRESSURE GAUGE MAKE: AAVAD DIAL SIZE: 100 MM RANGE: 0 TO 7KG/CM2 CASE & BEZEL: SS 304, BAYONET TYPE SOCKET: SS 304 MOVEMENT: SS 304 SENSING MATERIAL: SS 316, BOURDON TUBE DIAL: ALUMINIUM, BLACK MARKINGS ON WHITE BACKGROUND POINTER: ALUMINIUM, BLACK WINDOW: ACRYLIC GLASS ACCURACY: +/- 1.0% OF FSD OVER-RANGE PROTECTION: 130% OF FSD CONNECTION: 1/2" BSP (M), SS 304 MOUNTING: DIRECT BOTTOM JOINT: ARGON WELDING GLYCERINE FILLED: YES | 10 | 1,925 | 15 | 18 | 19,308 |

| 2 | Part No:RANGE: 0 TO 7 KG/CM2 PRESSURE GAUGE MAKE: AAVAD DIAL SIZE: 63 MM RANGE: 0 TO 7 KG/CM2 CASE & BEZEL: SS 304, CRIMPING TYPE SOCKET: SS 304 MOVEMENT: SS 304 SENSING MATERIAL: SS 316, BOURDON TUBE DIAL: ALUMINIUM, BLACK MARKINGS ON WHITE BACKGROUND POINTER: ALUMINIUM, BLACK WINDOW: ACRYLIC GLASS ACCURACY: +/- 1.6% OF FSD OVER-RANGE PROTECTION: 130% OF FSD CONNECTION: 3/8"BSP (M) MOUNTING: DIRECT BOTTOM ENTRY GLYCERINE FILLED: YES | 5 | 835 | 15 | 18 | 4,188 |
|---|---|---|-------|----|----|-------|
| 3 | Part No:RANGE: 0 TO 50?C BI-METAL TEMPERATURE GAUGE MAKE: AAVAD DIAL SIZE: 100 MM RANGE: 0 TO 50?C CONFIGURATION: BIMETAL STRIP CASE & BEZEL: SS 304, BAYONET TYPE STEM OD × LENGTH: 08 × 250 MM DIAL: ALUMINIUM, BLACK MARKINGS ON WHITE BACKGROUND POINTER: ALUMINIUM, BLACK WINDOW: PLAIN GLASS ACCURACY: +/- 1.6% OF FSD OVER-RANGE PROTECTION: 130% OF FSD CONNECTION: 1/2" BSP (M) ADJUSTABLE MOUNTING: DIRECT BOTTOM ENTRY | 2 | 1,050 | 15 | 18 | 2,106 |