

PM-GroupProject

Dennis Goldenberg, Solomon Gao, Suleman Sadiq, Alana Berson

2024-04-23

```
library(readxl)
library(ggplot2)
suppressWarnings(library(zoo))
library(nlme)
suppressWarnings(library(forecast))
library(rpart)
suppressWarnings(library(rpart.plot))
library(tree)
```

```
## Warning: package 'tree' was built under R version 4.3.3
```

```
suppressWarnings(library(randomForest))
```

1. Data Exploration and Preprocessing

Reading in USA fatality data:

```
USAFat <- as.vector(t(as.matrix(read_excel("data/USA-FatalCrashes.xlsx",
  range = "B8:M22", col_names = FALSE, .name_repair = "unique_quiet")))))
```


Reading in USA population data (in hundreds of thousands):

```
USAPOP <- read_excel("data/USAPOP.xlsx")
colnames(USAPOP) <- c("Year", "Alabama", "Alaska", "Arizona", "Arkansas",
  "California", "Colorado", "Connecticut", "Delaware", "D.C.", "Florida", "Georgia",
  "Hawaii", "Idaho", "Illinois", "Indiana", "Iowa", "Kansas", "Kentucky", "Louisiana",
  "Maine", "Maryland", "Massachusetts", "Michigan", "Minnesota", "Mississippi",
  "Missouri", "Montana", "Nebraska", "Nevada", "New Hampshire", "New Jersey",
  "New Mexico", "New York", "North Carolina", "North Dakota", "Ohio", "Oklahoma",
  "Oregon", "Pennsylvania", "Rhode Island", "South Carolina", "South Dakota",
  "Tennessee", "Texas", "Utah", "Vermont", "Virginia", "Washington",
  "West Virginia", "Wisconsin", "Wyoming")
USAPOP$Year <- (2008:2023)*1000
USAPOP <- USAPOP/1000
USAPOP$Year <- as.integer(USAPOP$Year)
```

a. Seasonality of Data

```
USADate <- as.yearmon("2008-01") + seq((1/12), (180/12), by = (1/12)) - (1/12)
USAData <- zoo(USAFat, USADate)
plot(USAData, main = "USA Fatal Motor Vehicle Crashes by Month, 2008-2022",
  xlab = "Month and Year", ylab = "Monthly Fatal Vehicle Crashes")
```


USA Fatal Motor Vehicle Crashes by Month, 2008–2022



Examining a typical year:

```
plot(USAData[49:60], main = "USA Fatal Motor Vehicle Crashes by Month, 2013",  
     xlab = "Month", ylab = "Monthly Fatal Vehicle Crashes")
```


USA Fatal Motor Vehicle Crashes by Month, 2013



Looking at the Seasonality:

```
tsUSA <- ts(USAFat, start = 2008, freq = 12)
plot(decompose(tsUSA, type = "add"))
```

Decomposition of additive time series



b. Collecting fatality data on states that legalized pre-2022

```
legStates <- c("Colorado", "Washington", "D.C.", "Oregon", "Alaska", "California",
               "Massachusetts", "Nevada", "Maine", "Vermont", "Michigan",
               "Illinois", "Arizona", "Montana", "New Jersey", "New York",
               "New Mexico", "Virginia", "Connecticut")
legEffDate <- as.yearmon("2012-11") +
  (c(1, 2, 29, 33, 39, 49, 50, 51, 52, 69, 74, 87, 98, 99, 101, 102, 105, 105, 105)/12) - (1/12)
```


c. Calculating State by State Population Data

2. Modeling

a. Autocorrelation function

```
pacf(USAData)
```

Series USAData



```
arima(USAData, order = c(1,0,0), method = "ML")
```

```
##
## Call:
## arima(x = USAData, order = c(1, 0, 0), method = "ML")
##
## Coefficients:
##          ar1  intercept
##          0.8334 2787.4896
## s.e.    0.0406   93.9691
##
## sigma^2 estimated as 46541:  log likelihood = -1223.33,  aic = 2452.66
```

b. Difference of Means on Panel Data

I do a difference of means test to see if there is a change in the average number of fatal crashes per 100,000 in the year pre-legalization vs. the year when legalization went into effect. I linearly interpolate between population estimates to get the population estimate to divide by (i.e. if legalization went into effect at March 2015, I take 2/12 of the population of 2015 and add 10/12 of the population of 2014 for the pre-legalization population):

```
effDatefracs <- as.numeric(legEffDate) - as.integer(legEffDate)
yearsLeg <- as.integer(legEffDate)
avgs_pre <- c()
avgs_post <- c()
for(i in 1:length(legStates)){
  stateInfo <- as.vector(t(as.matrix(read_excel(
```

```


paste("data/",legStates[i],".xlsx",sep = ""),range = "B9:M23",
col_names = FALSE,.name_repair = "unique_quiet"))))

#linear interpolation
pop_est_pre <- effDatefracs[i] * USAPOP[yearsLeg[i] - 2007,legStates[i]] +
  (1 - effDatefracs[i]) * USAPOP[yearsLeg[i] - 2008,legStates[i]]
pop_est_post <- (1-effDatefracs[i])*USAPOP[yearsLeg[i] - 2007,legStates[i]]+
  effDatefracs[i] * USAPOP[yearsLeg[i] - 2006,legStates[i]]

#find point in state info, calculate averages
index_Leg <- (as.numeric(legEffDate[i]) - 2008)*12 + 1
pre_per_HT <- mean(stateInfo[(index_Leg - 12):(index_Leg - 1)])/pop_est_pre
post_per_HT <- mean(stateInfo[(index_Leg):(index_Leg + 12)])/pop_est_post
avgs_pre <- append(avgs_pre,pre_per_HT)
avgs_post <- append(avgs_post, post_per_HT)
}
hist(avgs_post - avgs_pre, breaks = 10,
main = "Differences of Average Fatal Crash Number, Pre/Post Legalization",
xlab = "Difference")

```

Differences of Average Fatal Crash Number, Pre/Post Legalization



I generate the data-frame with data, and run a paired sample t-test:

```

pairedData <- as.data.frame(cbind(legStates,avgs_pre,avgs_post))
colnames(pairedData) <- c("State", "avg_pre_Leg","avg_post_Leg")
pairedData$avg_pre_Leg <- round(as.numeric(pairedData$avg_pre_Leg),6)
pairedData$avg_post_Leg <- round(as.numeric(pairedData$avg_post_Leg),6)

```

```
testMeans <- t.test(pairedData$avg_post_Leg, pairedData$avg_pre_Leg,
  paired = TRUE, alternative = "greater")
```

The test statistic is $t = \frac{m}{\frac{s}{\sqrt{n}}}$, where m is the mean difference, s is the sample standard deviation of the difference, and n is the number of observations (in this case, 19). I calculate:

```
sprintf("Sample Mean Difference: %.5f", testMeans$estimate)
```

```
## [1] "Sample Mean Difference: 0.60166"
```

```
sprintf("Test statistic: %.5f", testMeans$statistic["t"])
```

```
## [1] "Test statistic: 2.41257"
```

```
sprintf("Degrees of Freedom: %.0f", testMeans$parameter)
```

```
## [1] "Degrees of Freedom: 18"
```

```
sprintf("p-value: %.5f", testMeans$p.value)
```

```
## [1] "p-value: 0.01336"
```

```
print("95% Confidence Interval:")
```

```
## [1] "95% Confidence Interval:"
```

```
print(testMeans$conf.int[1:2])
```

```
## [1] 0.1692114      Inf
```

So, $\mathbb{P}(T_{18} > 2.41257) = 0.01336 < 0.05$; I reject H_0 at $\alpha = 0.05$.

c. Decision Tree and Random Forest to Predict Crashes

i. Collecting Data

Features to split on: (Note Rhode Island legalized on 05/22/2022 so it should probably be excluded)

- Marijuana Legal? (Pre-2022)
- Billions of Highway Miles-driven per 100,000 (2022)
- Proportion of Population in Urban Areas (2020)
- Speed Limits on Urban Interstates (as of 2024)
-
- Damage in Millions of Dollars per 100,000 by Hazardous Weather (2022)
-

```
#Create response variable:
```

```
avg2022 <- as.vector(t(as.matrix(read_excel("rfddata/2022StateData.xlsx",
  range = "B7:AZ8", col_names = TRUE, .name_repair = "unique_quiet"))))/12
pop2022 <- as.vector(t(as.matrix(USAPOP[2022 - 2007, 2:dim(USAPOP)[2]])))
resp <- avg2022/pop2022
```

```
#Getting Percent Urban Population
```

```
urbRaw <- read_excel("rfddata/UrbanRural.xlsx", sheet = "Data", range = "B1:AZ4")
urb <- as.vector(t(urbRaw[2,]))/as.vector(t(urbRaw[1,]))
```

```
#Speed Limits on Urban Interstates
```

```

spL <- c(70, 55, 65, 65, 65, 65, 55, 55, 55, 65, 70, 60, 75, 55, 55,
        55, 75, 65, 70, 75, 70, 65, 70, 65, 70, 60, 65, 70, 65, 65, 55, 75, 65,
        70, 75, 65, 70, 55, 70, 55, 70, 80, 70, 75, 70, 55, 70, 60, 55, 70, 75)

#Marijuana Legalized?
legMar <- as.integer(c(0,1,1,0,1,1,1,0,1,0,0,0,1,0,0,0,0,1,0,
                      1,1,0,0,0,1,0,1,0,1,1,1,0,0,0,0,1,0,0,0,0,0,1,1,1,0,0,0))

#% Population Over 70 by State, 2022
over_70 <- as.numeric(read_excel("rfdata/USAAge70Over.xlsx")[1, ])

#Total Damage (in millions of $) from Hazardous Weather Events, 2022
hazard <- c(18.25, 30.97, 26.33, 44.48, 86.33, 1.1, 0.19, 0.26, 0, 17004.67,
           4.26, 1.33, 311.26, 25.70, 15.98, 24.97, 105.49, 8.22, 191.57,
           0.9, 7.84, 32.83, 75.24, 73.41, 183.68, 63.23, 4.27, 30.98,
           70.07, 443.28, 11, 0.17, 183.12, 10.59, 57.63, 20.17, 44.83,
           9.83, 8.08, 1.12, 2.08, 499.83, 3.5, 1527.29, 36.76, 69.56, 5.69,
           358.53, 11.48, 24.11, 25.17)
hazard <- hazard/pop2022

#Binge Drinking Prevalence among Adults
binge <- as.vector(t(as.matrix(read_excel("rfdata/BingeDrinking.xlsx",
                                         sheet = "Data", range="C6:C57")))/100)

#Billions of Highway-Miles Driven per 100,000 people
hMiles <- t(as.matrix(read_excel("rfdata/hMiles.xlsx", range = "C1:C53")))
#remove Puerto Rico
hMiles <- hMiles[-c(40)]
#take billions of Miles per 100,000 people
hperHT <- (hMiles/1000)/pop2022

#Final Data Gathering
finData <- as.data.frame(cbind(resp, legMar, hperHT, urb, spL, over_70, hazard, binge))
corMat <- cor(finData)
finData$legMar <- factor(finData$legMar)
finData$spL <- factor(finData$spL)
finData$hperHT <- round(finData$hperHT, 6)
finData$urb <- round(finData$urb, 6)
finData$over_70 <- round(finData$over_70, 6)
finData$hazard <- round(finData$hazard, 6)
finData$states <- colnames(USAPOP)[2:52]
finData <- finData[,c(1,9,2:8)]
colnames(finData) <- c("resp", "State", "Legal", "HW_travel",
                     "Urban", "Speed_Lim", "over_70", "hazard", "binge")
finData <- finData[which(finData$State != "Rhode Island"),]

```

ii. 1 tree (for example)

```


set.seed(1)
train_index <- sample(1:nrow(finData), .8 * nrow(finData), replace = FALSE)
test_index <- setdiff(1:50, train_index)
rtree <- tree(resp ~ ., data = finData[train_index, -c(2)])
cv <- cv.tree(rtree, K = 5, FUN = prune.tree)

```




```
par(oma = c(0,0,2,0))
plot(cv)
title(main = "Deviance of Tree vs. Number of Leaves, corresponding alpha",
outer = TRUE)
```

Deviance of Tree vs. Number of Leaves, corresponding alpha



```
rmtree <- rpart(resp ~., data = finData[train_index,-c(2)], method = "anova",
               control = rpart.control(cp = 1/20))
prp(rmtree, main = "Regression Tree for Fatal Crashes per 100,000",
    roundint = FALSE, extra = 1, digits = 4, branch.lty = 3)
```

Regression Tree for Fatal Crashes per 100,000



```

oneTree <- tree(resp ~ ., data = finData[train_index, -c(2)], method = "anova")
oneTree <- prune.tree(oneTree, k = 30)
predOneTree <- predict(oneTree, newdata = finData[test_index, 3:9])
mseOneTree <- mean((predOneTree - finData$resp[test_index])^2)
pseudoROneTree <- 1 - (mseOneTree * 50)/(var(finData$resp) * 49)
  
```

iii. Bagging

I generate 5 different iterations of the random Forest for bagging in order to try and optimize for the number of trees:


```

num_tree = 200
mseRBs <- c()
for(j in 1:5){
  set.seed(j)
  rB_raw <- randomForest(resp ~ ., data = finData[, -c(2)], ntree = num_tree,
    mtry = dim(finData)[2] - 2, importance = TRUE, keep.inbag = TRUE)
  mseRBs <- append(mseRBs, rB_raw$mse)
}
mseRBs <- as.data.frame(matrix(mseRBs, nrow = num_tree, ncol = j))
colnames(mseRBs) <- c(1:5)
plotMSE <- ggplot(data = mseRBs, aes(x = 1:200)) +
  geom_line(aes(y = `1`, color = "Seed 1")) +
  geom_line(aes(y = `2`, color = "Seed 2")) +
  geom_line(aes(y = `3`, color = "Seed 3")) +
  geom_line(aes(y = `4`, color = "Seed 4")) +
  geom_line(aes(y = `5`, color = "Seed 5")) +
  
```

```

xlab("Number of Trees") + ylab("OOB MSE") +
ggtitle("OOB MSE as a function of the number of Trees, 5 Simulations") +
theme(legend.title = element_blank(), plot.title = element_text(hjust = 0.5))
plotMSE

```



It seems as though around 50 is where the OOB MSE finishes decreasing. For the sake of bias-variance trade-off, I select 50 as the number of trees, and fit a random forest model:

```

set.seed(6)
RB <- randomForest(resp ~., data = finData[, -c(2)], ntree = 50,
  mtry = dim(finData)[2] - 2, importance = TRUE, keep.inbag = TRUE)
mseRB <- RB$mse[50]
pseudoRRB <- 1 - (mseRB * 50) / (var(finData$resp) * 49)
RB$importance

```

```

##           %IncMSE IncNodePurity
## Legal      0.04685631      1.713326
## HW_travel 11.59499367     426.179536
## Urban     -0.19137532      24.914778
## Speed_Lim -0.21115978      27.582473
## over_70   -0.33457491      31.267251
## hazard    -0.01103727      28.871072
## binge      0.34190161      34.615816

```

iv. Random Forest

I generate summary statistics:

```
sumstats <- as.data.frame(cbind(c(mseOneTree, mseRB),
                                c(pseudoROneTree, pseudoRRB)))
colnames(sumstats) <- c("MSE", "Pseudo Rsq.")
sumstats$Algorithm <- c("Decision Tree", "Bagged Forest")
sumstats <- sumstats[,c(3,1,2)]
sumstats
```


```
##      Algorithm      MSE Pseudo Rsq.
## 1 Decision Tree 6.605976  0.4375485
## 2 Bagged Forest 5.609170  0.5224193
```

d. Regression Analysis

i. Testing distribution of Response

```
set.seed(1)
lambdaMLE <- mean(resp * 12)
#hist(resp, breaks = 20)
#qqplot(resp, distribution = "poisson")
PoissonDist <- rpois(length(resp), lambdaMLE)
title <- sprintf("QQ Plot, Poisson Dist. with lambda = %.4f", lambdaMLE)
qqplot(resp * 12, PoissonDist, main = title)
abline(0,1,col = 'red')
```


QQ Plot, Poisson Dist. with lambda = 123.0635



```
set.seed(1)
meanResp <- mean(resp)
```


```
sdResp <- sd(resp)
NormalDist <- rnorm(length(resp), meanResp, sdResp)
title <- sprintf("QQ Plot, Normal Dist. with mean = %.4f and SD = %.4f", meanResp, sdResp)
qqplot(resp, NormalDist, main = title)
abline(0, 1, col = 'red')
```

QQ Plot, Normal Dist. with mean = 10.2553 and SD = 3.5458



```
set.seed(1)
meanLogResp <- mean(log(resp))
sdLogResp <- sd(log(resp))
LogNormalDist <- rlnorm(length(resp), meanLogResp, sdLogResp)
title <- sprintf("QQ Plot, Log-Normal Dist. with meanLog = %.4f and sdLog = %.4f", meanLogResp, sdLogResp)
qqplot(resp, LogNormalDist, main = title)
abline(0, 1, col = 'red')
```

QQ Plot, Log-Normal Dist. with meanLog = 2.2634 and sdLog = 0.371



Actual Linear Modeling

```
linMod <- lm("log(resp) ~ Speed_Lim",  
             data = finData)  
summary(linMod)
```

```
##  
## Call:  
## lm(formula = "log(resp) ~ Speed_Lim", data = finData)  
##  
## Residuals:  
##      Min       1Q   Median       3Q      Max   
## -0.86126 -0.19085 -0.01437  0.30527  0.53962   
##  
## Coefficients:  
##              Estimate Std. Error t value Pr(>|t|)      
## (Intercept)  2.10762    0.10562  19.955  <2e-16 ***  
## Speed_Lim60  0.03396    0.22816   0.149   0.8824      
## Speed_Lim65  0.12207    0.14351   0.851   0.3996      
## Speed_Lim70  0.28785    0.13905   2.070   0.0443 *     
## Speed_Lim75  0.34148    0.16936   2.016   0.0499 *     
## Speed_Lim80  0.29771    0.36587   0.814   0.4202      
## ---  
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1  
##  
## Residual standard error: 0.3503 on 44 degrees of freedom
```

```
## Multiple R-squared:  0.1337, Adjusted R-squared:  0.03521
## F-statistic: 1.358 on 5 and 44 DF,  p-value: 0.2586
```

Auto Regression Code below

```
# Splitting data set into first 80% as train set and last 20% as test set
train_set <- ts(USAFat[1:floor(0.8 * length(USAFat))], start = 2008, freq = 12)
test_set <- ts(USAFat[(floor(0.8 * length(USAFat)) + 1):length(USAFat)], start = 2020, freq = 12)

ar1_model <- ar(train_set, method = "mle")
summary(ar1_model)

##              Length Class  Mode
## order          1    -none- numeric
## ar             12    -none- numeric
## var.pred        1    -none- numeric
## x.mean          1    -none- numeric
## aic             13    -none- numeric
## n.used          1    -none- numeric
## n.obs           1    -none- numeric
## order.max       1    -none- numeric
## partialacf      0    -none- NULL
## resid          144    ts      numeric
## method          1    -none- character
## series          1    -none- character
## frequency       1    -none- numeric
## call            3    -none- call
## asy.var.coef 144    -none- numeric

predictions <- forecast(ar1_model, h = length(test_set))
plot(predictions, main = "Forecasts From AR(1)", xlab = "Time", ylab = "Monthly Fatal Vehicle Crashes")
lines(test_set, col = "red", type = "o")
legend("bottomleft", legend = c("Forecasts", "Actual"), col = c("black", "red"), lty = 1)
```

Forecasts From AR(1)

