

ADVANCE ALL MARCH EVERLASTING

DEFENSE: ENSEMBLE TRAINING

35

► Randomized Loss Function:

► Augment Adversarial Examples from the other models as well while training.


► Most used method in NIPS 2017 Adversarial Machine Learning challenge

$$x' = x + \alpha \cdot \text{sign}(\mathcal{N}(0^d, I^d))$$

$$x^{adv} = x' + (\epsilon - \alpha) \cdot \text{sign}(\nabla_x L(x', y))$$

Tramèr, F., Kurakin, A., Papernot, N., Boneh, D., & McDaniel, P. (2017). Ensemble Adversarial Training: Attacks and Defenses.

DEFENSE: DISTILLATION



An overview of distillation defence mechanism based on a transfer of knowledge contained in probability vectors through distillation: We first train an initial network F on data X with a softmax temperature of T . We then use the probability vector $F(X)$, which includes additional knowledge about classes compared to a class label, predicted by network F to train a distilled network F^d at temperature T on the same data X .

DEFENSE: ENSEMBLE TRAINING

- ▶ Randomized Loss Function:

$$x' = x + \alpha \cdot \text{sign}(\mathcal{N}(0^d, I^d))$$
$$x^{adv} = x' + (\epsilon - \alpha) \cdot \text{sign}(\nabla_x L(x', y))$$

- ▶ Augment Adversarial Examples from the other models as well while training.
- ▶ Most used method in NIPS 2017 Adversarial Machine Learning challenge