Shut down commands systemd

YOU

Oct 11, 12:40 AM

Instead of systemctl restart now, how do I shut down?

AI ASSISTANT

Oct 11, 12:40 AM

If you want to **shut down** instead of restarting with `systemctl`, here are your options:

🧰 Safe systemd shutdown commands

Action	Command	Description
Shut down immediately	`sudo systemctl poweroff`	Powers off the machine completely.
Halt (stop all CPUs, but don't cut power)	`sudo systemctl halt`	Stops the OS but doesn't turn off power (useful for debugging).
Reboot	`sudo systemctl reboot`	Restarts the system (what you're replacing).
Suspend (sleep)	`sudo systemctl suspend`	Puts system into low-power sleep mode.
Hibernate	`sudo systemctl hibernate`	Saves memory to disk and powers off; resumes later.

🔋 Simpler equivalents

You can also use:

```bash
sudo shutdown now
```

or, to power off after a minute delay:

```bash
sudo shutdown -h now
```

(`-h` means halt, which in modern systems = full shutdown)

✅ **Recommendation:**
For a clean, immediate power-off on Ubuntu or Debian systems, use:

```
bash
sudo systemctl poweroff
```

Would you like me to include how to schedule a shutdown (e.g., in 10 minutes or at 23:00)?

YOU

Oct 11, 12:40 AM

root octavian ~ sudo systemctl poweroff now Too many arguments. root octavian ~ sudo systemctl poweroff Failed to set wall message, ignoring: Transport endpoint is not connected Call to PowerOff failed: Transport endpoint is not connected root octavian ~ sudo shutdown now Failed to set wall message, ignoring: Transport endpoint is not connected Call to PowerOff failed: Transport endpoint is not connected

AI ASSISTANT

Oct 11, 12:40 AM

You're hitting two separate things:

1. `Too many arguments.` → `systemctl poweroff` doesn't take `now`. Just use it with no args (you already tried).
2. `Transport endpoint is not connected` → usually a broken FUSE/sshfs mount or a busted systemd/dbus connection is blocking the call to PID 1.

Here's how to get it to shut down anyway, safest → strongest:

A. Quick fixes (often enough)

1. Move off any dead mount and retry:

```
bash
cd /
sudo systemctl poweroff -i
```

(`-i` ignores inhibitors.)

2. If you have sshfs/other FUSE mounts, lazily unmount them first:

```
bash
mount | grep fuse
# for each suspicious mount point:
sudo umount -l /path/to/mount   # or: fusermount -uz /path/to/mount
sudo systemctl poweroff -i
```

3. Try via logind (sometimes works when `systemctl` bus is glitchy):

```
bash
sudo loginctl poweroff
```

B. Check you're actually under systemd

If you're in a container/chroot, `systemctl` can't talk to PID 1:

```
bash
ps -p1 -o comm=
# should print: systemd
```

If not `systemd`, use the host/hypervisor to shut down the VM/container, or force poweroff below.

C. If it's a VM and guest shutdown fails

Use your hypervisor's UI ("ACPI Shutdown" / "Power Off"). On Proxmox/KVM this is reliable when the guest can't reach systemd.

D. Emergency kernel SysRq power-off (last resort)

This bypasses systemd entirely. It's immediate—ensure disks are synced first to minimize risk:

```
bash
sudo sh -c 'sync; sleep 1; echo s > /proc/sysrq-trigger; echo u > /proc/sysrq-
trigger; echo o > /proc/sysrq-trigger'
```

- `s`: flush buffers
- `u`: remount filesystems read-only
- `o`: power off now

If `/proc/sysrq-trigger` is disabled, enable temporarily:

```
bash
echo 1 | sudo tee /proc/sys/kernel/sysrq
```

If you want, paste the output of:

```
bash
mount | grep fuse || true
dmesg | tail -n 50
```

and I'll point out the exact mount causing the "Transport endpoint is not connected" error.