

## wolfSentry Embedded Firewall/IDPS v1.6.1 API Reference

WolfSSL Inc., Sat Nov 18 2023



<b>1 wolfSentry – The Wolfssl Embedded Firewall/IDPS</b>	<b>1</b>
<b>2 Building and Initializing wolfSentry for an application on FreeRTOS/IWIP</b>	<b>7</b>
<b>3 Configuring wolfSentry using a JSON document</b>	<b>11</b>
<b>4 wolfSentry Release History and Change Log</b>	<b>21</b>
<b>5 Topic Index</b>	<b>45</b>
5.1 Topics . . . . .	45
<b>6 Data Structure Index</b>	<b>47</b>
6.1 Data Structures . . . . .	47
<b>7 File Index</b>	<b>49</b>
7.1 File List . . . . .	49
<b>8 Topic Documentation</b>	<b>51</b>
8.1 Core Types and Macros . . . . .	51
8.1.1 Detailed Description . . . . .	52
8.2 Startup/Configuration/Shutdown Subsystem . . . . .	52
8.2.1 Detailed Description . . . . .	56
8.2.2 Enumeration Type Documentation . . . . .	56
8.2.2.1 wolfsentry_clone_flags_t . . . . .	57
8.2.2.2 wolfsentry_config_load_flags . . . . .	57
8.2.2.3 wolfsentry_init_flags_t . . . . .	58
8.2.3 Function Documentation . . . . .	58
8.2.3.1 wolfsentry_context_clone() . . . . .	58
8.2.3.2 wolfsentry_context_enable_actions() . . . . .	58
8.2.3.3 wolfsentry_context_exchange() . . . . .	59
8.2.3.4 wolfsentry_context_flush() . . . . .	59
8.2.3.5 wolfsentry_context_free() . . . . .	59
8.2.3.6 wolfsentry_context_inhibit_actions() . . . . .	60
8.2.3.7 wolfsentry_defaultconfig_get() . . . . .	60
8.2.3.8 wolfsentry_defaultconfig_update() . . . . .	60
8.2.3.9 wolfsentry_init() . . . . .	61
8.2.3.10 wolfsentry_shutdown() . . . . .	61
8.3 Diagnostics, Control Flow Helpers, and Compiler Attribute Helpers . . . . .	62
8.3.1 Detailed Description . . . . .	66
8.3.2 Macro Definition Documentation . . . . .	66
8.3.2.1 WOLFSENTRY_DEBUG_CALL_TRACE . . . . .	66
8.3.2.2 WOLFSENTRY_ERROR_UNLOCK_AND_RETURN . . . . .	66
8.3.2.3 WOLFSENTRY_MUTEX_OR_RETURN . . . . .	67
8.3.2.4 WOLFSENTRY_PROMOTABLE_EX . . . . .	67
8.3.2.5 WOLFSENTRY_PROMOTABLE_OR_RETURN . . . . .	67

8.3.2.6 WOLFSENTRY_SHARED_EX . . . . .	67
8.3.2.7 WOLFSENTRY_SHARED_OR_RETURN . . . . .	67
8.3.2.8 WOLFSENTRY_UNLOCK_AND_RETURN . . . . .	68
8.3.2.9 WOLFSENTRY_UNLOCK_AND_UNRESERVE_FOR_RETURN . . . . .	68
8.3.2.10 WOLFSENTRY_UNLOCK_AND_UNRESERVE_FOR_RETURN_EX . . . . .	68
8.3.2.11 WOLFSENTRY_UNLOCK_FOR_RETURN . . . . .	68
8.3.2.12 WOLFSENTRY_UNLOCK_FOR_RETURN_EX . . . . .	68
8.4 Route/Rule Subsystem . . . . .	69
8.4.1 Detailed Description . . . . .	75
8.4.2 Macro Definition Documentation . . . . .	75
8.4.2.1 WOLFSENTRY_ROUTE_INTERNAL_FLAGS . . . . .	75
8.4.2.2 WOLFSENTRY_SOCKADDR . . . . .	75
8.4.3 Enumeration Type Documentation . . . . .	76
8.4.3.1 wolfsentry_format_flags_t . . . . .	76
8.4.3.2 wolfsentry_route_flags_t . . . . .	76
8.4.4 Function Documentation . . . . .	77
8.4.4.1 wolfsentry_route_bulk_clear_insert_action_status() . . . . .	77
8.4.4.2 wolfsentry_route_bulk_insert_actions() . . . . .	78
8.4.4.3 wolfsentry_route_delete() . . . . .	78
8.4.4.4 wolfsentry_route_delete_by_id() . . . . .	79
8.4.4.5 wolfsentry_route_drop_reference() . . . . .	79
8.4.4.6 wolfsentry_route_event_dispatch() . . . . .	80
8.4.4.7 wolfsentry_route_export() . . . . .	81
8.4.4.8 wolfsentry_route_exports_render() . . . . .	81
8.4.4.9 wolfsentry_route_flush_table() . . . . .	82
8.4.4.10 wolfsentry_route_get_addrs() . . . . .	82
8.4.4.11 wolfsentry_route_get_flags() . . . . .	82
8.4.4.12 wolfsentry_route_get_main_table() . . . . .	83
8.4.4.13 wolfsentry_route_get_metadata() . . . . .	83
8.4.4.14 wolfsentry_route_get_private_data() . . . . .	83
8.4.4.15 wolfsentry_route_get_reference() . . . . .	84
8.4.4.16 wolfsentry_route_insert() . . . . .	85
8.4.4.17 wolfsentry_route_parent_event() . . . . .	85
8.4.4.18 wolfsentry_route_render() . . . . .	86
8.4.4.19 wolfsentry_route_set_wildcard() . . . . .	86
8.4.4.20 wolfsentry_route_stale_purge() . . . . .	87
8.4.4.21 wolfsentry_route_table_default_policy_get() . . . . .	87
8.4.4.22 wolfsentry_route_table_default_policy_set() . . . . .	88
8.4.4.23 wolfsentry_route_table_fallthrough_route_get() . . . . .	88
8.4.4.24 wolfsentry_route_table_iterate_current() . . . . .	88
8.4.4.25 wolfsentry_route_table_iterate_end() . . . . .	89
8.4.4.26 wolfsentry_route_table_iterate_next() . . . . .	89

8.4.4.27 wolfsentry_route_table_iterate_prev()	90
8.4.4.28 wolfsentry_route_table_iterate_seek_to_head()	90
8.4.4.29 wolfsentry_route_table_iterate_seek_to_tail()	90
8.4.4.30 wolfsentry_route_table_iterate_start()	91
8.4.4.31 wolfsentry_route_update_flags()	91
8.5 Action Subsystem	92
8.5.1 Detailed Description	94
8.5.2 Typedef Documentation	94
8.5.2.1 wolfsentry_action_callback_t	94
8.5.3 Enumeration Type Documentation	95
8.5.3.1 wolfsentry_action_flags_t	95
8.5.3.2 wolfsentry_action_res_t	95
8.5.3.3 wolfsentry_action_type_t	96
8.5.4 Function Documentation	96
8.5.4.1 wolfsentry_action_delete()	96
8.5.4.2 wolfsentry_action_drop_reference()	97
8.5.4.3 wolfsentry_action_flush_all()	97
8.5.4.4 wolfsentry_action_get_flags()	98
8.5.4.5 wolfsentry_action_get_label()	98
8.5.4.6 wolfsentry_action_get_reference()	98
8.5.4.7 wolfsentry_action_insert()	99
8.5.4.8 wolfsentry_action_update_flags()	100
8.6 Event Subsystem	100
8.6.1 Detailed Description	102
8.6.2 Enumeration Type Documentation	102
8.6.2.1 wolfsentry_event_flags_t	102
8.6.2.2 wolfsentry_eventconfig_flags_t	102
8.6.3 Function Documentation	103
8.6.3.1 wolfsentry_event_action_append()	103
8.6.3.2 wolfsentry_event_action_delete()	103
8.6.3.3 wolfsentry_event_action_insert_after()	104
8.6.3.4 wolfsentry_event_action_list_done()	104
8.6.3.5 wolfsentry_event_action_list_next()	105
8.6.3.6 wolfsentry_event_action_list_start()	105
8.6.3.7 wolfsentry_event_action_prepend()	106
8.6.3.8 wolfsentry_event_delete()	107
8.6.3.9 wolfsentry_event_drop_reference()	107
8.6.3.10 wolfsentry_event_flush_all()	107
8.6.3.11 wolfsentry_event_get_config()	108
8.6.3.12 wolfsentry_event_get_flags()	108
8.6.3.13 wolfsentry_event_get_label()	109
8.6.3.14 wolfsentry_event_get_reference()	109

8.6.3.15 wolfsentry_event_insert()	109
8.6.3.16 wolfsentry_event_set_aux_event()	110
8.6.3.17 wolfsentry_event_update_config()	110
8.6.3.18 wolfsentry_eventconfig_check()	112
8.6.3.19 wolfsentry_eventconfig_init()	112
8.7 Address Family Subsystem	113
8.7.1 Detailed Description	116
8.8 User-Defined Value Subsystem	116
8.8.1 Detailed Description	120
8.8.2 Typedef Documentation	120
8.8.2.1 wolfsentry_kv_validator_t	120
8.8.3 Function Documentation	120
8.8.3.1 wolfsentry_user_value_get_bytes()	120
8.8.3.2 wolfsentry_user_value_get_json()	120
8.8.3.3 wolfsentry_user_value_get_string()	120
8.9 Object Subsystem	121
8.9.1 Detailed Description	121
8.9.2 Enumeration Type Documentation	121
8.9.2.1 wolfsentry_object_type_t	121
8.9.3 Function Documentation	122
8.9.3.1 wolfsentry_get_object_id()	122
8.9.3.2 wolfsentry_get_object_type()	122
8.9.3.3 wolfsentry_table_n_deletes()	123
8.9.3.4 wolfsentry_table_n_inserts()	123
8.10 Thread Synchronization Subsystem	123
8.10.1 Detailed Description	128
8.10.2 Macro Definition Documentation	128
8.10.2.1 WOLFSENTRY_THREAD_HEADER	128
8.10.2.2 WOLFSENTRY_THREAD_HEADER_CHECK	128
8.10.2.3 WOLFSENTRY_THREAD_HEADER_CHECKED	129
8.10.2.4 WOLFSENTRY_THREAD_HEADER_DECLS	129
8.10.2.5 WOLFSENTRY_THREAD_HEADER_INIT	129
8.10.2.6 WOLFSENTRY_THREAD_HEADER_INIT_CHECKED	129
8.10.2.7 WOLFSENTRY_THREAD_TAILER	129
8.10.3 Enumeration Type Documentation	129
8.10.3.1 wolfsentry_lock_flags_t	129
8.10.3.2 wolfsentry_thread_flags_t	130
8.10.4 Function Documentation	130
8.10.4.1 wolfsentry_lock_alloc()	130
8.10.4.2 wolfsentry_lock_destroy()	132
8.10.4.3 wolfsentry_lock_free()	132
8.10.4.4 wolfsentry_lock_get_flags()	133

8.10.4.5 wolfsentry_lock_have_either()	133
8.10.4.6 wolfsentry_lock_have_mutex()	134
8.10.4.7 wolfsentry_lock_have_shared()	134
8.10.4.8 wolfsentry_lock_have_shared2mutex_reservation()	135
8.10.4.9 wolfsentry_lock_init()	135
8.10.4.10 wolfsentry_lock_mutex()	136
8.10.4.11 wolfsentry_lock_mutex2shared()	136
8.10.4.12 wolfsentry_lock_mutex_abstimed()	137
8.10.4.13 wolfsentry_lock_mutex_timed()	137
8.10.4.14 wolfsentry_lock_shared()	138
8.10.4.15 wolfsentry_lock_shared2mutex()	138
8.10.4.16 wolfsentry_lock_shared2mutex_abandon()	139
8.10.4.17 wolfsentry_lock_shared2mutex_abstimed()	139
8.10.4.18 wolfsentry_lock_shared2mutex_redeem()	140
8.10.4.19 wolfsentry_lock_shared2mutex_redeem_abstimed()	140
8.10.4.20 wolfsentry_lock_shared2mutex_redeem_timed()	141
8.10.4.21 wolfsentry_lock_shared2mutex_reserve()	141
8.10.4.22 wolfsentry_lock_shared2mutex_timed()	142
8.10.4.23 wolfsentry_lock_shared_abstimed()	142
8.10.4.24 wolfsentry_lock_shared_timed()	143
8.10.4.25 wolfsentry_lock_unlock()	144
8.11 Allocator (Heap) Functions and Callbacks	144
8.11.1 Detailed Description	145
8.12 Time Functions and Callbacks	145
8.12.1 Detailed Description	146
8.13 Semaphore Function Callbacks	146
8.13.1 Detailed Description	147
8.13.2 Typedef Documentation	147
8.13.2.1 sem_destroy_cb_t	147
8.13.2.2 sem_init_cb_t	147
8.13.2.3 sem_post_cb_t	147
8.13.2.4 sem_timedwait_cb_t	147
8.13.2.5 sem_trywait_cb_t	147
8.13.2.6 sem_wait_cb_t	148
8.14 lwIP Callback Activation Functions	148
8.14.1 Detailed Description	148
<b>9 Data Structure Documentation</b>	<b>149</b>
9.1 JSON_CALLBACKS Struct Reference	149
9.2 JSON_CONFIG Struct Reference	149
9.3 JSON_DOM_PARSER Struct Reference	149
9.4 JSON_INPUT_POS Struct Reference	150

9.5 JSON_PARSER Struct Reference . . . . .	150
9.6 JSON_VALUE Struct Reference . . . . .	150
9.7 wolfsentry_allocator Struct Reference . . . . .	151
9.7.1 Detailed Description . . . . .	151
9.8 wolfsentry_build_settings Struct Reference . . . . .	151
9.8.1 Detailed Description . . . . .	151
9.8.2 Field Documentation . . . . .	151
9.8.2.1 config . . . . .	151
9.8.2.2 version . . . . .	152
9.9 wolfsentry_data Struct Reference . . . . .	152
9.10 wolfsentry_eventconfig Struct Reference . . . . .	152
9.10.1 Detailed Description . . . . .	153
9.11 wolfsentry_host_platform_interface Struct Reference . . . . .	153
9.11.1 Detailed Description . . . . .	153
9.11.2 Field Documentation . . . . .	153
9.11.2.1 allocator . . . . .	153
9.11.2.2 caller_build_settings . . . . .	153
9.11.2.3 semcbcs . . . . .	153
9.11.2.4 timecbcs . . . . .	153
9.12 wolfsentry_kv_pair Struct Reference . . . . .	154
9.12.1 Detailed Description . . . . .	154
9.12.2 Field Documentation . . . . .	154
9.12.2.1 b . . . . .	154
9.13 wolfsentry_route_endpoint Struct Reference . . . . .	154
9.13.1 Detailed Description . . . . .	155
9.14 wolfsentry_route_exports Struct Reference . . . . .	155
9.14.1 Detailed Description . . . . .	156
9.15 wolfsentry_route_metadata_exports Struct Reference . . . . .	156
9.15.1 Detailed Description . . . . .	156
9.16 wolfsentry_semcbcs Struct Reference . . . . .	156
9.16.1 Detailed Description . . . . .	157
9.17 wolfsentry_sockaddr Struct Reference . . . . .	157
9.17.1 Detailed Description . . . . .	157
9.18 wolfsentry_thread_context_public Struct Reference . . . . .	158
9.18.1 Detailed Description . . . . .	158
9.19 wolfsentry_timecbcs Struct Reference . . . . .	158
9.19.1 Detailed Description . . . . .	158
<b>10 File Documentation . . . . .</b>	<b>159</b>
10.1 centijson_dom.h . . . . .	159
10.2 centijson_sax.h . . . . .	161
10.3 centijson_value.h . . . . .	165



10.4 wolfsentry/wolfsentry.h File Reference . . . . .	172
10.4.1 Detailed Description . . . . .	194
10.5 wolfsentry.h . . . . .	194
10.6 wolfsentry/wolfsentry_af.h File Reference . . . . .	213
10.6.1 Detailed Description . . . . .	216
10.7 wolfsentry_af.h . . . . .	217
10.8 wolfsentry/wolfsentry_errcodes.h File Reference . . . . .	218
10.8.1 Detailed Description . . . . .	222
10.9 wolfsentry_errcodes.h . . . . .	223
10.10 wolfsentry/wolfsentry_json.h File Reference . . . . .	228
10.10.1 Detailed Description . . . . .	229
10.11 wolfsentry_json.h . . . . .	229
10.12 wolfsentry/wolfsentry_lwip.h File Reference . . . . .	230
10.12.1 Detailed Description . . . . .	231
10.13 wolfsentry_lwip.h . . . . .	231
10.14 wolfsentry/wolfsentry_settings.h File Reference . . . . .	232
10.14.1 Detailed Description . . . . .	235
10.15 wolfsentry_settings.h . . . . .	236
10.16 wolfsentry/wolfsentry_util.h File Reference . . . . .	244
10.16.1 Detailed Description . . . . .	246
10.16.2 Macro Definition Documentation . . . . .	246
10.16.2.1 WOLFSENTRY_ATOMIC_DECREMENT_UNSIGNED_SAFELY . . . . .	246
10.16.2.2 WOLFSENTRY_ATOMIC_DECREMENT_UNSIGNED_SAFELY_BY_ONE . . . . .	246
10.16.2.3 WOLFSENTRY_ATOMIC_INCREMENT_UNSIGNED_SAFELY . . . . .	247
10.16.2.4 WOLFSENTRY_ATOMIC_INCREMENT_UNSIGNED_SAFELY_BY_ONE . . . . .	247
10.16.2.5 WOLFSENTRY_ATOMIC_RESET . . . . .	247
10.16.2.6 WOLFSENTRY_ATOMIC_TEST_AND_SET . . . . .	247
10.16.2.7 WOLFSENTRY_ATOMIC_UPDATE_FLAGS . . . . .	248
10.17 wolfsentry_util.h . . . . .	248
10.18 wolfsentry/wolfssl_test.h File Reference . . . . .	251
10.18.1 Detailed Description . . . . .	251
10.19 wolfssl_test.h . . . . .	252
<b>Index</b>	<b>259</b>



## Chapter 1

# wolfSentry – The Wolfssl Embedded Firewall/IDPS

### Description

wolfSentry is the wolfSSL embedded IDPS (Intrusion Detection and Prevention System). In simple terms, wolfSentry is an embedded firewall engine (both static and fully dynamic), with prefix-based and wildcard-capable lookup of known hosts/netblocks qualified by interface, address family, protocol, port, and other traffic parameters. Additionally, wolfSentry can be used as a dynamically configurable logic hub, arbitrarily associating user-defined events with user-defined actions, contextualized by connection attributes. The evolution of client-server relationships can thus be tracked in detail, freely passing traffic matching expected usage patterns, while efficiently rejecting abusive traffic.

wolfSentry is fully integrated with the lwIP stack, through a patchset in the `lwip/` subdirectory of the source tree, and has basic integration with the wolfSSL library for application-level filtering of inbound and outbound connections.

The wolfSentry engine is dynamically configurable programmatically through an API, or from a textual input file in JSON supplied to the engine, or dynamically and incrementally with JSON fragments, or any combination of these methods. Reconfiguration is protected by transactional semantics, and advanced internal locks on threaded targets assure seamless service availability with atomic policy transition. Callbacks allow for transport-agnostic remote logging, e.g. through MQTT, syslog, or DDS message buses.

wolfSentry is designed from the ground up to function well in resource-constrained, bare-metal, and realtime environments, with algorithms to stay within designated maximum memory footprints and maintain deterministic throughput. This allows full firewall and IDPS functionality on embedded targets such as FreeRTOS, Nucleus, NUTTX, Zephyr, VxWorks, and Green Hills Integrity, and on ARM and other common embedded CPUs and MCUs. wolfSentry with dynamic firewalling can add as little as 64k to the code footprint, and 32k to the volatile state footprint, and can fully leverage the existing logic and state of applications and sibling libraries.

### Documentation

With `doxygen` installed, the HTML version of the full API reference manual can be generated from the top of the wolfSentry source tree with `make doc-html`. This, and the source code itself, are the recommended API references.

The PDF version of the API reference manual is pregenerated and included with source distributions in the `doc/` subdirectory at `doc/wolfSentry_refman.pdf`. The latest version is always available [on GitHub](#).

## Dependencies

In its default build, wolfSentry depends on a POSIX runtime, specifically the heap allocator, `clock_gettime`, `stdio`, `semaphore`, `pthread`s, and string APIs. However, these dependencies can be avoided with various build-time options. The recipe

```
make STATIC=1 SINGLETHREADED=1 NO_STDIO=1 EXTRA_CFLAGS="-DWOLFSENTRY_NO_↵
CLOCK_BUILTIN -DWOLFSENTRY_NO_MALLOC_BUILTIN"
```

builds a `libwolfentry.a` that depends on only a handful of basic string functions and the `inet_ntop()` library function (from POSIX.1-2001, and also implemented by lwIP). Allocator and time callbacks must then be set in a struct `wolfentry_host_platform_interface` supplied to `wolfentry_init()`.

The wolfSentry Makefile depends on a modern (v4.0+) Gnu make. The library itself can be built outside make, within another project/framework, by creating a user settings macro file and passing its path to the compiler with the `WOLFSENTRY_USER_SETTINGS_FILE` macro.

## Building

wolfSentry was written with portability in mind, with provisions for non-POSIX and C89 targets. For example, all its dependencies can be met with the FreeRTOS/newlib-nano/lwIP runtime. If you have difficulty building wolfSentry, please don't hesitate to seek support through our [support forums](#) or contact us directly at [support@wolfssl.com](mailto:support@wolfssl.com).

The current wolfSentry release can be downloaded from [the wolfSSL website as a ZIP file](#), and developers can [browse the release history](#) and clone [the wolfSentry Git repository](#) for the latest pre-release updates.

There are several flags that can be passed to make to control the build parameters. make will store them at build time in `wolfentry/wolfentry_options.h` in the build tree. If you are not using make, then the C macro `WOLFSENTRY_USER_SETTINGS_FILE` should be defined to the path to a file containing settings, both when building wolfSentry and when building the application.

The following feature control variables are recognized. True/false features (LWIP, NO\_STDIO, NO\_JSON, etc.) are undefined by default, and activated when defined. Macros can be supplied using the `EXTRA_CFLAGS` option, or by placing them in a `USER_SETTINGS_FILE`. More detailed documentation for macros is available in the reference manual "Startup/Configuration/Shutdown Subsystem" topic.

make Option	Macro Option	Description
V		Verbose make output e.g. <code>make V=1 -j test</code>
USER_MAKE_CONF		User-defined make clauses to include at the top of the main Makefile e.g. <code>make -j USER_MAKE_↵CONF=Makefile.settings</code>
EXTRA_CFLAGS		Additional arguments to be passed verbatim to the compiler
EXTRA_LDFLAGS		Additional arguments to be passed verbatim to the linker
SRC_TOP		The source code top level directory (default <code>pwd -P</code> )

make Option	Macro Option	Description
BUILD_TOP		Build with artifacts in an alternate location (outside or in a subdirectory of the source tree) e.g. <code>make BUILD_TOP=./build -j test</code>
DEBUG		Compiler debugging flag to use (default <code>-ggdb</code> )
OPTIM		The optimizer flag to use (default <code>-O3</code> )
HOST		The target host tuple, for cross-compilation (default unset, i.e. native targeting)
RUNTIME		The target runtime ecosystem – default unset, <code>FreeRTOS-lwIP</code> and <code>Linux-lwIP</code> are recognized
C_WARNFLAGS		The warning flags to use (overriding the generally applicable defaults)
STATIC		Build statically linked unit tests
STRIPPED		Strip binaries of debugging symbols
BUILD_DYNAMIC		Build dynamically linked library
VERY_QUIET		Inhibit all non-error output during build
TAR		Path to GNU tar binary for <code>make dist</code> , should be set to <code>gtar</code> for macOS
VERSION		The version to package for <code>make dist</code>
LWIP	WOLFSENTRY_LWIP	True/false – Activates appropriate build settings for lwIP
NO_STDIO_STREAMS	WOLFSENTRY_NO_STDIO_STREAMS	Define to omit functionality that depends on <code>stdio</code> stream I/O
	WOLFSENTRY_NO_STDIO_H	Define to inhibit inclusion of <code>stdio.h</code>
NO_ADDR_BITMASK_MATCHING	WOLFSENTRY_NO_ADDR_BITMASK_MATCHING	Define to omit support for bitmask matching of addresses, i.e. support only prefix matching.
NO_IPV6	WOLFSENTRY_NO_IPV6	Define to omit support for the IPv6 address family.
NO_JSON	WOLFSENTRY_NO_JSON	Define to omit JSON configuration support
NO_JSON_DOM	WOLFSENTRY_NO_JSON_DOM	Define to omit JSON DOM API
CALL_TRACE	WOLFSENTRY_DEBUG_CALL_TRACE	Define to activate runtime call stack logging (profusely verbose)
USER_SETTINGS_FILE	WOLFSENTRY_USER_SETTINGS_FILE	A substitute settings file, replacing autogenerated <a href="#">wolfentry_settings.h</a>
SINGLETHREADED	WOLFSENTRY_SINGLETHREADED	Define to omit thread safety logic, and replace thread safety functions and macros with no-op macros.

make Option	Macro Option	Description
	WOLFSENTRY_NO_↔ PROTOCOL_NAMES	If defined, omit APIs for rendering error codes and source code files in human readable form. They will be rendered numerically.
	WOLFSENTRY_NO_↔ GETPROTOBY	Define to disable lookup and rendering of protocols and services by name.
	WOLFSENTRY_NO_ERROR_↔ STRINGS	If defined, omit APIs for rendering error codes and source code files in human readable form. They will be rendered numerically.
	WOLFSENTRY_NO_MALLOC_↔ BUILTINS	If defined, omit built-in heap allocator primitives; the <a href="#">wolfentry_host_platform_interface</a> supplied to wolfSentry APIs must include implementations of all functions in struct <a href="#">wolfentry_allocator</a> .
	WOLFSENTRY_HAVE_↔ NONGNU_ATOMICS	Define if gnu-style atomic intrinsics are not available. WOLFSENTRY_↔ _ATOMIC_*() macro definitions for intrinsics will need to be supplied in WOLFSENTRY_↔ USER_SETTINGS_FILE (see <a href="#">wolfentry_util.h</a> ).
	WOLFSENTRY_NO_CLOCK_↔ BUILTIN	If defined, omit built-in time primitives; the <a href="#">wolfentry_host_platform_interface</a> supplied to wolfSentry APIs must include implementations of all functions in struct <a href="#">wolfentry_timecbs</a> .
	WOLFSENTRY_NO_SEM_↔ BUILTIN	If defined, omit built-in semaphore primitives; the <a href="#">wolfentry_host_platform_interface</a> supplied to wolfSentry APIs must include implementations of all functions in struct <a href="#">wolfentry_semcbs</a> .
	WOLFSENTRY_USE_↔ NONPOSIX_SEMAPHORES	Define if POSIX semaphore API is not available. If no non-POSIX builtin implementation is present in <a href="#">wolfentry_util.c</a> , then <a href="#">WOLFSENTRY_NO_SEM_BUILTIN</a> must be set, and the <a href="#">wolfentry_host_platform_interface</a> supplied to wolfSentry APIs must include a full semaphore implementation (shim set) in its <a href="#">wolfentry_semcbs</a> slot.
	WOLFSENTRY_SEMAPHORE_↔ INCLUDE	Define to the path of a header file declaring a semaphore API.

make Option	Macro Option	Description
	WOLFSENTRY_USE_↔ NONPOSIX_THREADS	Define if POSIX thread API is not available. WOLFSENTRY_↔ _THREAD_INCLUDE, WOLFSENTRY_THREAD_ID_T, and WOLFSENTRY_THREAD_↔ GET_ID_HANDLER will need to be defined.
	WOLFSENTRY_THREAD_↔ INCLUDE	Define to the path of a header file declaring a threading API.
	WOLFSENTRY_THREAD_ID_T	Define to the appropriate type anal- ogous to POSIX pthread_t.
	WOLFSENTRY_THREAD_GET↔ _ID_HANDLER	Define to the name of a void function analogous to POSIX pthread_self, returning a value of type WOLFSENTRY_↔ THREAD_ID_T.
	FREERTOS	Build for FreeRTOS

## Build and Self-Test Examples

Building and testing libwolfssentry.a on Linux:

```
make -j test
```

Build verbosely:

```
make V=1 -j test
```

Build with artifacts in an alternate location (outside or in a subdirectory of the source tree):

```
make BUILD_TOP=./build -j test
```

Install from an alternate build location to a non-standard destination:

```
make BUILD_TOP=./build INSTALL_DIR=/usr INSTALL_LIBDIR=/usr/lib64 install
```

Build libwolfssentry.a and test it in various configurations:

```
make -j check
```

Build and test libwolfssentry.a without support for multithreading:

```
make -j SINGLETHREADED=1 test
```

Other available make flags are `STATIC=1`, `STRIPPED=1`, `NO_JSON=1`, and `NO_JSON_DOM=1`, and the defaults values for `DEBUG`, `OPTIM`, and `C_WARNFLAGS` can also be usefully overridden.

Build with a user-supplied makefile preamble to override defaults:

```
make -j USER_MAKE_CONF=Makefile.settings
```

(`Makefile.settings` can contain simple settings like `OPTIM := -Os`, or elaborate makefile code including additional rules and dependency mechanisms.)

Build the smallest simplest possible library:

```
make -j SINGLETHREADED=1 NO_STDIO=1 DEBUG= OPTIM=-Os EXTRA_CFLAGS="-DWOLFSENTRY_↔  
_NO_CLOCK_BUILTIN -DWOLFSENTRY_NO_MALLOC_BUILTIN -DWOLFSENTRY_NO_ERROR_↔  
STRINGS -Wno-error=inline -Wno-inline"
```

Build and test with user settings:

```
make -j USER_SETTINGS_FILE=user_settings.h test
```

Build for FreeRTOS on ARM32, assuming FreeRTOS and lwIP source trees are located as shown:

```
make -j HOST=arm-none-eabi RUNTIME=FreeRTOS-lwIP FREERTOS_TOP=../third/↔  
FreeRTOSv202212.00 LWIP_TOP=../third/lwip EXTRA_CFLAGS=-mcpu=cortex-m7
```

## Project Examples

In the `wolfSentry/examples/` subdirectory are a set of example ports and applications, including a demo pop-up notification system implementing a toy TLS-enabled embedded web server, integrating with the Linux D-Bus facility.

More comprehensive examples of API usage are in `tests/unittests.c`, particularly `test_static_routes()`, `test_dynamic_rules()`, and `test_json()`, and the JSON configuration files at `tests/test-config*.json`.

In [the wolfSSL repository](#), see code in `wolfssl/test.h` gated on `WOLFSSL_WOLFSENTRY_HOOKS`, including `wolfSentry_store_endpoints()`, `wolfSentry_NetworkFilterCallback()`, `wolfSentry_setup()`, and `tcp_connect_with_wolfSentry()`. See also code in `examples/server/server.c` and `examples/client/client.c` gated on `WOLFSSL_WOLFSENTRY_HOOKS`. Configure wolfssl with `--enable-wolfSentry` to build with wolfSentry integration, and use `--with-wolfSentry=/the/install/path` if wolfSentry is installed in a nonstandard location. The wolfSSL test client/server can be loaded with user-supplied wolfSentry JSON configurations from the command line, using `--wolfSentry-config <file>`.



## Chapter 2

# Building and Initializing wolfSentry for an application on FreeRTOS/lwIP

Building the wolfSentry library for FreeRTOS with lwIP and newlib-nano is supported directly by the top level Makefile. E.g., for an ARM Cortex M7, `libwolfSentry.a` can be built with

```
make HOST=arm-none-eabi EXTRA_CFLAGS='-mcpu=cortex-m7' RUNTIME=FreeRTOS-lwIP FREERTOS_TOP="$FREERTOS_TOP"
LWIP_TOP="$LWIP_TOP"
```

`FREERTOS_TOP` is the path to the top of the FreeRTOS distribution, with `FreeRTOS/Source` directly under it, and `LWIP_TOP` is the path to the top of the lwIP distribution, with `src` directly under it.

The below code fragments can be added to a FreeRTOS application to enable wolfSentry with dynamically loaded policies (JSON). Many of the demonstrated code patterns are optional. The only calls that are indispensable are `wolfSentry_init()`, `wolfSentry_config_json_oneShot()`, and `wolfSentry_install_lwip_filter_callbacks()`. Each of these also has API variants that give the user more control.

```
#define WOLFSENTRY_SOURCE_ID WOLFSENTRY_SOURCE_ID_USER_BASE
#define WOLFSENTRY_ERROR_ID_USER_APP_ERR0 (WOLFSENTRY_ERROR_ID_USER_BASE-1)
/* user-defined error IDs count down starting at WOLFSENTRY_ERROR_ID_USER_BASE (which is negative). */

#include <wolfSentry/wolfSentry_json.h>
#include <wolfSentry/wolfSentry_lwip.h>

static struct wolfSentry_context *wolfSentry_lwip_ctx = NULL;

static const struct wolfSentry_eventconfig demo_config = {
#ifdef WOLFSENTRY_HAVE_DESIGNATED_INITIALIZERS
    .route_private_data_size = 64,
    .route_private_data_alignment = 0,
    .max_connection_count = 10,
    .derogatory_threshold_for_penaltybox = 4,
    .penaltybox_duration = 300,
    .route_idle_time_for_purge = 0,
    .flags = WOLFSENTRY_EVENTCONFIG_FLAG_COMMENDABLE_CLEAR_DEROGATORY,
    .route_flags_to_add_on_insert = 0,
    .route_flags_to_clear_on_insert = 0,
    .action_res_filter_bits_set = 0,
    .action_res_filter_bits_unset = 0,
    .action_res_bits_to_add = 0,
    .action_res_bits_to_clear = 0,
    /* default alignment -- same as sizeof(void *). */
    /* by default, don't allow more than 10 simultaneous
     * connections that match the same route.
     */
    /* after 4 derogatory events matching the same route,
     * put the route in penalty box status.
     */
    /* keep routes in penalty box status for 5 minutes.
     * denominated in seconds when passing to
     * wolfSentry_init().
     */
    /* 0 to disable -- autopurge doesn't usually make
     * much sense as a default config.
     */
    /* automatically clear
     * derogatory count for a route when a commendable
     * event matches the route.
     */

```

```

#else
    64,
    0,
    10,
    4,
    300,
    0,
    WOLFSENTRY_EVENTCONFIG_FLAG_COMMENDABLE_CLEARS_DEROGATORY,
    0,
    0,
    0,
    0,
    0,
    0
#endif
};

/* This routine is to be called once by the application before any direct calls
 * to lwIP -- i.e., before lwip_init() or tcpip_init().
 */
wolf_sentry_errcode_t activate_wolf_sentry_lwip(const char *json_config, int json_config_len)
{
    wolf_sentry_errcode_t ret;
    char err_buf[512]; /* buffer for detailed error messages from
                        * wolf_sentry_config_json_oneshot().
                        */

    /* Allocate a thread state struct on the stack. Note that the final
     * semicolon is supplied by the macro definition, so that in single-threaded
     * application builds this expands to nothing at all.
     */
    WOLFSENTRY_THREAD_HEADER_DECLS

    if (wolf_sentry_lwip_ctx != NULL) {
        printf("activate_wolf_sentry_lwip() called multiple times.\n");
        WOLFSENTRY_ERROR_RETURN(ALREADY);
    }

#ifdef WOLFSENTRY_ERROR_STRINGS
    /* Enable pretty-printing of the app source code filename for
     * WOLFSENTRY_ERROR_FMT/WOLFSENTRY_ERROR_FMT_ARGS().
     */
    ret = WOLFSENTRY_REGISTER_SOURCE();
    WOLFSENTRY_RERETURN_IF_ERROR(ret);

    /* Enable pretty-printing of an app-specific error code. */
    ret = WOLFSENTRY_REGISTER_ERROR(USER_APP_ERR0, "failure in application code");
    WOLFSENTRY_RERETURN_IF_ERROR(ret);
#endif

    /* Initialize the thread state struct -- this sets the thread ID. */
    WOLFSENTRY_THREAD_HEADER_INIT_CHECKED(WOLFSENTRY_THREAD_FLAG_NONE);

    /* Call the main wolfSentry initialization routine.
     *
     * WOLFSENTRY_CONTEXT_ARGS_OUT() is a macro that abstracts away
     * conditionally passing the thread struct pointer to APIs that need it. If
     * this is a single-threaded build (!defined(WOLFSENTRY_THREADSAFE)), then
     * the thread arg is omitted entirely.
     *
     * WOLFSENTRY_CONTEXT_ARGS_OUT_EX() is a variant that allows the caller to
     * supply the first arg explicitly, when "wolf_sentry" is not the correct arg
     * to pass. This is used here to pass a null pointer for the host platform
     * interface ("hpi").
     */
    ret = wolf_sentry_init(
        wolf_sentry_build_settings,
        WOLFSENTRY_CONTEXT_ARGS_OUT_EX(NULL /* hpi */),
        &demo_config,
        &wolf_sentry_lwip_ctx);
    if (ret < 0) {
        printf("wolf_sentry_init() failed: " WOLFSENTRY_ERROR_FMT "\n",
            WOLFSENTRY_ERROR_FMT_ARGS(ret));
        goto out;
    }

    /* Insert user-defined actions here, if any. */
    ret = wolf_sentry_action_insert(
        WOLFSENTRY_CONTEXT_ARGS_OUT_EX(wolf_sentry_lwip_ctx),
        "my-action",
        WOLFSENTRY_LENGTH_NULL_TERMINATED,
        WOLFSENTRY_ACTION_FLAG_NONE,
        my_action_handler,
        NULL,
        NULL);
    if (ret < 0) {
        printf("wolf_sentry_action_insert() failed: " WOLFSENTRY_ERROR_FMT "\n",

```

```

        WOLFSENTRY_ERROR_FMT_ARGS(ret));
    goto out;
}

if (json_config) {
    if (json_config_len < 0)
        json_config_len = (int)strlen(json_config);

    /* Do the initial load of the policy. */
    ret = wolfentry_config_json_oneshot(
        WOLFSENTRY_CONTEXT_ARGS_OUT_EX(wolfentry_lwip_ctx),
        (unsigned char *)json_config,
        (size_t)json_config_len,
        WOLFSENTRY_CONFIG_LOAD_FLAG_NONE,
        err_buf,
        sizeof err_buf);
    if (ret < 0) {
        printf("wolfentry_config_json_oneshot() failed: %s\n", err_buf);
        goto out;
    }
} /* else the application will need to set up the policy programmatically,
 * or itself call wolfentry_config_json_oneshot() or sibling APIs.
 */

/* Install lwIP callbacks. Once this call returns with success, all lwIP
 * traffic designated for filtration by the mask arguments shown below will
 * be subject to filtering (or other supplementary processing) according to
 * the policy loaded above.
 *
 * Note that if a given protocol is gated out of LWIP, its mask argument
 * must be passed as zero here, else the call will return
 * IMPLEMENTATION_MISSING error will occur.
 *
 * The callback installation also registers a cleanup routine that will be
 * called automatically by wolfentry_shutdown().
 */

#define LWIP_ALL_EVENTS (
    (1U < FILT_BINDING) |
    (1U < FILT DISSOCIATE) |
    (1U < FILT_LISTENING) |
    (1U < FILT_STOP_LISTENING) |
    (1U < FILT_CONNECTING) |
    (1U < FILT_ACCEPTING) |
    (1U < FILT_CLOSED) |
    (1U < FILT_REMOTE_RESET) |
    (1U < FILT_RECEIVING) |
    (1U < FILT_SENDING) |
    (1U < FILT_ADDR_UNREACHABLE) |
    (1U < FILT_PORT_UNREACHABLE) |
    (1U < FILT_INBOUND_ERR) |
    (1U < FILT_OUTBOUND_ERR))

ret = wolfentry_install_lwip_filter_callbacks(
    WOLFSENTRY_CONTEXT_ARGS_OUT_EX(wolfentry_lwip_ctx),

#if LWIP_ARP || LWIP_ETHERNET
    LWIP_ALL_EVENTS, /* ethernet_mask */
#else
    0,
#endif
#if LWIP_IPV4 || LWIP_IPV6
    LWIP_ALL_EVENTS, /* ip_mask */
#else
    0,
#endif
#if LWIP_ICMP || LWIP_ICMP6
    LWIP_ALL_EVENTS, /* icmp_mask */
#else
    0,
#endif
#if LWIP_TCP
    LWIP_ALL_EVENTS, /* tcp_mask */
#else
    0,
#endif
#if LWIP_UDP
    LWIP_ALL_EVENTS /* udp_mask */
#else
    0
#endif
);
if (ret < 0) {
    printf("wolfentry_install_lwip_filter_callbacks: "
        WOLFSENTRY_ERROR_FMT "\n", WOLFSENTRY_ERROR_FMT_ARGS(ret));
}

```

```
    }

out:
    if (ret < 0) {
        /* Clean up if initialization failed. */
        wolfsentry_errcode_t shutdown_ret =
            wolfsentry_shutdown(WOLFSENTRY_CONTEXT_ARGS_OUT_EX(&wolfsentry_lwip_ctx));
        if (shutdown_ret < 0)
            printf("wolfsentry_shutdown: "
                WOLFSENTRY_ERROR_FMT "\n", WOLFSENTRY_ERROR_FMT_ARGS(shutdown_ret));
    }

    WOLFSENTRY_THREAD_TAILER_CHECKED(WOLFSENTRY_THREAD_FLAG_NONE);

    WOLFSENTRY_ERROR_RERETURN(ret);
}

/* to be called once by the application after any final calls to lwIP. */
wolfsentry_errcode_t shutdown_wolfsentry_lwip(void)
{
    wolfsentry_errcode_t ret;
    if (wolfsentry_lwip_ctx == NULL) {
        printf("shutdown_wolfsentry_lwip() called before successful activation.\n");
        return -1;
    }

    /* after successful shutdown, wolfsentry_lwip_ctx will once again be a null
     * pointer as it was before init.
     */
    ret = wolfsentry_shutdown(WOLFSENTRY_CONTEXT_ARGS_OUT_EX4(&wolfsentry_lwip_ctx, NULL));
    if (ret < 0) {
        printf("wolfsentry_shutdown: "
            WOLFSENTRY_ERROR_FMT "\n", WOLFSENTRY_ERROR_FMT_ARGS(ret));
    }

    return ret;
}
```

## Chapter 3

# Configuring wolfSentry using a JSON document

Most of the capabilities of wolfSentry can be configured, and dynamically reconfigured, by supplying JSON documents to the library. To use this capability, add the following to wolfSentry initialization in the application:

```
#include <wolfsentry/wolfsentry_json.h>
```

After initialization and installation of application-supplied callbacks (if any), call one of the APIs to load the config:

- `wolfsentry_config_json_oneshot()`
- `wolfsentry_config_json_oneshot_ex()`, with an additional `json_config` arg for fine control of JSON parsing (see `struct JSON_CONFIG` in `wolfsentry/centijson_sax.h`)
- streaming API:
  - `wolfsentry_config_json_init()` or `wolfsentry_config_json_init_ex()`
  - `wolfsentry_config_json_feed()`
  - `wolfsentry_config_json_fini()`

See `wolfsentry/wolfsentry_json.h` for details on arguments.

## JSON Basics

wolfSentry configuration uses standard JSON syntax as defined in RFC 8259, as restricted by RFC 7493, with certain additional requirements. In particular, certain sections in the JSON document are restricted in their sequence of appearance.

- `"wolfsentry-config-version"` shall appear first, and each event definition shall appear before any definitions for events, routes, or default policies that refer to it through `"aux-parent-event"`, `"parent-event"`, or `"default-event"` clauses.
- Within event definitions, the `"label"`, `"priority"`, and `"config"` elements shall appear before any other elements.

These sequence constraints are necessary to allow for high efficiency SAX-style (sequential-incremental) loading of the configuration.

All wildcard flags are implicitly set on routes, and are cleared for fields with explicit assignments in the configuration. For example, if a route designates a particular "family", then `WOLFSENTRY_ROUTE_FLAG_SA_FAMILY↔_WILDCARD` will be implicitly cleared. Thus, wildcard flags need not be explicitly set or cleared in route definitions.

Note that certain element variants may be unavailable due to build settings:

- `address_family_name`: available if defined (`WOLFSENTRY_PROTOCOL_NAMES`)
- `route_protocol_name`: available if !defined (`WOLFSENTRY_NO_GETPROTOBY`)
- `address_port_name`: available if !defined (`WOLFSENTRY_NO_GETPROTOBY`)
- `json_value_clause`: available if defined (`WOLFSENTRY_HAVE_JSON_DOM`)

Caller-supplied event and action labels shall not begin with `WOLFSENTRY_BUILTIN_LABEL_PREFIX` (by default "%"), as these are reserved for built-ins.

"config-update" allows the default configuration to be updated. It is termed an "update" because wolfSentry is initially configured by the `config` argument to `wolfentry_init()` (which can be passed in `NULL`, signifying built-in defaults). Note that times (`wolfentry_eventconfig.penaltybox_duration` and `wolfentry_eventconfig.route_idle_time_for_purge`) shall be passed to `wolfentry_init()` denominated in seconds, notwithstanding the `wolfentry_time_t` type of the members.

## JSON load flags

The `flags` argument to `wolfentry_config_json_init()` and `wolfentry_config_json_one_shot()`, constructed by bitwise-or, changes the way the JSON is processed, as follows:

- `WOLFSENTRY_CONFIG_LOAD_FLAG_NONE` – Not a flag, but all-zeros, signifying default behavior: The wolfSentry core is locked, the current configuration is flushed, and the new configuration is loaded incrementally. Any error during load leaves wolfSentry in an undefined state that can be recovered with a subsequent flush and load that succeeds.
- `WOLFSENTRY_CONFIG_LOAD_FLAG_NO_FLUSH` – Inhibit initial flush of configuration, to allow incremental load. Error during load leaves wolfSentry in an undefined state that can only be recovered with a subsequent flush and load that succeeds, unless `WOLFSENTRY_CONFIG_LOAD_FLAG_DRY_RUN` or `WOLFSENTRY_CONFIG_LOAD_FLAG_LOAD_THEN_COMMIT` was also supplied.
- `WOLFSENTRY_CONFIG_LOAD_FLAG_DRY_RUN` – Load into a temporary configuration, and deallocate before return. Running configuration is unchanged.
- `WOLFSENTRY_CONFIG_LOAD_FLAG_LOAD_THEN_COMMIT` – Load into a newly allocated configuration, and install it only if load completes successfully. On error, running configuration is unchanged. On success, the old configuration is deallocated.
- `WOLFSENTRY_CONFIG_LOAD_FLAG_NO_ROUTES_OR_EVENTS` – Inhibit loading of "routes" and "events" sections in the supplied JSON.
- `WOLFSENTRY_CONFIG_LOAD_FLAG_FLUSH_ONLY_ROUTES` – At beginning of load process, retain all current configuration except for routes, which are flushed. This is convenient in combination with `wolfentry_route_table_dump_json_*` for save/restore of dynamically added routes.
- `WOLFSENTRY_CONFIG_LOAD_FLAG_JSON_DOM_DUPKEY_ABORT` – When processing user-defined JSON values, abort load on duplicate keys.

- `WOLFSENTRY_CONFIG_LOAD_FLAG_JSON_DOM_DUPKEY_USEFIRST` – When processing user-defined JSON values, for any given key in an object use the first occurrence encountered.
- `WOLFSENTRY_CONFIG_LOAD_FLAG_JSON_DOM_DUPKEY_USELAST` – When processing user-defined JSON values, for any given key in an object use the last occurrence encountered.
- `WOLFSENTRY_CONFIG_LOAD_FLAG_JSON_DOM_MAINTAIN_DICT_ORDER` – When processing user-defined JSON values, store sequence information so that subsequent calls to `wolfentry_kv_render_value()` or `json_dom_dump(..., JSON_DOM_DUMP_PREFER_DICT_ORDER)` render objects in their supplied sequence, rather than lexically sorted.

Note that `WOLFSENTRY_CONFIG_LOAD_FLAG_JSON_DOM_*` flags are allowed only if `WOLFSENTRY_HAVE_JSON_DOM` is defined in the build, as it is with default settings.

## Overview of JSON syntax

Below is a JSON “lint” pseudodocument demonstrating all available configuration nodes, with value specifiers that refer to the ABNF definitions below. The allowed values are as in the ABNF formal syntax later in this document.

```
{
  "wolfentry-config-version" : 1,
  "config-update" : {
    "max-connection-count" : uint32,
    "penalty-box-duration" : duration,
    "route-idle-time-for-purge" : duration,
    "derog-thresh-for-penalty-boxing" : uint16,
    "derog-thresh-ignore-commendable" : boolean,
    "commendable-clears-derogatory" : boolean,
    "route-flags-to-add-on-insert" : route_flag_list,
    "route-flags-to-clear-on-insert" : route_flag_list,
    "action-res-filter-bits-set" : action_res_flag_list,
    "action-res-filter-bits-unset" : action_res_flag_list,
    "action-res-bits-to-add" : action_res_flag_list,
    "action-res-bits-to-clear" : action_res_flag_list,
    "max-purgeable-routes" : uint32,
    "max-purgeable-idle-time" : duration
  },
  "events" : [
    { "label" : label,
      "priority" : uint16,
      "config" : {
        "max-connection-count" : uint32,
        "penalty-box-duration" : duration,
        "route-idle-time-for-purge" : duration,
        "derog-thresh-for-penalty-boxing" : uint16,
        "derog-thresh-ignore-commendable" : boolean,
        "commendable-clears-derogatory" : boolean,
        "route-flags-to-add-on-insert" : route_flag_list,
        "route-flags-to-clear-on-insert" : route_flag_list,
        "action-res-filter-bits-set" : action_res_flag_list,
        "action-res-filter-bits-unset" : action_res_flag_list,
        "action-res-bits-to-add" : action_res_flag_list,
        "action-res-bits-to-clear" : action_res_flag_list
      },
      "aux-parent-event" : label,
      "post-actions" : action_list,
      "insert-actions" : action_list,
      "match-actions" : action_list,
      "update-actions" : action_list,
      "delete-actions" : action_list,
      "decision-actions" : action_list
    }
  ],
  "default-policies" : {
    "default-policy" : default_policy_value,
    "default-event" : label
  },
  "routes" : [
    {
      "parent-event" : label,
      "af-wild" : boolean,
      "raddr-wild" : boolean,
      "rport-wild" : boolean,
      "laddr-wild" : boolean,

```

```

    "lport-wild" : boolean,
    "riface-wild" : boolean,
    "liface-wild" : boolean,
    "tcplike-port-numbers" : boolean,
    "direction-in" : boolean,
    "direction-out" : boolean,
    "penalty-boxed" : boolean,
    "green-listed" : boolean,
    "dont-count-hits" : boolean,
    "dont-count-current-connections" : boolean,
    "port-reset" : boolean,

    "family" : address_family,
    "protocol" : route_protocol,
    "remote" : {
        "interface" : uint8,
        "address" : route_address,
        "prefix-bits" : uint16,
        "bitmask" : route_address,
        "port" : endpoint_port
    },
    "local" : {
        "interface" : uint8,
        "address" : route_address,
        "prefix-bits" : uint16,
        "bitmask" : route_address,
        "port" : endpoint_port
    }
},
"user-values" : {
    label : null,
    label : true,
    label : false,
    label : number_sint64,
    label : number_float,
    label : string,
    label : { "uint" : number_uint64 },
    label : { "sint" : number_sint64 },
    label : { "float" : number_float },
    label : { "string" : string_value },
    label : { "base64" : base64_value },
    label : { "json" : json_value }
}
}

```

## Descriptions of elements

**wolfSentry-config-version** – Shall appear first, with the value 1.

**config-update** – Sets default and global parameters. The default parameters apply to routes that have no parent event, or a parent event with no config of its own.

- **max-connection-count** – If nonzero, the concurrent connection limit, beyond which additional connection requests are rejected.
- **penalty-box-duration** – If nonzero, the duration that a route stays in penalty box status before automatic release.
- **derog-thresh-for-penalty-boxing** – If nonzero, the threshold at which accumulated derogatory counts (from WOLFSENTRY\_ACTION\_RES\_DEROGATORY incidents) automatically penalty boxes a route.
- **derog-thresh-ignore-commendable** – If true, then counts from WOLFSENTRY\_ACTION\_RES←\_COMMENDABLE are not subtracted from the derogatory count when checking for automatic penalty boxing.
- **commendable-clears-derogatory** – If true, then each count from WOLFSENTRY\_ACTION\_RES←\_COMMENDABLE zeroes the derogatory count.
- **max-purgeable-routes** – Global limit on the number of ephemeral routes to allow in the route table, beyond which the least recently matched ephemeral route is forced out early. Not allowed in **config** clauses of events.



- **max-purgeable-idle-time** – Global absolute maximum idle time for ephemeral routes, controlling purges of stale (expired) ephemeral routes with nonzero `wolfssentry_route_metadata_exports.connection_co`. Default is no limit. Not allowed in **config** clauses of events.
- **route-idle-time-for-purge** – If nonzero, the time after the most recent dispatch match for a route to be garbage-collected. Useful primarily in **config** clauses of events (see **events** below).
- **route-flags-to-add-on-insert** – List of route flags to set on new routes upon insertion. Useful primarily in **config** clauses of events (see **events** below).
- **route-flags-to-clear-on-insert** – List of route flags to clear on new routes upon insertion. Useful primarily in **config** clauses of events (see **events** below).
- **action-res-filter-bits-set** – List of `action_res` flags that must be set at lookup time (dispatch) for referring routes to match. Useful primarily in **config** clauses of events (see **events** below).
- **action-res-filter-bits-unset** – List of `action_res` flags that must be clear at lookup time (dispatch) for referring routes to match. Useful primarily in **config** clauses of events (see **events** below).
- **action-res-bits-to-add** – List of `action_res` flags to be set upon match.
- **action-res-bits-to-clear** – List of `action_res` flags to be cleared upon match.

**events** – The list of events with their respective definitions. This section can appear more than once, but any given event definition shall precede any definitions that refer to it.

Each event is composed of the following elements, all of which are optional except for **label**. **label**, **priority**, and **config** shall appear before the other elements.

- **label** – The name by which the event is identified. See the definition of `label` in the ABNF grammar below for permissible values.
- **priority** – The priority of routes that have this event as their **parent-event** (see **routes** below). Lower number means higher priority.
- **config** – The configuration to associate with routes with this **parent-event**, as above for **config-update**.
- **aux-parent-event** – An event reference for use by action handlers, e.g. built-in "`%track-peer-v1`" creates routes with **aux-parent-event** as the new route's **parent-event**.
- **post-actions** – List of actions to take when this event is passed via **event\_label** to a dispatch routine such as `wolfssentry_route_event_dispatch()`.
- **insert-actions** – List of actions to take when a route is inserted with this event as **parent-event**.
- **match-actions** – List of actions to take when a route is matched by a dispatch routine, and the route has this event as its **parent-event**.
- **update-actions** – List of actions to take when a route has a status update, such as a change of penalty box status, and has this event as its **parent-event**.
- **delete-actions** – List of actions to take when a route is deleted, and has this event as its **parent-event**.
- **decision-actions** – List of actions to take when dispatch final decision (final value of **action\_↔results**) is determined, and the matched route has this event as its **parent-event**.

**default-policies** – The global fallback default policies for dispatch routines such as `wolfssentry_route_event_dispatcher`.

- **default-policy** – A simple **action\_result** flag to set by default, either **accept**, **reject**, or **reset**, the latter of which causes generation of TCP reset and ICMP unreachable reply packets where relevant.

- **default-event** – An event to use when a dispatch routine is called with a null **event\_label**.

**routes** – The list of routes with their respective definitions. This section can appear more than once.

Each route is composed of the following elements, all of which are optional.

- **parent-event** – The event whose attributes determine the dynamics of the route.
- **family** – The address family to match. See `address_family` definition in the ABNF grammar below for permissible values.
- **protocol** – The protocol to match. See `route_protocol` definition in the ABNF grammar below for permissible values.
- **remote** – The attributes to match for the remote endpoint of the traffic.
  - **interface** – Network interface ID, as an arbitrary integer chosen and used consistently by the caller or IP stack integration.
  - **address** – The network address, in idiomatic form. IPv4, IPv6, and MAC addresses shall enumerate all octets. See `route_address` definition in the ABNF grammar below for permissible values.
  - **prefix-bits** – The number of bits in the **address** that traffic must match (mutually exclusive with **bitmask**).
  - **bitmask** – A bitmask to be applied to the traffic address before matching with the route **address** (mutually exclusive with **prefix-bits**).
  - **port** – The port number that traffic must match.
- **local** – The attributes to match for the local endpoint of the traffic. The same nodes are available as for **remote**.
- **direction-in** – If true, match inbound traffic.
- **direction-out** – If true, match outbound traffic.
- **penalty-boxed** – If true, traffic matching the route is penalty boxed (rejected or reset).
- **green-listed** – If true, traffic matching the route is accepted.
- **dont-count-hits** – If true, inhibit statistical bookkeeping (no effect on dynamics).
- **dont-count-current-connections** – If true, inhibit tracking of concurrent connections, so that **max-connection-count** has no effect on traffic matching this route.
- **port-reset** – If true, set the `WOLFSENTRY_ACTION_RES_PORT_RESET` flag in the **action\_results** when this route is matched, causing TCP reset or ICMP unreachable reply packet to be generated if IP stack integration is activated (e.g. `wolfssentry_install_lwip_filter_callbacks()`).

**user-values** – One or more sections of fully user-defined data available to application code for any use. Each key is a label as defined in the ABNF grammar below. The value can be any of:

- **null**
- **true**
- **false**
- an integral number, implicitly a signed 64 bit integer
- a floating point number, as defined in the ABNF grammar below for `number_float`
- a quoted string allowing standard JSON escapes

- any of several explicitly typed constructs, with values as defined in the ABNF grammar below.

```

- { "uint" :  number_uint64 }
- { "sint" :  number_sint64 }
- { "float" :  number_float }
- { "string" :  string_value }
- { "base64" :  base64_value }
- { "json" :  json_value }

```

## Formal ABNF grammar

Below is the formal ABNF definition of the configuration syntax and permitted values.

This definition uses ABNF syntax as prescribed in RFC 5234 and 7405, except:

- Whitespace is ignored, as provided in RFC 8259.
- a – operator is added, accepting a quoted literal string or a group of literal characters, to provide for omitted character(s) in the target text (here, trailing comma separators) by performing all notional matching operations of the containing group up to that point with the target text notionally extended with the argument to the operator.

The length limits used in the definition assume the default values in [wolfsentry\\_settings.h](#), 32 octets for labels (WOLFSENTRY\_MAX\_LABEL\_BYTES), and 16384 octets for user-defined values (WOLFSENTRY\_KV\_MAX\_VALUE\_BYTES). These values can be overridden at build time with user-supplied values.

```

"{"
  DQUOTE %s"wolfsentry-config-version" DQUOTE ":" uint32
  [ "," DQUOTE %s"config-update" DQUOTE ":" top_config_list "," ]
  *( "," DQUOTE %s"events" ":" "["
    event *( "," event)
  "]" )
  [ "," DQUOTE %s"default-policies" DQUOTE ":" "{"
    default_policy_item *( "," default_policy_item)
  "]" ]
  *( "," DQUOTE %s"routes" DQUOTE ":" "["
    route *( "," route)
  "]" )
  *( "," DQUOTE %s"user-values" DQUOTE ":" "{"
    user_item *( "," user_item)
  "]" )
"}"

event = "{" label_clause
  [ "," priority_clause ]
  [ "," event_config_clause ]
  [ "," aux_parent_event_clause ]
  *( "," action_list_clause ) "}"

default_policy_item =
  (DQUOTE %s"default-policy" DQUOTE ":" default_policy_value) /
  (DQUOTE %s"default-event" DQUOTE ":" label)

default_policy_value = (%s"accept" / %s"reject" / %s"reset")

label_clause = DQUOTE %s"label" DQUOTE ":" label

priority_clause = DQUOTE %s"priority" DQUOTE ":" uint16

event_config_clause = DQUOTE %s"config" DQUOTE ":" event_config_list

aux_parent_event_clause = DQUOTE %s"aux-parent-event" DQUOTE ":" label

action_list_clause = DQUOTE (%s"post-actions" / %s"insert-actions" / %s"match-actions"
  / %s"update-actions" / %s"delete-actions" / %s"decision-actions") DQUOTE

```

```

    ":" action_list

action_list = "[" label *("," label) "]"

event_config_list = "[" event_config_item *("," event_config_item) "]"

top_config_list = "[" top_config_item *("," top_config_item) "]"

top_config_item = event_config_item / max_purgeable_routes_clause / max_purgeable_idle_time_clause

event_config_item =
    (DQUOTE %s"max-connection-count" DQUOTE ":" uint32) /
    (DQUOTE %s"penalty-box-duration" DQUOTE ":" duration) /
    (DQUOTE %s"route-idle-time-for-purge" DQUOTE ":" duration) /
    (DQUOTE %s"derog-thresh-for-penalty-boxing" DQUOTE ":" uint16 /
    (DQUOTE %s"derog-thresh-ignore-commendable" DQUOTE ":" boolean /
    (DQUOTE %s"commendable-clears-derogatory" DQUOTE ":" boolean /
    (DQUOTE (%s"route-flags-to-add-on-insert" / %s"route-flags-to-clear-on-insert") DQUOTE ":"
        route_flag_list) /
    (DQUOTE (%s"action-res-filter-bits-set" / %s"action-res-filter-bits-unset" / %s"action-res-bits-to-add" /
        %s"action-res-bits-to-clear") DQUOTE ":" action_res_flag_list)

duration = number_sint64 / (DQUOTE number_sint64 [ %s"d" / %s"h" / %s"m" / %s"s" ] DQUOTE)

max_purgeable_routes_clause = DQUOTE %s"max-purgeable-routes" DQUOTE ":" uint32

max_purgeable_idle_time_clause = DQUOTE %s"max-purgeable-idle-time" DQUOTE ":" duration

route_flag_list = "[" route_flag *("," route_flag) "]"

action_res_flag_list = "[" action_res_flag *("," action_res_flag) "]"

route = "{"
    [ parent_event_clause "," ]
    * (route_flag_clause ",")
    [ family_clause ","
        [ route_protocol_clause "," ]
    ]
    [ route_remote_endpoint_clause "," ]
    [ route_local_endpoint_clause "," ]
    - ","
"}"

parent_event_clause = DQUOTE %s"parent-event" DQUOTE ":" label
route_flag_clause = route_flag ":" boolean
family_clause = DQUOTE %s"family" DQUOTE ":" address_family
route_protocol_clause = DQUOTE %s"protocol" DQUOTE ":" route_protocol

route_remote_endpoint_clause = DQUOTE %s"remote" DQUOTE ":" route_endpoint
route_local_endpoint_clause = DQUOTE %s"local" DQUOTE ":" route_endpoint

route_endpoint = "{"
    [ route_interface_clause "," ]
    [ route_address_clause ","
        [ (route_address_prefix_bits_clause / route_address_bitmask_clause) "," ]
    ]
    [ route_port_clause "," ]
    - ","
"}"

route_interface_clause = DQUOTE %s"interface" DQUOTE ":" uint8

route_address_clause = DQUOTE %s"address" DQUOTE ":" route_address

route_address_bitmask_clause = DQUOTE %s"bitmask" DQUOTE ":" route_address

route_address = DQUOTE (route_address_ipv4 / route_address_ipv6 / route_address_mac / route_address_user)
    DQUOTE

route_address_ipv4 = uint8 3*3(" uint8)

route_address_ipv6 = < IPv6address from RFC 5954 section 4.1 >

route_address_mac = 1*2HEXDIG ( 5*5(":" 1*2HEXDIG) / 7*7(":" 1*2HEXDIG) )

route_address_user = < an address in a form recognized by a parser
    installed with `wolfssentry_addr_family_handler_install()` `
    >

address_family = uint16 / address_family_name

address_family_name = DQUOTE ( "inet" / "inet6" / "link" / < a value recognized by

```

---

```

        wolfentry_addr_family_pton() > ) DQUOTE

route_address_prefix_bits_clause = DQUOTE %s"prefix-bits" DQUOTE ":" uint16

route_protocol = uint16 / route_protocol_name

route_protocol_name = DQUOTE < a value recognized by getprotobyname_r(), requiring address family inet or
    inet6 >

route_port_clause = DQUOTE %s"port" DQUOTE ":" endpoint_port

endpoint_port = uint16 / endpoint_port_name

endpoint_port_name = DQUOTE < a value recognized by getservbyname_r() for the previously designated protocol
    > DQUOTE

route_flag = DQUOTE (
    %s"af-wild" /
    %s"raddr-wild" /
    %s"rport-wild" /
    %s"laddr-wild" /
    %s"lport-wild" /
    %s"riface-wild" /
    %s"liface-wild" /
    %s"tcplike-port-numbers" /
    %s"direction-in" /
    %s"direction-out" /
    %s"penalty-boxed" /
    %s"green-listed" /
    %s"dont-count-hits" /
    %s"dont-count-current-connections" /
    %s"port-reset"
) DQUOTE

action_res_flag = DQUOTE (
    %s"none" /
    %s"accept" /
    %s"reject" /
    %s"connect" /
    %s"disconnect" /
    %s"derogatory" /
    %s"commendable" /
    %s"stop" /
    %s"deallocated" /
    %s"inserted" /
    %s"error" /
    %s"fallthrough" /
    %s"update" /
    %s"port-reset" /
    %s"sending" /
    %s"received" /
    %s"binding" /
    %s"listening" /
    %s"stopped-listening" /
    %s"connecting-out" /
    %s"closed" /
    %s"unreachable" /
    %s"sock-error" /
    %s"user+0" /
    %s"user+1" /
    %s"user+2" /
    %s"user+3" /
    %s"user+4" /
    %s"user+5" /
    %s"user+6" /
    %s"user+7"
) DQUOTE

user_item = label ":" ( null / true / false / number_sint64_decimal / number_float / string /
    strongly_typed_user_item )

strongly_typed_user_item =
( "{" DQUOTE %s"uint" DQUOTE ":" number_uint64 "}" ) /
( "{" DQUOTE %s"sint" DQUOTE ":" number_sint64 "}" ) /
( "{" DQUOTE %s"float" DQUOTE ":" number_float "}" ) /
( "{" DQUOTE %s"string" DQUOTE ":" string_value "}" ) /
( "{" DQUOTE %s"base64" DQUOTE ":" base64_value "}" ) /

```

```

    json_value_clause

json_value_clause = "{" DQUOTE %s"json" DQUOTE ":" json_value "}"

null = %s"null"

true = %s"true"

false = %s"false"

boolean = true / false

number_uint64 = < decimal number in the range 0...18446744073709551615 > /
    ( DQUOTE < hexadecimal number in the range 0x0...0xffffffffffffffff > DQUOTE ) /
    ( DQUOTE < octal number in the range 00...0177777777777777777777 > DQUOTE )

number_sint64_decimal = < decimal number in the range -9223372036854775808...9223372036854775807 >

number_sint64 = number_sint64_decimal /
    ( DQUOTE < hexadecimal number in the range -0x8000000000000000...0x7fffffffffffffff > DQUOTE
    ) /
    ( DQUOTE < octal number in the range -0100000000000000000000...0777777777777777777777 >
    DQUOTE )

number_float = < floating point value in a form and range recognized by the linked strtod() implementation >

string_value = DQUOTE < any RFC 8259 JSON-valid string that decodes to at most 16384 octets > DQUOTE

base64_value = DQUOTE < any valid RFC 4648 base64 encoding that decodes to at most 16384 octets > DQUOTE

json_value = < any valid, complete and balanced RFC 8259 JSON expression, with
    keys limited to WOLFSENTRY_MAX_LABEL_BYTES (default 32 bytes),
    overall input length limited to WOLFSENTRY_JSON_VALUE_MAX_BYTES
    if set (default unset), and overall depth limited to
    WOLFSENTRY_MAX_JSON_NESTING (default 16) including the 4 parent
    levels
    >

label = DQUOTE < any RFC 8259 JSON-valid string that decodes to at at least 1 and at most 32 octets > DQUOTE

uint32 = < decimal integral number in the range 0...4294967295 >

uint16 = < decimal integral number in the range 0...65535 >

uint8 = < decimal integral number in the range 0...255 >

```

## Chapter 4

# wolfSentry Release History and Change Log

### wolfSentry Release 1.6.1 (November 18, 2023)

Release 1.6.1 of the wolfSentry embedded firewall/IDPS has enhancements, additions, and improvements including:

#### New Features

Dynamic rules with nonzero connection counts are now subject to deferred expiration, to assure traffic over established connections is allowed until all connections are closed, even with pauses in traffic flow exceeding the max idle time configured for the rule.

When a rule with a nonzero connection count is deleted, actual deletion is deferred until all connections are closed or the "max-purgeable-idle-time" is reached (see below). New success code `WOLFSENTRY_SUCCESS↵_ID_DEFERRED` is returned in that case. If an identical rule is inserted before the deferred deletion, the existing rule is unmarked for deletion and the insertion call returns another new success code, `WOLFSENTRY_SUCCESS↵_ID_ALREADY_OK`.

A "max-purgeable-idle-time" JSON configuration option has been added, forcing expiration and purge of a zombie dynamic rule even if its current connection count is nonzero. New related APIs are also added: `wolfentry_route_table_max_purgeable_idle_time_get()`, `wolfentry_route_table_max_purgeabl` and `wolfentry_route_purge_time_set()`.

#### Noteworthy Changes and Additions

A new `FILT_CLOSE_WAIT` event type is added to the lwIP integration patch, and a corresponding `WOLFSENTRY_ACTION_RES_CLOSE_WAIT` result bit is added. Appropriate callbacks are added to lwIP `tcp_process()` and `tcp_receive()`, and the lwIP glue logic now handles mapping from `FILT_CLOSE↵_WAIT` to `WOLFSENTRY_ACTION_RES_CLOSE_WAIT`.

The lwIP patch has been rebased on upstream 5e3268cf3e (Oct 14 2023), while maintaining compatibility with lwIP 2.1.3-RELEASE.

## Bug Fixes, Cleanups, and Debugging Aids

The lwIP patch includes several fixes:

- In `tcp_process()`, when handling passive close and entering `CLOSE_WAIT`, don't `tcp_filter_↵ dispatch_incoming(FILT_CLOSED, ...)` – this happens later, at deallocation.
- Fix TCP `FILT_CLOSED` callbacks to assure accurate interface ID and `local_port` are passed.

The route/rule system includes several fixes:

- Add error checking to `meta.connection_count` decrement in `wolfentry_route_event_↵ dispatch_0()`, so that rule churn can never result in count underflow.
- Mask out internal flags (via new macro `WOLFSENTRY_ROUTE_INTERNAL_FLAGS`) from `route_↵ exports->flags` in `wolfentry_route_init_by_exports()`.
- In `wolfentry_route_init_by_exports()`, fix pointer math in `memset()` argument to correctly treat `route_exports->private_data_size` as a byte count.
- In `wolfentry_route_new_by_exports()`, fix check on `route_exports->private_↵ data_size` to properly reflect `config->route_private_data_padding`.
- Add missing implementation of `wolfentry_route_insert_by_exports()`.
- In `wolfentry_route_clone()`, fix allocation to use `WOLFSENTRY_MEMALIGN_1()` when `.route_private_data_alignment` is nonzero.
- In `wolfentry_route_event_dispatch_0()`, don't increment/decrement counts when `WOLFSENTRY_↵ _ACTION_RES_FALLTHROUGH`.

In `src/lwip/packet_filter_glue.c`, add `action_results` and `local.sa.interface` to `WOLFSENTRY_DEBUG_LWIP` messages, and add missing gates for `LWIP_IPV6` in `WOLFSENTRY_DEBUG_↵ _LWIP` paths.

In `tcp_filter_with_wolfentry()`, don't set `WOLFSENTRY_ROUTE_FLAG_DIRECTION_IN` for `FILT_REMOTE_RESET`, and fix typo "&event" in call to `wolfentry_route_event_dispatch_with_initiated_result`

Remove several incorrect calls to `wolfentry_table_ent_delete_by_id_1()` immediately following failed calls to `wolfentry_table_ent_insert()` – the former is implicit to the latter.

## Self-Test Enhancements

Add to `test_json()` a workout of `connection_count` and deferred deletion dynamics.

`Makefile.analyzers`: add `sanitize-all-NO_POSIX_MEMALIGN-gcc`; tweak `notification-demo-build-test` to explicitly use the master branch of `wolfssl`.

`Makefile,Makefile.analyzers`: tweaks for MacOS X compatibility.



## wolfSentry Release 1.6.0 (October 24, 2023)

Release 1.6.0 of the wolfSentry embedded firewall/IDPS has enhancements, additions, and improvements including:

### New Features

This release adds native support for the CAN bus address family, and for bitmask-based address matching. CAN addresses and bitmasks are now handled in configuration JSON, as numbers in decimal, octal, or hexadecimal, supporting both 11 bit (part A) and 29 bit (part B) identifiers.

### Noteworthy Changes and Additions

`wolfentry/wolfentry.h`:

- Add `WOLFSENTRY_ROUTE_FLAG_REMOTE_ADDR_BITMASK` and `WOLFSENTRY_ROUTE_FLAG_LOCAL_ADDR_BITMASK` to `wolfentry_route_flags_t`.
- Add `WOLFSENTRY_ACTION_RES_USER0-WOLFSENTRY_ACTION_RES_USER6` to `wolfentry_action_res_t` enum, add `WOLFSENTRY_ACTION_RES_USER7` macro, and refactor `WOLFSENTRY_ACTION_RES_USER_BASE` as a macro aliased to `WOLFSENTRY_ACTION_RES_USER0`.
- Remove `!WOLFSENTRY_NO_STDIO` gate around `wolfentry_kv_render_value()`.

`wolfentry/wolfentry_settings.h`:

- Rename `WOLFSENTRY_NO_STDIO` to `WOLFSENTRY_NO_STDIO_STREAMS`.
- Rename `WOLFSENTRY_HAVE_NONGNU_ATOMICS` to `WOLFSENTRY_NO_GNU_ATOMICS`.
- Added handling for `WOLFSENTRY_NO_SEM_BUILTIN`, `WOLFSENTRY_NO_ADDR_BITMASK_MATCHING`, and `WOLFSENTRY_NO_IPV6`.
- Gate inclusion of `stdio.h` on `!WOLFSENTRY_NO_STDIO_H`, formerly `!WOLFSENTRY_NO_STDIO`.
- Added `WOLFSENTRY_CONFIG_FLAG_ADDR_BITMASKS`, and rename `WOLFSENTRY_CONFIG_FLAG_NO_STDIO` to `WOLFSENTRY_CONFIG_FLAG_NO_STDIO_STREAMS`.

`src/addr_families.c` and `wolfentry/wolfentry_af.h`: Split `WOLFSENTRY_AF_LINK` into `WOLFSENTRY_AF_LINK48` and `WOLFSENTRY_AF_LINK64`, with `WOLFSENTRY_AF_LINK` aliased to `WOLFSENTRY_AF_LINK48`.

`src/kv.c`: remove `!WOLFSENTRY_NO_STDIO` gate around `wolfentry_kv_render_value()`.

`src/json/load_config.c`: In `convert_sockaddr_address()`, add separate handling for `WOLFSENTRY_AF_LINK48` and `WOLFSENTRY_AF_LINK64`.

Makefile:

- Refactor `NO_STDIO`, `NO_JSON`, `NO_JSON_DOM`, `SINGLETHREADED`, `STATIC`, and `STRIPPED` to pivot on definedness, not oneness.
- Add feature flags `NO_ADDR_BITMASK_MATCHING` and `NO_IPV6`.
- Rename feature flag `NO_STDIO` to `NO_STDIO_STREAMS`.

## Performance Improvements

src/routes.c: Added AF-mismatch optimization to `wolfentry_route_lookup_0()`.

## Documentation

Add inline documentation for `WOLFENTRY_NO_GETPROTOBY`, `WOLFENTRY_SEMAPHORE_INCLUDE`, `WOLFENTRY_THREAD_INCLUDE`, `WOLFENTRY_THREAD_ID_T`, and `WOLFENTRY_THREAD_GET_ID_HANDLER`.

doc/json\_configuration.md: add documentation and ABNF grammar for "bitmask" node in route endpoints.

## Bug Fixes and Cleanups

Fixes for user settings file handling:

- Don't `#include <wolfentry/wolfentry_options.h>` if `defined(WOLFENTRY_USER_SETTINGS_FILE)`.
- Generate and install `wolfentry/wolfentry_options.h` only if `USER_SETTINGS_FILE` is undefined, and if `USER_SETTINGS_FILE` is defined, depend on it where previously the dependency was unconditionally on `wolfentry/wolfentry_options.h`.
- If `USER_SETTINGS_FILE` is set search it to derive JSON build settings.

Makefile: Don't add `-pthread` to `LDFLAGS` if `RUNTIME` is `FreeRTOS-lwIP`.

`wolfentry/wolfentry_settings.h`:

- Eliminate inclusion of `errno.h` – now included only in source files that need it.
- Fix handling for `WOLFENTRY_SEMAPHORE_INCLUDE` to give it effect in all code paths (previously ignored in POSIX and FreeRTOS paths).

src/routes.c:

- in `wolfentry_route_event_dispatch_0()`, move update of `meta.purge_after` inside the mutex.
- in `wolfentry_route_get_metadata()`, conditionalize use of 64 bit `WOLFENTRY_ATOMIC_LOAD()` on pointer size, to avoid dependency on library implementation of `__atomic_load_8()`.

src/wolfentry\_internal.c: fix use-after-free bug in `wolfentry_table_free_ents()`, using new `table->coupled_ent_fn` mechanism.

src/json/load\_config.c: In `convert_sockaddr_address()`, handle `sa->addr_len` consistently – don't overwrite nonzero values.

src/json/{centijson\_dom.c, centijson\_sax.c, centijson\_value.c}: eliminate direct calls to heap allocator functions in `WOLFENTRY` code paths, i.e. use only `wolfentry_allocator`.

src/json/centijson\_value.c: fix uninited-variable defect on `cmp` in `json_value_dict_get_or_add_()`.

## Self-Test Enhancements

Makefile.analyzers new and enhanced test targets:

- `user-settings-build-test`: construct a user settings file, then build and self-test using it.
- `library-dependency-singlethreaded-build-test` and `library-dependency-multithreaded-build-test`: comprehensive check for unexpected unresolved symbols in the library.
- `no-addr-bitmask-matching-test`, `no-ipv6-test`, `linux-lwip-test-no-ipv6`: tests for new feature gates.
- `freertos-arm32-build-test`: newly refactored to perform a final link of `test_lwip` kernel using lwIP and FreeRTOS kernel files and newlib-nano, followed by a check on the size of the kernel.

Added `wolfSentry/wolfssl_test.h`, containing self-test and example logic relocated from `wolfssl/wolfssl/test.h` verbatim.

`tests/test-config*.json`: added several bitmask-matched routes, added several diagnostic events ("set-user-0" through "set-user-4"), and added no-bitmasks and no-ipv6 variants. Also removed AF-wildcard route from `tests/test-config-numeric.json` to increase test coverage.

`tests/unittests.c`:

- Additional tweaks for portability to 32 bit FreeRTOS
- Add FreeRTOS-specific implementations of `test_lwip()` and `main()`.
- In `test_json()`, add `wolfSentry_addr_family_handler_install(..., "my_AF2", ...)`.
- In `test_json()`, add bitmask tests.
- Added stub implementations for various FreeRTOS/newlib dependencies to support final link in `freertos-arm32-build-test` target.

## wolfSentry Release 1.5.0 (September 13, 2023)

Release 1.5.0 of the wolfSentry embedded firewall/IDPS has enhancements, additions, and improvements including:

## Noteworthy Changes and Additions

In JSON configuration, recognize "events" as equivalent to legacy "events-insert", and "routes" as equivalent to legacy "static-routes-insert". Legacy keys will continue to be recognized.

In the Makefile, FREERTOS\_TOP and LWIP\_TOP now refer to actual distribution top – previously, FREERTOS\_TOP expected a path to the FreeRTOS/Source subdirectory, and LWIP\_TOP expected a path to the src subdirectory.

Added public functions `wolfentry_route_default_policy_set()` and `wolfentry_route_default_policy_get()` to implicitly accessing the main route table.

Added public functions `wolfentry_get_object_type()` and `wolfentry_object_release()`, companions to existing `wolfentry_object_checkout()` and `wolfentry_get_object_id()`.

Added `wolfentry_lock_size()` to facilitate caller-allocated `wolfentry_rwlock`s.

WOLFENTRY\_CONTEXT\_ARGS\_OUT is now the first argument to utility routines `wolfentry_object_checkout()`, `wolfentry_defaultconfig_get()`, and `wolfentry_defaultconfig_update()`, rather than a bare `wolfentry` context pointer.

`ports/Linux-lwIP/include/lwipopts.h`: Add core locking code.

Removed unneeded routine `wolfentry_config_json_set_default_config()`.

Improved `wolfentry_kv_render_value()` to use `json_dump_string()` for `_KV_STRING` rendering, if available, to get JSON-style escapes in output.

Implemented support for user-supplied semaphore callbacks.

## Performance Improvements

The critical paths for traffic evaluation have been streamlined by eliminating ephemeral heap allocations, eliminating redundant internal initializations, adding early shortcircuit paths to avoid frivolous processing, and eliminating redundant time lookups and context locking. This results in a 33%-49% reduction in cycles per `wolfentry_route_event_dispatch()` on `benchmark-test`, and a 29%-61% reduction on `benchmark-singlethreaded-test`, at under 100 cycles for a simple default-policy scenario on a 64 bit target.

## Documentation

Added `doc/freertos-lwip-app.md`, "Building and Initializing wolfSentry for an application on FreeRTOS/lwIP".

Added `doc/json_configuration.md`, "Configuring wolfSentry using a JSON document".

Doxygen-based annotations are now included in all wolfSentry header files, covering all functions, macros, types, enums, and structures.

The PDF version of the reference manual is now included in the repository and releases at `doc/wolfSentry_refman.pdf`.

The Makefile now has targets `doc-html`, `doc-pdf`, and related targets for generating and cleaning the documentation artifacts.

## Bug Fixes and Cleanups

lwip/LWIP\_PACKET\_FILTER\_API.patch has fixes for -Wconversion and -Wshadow warnings.

src/json/centijson\_sax.c: Fix bug in json\_dump\_double() such that floating point numbers were rendered with an extra decimal place.

In wolfentry\_config\_json\_init\_ex(), error if json\_config.max\_key\_len is greater than WOLFSENTRY\_MAX\_LABEL\_BYTES (required for memory safety).

In wolfentry\_config\_json\_init\_ex(), call wolfentry\_defaultconfig\_get() to initialize jps->default\_config with settings previously passed to wolfentry\_init().

src/kv.c: Fixed \_KV\_STRING and \_KV\_BYTES cases in wolfentry\_kv\_value\_eq\_1() (inadvertently inverted memcmp()), and fixed \_KV\_NONE case to return true.

Fixed wolfentry\_kv\_render\_value() for \_KV\_JSON case to pass JSON\_DOM\_DUMP\_PREFERDICTORDER to json\_dom\_dump().

src/lwip/packet\_filter\_glue.c: In wolfentry\_install\_lwip\_filter\_callbacks(), if error encountered, disable all callbacks to assure known state on return.

In wolfentry\_init\_ex(), correctly convert user-supplied route\_idle\_time\_for\_purge from seconds to wolfentry\_time\_t.

Pass route\_table->default\_event to wolfentry\_route\_event\_dispatch\_0() if caller-supplied trigger event is null (changed in wolfentry\_route\_event\_dispatch\_1(), wolfentry\_route\_event\_dispatch\_by\_id\_1(), and wolfentry\_route\_event\_dispatch\_by\_route\_1()).

In wolfentry\_route\_lookup\_0(), fixed scoping of WOLFSENTRY\_ACTION\_RES\_EXCLUDE\_REJECT\_ROUTES to only check WOLFSENTRY\_ROUTE\_FLAG\_PENALTYBOXED, not WOLFSENTRY\_ROUTE\_FLAG\_PORT\_RESET.

In wolfentry\_route\_delete\_0(), properly set WOLFSENTRY\_ROUTE\_FLAG\_PENDING\_DELETE.

In wolfentry\_route\_event\_dispatch\_0() and wolfentry\_route\_event\_dispatch\_1(), properly set WOLFSENTRY\_ACTION\_RES\_ERROR at end if ret < 0.

In wolfentry\_route\_event\_dispatch\_1(), properly set WOLFSENTRY\_ACTION\_RES\_FALLTHROUGH when route\_table->default\_policy is used.

Added missing action\_results reset to wolfentry\_route\_delete\_for\_filter().

In wolfentry\_lock\_init(), properly forbid all inapplicable flags.

Fixed wolfentry\_eventconfig\_update\_1() to copy over all relevant elements.

Fixed and updated expression for WOLFSENTRY\_USER\_DEFINED\_TYPES.

## Self-Test Enhancements

Makefile.analyzers: Added targets `test_lwip`, `minimal-threaded-build-test`, `pahole-test`, `route-holes-test`, `benchmark-test`, `benchmark-singlethreaded-test`, and `doc-check`.

Implemented tripwires in `benchmark-test` and `benchmark-singlethreaded-test` for unexpectedly high cycles/call.

Enlarged coverage of target `notification-demo-build-test` to run the applications and check for expected and unexpected output.

tests/unittests.c:

- Add `test_lwip()` with associated helper functions;
- Add `WOLFSENTRY_UNITTEST_BENCHMARKS` sections in `test_static_routes()` and `test_json()`;
- Add to `test_init()` tests of `wolfentry_errcode_source_string()` and `wolfentry_errcode_error_s`
- Add to `test_static_routes()` tests of `wolfentry_route_default_policy_set()` and `wolfentry_get_object_type()`, `wolfentry_object_checkout()`, and `wolfentry_object_relea`

## wolfSentry Release 1.4.1 (July 20, 2023)

Release 1.4.1 of the wolfSentry embedded firewall/IDPS has bug fixes including:

### Bug Fixes and Cleanups

Add inline implementations of `WOLFSENTRY_ERROR_DECODE_{ERROR_CODE, SOURCE_ID, LINE_NUMBER}()` for portable protection from multiple argument evaluation, and refactor `WOLFSENTRY_ERROR_ENCODE()` and `WOLFSENTRY_SUCCESS_ENCODE()` to avoid unnecessary dependence on non-portable (gnu-specific) construct.

Use a local stack variable in `WOLFSENTRY_ERROR_ENCODE_1()` to assure a single evaluation of the argument.

Add `-Wno-inline` to `CALL_TRACE_CFLAGS`.

Correct the release date of 1.4.0 in `ChangeLog`.

## Self-Test Enhancements

Add `CALL_TRACE-test` to `Makefile.analyzers`, and include it in the `check-extra` dep list.

## wolfSentry Release 1.4.0 (July 19, 2023)

Release 1.4.0 of the wolfSentry embedded firewall/IDPS has bug fixes and improvements including:

### New Features

Routes can now be configured to match traffic with designated `action_results` bit constraints, and can be configured to update `action_results` bits, by inserting the route with a parent event that has the desired configuration. Parent events can now also be configured to add or clear route flags for all routes inserted with that parent event.

Added new `aux_event` mechanism to facilitate distinct configurations for a static generator route and the narrower ephemeral routes dynamically created when it is matched.

Added a new built-in action, "`%track-peer-v1`", that can be used in combination with the above new facilities to dynamically spawn ephemeral routes, allowing for automatic pinhole routes, automatic adversary tracking, and easy implementation of dynamic blocks and/or notifications for port scanning adversaries.

### Noteworthy Changes and Additions

Added new APIs `wolfentry_event_set_aux_event()` and `wolfentry_event_get_aux_event()`.

Added flag filters and controls to struct `wolfentry_eventconfig`, and added corresponding clauses to JSON "`config`" sections:

- `.action_res_filter_bits_set`, "`action-res-filter-bits-set`"
- `.action_res_filter_bits_unset`, "`action-res-filter-bits-unset`"
- `.action_res_bits_to_add`, "`action-res-bits-to-add`"
- `.action_res_bits_to_clear`, "`action-res-bits-to-clear`"
- `.route_flags_to_add_on_insert`, "`route-flags-to-add-on-insert`"
- `.route_flags_to_clear_on_insert`, "`route-flags-to-clear-on-insert`"

Added new `WOLFSENTRY_ACTION_RES_*` (action result) flags to support filtering matches by generic traffic type:

- `WOLFSENTRY_ACTION_RES_SENDING`
- `WOLFSENTRY_ACTION_RES_RECEIVED`
- `WOLFSENTRY_ACTION_RES_BINDING`
- `WOLFSENTRY_ACTION_RES_LISTENING`
- `WOLFSENTRY_ACTION_RES_STOPPED_LISTENING`
- `WOLFSENTRY_ACTION_RES_CONNECTING_OUT`
- `WOLFSENTRY_ACTION_RES_CLOSED`
- `WOLFSENTRY_ACTION_RES_UNREACHABLE`

- `WOLFSENTRY_ACTION_RES SOCK_ERROR`

These flags are now passed by the lwIP integration code in `src/lwip/packet_filter_glue.c`. Detailed descriptions of these and other `_ACTION_RES_` bits are in [wolfentry/wolfentry.h](#).

Added `wolfentry_addr_family_max_addr_bits()`, to allow programmatic determination of whether a given address is a prefix or fully specified.

Added a family of functions to let routes be inserted directly from a prepared `struct wolfentry_route_exports`, and related helper functions to prepare it:

- `wolfentry_route_insert_by_exports_into_table()`
- `wolfentry_route_insert_by_exports()`
- `wolfentry_route_insert_by_exports_into_table_and_check_out()`
- `wolfentry_route_insert_by_exports_and_check_out()`
- `wolfentry_route_reset_metadata_exports()`

Added convenience accessor/validator functions for routes:

- `wolfentry_route_get_addrs()`
- `wolfentry_route_check_flags_sensical()`

Refactored the event action list implementation so that the various action lists (`WOLFSENTRY_ACTION_←_TYPE_POST`, `_INSERT`, `_MATCH`, `_UPDATE`, `_DELETE`, and `_DECISION`) are represented directly in the `struct wolfentry_event`, rather than through a "subevent". The related APIs (`wolfentry_event_action_prepend()`, `wolfentry_event_action_append()`, `wolfentry_event_acti←wolfentry_event_action_delete()`, `wolfentry_event_action_list_start()`) each gain an additional argument, `which_action_list`. The old JSON grammar is still supported via internal emulation (still tested by `test-config.json`). The JSON configuration for the new facility is "post-actions", "insert-actions", "match-actions", "update-actions", "delete-actions", and "decision-actions", each optional, and each expecting an array of zero or more actions.

Added a restriction that user-defined action and event labels can't start with "%", and correspondingly, all built-in actions and events have labels that start with "%". This can be overridden by predefining `WOLFSENTRY_←BUILTIN_LABEL_PREFIX` in user settings.

Removed unused flag `WOLFSENTRY_ACTION_RES_CONTINUE`, as it was semantically redundant relative to `WOLFSENTRY_ACTION_RES_STOP`.

Removed flags `WOLFSENTRY_ACTION_RES_INSERT` and `WOLFSENTRY_ACTION_RES_DELETE`, as the former is superseded by the new builtin action facility, and the latter will be implemented later with another builtin action.

Added flag `WOLFSENTRY_ACTION_RES_INSERTED`, to indicate when a side-effect route insertion was performed. This flag is now always set by the route insert routines when they succeed. Action plugins must copy this flag as shown in the new `wolfentry_builtin_action_track_peer()` to assure proper internal accounting.

Reduced number of available user-defined `_ACTION_RESULT_` bits from 16 to 8, to accommodate new generic traffic bits (see above).

In `struct wolfentry_route_metadata_exports`, changed `.connection_count`, `.derogatory_←_count`, and `.commendable_count`, from `wolfentry_hitcount_t` to `uint16_t`, to match internal representations. Similarly, in `struct wolfentry_route_exports`, changed `.parent_event_←label_len` from `size_t` to `int` to match `label_len` arg type.

Added `wolfentry_table_ent_get_by_id()` to the public API.

Renamed public API `wolfentry_action_res_decode()` as `wolfentry_action_res_assoc_by_flag()` for clarity and consistency.



## Bug Fixes and Cleanups

Consistently set the `WOLFSENTRY_ACTION_RES_FALLTHROUGH` flag in `action_results` when dispatch classification (`_ACCEPT/_REJECT`) was by fallthrough policy.

Refactored internal code to avoid function pointer casts, previously used to allow implementations with struct pointers where a handler pointer has a type that expects `void *`. The refactored code has shim implementations with fully conformant signatures, that cast the arguments to pass them to the actual implementations. This works around over-eager analysis by the `clang` UB sanitizer.

Fix missing default cases in non-enum `switch()` constructs.

## Self-Test Enhancements

Added new clauses to `test-config*.json` for `wolfentry_builtin_action_track_peer()` (events "ephemeral-pinhole-parent", "pinhole-generator-parent", "ephemeral-port-scanner-parent", "port-scanner-generator-parent", and related routes), and added full dynamic workout for them to `test_json()`.

Add unit test coverage:

- `wolfentry_event_set_aux_event()`
- `wolfentry_event_get_aux_event()`
- `wolfentry_event_get_label()`
- `wolfentry_addr_family_max_addr_bits()`

## wolfSentry Release 1.3.1 (July 5, 2023)

Release 1.3.1 of the wolfSentry embedded firewall/IDPS has bug fixes and improvements including:

### Bug Fixes and Cleanups

Updated lwIP patches to fix `packet_filter_event_t` checking on short-enum targets.

Fixed copying of route table header fields (table config) when cloning or rebuilding (preserve default policy etc when loading with `WOLFSENTRY_CONFIG_LOAD_FLAG_LOAD_THEN_COMMIT` | `WOLFSENTRY_CONFIG_LOAD_FLAG_NO_FLUSH` or `WOLFSENTRY_CONFIG_LOAD_FLAG_FLUSH_ONLY_ROUTES`).

Implemented proper locking in `wolfentry_route_get_reference()`, and corresponding lock assertion in `wolfentry_table_cursor_init()`.

Fixed logic in address matching to properly match zero-length addresses when performing subnet matching, even if the corresponding `_ADDR_WILDCARD` flag bit is clear.

## Self-Test Enhancements

Makefile.analyzers: add `-fshort-enums` variants to `sanitize-all` and `sanitize-all-gcc` recipes, and add `short-enums-test` recipe.

Added `wolfentry_route_event_dispatch()` cases to `test_json()`.

Added unit test coverage to confirm correct copying of route table header fields when cloning.

## wolfSentry Release 1.3 (May 19, 2023)

Release 1.3 of the wolfSentry embedded firewall/IDPS has bug fixes and improvements including:

### New Features

#### Route dump to JSON

The route (rule) table can now be dumped in conformant JSON format to a byte stream, using wolfSentry intrinsics (no `stdio` dependencies), and subsequently reloaded.

- `wolfentry_route_table_dump_json_start()`, `_next()`, `_end()`
- Byte streams using new `WOLFSENTRY_BYTE_STREAM_*` macros, with stack and heap options.
- Retryable rendering on `_BUFFER_TOO_SMALL` error, by flushing the byte stream, calling `WOLFSENTRY_BYTE_STREAM_RENDER()` and retrying the `wolfentry_route_table_dump_json_*` call.
- New flag `WOLFSENTRY_CONFIG_LOAD_FLAG_FLUSH_ONLY_ROUTES`, to allow reloads that leave all event and key-value configuration intact, and only replace the routes.

### Bug Fixes and Cleanups

- Non-threadsafe `get{proto,serv}by{name.number}()` calls (already configuration-gated) have been replaced by their `_r()` counterparts, and gated on compatible glibc.
- Fixed an underread bug in `convert_hex_byte()` that affected parsing of MAC addresses.

### Self-Test Enhancements

- Added `__wolfentry_wur` to `WOLFSENTRY_LOCAL`.
- Added new clauses in `test_json()` to verify bitwise idempotency of route table export-ingest cycles to/from JSON.
- Added new target `notification-demo-build-test`.

## wolfSentry Release 1.2.2 (May 4, 2023)

Release 1.2.2 of the wolfSentry embedded firewall/IDPS has bug fixes and improvements including:

### Noteworthy Changes and Additions

Added C89 pedantic compatibility in core codebase, including unit tests, via `-DWOLFSENTRY_C89`.

Added error code `IO_FAILED`, returned for various stdio failures that previously returned `SYS_OP_FAILED` or went undetected.

Refined `wolfentry_lock_unlock()` so that final unlock while holding a promotion reservation is not an error and implicitly drops the reservation.

### Bug Fixes and Cleanups

Cleanups guided by `clang-tidy` and `cppcheck`: fixed a misused retval from `posix_memalign()`, fixed overwritten retvals in `wolfentry_lock_unlock()`, and effected myriad cleanups to improve clarity and portability.

Fixed missing assignment of `new->prev` in `wolfentry_table_clone()`.

Fixed route metadata coherency in transactional configuration updates: add `wolfentry_route_copy_metadata()`, and call it from `wolfentry_context_exchange()`.

When `wolfentry_route_event_dispatch*()` results in a default policy fallback, return `USED_FALLBACK` success code.

Properly release lock promotion reservation in `wolfentry_config_json_init_ex()` if obtained.

Fixed several accounting bugs in the lock kernel related to promotion reservations.

Copy `fallthrough_route` pointer in `wolfentry_route_table_clone_header()`, rather than improperly trying to clone the fallthrough route.

### Self-Test Enhancements

Added new global compiler warnings to `Makefile`:

- `-Wmissing-prototypes`
- `-Wdeclaration-after-statement`
- `-Wnested-externs`
- `-Wlogical-not-parentheses`
- `-Wpacked-not-aligned`

Added new targets to `Makefile.analyzers`:

- clang-tidy-build-test
- cppcheck-analyze
- c89-test
- m32-c89-test
- freertos-arm32-c89-build-test
- freertos-arm32-singlethreaded-build-test
- sanitize-aarch64-be-test
- sanitize-all-no-inline-gcc
- no-inline-test
- no-allocat-test
- release-check

Added `WOLFSENTRY_CONFIG_LOAD_FLAG_NO_FLUSH` coverage and an array of should-fail JSON objects to `unittests.c:test_json()`.

Added more `arg-not-null` and `thread-init` checks to thread/lock routines in `src/wolfentry_util.c`, and corresponding unit test coverage for all null/uninit arg permutations.

Added assert in release recipe to assure that [wolfentry.h](https://www.wolfssl.com/wolfSentry/) has a version that matches the tagged version.

## wolfSentry Release 1.2.1 (Apr 5, 2023)

Release 1.2.1 of the wolfSentry embedded firewall/IDPS has bug fixes and improvements including:

### Noteworthy Changes and Additions

Added API `wolfentry_route_render_flags()`, now used in `wolfentry_route_render()` and `wolfentry_route_exports_render()`.

Refactored `wolfentry_route_lookup_0()` to consistently return the highest-priority matching route, breaking ties using `compare_match_exactness()`.

Added `DEBUG_ROUTE_LOOKUP` code paths in `wolfentry_route_lookup_0()`, for verbose troubleshooting of configurations and internal logic.

Added to `convert_hex_byte()` (and therefore to MAC address parsing) tolerance for single-hex-digit byte values, as in `a:b:c:1:2:3`.

## Bug Fixes

Removed several inappropriate wildcard flags on queries in lwIP event handlers, particularly `_SA_LOCAL_PORT↵_WILDCARD` for `FILT_PORT_UNREACHABLE` and `*_INTERFACE_WILDCARD` for `FILT_BINDING/FILT↵_LISTENING/FILT_STOP_LISTENING` and when `event->netif` is null.

Added nullness checks for `laddr` and `raddr` in lwIP event handlers, and if null, set all-zeros address.

Refactored wildcard handling in `wolfentry_route_init()`, `wolfentry_route_new()`, and `wolfentry_route_insert_1()`, to zero out wildcard fields at insert time, rather than at init time, so that routes used as targets contain accurate information for `compare_match_exactness()`, regardless of wildcard bits.

Fixed `WOLFSENTRY_VERSION_*` values, which were inadvertently swapped in release 1.2.0.

## wolfSentry Release 1.2.0 (Mar 24, 2023)

Production Release 1.2.0 of the wolfSentry embedded firewall/IDPS has bug fixes and improvements including:

### New Features

#### lwIP full firewall integration

When wolfSentry is built with make options `LWIP=1 LWIP_TOP=<path-to-lwIP-source>`, the library is built with new APIs `wolfentry_install_lwip_filter_ethernet_callback()`, `wolfentry_install_lwip_filter_ip_callbacks()`, `wolfentry_install_lwip_filter_icmp_callba`, `wolfentry_install_lwip_filter_tcp_callback()`, `wolfentry_install_lwip_filter_udp_callbac` and the all-on-one `wolfentry_install_lwip_filter_callbacks()`. For each layer/protocol, a simple bitmask, of type `packet_filter_event_mask_t`, allows events to be selectively filtered, with other traffic passed with negligible overhead. For example, TCP connection requests can be fully evaluated by wolfSentry, while traffic within established TCP connections can pass freely.

wolfSentry `LWIP=1` relies on a patchset to lwIP, gated on the macro `LWIP_PACKET_FILTER_API`, that adds generic filter callback APIs to each layer and protocol. See `lwip/README.md` for details.

In addition to `LWIP_DEBUG` instrumentation, the new integration supports `WOLFSENTRY_DEBUG_PACKET_↵FILTER`, which renders the key attributes and outcome for all callout events.

### Noteworthy Changes and Additions

Routes and default actions can now be annotated to return `WOLFSENTRY_ACTION_RES_PORT_RESET` in their `action_results`. This is used in the new lwIP integration to control whether TCP reset and ICMP port-unreachable packets are sent (versus dropping the rejected packet unacknowledged).

A new `ports/` tree is added, and the former `FreeRTOS/` tree is moved to `ports/FreeRTOS-lwIP`.

New helper macros are added for managing thread state: `WOLFSENTRY_THREAD_HEADER_DECLS`, `WOLFSENTRY_THREAD_HEADER_INIT()`, `WOLFSENTRY_THREAD_HEADER_INIT_CHECKED()`.

New flags `WOLFSENTRY_ROUTE_FLAG_PORT_RESET` and `WOLFSENTRY_ACTION_RES_EXCLUDE_↵REJECT_ROUTES` to support firewall functionalities.

## Bug Fixes

Wildcard matching in the routes/rules table now works correctly even for non-contiguous wildcard matching.

struct `wolfentry_sockaddr` now aligns its `addr` member to a 4 byte boundary, for safe casting to `(int *)`, using a new `attr_align_to()` macro.

The route lookup algorithm has been improved for correct results with non-contiguous wildcards, to correctly break ties using the new `compare_match_exactness()`, and to correctly give priority to routes with a matching event.

When matching target routes (e.g. with `wolfentry_route_event_dispatch()`), ignore failure in `wolfentry_event_get_reference()` if `WOLFSENTRY_ROUTE_FLAG_PARENT_EVENT_↵` WILDCARD is set in the flags.

## wolfSentry Release 1.1.0 (Feb 23, 2023)

Production Release 1.1.0 of the wolfSentry embedded firewall/IDPS has bug fixes and improvements including:

### New Features

Internal settings, types, alignments, constants, a complete set of internal shims, and Makefile clauses, for portability to native FreeRTOS with threads on 32 bit gcc targets.

### Noteworthy Changes and Additions

rwlock control contexts can now be allocated inside interrupt handlers, and `WOLFSENTRY_LOCK_FLAG_↵` RETAIN\_SEMAPHORE can be supplied to the new `wolfentry_context_lock_mutex_timed_ex()`, allowing safe trylock followed by automatic lock recursion.

API routines are now marked warn-unused-return by default, subject to user-defined override. This new default warns on untrapped errors, to aid preventing undefined behavior.

API arguments previously accepting "long" ints for counts of seconds now expect `time_t`, for portability to ARM32 and FreeRTOS.

New unit test: `test_json_corpus`, for highly configurable bulk trial runs of the JSON processing subsystem.

New tests in `Makefile.analyzers`: `no-getprotoby-test`, `freertos-arm32-build-test`.

A new guard macro, `WOLFSENTRY_NO_GETPROTOBY`, allows narrow elimination of dependencies on `getprotobyname()` and `getprotobynumber()`.

Recursive JSON DOM tree processing logic was refactored to greatly reduce stack burden.

Substantial enlargement of code coverage by unit tests, guided by `gcov`.

New convenience macros for typical threaded state tracking wrappers: `WOLFSENTRY_THREAD_HEADER_CHECKED()` and `WOLFSENTRY_THREAD_TAILER_CHECKED()`.

## Bug Fixes

Cloning of user-defined deep JSON objects is now implemented, as needed for configuration load dry runs and load-then-commit semantics.

JSON processing of UTF-8 surrogate pairs is now fixed.

Fixed retval testing in `wolfentry_action_list_{append,prepend,insert}_1()`, and added missing `point_action` lookup in `wolfentry_action_list_insert_after()`.

Fixed potential use-after-free defect in `wolfentry_event_delete()`.

## wolfSentry Release 1.0.0 (Jan 18, 2023)

Production Release 1.0.0 of the wolfSentry embedded firewall/IDPS has bug fixes and improvements including:

### Noteworthy Changes and Additions

- Makefile improvements around `wolfentry_options.h`, and a new com-bundle rule.
- A new macro `WOLFSENTRY_USE_NONPOSIX_THREADS`, separated from `WOLFSENTRY_USE_↔NONPOSIX_SEMAPHORES`, supporting mixed-model targets, e.g. Mac OS X.

## Bug Fixes

- In `examples/notification-demo/log_server/log_server.c`, in `main()`, properly reset `transaction_successful` at top of the accept loop.

## wolfSentry Release 0.8.0 (Jan 6, 2023)

Preview Release 0.8.0 of the wolfSentry embedded firewall/IDPS has bug fixes and new features including:

### New Features

#### Multithreaded application support

- Automatic locking on API entry, using a high performance, highly portable semaphore-based readwrite lock facility, with error checking and opportunistic lock sharing.
- Thread-specific deadlines set by the caller, limiting waits for lock acquisition as needed for realtime applications.
- A mechanism for per-thread private data, accessible to user plugins.
- No dependencies on platform-supplied thread-local storage.

## Updated Examples

### examples/notification-demo

- Add interrupt handling for clean error-checked shutdown in `log_server`.
- Add `/kill-server` admin command to `log_server`.
- Reduce penalty-box-duration in `notify-config.{json,h}` to 10s for demo convenience.

## Noteworthy Changes and Additions

- A new first argument to `wolfentry_init_ex()` and `wolfentry_init()`, `caller_build_settings`, for runtime error-checking of application/library compatibility. This mechanism will also allow future library changes to be conditionalized on caller version and/or configuration expectations as needed, often avoiding the need for application recompilation.
- `src/util.c` was renamed to `src/wolfentry_util.c`.
- `wolfentry/wolfentry_settings.h` was added, containing setup code previously in `wolfentry/wolfentry.h`.
- Error IDs in `enum wolfentry_error_id` are all now negative, and a new `WOLFENTRY_SUCCESS_ID_*` namespace was added, with positive values and supporting macros.

### New public utility APIs, macros, types, etc.

- `WOLFENTRY_VERSION_*` macros, for version testing
- `wolfentry_init_thread_context()`, `wolfentry_alloc_thread_context()`, `wolfentry_get_thread_id()`, `wolfentry_get_thread_user_context()`, `wolfentry_get_thread_flags()`, `wolfentry_destroy_thread_context()`, `wolfentry_free_thread_context()`, `wolfentry_set_deadline_rel_usecs()`, `wolfentry_set_deadline_abs()`, `wolfentry_clear_deadline()`, `wolfentry_set_thread_readonly()`, `wolfentry_set_thread_readwrite()`
- `WOLFENTRY_DEADLINE_NEVER` and `WOLFENTRY_DEADLINE_NOW`, used internally and for testing values returned by `wolfentry_get_thread_deadline()`
- Many new values in the `WOLFENTRY_LOCK_FLAG_*` set.
- `wolfentry_lock_*` APIs now firmed, and new `wolfentry_context_lock_shared_with_reservation`
- `WOLFENTRY_CONTEXT_*` helper macros.
- `WOLFENTRY_UNLOCK_*`, `WOLFENTRY_SHARED_*`, `WOLFENTRY_MUTEX_*`, and `WOLFENTRY_PROMOTABLE_*` helper macros
- `WOLFENTRY_ERROR_UNLOCK_AND_RETURN()`, `WOLFENTRY_SUCCESS_UNLOCK_AND_RETURN()`, and related helper macros.

## Bug Fixes

- Various fixes, and additional hardening and cleanup, in the readwrite lock kernel.
- Various fixes in `Makefile`, for proper handling and installation of `wolfentry_options.h`.



## wolfSentry Release 0.7.0 (Nov 7, 2022)

Preview Release 0.7.0 of the wolfSentry embedded firewall/IDPS has bug fixes and new features including:

### New Features

**Support for freeform user-defined JSON objects in the "user-values" (key-value pair) section of the config package.**

- Uses syntax `"key" : { "json" : x }` where `x` is any valid standalone JSON expression.
- Key length limited to `WOLFSENTRY_MAX_LABEL_BYTES` by default.
- String length limited to `WOLFSENTRY_KV_MAX_VALUE_BYTES` by default.
- JSON tree depth limited to `WOLFSENTRY_MAX_JSON_NESTING` by default.
- All default limits subject to caller runtime override using the `json_config` arg to the new APIs `wolfentry_config_json_init_ex()` and `wolfentry_config_json_oneshot_ex()`, accepting a `JSON_CONFIG *` (accepted as `const`).

### New APIs for JSON KVs

- `wolfentry_user_value_store_json()`
- `wolfentry_user_value_get_json()`
- `WOLFSENTRY_KV_V_JSON()`
- `wolfentry_config_json_init_ex()`
- `wolfentry_config_json_oneshot_ex()`

### New config load flags controlling JSON KV parsing

- `WOLFSENTRY_CONFIG_LOAD_FLAG_JSON_DOM_DUPKEY_ABORT`
- `WOLFSENTRY_CONFIG_LOAD_FLAG_JSON_DOM_DUPKEY_USEFIRST`
- `WOLFSENTRY_CONFIG_LOAD_FLAG_JSON_DOM_DUPKEY_USELAST`
- `WOLFSENTRY_CONFIG_LOAD_FLAG_JSON_DOM_MAINTAININDICTORDER`

### Support for setting a user KV as read-only.

- Read-only KVs can't be deleted or overwritten without first setting them read-write.
- Mechanism can be used to protect user-configured data from dynamic changes by JSON configuration package – JSON cannot change or override the read-only bit.

### KV mutability APIs:

- `wolfentry_user_value_set_mutability()`
- `wolfentry_user_value_get_mutability()`

## Updated Examples

### examples/notification-demo

- Update and clean up `udp_to_dbus`, and add `--kv-string` and `--kv-int` command line args for runtime ad hoc config overrides.
- Rename config node controlling the `udp_to_dbus` listen address from "notification-dest-addr" to "notification-listen-addr".

### Added examples/notification-demo/log\_server

- Toy embedded web server demonstrating HTTPS with dynamic insertion of limited-lifespan wolfSentry rules blocking (penalty boxing) abusive peers.
- Demonstrates mutual authentication using TLS, and role-based authorizations pivoting on client certificate issuer (certificate authority).

## Noteworthy Changes and Additions

- JSON strings (natively UTF-8) are now consistently passed in and out with `unsigned char` pointers.
- `wolfentry_kv_render_value()` now has a `struct wolfentry_context *` as its first argument (necessitated by addition of freeform JSON rendering).
- Added new API routine `wolfentry_centijson_errcode_translate()`, allowing conversion of all CentiJSON return codes (e.g. from `json_dom_parse()`, `json_value_path()`, and `json_value_build_path()`) from native CentiJSON to roughly-corresponding native wolfSentry codes.

### Cleanup of JSON DOM implementation

- Added `json_` prefix to all JSON functions and types.
- CentiJSON now uses wolfSentry configured allocator for all heap operations.

### New utility APIs

- `wolfentry_get_allocator()`
- `wolfentry_get_timecbs()`

## Bug Fixes

- Fix error-path memory leak in JSON KV handling.
- Fix "echo: write error: Broken pipe" condition in recipe for rule "force"
- Various minor portability fixes.
- Enlarged scope for build-time pedantic warnings – now includes all of CentiJSON.

## wolfSentry Release 0.6.0 (Sep 30, 2022)

Preview Release 0.6.0 of the wolfSentry embedded firewall/IDPS has bug fixes and new features including:

### New Features

**Core support for automatic penalty boxing, with configurable threshold when derogatory count reaches threshold**

**New APIs for manipulating route derogatory/commendable counts from application/plugin code:**

- `wolfentry_route_increment_derogatory_count()`
- `wolfentry_route_increment_commendable_count()`
- `wolfentry_route_reset_derogatory_count()`
- `wolfentry_route_reset_commendable_count()`

**New JSON config nodes:**

- `derog-thresh-for-penalty-boxing`
- `derog-thresh-ignore-commendable`
- `commendable-clears-derogatory`

**Automatic purging of expired routes:**

- constant time garbage collection
- `wolfentry_route_table_max_purgeable_routes_get()`
- `wolfentry_route_table_max_purgeable_routes_set()`
- `wolfentry_route_stale_purge_one()`

### Noteworthy Changes and Additions

- New API `wolfentry_route_insert_and_check_out()`, allowing efficient update of route state after insert; also related new API `wolfentry_object_checkout()`.
- New APIs `wolfentry_route_event_dispatch_by_route()` and `wolfentry_route_event_dispatch_by_id()` analogous to the `_by_id()` variants, but accepting a struct `wolfentry_route` pointer directly.
- `wolfentry_route_init()` and `wolfentry_route_new()` now allow (and ignore) nonzero supplied values in wildcarded `wolfentry_sockaddr` members.
- New debugging aid, make `CALL_TRACE=1`, gives full call stack trace with codepoints and error codes, to aid debugging of library, plugins, and configurations.

## Bug Fixes

- src/internal.c: fix wrong constant of iteration in `wolfentry_table_ent_get_by_id()`.

## wolfSentry Release 0.5.0 (Aug 1, 2022)

Preview Release 0.5.0 of the wolfSentry embedded firewall/IDPS has bug fixes and new features including:

### New Example

#### examples/notification-demo

Added examples/notification-demo, demonstrating plugin actions, JSON event representation, and pop-up messages using the D-Bus notification facility and a middleware translation daemon.

### Noteworthy Changes

- Added new API `wolfentry_init_ex()` with `wolfentry_init_flags_t` argument.
- Added runtime error-checking on lock facility.

## Bug Fixes

Fix missing assignment in `wolfentry_list_ent_insert_after()`.

## wolfSentry Release 0.4.0 (May 27, 2022)

Preview Release 0.4.0 of the wolfSentry embedded firewall/IDPS has bug fixes and new features including:

## New Features

- User-defined key-value pairs in JSON configuration: allows user plugins to access custom config parameters in the wolfSentry config using the new `wolf_sentry_user_value_*` family of API functions. Binary configuration data can be supplied in the configuration using base64 encoding, and are decoded at parse time and directly available to user plugins in the original raw binary form. The key-value facility also supports a custom validator callback to enforce constraints on user-defined config params in the JSON.
- User-defined address families: allows user plugins for custom address families and formats, using new `wolf_sentry_addr_family_*` API routines. This allows idiomatic formats for non-Internet addresses in the JSON config, useful for various buses and device namespaces.
- Formalization of the concepts of default events and fallback rules in the rule tables.
- A new subevent action list facility to support logging and notifications around the final decisions of the rule engine, alongside the existing subevents for rule insertions, matches, and deletions.
- The main plugin interface (`wolf_sentry_action_callback_t`) now passes two separate routes, a "trigger\_route" with full attributes of the instant traffic, and a "rule\_route" that matches that traffic. In dynamic rule scenarios, plugins can manipulate the passed `rule_route` and set the `WOLFSENTRY_ACTION_RES_INSERT` bit in the to define a new rule that will match the traffic thereafter. All actions in the chain retain read-only access to the unmodified trigger route for informational purposes.
- The JSON DOM facility from CentiJSON is now included in the library by default (disabled by `make NO_JSON_DOM=1`), layered on the SAX facility used directly by the wolfSentry core to process the JSON config package. The DOM facility can be used as a helper in user plugins and applications, for convenient JSON parsing, random access, and production.

## Noteworthy Changes

- In the JSON config, non-event-specific members of top level node "config-update" node have been moved to the new top level node "default-policies", which must appear after "event-insert". "default-policies" members are "default-policy-static", "default-policy-dynamic", "default-event-static", and "default-event-dynamic".

## Bug Fixes

- In `wolf_sentry_config_json_init()`, properly copy the `load_flags` from the caller into the `_json_process_state`.
- The JSON SAX API routines (`wolf_sentry/centijson_sax.h`) are now properly exported.

## wolfSentry Release 0.3.0 (Dec 30, 2021)

Preview Release 0.3.0 of the wolfSentry embedded firewall/IDPS has bug fixes and new features including:

## New Ports and Examples

### examples/Linux-LWIP

This demo uses Linux-hosted LWIP in Docker containers to show packet-level and connection-level filtering using wolfSentry. Filtering can be by MAC, IPv4, or IPv6 address. Demos include pre-accept TCP filtering, and filtering of ICMP packets.

See `examples/Linux-LWIP/README.md` for the installation and usage guide, and `examples/Linux-LWIP/echo-config.json` for the associated wolfSentry configuration.

## FreeRTOS with LWIP on STM32

This demo is similar to Linux-LWIP, but targets the STM32 ARM core and the STM32CubeMX or STM32CubeIDE toolchain, with a FreeRTOS+LWIP runtime. It shows wolfSentry functionality in a fully embedded (bare metal) application.

See `examples/STM32/README.md` for the installation and usage guide, and `examples/STM32/Src/sentry.c` for the compiled-in wolfSentry configuration.

## New Features

- Autogeneration and inclusion of `wolfentry_options.h`, synchronizing applications with wolfSentry library options as built.
- New APIs `wolfentry_route_event_dispatch_[by_id]with_initiated_result()`, for easy caller designation of known traffic attributes, e.g. `WOLFSENTRY_ACTION_RES_CONNECT` or `WOLFSENTRY_ACTION_RES_DISCONNECT`.
- Efficient support for aligned heap allocations on targets that don't have a native aligned allocation API: `wolfentry_free_aligned_cb_t`, `wolfentry_allocator.free_aligned`, `wolfentry_builtin_free_aligned()`, `wolfentry_free_aligned()`, and `WOLFSENTRY_FREE_ALIGNED()`.
- Semaphore wrappers for FreeRTOS, for use by the `wolfentry_lock_*`() shareable-upgradeable lock facility.

## Bug Fixes

- `wolfentry_route_event_dispatch_1()`: don't impose `config.penaltybox_duration` on routes with `route->meta.last_penaltybox_time == 0`.
- trivial fixes for backward compat with gcc-5.4.0, re `-Wconversion` and `-Winline`.

Please send questions or comments to [douzzzer@wolfssl.com](mailto:douzzzer@wolfssl.com)

# Chapter 5

## Topic Index

### 5.1 Topics

Here is a list of all topics with brief descriptions:

Core Types and Macros . . . . .	51
Startup/Configuration/Shutdown Subsystem . . . . .	52
Diagnostics, Control Flow Helpers, and Compiler Attribute Helpers . . . . .	62
Route/Rule Subsystem . . . . .	69
Action Subsystem . . . . .	92
Event Subsystem . . . . .	100
Address Family Subsystem . . . . .	113
User-Defined Value Subsystem . . . . .	116
Object Subsystem . . . . .	121
Thread Synchronization Subsystem . . . . .	123
Allocator (Heap) Functions and Callbacks . . . . .	144
Time Functions and Callbacks . . . . .	145
Semaphore Function Callbacks . . . . .	146
lwIP Callback Activation Functions . . . . .	148





## Chapter 6

# Data Structure Index

### 6.1 Data Structures

Here are the data structures with brief descriptions:

<a href="#">JSON_CALLBACKS</a>	149
<a href="#">JSON_CONFIG</a>	149
<a href="#">JSON_DOM_PARSER</a>	149
<a href="#">JSON_INPUT_POS</a>	150
<a href="#">JSON_PARSER</a>	150
<a href="#">JSON_VALUE</a>	150
<a href="#">wolfsentry_allocator</a>	
Struct for passing shims that abstract the native implementation of the heap allocator	151
<a href="#">wolfsentry_build_settings</a>	
Struct for passing the build version and configuration	151
<a href="#">wolfsentry_data</a>	152
<a href="#">wolfsentry_eventconfig</a>	
Struct for representing event configuration	152
<a href="#">wolfsentry_host_platform_interface</a>	
Struct for passing shims that abstract native implementations of the heap allocator, time functions, and semaphores	153
<a href="#">wolfsentry_kv_pair</a>	
Public structure for passing user-defined values in/out of wolfSentry	154
<a href="#">wolfsentry_route_endpoint</a>	
Struct for exporting socket addresses, with fixed-length fields	154
<a href="#">wolfsentry_route_exports</a>	
Struct for exporting a route for access by applications	155
<a href="#">wolfsentry_route_metadata_exports</a>	
Struct for exporting route metadata for access by applications	156
<a href="#">wolfsentry_semcbs</a>	
Struct for passing shims that abstract the native implementation of counting semaphores	156
<a href="#">wolfsentry_sockaddr</a>	
Struct for passing socket addresses into <code>wolfsentry_route_*</code> () API routines	157
<a href="#">wolfsentry_thread_context_public</a>	
Right-sized, right-aligned opaque container for thread state	158
<a href="#">wolfsentry_timecbs</a>	
Struct for passing shims that abstract the native implementation of time functions	158



# Chapter 7

## File Index

### 7.1 File List

Here is a list of all documented files with brief descriptions:

wolfentry/ <a href="#">centijson_dom.h</a>	159
wolfentry/ <a href="#">centijson_sax.h</a>	161
wolfentry/ <a href="#">centijson_value.h</a>	165
wolfentry/ <a href="#">wolfentry.h</a>	
The main include file for wolfSentry applications	172
wolfentry/ <a href="#">wolfentry_af.h</a>	
Definitions for address families	213
wolfentry/ <a href="#">wolfentry_errcodes.h</a>	
Definitions for diagnostics	218
wolfentry/ <a href="#">wolfentry_json.h</a>	
Types and prototypes for loading/reloading configuration using JSON	228
wolfentry/ <a href="#">wolfentry_lwip.h</a>	
Prototypes for lwIP callback installation functions, for use in lwIP applications	230
wolfentry/ <a href="#">wolfentry_settings.h</a>	
Target- and config-specific settings and abstractions for wolfSentry	232
wolfentry/ <a href="#">wolfentry_util.h</a>	
Utility and convenience macros for both internal and application use	244
wolfentry/ <a href="#">wolfssl_test.h</a>	
Macros and helper functions for wolfSSL --enable-wolfentry	251



# Chapter 8

## Topic Documentation

### 8.1 Core Types and Macros

#### Macros

- **#define WOLFSENTRY\_NO\_ALLOCA**  
*Build flag to use only implementations that avoid `alloca()`.*
- **#define WOLFSENTRY\_C89**  
*Build flag to use only constructs that are pedantically legal in C89.*
- **#define \_\_attribute\_maybe\_unused\_\_**  
*Attribute abstraction to mark a function or variable (typically a `static`) as possibly unused.*
- **#define DO\_NOTHING**  
*Statement-type abstracted construct that executes no code.*
- **#define WOLFSENTRY\_NO\_POSIX\_MEMALIGN**  
*Define if `posix_memalign()` is not available.*
- **#define WOLFSENTRY\_FLEXIBLE\_ARRAY\_SIZE**  
*Value appropriate as a size for an array that will be allocated to a variable size. Built-in value usually works.*
- **#define SIZE\_T\_FMT**  
*printf-style format string appropriate for pairing with `size_t`*
- **#define WOLFSENTRY\_ENT\_ID\_FMT**  
*printf-style format string appropriate for pairing with `wolfentry_ent_id_t`*
- **#define WOLFSENTRY\_ENT\_ID\_NONE**  
*always-invalid object ID*
- **#define WOLFSENTRY\_HITCOUNT\_FMT**  
*printf-style format string appropriate for pairing with `wolfentry_hitcount_t`*
- **#define \_\_wolfentry\_wur**  
*abstracted attribute designating that the return value must be checked to avoid a compiler warning*
- **#define wolfentry\_static\_assert(c)**  
*abstracted static assert – `c` must be true, else `c` is printed*
- **#define wolfentry\_static\_assert2(c, m)**  
*abstracted static assert – `c` must be true, else `m` is printed*
- **#define WOLFSENTRY\_API\_VOID**  
*Function attribute for declaring/defining public void API functions.*
- **#define WOLFSENTRY\_API**  
*Function attribute for declaring/defining public API functions with return values.*
- **#define WOLFSENTRY\_LOCAL\_VOID**

Function attribute for declaring/defining private void functions.

- #define **WOLFSENTRY\_LOCAL**

Function attribute for declaring/defining private functions with return values.

- #define **WOLFSENTRY\_MAX\_ADDR\_BYTES** 16

The maximum size allowed for an address, in bytes. Can be overridden. Note that support for bitmask matching for an address family depends on [WOLFSENTRY\\_MAX\\_ADDR\\_BYTES](#) at least twice the max size of a bare address in that family, as the address and mask are internally stored as a single double-length byte vector. Note also that [WOLFSENTRY\\_MAX\\_ADDR\\_BYTES](#) entails proportional overhead if wolfSentry is built [WOLFSENTRY\\_NO\\_ALLOCA](#) or [WOLFSENTRY\\_C89](#).

- #define **WOLFSENTRY\_MAX\_ADDR\_BITS** ([WOLFSENTRY\\_MAX\\_ADDR\\_BYTES](#)\*8)

The maximum size allowed for an address, in bits. Can be overridden.

- #define **WOLFSENTRY\_MAX\_LABEL\_BYTES** 32

The maximum size allowed for a label, in bytes. Can be overridden.

- #define **WOLFSENTRY\_BUILTIN\_LABEL\_PREFIX** "%"

The prefix string reserved for use in names of built-in actions and events.

- #define **WOLFSENTRY\_KV\_MAX\_VALUE\_BYTES** 16384

The maximum size allowed for scalar user-defined values. Can be overridden.

## Typedefs

- typedef unsigned char **byte**

8 bits unsigned

- typedef uint16\_t **wolfentry\_addr\_family\_t**

integer type for holding address family number

- typedef uint16\_t **wolfentry\_proto\_t**

integer type for holding protocol number

- typedef uint16\_t **wolfentry\_port\_t**

integer type for holding port number

- typedef uint32\_t **wolfentry\_ent\_id\_t**

integer type for holding table entry ID

- typedef uint16\_t **wolfentry\_addr\_bits\_t**

integer type for address prefix lengths (in bits)

- typedef uint32\_t **wolfentry\_hitcount\_t**

integer type for holding hit count statistics

- typedef int64\_t **wolfentry\_time\_t**

integer type for holding absolute and relative times, using microseconds in built-in implementations.

- typedef uint16\_t **wolfentry\_priority\_t**

integer type for holding event priority (smaller number is higher priority)

### 8.1.1 Detailed Description

## 8.2 Startup/Configuration/Shutdown Subsystem

### Data Structures

- struct [wolfentry\\_host\\_platform\\_interface](#)

struct for passing shims that abstract native implementations of the heap allocator, time functions, and semaphores

- struct [wolfentry\\_build\\_settings](#)

struct for passing the build version and configuration

## Macros

- **#define WOLFSENTRY\_VERSION\_MAJOR**  
Macro for major version number of installed headers.
- **#define WOLFSENTRY\_VERSION\_MINOR**  
Macro for minor version number of installed headers.
- **#define WOLFSENTRY\_VERSION\_TINY**  
Macro for tiny version number of installed headers.
- **#define WOLFSENTRY\_VERSION\_ENCODE(major, minor, tiny)**  
Macro to convert a wolfSentry version to a single integer, for comparison to other similarly converted versions.
- **#define WOLFSENTRY\_VERSION**  
The version recorded in [wolfentry.h](#), encoded as an integer.
- **#define WOLFSENTRY\_VERSION\_GT(major, minor, tiny)**  
Helper macro that is true if the given version is greater than that in [wolfentry.h](#).
- **#define WOLFSENTRY\_VERSION\_GE(major, minor, tiny)**  
Helper macro that is true if the given version is greater than or equal to that in [wolfentry.h](#).
- **#define WOLFSENTRY\_VERSION\_EQ(major, minor, tiny)**  
Helper macro that is true if the given version equals that in [wolfentry.h](#).
- **#define WOLFSENTRY\_VERSION\_LT(major, minor, tiny)**  
Helper macro that is true if the given version is less than that in [wolfentry.h](#).
- **#define WOLFSENTRY\_VERSION\_LE(major, minor, tiny)**  
Helper macro that is true if the given version is less than or equal to that in [wolfentry.h](#).
- **#define WOLFSENTRY\_MAX\_JSON\_NESTING 16**  
Can be overridden.
- **#define WOLFSENTRY\_USER\_SETTINGS\_FILE "the\_path"**  
Define to the path of a user settings file to be included, containing extra and override definitions and directives. Can be an absolute or a relative path, subject to a `-I` path supplied to `make` using `EXTRA_CFLAGS`. Include quotes or `<>` around the path.
- **#define WOLFSENTRY\_NO\_INTTYPES\_H**  
Define to inhibit inclusion of `inttypes.h` (alternative typedefs or include must be supplied with [WOLFSENTRY\\_USER\\_SETTINGS\\_FILE](#)).
- **#define WOLFSENTRY\_NO\_STDINT\_H**  
Define to inhibit inclusion of `stdint.h` (alternative typedefs or include must be supplied with [WOLFSENTRY\\_USER\\_SETTINGS\\_FILE](#)).
- **#define WOLFSENTRY\_SINGLETHREADED**  
Define to disable all thread handling and safety in wolfSentry.
- **#define WOLFSENTRY\_USE\_NONPOSIX\_SEMAPHORES**  
Define if POSIX semaphore API is not available. If no non-POSIX builtin implementation is present in `wolfentry_util.c`, then [WOLFSENTRY\\_NO\\_SEM\\_BUILTIN](#) must be set, and the [wolfentry\\_host\\_platform\\_interface](#) supplied to wolfSentry APIs must include a full semaphore implementation (shim set) in its [wolfentry\\_semcbcs](#) slot.
- **#define WOLFSENTRY\_USE\_NONPOSIX\_THREADS**  
Define if POSIX thread API is not available. `WOLFSENTRY_THREAD_INCLUDE`, `WOLFSENTRY_THREAD_ID_T`, and `WOLFSENTRY_THREAD_GET_ID_HANDLER` will need to be supplied in [WOLFSENTRY\\_USER\\_SETTINGS\\_FILE](#).
- **#define WOLFSENTRY\_NO\_GNU\_ATOMICS**  
Define if `gnu`-style atomic intrinsics are not available. `WOLFSENTRY_ATOMIC_*()` macro definitions for intrinsics will need to be supplied in [WOLFSENTRY\\_USER\\_SETTINGS\\_FILE](#) (see [wolfentry\\_util.h](#)).
- **#define WOLFSENTRY\_NO\_CLOCK\_BUILTIN**  
If defined, omit built-in time primitives; the [wolfentry\\_host\\_platform\\_interface](#) supplied to wolfSentry APIs must include implementations of all functions in [wolfentry\\_timecbcs](#).
- **#define WOLFSENTRY\_NO\_SEM\_BUILTIN**  
If defined, omit built-in semaphore primitives; the [wolfentry\\_host\\_platform\\_interface](#) supplied to wolfSentry APIs must include implementations of all functions in [wolfentry\\_semcbcs](#).
- **#define WOLFSENTRY\_NO\_MALLOC\_BUILTIN**

If defined, omit built-in heap allocator primitives; the [wolfentry\\_host\\_platform\\_interface](#) supplied to wolfSentry APIs must include implementations of all functions in [wolfentry\\_allocator](#).

- **#define WOLFSENTRY\_NO\_ERROR\_STRINGS**  
If defined, omit APIs for rendering error codes and source code files in human readable form. They will be rendered numerically.
- **#define WOLFSENTRY\_NO\_PROTOCOL\_NAMES**  
If defined, omit APIs for rendering error codes and source code files in human readable form. They will be rendered numerically.
- **#define WOLFSENTRY\_NO\_ADDR\_BITMASK\_MATCHING**  
If defined, omit support for bitmask matching of addresses, and support only prefix matching.
- **#define WOLFSENTRY\_NO\_IPV6**  
If defined, omit support for IPv6.
- **#define WOLFSENTRY\_MAX\_BITMASK\_MATCHED\_AFS**  
The maximum number of distinct address families that can use bitmask matching in routes. Default value is 4.
- **#define WOLFSENTRY\_NO\_GETPROTOBY**  
Define this to gate out calls to `getprotobyname_r()` and `getservbyname_r()`, necessitating numeric identification of protocols (e.g. 6 for TCP) and services (e.g. 25 for SMTP) in configuration JSON documents.
- **#define WOLFSENTRY\_SEMAPHORE\_INCLUDE** "the\_path"  
Define to the path of a header file declaring a semaphore API. Can be an absolute or a relative path, subject to a `-I` path supplied to `make` using `EXTRA_CFLAGS`. Include quotes or `<>` around the path.
- **#define WOLFSENTRY\_THREAD\_INCLUDE** "the\_path"  
Define to the path of a header file declaring a threading API. Can be an absolute or a relative path, subject to a `-I` path supplied to `make` using `EXTRA_CFLAGS`. Include quotes or `<>` around the path.
- **#define WOLFSENTRY\_THREAD\_ID\_T** thread\_id\_type  
Define to the appropriate type analogous to POSIX `pthread_t`.
- **#define WOLFSENTRY\_THREAD\_GET\_ID\_HANDLER** pthread\_self\_ish\_function  
Define to the name of a void function analogous to POSIX `pthread_self`, returning a value of type [WOLFSENTRY\\_THREAD\\_ID\\_T](#).
- **#define WOLFSENTRY\_CONFIG\_SIGNATURE**  
Macro to use as the initializer for [wolfentry\\_build\\_settings.config](#) and [wolfentry\\_host\\_platform\\_interface.caller\\_build\\_settings](#).

## Typedefs

- **typedef void(\* wolfentry\_cleanup\_callback\_t)** (WOLFSENTRY\_CONTEXT\_ARGS\_IN, void \*cleanup\_↔ arg)  
Function type to pass to [wolfentry\\_cleanup\\_push\(\)](#)
- **typedef uint32\_t wolfentry\_config\_load\_flags\_t**  
Type for holding flag bits from [wolfentry\\_config\\_load\\_flags](#).

## Enumerations

- **enum wolfentry\_init\_flags\_t** {  
WOLFSENTRY\_INIT\_FLAG\_NONE ,  
WOLFSENTRY\_INIT\_FLAG\_LOCK\_SHARED\_ERROR\_CHECKING }  
flags to pass to [wolfentry\\_init\\_ex\(\)](#), to be OR'd together.
- **enum wolfentry\_clone\_flags\_t** {  
WOLFSENTRY\_CLONE\_FLAG\_NONE ,  
WOLFSENTRY\_CLONE\_FLAG\_AS\_AT\_CREATION ,  
WOLFSENTRY\_CLONE\_FLAG\_NO\_ROUTES }  
Flags to be OR'd together to control the dynamics of [wolfentry\\_context\\_clone\(\)](#) and other cloning functions.



- enum `wolfentry_config_load_flags` {  
`WOLFENTRY_CONFIG_LOAD_FLAG_NONE` ,  
`WOLFENTRY_CONFIG_LOAD_FLAG_NO_FLUSH` ,  
`WOLFENTRY_CONFIG_LOAD_FLAG_DRY_RUN` ,  
`WOLFENTRY_CONFIG_LOAD_FLAG_LOAD_THEN_COMMIT` ,  
`WOLFENTRY_CONFIG_LOAD_FLAG_NO_ROUTES_OR_EVENTS` ,  
`WOLFENTRY_CONFIG_LOAD_FLAG_JSON_DOM_DUPKEY_ABORT` ,  
`WOLFENTRY_CONFIG_LOAD_FLAG_JSON_DOM_DUPKEY_USEFIRST` ,  
`WOLFENTRY_CONFIG_LOAD_FLAG_JSON_DOM_DUPKEY_USELAST` ,  
`WOLFENTRY_CONFIG_LOAD_FLAG_JSON_DOM_MAINTAININDICTORDER` ,  
`WOLFENTRY_CONFIG_LOAD_FLAG_FLUSH_ONLY_ROUTES` ,  
`WOLFENTRY_CONFIG_LOAD_FLAG_FINI` }

Flags to be OR'd together to communicate options to `wolfentry_config_json_init()`

## Functions

- WOLFENTRY\_API struct `wolfentry_build_settings` `wolfentry_get_build_settings` (void)  
Return the `wolfentry_build_settings` of the library as built.
- WOLFENTRY\_API `wolfentry_errcode_t` `wolfentry_build_settings_compatible` (struct `wolfentry_build_settings` caller\_build\_settings)  
Return success if the application and library were built with mutually compatible wolfSentry version and configuration.
- WOLFENTRY\_API struct `wolfentry_host_platform_interface` \* `wolfentry_get_hpi` (struct `wolfentry_context` \*wolfentry)  
Return a pointer to the `wolfentry_host_platform_interface` associated with the supplied `wolfentry_context`, mainly for passing to `wolfentry_alloc_thread_context()`, `wolfentry_free_thread_context()`, `wolfentry_lock_init()`, and `wolfentry_lock_alloc()`.
- WOLFENTRY\_API `wolfentry_errcode_t` `wolfentry_cleanup_push` (WOLFENTRY\_CONTEXT\_ARGS\_IN, `wolfentry_cleanup_callback_t` handler, void \*arg)  
Register handler to be called at shutdown with arg arg.
- WOLFENTRY\_API `wolfentry_errcode_t` `wolfentry_cleanup_pop` (WOLFENTRY\_CONTEXT\_ARGS\_IN, int execute\_p)  
Remove the most recently registered and unpopped handler from the cleanup stack, and if execute\_p is nonzero, call it with the arg with which it was registered.
- WOLFENTRY\_API `wolfentry_errcode_t` `wolfentry_cleanup_all` (WOLFENTRY\_CONTEXT\_ARGS\_IN)  
Iteratively call `wolfentry_cleanup_pop()`, executing each handler as it is popped, passing it the arg with which it was registered.
- WOLFENTRY\_API `wolfentry_errcode_t` `wolfentry_init_ex` (struct `wolfentry_build_settings` caller\_build\_settings, WOLFENTRY\_CONTEXT\_ARGS\_IN\_EX(const struct `wolfentry_host_platform_interface` \*hpi), const struct `wolfentry_eventconfig` \*config, struct `wolfentry_context` \*\*wolfentry, `wolfentry_init_flags_t` flags)  
Variant of `wolfentry_init()` that accepts a flags argument, for additional control over configuration.
- WOLFENTRY\_API `wolfentry_errcode_t` `wolfentry_init` (struct `wolfentry_build_settings` caller\_build\_settings, WOLFENTRY\_CONTEXT\_ARGS\_IN\_EX(const struct `wolfentry_host_platform_interface` \*hpi), const struct `wolfentry_eventconfig` \*config, struct `wolfentry_context` \*\*wolfentry)  
Allocates and initializes the wolfentry context.
- WOLFENTRY\_API `wolfentry_errcode_t` `wolfentry_defaultconfig_get` (WOLFENTRY\_CONTEXT\_ARGS\_IN, struct `wolfentry_eventconfig` \*config)  
Get the default config from a wolfentry context.
- WOLFENTRY\_API `wolfentry_errcode_t` `wolfentry_defaultconfig_update` (WOLFENTRY\_CONTEXT\_ARGS\_IN, const struct `wolfentry_eventconfig` \*config)  
Updates mutable fields of the default config (all but `wolfentry_eventconfig::route_private_data_size` and `wolfentry_eventconfig::route_private_data_alignment`)
- WOLFENTRY\_API `wolfentry_errcode_t` `wolfentry_context_flush` (WOLFENTRY\_CONTEXT\_ARGS\_IN)  
Flushes the route, event, and user value tables from the wolfentry context.

- WOLFSENTRY\_API [wolfentry\\_errcode\\_t wolfentry\\_context\\_free](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN\_EX(struct wolfentry\_context \*\*wolfentry))  
*Frees the wolfentry context and the tables within it. The wolfentry context will be a pointer to NULL upon success.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t wolfentry\\_shutdown](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN\_EX(struct wolfentry\_context \*\*wolfentry))  
*Shut down wolfSentry, freeing all resources. Gets an exclusive lock on the context, then calls [wolfentry\\_context\\_free\(\)](#).*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t wolfentry\\_context\\_inhibit\\_actions](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN)  
*Disable automatic dispatch of actions on the wolfentry context.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t wolfentry\\_context\\_enable\\_actions](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN)  
*Re-enable automatic dispatch of actions on the wolfentry context.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t wolfentry\\_context\\_clone](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, struct wolfentry\_context \*\*clone, [wolfentry\\_clone\\_flags\\_t](#) flags)  
*Clones a wolfentry context.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t wolfentry\\_context\\_exchange](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, struct wolfentry\_context \*wolfentry2)  
*Swaps information between two wolfentry contexts.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t wolfentry\\_centijson\\_errcode\\_translate](#) (wolfentry\_errcode\_t centijson\_errcode)  
*Convert CentiJSON numeric error code to closest-corresponding wolfSentry error code.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t wolfentry\\_config\\_json\\_init](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, [wolfentry\\_config\\_load\\_flags\\_t](#) load\_flags, struct wolfentry\_json\_process\_state \*\*jps)  
*Allocate and initialize a struct wolfentry\_json\_process\_state with the designated load\_flags, to subsequently pass to [wolfentry\\_config\\_json\\_feed\(\)](#).*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t wolfentry\\_config\\_json\\_init\\_ex](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, [wolfentry\\_config\\_load\\_flags\\_t](#) load\_flags, const JSON\_CONFIG \*json\_config, struct wolfentry\_json↵\_process\_state \*\*jps)  
*Variant of [wolfentry\\_config\\_json\\_init\(\)](#) with an additional JSON\_CONFIG argument, json↵\_config, for tailoring of JSON parsing dynamics.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t wolfentry\\_config\\_json\\_feed](#) (struct wolfentry\_json\_process↵\_state \*jps, const unsigned char \*json\_in, size\_t json\_in\_len, char \*err\_buf, size\_t err\_buf\_size)  
*Pass a segment of JSON configuration into the parsing engine. Segments can be as short or as long as desired, to facilitate incremental read-in.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t wolfentry\\_config\\_centijson\\_errcode](#) (struct wolfentry\_json↵\_process\_state \*jps, int \*json\_errcode, const char \*\*json\_errmsg)  
*Copy the current error code and/or human-readable error message from a struct wolfentry\_json↵\_process\_state allocated by [wolfentry\\_config\\_json\\_init\(\)](#).*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t wolfentry\\_config\\_json\\_fini](#) (struct wolfentry\_json\_process↵\_state \*\*jps, char \*err\_buf, size\_t err\_buf\_size)  
*To be called when done iterating [wolfentry\\_config\\_json\\_feed\(\)](#), completing the configuration load.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t wolfentry\\_config\\_json\\_oneshot](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const unsigned char \*json\_in, size\_t json\_in\_len, [wolfentry\\_config\\_load\\_flags\\_t](#) load\_flags, char \*err\_buf, size\_t err\_buf\_size)  
*Load a complete JSON configuration from an in-memory buffer.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t wolfentry\\_config\\_json\\_oneshot\\_ex](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const unsigned char \*json\_in, size\_t json\_in\_len, [wolfentry\\_config\\_load\\_flags\\_t](#) load\_flags, const JSON\_CONFIG \*json\_config, char \*err\_buf, size\_t err\_buf\_size)  
*Variant of [wolfentry\\_config\\_json\\_oneshot\(\)](#) with an additional JSON\_CONFIG argument, json↵\_config, for tailoring of JSON parsing dynamics.*

## 8.2.1 Detailed Description

## 8.2.2 Enumeration Type Documentation

**8.2.2.1 wolfsentry\_clone\_flags\_t**

```
enum wolfsentry_clone_flags_t
```

Flags to be OR'd together to control the dynamics of `wolfsentry_context_clone()` and other cloning functions.

**Enumerator**

WOLFSENTRY_CLONE_FLAG_NONE	Default behavior.
WOLFSENTRY_CLONE_FLAG_AS_AT_CREATION	Don't copy routes, events, or user values, and copy default config as it existed upon return from <code>wolfsentry_init()</code> . Action and address family tables are copied as usual.
WOLFSENTRY_CLONE_FLAG_NO_ROUTES	Don't copy route table entries. Route table config, default config, and all other tables, are copied as usual.

**8.2.2.2 wolfsentry\_config\_load\_flags**

```
enum wolfsentry_config_load_flags
```

Flags to be OR'd together to communicate options to `wolfsentry_config_json_init()`

**Enumerator**

WOLFSENTRY_CONFIG_LOAD_FLAG_NONE	Default behavior.
WOLFSENTRY_CONFIG_LOAD_FLAG_NO_FLUSH	Add to current configuration, rather than replacing it.
WOLFSENTRY_CONFIG_LOAD_FLAG_DRY_RUN	Test the load operation, as modified by other flags, without updating current configuration.
WOLFSENTRY_CONFIG_LOAD_FLAG_LOAD ↵ THEN_COMMIT	Test the load operation before replacing the current configuration.
WOLFSENTRY_CONFIG_LOAD_FLAG_NO ↵ ROUTES_OR_EVENTS	Skip routes and events in the supplied configuration.
WOLFSENTRY_CONFIG_LOAD_FLAG_JSON ↵ DOM_DUPKEY_ABORT	When loading JSON user values, treat as an error when duplicate keys are found.
WOLFSENTRY_CONFIG_LOAD_FLAG_JSON ↵ DOM_DUPKEY_USEFIRST	When loading JSON user values, when duplicate keys are found, keep the first one.
WOLFSENTRY_CONFIG_LOAD_FLAG_JSON ↵ DOM_DUPKEY_USELAST	When loading JSON user values, when duplicate keys are found, keep the last one.
WOLFSENTRY_CONFIG_LOAD_FLAG_JSON ↵ DOM_MAINTAINDICTIONARYORDER	When loading JSON user values, store extra sequence information so that dictionaries are rendered in same sequence by <code>json_dom_dump()</code> and <code>wolfsentry_kv_render_value()</code> .
WOLFSENTRY_CONFIG_LOAD_FLAG_FLUSH ↵ ONLY_ROUTES	Don't flush the events or user values, just flush the routes, before loading incremental configuration JSON.
WOLFSENTRY_CONFIG_LOAD_FLAG_FINI	Internal use.

### 8.2.2.3 wolfentry\_init\_flags\_t

enum `wolfentry_init_flags_t`

flags to pass to `wolfentry_init_ex()`, to be OR'd together.

Enumerator

<code>WOLFENTRY_INIT_FLAG_NONE</code>	Default behavior.
<code>WOLFENTRY_INIT_FLAG_LOCK_SHARED ↔ ERROR_CHECKING</code>	Enables supplementary error checking on shared lock usage (not currently implemented)

## 8.2.3 Function Documentation

### 8.2.3.1 wolfentry\_context\_clone()

```
WOLFENTRY_API wolfentry_errcode_t wolfentry_context_clone (
    WOLFENTRY_CONTEXT_ARGS_IN ,
    struct wolfentry_context ** clone,
    wolfentry_clone_flags_t flags )
```

Clones a wolfentry context.

Parameters

<i>clone</i>	the destination wolfentry context, should be a pointer to a NULL pointer as this function will malloc
<i>flags</i>	set to <code>WOLFENTRY_CLONE_FLAG_AT_CREATION</code> to use the config at the creation of the original wolfentry context instead of the current configuration

Returns

`WOLFENTRY_IS_SUCCESS(ret)` is true on success.

See also

`WOLFENTRY_CONTEXT_ARGS_IN`

### 8.2.3.2 wolfentry\_context\_enable\_actions()

```
WOLFENTRY_API wolfentry_errcode_t wolfentry_context_enable_actions (
    WOLFENTRY_CONTEXT_ARGS_IN )
```

Re-enable automatic dispatch of actions on the wolfentry context.

Returns

`WOLFENTRY_IS_SUCCESS(ret)` is true on success.

See also

`WOLFENTRY_CONTEXT_ARGS_IN`

### 8.2.3.3 `wolfentry_context_exchange()`

```
WOLFENTRY_API wolfentry_errcode_t wolfentry_context_exchange (
    WOLFENTRY_CONTEXT_ARGS_IN ,
    struct wolfentry_context * wolfentry2 )
```

Swaps information between two wolfentry contexts.

#### Parameters

<code>wolfentry2</code>	the new context to swap into the primary context
-------------------------	--

#### Returns

`WOLFENTRY_IS_SUCCESS(ret)` is true on success.

#### See also

[WOLFENTRY\\_CONTEXT\\_ARGS\\_IN](#)

### 8.2.3.4 `wolfentry_context_flush()`

```
WOLFENTRY_API wolfentry_errcode_t wolfentry_context_flush (
    WOLFENTRY_CONTEXT_ARGS_IN )
```

Flushes the route, event, and user value tables from the wolfentry context.

#### Returns

`WOLFENTRY_IS_SUCCESS(ret)` is true on success.

#### See also

[WOLFENTRY\\_CONTEXT\\_ARGS\\_IN](#)

### 8.2.3.5 `wolfentry_context_free()`

```
WOLFENTRY_API wolfentry_errcode_t wolfentry_context_free (
    WOLFENTRY_CONTEXT_ARGS_IN_EX(struct wolfentry_context **wolfentry) )
```

Frees the wolfentry context and the tables within it. The wolfentry context will be a pointer to NULL upon success.

#### Returns

`WOLFENTRY_IS_SUCCESS(ret)` is true, and `*wolfentry` is NULL, on success.

#### See also

`wolfentry_context_shutdown`

[WOLFENTRY\\_CONTEXT\\_ARGS\\_IN\\_EX](#)

### 8.2.3.6 wolfsentry\_context\_inhibit\_actions()

```
WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_context_inhibit_actions (
    WOLFSENTRY_CONTEXT_ARGS_IN )
```

Disable automatic dispatch of actions on the wolfsentry context.

#### Returns

[WOLFSENTRY\\_IS\\_SUCCESS\(ret\)](#) is true on success.

#### See also

[WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#)

### 8.2.3.7 wolfsentry\_defaultconfig\_get()

```
WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_defaultconfig_get (
    WOLFSENTRY_CONTEXT_ARGS_IN ,
    struct wolfsentry_eventconfig * config )
```

Get the default config from a wolfsentry context.

#### Parameters

<i>config</i>	a config struct to be loaded with a copy of the config
---------------	--

#### Returns

[WOLFSENTRY\\_IS\\_SUCCESS\(ret\)](#) is true on success.

### 8.2.3.8 wolfsentry\_defaultconfig\_update()

```
WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_defaultconfig_update (
    WOLFSENTRY_CONTEXT_ARGS_IN ,
    const struct wolfsentry_eventconfig * config )
```

Updates mutable fields of the default config (all but [wolfsentry\\_eventconfig::route\\_private\\_data\\_size](#) and [wolfsentry\\_eventconfig::route\\_private\\_data\\_alignment](#))

#### Parameters

<i>config</i>	the config struct to load from
---------------	--------------------------------

#### Returns

[WOLFSENTRY\\_IS\\_SUCCESS\(ret\)](#) is true on success.

See also

[WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#)

### 8.2.3.9 wolfentry\_init()

```
WOLFSENTRY_API wolfentry_errcode_t wolfentry_init (
    struct wolfentry_build_settings caller_build_settings,
    WOLFSENTRY_CONTEXT_ARGS_IN_EX(const struct wolfentry_host_platform_interface
    *hpi) ,
    const struct wolfentry_eventconfig * config,
    struct wolfentry_context ** wolfentry )
```

Allocates and initializes the wolfentry context.

#### Parameters

<i>caller_build_settings</i>	Pass <a href="#">wolfentry_build_settings</a> here (definition is in <a href="#">wolfentry_settings.h</a> )
<i>config</i>	a pointer to a <a href="#">wolfentry_eventconfig</a> to use (can be NULL)
<i>wolfentry</i>	a pointer to the <a href="#">wolfentry_context</a> to initialize

#### Returns

[WOLFSENTRY\\_IS\\_SUCCESS\(ret\)](#) is true on success.

See also

[struct wolfentry\\_host\\_platform\\_interface](#)  
[WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN\\_EX](#)

### 8.2.3.10 wolfentry\_shutdown()

```
WOLFSENTRY_API wolfentry_errcode_t wolfentry_shutdown (
    WOLFSENTRY_CONTEXT_ARGS_IN_EX(struct wolfentry_context **wolfentry) )
```

Shut down wolfSentry, freeing all resources. Gets an exclusive lock on the context, then calls [wolfentry\\_context\\_free\(\)](#).

#### Returns

[WOLFSENTRY\\_IS\\_SUCCESS\(ret\)](#) is true, and *wolfentry* is NULL, on success.

See also

[wolfentry\\_context\\_free](#)  
[WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN\\_EX](#)

## 8.3 Diagnostics, Control Flow Helpers, and Compiler Attribute Helpers

### Macros

- **#define WOLFSENTRY\_SOURCE\_ID**  
*In each source file in the wolfSentry library, WOLFSENTRY\_SOURCE\_ID is defined to a number that is decoded using `enum wolfentry_source_id`. Application source files that use the below error encoding and rendering macros must also define WOLFSENTRY\_SOURCE\_ID to a number, starting with WOLFSENTRY\_SOURCE\_ID\_USER\_BASE, and can use `wolfentry_user_source_string_set()` or `WOLFSENTRY_REGISTER_SOURCE()` to arrange for error and warning messages that render the source code file by name.*
- **#define WOLFSENTRY\_ERRCODE\_FMT**  
*String-literal macro for formatting `wolfentry_errcode_t` using `printf()`-type functions.*
- **#define WOLFSENTRY\_SOURCE\_ID\_MAX** 127
- **#define WOLFSENTRY\_ERROR\_ID\_MAX** 255
- **#define WOLFSENTRY\_LINE\_NUMBER\_MAX** 65535
- **#define WOLFSENTRY\_ERROR\_DECODE\_ERROR\_CODE(x)**  
*Extract the bare error (negative) or success (zero/positive) code from an encoded `wolfentry_errcode_t`*
- **#define WOLFSENTRY\_ERROR\_DECODE\_SOURCE\_ID(x)**  
*Extract the bare source file ID from an encoded `wolfentry_errcode_t`*
- **#define WOLFSENTRY\_ERROR\_DECODE\_LINE\_NUMBER(x)**  
*Extract the bare source line number from an encoded `wolfentry_errcode_t`*
- **#define WOLFSENTRY\_ERROR\_RECODE(x)**  
*Take an encoded `wolfentry_errcode_t` and recode it with the current source ID and line number.*
- **#define WOLFSENTRY\_ERROR\_CODE\_IS(x, name)**  
*Take an encoded `wolfentry_errcode_t` `x` and test if its error code matches short-form error name (e.g. `INVALID_ARG`).*
- **#define WOLFSENTRY\_SUCCESS\_CODE\_IS(x, name)**  
*Take an encoded `wolfentry_errcode_t` `x` and test if its error code matches short-form success name (e.g. `OK`).*
- **#define WOLFSENTRY\_IS\_FAILURE(x)**  
*Evaluates to true if `x` is a `wolfentry_errcode_t` that encodes a failure.*
- **#define WOLFSENTRY\_IS\_SUCCESS(x)**  
*Evaluates to true if `x` is a `wolfentry_errcode_t` that encodes a success.*
- **#define WOLFSENTRY\_ERROR\_FMT**  
*Convenience string-constant macro for formatting a `wolfentry_errcode_t` for rendering by a `printf`-type function.*
- **#define WOLFSENTRY\_ERROR\_FMT\_ARGS(x)**  
*Convenience macro supplying args to match the format directives in WOLFSENTRY\_ERROR\_FMT.*
- **#define WOLFSENTRY\_ERROR\_ENCODE(name)**  
*Compute a `wolfentry_errcode_t` encoding the current source ID and line number, and the designated short-form error name (e.g. `INVALID_ARG`).*
- **#define WOLFSENTRY\_SUCCESS\_ENCODE(x)**  
*Compute a `wolfentry_errcode_t` encoding the current source ID and line number, and the designated short-form success name (e.g. `OK`).*
- **#define WOLFSENTRY\_DEBUG\_CALL\_TRACE**  
*Define to build the library or application to output codepoint and error code info at each return point.*
- **#define WOLFSENTRY\_ERROR\_RETURN(x)**  
*Return a `wolfentry_errcode_t` encoding the current source ID and line number, and the designated short-form error name (e.g. `INVALID_ARG`).*
- **#define WOLFSENTRY\_SUCCESS\_RETURN(x)**  
*Return a `wolfentry_errcode_t` encoding the current source ID and line number, and the designated short-form success name (e.g. `OK`).*



- **#define WOLFSENTRY\_ERROR\_RETURN\_RECODED(x)**  
Take an encoded `wolfentry_errcode_t`, recode it with the current source ID and line number, and return it.
- **#define WOLFSENTRY\_ERROR\_REReturn(x)**  
Return an encoded `wolfentry_errcode_t`.
- **#define WOLFSENTRY\_RETURN\_VALUE(x)**  
Return an arbitrary value.
- **#define WOLFSENTRY\_RETURN\_VOID**  
Return from a void function.
- **#define WOLFSENTRY\_SUCCESS\_RETURN\_RECODED(x)**  
Take an encoded `wolfentry_errcode_t`, recode it with the current source ID and line number, and return it.
- **#define WOLFSENTRY\_SUCCESS\_REReturn(x)**  
Return an encoded `wolfentry_errcode_t`.
- **#define WOLFSENTRY\_UNLOCK\_FOR\_RETURN\_EX(ctx)**
- **#define WOLFSENTRY\_UNLOCK\_FOR\_RETURN()**  
Unlock a previously locked `wolfentry_context`, and if the unlock fails, return the error.
- **#define WOLFSENTRY\_UNLOCK\_AND\_UNRESERVE\_FOR\_RETURN\_EX(ctx)**
- **#define WOLFSENTRY\_UNLOCK\_AND\_UNRESERVE\_FOR\_RETURN()**  
Unlock a previously locked `wolfentry_context`, and abandon a held promotion reservation if any (see `wolfentry_lock_unlock()`), and if the operation fails, return the error.
- **#define WOLFSENTRY\_MUTEX\_EX(ctx)**  
Get a mutex on a `wolfentry_context`, evaluating to the resulting `wolfentry_errcode_t`.
- **#define WOLFSENTRY\_MUTEX\_OR\_RETURN()**
- **#define WOLFSENTRY\_SHARED\_EX(ctx)**  
Get a mutex on the current context, and on failure, return the `wolfentry_errcode_t`.
- **#define WOLFSENTRY\_SHARED\_OR\_RETURN()**
- **#define WOLFSENTRY\_PROMOTABLE\_EX(ctx)**  
Get a shared lock on the current context, and on failure, return the `wolfentry_errcode_t`.
- **#define WOLFSENTRY\_PROMOTABLE\_OR\_RETURN()**
- **#define WOLFSENTRY\_UNLOCK\_AND\_RETURN(ret)**  
Get a shared lock with mutex promotion reservation on the current context, and on failure, return the `wolfentry_errcode_t`.
- **#define WOLFSENTRY\_ERROR\_UNLOCK\_AND\_RETURN(name)**  
Unlock the current context, and return the supplied `wolfentry_errcode_t`.
- **#define WOLFSENTRY\_ERROR\_UNLOCK\_AND\_RETURN\_RECODED(x)**  
Unlock the current context, then take an encoded `wolfentry_errcode_t x`, recode it with the current source ID and line number, and return it.
- **#define WOLFSENTRY\_ERROR\_UNLOCK\_AND\_RETURN\_EX(ctx, name)**  
Unlock a previously locked `wolfentry_context ctx`, and return a `wolfentry_errcode_t` encoding the current source ID and line number, and the designated short-form error name (e.g. `INVALID_ARG`).
- **#define WOLFSENTRY\_ERROR\_UNLOCK\_AND\_RETURN\_RECODED\_EX(ctx, x)**  
Unlock a previously locked `wolfentry_context ctx`, then take an encoded `wolfentry_errcode_t x`, recode it with the current source ID and line number, and return it.
- **#define WOLFSENTRY\_ERROR\_UNLOCK\_AND\_REReturn(x)**  
Unlock the current context, and return an encoded `wolfentry_errcode_t`.
- **#define WOLFSENTRY\_ERROR\_REReturn\_AND\_UNLOCK(y)**  
Calculate the `wolfentry_errcode_t` return value for an expression `y`, then unlock the current context, and finally, return the encoded `wolfentry_errcode_t`.
- **#define WOLFSENTRY\_SUCCESS\_UNLOCK\_AND\_RETURN(name)**  
Unlock the current context, and return a `wolfentry_errcode_t` encoding the current source ID and line number, and the designated short-form success name (e.g. `INVALID_ARG`).
- **#define WOLFSENTRY\_SUCCESS\_UNLOCK\_AND\_RETURN\_RECODED(x)**  
Unlock the current context, then take an encoded `wolfentry_errcode_t x`, recode it with the current source ID and line number, and return it.

- **#define WOLFSENTRY\_SUCCESS\_UNLOCK\_AND\_RERETURN(x)**  
*Unlock the current context, and return an encoded `wolfentry_errcode_t`.*
- **#define WOLFSENTRY\_SUCCESS\_RERETURN\_AND\_UNLOCK(y)**  
*Calculate the `wolfentry_errcode_t` return value for an expression `y`, then unlock the current context, and finally, return the encoded `wolfentry_errcode_t`.*
- **#define WOLFSENTRY\_UNLOCK\_AND\_RETURN\_VALUE(x)**  
*Unlock the current context, and return a value `x`.*
- **#define WOLFSENTRY\_UNLOCK\_AND\_RETURN\_VOID**  
*Unlock the current context, and return void.*
- **#define WOLFSENTRY\_RETURN\_OK**  
*Return a `wolfentry_errcode_t` encoding the current source ID and line number, and the success code `OK`.*
- **#define WOLFSENTRY\_UNLOCK\_AND\_RETURN\_OK**  
*Unlock the current context, and return a `wolfentry_errcode_t` encoding the current source ID and line number, and the success code `OK`.*
- **#define WOLFSENTRY\_RERETURN\_IF\_ERROR(y)**  
*If `wolfentry_errcode_t y` is a failure code, return it.*
- **#define WOLFSENTRY\_UNLOCK\_AND\_RERETURN\_IF\_ERROR(y)**  
*If `wolfentry_errcode_t y` is a failure code, unlock the current context and return the code.*
- **#define WOLFSENTRY\_WARN(fmt, ...)**  
*Render a warning message using `WOLFSENTRY_PRINTF_ERR()`, or if `WOLFSENTRY_NO_STDIO_STREAMS` or `WOLFSENTRY_NO_DIAG_MSGS` is set, `DO_NOTHING`.*
- **#define WOLFSENTRY\_WARN\_ON\_FAILURE(...)**  
*Evaluate the supplied expression, and if the resulting `wolfentry_errcode_t` encodes an error, render the expression and the decoded error using `WOLFSENTRY_PRINTF_ERR()`, but if `WOLFSENTRY_NO_STDIO_STREAMS` or `WOLFSENTRY_NO_DIAG_MSGS` is set, don't render a warning.*
- **#define WOLFSENTRY\_WARN\_ON\_FAILURE\_LIBC(...)**  
*Evaluate the supplied expression, and if it evaluates to a negative value, render the expression and the decoded `errno` using `WOLFSENTRY_PRINTF_ERR()`, but if `WOLFSENTRY_NO_STDIO_STREAMS` or `WOLFSENTRY_NO_DIAG_MSGS` is set, don't render a warning.*
- **#define WOLFSENTRY\_REGISTER\_SOURCE()**  
*Helper macro to call `wolfentry_user_source_string_set()` with appropriate arguments.*
- **#define WOLFSENTRY\_REGISTER\_ERROR(name, msg)**  
*Helper macro to call `wolfentry_user_error_string_set()` with appropriate arguments, given a short-form `name` and freeform string `msg`.*
- **#define WOLFSENTRY\_PRINTF\_ERR(...)**  
*printf-like macro, expecting a format as first arg, used for rendering warning and error messages. Can be overridden in `WOLFSENTRY_USER_SETTINGS_FILE`.*

## Typedefs

- **typedef int32\_t wolfentry\_errcode\_t**  
*The structured result code type for `wolfSentry`. It encodes a failure or success code, a source code file ID, and a line number.*

## Enumerations

- **enum wolfentry\_source\_id {**  
**WOLFSENTRY\_SOURCE\_ID\_UNSET = 0 ,**  
**WOLFSENTRY\_SOURCE\_ID\_ACTIONS\_C = 1 ,**  
**WOLFSENTRY\_SOURCE\_ID\_EVENTS\_C = 2 ,**  
**WOLFSENTRY\_SOURCE\_ID\_WOLFSENTRY\_INTERNAL\_C = 3 ,**  
**WOLFSENTRY\_SOURCE\_ID\_ROUTES\_C = 4 ,**  
**}**

```

WOLFSENTRY_SOURCE_ID_WOLFSENTRY_UTIL_C = 5 ,
WOLFSENTRY_SOURCE_ID_KV_C = 6 ,
WOLFSENTRY_SOURCE_ID_ADDR_FAMILIES_C = 7 ,
WOLFSENTRY_SOURCE_ID_JSON_LOAD_CONFIG_C = 8 ,
WOLFSENTRY_SOURCE_ID_JSON_JSON_UTIL_C = 9 ,
WOLFSENTRY_SOURCE_ID_LWIP_PACKET_FILTER_GLUE_C = 10 ,
WOLFSENTRY_SOURCE_ID_ACTION_BUILTINS_C = 11 ,
WOLFSENTRY_SOURCE_ID_USER_BASE = 112 }
• enum wolfentry_error_id {
WOLFSENTRY_ERROR_ID_OK = 0 ,
WOLFSENTRY_ERROR_ID_NOT_OK = -1 ,
WOLFSENTRY_ERROR_ID_INTERNAL_CHECK_FATAL = -2 ,
WOLFSENTRY_ERROR_ID_SYS_OP_FATAL = -3 ,
WOLFSENTRY_ERROR_ID_SYS_OP_FAILED = -4 ,
WOLFSENTRY_ERROR_ID_SYS_RESOURCE_FAILED = -5 ,
WOLFSENTRY_ERROR_ID_INCOMPATIBLE_STATE = -6 ,
WOLFSENTRY_ERROR_ID_TIMED_OUT = -7 ,
WOLFSENTRY_ERROR_ID_INVALID_ARG = -8 ,
WOLFSENTRY_ERROR_ID_BUSY = -9 ,
WOLFSENTRY_ERROR_ID_INTERRUPTED = -10 ,
WOLFSENTRY_ERROR_ID_NUMERIC_ARG_TOO_BIG = -11 ,
WOLFSENTRY_ERROR_ID_NUMERIC_ARG_TOO_SMALL = -12 ,
WOLFSENTRY_ERROR_ID_STRING_ARG_TOO_LONG = -13 ,
WOLFSENTRY_ERROR_ID_BUFFER_TOO_SMALL = -14 ,
WOLFSENTRY_ERROR_ID_IMPLEMENTATION_MISSING = -15 ,
WOLFSENTRY_ERROR_ID_ITEM_NOT_FOUND = -16 ,
WOLFSENTRY_ERROR_ID_ITEM_ALREADY_PRESENT = -17 ,
WOLFSENTRY_ERROR_ID_ALREADY_STOPPED = -18 ,
WOLFSENTRY_ERROR_ID_WRONG_OBJECT = -19 ,
WOLFSENTRY_ERROR_ID_DATA_MISSING = -20 ,
WOLFSENTRY_ERROR_ID_NOT_PERMITTED = -21 ,
WOLFSENTRY_ERROR_ID_ALREADY = -22 ,
WOLFSENTRY_ERROR_ID_CONFIG_INVALID_KEY = -23 ,
WOLFSENTRY_ERROR_ID_CONFIG_INVALID_VALUE = -24 ,
WOLFSENTRY_ERROR_ID_CONFIG_OUT_OF_SEQUENCE = -25 ,
WOLFSENTRY_ERROR_ID_CONFIG_UNEXPECTED = -26 ,
WOLFSENTRY_ERROR_ID_CONFIG_MISPLACED_KEY = -27 ,
WOLFSENTRY_ERROR_ID_CONFIG_PARSER = -28 ,
WOLFSENTRY_ERROR_ID_CONFIG_MISSING_HANDLER = -29 ,
WOLFSENTRY_ERROR_ID_CONFIG_JSON_VALUE_SIZE = -30 ,
WOLFSENTRY_ERROR_ID_OP_NOT_SUPP_FOR_PROTO = -31 ,
WOLFSENTRY_ERROR_ID_WRONG_TYPE = -32 ,
WOLFSENTRY_ERROR_ID_BAD_VALUE = -33 ,
WOLFSENTRY_ERROR_ID_DEADLOCK_AVERTED = -34 ,
WOLFSENTRY_ERROR_ID_OVERFLOW_AVERTED = -35 ,
WOLFSENTRY_ERROR_ID_LACKING_MUTEX = -36 ,
WOLFSENTRY_ERROR_ID_LACKING_READ_LOCK = -37 ,
WOLFSENTRY_ERROR_ID_LIB_MISMATCH = -38 ,
WOLFSENTRY_ERROR_ID_LIBCONFIG_MISMATCH = -39 ,
WOLFSENTRY_ERROR_ID_IO_FAILED = -40 ,
WOLFSENTRY_ERROR_ID_WRONG_ATTRIBUTES = -41 ,
WOLFSENTRY_ERROR_ID_USER_BASE = -128 ,
WOLFSENTRY_SUCCESS_ID_OK = 0 ,
WOLFSENTRY_SUCCESS_ID_LOCK_OK_AND_GOT_RESV = 1 ,
WOLFSENTRY_SUCCESS_ID_HAVE_MUTEX = 2 ,
WOLFSENTRY_SUCCESS_ID_HAVE_READ_LOCK = 3 ,
WOLFSENTRY_SUCCESS_ID_USED_FALLBACK = 4 ,
WOLFSENTRY_SUCCESS_ID_YES = 5 ,

```

```
WOLFSENTRY_SUCCESS_ID_NO = 6 ,
WOLFSENTRY_SUCCESS_ID_ALREADY_OK = 7 ,
WOLFSENTRY_SUCCESS_ID_DEFERRED = 8 ,
WOLFSENTRY_SUCCESS_ID_USER_BASE = 128 }
```

## Functions

- WOLFSENTRY\_API const char \* **wolfentry\_errcode\_source\_string** ([wolfentry\\_errcode\\_t](#) e)  
*Return the name of the source code file associated with `wolfentry_errcode_t` e, or "unknown user defined source", or "unknown source".*
- WOLFSENTRY\_API const char \* **wolfentry\_errcode\_error\_string** ([wolfentry\\_errcode\\_t](#) e)  
*Return a description of the failure or success code associated with `wolfentry_errcode_t` e, or various "unknown" strings if not known.*
- WOLFSENTRY\_API const char \* **wolfentry\_errcode\_error\_name** ([wolfentry\\_errcode\\_t](#) e)  
*Return the short name of the failure or success code associated with `wolfentry_errcode_t` e, or `wolfentry_errcode_error_string(e)` if not known.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) **wolfentry\_user\_source\_string\_set** (enum `wolfentry_errcode_t` source\_id `wolfentry_source_id`, const char \*source\_string)  
*Register a source code file so that `wolfentry_errcode_source_string()`, and therefore `WOLFSENTRY_ERROR_FMT_ARGS()` and `WOLFSENTRY_WARN_ON_FAILURE()`, can render it. Note that `source_string` must be a string constant or otherwise remain valid for the duration of runtime.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) **wolfentry\_user\_error\_string\_set** (enum `wolfentry_errcode_t` error\_id `wolfentry_error_id`, const char \*message\_string)  
*Register an error (negative) or success (positive) code, and corresponding message, so that `wolfentry_errcode_error_string()` and therefore `WOLFSENTRY_ERROR_FMT_ARGS()` and `WOLFSENTRY_WARN_ON_FAILURE()`, can render it in human-readable form. Note that `error_string` must be a string constant or otherwise remain valid for the duration of runtime.*

### 8.3.1 Detailed Description

### 8.3.2 Macro Definition Documentation

#### 8.3.2.1 WOLFSENTRY\_DEBUG\_CALL\_TRACE

```
#define WOLFSENTRY_DEBUG_CALL_TRACE
```

Define to build the library or application to output codepoint and error code info at each return point.

In the `wolfSentry` library, and optionally in applications, all returns from functions are through macros, typically `WOLFSENTRY_ERROR_RETURN()`. In normal builds, these macros just return as usual. But if `WOLFSENTRY_DEBUG_CALL_TRACE` is defined, then alternative implementations are used that print trace info, using the `WOLFSENTRY_PRINTF_ERR()` macro, which has platform-specific default definitions in `wolfentry_settings.h`, subject to override.

#### 8.3.2.2 WOLFSENTRY\_ERROR\_UNLOCK\_AND\_RETURN

```
#define WOLFSENTRY_ERROR_UNLOCK_AND_RETURN(  
    name )
```

Unlock the current context, and return the supplied `wolfentry_errcode_t`.

<

Unlock the current context, and return a `wolfentry_errcode_t` encoding the current source ID and line number, and the designated short-form error name (e.g. `INVALID_ARG`).

### 8.3.2.3 WOLFSENTRY\_MUTEX\_OR\_RETURN

```
#define WOLFSENTRY_MUTEX_OR_RETURN( )
```

**Value:**

```
do {
    wolfentry_errcode_t _lock_ret;
    if ((_lock_ret = WOLFSENTRY_MUTEX_EX(wolfentry)) < 0)
        WOLFSENTRY_ERROR_RERETURN(_lock_ret);
} while (0)
```

### 8.3.2.4 WOLFSENTRY\_PROMOTABLE\_EX

```
#define WOLFSENTRY_PROMOTABLE_EX(
    ctx )
```

Get a shared lock on the current context, and on failure, return the `wolfentry_errcode_t`.

<

Get a mutex on a `wolfentry_context`, evaluating to the resulting `wolfentry_errcode_t`.

### 8.3.2.5 WOLFSENTRY\_PROMOTABLE\_OR\_RETURN

```
#define WOLFSENTRY_PROMOTABLE_OR_RETURN( )
```

**Value:**

```
do {
    wolfentry_errcode_t _lock_ret;
    if (thread == NULL)
        _lock_ret = WOLFSENTRY_MUTEX_EX(wolfentry);
    else
        _lock_ret = WOLFSENTRY_PROMOTABLE_EX(wolfentry);
    WOLFSENTRY_RERETURN_IF_ERROR(_lock_ret);
} while (0)
```

### 8.3.2.6 WOLFSENTRY\_SHARED\_EX

```
#define WOLFSENTRY_SHARED_EX(
    ctx )
```

Get a mutex on the current context, and on failure, return the `wolfentry_errcode_t`.

<

Get a shared lock on a `wolfentry_context`, evaluating to the resulting `wolfentry_errcode_t`.

### 8.3.2.7 WOLFSENTRY\_SHARED\_OR\_RETURN

```
#define WOLFSENTRY_SHARED_OR_RETURN( )
```

**Value:**

```
do {
    wolfentry_errcode_t _lock_ret;
    if (thread == NULL)
        _lock_ret = WOLFSENTRY_MUTEX_EX(wolfentry);
    else
        _lock_ret = WOLFSENTRY_SHARED_EX(wolfentry);
    WOLFSENTRY_RERETURN_IF_ERROR(_lock_ret);
} while (0)
```

### 8.3.2.8 WOLFSENTRY\_UNLOCK\_AND\_RETURN

```
#define WOLFSENTRY_UNLOCK_AND_RETURN(  
    ret )
```

Get a shared lock with mutex promotion reservation on the current context, and on failure, return the `wolfentry_errcode_t`.

<

### 8.3.2.9 WOLFSENTRY\_UNLOCK\_AND\_UNRESERVE\_FOR\_RETURN

```
#define WOLFSENTRY_UNLOCK_AND_UNRESERVE_FOR_RETURN( )
```

Unlock a previously locked `wolfentry_context`, and abandon a held promotion reservation if any (see [wolfentry\\_lock\\_unlock\(\)](#)), and if the operation fails, return the error.

<

Unlock the current context, and abandon a held promotion reservation if any (see [wolfentry\\_lock\\_unlock\(\)](#)), and if the operation fails, return the error.

### 8.3.2.10 WOLFSENTRY\_UNLOCK\_AND\_UNRESERVE\_FOR\_RETURN\_EX

```
#define WOLFSENTRY_UNLOCK_AND_UNRESERVE_FOR_RETURN_EX(  
    ctx )
```

Value:

```
do { \
    wolfentry_errcode_t _lock_ret;
    if ((_lock_ret = wolfentry_context_unlock_and_abandon_reservation(ctx, thread)) < 0) { \
        WOLFSENTRY_ERROR_RERETURN(_lock_ret);
    }
} while (0)
```

### 8.3.2.11 WOLFSENTRY\_UNLOCK\_FOR\_RETURN

```
#define WOLFSENTRY_UNLOCK_FOR_RETURN( )
```

Unlock a previously locked `wolfentry_context`, and if the unlock fails, return the error.

<

Unlock the current context, and if the unlock fails, return the error.

### 8.3.2.12 WOLFSENTRY\_UNLOCK\_FOR\_RETURN\_EX

```
#define WOLFSENTRY_UNLOCK_FOR_RETURN_EX(  
    ctx )
```

Value:

```
do { \
    wolfentry_errcode_t _lock_ret;
    if ((_lock_ret = wolfentry_context_unlock(ctx, thread)) < 0) { \
        WOLFSENTRY_ERROR_RERETURN(_lock_ret);
    }
} while (0)
```

## 8.4 Route/Rule Subsystem

### Data Structures

- struct [wolfentry\\_route\\_endpoint](#)  
*struct for exporting socket addresses, with fixed-length fields*
- struct [wolfentry\\_route\\_metadata\\_exports](#)  
*struct for exporting route metadata for access by applications*
- struct [wolfentry\\_route\\_exports](#)  
*struct for exporting a route for access by applications*
- struct [wolfentry\\_sockaddr](#)  
*struct for passing socket addresses into `wolfentry_route_*()` API routines*

### Macros

- #define **WOLFSENTRY\_ROUTE\_DEFAULT\_POLICY\_MASK** ([WOLFSENTRY\\_ACTION\\_RES\\_ACCEPT](#) | [WOLFSENTRY\\_ACTION\\_RES\\_REJECT](#) | [WOLFSENTRY\\_ACTION\\_RES\\_STOP](#) | [WOLFSENTRY\\_ACTION\\_RES\\_ERROR](#))  
*Bit mask spanning the bits allowed by `wolfentry_route_table_default_policy_set()`*
- #define **WOLFSENTRY\_ROUTE\_WILDCARD\_FLAGS**  
*Bit mask for the wildcard bits in a `wolfentry_route_flags_t`.*
- #define **WOLFSENTRY\_ROUTE\_IMMUTABLE\_FLAGS**  
*Bit mask for the bits in a `wolfentry_route_flags_t` that can't change after the implicated route has been inserted in the route table.*
- #define [WOLFSENTRY\\_ROUTE\\_INTERNAL\\_FLAGS](#)
- #define [WOLFSENTRY\\_SOCKADDR](#)(n)

### Enumerations

- enum [wolfentry\\_route\\_flags\\_t](#) {  
[WOLFSENTRY\\_ROUTE\\_FLAG\\_NONE](#) = 0U ,  
[WOLFSENTRY\\_ROUTE\\_FLAG\\_SA\\_FAMILY\\_WILDCARD](#) ,  
[WOLFSENTRY\\_ROUTE\\_FLAG\\_SA\\_REMOTE\\_ADDR\\_WILDCARD](#) ,  
[WOLFSENTRY\\_ROUTE\\_FLAG\\_SA\\_PROTO\\_WILDCARD](#) ,  
[WOLFSENTRY\\_ROUTE\\_FLAG\\_SA\\_LOCAL\\_PORT\\_WILDCARD](#) ,  
[WOLFSENTRY\\_ROUTE\\_FLAG\\_SA\\_LOCAL\\_ADDR\\_WILDCARD](#) ,  
[WOLFSENTRY\\_ROUTE\\_FLAG\\_SA\\_REMOTE\\_PORT\\_WILDCARD](#) ,  
[WOLFSENTRY\\_ROUTE\\_FLAG\\_REMOTE\\_INTERFACE\\_WILDCARD](#) ,  
[WOLFSENTRY\\_ROUTE\\_FLAG\\_LOCAL\\_INTERFACE\\_WILDCARD](#) ,  
[WOLFSENTRY\\_ROUTE\\_FLAG\\_PARENT\\_EVENT\\_WILDCARD](#) ,  
[WOLFSENTRY\\_ROUTE\\_FLAG\\_TCPLIKE\\_PORT\\_NUMBERS](#) ,  
[WOLFSENTRY\\_ROUTE\\_FLAG\\_DIRECTION\\_IN](#) ,  
[WOLFSENTRY\\_ROUTE\\_FLAG\\_DIRECTION\\_OUT](#) ,  
[WOLFSENTRY\\_ROUTE\\_FLAG\\_REMOTE\\_ADDR\\_BITMASK](#) ,  
[WOLFSENTRY\\_ROUTE\\_FLAG\\_LOCAL\\_ADDR\\_BITMASK](#) ,  
[WOLFSENTRY\\_ROUTE\\_FLAG\\_IN\\_TABLE](#) ,  
[WOLFSENTRY\\_ROUTE\\_FLAG\\_PENDING\\_DELETE](#) ,  
[WOLFSENTRY\\_ROUTE\\_FLAG\\_INSERT\\_ACTIONS\\_CALLED](#) ,  
[WOLFSENTRY\\_ROUTE\\_FLAG\\_DELETE\\_ACTIONS\\_CALLED](#) ,  
[WOLFSENTRY\\_ROUTE\\_FLAG\\_PENALTYBOXED](#) ,  
[WOLFSENTRY\\_ROUTE\\_FLAG\\_GREENLISTED](#) ,  
[WOLFSENTRY\\_ROUTE\\_FLAG\\_DONT\\_COUNT\\_HITS](#) ,  
[WOLFSENTRY\\_ROUTE\\_FLAG\\_DONT\\_COUNT\\_CURRENT\\_CONNECTIONS](#) ,  
[WOLFSENTRY\\_ROUTE\\_FLAG\\_PORT\\_RESET](#) }

*bit field specifying attributes of a route/rule*

- enum `wolfentry_format_flags_t` {  
`WOLFENTRY_FORMAT_FLAG_NONE` ,  
`WOLFENTRY_FORMAT_FLAG_ALWAYS_NUMERIC` }

Macro to instantiate a `wolfentry_sockaddr` with an `addr` field sized to hold `n` bits of address data. Cast to `struct wolfentry_sockaddr` to pass as API argument.

## Functions

- WOLFENTRY\_API `wolfentry_errcode_t wolfentry_route_check_flags_sensical` (`wolfentry_route_flags_t` flags)

*Check the self-consistency of flags.*

- WOLFENTRY\_API `wolfentry_errcode_t wolfentry_route_insert_into_table` (`WOLFENTRY_CONTEXT_ARGS_IN`, `struct wolfentry_route_table *route_table`, `void *caller_arg`, `const struct wolfentry_sockaddr *remote`, `const struct wolfentry_sockaddr *local`, `wolfentry_route_flags_t` flags, `const char *event_label`, `int event_label_len`, `wolfentry_ent_id_t *id`, `wolfentry_action_res_t *action_results`)

*Variant of `wolfentry_route_insert()` that takes an explicit `route_table`.*

- WOLFENTRY\_API `wolfentry_errcode_t wolfentry_route_insert_by_exports_into_table` (`WOLFENTRY_CONTEXT_ARGS_IN`, `struct wolfentry_route_table *route_table`, `void *caller_arg`, `const struct wolfentry_route_exports *route_exports`, `wolfentry_ent_id_t *id`, `wolfentry_action_res_t *action_results`)

*Variant of `wolfentry_route_insert()` that accepts the new route as `wolfentry_route_exports`, and takes an explicit `route_table`.*

- WOLFENTRY\_API `wolfentry_errcode_t wolfentry_route_insert` (`WOLFENTRY_CONTEXT_ARGS_IN`, `void *caller_arg`, `const struct wolfentry_sockaddr *remote`, `const struct wolfentry_sockaddr *local`, `wolfentry_route_flags_t` flags, `const char *event_label`, `int event_label_len`, `wolfentry_ent_id_t *id`, `wolfentry_action_res_t *action_results`)

*Insert a route into the route table.*

- WOLFENTRY\_API `wolfentry_errcode_t wolfentry_route_insert_by_exports` (`WOLFENTRY_CONTEXT_ARGS_IN`, `void *caller_arg`, `const struct wolfentry_route_exports *route_exports`, `wolfentry_ent_id_t *id`, `wolfentry_action_res_t *action_results`)

*Variant of `wolfentry_route_insert()` that accepts the new route as `wolfentry_route_exports`.*

- WOLFENTRY\_API `wolfentry_errcode_t wolfentry_route_insert_into_table_and_check_out` (`WOLFENTRY_CONTEXT_ARGS_IN`, `struct wolfentry_route_table *route_table`, `void *caller_arg`, `const struct wolfentry_sockaddr *remote`, `const struct wolfentry_sockaddr *local`, `wolfentry_route_flags_t` flags, `const char *event_label`, `int event_label_len`, `struct wolfentry_route **route`, `wolfentry_action_res_t *action_results`)

*Variant of `wolfentry_route_insert()` that takes an explicit `route_table`, and returns the inserted route, which the caller must eventually drop using `wolfentry_route_drop_reference()` or `wolfentry_object_release()`*

- WOLFENTRY\_API `wolfentry_errcode_t wolfentry_route_insert_by_exports_into_table_and_check_out` (`WOLFENTRY_CONTEXT_ARGS_IN`, `struct wolfentry_route_table *route_table`, `void *caller_arg`, `const struct wolfentry_route_exports *route_exports`, `struct wolfentry_route **route`, `wolfentry_action_res_t *action_results`)

*Variant of `wolfentry_route_insert()` that accepts the new route as `wolfentry_route_exports`, takes an explicit `route_table`, and returns the inserted route, which the caller must eventually drop using `wolfentry_route_drop_reference()` or `wolfentry_object_release()`*

- WOLFENTRY\_API `wolfentry_errcode_t wolfentry_route_insert_and_check_out` (`WOLFENTRY_CONTEXT_ARGS_IN`, `void *caller_arg`, `const struct wolfentry_sockaddr *remote`, `const struct wolfentry_sockaddr *local`, `wolfentry_route_flags_t` flags, `const char *event_label`, `int event_label_len`, `struct wolfentry_route **route`, `wolfentry_action_res_t *action_results`)

*Variant of `wolfentry_route_insert()` that returns the inserted route, which the caller must eventually drop using `wolfentry_route_drop_reference()` or `wolfentry_object_release()`*

- WOLFENTRY\_API `wolfentry_errcode_t wolfentry_route_insert_by_exports_and_check_out` (`WOLFENTRY_CONTEXT_ARGS_IN`, `void *caller_arg`, `const struct wolfentry_route_exports *route_exports`, `struct wolfentry_route **route`, `wolfentry_action_res_t *action_results`)

*Variant of `wolfentry_route_insert()` that accepts the new route as `wolfentry_route_exports` and returns the inserted route, which the caller must eventually drop using `wolfentry_route_drop_reference()` or `wolfentry_object_release()`*



- WOLFSENTRY\_API [wolfentry\\_errcode\\_t wolfentry\\_route\\_delete\\_from\\_table](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, struct wolfentry\_route\_table \*route\_table, void \*caller\_arg, const struct [wolfentry\\_sockaddr](#) \*remote, const struct [wolfentry\\_sockaddr](#) \*local, [wolfentry\\_route\\_flags\\_t](#) flags, const char \*event\_label, int event\_label\_len, [wolfentry\\_action\\_res\\_t](#) \*action\_results, int \*n\_deleted)  
*Variant of [wolfentry\\_route\\_delete\(\)](#) that takes an explicit route\_table.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t wolfentry\\_route\\_delete](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, void \*caller\_arg, const struct [wolfentry\\_sockaddr](#) \*remote, const struct [wolfentry\\_sockaddr](#) \*local, [wolfentry\\_route\\_flags\\_t](#) flags, const char \*trigger\_label, int trigger\_label\_len, [wolfentry\\_action\\_res\\_t](#) \*action\_results, int \*n\_deleted)  
*Delete route from the route table. The supplied parameters, including the flags, must match the route exactly, else ITEM\_NOT\_FOUND will result. To avoid fidgety parameter matching, use [wolfentry\\_route\\_delete\\_by\\_id\(\)](#). The supplied trigger event, if any, is passed to action handlers, and has no bearing on route matching.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t wolfentry\\_route\\_delete\\_by\\_id](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, void \*caller\_arg, [wolfentry\\_ent\\_id\\_t](#) id, const char \*trigger\_label, int trigger\_label\_len, [wolfentry\\_action\\_res\\_t](#) \*action\_results)  
*Delete a route from its route table using its ID. The supplied trigger event, if any, is passed to action handlers, and has no bearing on route matching.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t wolfentry\\_route\\_get\\_main\\_table](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, struct wolfentry\_route\_table \*\*table)  
*Get a pointer to the internal route table. Caller must have a lock on the context at entry.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t wolfentry\\_route\\_table\\_iterate\\_start](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const struct wolfentry\_route\_table \*table, struct wolfentry\_cursor \*\*cursor)  
*Open a cursor to iterate through a routes table. Caller must have a lock on the context at entry.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t wolfentry\\_route\\_table\\_iterate\\_seek\\_to\\_head](#) (const struct wolfentry\_route\_table \*table, struct wolfentry\_cursor \*cursor)  
*Reset the cursor to the beginning of a table.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t wolfentry\\_route\\_table\\_iterate\\_seek\\_to\\_tail](#) (const struct wolfentry\_route\_table \*table, struct wolfentry\_cursor \*cursor)  
*Move the cursor to the end of a table.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t wolfentry\\_route\\_table\\_iterate\\_current](#) (const struct wolfentry\_route\_table \*table, struct wolfentry\_cursor \*cursor, struct wolfentry\_route \*\*route)  
*Get the current position for the table cursor.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t wolfentry\\_route\\_table\\_iterate\\_prev](#) (const struct wolfentry\_route\_table \*table, struct wolfentry\_cursor \*cursor, struct wolfentry\_route \*\*route)  
*Get the previous position for the table cursor.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t wolfentry\\_route\\_table\\_iterate\\_next](#) (const struct wolfentry\_route\_table \*table, struct wolfentry\_cursor \*cursor, struct wolfentry\_route \*\*route)  
*Get the next position for the table cursor.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t wolfentry\\_route\\_table\\_iterate\\_end](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const struct wolfentry\_route\_table \*table, struct wolfentry\_cursor \*\*cursor)  
*Frees the table cursor. Caller must have a lock on the context at entry.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t wolfentry\\_route\\_table\\_default\\_policy\\_set](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, struct wolfentry\_route\_table \*table, [wolfentry\\_action\\_res\\_t](#) default\_policy)  
*Set a table's default policy.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t wolfentry\\_route\\_default\\_policy\\_set](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, [wolfentry\\_action\\_res\\_t](#) default\_policy)  
*variant of [wolfentry\\_route\\_table\\_default\\_policy\\_set\(\)](#) that uses the main route table implicitly, and takes care of context locking.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t wolfentry\\_route\\_table\\_default\\_policy\\_get](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, struct wolfentry\_route\_table \*table, [wolfentry\\_action\\_res\\_t](#) \*default\_policy)  
*Get a table's default policy. Caller must have a lock on the context at entry.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t wolfentry\\_route\\_default\\_policy\\_get](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, [wolfentry\\_action\\_res\\_t](#) \*default\_policy)  
*variant of [wolfentry\\_route\\_table\\_default\\_policy\\_get\(\)](#) that uses the main route table implicitly. Caller must have a lock on the context at entry.*

- WOLFSENTRY\_API [wolfentry\\_errcode\\_t wolfentry\\_route\\_get\\_reference](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const struct wolfentry\_route\_table \*table, const struct [wolfentry\\_sockaddr](#) \*remote, const struct [wolfentry\\_sockaddr](#) \*local, [wolfentry\\_route\\_flags\\_t](#) flags, const char \*event\_label, int event\_label\_len, int exact\_p, [wolfentry\\_route\\_flags\\_t](#) \*inexact\_matches, struct wolfentry\_route \*\*route)  
*Increments a reference counter for a route.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t wolfentry\\_route\\_drop\\_reference](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, struct wolfentry\_route \*route, [wolfentry\\_action\\_res\\_t](#) \*action\_results)  
*Decrease a reference counter for a route.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t wolfentry\\_route\\_table\\_clear\\_default\\_event](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, struct wolfentry\_route\_table \*table)  
*Clear an event previously set by [wolfentry\\_route\\_table\\_set\\_default\\_event\(\)](#).*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t wolfentry\\_route\\_table\\_set\\_default\\_event](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, struct wolfentry\_route\_table \*table, const char \*event\_label, int event\_label\_len)  
*Set an event to be used as a foster parent event for routes with no parent event of their own.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t wolfentry\\_route\\_table\\_get\\_default\\_event](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, struct wolfentry\_route\_table \*table, char \*event\_label, int \*event\_label\_len)  
*Get the event, if any, set by [wolfentry\\_route\\_table\\_set\\_default\\_event\(\)](#)*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t wolfentry\\_route\\_table\\_fallthrough\\_route\\_get](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, struct wolfentry\_route\_table \*route\_table, const struct wolfentry\_route \*\*fallthrough\_route)  
*Retrieve the default route in a route table, chiefly to pass to [wolfentry\\_route\\_update\\_flags\(\)](#).*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t wolfentry\\_route\\_get\\_addrs](#) (const struct wolfentry\_route \*route, [wolfentry\\_addr\\_family\\_t](#) \*af, [wolfentry\\_addr\\_bits\\_t](#) \*local\_addr\_len, const [byte](#) \*\*local\_addr, [wolfentry\\_addr\\_bits\\_t](#) \*remote\_addr\_len, const [byte](#) \*\*remote\_addr)  
*Extract numeric address family and binary address pointers from a [wolfentry\\_route](#)*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t wolfentry\\_route\\_export](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const struct wolfentry\_route \*route, struct [wolfentry\\_route\\_exports](#) \*route\_exports)  
*Exports a route.*
- WOLFSENTRY\_API const struct wolfentry\_event \* [wolfentry\\_route\\_parent\\_event](#) (const struct wolfentry\_route \*route)  
*Get a parent event from a given route. Typically used in the [wolfentry\\_action\\_callback\\_t](#) callback. Note: returned [wolfentry\\_event](#) remains valid only as long as the [wolfentry](#) lock is held (shared or exclusive).*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t wolfentry\\_route\\_event\\_dispatch\\_with\\_table](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, struct wolfentry\_route\_table \*route\_table, const struct [wolfentry\\_sockaddr](#) \*remote, const struct [wolfentry\\_sockaddr](#) \*local, [wolfentry\\_route\\_flags\\_t](#) flags, const char \*event\_label, int event\_label\_len, void \*caller\_arg, [wolfentry\\_ent\\_id\\_t](#) \*id, [wolfentry\\_route\\_flags\\_t](#) \*inexact\_matches, [wolfentry\\_action\\_res\\_t](#) \*action\_results)  
*Variant of [wolfentry\\_route\\_event\\_dispatch\(\)](#) that accepts an explicit [route\\_table](#).*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t wolfentry\\_route\\_event\\_dispatch](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const struct [wolfentry\\_sockaddr](#) \*remote, const struct [wolfentry\\_sockaddr](#) \*local, [wolfentry\\_route\\_flags\\_t](#) flags, const char \*event\_label, int event\_label\_len, void \*caller\_arg, [wolfentry\\_ent\\_id\\_t](#) \*id, [wolfentry\\_route\\_flags\\_t](#) \*inexact\_matches, [wolfentry\\_action\\_res\\_t](#) \*action\_results)  
*Submit an event into [wolfentry](#) and pass it through the filters. The [action\\_results](#) are cleared on entry, and can be checked to see what actions [wolfentry](#) took, and what actions the caller should take (most saliently, [WOLFSENTRY\\_ACTION\\_RES\\_ACCEPT](#) or [WOLFSENTRY\\_ACTION\\_RES\\_REJECT](#)). [action\\_results](#) can be filtered with constructs like [WOLFSENTRY\\_MASKIN\\_BITS\(action\\_results, WOLFSENTRY\\_ACTION\\_RES\\_REJECT\)](#)*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t wolfentry\\_route\\_event\\_dispatch\\_with\\_table\\_with\\_initiated\\_result](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, struct wolfentry\_route\_table \*route\_table, const struct [wolfentry\\_sockaddr](#) \*remote, const struct [wolfentry\\_sockaddr](#) \*local, [wolfentry\\_route\\_flags\\_t](#) flags, const char \*event\_label, int event\_label\_len, void \*caller\_arg, [wolfentry\\_ent\\_id\\_t](#) \*id, [wolfentry\\_route\\_flags\\_t](#) \*inexact\_matches, [wolfentry\\_action\\_res\\_t](#) \*action\_results)  
*Variant of [wolfentry\\_route\\_event\\_dispatch\(\)](#) that accepts an explicit [route\\_table](#), and doesn't clear [action\\_results](#) on entry.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t wolfentry\\_route\\_event\\_dispatch\\_with\\_initiated\\_result](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const struct [wolfentry\\_sockaddr](#) \*remote, const struct [wolfentry\\_sockaddr](#) \*local, [wolfentry\\_route\\_flags\\_t](#) flags, const char \*event\_label, int event\_label\_len, void \*caller\_arg, [wolfentry\\_ent\\_id\\_t](#) \*id, [wolfentry\\_route\\_flags\\_t](#) \*inexact\_matches, [wolfentry\\_action\\_res\\_t](#) \*action\_results)

Variant of `wolfentry_route_event_dispatch()` that doesn't clear `action_results` on entry.

- WOLFENTRY\_API `wolfentry_errcode_t wolfentry_route_event_dispatch_by_id` (`WOLFENTRY_CONTEXT_ARGS_IN`, `wolfentry_ent_id_t` id, const char \*event\_label, int event\_label\_len, void \*caller\_arg, `wolfentry_action_res_t` \*action\_results)

Variant of `wolfentry_route_event_dispatch()` that preselects the matched route by ID, mainly for use by application code that tracks ID/session relationships.

- WOLFENTRY\_API `wolfentry_errcode_t wolfentry_route_event_dispatch_by_id_with_initiated_result` (`WOLFENTRY_CONTEXT_ARGS_IN`, `wolfentry_ent_id_t` id, const char \*event\_label, int event\_label\_len, void \*caller\_arg, `wolfentry_action_res_t` \*action\_results)

Variant of `wolfentry_route_event_dispatch()` that preselects the matched route by ID, and doesn't clear `action_results` on entry, mainly for use by application code that tracks ID/session relationships.

- WOLFENTRY\_API `wolfentry_errcode_t wolfentry_route_event_dispatch_by_route` (`WOLFENTRY_CONTEXT_ARGS_IN`, struct `wolfentry_route` \*route, const char \*event\_label, int event\_label\_len, void \*caller\_arg, `wolfentry_action_res_t` \*action\_results)

Variant of `wolfentry_route_event_dispatch()` that preselects the matched route by ID, mainly for use by application code that tracks route/session relationships.

- WOLFENTRY\_API `wolfentry_errcode_t wolfentry_route_event_dispatch_by_route_with_initiated_result` (`WOLFENTRY_CONTEXT_ARGS_IN`, struct `wolfentry_route` \*route, const char \*event\_label, int event\_label\_len, void \*caller\_arg, `wolfentry_action_res_t` \*action\_results)

Variant of `wolfentry_route_event_dispatch()` that preselects the matched route by ID, and doesn't clear `action_results` on entry, mainly for use by application code that tracks route/session relationships.

- WOLFENTRY\_API `wolfentry_errcode_t wolfentry_route_table_max_purgeable_routes_get` (`WOLFENTRY_CONTEXT_ARGS_IN`, struct `wolfentry_route_table` \*table, `wolfentry_hitcount_t` \*max\_purgeable\_routes)

Retrieve the current limit for ephemeral routes in `table`. Caller must have a lock on the context at entry.

- WOLFENTRY\_API `wolfentry_errcode_t wolfentry_route_table_max_purgeable_routes_set` (`WOLFENTRY_CONTEXT_ARGS_IN`, struct `wolfentry_route_table` \*table, `wolfentry_hitcount_t` max\_purgeable\_routes)

Set the limit for ephemeral routes in `table`. Caller must have a mutex on the context at entry.

- WOLFENTRY\_API `wolfentry_errcode_t wolfentry_route_table_max_purgeable_idle_time_get` (`WOLFENTRY_CONTEXT_ARGS_IN`, struct `wolfentry_route_table` \*table, `wolfentry_time_t` \*max\_purgeable\_idle\_time)

Retrieve the current absolute maximum idle time for a purgeable route (controls forced purges of routes with nonzero `wolfentry_route_metadata_exports.connection_count`). Caller must have a lock on the context at entry.

- WOLFENTRY\_API `wolfentry_errcode_t wolfentry_route_table_max_purgeable_idle_time_set` (`WOLFENTRY_CONTEXT_ARGS_IN`, struct `wolfentry_route_table` \*table, `wolfentry_time_t` max\_purgeable\_idle\_time)

Set the maximum idle time for a purgeable route (controls forced purges of routes with nonzero `wolfentry_route_metadata_exports.connection_count`). Default is no limit. Caller must have a mutex on the context at entry.

- WOLFENTRY\_API `wolfentry_errcode_t wolfentry_route_purge_time_set` (`WOLFENTRY_CONTEXT_ARGS_IN`, struct `wolfentry_route` \*route, `wolfentry_time_t` purge\_after)

Set the time after which `route` in `table` is to be subject to automatic purge. 0 sets the route as persistent. Caller must have a mutex on the context at entry.

- WOLFENTRY\_API `wolfentry_errcode_t wolfentry_route_stale_purge` (`WOLFENTRY_CONTEXT_ARGS_IN`, struct `wolfentry_route_table` \*table, `wolfentry_action_res_t` \*action\_results)

Purges all stale (expired) routes from `table`.

- WOLFENTRY\_API `wolfentry_errcode_t wolfentry_route_stale_purge_one` (`WOLFENTRY_CONTEXT_ARGS_IN`, struct `wolfentry_route_table` \*table, `wolfentry_action_res_t` \*action\_results)

Variant of `wolfentry_route_stale_purge()` that purges at most one stale route, to limit time spent working.

- WOLFENTRY\_API `wolfentry_errcode_t wolfentry_route_stale_purge_one_opportunistically` (`WOLFENTRY_CONTEXT_ARGS_IN`, struct `wolfentry_route_table` \*table, `wolfentry_action_res_t` \*action\_results)

Variant of `wolfentry_route_stale_purge()` that purges at most one stale route, and only if the context lock is uncontended.

- WOLFENTRY\_API `wolfentry_errcode_t wolfentry_route_flush_table` (`WOLFENTRY_CONTEXT_ARGS_IN`, struct `wolfentry_route_table` \*table, `wolfentry_action_res_t` \*action\_results)

Flush routes from a given table.

- WOLFSENTRY\_API [wolfentry\\_errcode\\_t wolfentry\\_route\\_bulk\\_clear\\_insert\\_action\\_status](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, [wolfentry\\_action\\_res\\_t](#) \*action\_results)  
*Clears the [WOLFSENTRY\\_ROUTE\\_FLAG\\_INSERT\\_ACTIONS\\_CALLED](#) flag on all routes in the table.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t wolfentry\\_route\\_bulk\\_insert\\_actions](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, [wolfentry\\_action\\_res\\_t](#) \*action\_results)  
*Executes the insert actions for all routes in the table that don't have [WOLFSENTRY\\_ROUTE\\_FLAG\\_INSERT\\_ACTIONS\\_CALLED](#) set.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t wolfentry\\_route\\_get\\_private\\_data](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, struct [wolfentry\\_route](#) \*route, void \*\*private\_data, size\_t \*private\_data\_size)  
*Gets the private data for a given route.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t wolfentry\\_route\\_get\\_flags](#) (const struct [wolfentry\\_route](#) \*route, [wolfentry\\_route\\_flags\\_t](#) \*flags)  
*Gets the flags for a route.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t wolfentry\\_route\\_get\\_metadata](#) (const struct [wolfentry\\_route](#) \*route, struct [wolfentry\\_route\\_metadata\\_exports](#) \*metadata)  
*Gets the metadata for a route.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t wolfentry\\_route\\_reset\\_metadata\\_exports](#) (struct [wolfentry\\_route\\_exports](#) \*route\_exports)  
*clear metadata counts ([wolfentry\\_route\\_metadata\\_exports::purge\\_after](#), [wolfentry\\_route\\_metadata\\_exports::connection\\_count](#), [wolfentry\\_route\\_metadata\\_exports::derogatory\\_count](#), and [wolfentry\\_route\\_metadata\\_exports::commendable\\_count](#)) in [wolfentry\\_route\\_exports](#) to prepare for use with [wolfentry\\_route\\_insert\\_by\\_exports\(\)](#)*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t wolfentry\\_route\\_update\\_flags](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, struct [wolfentry\\_route](#) \*route, [wolfentry\\_route\\_flags\\_t](#) flags\_to\_set, [wolfentry\\_route\\_flags\\_t](#) flags\_to\_clear, [wolfentry\\_route\\_flags\\_t](#) \*flags\_before, [wolfentry\\_route\\_flags\\_t](#) \*flags\_after, [wolfentry\\_action\\_res\\_t](#) \*action\_results)  
*Update the route flags.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t wolfentry\\_route\\_increment\\_derogatory\\_count](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, struct [wolfentry\\_route](#) \*route, int count\_to\_add, int \*new\_derogatory\_count\_ptr)  
*Increase the derogatory event count of a route.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t wolfentry\\_route\\_increment\\_commendable\\_count](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, struct [wolfentry\\_route](#) \*route, int count\_to\_add, int \*new\_commendable\_count)  
*Increase the commendable event count of a route.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t wolfentry\\_route\\_reset\\_derogatory\\_count](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, struct [wolfentry\\_route](#) \*route, int \*old\_derogatory\_count\_ptr)  
*Reset the derogatory event count of a route.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t wolfentry\\_route\\_reset\\_commendable\\_count](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, struct [wolfentry\\_route](#) \*route, int \*old\_commendable\_count\_ptr)  
*Reset the commendable event count of a route.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t wolfentry\\_route\\_set\\_wildcard](#) (struct [wolfentry\\_route](#) \*route, [wolfentry\\_route\\_flags\\_t](#) wildcards\_to\_set)  
*Set wildcard flags for a route.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t wolfentry\\_route\\_format\\_address](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, [wolfentry\\_addr\\_family\\_t](#) sa\_family, const byte \*addr, unsigned int addr\_bits, char \*buf, int \*buflen)  
*Render a binary address in human-readable form to a buffer.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t wolfentry\\_route\\_flag\\_assoc\\_by\\_flag](#) ([wolfentry\\_route\\_flags\\_t](#) flag, const char \*\*name)  
*Retrieve the name of a route flag, given its numeric value. Note that `flag` must have exactly one bit set, else `ITEM_NOT_FOUND` will be returned.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t wolfentry\\_route\\_flag\\_assoc\\_by\\_name](#) (const char \*name, int len, [wolfentry\\_route\\_flags\\_t](#) \*flag)  
*Retrieve the numeric value of a route flag, given its name.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t wolfentry\\_route\\_format\\_json](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const struct [wolfentry\\_route](#) \*r, unsigned char \*\*json\_out, size\_t \*json\_out\_len, [wolfentry\\_format\\_flags\\_t](#) flags)

Render a route to an output buffer, in JSON format, advancing the output buffer pointer by the length of the rendered output.

- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_route\\_table\\_dump\\_json\\_start](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const struct wolfentry\_route\_table \*table, struct wolfentry\_cursor \*\*cursor, unsigned char \*\*json\_out, size\_t \*json\_out\_len, [wolfentry\\_format\\_flags\\_t](#) flags)

Start a rendering loop to export the route table contents as a JSON document that is valid input for [wolfentry\\_config\\_json\\_feed\(\)](#) or [wolfentry\\_config\\_json\\_oneshot\(\)](#), advancing the output buffer pointer by the length of the rendered output, and decrementing `json_out_len` by the same amount. Caller must have a shared or exclusive lock on the context at entry.

- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_route\\_table\\_dump\\_json\\_next](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const struct wolfentry\_route\_table \*table, struct wolfentry\_cursor \*cursor, unsigned char \*\*json\_out, size\_t \*json\_out\_len, [wolfentry\\_format\\_flags\\_t](#) flags)

Render a route within a loop started with [wolfentry\\_route\\_table\\_dump\\_json\\_start\(\)](#), advancing the output buffer pointer by the length of the rendered output, and decrementing `json_out_len` by the same amount.

- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_route\\_table\\_dump\\_json\\_end](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const struct wolfentry\_route\_table \*table, struct wolfentry\_cursor \*\*cursor, unsigned char \*\*json\_out, size\_t \*json\_out\_len, [wolfentry\\_format\\_flags\\_t](#) flags)

Finish a rendering loop started with [wolfentry\\_route\\_table\\_dump\\_json\\_start\(\)](#), advancing the output buffer pointer by the length of the rendered output, and decrementing `json_out_len` by the same amount.

- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_route\\_render\\_flags](#) ([wolfentry\\_route\\_flags\\_t](#) flags, FILE \*f)

Render route flags in human-readable form to a stream.

- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_route\\_render](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const struct wolfentry\_route \*r, FILE \*f)

Renders route information to a file pointer.

- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_route\\_exports\\_render](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const struct [wolfentry\\_route\\_exports](#) \*r, FILE \*f)

Renders route exports information to a file pointer.

## 8.4.1 Detailed Description

## 8.4.2 Macro Definition Documentation

### 8.4.2.1 WOLFSENTRY\_ROUTE\_INTERNAL\_FLAGS

```
#define WOLFSENTRY_ROUTE_INTERNAL_FLAGS
```

Value:

```
((wolfentry_route_flags_t) \
(WOLFSENTRY_ROUTE_FLAG_IN_TABLE | \
 WOLFSENTRY_ROUTE_FLAG_PENDING_DELETE | \
 WOLFSENTRY_ROUTE_FLAG_INSERT_ACTIONS_CALLED | \
 WOLFSENTRY_ROUTE_FLAG_DELETE_ACTIONS_CALLED))
```

### 8.4.2.2 WOLFSENTRY\_SOCKADDR

```
#define WOLFSENTRY_SOCKADDR(
    n )
```

Value:

```
struct {
    wolfentry_addr_family_t sa_family;
    wolfentry_proto_t sa_proto;
    wolfentry_port_t sa_port;
    wolfentry_addr_bits_t addr_len;
    byte interface;
    attr_align_to(4) byte addr[WOLFSENTRY_BITS_TO_BYTES(n)];
}
```



### 8.4.3 Enumeration Type Documentation

#### 8.4.3.1 wolfsentry\_format\_flags\_t

enum `wolfsentry_format_flags_t`

Macro to instantiate a `wolfsentry_sockaddr` with an `addr` field sized to hold `n` bits of address data. Cast to `struct wolfsentry_sockaddr` to pass as API argument.

<

bit field with options for rendering

Enumerator

WOLFSENTRY_FORMAT_FLAG_NONE	Default rendering behavior.
WOLFSENTRY_FORMAT_FLAG_ALWAYS_↔ NUMERIC	When rendering address families and protocols, always render as bare integers. Currently honored by <code>wolfsentry_route_format_json()</code> .

#### 8.4.3.2 wolfsentry\_route\_flags\_t

enum `wolfsentry_route_flags_t`

bit field specifying attributes of a route/rule

Enumerator

WOLFSENTRY_ROUTE_FLAG_NONE	No attributes
WOLFSENTRY_ROUTE_FLAG_SA_FAMILY_↔ WILDCARD	Address family is wildcard – match all traffic in specified direction(s), optionally with specified interfaces.
WOLFSENTRY_ROUTE_FLAG_SA_REMOTE_↔ ADDR_WILDCARD	Remote address is wildcard – match any remote address.
WOLFSENTRY_ROUTE_FLAG_SA_PROTO_↔ WILDCARD	Protocol is wildcard – match any protocol.
WOLFSENTRY_ROUTE_FLAG_SA_LOCAL_↔ PORT_WILDCARD	Local port is wildcard – match any local port.
WOLFSENTRY_ROUTE_FLAG_SA_LOCAL_↔ ADDR_WILDCARD	Local address is wildcard – match any local address.
WOLFSENTRY_ROUTE_FLAG_SA_REMOTE_↔ PORT_WILDCARD	Remote port is wildcard – match any remote port.
WOLFSENTRY_ROUTE_FLAG_REMOTE_↔ INTERFACE_WILDCARD	Ingestion interface is wildcard – match any ingestion interface.
WOLFSENTRY_ROUTE_FLAG_LOCAL_↔ INTERFACE_WILDCARD	Local interface (usually same as remote interface) is wildcard – match any local interface.
WOLFSENTRY_ROUTE_FLAG_PARENT_EVENT_↔ _WILDCARD	Match regardless of parent event mismatch.
WOLFSENTRY_ROUTE_FLAG_TCPLIKE_PORT_↔ _NUMBERS	Interpret port names using TCP/UDP mappings (available unless build option <code>WOLFSENTRY_NO_GETPROTOBY</code> is defined)
WOLFSENTRY_ROUTE_FLAG_DIRECTION_IN	Match inbound traffic.

## Enumerator

WOLFSENTRY_ROUTE_FLAG_DIRECTION_OUT	Match outbound traffic (if <a href="#">WOLFSENTRY_ROUTE_FLAG_DIRECTION_IN</a> and <a href="#">WOLFSENTRY_ROUTE_FLAG_DIRECTION_OUT</a> are both set, traffic in both directions is matched)
WOLFSENTRY_ROUTE_FLAG_REMOTE_ADDR↔ _BITMASK	Supplied remote address consists of an address followed by a bitmask, and its <code>addr_len</code> is the total bit count for the address and mask. The bit count for the address and bitmask must be equal, and each must be a multiple of 8, i.e. aligned to a byte boundary. Matching will be performed by checking that masked addresses are equal.
WOLFSENTRY_ROUTE_FLAG_LOCAL_ADDR↔ _BITMASK	Supplied local address consists of an address followed by a bitmask, and its <code>addr_len</code> is the total bit count for the address and mask. The bit count for the address and bitmask must be equal, and each must be a multiple of 8, i.e. aligned to a byte boundary. Matching will be performed by checking that masked addresses are equal.
WOLFSENTRY_ROUTE_FLAG_IN_TABLE	Internal use – marks route as resident in table.
WOLFSENTRY_ROUTE_FLAG_PENDING_DELETE	Internal use – marks route as deleted.
WOLFSENTRY_ROUTE_FLAG_INSERT↔ ACTIONS_CALLED	Internal use – records that route insertion actions have been completed.
WOLFSENTRY_ROUTE_FLAG_DELETE↔ ACTIONS_CALLED	Internal use – records that route deletion actions have been completed.
WOLFSENTRY_ROUTE_FLAG_PENALTYBOXED	Traffic that matches a route with this flag set will be rejected.
WOLFSENTRY_ROUTE_FLAG_GREENLISTED	Traffic that matches a route with this flag set will be accepted.
WOLFSENTRY_ROUTE_FLAG_DONT_COUNT↔ HITS	Don't keep traffic statistics for this rule (avoid counting overhead)
WOLFSENTRY_ROUTE_FLAG_DONT_COUNT↔ CURRENT_CONNECTIONS	Don't keep concurrent connection count for this rule (don't impose connection limit, even if set in the applicable <a href="#">wolfentry_eventconfig</a> )
WOLFSENTRY_ROUTE_FLAG_PORT_RESET	If traffic is rejected by this rule, set <a href="#">WOLFSENTRY_ACTION_RES_PORT_RESET</a> in the returned <a href="#">wolfentry_action_res_t</a> , prompting generation by the network stack of a TCP reset, ICMP unreachable, or other applicable reply packet.

## 8.4.4 Function Documentation

8.4.4.1 `wolfentry_route_bulk_clear_insert_action_status()`

```
WOLFSENTRY_API wolfentry_errcode_t wolfentry_route_bulk_clear_insert_action_status (
    WOLFSENTRY_CONTEXT_ARGS_IN ,
    wolfentry_action_res_t * action_results )
```

Clears the [WOLFSENTRY\\_ROUTE\\_FLAG\\_INSERT\\_ACTIONS\\_CALLED](#) flag on all routes in the table.

**Returns**

[WOLFSENTRY\\_IS\\_SUCCESS\(ret\)](#) is true on success.

**See also**

[wolfentry\\_route\\_bulk\\_insert\\_actions\(\)](#)

[WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#)

**8.4.4.2 wolfentry\_route\_bulk\_insert\_actions()**

```
WOLFSENTRY_API wolfentry_errcode_t wolfentry_route_bulk_insert_actions (
    WOLFSENTRY_CONTEXT_ARGS_IN ,
    wolfentry_action_res_t * action_results )
```

Executes the insert actions for all routes in the table that don't have [WOLFSENTRY\\_ROUTE\\_FLAG\\_INSERT\\_ACTIONS\\_CALLED](#) set.

**Returns**

[WOLFSENTRY\\_IS\\_SUCCESS\(ret\)](#) is true on success.

**See also**

[wolfentry\\_route\\_bulk\\_clear\\_insert\\_action\\_status\(\)](#)

[WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#)

**8.4.4.3 wolfentry\_route\_delete()**

```
WOLFSENTRY_API wolfentry_errcode_t wolfentry_route_delete (
    WOLFSENTRY_CONTEXT_ARGS_IN ,
    void * caller_arg,
    const struct wolfentry_sockaddr * remote,
    const struct wolfentry_sockaddr * local,
    wolfentry_route_flags_t flags,
    const char * trigger_label,
    int trigger_label_len,
    wolfentry_action_res_t * action_results,
    int * n_deleted )
```

Delete route from the route table. The supplied parameters, including the flags, must match the route exactly, else `ITEM_NOT_FOUND` will result. To avoid fidgety parameter matching, use [wolfentry\\_route\\_delete\\_by\\_id\(\)](#). The supplied trigger event, if any, is passed to action handlers, and has no bearing on route matching.

**Parameters**

<i>caller_arg</i>	an arbitrary pointer to be passed to callbacks
<i>remote</i>	the remote sockaddr for the route
<i>local</i>	the local sockaddr for the route
<i>flags</i>	flags for the route
<i>trigger_label</i>	a label for the trigger event (or null)
<i>trigger_label_len</i>	the length of the <i>trigger_label</i> parameter
<i>action_results</i>	a pointer to results of the insert action – all bits are cleared on entry.
<i>n_deleted</i>	a counter for the number of entries deleted



## Returns

[WOLFSENTRY\\_IS\\_SUCCESS\(ret\)](#) is true on success.

## See also

[WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#)

8.4.4.4 `wolfentry_route_delete_by_id()`

```
WOLFSENTRY_API wolfentry_errcode_t wolfentry_route_delete_by_id (
    WOLFSENTRY_CONTEXT_ARGS_IN ,
    void * caller_arg,
    wolfentry_ent_id_t id,
    const char * trigger_label,
    int trigger_label_len,
    wolfentry_action_res_t * action_results )
```

Delete a route from its route table using its ID. The supplied trigger event, if any, is passed to action handlers, and has no bearing on route matching.

## Parameters

<i>caller_arg</i>	an arbitrary pointer to be passed to callbacks
<i>id</i>	the object ID, as returned by <a href="#">wolfentry_route_insert()</a> or <a href="#">wolfentry_get_object_id()</a>
<i>trigger_label</i>	a label for a trigger event (or null)
<i>trigger_label_len</i>	the length of the <i>trigger_label</i> parameter
<i>action_results</i>	a pointer to results of the insert action – all bits are cleared on entry.

## Returns

[WOLFSENTRY\\_IS\\_SUCCESS\(ret\)](#) is true on success.

## See also

[WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#)

8.4.4.5 `wolfentry_route_drop_reference()`

```
WOLFSENTRY_API wolfentry_errcode_t wolfentry_route_drop_reference (
    WOLFSENTRY_CONTEXT_ARGS_IN ,
    struct wolfentry_route * route,
    wolfentry_action_res_t * action_results )
```

Decrease a reference counter for a route.

## Parameters

<i>route</i>	the route to drop the reference for
<i>action_results</i>	a pointer to results of the action

**Returns**

[WOLFSENTRY\\_IS\\_SUCCESS\(ret\)](#) is true on success.

**See also**

[WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#)

**8.4.4.6 wolfentry\_route\_event\_dispatch()**

```
WOLFSENTRY_API wolfentry_errcode_t wolfentry_route_event_dispatch (
    WOLFSENTRY_CONTEXT_ARGS_IN ,
    const struct wolfentry_sockaddr * remote,
    const struct wolfentry_sockaddr * local,
    wolfentry_route_flags_t flags,
    const char * event_label,
    int event_label_len,
    void * caller_arg,
    wolfentry_ent_id_t * id,
    wolfentry_route_flags_t * inexact_matches,
    wolfentry_action_res_t * action_results )
```

Submit an event into wolfentry and pass it through the filters. The `action_results` are cleared on entry, and can be checked to see what actions wolfentry took, and what actions the caller should take (most saliently, [WOLFSENTRY\\_ACTION\\_RES\\_ACCEPT](#) or [WOLFSENTRY\\_ACTION\\_RES\\_REJECT](#)). `action_results` can be filtered with constructs like [WOLFSENTRY\\_MASKIN\\_BITS\(action\\_results, WOLFSENTRY\\_ACTION\\_RES\\_REJECT\)](#)

**Parameters**

<i>remote</i>	the remote sockaddr details
<i>local</i>	the local sockaddr details
<i>flags</i>	the flags for the event, set to <a href="#">WOLFSENTRY_ROUTE_FLAG_DIRECTION_IN</a> for an incoming event
<i>event_label</i>	an optional label for a trigger event
<i>event_label_len</i>	the length of <code>event_label</code>
<i>caller_arg</i>	an arbitrary pointer to be passed to action callbacks
<i>id</i>	an optional pointer to a <a href="#">wolfentry_ent_id_t</a> that will be set to the ID of the matched route, if any
<i>inexact_matches</i>	details for inexact matches
<i>action_results</i>	a pointer to a <a href="#">wolfentry_action_res_t</a> , which will be used to record actions taken and to be taken

**Returns**

[WOLFSENTRY\\_IS\\_SUCCESS\(ret\)](#) is true on success.

**See also**

[WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#)

#### 8.4.4.7 wolfsentry\_route\_export()

```
WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_route_export (
    WOLFSENTRY_CONTEXT_ARGS_IN ,
    const struct wolfsentry_route * route,
    struct wolfsentry_route_exports * route_exports )
```

Exports a route.

`route_exports` remains valid only as long as the wolfsentry lock is held (shared or exclusive), unless the route was obtained via [wolfsentry\\_route\\_get\\_reference\(\)](#), in which case it's valid until [wolfsentry\\_route\\_drop\\_reference\(\)](#).

##### Parameters

<i>route</i>	the route to export
<i>route_exports</i>	the struct to export into

##### Returns

[WOLFSENTRY\\_IS\\_SUCCESS\(ret\)](#) is true on success.

##### See also

[WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#)

#### 8.4.4.8 wolfsentry\_route\_exports\_render()

```
WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_route_exports_render (
    WOLFSENTRY_CONTEXT_ARGS_IN ,
    const struct wolfsentry_route_exports * r,
    FILE * f )
```

Renders route exports information to a file pointer.

##### Parameters

<i>r</i>	the route exports to render
<i>f</i>	the pointer to render to

##### Returns

[WOLFSENTRY\\_IS\\_SUCCESS\(ret\)](#) is true on success.

##### See also

[WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#)

#### 8.4.4.9 wolfsentry\_route\_flush\_table()

```
WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_route_flush_table (
    WOLFSENTRY_CONTEXT_ARGS_IN ,
    struct wolfsentry_route_table * table,
    wolfsentry_action_res_t * action_results )
```

Flush routes from a given table.

##### Parameters

<i>table</i>	the table to purge
<i>action_results</i>	the result bit field, pooling results from all constituent operations

##### Returns

[WOLFSENTRY\\_IS\\_SUCCESS\(ret\)](#) is true on success.

##### See also

[WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#)

#### 8.4.4.10 wolfsentry\_route\_get\_addrs()

```
WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_route_get_addrs (
    const struct wolfsentry_route * route,
    wolfsentry_addr_family_t * af,
    wolfsentry_addr_bits_t * local_addr_len,
    const byte ** local_addr,
    wolfsentry_addr_bits_t * remote_addr_len,
    const byte ** remote_addr )
```

Extract numeric address family and binary address pointers from a `wolfsentry_route`

`local_addr` and `remote_addr` remain valid only as long as the `wolfsentry` lock is held (shared or exclusive), unless the route was obtained via [wolfsentry\\_route\\_get\\_reference\(\)](#), in which case it's valid until [wolfsentry\\_route\\_drop\\_reference\(\)](#).

#### 8.4.4.11 wolfsentry\_route\_get\_flags()

```
WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_route_get_flags (
    const struct wolfsentry_route * route,
    wolfsentry_route_flags_t * flags )
```

Gets the flags for a route.

##### Parameters

<i>route</i>	the route to get the flags for
<i>flags</i>	a pointer to receive the flags

## Returns

[WOLFSENTRY\\_IS\\_SUCCESS\(ret\)](#) is true on success.

**8.4.4.12 wolfentry\_route\_get\_main\_table()**

```
WOLFSENTRY_API wolfentry_errcode_t wolfentry_route_get_main_table (
    WOLFSENTRY_CONTEXT_ARGS_IN ,
    struct wolfentry_route_table ** table )
```

Get a pointer to the internal route table. Caller must have a lock on the context at entry.

## Parameters

<i>table</i>	a pointer to a pointer to a table which will be filled
--------------	--

## Returns

[WOLFSENTRY\\_IS\\_SUCCESS\(ret\)](#) is true on success.

## See also

[WOLFSENTRY\\_SHARED\\_OR\\_RETURN\(\)](#)  
[WOLFSENTRY\\_UNLOCK\\_AND\\_RETURN\(\)](#)  
[WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#)

**8.4.4.13 wolfentry\_route\_get\_metadata()**

```
WOLFSENTRY_API wolfentry_errcode_t wolfentry_route_get_metadata (
    const struct wolfentry_route * route,
    struct wolfentry_route_metadata_exports * metadata )
```

Gets the metadata for a route.

## Parameters

<i>route</i>	the route to get the metadata for
<i>metadata</i>	a pointer to a pointer to receive the metadata

## Returns

[WOLFSENTRY\\_IS\\_SUCCESS\(ret\)](#) is true on success.

**8.4.4.14 wolfentry\_route\_get\_private\_data()**

```
WOLFSENTRY_API wolfentry_errcode_t wolfentry_route_get_private_data (
    WOLFSENTRY_CONTEXT_ARGS_IN ,
```

```

struct wolfentry_route * route,
void ** private_data,
size_t * private_data_size )

```

Gets the private data for a given route.

#### Parameters

<i>route</i>	the route to get the data from
<i>private_data</i>	a pointer to a pointer that will receive the data
<i>private_data_size</i>	a pointer that will receive the size of the data

#### Returns

[WOLFENTRY\\_IS\\_SUCCESS\(ret\)](#) is true on success.

#### See also

[WOLFENTRY\\_CONTEXT\\_ARGS\\_IN](#)

#### 8.4.4.15 wolfentry\_route\_get\_reference()

```

WOLFENTRY_API wolfentry_errcode_t wolfentry_route_get_reference (
    WOLFENTRY_CONTEXT_ARGS_IN ,
    const struct wolfentry_route_table * table,
    const struct wolfentry_sockaddr * remote,
    const struct wolfentry_sockaddr * local,
    wolfentry_route_flags_t flags,
    const char * event_label,
    int event_label_len,
    int exact_p,
    wolfentry_route_flags_t * inexact_matches,
    struct wolfentry_route ** route )

```

Increments a reference counter for a route.

#### Parameters

<i>table</i>	the table to get the route from
<i>remote</i>	the remote sockaddr
<i>local</i>	the local sockaddr
<i>flags</i>	flags for the route
<i>event_label</i>	a label for the event
<i>event_label_len</i>	the length of the event_label parameter
<i>exact_p</i>	set to 1 for exact matches only
<i>inexact_matches</i>	wildcard flags hit
<i>route</i>	the route returned

## Returns

[WOLFSENTRY\\_IS\\_SUCCESS\(ret\)](#) is true on success.

## See also

[WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#)

**8.4.4.16 wolfentry\_route\_insert()**

```
WOLFSENTRY_API wolfentry_errcode_t wolfentry_route_insert (
    WOLFSENTRY_CONTEXT_ARGS_IN ,
    void * caller_arg,
    const struct wolfentry_sockaddr * remote,
    const struct wolfentry_sockaddr * local,
    wolfentry_route_flags_t flags,
    const char * event_label,
    int event_label_len,
    wolfentry_ent_id_t * id,
    wolfentry_action_res_t * action_results )
```

Insert a route into the route table.

## Parameters

<i>caller_arg</i>	an arbitrary pointer to be passed to callbacks
<i>remote</i>	the remote sockaddr for the route
<i>local</i>	the local sockaddr for the route
<i>flags</i>	flags for the route
<i>event_label</i>	a label for the route
<i>event_label_len</i>	the length of the event_label parameter
<i>id</i>	the object ID
<i>action_results</i>	a pointer to results of the insert action

## Returns

[WOLFSENTRY\\_IS\\_SUCCESS\(ret\)](#) is true on success.

## See also

[WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#)

**8.4.4.17 wolfentry\_route\_parent\_event()**

```
WOLFSENTRY_API const struct wolfentry_event * wolfentry_route_parent_event (
    const struct wolfentry_route * route )
```

Get a parent event from a given route. Typically used in the `wolfentry_action_callback_t` callback. Note: returned `wolfentry_event` remains valid only as long as the wolfentry lock is held (shared or exclusive).

**Parameters**

<i>route</i>	a pointer to the route
--------------	------------------------

**Returns**

a pointer to the parent event

**See also**

[WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#)

**8.4.4.18 wolfentry\_route\_render()**

```
WOLFSENTRY_API wolfentry_errcode_t wolfentry_route_render (
    WOLFSENTRY_CONTEXT_ARGS_IN ,
    const struct wolfentry_route * r,
    FILE * f )
```

Renders route information to a file pointer.

**Parameters**

<i>r</i>	the route to render
<i>f</i>	the pointer to render to

**Returns**

[WOLFSENTRY\\_IS\\_SUCCESS\(ret\)](#) is true on success.

**See also**

[WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#)

**8.4.4.19 wolfentry\_route\_set\_wildcard()**

```
WOLFSENTRY_API wolfentry_errcode_t wolfentry_route_set_wildcard (
    struct wolfentry_route * route,
    wolfentry_route_flags_t wildcards_to_set )
```

Set wildcard flags for a route.

**Parameters**

<i>route</i>	the route to set the flags for
<i>wildcards_to_set</i>	the wildcards to be set



## Returns

[WOLFENTRY\\_IS\\_SUCCESS\(ret\)](#) is true on success.

**8.4.4.20 wolfentry\_route\_stale\_purge()**

```
WOLFENTRY_API wolfentry_errcode_t wolfentry_route_stale_purge (
    WOLFENTRY_CONTEXT_ARGS_IN ,
    struct wolfentry_route_table * table,
    wolfentry_action_res_t * action_results )
```

Purges all stale (expired) routes from `table`.

## Parameters

<i>table</i>	the table to purge from
<i>action_results</i>	the result bit field, pooling results from all constituent operations

## Returns

[WOLFENTRY\\_IS\\_SUCCESS\(ret\)](#) is true on success.

## See also

[WOLFENTRY\\_CONTEXT\\_ARGS\\_IN](#)

**8.4.4.21 wolfentry\_route\_table\_default\_policy\_get()**

```
WOLFENTRY_API wolfentry_errcode_t wolfentry_route_table_default_policy_get (
    WOLFENTRY_CONTEXT_ARGS_IN ,
    struct wolfentry_route_table * table,
    wolfentry_action_res_t * default_policy )
```

Get a table's default policy. Caller must have a lock on the context at entry.

## Parameters

<i>table</i>	the table to set the policy for
<i>default_policy</i>	the policy retrieved

## Returns

[WOLFENTRY\\_IS\\_SUCCESS\(ret\)](#) is true on success.

## See also

[wolfentry\\_defaultconfig\\_update\(\)](#)  
[WOLFENTRY\\_SHARED\\_OR\\_RETURN\(\)](#)  
[WOLFENTRY\\_UNLOCK\\_AND\\_RETURN\(\)](#)  
[WOLFENTRY\\_CONTEXT\\_ARGS\\_IN](#)

#### 8.4.4.22 `wolfentry_route_table_default_policy_set()`

```
WOLFENTRY_API wolfentry_errcode_t wolfentry_route_table_default_policy_set (
    WOLFENTRY_CONTEXT_ARGS_IN ,
    struct wolfentry_route_table * table,
    wolfentry_action_res_t default_policy )
```

Set a table's default policy.

##### Parameters

<i>table</i>	the table to set the policy for
<i>default_policy</i>	the policy to set

##### Returns

[WOLFENTRY\\_IS\\_SUCCESS\(ret\)](#) is true on success.

##### See also

[WOLFENTRY\\_CONTEXT\\_ARGS\\_IN](#)

#### 8.4.4.23 `wolfentry_route_table_fallthrough_route_get()`

```
WOLFENTRY_API wolfentry_errcode_t wolfentry_route_table_fallthrough_route_get (
    WOLFENTRY_CONTEXT_ARGS_IN ,
    struct wolfentry_route_table * route_table,
    const struct wolfentry_route ** fallthrough_route )
```

Retrieve the default route in a route table, chiefly to pass to [wolfentry\\_route\\_update\\_flags\(\)](#).

Caller must have a shared or mutex lock on the context at entry, but can release the lock on return and safely continue to access or update the route. Caller must drop the route when done, using [wolfentry\\_route\\_drop\\_reference\(\)](#) or [wolfentry\\_object\\_release\(\)](#).

##### See also

[WOLFENTRY\\_SHARED\\_OR\\_RETURN\(\)](#)

[WOLFENTRY\\_UNLOCK\\_FOR\\_RETURN\(\)](#)

#### 8.4.4.24 `wolfentry_route_table_iterate_current()`

```
WOLFENTRY_API wolfentry_errcode_t wolfentry_route_table_iterate_current (
    const struct wolfentry_route_table * table,
    struct wolfentry_cursor * cursor,
    struct wolfentry_route ** route )
```

Get the current position for the table cursor.

## Parameters

<i>table</i>	the table for the cursor
<i>cursor</i>	a pointer for the cursor
<i>route</i>	a pointer to a pointer for the returned route

## Returns

[WOLFENTRY\\_IS\\_SUCCESS\(ret\)](#) is true on success.

**8.4.4.25 wolfentry\_route\_table\_iterate\_end()**

```
WOLFENTRY_API wolfentry_errcode_t wolfentry_route_table_iterate_end (
    WOLFENTRY_CONTEXT_ARGS_IN ,
    const struct wolfentry_route_table * table,
    struct wolfentry_cursor ** cursor )
```

Frees the table cursor. Caller must have a lock on the context at entry.

## Parameters

<i>table</i>	the table for the cursor
<i>cursor</i>	a pointer to a pointer for the cursor to free

## Returns

[WOLFENTRY\\_IS\\_SUCCESS\(ret\)](#) is true on success.

## See also

[WOLFENTRY\\_SHARED\\_OR\\_RETURN\(\)](#)  
[WOLFENTRY\\_UNLOCK\\_AND\\_RETURN\(\)](#)  
[WOLFENTRY\\_CONTEXT\\_ARGS\\_IN](#)

**8.4.4.26 wolfentry\_route\_table\_iterate\_next()**

```
WOLFENTRY_API wolfentry_errcode_t wolfentry_route_table_iterate_next (
    const struct wolfentry_route_table * table,
    struct wolfentry_cursor * cursor,
    struct wolfentry_route ** route )
```

Get the next position for the table cursor.

## Parameters

<i>table</i>	the table for the cursor
<i>cursor</i>	a pointer for the cursor
<i>route</i>	a pointer to a pointer for the returned route

**Returns**

`WOLFSENTRY_IS_SUCCESS(ret)` is true on success.

**8.4.4.27 wolfentry\_route\_table\_iterate\_prev()**

```
WOLFSENTRY_API wolfentry_errcode_t wolfentry_route_table_iterate_prev (
    const struct wolfentry_route_table * table,
    struct wolfentry_cursor * cursor,
    struct wolfentry_route ** route )
```

Get the previous position for the table cursor.

**Parameters**

<i>table</i>	the table for the cursor
<i>cursor</i>	a pointer for the cursor
<i>route</i>	a pointer to a pointer for the returned route

**Returns**

`WOLFSENTRY_IS_SUCCESS(ret)` is true on success.

**8.4.4.28 wolfentry\_route\_table\_iterate\_seek\_to\_head()**

```
WOLFSENTRY_API wolfentry_errcode_t wolfentry_route_table_iterate_seek_to_head (
    const struct wolfentry_route_table * table,
    struct wolfentry_cursor * cursor )
```

Reset the cursor to the beginning of a table.

**Parameters**

<i>table</i>	the table for the cursor
<i>cursor</i>	a pointer for the cursor

**Returns**

`WOLFSENTRY_IS_SUCCESS(ret)` is true on success.

**8.4.4.29 wolfentry\_route\_table\_iterate\_seek\_to\_tail()**

```
WOLFSENTRY_API wolfentry_errcode_t wolfentry_route_table_iterate_seek_to_tail (
    const struct wolfentry_route_table * table,
    struct wolfentry_cursor * cursor )
```

Move the cursor to the end of a table.

## Parameters

<i>table</i>	the table for the cursor
<i>cursor</i>	a pointer for the cursor

## Returns

[WOLFSENTRY\\_IS\\_SUCCESS\(ret\)](#) is true on success.

**8.4.4.30 wolfentry\_route\_table\_iterate\_start()**

```
WOLFSENTRY_API wolfentry_errcode_t wolfentry_route_table_iterate_start (
    WOLFSENTRY_CONTEXT_ARGS_IN ,
    const struct wolfentry_route_table * table,
    struct wolfentry_cursor ** cursor )
```

Open a cursor to iterate through a routes table. Caller must have a lock on the context at entry.

## Parameters

<i>table</i>	a pointer to the table to open the cursor on
<i>cursor</i>	a pointer to a pointer for the cursor

## Returns

[WOLFSENTRY\\_IS\\_SUCCESS\(ret\)](#) is true on success.

## See also

[WOLFSENTRY\\_SHARED\\_OR\\_RETURN\(\)](#)  
[WOLFSENTRY\\_UNLOCK\\_AND\\_RETURN\(\)](#)  
[WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#)

**8.4.4.31 wolfentry\_route\_update\_flags()**

```
WOLFSENTRY_API wolfentry_errcode_t wolfentry_route_update_flags (
    WOLFSENTRY_CONTEXT_ARGS_IN ,
    struct wolfentry_route * route,
    wolfentry_route_flags_t flags_to_set,
    wolfentry_route_flags_t flags_to_clear,
    wolfentry_route_flags_t * flags_before,
    wolfentry_route_flags_t * flags_after,
    wolfentry_action_res_t * action_results )
```

Update the route flags.

## Parameters

<i>route</i>	the route to update the flags for
--------------	-----------------------------------

## Parameters

<i>flags_to_set</i>	new flags to set
<i>flags_to_clear</i>	old flags to clear
<i>flags_before</i>	a pointer that will be filled with the flags before the change
<i>flags_after</i>	a pointer that will be filled with flags after the change
<i>action_results</i>	the results bit field

## Returns

[WOLFSENTRY\\_IS\\_SUCCESS\(ret\)](#) is true on success.

## See also

[WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#)

## 8.5 Action Subsystem

## Macros

- `#define WOLFSENTRY_ACTION_RES_USER_SHIFT 24U`  
*Bit shift for user-defined bit span in [wolfentry\\_action\\_res\\_t](#).*
- `#define WOLFSENTRY_ACTION_RES_USER7 (1U << 31U)`  
*user-defined result bit #8 of 8. Defined with a macro to retain ISO C compliance on enum range.*

## Typedefs

- typedef [wolfentry\\_errcode\\_t](#)(\* [wolfentry\\_action\\_callback\\_t](#)) ([WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#), const struct wolfentry\_action \*action, void \*handler\_arg, void \*caller\_arg, const struct wolfentry\_event \*trigger\_event, [wolfentry\\_action\\_type\\_t](#) action\_type, const struct wolfentry\_route \*trigger\_route, struct wolfentry\_route\_table \*route\_table, struct wolfentry\_route \*rule\_route, [wolfentry\\_action\\_res\\_t](#) \*action\_results)  
*A callback that is triggered when an action is taken.*

## Enumerations

- enum [wolfentry\\_action\\_flags\\_t](#) {  
[WOLFSENTRY\\_ACTION\\_FLAG\\_NONE](#) ,  
[WOLFSENTRY\\_ACTION\\_FLAG\\_DISABLED](#) }  
*enum for communicating attributes of an action object*
- enum [wolfentry\\_action\\_type\\_t](#) {  
[WOLFSENTRY\\_ACTION\\_TYPE\\_NONE](#) ,  
[WOLFSENTRY\\_ACTION\\_TYPE\\_POST](#) ,  
[WOLFSENTRY\\_ACTION\\_TYPE\\_INSERT](#) ,  
[WOLFSENTRY\\_ACTION\\_TYPE\\_MATCH](#) ,  
[WOLFSENTRY\\_ACTION\\_TYPE\\_UPDATE](#) ,  
[WOLFSENTRY\\_ACTION\\_TYPE\\_DELETE](#) ,  
[WOLFSENTRY\\_ACTION\\_TYPE\\_DECISION](#) }  
*enum communicating (to action handlers and internal logic) what type of action is being evaluated*

- enum `wolfentry_action_res_t` {  
`WOLFENTRY_ACTION_RES_NONE` ,  
`WOLFENTRY_ACTION_RES_ACCEPT` ,  
`WOLFENTRY_ACTION_RES_REJECT` ,  
`WOLFENTRY_ACTION_RES_CONNECT` ,  
`WOLFENTRY_ACTION_RES_DISCONNECT` ,  
`WOLFENTRY_ACTION_RES_DEROGATORY` ,  
`WOLFENTRY_ACTION_RES_COMMENDABLE` ,  
`WOLFENTRY_ACTION_RES_STOP` ,  
`WOLFENTRY_ACTION_RES_DEALLOCATED` ,  
`WOLFENTRY_ACTION_RES_INSERTED` ,  
`WOLFENTRY_ACTION_RES_ERROR` ,  
`WOLFENTRY_ACTION_RES_FALLTHROUGH` ,  
`WOLFENTRY_ACTION_RES_UPDATE` ,  
`WOLFENTRY_ACTION_RES_PORT_RESET` ,  
`WOLFENTRY_ACTION_RES_SENDING` ,  
`WOLFENTRY_ACTION_RES_RECEIVED` ,  
`WOLFENTRY_ACTION_RES_BINDING` ,  
`WOLFENTRY_ACTION_RES_LISTENING` ,  
`WOLFENTRY_ACTION_RES_STOPPED_LISTENING` ,  
`WOLFENTRY_ACTION_RES_CONNECTING_OUT` ,  
`WOLFENTRY_ACTION_RES_CLOSED` ,  
`WOLFENTRY_ACTION_RES_UNREACHABLE` ,  
`WOLFENTRY_ACTION_RES_SOCKET_ERROR` ,  
`WOLFENTRY_ACTION_RES_CLOSE_WAIT` ,  
`WOLFENTRY_ACTION_RES_USER0` ,  
`WOLFENTRY_ACTION_RES_USER1` ,  
`WOLFENTRY_ACTION_RES_USER2` ,  
`WOLFENTRY_ACTION_RES_USER3` ,  
`WOLFENTRY_ACTION_RES_USER4` ,  
`WOLFENTRY_ACTION_RES_USERS5` ,  
`WOLFENTRY_ACTION_RES_USER6` }

*bit field used to communicate states and attributes through the evaluation pipeline.*

## Functions

- WOLFENTRY\_API const char \* **wolfentry\_action\_res\_assoc\_by\_flag** (`wolfentry_action_res_t` res, unsigned int bit)  
*Given a bit number (from 0 to 31), return the name of that bit if set in res, else return a null pointer.*
- WOLFENTRY\_API `wolfentry_errcode_t` **wolfentry\_action\_res\_assoc\_by\_name** (const char \*bit\_name, size\_t bit\_name\_len, `wolfentry_action_res_t` \*res)  
*Given a bit\_name, set \*res to the corresponding bit number if known, failing which, return ITEM\_NOT\_FOUND.*
- WOLFENTRY\_API `wolfentry_errcode_t` **wolfentry\_action\_insert** (`WOLFENTRY_CONTEXT_ARGS_IN`, const char \*label, int label\_len, `wolfentry_action_flags_t` flags, `wolfentry_action_callback_t` handler, void \*handler\_arg, `wolfentry_ent_id_t` \*id)  
*Insert a new action into wolfentry.*
- WOLFENTRY\_API `wolfentry_errcode_t` **wolfentry\_action\_delete** (`WOLFENTRY_CONTEXT_ARGS_IN`, const char \*label, int label\_len, `wolfentry_action_res_t` \*action\_results)  
*Delete an action from wolfentry.*
- WOLFENTRY\_API `wolfentry_errcode_t` **wolfentry\_action\_flush\_all** (`WOLFENTRY_CONTEXT_ARGS_IN`)  
*Flush all actions from wolfentry.*
- WOLFENTRY\_API `wolfentry_errcode_t` **wolfentry\_action\_get\_reference** (`WOLFENTRY_CONTEXT_ARGS_IN`, const char \*label, int label\_len, struct `wolfentry_action` \*\*action)  
*Get a reference to an action.*

- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_action\\_drop\\_reference](#) ([WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#), struct [wolfentry\\_action](#) \*action, [wolfentry\\_action\\_res\\_t](#) \*action\_results)  
*Drop a reference to an action.*
- WOLFSENTRY\_API const char \* [wolfentry\\_action\\_get\\_label](#) (const struct [wolfentry\\_action](#) \*action)  
*Get the label for an action. This is the internal pointer to the label so should not be freed by the application.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_action\\_get\\_flags](#) (struct [wolfentry\\_action](#) \*action, [wolfentry\\_action\\_flags\\_t](#) \*flags)  
*Get the flags for an action.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_action\\_update\\_flags](#) (struct [wolfentry\\_action](#) \*action, [wolfentry\\_action\\_flags\\_t](#) flags\_to\_set, [wolfentry\\_action\\_flags\\_t](#) flags\_to\_clear, [wolfentry\\_action\\_flags\\_t](#) \*flags\_before, [wolfentry\\_action\\_flags\\_t](#) \*flags\_after)  
*Update the flags for an action.*

## 8.5.1 Detailed Description

## 8.5.2 Typedef Documentation

### 8.5.2.1 wolfentry\_action\_callback\_t

```
typedef wolfentry\_errcode\_t(* wolfentry_action_callback_t) (WOLFSENTRY\_CONTEXT\_ARGS\_IN,
const struct wolfentry\_action *action, void *handler_arg, void *caller_arg, const struct wolfentry↵
_event *trigger_event, wolfentry\_action\_type\_t action_type, const struct wolfentry\_route↵
*trigger_route, struct wolfentry\_route\_table *route_table, struct wolfentry\_route *rule_↵
route, wolfentry\_action\_res\_t *action_results)
```

A callback that is triggered when an action is taken.

#### Parameters

<i>action</i>	a pointer to action details
<i>handler_arg</i>	an opaque pointer registered with <a href="#">wolfentry_action_insert()</a> , passed to every invocation of the handler
<i>caller_arg</i>	an opaque pointer supplied by the caller to the dispatching <a href="#">wolfentry_route_*</a> () API
<i>trigger_event</i>	the event which triggered the action, if any
<i>action_type</i>	the action type
<i>trigger_route</i>	a pointer to the subject route, reflecting instantaneous traffic attributes and contents
<i>route_table</i>	a pointer to the implicated route table
<i>rule_route</i>	a pointer to the matched route, reflecting rule logic
<i>action_results</i>	a pointer to the action results, to be read and/or updated by the handler

#### Returns

[WOLFSENTRY\\_RETURN\\_OK](#) if there is no error

#### See also

[WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#)



### 8.5.3 Enumeration Type Documentation

#### 8.5.3.1 wolfsentry\_action\_flags\_t

enum wolfsentry\_action\_flags\_t

enum for communicating attributes of an action object

Enumerator

WOLFSENTRY_ACTION_FLAG_NONE	Default attributes.
WOLFSENTRY_ACTION_FLAG_DISABLED	Disable this action – while this bit is set, dispatches will not call this action.

#### 8.5.3.2 wolfsentry\_action\_res\_t

enum wolfsentry\_action\_res\_t

bit field used to communicate states and attributes through the evaluation pipeline.

Enumerator

WOLFSENTRY_ACTION_RES_NONE	initializer for wolfsentry_action_res_t.
WOLFSENTRY_ACTION_RES_ACCEPT	the route state or an action determined the event should be allowed.
WOLFSENTRY_ACTION_RES_REJECT	the route state or an action determined the event should be forbidden.
WOLFSENTRY_ACTION_RES_CONNECT	caller-preinitiated bit signaling that a connection was established.
WOLFSENTRY_ACTION_RES_DISCONNECT	caller-preinitiated bit signaling that a connection was dissolved.
WOLFSENTRY_ACTION_RES_DEROGATORY	the caller or an action designated this event derogatory for the peer.
WOLFSENTRY_ACTION_RES_COMMENDABLE	the caller or an action designated this event commendable for the peer.
WOLFSENTRY_ACTION_RES_STOP	when an action returns this, don't evaluate any more actions in the current action list.
WOLFSENTRY_ACTION_RES_DEALLOCATED	when an API call returns this, an object and its associated ID were deallocated from the system.
WOLFSENTRY_ACTION_RES_INSERTED	a side-effect route insertion was performed.
WOLFSENTRY_ACTION_RES_ERROR	an error occurred while processing actions.
WOLFSENTRY_ACTION_RES_FALLTHROUGH	dispatch classification (ACCEPT/REJECT) was by fallthrough policy.
WOLFSENTRY_ACTION_RES_UPDATE	signals to subsequent actions and the caller that the route state was updated (e.g. penaltyboxed).
WOLFSENTRY_ACTION_RES_PORT_RESET	when an action returns this, send a TCP reset or ICMP port unreachable packet.
WOLFSENTRY_ACTION_RES_SENDING	caller-preinitiated bit signaling outbound traffic.
WOLFSENTRY_ACTION_RES_RECEIVED	caller-preinitiated bit signaling inbound traffic.
WOLFSENTRY_ACTION_RES_BINDING	caller-preinitiated bit signaling that a socket will be bound.

## Enumerator

WOLFSENTRY_ACTION_RES_LISTENING	caller-preinited bit signaling that a socket will be listened.
WOLFSENTRY_ACTION_RES_STOPPED_↔ LISTENING	caller-preinited bit signaling that a socket will stop being listened.
WOLFSENTRY_ACTION_RES_CONNECTING_OUT	caller-preinited bit signaling that an outbound connection will be attempted.
WOLFSENTRY_ACTION_RES_CLOSED	caller-preinited bit signaling that an association has closed/ended that wasn't created with <code>_CONNECT</code> .
WOLFSENTRY_ACTION_RES_UNREACHABLE	caller-preinited bit signaling that traffic destination was unreachable (unbound/unlistened).
WOLFSENTRY_ACTION_RES SOCK_ERROR	caller-preinited bit signaling that a transport error occurred.
WOLFSENTRY_ACTION_RES_CLOSE_WAIT	caller-preinited bit signaling that an association has entered <code>CLOSE_WAIT</code> and will be closed.
WOLFSENTRY_ACTION_RES_USER0	user-defined result bit #1 of 8.
WOLFSENTRY_ACTION_RES_USER1	user-defined result bit #2 of 8.
WOLFSENTRY_ACTION_RES_USER2	user-defined result bit #3 of 8.
WOLFSENTRY_ACTION_RES_USER3	user-defined result bit #4 of 8.
WOLFSENTRY_ACTION_RES_USER4	user-defined result bit #5 of 8.
WOLFSENTRY_ACTION_RES_USER5	user-defined result bit #6 of 8.
WOLFSENTRY_ACTION_RES_USER6	user-defined result bit #7 of 8. start of user-defined results, with user-defined scheme (bit field, sequential, or other). 8 bits are available.

8.5.3.3 `wolfentry_action_type_t`

```
enum wolfentry_action_type_t
```

enum communicating (to action handlers and internal logic) what type of action is being evaluated

## Enumerator

WOLFSENTRY_ACTION_TYPE_NONE	no action
WOLFSENTRY_ACTION_TYPE_POST	called when an event is posted.
WOLFSENTRY_ACTION_TYPE_INSERT	called when a route is added to the route table for this event.
WOLFSENTRY_ACTION_TYPE_MATCH	called by <code>wolfentry_route_dispatch()</code> for a route match.
WOLFSENTRY_ACTION_TYPE_UPDATE	called by <code>wolfentry_route_dispatch()</code> when the logical state (currently, flags) of an existing route changes.
WOLFSENTRY_ACTION_TYPE_DELETE	called when a route associated with this event expires or is otherwise deleted.
WOLFSENTRY_ACTION_TYPE_DECISION	called after final decision has been made by <code>wolfentry_route_event_dispatch*()</code> .

## 8.5.4 Function Documentation

8.5.4.1 `wolfentry_action_delete()`

```
WOLFSENTRY_API wolfentry_errcode_t wolfentry_action_delete (
```

```
WOLFSENTRY_CONTEXT_ARGS_IN ,
const char * label,
int label_len,
wolfentry_action_res_t * action_results )
```

Delete an action from wolfentry.

#### Parameters

<i>label</i>	the label of the action to delete
<i>label_len</i>	the length of the label, use WOLFSENTRY_LENGTH_NULL_TERMINATED for a NUL terminated string
<i>action_results</i>	the returned result of the delete

#### Returns

[WOLFSENTRY\\_IS\\_SUCCESS\(ret\)](#) is true on success.

#### See also

[WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#)

#### 8.5.4.2 wolfentry\_action\_drop\_reference()

```
WOLFSENTRY_API wolfentry_errcode_t wolfentry_action_drop_reference (
    WOLFSENTRY_CONTEXT_ARGS_IN ,
    struct wolfentry_action * action,
    wolfentry_action_res_t * action_results )
```

Drop a reference to an action.

#### Parameters

<i>action</i>	the action to drop the reference for
<i>action_results</i>	a pointer to the result of the function

#### Returns

[WOLFSENTRY\\_IS\\_SUCCESS\(ret\)](#) is true on success.

#### See also

[WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#)

#### 8.5.4.3 wolfentry\_action\_flush\_all()

```
WOLFSENTRY_API wolfentry_errcode_t wolfentry_action_flush_all (
    WOLFSENTRY_CONTEXT_ARGS_IN )
```

Flush all actions from wolfentry.

**Returns**

`WOLFSENTRY_IS_SUCCESS(ret)` is true on success.

**See also**

`WOLFSENTRY_CONTEXT_ARGS_IN`

**8.5.4.4 wolfentry\_action\_get\_flags()**

```
WOLFSENTRY_API wolfentry_errcode_t wolfentry_action_get_flags (
    struct wolfentry_action * action,
    wolfentry_action_flags_t * flags )
```

Get the flags for an action.

**Parameters**

<i>action</i>	the action to get the flags for
<i>flags</i>	the flags to be returned

**Returns**

`WOLFSENTRY_IS_SUCCESS(ret)` is true on success.

**8.5.4.5 wolfentry\_action\_get\_label()**

```
WOLFSENTRY_API const char * wolfentry_action_get_label (
    const struct wolfentry_action * action )
```

Get the label for an action. This is the internal pointer to the label so should not be freed by the application.

**Parameters**

<i>action</i>	the action to get the label for
---------------	---------------------------------

**Returns**

the label for the action

**8.5.4.6 wolfentry\_action\_get\_reference()**

```
WOLFSENTRY_API wolfentry_errcode_t wolfentry_action_get_reference (
    WOLFSENTRY_CONTEXT_ARGS_IN ,
    const char * label,
    int label_len,
    struct wolfentry_action ** action )
```

Get a reference to an action.

## Parameters

<i>label</i>	the label of the action to get the reference for
<i>label_len</i>	the length of the label, use WOLFSENTRY_LENGTH_NULL_TERMINATED for a NUL terminated string
<i>action</i>	a pointer to a pointer for the action returned

## Returns

[WOLFSENTRY\\_IS\\_SUCCESS\(ret\)](#) is true on success.

## See also

[WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#)

**8.5.4.7 wolfentry\_action\_insert()**

```
WOLFSENTRY_API wolfentry_errcode_t wolfentry_action_insert (
    WOLFSENTRY_CONTEXT_ARGS_IN ,
    const char * label,
    int label_len,
    wolfentry_action_flags_t flags,
    wolfentry_action_callback_t handler,
    void * handler_arg,
    wolfentry_ent_id_t * id )
```

Insert a new action into wolfentry.

## Parameters

<i>label</i>	the label for the action
<i>label_len</i>	the length of the label, use WOLFSENTRY_LENGTH_NULL_TERMINATED for a NUL terminated string
<i>flags</i>	set flags for the action
<i>handler</i>	a callback handler when the action commences
<i>handler_arg</i>	an arbitrary pointer for the handler callback
<i>id</i>	the returned ID for the inserted action

## Returns

[WOLFSENTRY\\_IS\\_SUCCESS\(ret\)](#) is true on success.

## See also

[WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#)

#### 8.5.4.8 wolfsentry\_action\_update\_flags()

```
WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_action_update_flags (
    struct wolfsentry_action * action,
    wolfsentry_action_flags_t flags_to_set,
    wolfsentry_action_flags_t flags_to_clear,
    wolfsentry_action_flags_t * flags_before,
    wolfsentry_action_flags_t * flags_after )
```

Update the flags for an action.

##### Parameters

<i>action</i>	the action to update
<i>flags_to_set</i>	new flags to set
<i>flags_to_clear</i>	old flags to clear
<i>flags_before</i>	the flags before the change
<i>flags_after</i>	the flags after the change

##### Returns

[WOLFSENTRY\\_IS\\_SUCCESS\(ret\)](#) is true on success.

## 8.6 Event Subsystem

### Data Structures

- struct [wolfsentry\\_eventconfig](#)  
*struct for representing event configuration*

### Enumerations

- enum [wolfsentry\\_event\\_flags\\_t](#) {  
[WOLFSENTRY\\_EVENT\\_FLAG\\_NONE](#) ,  
[WOLFSENTRY\\_EVENT\\_FLAG\\_IS\\_PARENT\\_EVENT](#) ,  
[WOLFSENTRY\\_EVENT\\_FLAG\\_IS\\_SUBEVENT](#) }  
*bit field with attribute flags for events*
- enum [wolfsentry\\_eventconfig\\_flags\\_t](#) {  
[WOLFSENTRY\\_EVENTCONFIG\\_FLAG\\_NONE](#) ,  
[WOLFSENTRY\\_EVENTCONFIG\\_FLAG\\_DEROGATORY\\_THRESHOLD\\_IGNORE\\_COMMENDABLE](#) ,  
[WOLFSENTRY\\_EVENTCONFIG\\_FLAG\\_COMMENDABLE\\_CLEAR\\_DEROGATORY](#) ,  
[WOLFSENTRY\\_EVENTCONFIG\\_FLAG\\_INHIBIT\\_ACTIONS](#) }  
*bit field with config flags for events*

## Functions

- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_eventconfig\\_init](#) (struct [wolfentry\\_context](#) \*wolfentry, struct [wolfentry\\_eventconfig](#) \*config)  
*Initializes a [wolfentry\\_eventconfig](#) struct with the defaults from the wolfentry context. If no wolfentry context is provided this will initialize to zero.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_eventconfig\\_check](#) (const struct [wolfentry\\_eventconfig](#) \*config)  
*Checks the config for self-consistency and validity.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_event\\_insert](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const char \*label, int label\_len, [wolfentry\\_priority\\_t](#) priority, const struct [wolfentry\\_eventconfig](#) \*config, [wolfentry\\_event\\_flags\\_t](#) flags, [wolfentry\\_ent\\_id\\_t](#) \*id)  
*Insert an event into wolfentry.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_event\\_delete](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const char \*label, int label\_len, [wolfentry\\_action\\_res\\_t](#) \*action\_results)  
*Delete an event from wolfentry.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_event\\_flush\\_all](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN)  
*Flush all events from wolfentry.*
- WOLFSENTRY\_API const char \* [wolfentry\\_event\\_get\\_label](#) (const struct [wolfentry\\_event](#) \*event)  
*Get the label for an event. This is the internal pointer to the label so should not be freed by the application.*
- WOLFSENTRY\_API [wolfentry\\_event\\_flags\\_t](#) [wolfentry\\_event\\_get\\_flags](#) (const struct [wolfentry\\_event](#) \*event)  
*Get the flags for an event.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_event\\_get\\_config](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const char \*label, int label\_len, struct [wolfentry\\_eventconfig](#) \*config)  
*Get the configuration for an event.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_event\\_update\\_config](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const char \*label, int label\_len, const struct [wolfentry\\_eventconfig](#) \*config)  
*Update the configuration for an event.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_event\\_get\\_reference](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const char \*label, int label\_len, struct [wolfentry\\_event](#) \*\*event)  
*Get a reference to an event.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_event\\_drop\\_reference](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, struct [wolfentry\\_event](#) \*event, [wolfentry\\_action\\_res\\_t](#) \*action\_results)  
*Drop a reference to an event.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_event\\_action\\_prepend](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const char \*event\_label, int event\_label\_len, [wolfentry\\_action\\_type\\_t](#) which\_action\_list, const char \*action\_label, int action\_label\_len)  
*Prepend an action into an event.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_event\\_action\\_append](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const char \*event\_label, int event\_label\_len, [wolfentry\\_action\\_type\\_t](#) which\_action\_list, const char \*action\_label, int action\_label\_len)  
*Append an action into an event.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_event\\_action\\_insert\\_after](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const char \*event\_label, int event\_label\_len, [wolfentry\\_action\\_type\\_t](#) which\_action\_list, const char \*action\_label, int action\_label\_len, const char \*point\_action\_label, int point\_action\_label\_len)  
*Insert an action into an event after another action.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_event\\_action\\_delete](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const char \*event\_label, int event\_label\_len, [wolfentry\\_action\\_type\\_t](#) which\_action\_list, const char \*action\_label, int action\_label\_len)  
*Delete an action from an event.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_event\\_set\\_aux\\_event](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const char \*event\_label, int event\_label\_len, const char \*aux\_event\_label, int aux\_event\_label\_len)  
*Set an auxiliary event for an event.*

- WOLFSENTRY\_API const struct wolfsentry\_event \* **wolfsentry\_event\_get\_aux\_event** (const struct wolfsentry\_event \*event)  
*Retrieve an auxiliary event previously set with [wolfsentry\\_event\\_set\\_aux\\_event\(\)](#).*
- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t](#) **wolfsentry\_event\_action\_list\_start** (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const char \*event\_label, int event\_label\_len, [wolfsentry\\_action\\_type\\_t](#) which\_action\_list, struct wolfsentry↵\_action\_list\_ent \*\*cursor)  
*Open a cursor for the actions in an event. Caller must have a lock on the context at entry.*
- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t](#) **wolfsentry\_event\_action\_list\_next** (WOLFSENTRY\_CONTEXT\_ARGS\_IN, struct wolfsentry\_action\_list\_ent \*\*cursor, const char \*\*action\_label, int \*action\_label\_len)  
*Get the next action in an event cursor. Caller must have a lock on the context at entry.*
- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t](#) **wolfsentry\_event\_action\_list\_done** (WOLFSENTRY\_CONTEXT\_ARGS\_IN, struct wolfsentry\_action\_list\_ent \*\*cursor)  
*End iteration started with [wolfsentry\\_event\\_action\\_list\\_start\(\)](#). Caller must have a lock on the context at entry.*

## 8.6.1 Detailed Description

## 8.6.2 Enumeration Type Documentation

### 8.6.2.1 wolfsentry\_event\_flags\_t

enum [wolfsentry\\_event\\_flags\\_t](#)

bit field with attribute flags for events

Enumerator

WOLFSENTRY_EVENT_FLAG_NONE	Default attributes.
WOLFSENTRY_EVENT_FLAG_IS_PARENT_EVENT	Internally set – Event is parent of one or more routes.
WOLFSENTRY_EVENT_FLAG_IS_SUBEVENT	Internally set – Event is subevent of another event.

### 8.6.2.2 wolfsentry\_eventconfig\_flags\_t

enum [wolfsentry\\_eventconfig\\_flags\\_t](#)

bit field with config flags for events

Enumerator

WOLFSENTRY_EVENTCONFIG_FLAG_NONE	Default config.
WOLFSENTRY_EVENTCONFIG_FLAG_↵ DEROGATORY_THRESHOLD_IGNORE_↵ COMMENDABLE	If set, then counts from WOLFSENTRY_ACTION_RES_COMMENDABLE are not subtracted from the derogatory count when checking for automatic penalty boxing.
WOLFSENTRY_EVENTCONFIG_FLAG_↵ COMMENDABLE_CLEARS_DEROGATORY	If set, then each count from WOLFSENTRY_ACTION_RES_COMMENDABLE zeroes the derogatory count.
WOLFSENTRY_EVENTCONFIG_FLAG_INHIBIT_↵ ACTIONS	Internal use – Inhibits dispatch of actions listed in this event.



### 8.6.3 Function Documentation

#### 8.6.3.1 wolfsentry\_event\_action\_append()

```
WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_event_action_append (
    WOLFSENTRY_CONTEXT_ARGS_IN ,
    const char * event_label,
    int event_label_len,
    wolfsentry_action_type_t which_action_list,
    const char * action_label,
    int action_label_len )
```

Append an action into an event.

##### Parameters

<i>event_label</i>	the label of the event to append the action into
<i>event_label_len</i>	the length of the event_label
<i>which_action_list</i>	the action list of the event to update
<i>action_label</i>	the label of the action to insert
<i>action_label_len</i>	the length of the action_label

##### Returns

[WOLFSENTRY\\_IS\\_SUCCESS\(ret\)](#) is true on success.

##### See also

[WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#)

#### 8.6.3.2 wolfsentry\_event\_action\_delete()

```
WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_event_action_delete (
    WOLFSENTRY_CONTEXT_ARGS_IN ,
    const char * event_label,
    int event_label_len,
    wolfsentry_action_type_t which_action_list,
    const char * action_label,
    int action_label_len )
```

Delete an action from an event.

##### Parameters

<i>event_label</i>	the label of the event to delete the action from
<i>event_label_len</i>	the length of the event_label
<i>which_action_list</i>	the action list of the event to update
<i>action_label</i>	the label of the action to delete
<i>action_label_len</i>	the length of the action_label

**Returns**

[WOLFSENTRY\\_IS\\_SUCCESS\(ret\)](#) is true on success.

**See also**

[WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#)

**8.6.3.3 wolfentry\_event\_action\_insert\_after()**

```
WOLFSENTRY_API wolfentry_errcode_t wolfentry_event_action_insert_after (
    WOLFSENTRY_CONTEXT_ARGS_IN ,
    const char * event_label,
    int event_label_len,
    wolfentry_action_type_t which_action_list,
    const char * action_label,
    int action_label_len,
    const char * point_action_label,
    int point_action_label_len )
```

Insert an action into an event after another action.

**Parameters**

<i>event_label</i>	the label of the event to insert the action into
<i>event_label_len</i>	the length of the event_label
<i>which_action_list</i>	the action list of the event to update
<i>action_label</i>	the label of the action to insert
<i>action_label_len</i>	the length of the action_label
<i>point_action_label</i>	the label of the action to insert after
<i>point_action_label_len</i>	the length of the point_action_label

**Returns**

[WOLFSENTRY\\_IS\\_SUCCESS\(ret\)](#) is true on success.

**See also**

[WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#)

**8.6.3.4 wolfentry\_event\_action\_list\_done()**

```
WOLFSENTRY_API wolfentry_errcode_t wolfentry_event_action_list_done (
    WOLFSENTRY_CONTEXT_ARGS_IN ,
    struct wolfentry_action_list_ent ** cursor )
```

End iteration started with [wolfentry\\_event\\_action\\_list\\_start\(\)](#). Caller must have a lock on the context at entry.

## Parameters

<i>cursor</i>	a pointer to a pointer for the cursor
---------------	---------------------------------------

## Returns

[WOLFSENTRY\\_IS\\_SUCCESS\(ret\)](#) is true on success.

## See also

[WOLFSENTRY\\_SHARED\\_OR\\_RETURN\(\)](#)  
[WOLFSENTRY\\_UNLOCK\\_AND\\_RETURN\(\)](#)  
[WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#)

**8.6.3.5 wolfentry\_event\_action\_list\_next()**

```
WOLFSENTRY_API wolfentry_errcode_t wolfentry_event_action_list_next (
    WOLFSENTRY_CONTEXT_ARGS_IN ,
    struct wolfentry_action_list_ent ** cursor,
    const char ** action_label,
    int * action_label_len )
```

Get the next action in an event cursor. Caller must have a lock on the context at entry.

## Parameters

<i>cursor</i>	a pointer to a pointer for the cursor
<i>action_label</i>	a pointer to a pointer to the returned action_label
<i>action_label_len</i>	the length of action_label

## Returns

[WOLFSENTRY\\_IS\\_SUCCESS\(ret\)](#) is true on success.

## See also

[WOLFSENTRY\\_SHARED\\_OR\\_RETURN\(\)](#)  
[WOLFSENTRY\\_UNLOCK\\_AND\\_RETURN\(\)](#)  
[WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#)

**8.6.3.6 wolfentry\_event\_action\_list\_start()**

```
WOLFSENTRY_API wolfentry_errcode_t wolfentry_event_action_list_start (
    WOLFSENTRY_CONTEXT_ARGS_IN ,
    const char * event_label,
    int event_label_len,
    wolfentry_action_type_t which_action_list,
    struct wolfentry_action_list_ent ** cursor )
```

Open a cursor for the actions in an event. Caller must have a lock on the context at entry.

## Parameters

<i>event_label</i>	the event label to open the iterator for
<i>event_label_len</i>	the length of the event_label
<i>which_action_list</i>	the action list of the event to list
<i>cursor</i>	a pointer to a pointer for the cursor to open

## Returns

[WOLFSENTRY\\_IS\\_SUCCESS\(ret\)](#) is true on success.

## See also

[WOLFSENTRY\\_SHARED\\_OR\\_RETURN\(\)](#)

[WOLFSENTRY\\_UNLOCK\\_AND\\_RETURN\(\)](#)

[WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#)

## 8.6.3.7 wolfentry\_event\_action\_prepend()

```
WOLFSENTRY_API wolfentry_errcode_t wolfentry_event_action_prepend (
    WOLFSENTRY_CONTEXT_ARGS_IN ,
    const char * event_label,
    int event_label_len,
    wolfentry_action_type_t which_action_list,
    const char * action_label,
    int action_label_len )
```

Prepend an action into an event.

## Parameters

<i>event_label</i>	the label of the event to prepend the action into
<i>event_label_len</i>	the length of the event_label
<i>which_action_list</i>	the action list of the event to update
<i>action_label</i>	the label of the action to insert
<i>action_label_len</i>	the length of the action_label

## Returns

[WOLFSENTRY\\_IS\\_SUCCESS\(ret\)](#) is true on success.

## See also

[WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#)

### 8.6.3.8 wolfsentry\_event\_delete()

```
WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_event_delete (
    WOLFSENTRY_CONTEXT_ARGS_IN ,
    const char * label,
    int label_len,
    wolfsentry_action_res_t * action_results )
```

Delete an event from wolfsentry.

#### Parameters

<i>label</i>	the label of the even to delete
<i>label_len</i>	the length of the label
<i>action_results</i>	the result of the delete action

#### Returns

[WOLFSENTRY\\_IS\\_SUCCESS\(ret\)](#) is true on success.

### 8.6.3.9 wolfsentry\_event\_drop\_reference()

```
WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_event_drop_reference (
    WOLFSENTRY_CONTEXT_ARGS_IN ,
    struct wolfsentry_event * event,
    wolfsentry_action_res_t * action_results )
```

Drop a reference to an event.

#### Parameters

<i>event</i>	the event to drop the reference for
<i>action_results</i>	a pointer to the result of the function

#### Returns

[WOLFSENTRY\\_IS\\_SUCCESS\(ret\)](#) is true on success.

#### See also

[WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#)

### 8.6.3.10 wolfsentry\_event\_flush\_all()

```
WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_event_flush_all (
    WOLFSENTRY_CONTEXT_ARGS_IN )
```

Flush all events from wolfsentry.

**Returns**

[WOLFSENTRY\\_IS\\_SUCCESS\(ret\)](#) is true on success.

**See also**

[WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#)

**8.6.3.11 wolfentry\_event\_get\_config()**

```
WOLFSENTRY_API wolfentry_errcode_t wolfentry_event_get_config (
    WOLFSENTRY_CONTEXT_ARGS_IN ,
    const char * label,
    int label_len,
    struct wolfentry_eventconfig * config )
```

Get the configuration for an event.

**Parameters**

<i>label</i>	the label for the event to get the config for
<i>label_len</i>	the length of the label
<i>config</i>	the configuration returned

**Returns**

[WOLFSENTRY\\_IS\\_SUCCESS\(ret\)](#) is true on success.

**See also**

[WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#)

**8.6.3.12 wolfentry\_event\_get\_flags()**

```
WOLFSENTRY_API wolfentry_event_flags_t wolfentry_event_get_flags (
    const struct wolfentry_event * event )
```

Get the flags for an event.

**Parameters**

<i>event</i>	the event to get the flags for
--------------	--------------------------------

**Returns**

the current flags of the event

### 8.6.3.13 wolfsentry\_event\_get\_label()

```
WOLFSENTRY_API const char * wolfsentry_event_get_label (
    const struct wolfsentry_event * event )
```

Get the label for an event. This is the internal pointer to the label so should not be freed by the application.

#### Parameters

<i>event</i>	the event to get the label for
--------------	--------------------------------

#### Returns

the label for the event

### 8.6.3.14 wolfsentry\_event\_get\_reference()

```
WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_event_get_reference (
    WOLFSENTRY_CONTEXT_ARGS_IN ,
    const char * label,
    int label_len,
    struct wolfsentry_event ** event )
```

Get a reference to an event.

#### Parameters

<i>label</i>	the label of the event to get the reference for
<i>label_len</i>	the length of the label, use WOLFSENTRY_LENGTH_NULL_TERMINATED for a NUL terminated string
<i>event</i>	a pointer to a pointer for the event returned

#### Returns

[WOLFSENTRY\\_IS\\_SUCCESS\(ret\)](#) is true on success.

#### See also

[WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#)

### 8.6.3.15 wolfsentry\_event\_insert()

```
WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_event_insert (
    WOLFSENTRY_CONTEXT_ARGS_IN ,
    const char * label,
    int label_len,
    wolfsentry_priority_t priority,
    const struct wolfsentry_eventconfig * config,
    wolfsentry_event_flags_t flags,
    wolfsentry_ent_id_t * id )
```

Insert an event into wolfsentry.

**Parameters**

<i>label</i>	the label for the event
<i>label_len</i>	the length of the label
<i>priority</i>	the priority of the event
<i>config</i>	event configuration details
<i>flags</i>	the flags for the event
<i>id</i>	the returned ID for the event

**Returns**

[WOLFSENTRY\\_IS\\_SUCCESS\(ret\)](#) is true on success.

**See also**

[WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#)

**8.6.3.16 wolfentry\_event\_set\_aux\_event()**

```
WOLFSENTRY_API wolfentry_errcode_t wolfentry_event_set_aux_event (
    WOLFSENTRY_CONTEXT_ARGS_IN ,
    const char * event_label,
    int event_label_len,
    const char * aux_event_label,
    int aux_event_label_len )
```

Set an auxiliary event for an event.

**Parameters**

<i>event_label</i>	the parent event label
<i>event_label_len</i>	the length of the event_label
<i>aux_event_label</i>	the aux event label
<i>aux_event_label_len</i>	the length of the aux event_label

**Returns**

[WOLFSENTRY\\_IS\\_SUCCESS\(ret\)](#) is true on success.

**See also**

[WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#)

**8.6.3.17 wolfentry\_event\_update\_config()**

```
WOLFSENTRY_API wolfentry_errcode_t wolfentry_event_update_config (
    WOLFSENTRY_CONTEXT_ARGS_IN ,
```



```
const char * label,  
int label_len,  
const struct wolfsentry_eventconfig * config )
```

Update the configuration for an event.

## Parameters

<i>label</i>	the label for the event to get the config for
<i>label_len</i>	the length of the label
<i>config</i>	the updated configuration

## Returns

[WOLFSENTRY\\_IS\\_SUCCESS\(ret\)](#) is true on success.

## See also

[WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#)

**8.6.3.18 wolfentry\_eventconfig\_check()**

```
WOLFSENTRY_API wolfentry_errcode_t wolfentry_eventconfig_check (  
    const struct wolfentry_eventconfig * config )
```

Checks the config for self-consistency and validity.

## Parameters

<i>config</i>	the pointer to the config to check
---------------	------------------------------------

## Returns

[WOLFSENTRY\\_IS\\_SUCCESS\(ret\)](#) is true on success.

**8.6.3.19 wolfentry\_eventconfig\_init()**

```
WOLFSENTRY_API wolfentry_errcode_t wolfentry_eventconfig_init (  
    struct wolfentry_context * wolfentry,  
    struct wolfentry_eventconfig * config )
```

Initializes a [wolfentry\\_eventconfig](#) struct with the defaults from the wolfentry context. If no wolfentry context is provided this will initialize to zero.

## Parameters

<i>wolfentry</i>	the wolfentry context
<i>config</i>	the pointer to the config to initialize

## Returns

[WOLFSENTRY\\_IS\\_SUCCESS\(ret\)](#) is true on success.

## 8.7 Address Family Subsystem

### Macros

- #define **WOLFSENTRY\_AF\_UNSPEC** 0
- #define **WOLFSENTRY\_AF\_UNIX** 1  
*Unix domain sockets.*
- #define **WOLFSENTRY\_AF\_LOCAL** 1  
*POSIX name for WOLFSENTRY\_AF\_UNIX.*
- #define **WOLFSENTRY\_AF\_INET** 2  
*Internet IP Protocol.*
- #define **WOLFSENTRY\_AF\_AX25** 3  
*Amateur Radio AX.25.*
- #define **WOLFSENTRY\_AF\_IPX** 4  
*Novell IPX.*
- #define **WOLFSENTRY\_AF\_APPLETALK** 5  
*AppleTalk DDP.*
- #define **WOLFSENTRY\_AF\_NETROM** 6  
*Amateur Radio NET/ROM.*
- #define **WOLFSENTRY\_AF\_BRIDGE** 7  
*Multiprotocol bridge.*
- #define **WOLFSENTRY\_AF\_ATMPVC** 8  
*ATM PVCs.*
- #define **WOLFSENTRY\_AF\_X25** 9  
*Reserved for X.25 project.*
- #define **WOLFSENTRY\_AF\_INET6** 10  
*IP version 6.*
- #define **WOLFSENTRY\_AF\_ROSE** 11  
*Amateur Radio X.25 PLP.*
- #define **WOLFSENTRY\_AF\_DECnet** 12  
*Reserved for DECnet project.*
- #define **WOLFSENTRY\_AF\_NETBEUI** 13  
*Reserved for 802.2LLC project.*
- #define **WOLFSENTRY\_AF\_SECURITY** 14  
*Security callback pseudo AF.*
- #define **WOLFSENTRY\_AF\_KEY** 15  
*PF\_KEY key management API.*
- #define **WOLFSENTRY\_AF\_NETLINK** 16
- #define **WOLFSENTRY\_AF\_ROUTE** WOLFSENTRY\_AF\_NETLINK  
*Alias to emulate 4.4BSD.*
- #define **WOLFSENTRY\_AF\_PACKET** 17  
*Packet family.*
- #define **WOLFSENTRY\_AF\_ASH** 18  
*Ash.*
- #define **WOLFSENTRY\_AF\_ECONET** 19  
*Acorn Econet.*
- #define **WOLFSENTRY\_AF\_ATMSVC** 20  
*ATM SVCs.*
- #define **WOLFSENTRY\_AF\_RDS** 21  
*RDS sockets.*
- #define **WOLFSENTRY\_AF\_SNA** 22

- Linux SNA Project (nutters!)*
- #define **WOLFSENTRY\_AF\_IRDA** 23  
*IRDA sockets.*
  - #define **WOLFSENTRY\_AF\_PPPOX** 24  
*PPPoX sockets.*
  - #define **WOLFSENTRY\_AF\_WANPIPE** 25  
*Wanpipe API Sockets.*
  - #define **WOLFSENTRY\_AF\_LLC** 26  
*Linux LLC.*
  - #define **WOLFSENTRY\_AF\_IB** 27  
*Native InfiniBand address.*
  - #define **WOLFSENTRY\_AF\_MPLS** 28  
*MPLS.*
  - #define **WOLFSENTRY\_AF\_CAN** 29  
*Controller Area Network.*
  - #define **WOLFSENTRY\_AF\_TIPC** 30  
*TIPC sockets.*
  - #define **WOLFSENTRY\_AF\_BLUETOOTH** 31  
*Bluetooth sockets.*
  - #define **WOLFSENTRY\_AF\_IUCV** 32  
*IUCV sockets.*
  - #define **WOLFSENTRY\_AF\_RXRPC** 33  
*RxRPC sockets.*
  - #define **WOLFSENTRY\_AF\_ISDN** 34  
*mISDN sockets*
  - #define **WOLFSENTRY\_AF\_PHONET** 35  
*Phonet sockets.*
  - #define **WOLFSENTRY\_AF\_IEEE802154** 36  
*IEEE802154 sockets.*
  - #define **WOLFSENTRY\_AF\_CAIF** 37  
*CAIF sockets.*
  - #define **WOLFSENTRY\_AF\_ALG** 38  
*Algorithm sockets.*
  - #define **WOLFSENTRY\_AF\_NFC** 39  
*NFC sockets.*
  - #define **WOLFSENTRY\_AF\_VSOCK** 40  
*vSockets*
  - #define **WOLFSENTRY\_AF\_KCM** 41  
*Kernel Connection Multiplexor.*
  - #define **WOLFSENTRY\_AF\_QIPCRTR** 42  
*Qualcomm IPC Router.*
  - #define **WOLFSENTRY\_AF\_SMC** 43  
*smc sockets: reserve number for PF\_SMC protocol family that reuses WOLFSENTRY\_AF\_INET address family*
  - #define **WOLFSENTRY\_AF\_XDP** 44  
*XDP sockets.*
  - #define **WOLFSENTRY\_AF\_BSD\_OFFSET** 100  
*from FreeBSD at commit a56e5ad6, except WOLFSENTRY\_AF\_LINK64, added here.*
  - #define **WOLFSENTRY\_AF\_IMPLINK** ([WOLFSENTRY\\_AF\\_BSD\\_OFFSET](#) + 3)  
*arpanet imp addresses*
  - #define **WOLFSENTRY\_AF\_PUP** ([WOLFSENTRY\\_AF\\_BSD\\_OFFSET](#) + 4)  
*pup protocols: e.g. BSP*

- #define **WOLFSENTRY\_AF\_CHAOS** ([WOLFSENTRY\\_AF\\_BSD\\_OFFSET](#) + 5)  
*mit CHAOS protocols*
- #define **WOLFSENTRY\_AF\_NETBIOS** ([WOLFSENTRY\\_AF\\_BSD\\_OFFSET](#) + 6)  
*SMB protocols.*
- #define **WOLFSENTRY\_AF\_ISO** ([WOLFSENTRY\\_AF\\_BSD\\_OFFSET](#) + 7)  
*ISO protocols.*
- #define **WOLFSENTRY\_AF\_OSI** [WOLFSENTRY\\_AF\\_ISO](#)
- #define **WOLFSENTRY\_AF\_ECMA** ([WOLFSENTRY\\_AF\\_BSD\\_OFFSET](#) + 8)  
*European computer manufacturers.*
- #define **WOLFSENTRY\_AF\_DATAKIT** ([WOLFSENTRY\\_AF\\_BSD\\_OFFSET](#) + 9)  
*datakit protocols*
- #define **WOLFSENTRY\_AF\_DLI** ([WOLFSENTRY\\_AF\\_BSD\\_OFFSET](#) + 13)  
*DEC Direct data link interface.*
- #define **WOLFSENTRY\_AF\_LAT** ([WOLFSENTRY\\_AF\\_BSD\\_OFFSET](#) + 14)  
*LAT.*
- #define **WOLFSENTRY\_AF\_HYLINK** ([WOLFSENTRY\\_AF\\_BSD\\_OFFSET](#) + 15)  
*NSC Hyperchannel.*
- #define **WOLFSENTRY\_AF\_LINK48** ([WOLFSENTRY\\_AF\\_BSD\\_OFFSET](#) + 18)  
*Link layer interface, explicit EUI-48.*
- #define **WOLFSENTRY\_AF\_LINK** [WOLFSENTRY\\_AF\\_LINK48](#)  
*Link layer interface, implicit EUI-48.*
- #define **WOLFSENTRY\_AF\_LINK64** ([WOLFSENTRY\\_AF\\_BSD\\_OFFSET](#) + 19)  
*Link layer interface, explicit EUI-64.*
- #define **WOLFSENTRY\_AF\_COIP** ([WOLFSENTRY\\_AF\\_BSD\\_OFFSET](#) + 20)  
*connection-oriented IP, aka ST II*
- #define **WOLFSENTRY\_AF\_CNT** ([WOLFSENTRY\\_AF\\_BSD\\_OFFSET](#) + 21)  
*Computer Network Technology.*
- #define **WOLFSENTRY\_AF\_SIP** ([WOLFSENTRY\\_AF\\_BSD\\_OFFSET](#) + 24)  
*Simple Internet Protocol.*
- #define **WOLFSENTRY\_AF\_SLOW** ([WOLFSENTRY\\_AF\\_BSD\\_OFFSET](#) + 33)  
*802.3ad slow protocol*
- #define **WOLFSENTRY\_AF\_SCLUSTER** ([WOLFSENTRY\\_AF\\_BSD\\_OFFSET](#) + 34)  
*Sitara cluster protocol.*
- #define **WOLFSENTRY\_AF\_ARP** ([WOLFSENTRY\\_AF\\_BSD\\_OFFSET](#) + 35)
- #define **WOLFSENTRY\_AF\_IEEE80211** ([WOLFSENTRY\\_AF\\_BSD\\_OFFSET](#) + 37)  
*IEEE 802.11 protocol.*
- #define **WOLFSENTRY\_AF\_INET\_SDP** ([WOLFSENTRY\\_AF\\_BSD\\_OFFSET](#) + 40)  
*OFED Socket Direct Protocol ipv4.*
- #define **WOLFSENTRY\_AF\_INET6\_SDP** ([WOLFSENTRY\\_AF\\_BSD\\_OFFSET](#) + 42)  
*OFED Socket Direct Protocol ipv6.*
- #define **WOLFSENTRY\_AF\_HYPERV** ([WOLFSENTRY\\_AF\\_BSD\\_OFFSET](#) + 43)  
*HyperV sockets.*
- #define **WOLFSENTRY\_AF\_USER\_OFFSET** 256

## Typedefs

- typedef [wolfentry\\_errcode\\_t](#)(\* [wolfentry\\_addr\\_family\\_parser\\_t](#)) ([WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#), const char \*addr\_text, int addr\_text\_len, [byte](#) \*addr\_internal, [wolfentry\\_addr\\_bits\\_t](#) \*addr\_internal\_bits)  
*Function type for parsing handler, to pass to [wolfentry\\_addr\\_family\\_handler\\_install\(\)](#)*
- typedef [wolfentry\\_errcode\\_t](#)(\* [wolfentry\\_addr\\_family\\_formatter\\_t](#)) ([WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#), const [byte](#) \*addr\_internal, unsigned int addr\_internal\_bits, char \*addr\_text, int \*addr\_text\_len)  
*Function type for formatting handler, to pass to [wolfentry\\_addr\\_family\\_handler\\_install\(\)](#)*

## Functions

- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_addr\\_family\\_handler\\_install](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, [wolfentry\\_addr\\_family\\_t](#) family\_bynumber, const char \*family\_byname, int family\_byname\_len, [wolfentry\\_addr\\_family\\_parser\\_t](#) parser, [wolfentry\\_addr\\_family\\_formatter\\_t](#) formatter, int max\_addr\_bits)  
*Install handlers for an address family.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_addr\\_family\\_get\\_parser](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, [wolfentry\\_addr\\_family\\_t](#) family, [wolfentry\\_addr\\_family\\_parser\\_t](#) \*parser)  
*Retrieve the parsing handler for an address family.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_addr\\_family\\_get\\_formatter](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, [wolfentry\\_addr\\_family\\_t](#) family, [wolfentry\\_addr\\_family\\_formatter\\_t](#) \*formatter)  
*Retrieve the formatting handler for an address family.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_addr\\_family\\_handler\\_remove\\_bynumber](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, [wolfentry\\_addr\\_family\\_t](#) family\_bynumber, [wolfentry\\_action\\_res\\_t](#) \*action\_results)  
*Remove the handlers for an address family.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_addr\\_family\\_drop\\_reference](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, struct [wolfentry\\_addr\\_family\\_bynumber](#) \*family\_bynumber, [wolfentry\\_action\\_res\\_t](#) \*action\_results)  
*Release an address family record previously returned by [wolfentry\\_addr\\_family\\_ntop\(\)](#)*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_addr\\_family\\_handler\\_remove\\_byname](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const char \*family\_byname, int family\_byname\_len, [wolfentry\\_action\\_res\\_t](#) \*action\_results)  
*Remove the handlers for an address family.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_addr\\_family\\_pton](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const char \*family\_name, int family\_name\_len, [wolfentry\\_addr\\_family\\_t](#) \*family\_number)  
*Look up an address family by name, returning its number.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_addr\\_family\\_ntop](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, [wolfentry\\_addr\\_family\\_t](#) family, struct [wolfentry\\_addr\\_family\\_bynumber](#) \*\*addr\_family, const char \*\*family\_name)  
*Look up an address family by number, returning a pointer to its name. The caller must release *addr\_family*, using [wolfentry\\_addr\\_family\\_drop\\_reference\(\)](#), when done accessing *family\_name*.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_addr\\_family\\_max\\_addr\\_bits](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, [wolfentry\\_addr\\_family\\_t](#) family, [wolfentry\\_addr\\_bits\\_t](#) \*bits)  
*Look up the max address size for an address family identified by number.*

### 8.7.1 Detailed Description

## 8.8 User-Defined Value Subsystem

### Data Structures

- struct [wolfentry\\_kv\\_pair](#)  
*public structure for passing user-defined values in/out of wolfSentry*

### Macros

- #define **WOLFSENTRY\_KV\_FLAG\_MASK**  
*A bit mask to retain only the flag bits in a [wolfentry\\_kv\\_type\\_t](#).*
- #define **WOLFSENTRY\_KV\_KEY\_LEN**(kv)  
*Evaluates to the length of the key of a [wolfentry\\_kv\\_pair](#).*
- #define **WOLFSENTRY\_KV\_KEY**(kv)  
*Evaluates to the key of a [wolfentry\\_kv\\_pair](#).*

- `#define WOLFSENTRY_KV_TYPE(kv)`  
*Evaluates to the type of a `wolfentry_kv_pair`, with flag bits masked out.*
- `#define WOLFSENTRY_KV_V_UINT(kv)`  
*Evaluates to the `uint64_t` value of a `wolfentry_kv_pair` of type `WOLFSENTRY_KV_UINT`.*
- `#define WOLFSENTRY_KV_V_SINT(kv)`  
*Evaluates to the `int64_t` value of a `wolfentry_kv_pair` of type `WOLFSENTRY_KV_INT`.*
- `#define WOLFSENTRY_KV_V_FLOAT(kv)`  
*Evaluates to the `double` value of a `wolfentry_kv_pair` of type `WOLFSENTRY_KV_FLOAT`.*
- `#define WOLFSENTRY_KV_V_STRING_LEN(kv)`  
*Evaluates to the `size_t` length of the value of a `wolfentry_kv_pair` of type `WOLFSENTRY_KV_STRING`.*
- `#define WOLFSENTRY_KV_V_STRING(kv)`  
*Evaluates to the `char *` value of a `wolfentry_kv_pair` of type `WOLFSENTRY_KV_STRING`.*
- `#define WOLFSENTRY_KV_V_BYTES_LEN(kv)`  
*Evaluates to the `size_t` length of the value of a `wolfentry_kv_pair` of type `WOLFSENTRY_KV_BYTES`.*
- `#define WOLFSENTRY_KV_V_BYTES(kv)`  
*Evaluates to the `byte *` value of a `wolfentry_kv_pair` of type `WOLFSENTRY_KV_BYTES`.*
- `#define WOLFSENTRY_KV_V_JSON(kv)`  
*Evaluates to the `JSON_VALUE *` value of a `wolfentry_kv_pair` of type `WOLFSENTRY_KV_JSON`.*
- `#define WOLFSENTRY_BASE64_DECODED_BUFSPC(buf, len)`  
*Given valid base64 string `buf` of length `len`, evaluates to the exact decoded length.*

### Typedefs

- `typedef wolfentry_errcode_t(* wolfentry_kv_validator_t) (WOLFSENTRY_CONTEXT_ARGS_IN, struct wolfentry_kv_pair *kv)`

### Enumerations

- `enum wolfentry_kv_type_t {`  
`WOLFSENTRY_KV_NONE = 0,`  
`WOLFSENTRY_KV_NULL,`  
`WOLFSENTRY_KV_TRUE,`  
`WOLFSENTRY_KV_FALSE,`  
`WOLFSENTRY_KV_UINT,`  
`WOLFSENTRY_KV_SINT,`  
`WOLFSENTRY_KV_FLOAT,`  
`WOLFSENTRY_KV_STRING,`  
`WOLFSENTRY_KV_BYTES,`  
`WOLFSENTRY_KV_JSON,`  
`WOLFSENTRY_KV_FLAG_READONLY = 1 << 30 }`  
*enum to represent the type of a user-defined value*

### Functions

- `WOLFSENTRY_API wolfentry_errcode_t wolfentry_user_value_set_validator (WOLFSENTRY_CONTEXT_ARGS_IN, wolfentry_kv_validator_t validator, wolfentry_action_res_t *action_results)`  
*Install a supplied `wolfentry_kv_validator_t` to validate all user values before inserting them into the value table.*
- `WOLFSENTRY_API wolfentry_errcode_t wolfentry_user_value_set_mutability (WOLFSENTRY_CONTEXT_ARGS_IN, const char *key, int key_len, int mutable)`

Set the user-defined value with the designated key as readwrite (*mutable=1*) or readonly (*mutable=0*). A read-only value cannot be changed or deleted.

- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_user\\_value\\_get\\_mutability](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const char \*key, int key\_len, int \*mutable)

Query the mutability of the user-defined value with the designated key. Readonly value cannot be changed or deleted.

- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_user\\_value\\_get\\_type](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const char \*key, int key\_len, [wolfentry\\_kv\\_type\\_t](#) \*type)

Returns the type of the value with the designated key, using [WOLFSENTRY\\_KV\\_TYPE\(\)](#).

- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_user\\_value\\_delete](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const char \*key, int key\_len)

Deletes the value with the designated key.

- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_user\\_value\\_store\\_null](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const char \*key, int key\_len, int overwrite\_p)

Inserts or overwrites a [WOLFSENTRY\\_KV\\_NULL](#) value with the designated key.

- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_user\\_value\\_store\\_bool](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const char \*key, int key\_len, [wolfentry\\_kv\\_type\\_t](#) value, int overwrite\_p)

Inserts or overwrites a [WOLFSENTRY\\_KV\\_TRUE](#) or [WOLFSENTRY\\_KV\\_FALSE](#) value with the designated key.

- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_user\\_value\\_get\\_bool](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const char \*key, int key\_len, [wolfentry\\_kv\\_type\\_t](#) \*value)

Gets a [WOLFSENTRY\\_KV\\_TRUE](#) or [WOLFSENTRY\\_KV\\_FALSE](#) value with the designated key.

- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_user\\_value\\_store\\_uint](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const char \*key, int key\_len, uint64\_t value, int overwrite\_p)

Inserts or overwrites a [WOLFSENTRY\\_KV\\_UINT](#) value with the designated key.

- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_user\\_value\\_get\\_uint](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const char \*key, int key\_len, uint64\_t \*value)

Gets a [WOLFSENTRY\\_KV\\_UINT](#) value with the designated key.

- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_user\\_value\\_store\\_sint](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const char \*key, int key\_len, int64\_t value, int overwrite\_p)

Inserts or overwrites a [WOLFSENTRY\\_KV\\_SINT](#) value with the designated key.

- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_user\\_value\\_get\\_sint](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const char \*key, int key\_len, int64\_t \*value)

Gets a [WOLFSENTRY\\_KV\\_UINT](#) value with the designated key.

- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_user\\_value\\_store\\_double](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const char \*key, int key\_len, double value, int overwrite\_p)

Inserts or overwrites a [WOLFSENTRY\\_KV\\_FLOAT](#) value with the designated key.

- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_user\\_value\\_get\\_float](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const char \*key, int key\_len, double \*value)

Gets a [WOLFSENTRY\\_KV\\_UINT](#) value with the designated key.

- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_user\\_value\\_store\\_string](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const char \*key, int key\_len, const char \*value, int value\_len, int overwrite\_p)

Inserts or overwrites a [WOLFSENTRY\\_KV\\_STRING](#) value with the designated key.

- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_user\\_value\\_get\\_string](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const char \*key, int key\_len, const char \*\*value, int \*value\_len, struct wolfentry\_kv\_pair\_internal \*\*user↔\_value\_record)

Gets a [WOLFSENTRY\\_KV\\_STRING](#) value with the designated key.

- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_user\\_value\\_store\\_bytes](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const char \*key, int key\_len, const byte \*value, int value\_len, int overwrite\_p)

Inserts or overwrites a [WOLFSENTRY\\_KV\\_BYTES](#) value with the designated key and a binary-clean value.

- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_user\\_value\\_store\\_bytes\\_base64](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const char \*key, int key\_len, const char \*value, int value\_len, int overwrite\_p)

Inserts or overwrites a [WOLFSENTRY\\_KV\\_BYTES](#) value with the designated key and a base64-encoded value.



- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_user\\_value\\_get\\_bytes](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const char \*key, int key\_len, const byte \*\*value, int \*value\_len, struct wolfentry\_kv\_pair\_internal \*\*user\_value\_record)  
*Gets a WOLFSENTRY\_KV\_BYTES value with the designated key.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_user\\_value\\_store\\_json](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const char \*key, int key\_len, JSON\_VALUE \*value, int overwrite\_p)  
*Inserts or overwrites a WOLFSENTRY\_KV\_JSON value with the designated key and a value from json\_document\_parse() (or built up programmatically with the centijson\_value.h API).*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_user\\_value\\_get\\_json](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const char \*key, int key\_len, JSON\_VALUE \*\*value, struct wolfentry\_kv\_pair\_internal \*\*user\_value\_record)  
*Gets a WOLFSENTRY\_KV\_JSON value with the designated key.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_user\\_value\\_release\\_record](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, struct wolfentry\_kv\_pair\_internal \*\*user\_value\_record)  
*Release a user\_value\_record from wolfentry\_user\_value\_get\_string(), wolfentry\_user\_value\_get\_bytes() or wolfentry\_user\_value\_get\_json().*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_kv\\_pair\\_export](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, struct wolfentry\_kv\_pair\_internal \*kv, const struct wolfentry\_kv\_pair \*\*kv\_exports)  
*Extract the struct wolfentry\_kv\_pair from a struct wolfentry\_kv\_pair\_internal. Caller must have a shared or exclusive lock on the context.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_kv\\_type\\_to\\_string](#) (wolfentry\_kv\_type\_t type, const char \*\*out)  
*Return a human-readable rendering of a wolfentry\_kv\_type\_t.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_kv\\_render\\_value](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const struct wolfentry\_kv\_pair \*kv, char \*out, int \*out\_len)  
*Render kv in human-readable form to caller-preallocated buffer out.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_user\\_values\\_iterate\\_start](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, struct wolfentry\_cursor \*\*cursor)  
*Start an iteration loop on the user values table of this context. Caller must have a lock on the context at entry.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_user\\_values\\_iterate\\_seek\\_to\\_head](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, struct wolfentry\_cursor \*cursor)  
*Move the cursor to point to the start of the user values table. Caller must have a lock on the context at entry.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_user\\_values\\_iterate\\_seek\\_to\\_tail](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, struct wolfentry\_cursor \*cursor)  
*Move the cursor to point to the end of the user values table. Caller must have a lock on the context at entry.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_user\\_values\\_iterate\\_current](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, struct wolfentry\_cursor \*cursor, struct wolfentry\_kv\_pair\_internal \*\*kv)  
*Return the item to which the cursor currently points, without moving the cursor. Caller must have a lock on the context at entry.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_user\\_values\\_iterate\\_prev](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, struct wolfentry\_cursor \*cursor, struct wolfentry\_kv\_pair\_internal \*\*kv)  
*Move the cursor to the previous item, and return it. Caller must have a lock on the context at entry.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_user\\_values\\_iterate\\_next](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, struct wolfentry\_cursor \*cursor, struct wolfentry\_kv\_pair\_internal \*\*kv)  
*Move the cursor to the next item, and return it. Caller must have a lock on the context at entry.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_user\\_values\\_iterate\\_end](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, struct wolfentry\_cursor \*\*cursor)  
*End an iteration loop started with wolfentry\_user\_values\_iterate\_start(). Caller must have a lock on the context at entry.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_base64\\_decode](#) (const char \*src, size\_t src\_len, byte \*dest, size\_t \*dest\_spc, int ignore\_junk\_p)  
*Convert base64-encoded input src to binary output dest, optionally ignoring (with nonzero ignore\_junk\_p) non-base64 characters in src.*

### 8.8.1 Detailed Description

### 8.8.2 Typedef Documentation

#### 8.8.2.1 wolfentry\_kv\_validator\_t

```
typedef wolfentry_errcode_t (* wolfentry_kv_validator_t) (WOLFSENTRY_CONTEXT_ARGS_IN, struct
wolfentry_kv_pair *kv)
```

Function type for user-supplied value validators.

### 8.8.3 Function Documentation

#### 8.8.3.1 wolfentry\_user\_value\_get\_bytes()

```
WOLFSENTRY_API wolfentry_errcode_t wolfentry_user_value_get_bytes (
    WOLFSENTRY_CONTEXT_ARGS_IN ,
    const char * key,
    int key_len,
    const byte ** value,
    int * value_len,
    struct wolfentry_kv_pair_internal ** user_value_record )
```

Gets a WOLFSENTRY\_KV\_BYTES value with the designated key.

The `user_value_record` will be used to store a pointer to an internal structure, which acts as a lease on the value. This must be released with `wolfentry_user_value_release_record()` when done.

#### 8.8.3.2 wolfentry\_user\_value\_get\_json()

```
WOLFSENTRY_API wolfentry_errcode_t wolfentry_user_value_get_json (
    WOLFSENTRY_CONTEXT_ARGS_IN ,
    const char * key,
    int key_len,
    JSON_VALUE ** value,
    struct wolfentry_kv_pair_internal ** user_value_record )
```

Gets a WOLFSENTRY\_KV\_JSON value with the designated key.

The `user_value_record` will be used to store a pointer to an internal structure, which acts as a lease on the value. This must be released with `wolfentry_user_value_release_record()` when done.

#### 8.8.3.3 wolfentry\_user\_value\_get\_string()

```
WOLFSENTRY_API wolfentry_errcode_t wolfentry_user_value_get_string (
    WOLFSENTRY_CONTEXT_ARGS_IN ,
    const char * key,
    int key_len,
    const char ** value,
    int * value_len,
    struct wolfentry_kv_pair_internal ** user_value_record )
```

Gets a WOLFSENTRY\_KV\_STRING value with the designated key.

The `user_value_record` will be used to store a pointer to an internal structure, which acts as a lease on the value. This must be released with `wolfentry_user_value_release_record()` when done.

## 8.9 Object Subsystem

### Typedefs

- typedef `wolfentry_errcode_t`(\* `wolfentry_make_id_cb_t`) (void \*context, `wolfentry_ent_id_t` \*id)

### Enumerations

- enum `wolfentry_object_type_t` {  
`WOLFENTRY_OBJECT_TYPE_UNINITED` ,  
`WOLFENTRY_OBJECT_TYPE_TABLE` ,  
`WOLFENTRY_OBJECT_TYPE_ACTION` ,  
`WOLFENTRY_OBJECT_TYPE_EVENT` ,  
`WOLFENTRY_OBJECT_TYPE_ROUTE` ,  
`WOLFENTRY_OBJECT_TYPE_KV` ,  
`WOLFENTRY_OBJECT_TYPE_ADDR_FAMILY_BYNUMBER` ,  
`WOLFENTRY_OBJECT_TYPE_ADDR_FAMILY_BYNAME` }

*enum for communicating the type of an object.*

### Functions

- WOLFENTRY\_API `wolfentry_object_type_t` `wolfentry_get_object_type` (const void \*object)  
*Get the object type from a wolfentry object pointer.*
- WOLFENTRY\_API `wolfentry_ent_id_t` `wolfentry_get_object_id` (const void \*object)  
*Get the ID from a wolfentry object pointer.*
- WOLFENTRY\_API `wolfentry_errcode_t` `wolfentry_table_ent_get_by_id` (`WOLFENTRY_CONTEXT_ARGS_IN`, `wolfentry_ent_id_t` id, struct `wolfentry_table_ent_header` \*\*ent)  
*Retrieve an object pointer given its ID. Lock must be obtained before entry, and ent is only valid while lock is held, or if `wolfentry_object_checkout()` is called for the object.*
- WOLFENTRY\_API `wolfentry_errcode_t` `wolfentry_object_checkout` (`WOLFENTRY_CONTEXT_ARGS_IN`, void \*object)  
*Increment the refcount for an object, making it safe from deallocation until `wolfentry_object_release()`. Caller must have a context lock on entry.*
- WOLFENTRY\_API `wolfentry_errcode_t` `wolfentry_object_release` (`WOLFENTRY_CONTEXT_ARGS_IN`, void \*object, `wolfentry_action_res_t` \*action\_results)  
*Decrement the refcount for an object, deallocating it if no references remain. Caller does not need to have a context lock on entry.*
- WOLFENTRY\_API `wolfentry_hitcount_t` `wolfentry_table_n_inserts` (struct `wolfentry_table_header` \*table)  
*Get the number of inserts into a table.*
- WOLFENTRY\_API `wolfentry_hitcount_t` `wolfentry_table_n_deletes` (struct `wolfentry_table_header` \*table)  
*Get the number of deletes from a table.*

### 8.9.1 Detailed Description

### 8.9.2 Enumeration Type Documentation

#### 8.9.2.1 `wolfentry_object_type_t`

enum `wolfentry_object_type_t`

enum for communicating the type of an object.

## Enumerator

WOLFSENTRY_OBJECT_TYPE_UNINITED	Object is null or uninitialized.
WOLFSENTRY_OBJECT_TYPE_TABLE	Not currently used.
WOLFSENTRY_OBJECT_TYPE_ACTION	Object is a <code>struct wolfsentry_action</code> .
WOLFSENTRY_OBJECT_TYPE_EVENT	Object is a <code>struct wolfsentry_event</code> .
WOLFSENTRY_OBJECT_TYPE_ROUTE	Object is a <code>struct wolfsentry_route</code> .
WOLFSENTRY_OBJECT_TYPE_KV	Object is a <code>struct wolfsentry_kv_pair_internal</code> .
WOLFSENTRY_OBJECT_TYPE_ADDR_FAMILY_↔ BYNUMBER	Object is a <code>struct wolfsentry_addr_family_bynumber</code> .
WOLFSENTRY_OBJECT_TYPE_ADDR_FAMILY_↔ BYNAME	Object is a <code>struct wolfsentry_addr_family_byname</code> .

### 8.9.3 Function Documentation

#### 8.9.3.1 wolfsentry\_get\_object\_id()

```
WOLFSENTRY_API wolfsentry_ent_id_t wolfsentry_get_object_id (
    const void * object )
```

Get the ID from a wolfsentry object pointer.

## Parameters

<i>object</i>	a pointer to the object
---------------	-------------------------

## Returns

the object ID, or WOLFSENTRY\_OBJECT\_TYPE\_UNINITED on error.

#### 8.9.3.2 wolfsentry\_get\_object\_type()

```
WOLFSENTRY_API wolfsentry_object_type_t wolfsentry_get_object_type (
    const void * object )
```

Get the object type from a wolfsentry object pointer.

## Parameters

<i>object</i>	a pointer to the object
---------------	-------------------------

## Returns

the object type, or WOLFSENTRY\_OBJECT\_TYPE\_UNINITED on error.

### 8.9.3.3 wolfsentry\_table\_n\_deletes()

```
WOLFSENTRY_API wolfsentry_hitcount_t wolfsentry_table_n_deletes (
    struct wolfsentry_table_header * table )
```

Get the number of deletes from a table.

#### Parameters

<i>table</i>	the table to get the deletes for
--------------	----------------------------------

#### Returns

the total delete count

### 8.9.3.4 wolfsentry\_table\_n\_inserts()

```
WOLFSENTRY_API wolfsentry_hitcount_t wolfsentry_table_n_inserts (
    struct wolfsentry_table_header * table )
```

Get the number of inserts into a table.

#### Parameters

<i>table</i>	the table to get the inserts for
--------------	----------------------------------

#### Returns

the total insert count

## 8.10 Thread Synchronization Subsystem

### Data Structures

- struct [wolfsentry\\_thread\\_context\\_public](#)  
*Right-sized, right-aligned opaque container for thread state.*

### Macros

- #define **WOLFSENTRY\_CONTEXT\_ARGS\_IN**  
*Common context argument generator for use at the beginning of arg lists in function prototypes and definitions. Pair with **WOLFSENTRY\_CONTEXT\_ARGS\_OUT** in the caller argument list.*
- #define **WOLFSENTRY\_CONTEXT\_ARGS\_IN\_EX**(ctx)  
*Variant of **WOLFSENTRY\_CONTEXT\_ARGS\_IN** that allows a fully type-qualified context to be supplied explicitly (allowing contexts other than `struct wolfsentry_context`)*
- #define **WOLFSENTRY\_CONTEXT\_ARGS\_IN\_EX4**(ctx, thr)  
*Variant of **WOLFSENTRY\_CONTEXT\_ARGS\_IN** that allows the identifiers for context and thread pointers to be supplied explicitly.*

- **#define WOLFSENTRY\_CONTEXT\_ELEMENTS**  
Variant of `WOLFSENTRY_CONTEXT_ARGS_IN` for constructing structs.
- **#define WOLFSENTRY\_CONTEXT\_SET\_ELEMENTS(s)**  
Counterpart to `WOLFSENTRY_CONTEXT_ELEMENTS` to access the `wolfentry` context.
- **#define WOLFSENTRY\_CONTEXT\_GET\_ELEMENTS(s)**  
Counterpart to `WOLFSENTRY_CONTEXT_ELEMENTS` to access the thread context (exists only if defined (`↔ WOLFSENTRY_THREADSAFE`))
- **#define WOLFSENTRY\_CONTEXT\_ARGS\_OUT**  
Common context argument generator to use in calls to functions taking `WOLFSENTRY_CONTEXT_ARGS_IN`
- **#define WOLFSENTRY\_CONTEXT\_ARGS\_OUT\_EX(ctx)**  
Variant of `WOLFSENTRY_CONTEXT_ARGS_OUT` that allows passing an explicitly identified context argument generator to use in calls to functions taking `WOLFSENTRY_CONTEXT_ARGS_IN_EX`
- **#define WOLFSENTRY\_CONTEXT\_ARGS\_OUT\_EX2(x)**  
Variant of `WOLFSENTRY_CONTEXT_ARGS_OUT` corresponding to `WOLFSENTRY_CONTEXT_ELEMENTS`
- **#define WOLFSENTRY\_CONTEXT\_ARGS\_OUT\_EX3(x, y)**  
Special-purpose variant of `WOLFSENTRY_CONTEXT_ARGS_OUT_EX` for accessing context element `y` in structure pointer `x`
- **#define WOLFSENTRY\_CONTEXT\_ARGS\_OUT\_EX4(x, y)**  
Special-purpose variant of `WOLFSENTRY_CONTEXT_ARGS_OUT` that simply expands to `x` or `x, y` depending on `WOLFSENTRY_THREADSAFE`
- **#define WOLFSENTRY\_CONTEXT\_ARGS\_NOT\_USED**  
Helper macro for function implementations that need to accept `WOLFSENTRY_CONTEXT_ARGS_IN` for API conformance, but don't actually use the arguments.
- **#define WOLFSENTRY\_CONTEXT\_ARGS\_THREAD\_NOT\_USED**  
Helper macro for function implementations that need to accept `WOLFSENTRY_CONTEXT_ARGS_IN` for API conformance, but don't actually use the `thread` argument.
- **#define WOLFSENTRY\_THREAD\_HEADER\_DECLS**
- **#define WOLFSENTRY\_THREAD\_HEADER\_INIT(flags)**  
For `WOLFSENTRY_THREADSAFE` applications, this allocates the required thread context on the stack.
- **#define WOLFSENTRY\_THREAD\_HEADER\_INIT\_CHECKED(flags)**  
For `WOLFSENTRY_THREADSAFE` applications, this performs the required thread context initialization, with options from its `wolfentry_thread_flags_t flags` arg.
- **#define WOLFSENTRY\_THREAD\_HEADER(flags)**  
For `WOLFSENTRY_THREADSAFE` applications, this performs the required thread context initialization, with options from its `wolfentry_thread_flags_t flags` arg, and returns on failure.
- **#define WOLFSENTRY\_THREAD\_HEADER\_CHECK()**  
For `WOLFSENTRY_THREADSAFE` applications, this allocates the required thread context on the stack, and initializes it with options from its `wolfentry_thread_flags_t flags` arg.
- **#define WOLFSENTRY\_THREAD\_HEADER\_CHECKED(flags)**  
For `WOLFSENTRY_THREADSAFE` applications, checks if thread context initialization succeeded, and returns on failure.
- **#define WOLFSENTRY\_THREAD\_TAILER(flags)**  
For `WOLFSENTRY_THREADSAFE` applications, this allocates the required thread context on the stack, and initializes it with options from its `wolfentry_thread_flags_t flags` arg, returning on failure.
- **#define WOLFSENTRY\_THREAD\_TAILER\_CHECKED(flags)**  
For `WOLFSENTRY_THREADSAFE` applications, this cleans up a thread context allocated with `WOLFSENTRY_↔ THREAD_HEADER*`, with options from its `wolfentry_thread_flags_t flags` arg, returning on error.
- **#define WOLFSENTRY\_THREAD\_GET\_ERROR**  
For `WOLFSENTRY_THREADSAFE` applications, this evaluates to the most recent result from `WOLFSENTRY_THREAD_HEADER_INIT` or `WOLFSENTRY_THREAD_TAILER()`
- **#define WOLFSENTRY\_DEADLINE\_NEVER (-1)**  
Value returned in `deadline->tv_sec` and `deadline->tv_nsec` by `wolfentry_get_thread_deadline()` when thread has no deadline set. Not allowed as explicit values passed to `wolfentry_set_deadline_abs()` – use `wolfentry_clear_deadline()` to clear any deadline. Can be overridden with user settings.

- **#define WOLFSENTRY\_DEADLINE\_NOW** (-2)  
*Value returned in `deadline->tv_sec` and `deadline->tv_nsec` by `wolfentry_get_thread_deadline()` when `thread` is in non-blocking mode. Not allowed as explicit values passed to `wolfentry_set_deadline_abs()` – use `wolfentry_set_deadline_rel_usecs(WOLFSENTRY_CONTEXT_ARGS_OUT, 0)` to put thread in non-blocking mode. Can be overridden with user settings.*
- **#define WOLFSENTRY\_THREAD\_NO\_ID** 0
- **#define WOLFSENTRY\_THREAD\_CONTEXT\_PUBLIC\_INITIALIZER** {0}

## Enumerations

- enum `wolfentry_thread_flags_t` {  
`WOLFSENTRY_THREAD_FLAG_NONE` ,  
`WOLFSENTRY_THREAD_FLAG_DEADLINE` ,  
`WOLFSENTRY_THREAD_FLAG_READONLY` }  
*`wolfentry_thread_flags_t` flags are to be ORed together.*
- enum `wolfentry_lock_flags_t` {  
`WOLFSENTRY_LOCK_FLAG_NONE` ,  
`WOLFSENTRY_LOCK_FLAG_PSHARED` ,  
`WOLFSENTRY_LOCK_FLAG_SHARED_ERROR_CHECKING` ,  
`WOLFSENTRY_LOCK_FLAG_NONRECURSIVE_MUTEX` ,  
`WOLFSENTRY_LOCK_FLAG_NONRECURSIVE_SHARED` ,  
`WOLFSENTRY_LOCK_FLAG_GET_RESERVATION_TOO` ,  
`WOLFSENTRY_LOCK_FLAG_TRY_RESERVATION_TOO` ,  
`WOLFSENTRY_LOCK_FLAG_ABANDON_RESERVATION_TOO` ,  
`WOLFSENTRY_LOCK_FLAG_AUTO_DOWNGRADE` ,  
`WOLFSENTRY_LOCK_FLAG_RETAIN_SEMAPHORE` }  
*flags to pass to `wolfentry_lock_*()` functions, to be ORd together*

## Functions

- WOLFSENTRY\_API `wolfentry_errcode_t wolfentry_init_thread_context` (struct `wolfentry_thread_↔`  
context \*thread\_context, `wolfentry_thread_flags_t` init\_thread\_flags, void \*user\_context)  
*Initialize `thread_context` according to `init_thread_flags`, storing `user_context` for later retrieval with `wolfentry_get_thread_user_context()`.*
- WOLFSENTRY\_API `wolfentry_errcode_t wolfentry_alloc_thread_context` (struct `wolfentry_host_platform_interface`  
\*`hpi`, struct `wolfentry_thread_context` \*\*thread\_context, `wolfentry_thread_flags_t` init\_thread\_flags, void  
\*user\_context)  
*Allocate space for `thread_context` using the allocator in `hpi`, then call `wolfentry_init_thread_context()`.*
- WOLFSENTRY\_API `wolfentry_errcode_t wolfentry_get_thread_id` (struct `wolfentry_thread_context`  
\*thread, `wolfentry_thread_id_t` \*id)  
*Write the `wolfentry_thread_id_t` of thread to `id`.*
- WOLFSENTRY\_API `wolfentry_errcode_t wolfentry_get_thread_user_context` (struct `wolfentry_↔`  
thread\_context \*thread, void \*\*user\_context)  
*Store to `user_context` the pointer previously passed to `wolfentry_init_thread_context()`.*
- WOLFSENTRY\_API `wolfentry_errcode_t wolfentry_get_thread_deadline` (struct `wolfentry_thread_↔`  
context \*thread, struct timespec \*deadline)  
*Store the deadline for thread to `deadline`, or if the thread has no deadline set, store `WOLFSENTRY_DEADLINE_NEVER`  
to `deadline->tv_sec` and `deadline->tv_nsec`.*
- WOLFSENTRY\_API `wolfentry_errcode_t wolfentry_get_thread_flags` (struct `wolfentry_thread_context`  
\*thread, `wolfentry_thread_flags_t` \*thread\_flags)  
*Store the flags of thread to `thread_flags`.*
- WOLFSENTRY\_API `wolfentry_errcode_t wolfentry_destroy_thread_context` (struct `wolfentry_thread_↔`  
context \*thread\_context, `wolfentry_thread_flags_t` thread\_flags)



*Perform final integrity checking on the thread state, and deallocate its ID.*

- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_free\\_thread\\_context](#) (struct [wolfentry\\_host\\_platform\\_interface](#) \*hpi, struct [wolfentry\\_thread\\_context](#) \*\*thread\_context, [wolfentry\\_thread\\_flags\\_t](#) thread\_flags)  
*Call [wolfentry\\_destroy\\_thread\\_context\(\)](#) on \*thread\_context, and if that succeeds, deallocate the thread object previously allocated by [wolfentry\\_alloc\\_thread\\_context\(\)](#).*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_set\\_deadline\\_rel\\_usec](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, int usecs)  
*Set the thread deadline to usecs in the future. The thread will not wait for a lock beyond that deadline.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_set\\_deadline\\_abs](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, time\_t epoch\_secs, long epoch\_nsecs)  
*Set the thread deadline to the time identified by epoch\_secs and epoch\_nsecs. The thread will not wait for a lock beyond that deadline.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_clear\\_deadline](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN)  
*Clear any thread deadline previously set. On time-unbounded calls such as [wolfentry\\_lock\\_shared\(\)](#) and [wolfentry\\_lock\\_mutex\(\)](#), the thread will sleep until the lock is available.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_set\\_thread\\_readonly](#) (struct [wolfentry\\_thread\\_context](#) \*thread\_context)  
*Set the thread state to allow only readonly locks to be gotten, allowing multiple shared locks to be concurrently held. If any mutexes or reservations are currently held, the call will fail.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_set\\_thread\\_readwrite](#) (struct [wolfentry\\_thread\\_context](#) \*thread\_context)  
*Set the thread state to allow both readonly and mutex locks to be gotten. If multiple shared locks are currently held, the call will fail.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_lock\\_init](#) (struct [wolfentry\\_host\\_platform\\_interface](#) \*hpi, struct [wolfentry\\_thread\\_context](#) \*thread, struct [wolfentry\\_rwlock](#) \*lock, [wolfentry\\_lock\\_flags\\_t](#) flags)  
*This initializes a semaphore lock structure created by the user.*
- WOLFSENTRY\_API size\_t [wolfentry\\_lock\\_size](#) (void)
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_lock\\_alloc](#) (struct [wolfentry\\_host\\_platform\\_interface](#) \*hpi, struct [wolfentry\\_thread\\_context](#) \*thread, struct [wolfentry\\_rwlock](#) \*\*lock, [wolfentry\\_lock\\_flags\\_t](#) flags)  
*Allocates and initializes a semaphore lock structure for use with wolfSentry.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_lock\\_shared](#) (struct [wolfentry\\_rwlock](#) \*lock, struct [wolfentry\\_thread\\_context](#) \*thread, [wolfentry\\_lock\\_flags\\_t](#) flags)  
*Requests a shared lock.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_lock\\_shared\\_abstimed](#) (struct [wolfentry\\_rwlock](#) \*lock, struct [wolfentry\\_thread\\_context](#) \*thread, const struct [timespec](#) \*abs\_timeout, [wolfentry\\_lock\\_flags\\_t](#) flags)  
*Requests a shared lock with an absolute timeout.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_lock\\_shared\\_timed](#) (struct [wolfentry\\_rwlock](#) \*lock, struct [wolfentry\\_thread\\_context](#) \*thread, [wolfentry\\_time\\_t](#) max\_wait, [wolfentry\\_lock\\_flags\\_t](#) flags)  
*Requests a shared lock with a relative timeout.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_lock\\_mutex](#) (struct [wolfentry\\_rwlock](#) \*lock, struct [wolfentry\\_thread\\_context](#) \*thread, [wolfentry\\_lock\\_flags\\_t](#) flags)  
*Requests an exclusive lock.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_lock\\_mutex\\_abstimed](#) (struct [wolfentry\\_rwlock](#) \*lock, struct [wolfentry\\_thread\\_context](#) \*thread, const struct [timespec](#) \*abs\_timeout, [wolfentry\\_lock\\_flags\\_t](#) flags)  
*Requests an exclusive lock with an absolute timeout.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_lock\\_mutex\\_timed](#) (struct [wolfentry\\_rwlock](#) \*lock, struct [wolfentry\\_thread\\_context](#) \*thread, [wolfentry\\_time\\_t](#) max\_wait, [wolfentry\\_lock\\_flags\\_t](#) flags)  
*Requests an exclusive lock with a relative timeout.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_lock\\_mutex2shared](#) (struct [wolfentry\\_rwlock](#) \*lock, struct [wolfentry\\_thread\\_context](#) \*thread, [wolfentry\\_lock\\_flags\\_t](#) flags)  
*Downgrade an exclusive lock to a shared lock.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_lock\\_shared2mutex](#) (struct [wolfentry\\_rwlock](#) \*lock, struct [wolfentry\\_thread\\_context](#) \*thread, [wolfentry\\_lock\\_flags\\_t](#) flags)



*Upgrade a shared lock to an exclusive lock.*

- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_lock\\_shared2mutex\\_abstimed](#) (struct wolfentry\_rwlock \*lock, struct wolfentry\_thread\_context \*thread, const struct timespec \*abs\_timeout, [wolfentry\\_lock\\_flags\\_t](#) flags)

*Attempt to upgrade a shared lock to an exclusive lock with an absolute timeout.*

- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_lock\\_shared2mutex\\_timed](#) (struct wolfentry\_rwlock \*lock, struct wolfentry\_thread\_context \*thread, [wolfentry\\_time\\_t](#) max\_wait, [wolfentry\\_lock\\_flags\\_t](#) flags)

*Attempt to upgrade a shared lock to an exclusive lock with a relative timeout.*

- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_lock\\_shared2mutex\\_reserve](#) (struct wolfentry\_rwlock \*lock, struct wolfentry\_thread\_context \*thread, [wolfentry\\_lock\\_flags\\_t](#) flags)

*Attempt to reserve a upgrade of a shared lock to an exclusive lock.*

- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_lock\\_shared2mutex\\_redeem](#) (struct wolfentry\_rwlock \*lock, struct wolfentry\_thread\_context \*thread, [wolfentry\\_lock\\_flags\\_t](#) flags)

*Redeem a reservation of a lock upgrade from shared to exclusive.*

- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_lock\\_shared2mutex\\_redeem\\_abstimed](#) (struct wolfentry\_rwlock \*lock, struct wolfentry\_thread\_context \*thread, const struct timespec \*abs\_timeout, [wolfentry\\_lock\\_flags\\_t](#) flags)

*Redeem a reservation of a lock upgrade from shared to exclusive with an absolute timeout.*

- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_lock\\_shared2mutex\\_redeem\\_timed](#) (struct wolfentry\_rwlock \*lock, struct wolfentry\_thread\_context \*thread, [wolfentry\\_time\\_t](#) max\_wait, [wolfentry\\_lock\\_flags\\_t](#) flags)

*Redeem a reservation of a lock upgrade from shared to exclusive with a relative timeout.*

- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_lock\\_shared2mutex\\_abandon](#) (struct wolfentry\_rwlock \*lock, struct wolfentry\_thread\_context \*thread, [wolfentry\\_lock\\_flags\\_t](#) flags)

*Abandon a reservation of a lock upgrade from shared to exclusive.*

- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_lock\\_have\\_shared](#) (struct wolfentry\_rwlock \*lock, struct wolfentry\_thread\_context \*thread, [wolfentry\\_lock\\_flags\\_t](#) flags)

*Check if the lock is held in shared state.*

- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_lock\\_have\\_mutex](#) (struct wolfentry\_rwlock \*lock, struct wolfentry\_thread\_context \*thread, [wolfentry\\_lock\\_flags\\_t](#) flags)

*Check if the lock is held in exclusive state.*

- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_lock\\_have\\_either](#) (struct wolfentry\_rwlock \*lock, struct wolfentry\_thread\_context \*thread, [wolfentry\\_lock\\_flags\\_t](#) flags)

*Check if the lock is held in either shared or exclusive state.*

- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_lock\\_have\\_shared2mutex\\_reservation](#) (struct wolfentry\_rwlock \*lock, struct wolfentry\_thread\_context \*thread, [wolfentry\\_lock\\_flags\\_t](#) flags)

*Check if an upgrade reservation is held on the lock.*

- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_lock\\_get\\_flags](#) (struct wolfentry\_rwlock \*lock, struct wolfentry\_thread\_context \*thread, [wolfentry\\_lock\\_flags\\_t](#) \*flags)

*Extract the current flags from the lock.*

- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_lock\\_unlock](#) (struct wolfentry\_rwlock \*lock, struct wolfentry\_thread\_context \*thread, [wolfentry\\_lock\\_flags\\_t](#) flags)

*Unlock a lock.*

- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_lock\\_destroy](#) (struct wolfentry\_rwlock \*lock, struct wolfentry\_thread\_context \*thread, [wolfentry\\_lock\\_flags\\_t](#) flags)

*Destroy a lock that was created with [wolfentry\\_lock\\_init\(\)](#)*

- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_lock\\_free](#) (struct wolfentry\_rwlock \*\*lock, struct wolfentry\_thread\_context \*thread, [wolfentry\\_lock\\_flags\\_t](#) flags)

*Destroy and free a lock that was created with [wolfentry\\_lock\\_alloc\(\)](#). The lock's pointer will also be set to NULL.*

- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_context\\_lock\\_mutex](#) ([WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#))

*Calls [wolfentry\\_lock\\_mutex\(\)](#) on the context.*

- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_context\\_lock\\_mutex\\_abstimed](#) ([WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#), const struct timespec \*abs\_timeout)

- Calls [wolfentry\\_lock\\_mutex\\_abstimed\(\)](#) on the context.*

  - WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_context\\_lock\\_mutex\\_abstimed\\_ex](#) ([WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#), const struct timespec \*abs\_timeout, [wolfentry\\_lock\\_flags\\_t](#) flags)
 

*variant of [wolfentry\\_context\\_lock\\_mutex\\_abstimed\(\)](#) with a *flags* arg.*
  - WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_context\\_lock\\_mutex\\_timed](#) ([WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#), [wolfentry\\_time\\_t](#) max\_wait)
 

*Calls [wolfentry\\_lock\\_mutex\\_timed\(\)](#) on the context.*
  - WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_context\\_lock\\_mutex\\_timed\\_ex](#) ([WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#), [wolfentry\\_time\\_t](#) max\_wait, [wolfentry\\_lock\\_flags\\_t](#) flags)
 

*variant of [wolfentry\\_context\\_lock\\_mutex\\_timed\(\)](#) with a *flags* arg.*
  - WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_context\\_lock\\_shared](#) ([WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#))
 

*Calls [wolfentry\\_lock\\_shared\(\)](#) on the context.*
  - WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_context\\_lock\\_shared\\_abstimed](#) ([WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#), const struct timespec \*abs\_timeout)
 

*Calls [wolfentry\\_lock\\_shared\\_abstimed\(\)](#) on the context.*
  - WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_context\\_lock\\_shared\\_with\\_reservation\\_abstimed](#) ([WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#), const struct timespec \*abs\_timeout)
 

*Calls [wolfentry\\_lock\\_shared\\_abstimed\(\)](#) on the context, with the [WOLFSENTRY\\_LOCK\\_FLAG\\_GET\\_RESERVATION\\_TOO](#) flag.*
  - WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_context\\_lock\\_shared\\_timed](#) ([WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#), [wolfentry\\_time\\_t](#) max\_wait)
 

*Calls [wolfentry\\_lock\\_shared\\_timed\(\)](#) on the context.*
  - WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_context\\_lock\\_shared\\_with\\_reservation\\_timed](#) ([WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#), [wolfentry\\_time\\_t](#) max\_wait)
 

*Calls [wolfentry\\_lock\\_shared\\_timed\(\)](#) on the context, with the [WOLFSENTRY\\_LOCK\\_FLAG\\_GET\\_RESERVATION\\_TOO](#) flag.*
  - WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_context\\_unlock](#) ([WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#))
 

*Calls [wolfentry\\_lock\\_unlock\(\)](#) on the context.*
  - WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_context\\_unlock\\_and\\_abandon\\_reservation](#) ([WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#))
 

*Calls [wolfentry\\_lock\\_unlock\(\)](#) on the context, with the [WOLFSENTRY\\_LOCK\\_FLAG\\_ABANDON\\_RESERVATION\\_TOO](#) flag.*

### 8.10.1 Detailed Description

### 8.10.2 Macro Definition Documentation

#### 8.10.2.1 WOLFSENTRY\_THREAD\_HEADER

```
#define WOLFSENTRY_THREAD_HEADER(  
    flags )
```

For WOLFSENTRY\_THREADSafe applications, this performs the required thread context initialization, with options from its `wolfentry_thread_flags_t flags` arg, and returns on failure.

<

#### 8.10.2.2 WOLFSENTRY\_THREAD\_HEADER\_CHECK

```
#define WOLFSENTRY_THREAD_HEADER_CHECK( )
```

For WOLFSENTRY\_THREADSafe applications, this allocates the required thread context on the stack, and initializes it with options from its `wolfentry_thread_flags_t flags` arg.

<

### 8.10.2.3 WOLFSENTRY\_THREAD\_HEADER\_CHECKED

```
#define WOLFSENTRY_THREAD_HEADER_CHECKED(  
    flags )
```

For WOLFSENTRY\_THREADSafe applications, checks if thread context initialization succeeded, and returns on failure.

<

### 8.10.2.4 WOLFSENTRY\_THREAD\_HEADER\_DECLS

```
#define WOLFSENTRY_THREAD_HEADER_DECLS
```

**Value:**

```
struct wolfentry_thread_context_public thread_buffer =  
    WOLFSENTRY_THREAD_CONTEXT_PUBLIC_INITIALIZER;  
struct wolfentry_thread_context *thread =  
    (struct wolfentry_thread_context *)&thread_buffer;  
wolfentry_errcode_t _thread_context_ret;
```

### 8.10.2.5 WOLFSENTRY\_THREAD\_HEADER\_INIT

```
#define WOLFSENTRY_THREAD_HEADER_INIT(  
    flags )
```

For WOLFSENTRY\_THREADSafe applications, this allocates the required thread context on the stack.

<

### 8.10.2.6 WOLFSENTRY\_THREAD\_HEADER\_INIT\_CHECKED

```
#define WOLFSENTRY_THREAD_HEADER_INIT_CHECKED(  
    flags )
```

For WOLFSENTRY\_THREADSafe applications, this performs the required thread context initialization, with options from its `wolfentry_thread_flags_t` flags arg.

<

### 8.10.2.7 WOLFSENTRY\_THREAD\_TAILER

```
#define WOLFSENTRY_THREAD_TAILER(  
    flags )
```

For WOLFSENTRY\_THREADSafe applications, this allocates the required thread context on the stack, and initializes it with options from its `wolfentry_thread_flags_t` flags arg, returning on failure.

<

For WOLFSENTRY\_THREADSafe applications, this cleans up a thread context allocated with WOLFSENTRY\_THREAD\_HEADER\*, with options from its `wolfentry_thread_flags_t` flags arg, storing the result.

## 8.10.3 Enumeration Type Documentation

### 8.10.3.1 wolfentry\_lock\_flags\_t

```
enum wolfentry_lock_flags_t
```

flags to pass to `wolfentry_lock_*` () functions, to be OR'd together

## Enumerator

WOLFSENTRY_LOCK_FLAG_NONE	Default lock behavior.
WOLFSENTRY_LOCK_FLAG_PSHARED	Initialize lock to be shared between processes (currently not used, only allowed by <a href="#">wolfentry_lock_init()</a> , and only functional on POSIX targets)
WOLFSENTRY_LOCK_FLAG_SHARED_ERROR↔ _CHECKING	Enables supplementary error checking on shared lock usage (not currently implemented)
WOLFSENTRY_LOCK_FLAG_NONRECURSIVE↔ MUTEX	Don't allow recursive mutex locking in this call.
WOLFSENTRY_LOCK_FLAG_NONRECURSIVE↔ SHARED	Don't allow recursive shared locking in this call.
WOLFSENTRY_LOCK_FLAG_GET↔ RESERVATION_TOO	If a shared lock is gotten in this call, require that a mutex upgrade reservation also be gotten.
WOLFSENTRY_LOCK_FLAG_TRY↔ RESERVATION_TOO	If a shared lock is gotten in this call, try to get a mutex upgrade reservation too.
WOLFSENTRY_LOCK_FLAG_ABANDON↔ RESERVATION_TOO	In a call to <a href="#">wolfentry_lock_unlock()</a> , if a shared lock is released and a mutex upgrade reservation is held, drop it too.
WOLFSENTRY_LOCK_FLAG_AUTO_DOWNGRADE	In a call to <a href="#">wolfentry_lock_unlock()</a> , if a held mutex was previously gotten by an upgrade, and this release will restore the recursion depth at which the upgrade was gotten, downgrade to a shared lock.
WOLFSENTRY_LOCK_FLAG_RETAIN↔ SEMAPHORE	For use in an interrupt handler: get an async-signal-safe mutex on the lock. Implicitly has <code>try</code> dynamics (immediate return).

## 8.10.3.2 wolfentry\_thread\_flags\_t

```
enum wolfentry_thread_flags_t
```

wolfentry\_thread\_flags\_t flags are to be ORed together.

## Enumerator

WOLFSENTRY_THREAD_FLAG_NONE	Default and normal thread state.
WOLFSENTRY_THREAD_FLAG_DEADLINE	This thread currently has a deadline associated with it, and will not wait for a lock beyond that deadline.
WOLFSENTRY_THREAD_FLAG_READONLY	This thread can only get and hold shared locks.

## 8.10.4 Function Documentation

## 8.10.4.1 wolfentry\_lock\_alloc()

```
WOLFENTRY_API wolfentry_errcode_t wolfentry_lock_alloc (
    struct wolfentry_host_platform_interface * hpi,
    struct wolfentry_thread_context * thread,
```

```
struct wolfsentry_rwlock ** lock,  
    wolfsentry_lock_flags_t flags )
```

Allocates and initializes a semaphore lock structure for use with wolfSentry.

**Parameters**

<i>hpi</i>	the <a href="#">wolfsentry_host_platform_interface</a>
<i>thread</i>	pointer to the <a href="#">wolfsentry_thread_context</a>
<i>lock</i>	a pointer to a pointer to a lock structure to be allocated and initialized
<i>flags</i>	the initial <a href="#">wolfsentry_lock_flags_t</a>

**Returns**

[WOLFSENTRY\\_IS\\_SUCCESS\(ret\)](#) is true on success.

**See also**

[wolfsentry\\_lock\\_init](#)

[wolfsentry\\_lock\\_free](#)

[WOLFSENTRY\\_ERROR\\_DECODE\\_ERROR\\_CODE\(\)](#)

**8.10.4.2 wolfsentry\_lock\_destroy()**

```
WOLFSENTRY_API wolfsentry\_errcode\_t wolfsentry_lock_destroy (
    struct wolfsentry_rwlock * lock,
    struct wolfsentry_thread_context * thread,
    wolfsentry\_lock\_flags\_t flags )
```

Destroy a lock that was created with [wolfsentry\\_lock\\_init\(\)](#)

**Parameters**

<i>lock</i>	a pointer to the lock
<i>thread</i>	pointer to the <a href="#">wolfsentry_thread_context</a>
<i>flags</i>	optional <a href="#">wolfsentry_lock_flags_t</a>

**Returns**

[WOLFSENTRY\\_IS\\_SUCCESS\(ret\)](#) is true on success.

**See also**

[wolfsentry\\_lock\\_init](#)

[WOLFSENTRY\\_ERROR\\_DECODE\\_ERROR\\_CODE](#)

**8.10.4.3 wolfsentry\_lock\_free()**

```
WOLFSENTRY_API wolfsentry\_errcode\_t wolfsentry_lock_free (
    struct wolfsentry_rwlock ** lock,
    struct wolfsentry_thread_context * thread,
    wolfsentry\_lock\_flags\_t flags )
```

Destroy and free a lock that was created with [wolfsentry\\_lock\\_alloc\(\)](#). The lock's pointer will also be set to NULL.

## Parameters

<i>lock</i>	a pointer to a pointer to the lock
<i>thread</i>	pointer to the <code>wolfentry_thread_context</code>
<i>flags</i>	optional <code>wolfentry_lock_flags_t</code>

## Returns

`WOLFENTRY_IS_SUCCESS(ret)` is true on success.

## See also

[wolfentry\\_lock\\_alloc](#)

[WOLFENTRY\\_ERROR\\_DECODE\\_ERROR\\_CODE](#)

**8.10.4.4 wolfentry\_lock\_get\_flags()**

```
WOLFENTRY_API wolfentry_errcode_t wolfentry_lock_get_flags (  
    struct wolfentry_rwlock * lock,  
    struct wolfentry_thread_context * thread,  
    wolfentry_lock_flags_t * flags )
```

Extract the current flags from the lock.

## Parameters

<i>lock</i>	a pointer to the lock
<i>thread</i>	pointer to the <code>wolfentry_thread_context</code>
<i>flags</i>	optional <code>wolfentry_lock_flags_t</code>

## Returns

`WOLFENTRY_IS_SUCCESS(ret)` is true on success.

## See also

[WOLFENTRY\\_ERROR\\_DECODE\\_ERROR\\_CODE](#)

**8.10.4.5 wolfentry\_lock\_have\_either()**

```
WOLFENTRY_API wolfentry_errcode_t wolfentry_lock_have_either (  
    struct wolfentry_rwlock * lock,  
    struct wolfentry_thread_context * thread,  
    wolfentry_lock_flags_t flags )
```

Check if the lock is held in either shared or exclusive state.

## Parameters

<i>lock</i>	a pointer to the lock
<i>thread</i>	pointer to the <code>wolfentry_thread_context</code>
<i>flags</i>	optional <code>wolfentry_lock_flags_t</code>

## Returns

When decoded using `WOLFENTRY_ERROR_DECODE_ERROR_CODE()`, `WOLFENTRY_SUCCESS_ID_HAVE_MUTEX` if it is a held mutex lock, `WOLFENTRY_SUCCESS_ID_HAVE_READ_LOCK` if it is a held shared lock, `WOLFENTRY_ERROR_ID_LACKING_READ_LOCK` if the lock is valid but not held by the designated thread, or `WOLFENTRY_ERROR_ID_INVALID_ARG` if the lock is not properly initialized.

## See also

[WOLFENTRY\\_ERROR\\_DECODE\\_ERROR\\_CODE](#)

8.10.4.6 `wolfentry_lock_have_mutex()`

```
WOLFENTRY_API wolfentry_errcode_t wolfentry_lock_have_mutex (
    struct wolfentry_rwlock * lock,
    struct wolfentry_thread_context * thread,
    wolfentry_lock_flags_t flags )
```

Check if the lock is held in exclusive state.

## Parameters

<i>lock</i>	a pointer to the lock
<i>thread</i>	pointer to the <code>wolfentry_thread_context</code>
<i>flags</i>	optional <code>wolfentry_lock_flags_t</code>

## Returns

When decoded using `WOLFENTRY_ERROR_DECODE_ERROR_CODE()`, `WOLFENTRY_SUCCESS_ID_HAVE_MUTEX` if it is a held mutex lock, `WOLFENTRY_ERROR_ID_LACKING_MUTEX` if the lock is not in mutex state, `WOLFENTRY_ERROR_ID_NOT_PERMITTED` if the mutex is held by another thread, or `WOLFENTRY_ERROR_ID_INVALID_ARG` if the lock is not properly initialized.

## See also

[WOLFENTRY\\_ERROR\\_DECODE\\_ERROR\\_CODE](#)

8.10.4.7 `wolfentry_lock_have_shared()`

```
WOLFENTRY_API wolfentry_errcode_t wolfentry_lock_have_shared (
    struct wolfentry_rwlock * lock,
    struct wolfentry_thread_context * thread,
    wolfentry_lock_flags_t flags )
```

Check if the lock is held in shared state.



## Parameters

<i>lock</i>	a pointer to the lock
<i>thread</i>	pointer to the <code>wolfentry_thread_context</code>
<i>flags</i>	optional <code>wolfentry_lock_flags_t</code>

## Returns

When decoded using [WOLFENTRY\\_ERROR\\_DECODE\\_ERROR\\_CODE\(\)](#), `WOLFENTRY_SUCCESS_ID↵`  
`ID_HAVE_READ_LOCK` if it is a held shared lock, `WOLFENTRY_ERROR_ID_LACKING_READ_LOCK` if  
the lock is valid but not held by the designated `thread`, or `WOLFENTRY_ERROR_ID_INVALID_ARG` if  
the lock is not properly initialized.

## See also

[WOLFENTRY\\_ERROR\\_DECODE\\_ERROR\\_CODE](#)

8.10.4.8 `wolfentry_lock_have_shared2mutex_reservation()`

```
WOLFENTRY_API wolfentry_errcode_t wolfentry_lock_have_shared2mutex_reservation (
    struct wolfentry_rwlock * lock,
    struct wolfentry_thread_context * thread,
    wolfentry_lock_flags_t flags )
```

Check if an upgrade reservation is held on the lock.

## Parameters

<i>lock</i>	a pointer to the lock
<i>thread</i>	pointer to the <code>wolfentry_thread_context</code>
<i>flags</i>	optional <code>wolfentry_lock_flags_t</code>

## Returns

When decoded using [WOLFENTRY\\_ERROR\\_DECODE\\_ERROR\\_CODE\(\)](#), `WOLFENTRY_ERROR_ID↵`  
`_OK` if it is shared lock. Or `WOLFENTRY_ERROR_ID_NOT_OK` if it is not a shared lock.

## See also

[WOLFENTRY\\_ERROR\\_DECODE\\_ERROR\\_CODE](#)

8.10.4.9 `wolfentry_lock_init()`

```
WOLFENTRY_API wolfentry_errcode_t wolfentry_lock_init (
    struct wolfentry_host_platform_interface * hpi,
    struct wolfentry_thread_context * thread,
    struct wolfentry_rwlock * lock,
    wolfentry_lock_flags_t flags )
```

This initializes a semaphore lock structure created by the user.

**Parameters**

<i>hpi</i>	the <a href="#">wolfentry_host_platform_interface</a>
<i>thread</i>	pointer to the <a href="#">wolfentry_thread_context</a>
<i>lock</i>	a pointer to a lock structure to be initialized
<i>flags</i>	the initial <a href="#">wolfentry_lock_flags_t</a>

**Returns**

[WOLFENTRY\\_IS\\_SUCCESS\(ret\)](#) is true on success.

**See also**

[wolfentry\\_lock\\_alloc](#)

[wolfentry\\_lock\\_destroy](#)

[WOLFENTRY\\_ERROR\\_DECODE\\_ERROR\\_CODE](#)

**8.10.4.10 wolfentry\_lock\_mutex()**

```
WOLFENTRY_API wolfentry\_errcode\_t wolfentry_lock_mutex (
    struct wolfentry_rwlock * lock,
    struct wolfentry_thread_context * thread,
    wolfentry\_lock\_flags\_t flags )
```

Requests an exclusive lock.

**Parameters**

<i>lock</i>	a pointer to the lock
<i>thread</i>	pointer to the <a href="#">wolfentry_thread_context</a>
<i>flags</i>	optional <a href="#">wolfentry_lock_flags_t</a>

**Returns**

[WOLFENTRY\\_IS\\_SUCCESS\(ret\)](#) is true on success.

**See also**

[WOLFENTRY\\_ERROR\\_DECODE\\_ERROR\\_CODE](#)

**8.10.4.11 wolfentry\_lock\_mutex2shared()**

```
WOLFENTRY_API wolfentry\_errcode\_t wolfentry_lock_mutex2shared (
    struct wolfentry_rwlock * lock,
    struct wolfentry_thread_context * thread,
    wolfentry\_lock\_flags\_t flags )
```

Downgrade an exclusive lock to a shared lock.

## Parameters

<i>lock</i>	a pointer to the lock
<i>thread</i>	pointer to the <code>wolfentry_thread_context</code>
<i>flags</i>	optional <code>wolfentry_lock_flags_t</code>

## Returns

`WOLFENTRY_IS_SUCCESS(ret)` is true on success.

## See also

[WOLFENTRY\\_ERROR\\_DECODE\\_ERROR\\_CODE](#)

**8.10.4.12 `wolfentry_lock_mutex_abstimed()`**

```
WOLFENTRY_API wolfentry_errcode_t wolfentry_lock_mutex_abstimed (
    struct wolfentry_rwlock * lock,
    struct wolfentry_thread_context * thread,
    const struct timespec * abs_timeout,
    wolfentry_lock_flags_t flags )
```

Requests an exclusive lock with an absolute timeout.

## Parameters

<i>lock</i>	a pointer to the lock
<i>thread</i>	pointer to the <code>wolfentry_thread_context</code>
<i>abs_timeout</i>	the absolute timeout for the lock
<i>flags</i>	optional <code>wolfentry_lock_flags_t</code>

## Returns

`WOLFENTRY_IS_SUCCESS(ret)` is true on success.

## See also

[WOLFENTRY\\_ERROR\\_DECODE\\_ERROR\\_CODE](#)

**8.10.4.13 `wolfentry_lock_mutex_timed()`**

```
WOLFENTRY_API wolfentry_errcode_t wolfentry_lock_mutex_timed (
    struct wolfentry_rwlock * lock,
    struct wolfentry_thread_context * thread,
    wolfentry_time_t max_wait,
    wolfentry_lock_flags_t flags )
```

Requests an exclusive lock with a relative timeout.

## Parameters

<i>lock</i>	a pointer to the lock
<i>thread</i>	pointer to the <code>wolfentry_thread_context</code>
<i>max_wait</i>	how long to wait for the timeout
<i>flags</i>	optional <code>wolfentry_lock_flags_t</code>

## Returns

`WOLFENTRY_IS_SUCCESS(ret)` is true on success.

## See also

`WOLFENTRY_ERROR_DECODE_ERROR_CODE`

**8.10.4.14 wolfentry\_lock\_shared()**

```
WOLFENTRY_API wolfentry_errcode_t wolfentry_lock_shared (
    struct wolfentry_rwlock * lock,
    struct wolfentry_thread_context * thread,
    wolfentry_lock_flags_t flags )
```

Requests a shared lock.

## Parameters

<i>lock</i>	a pointer to the lock
<i>thread</i>	pointer to the <code>wolfentry_thread_context</code>
<i>flags</i>	optional <code>wolfentry_lock_flags_t</code>

## Returns

`WOLFENTRY_IS_SUCCESS(ret)` is true on success.

## See also

`WOLFENTRY_ERROR_DECODE_ERROR_CODE`

**8.10.4.15 wolfentry\_lock\_shared2mutex()**

```
WOLFENTRY_API wolfentry_errcode_t wolfentry_lock_shared2mutex (
    struct wolfentry_rwlock * lock,
    struct wolfentry_thread_context * thread,
    wolfentry_lock_flags_t flags )
```

Upgrade a shared lock to an exclusive lock.

## Parameters

<i>lock</i>	a pointer to the lock
<i>thread</i>	pointer to the <code>wolfentry_thread_context</code>
<i>flags</i>	optional <code>wolfentry_lock_flags_t</code>

## Returns

`WOLFENTRY_IS_SUCCESS(ret)` is true on success.

## See also

[WOLFENTRY\\_ERROR\\_DECODE\\_ERROR\\_CODE](#)

**8.10.4.16 wolfentry\_lock\_shared2mutex\_abandon()**

```
WOLFENTRY_API wolfentry_errcode_t wolfentry_lock_shared2mutex_abandon (  
    struct wolfentry_rwlock * lock,  
    struct wolfentry_thread_context * thread,  
    wolfentry_lock_flags_t flags )
```

Abandon a reservation of a lock upgrade from shared to exclusive.

## Parameters

<i>lock</i>	a pointer to the lock
<i>thread</i>	pointer to the <code>wolfentry_thread_context</code>
<i>flags</i>	optional <code>wolfentry_lock_flags_t</code>

## Returns

`WOLFENTRY_IS_SUCCESS(ret)` is true on success.

## See also

[WOLFENTRY\\_ERROR\\_DECODE\\_ERROR\\_CODE](#)

**8.10.4.17 wolfentry\_lock\_shared2mutex\_abstimed()**

```
WOLFENTRY_API wolfentry_errcode_t wolfentry_lock_shared2mutex_abstimed (  
    struct wolfentry_rwlock * lock,  
    struct wolfentry_thread_context * thread,  
    const struct timespec * abs_timeout,  
    wolfentry_lock_flags_t flags )
```

Attempt to upgrade a shared lock to an exclusive lock with an absolute timeout.

## Parameters

<i>lock</i>	a pointer to the lock
<i>thread</i>	pointer to the <code>wolfentry_thread_context</code>
<i>abs_timeout</i>	the absolute timeout for the lock
<i>flags</i>	optional <code>wolfentry_lock_flags_t</code>

## Returns

`WOLFENTRY_IS_SUCCESS(ret)` is true on success.

## See also

`WOLFENTRY_ERROR_DECODE_ERROR_CODE`

**8.10.4.18 wolfentry\_lock\_shared2mutex\_redeem()**

```
WOLFENTRY_API wolfentry_errcode_t wolfentry_lock_shared2mutex_redeem (
    struct wolfentry_rwlock * lock,
    struct wolfentry_thread_context * thread,
    wolfentry_lock_flags_t flags )
```

Redeem a reservation of a lock upgrade from shared to exclusive.

## Parameters

<i>lock</i>	a pointer to the lock
<i>thread</i>	pointer to the <code>wolfentry_thread_context</code>
<i>flags</i>	optional <code>wolfentry_lock_flags_t</code>

## Returns

`WOLFENTRY_IS_SUCCESS(ret)` is true on success.

## See also

`WOLFENTRY_ERROR_DECODE_ERROR_CODE`

**8.10.4.19 wolfentry\_lock\_shared2mutex\_redeem\_abstimed()**

```
WOLFENTRY_API wolfentry_errcode_t wolfentry_lock_shared2mutex_redeem_abstimed (
    struct wolfentry_rwlock * lock,
    struct wolfentry_thread_context * thread,
    const struct timespec * abs_timeout,
    wolfentry_lock_flags_t flags )
```

Redeem a reservation of a lock upgrade from shared to exclusive with an absolute timeout.

## Parameters

<i>lock</i>	a pointer to the lock
<i>thread</i>	pointer to the <code>wolfentry_thread_context</code>
<i>abs_timeout</i>	the absolute timeout for the lock
<i>flags</i>	optional <code>wolfentry_lock_flags_t</code>

## Returns

[WOLFENTRY\\_IS\\_SUCCESS\(ret\)](#) is true on success.

## See also

[WOLFENTRY\\_ERROR\\_DECODE\\_ERROR\\_CODE](#)

**8.10.4.20 wolfentry\_lock\_shared2mutex\_redeem\_timed()**

```
WOLFENTRY_API wolfentry_errcode_t wolfentry_lock_shared2mutex_redeem_timed (
    struct wolfentry_rwlock * lock,
    struct wolfentry_thread_context * thread,
    wolfentry_time_t max_wait,
    wolfentry_lock_flags_t flags )
```

Redeem a reservation of a lock upgrade from shared to exclusive with a relative timeout.

## Parameters

<i>lock</i>	a pointer to the lock
<i>thread</i>	pointer to the <code>wolfentry_thread_context</code>
<i>max_wait</i>	how long to wait for the timeout
<i>flags</i>	optional <code>wolfentry_lock_flags_t</code>

## Returns

[WOLFENTRY\\_IS\\_SUCCESS\(ret\)](#) is true on success.

## See also

[WOLFENTRY\\_ERROR\\_DECODE\\_ERROR\\_CODE](#)

**8.10.4.21 wolfentry\_lock\_shared2mutex\_reserve()**

```
WOLFENTRY_API wolfentry_errcode_t wolfentry_lock_shared2mutex_reserve (
    struct wolfentry_rwlock * lock,
    struct wolfentry_thread_context * thread,
    wolfentry_lock_flags_t flags )
```

Attempt to reserve a upgrade of a shared lock to an exclusive lock.

## Parameters

<i>lock</i>	a pointer to the lock
<i>thread</i>	pointer to the <code>wolfentry_thread_context</code>
<i>flags</i>	optional <code>wolfentry_lock_flags_t</code>

## Returns

`WOLFENTRY_IS_SUCCESS(ret)` is true on success.

## See also

[wolfentry\\_lock\\_shared2mutex\\_redeem](#)  
[wolfentry\\_lock\\_shared2mutex\\_redeem\\_abstimed](#)  
[wolfentry\\_lock\\_shared2mutex\\_redeem\\_timed](#)  
[wolfentry\\_lock\\_shared2mutex\\_abandon](#)  
[WOLFENTRY\\_ERROR\\_DECODE\\_ERROR\\_CODE](#)

#### 8.10.4.22 `wolfentry_lock_shared2mutex_timed()`

```
WOLFENTRY_API wolfentry_errcode_t wolfentry_lock_shared2mutex_timed (
    struct wolfentry_rwlock * lock,
    struct wolfentry_thread_context * thread,
    wolfentry_time_t max_wait,
    wolfentry_lock_flags_t flags )
```

Attempt to upgrade a shared lock to an exclusive lock with a relative timeout.

## Parameters

<i>lock</i>	a pointer to the lock
<i>thread</i>	pointer to the <code>wolfentry_thread_context</code>
<i>max_wait</i>	how long to wait for the timeout
<i>flags</i>	optional <code>wolfentry_lock_flags_t</code>

## Returns

`WOLFENTRY_IS_SUCCESS(ret)` is true on success.

## See also

[WOLFENTRY\\_ERROR\\_DECODE\\_ERROR\\_CODE](#)

#### 8.10.4.23 `wolfentry_lock_shared_abstimed()`

```
WOLFENTRY_API wolfentry_errcode_t wolfentry_lock_shared_abstimed (
    struct wolfentry_rwlock * lock,
```



```
struct wolfsentry_thread_context * thread,  
const struct timespec * abs_timeout,  
wolfsentry_lock_flags_t flags )
```

Requests a shared lock with an absolute timeout.

#### Parameters

<i>lock</i>	a pointer to the lock
<i>thread</i>	pointer to the wolfsentry_thread_context
<i>abs_timeout</i>	the absolute timeout for the lock
<i>flags</i>	optional wolfsentry_lock_flags_t

#### Returns

[WOLFSENTRY\\_IS\\_SUCCESS\(ret\)](#) is true on success.

#### See also

[WOLFSENTRY\\_ERROR\\_DECODE\\_ERROR\\_CODE](#)

#### 8.10.4.24 wolfsentry\_lock\_shared\_timed()

```
WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_lock_shared_timed (  
    struct wolfsentry_rwlock * lock,  
    struct wolfsentry_thread_context * thread,  
    wolfsentry_time_t max_wait,  
    wolfsentry_lock_flags_t flags )
```

Requests a shared lock with a relative timeout.

#### Parameters

<i>lock</i>	a pointer to the lock
<i>thread</i>	pointer to the wolfsentry_thread_context
<i>max_wait</i>	how long to wait for the timeout
<i>flags</i>	optional wolfsentry_lock_flags_t

#### Returns

[WOLFSENTRY\\_IS\\_SUCCESS\(ret\)](#) is true on success.

#### See also

[WOLFSENTRY\\_ERROR\\_DECODE\\_ERROR\\_CODE](#)

### 8.10.4.25 wolfentry\_lock\_unlock()

```
WOLFSENTRY_API wolfentry_errcode_t wolfentry_lock_unlock (
    struct wolfentry_rwlock * lock,
    struct wolfentry_thread_context * thread,
    wolfentry_lock_flags_t flags )
```

Unlock a lock.

#### Parameters

<i>lock</i>	a pointer to the lock
<i>thread</i>	pointer to the <code>wolfentry_thread_context</code>
<i>flags</i>	optional <code>wolfentry_lock_flags_t</code>

#### Returns

`WOLFSENTRY_IS_SUCCESS(ret)` is true on success.

#### See also

[WOLFSENTRY\\_ERROR\\_DECODE\\_ERROR\\_CODE](#)

## 8.11 Allocator (Heap) Functions and Callbacks

### Data Structures

- struct [wolfentry\\_allocator](#)  
Struct for passing shims that abstract the native implementation of the heap allocator.

### Typedefs

- typedef void \*(\* **wolfentry\_malloc\_cb\_t**) (void \*context, struct wolfentry\_thread\_context \*thread, size\_t size)  
*Pointer to malloc-like function. Takes extra initial args context and, if !defined(WOLFSENTRY\_SINGLETHREADED), thread arg.*
- typedef void \*(\* **wolfentry\_free\_cb\_t**) (void \*context, struct wolfentry\_thread\_context \*thread, void \*ptr)  
*Pointer to free-like function. Takes extra initial args context and, if !defined(WOLFSENTRY\_SINGLETHREADED), thread arg.*
- typedef void \*(\* **wolfentry\_realloc\_cb\_t**) (void \*context, struct wolfentry\_thread\_context \*thread, void \*ptr, size\_t size)  
*Pointer to realloc-like function. Takes extra initial args context and, if !defined(WOLFSENTRY\_SINGLETHREADED), thread arg.*
- typedef void \*(\* **wolfentry\_memalign\_cb\_t**) (void \*context, struct wolfentry\_thread\_context \*thread, size\_t alignment, size\_t size)  
*Pointer to memalign-like function. Takes extra initial args context and, if !defined(WOLFSENTRY\_SINGLETHREADED), thread arg.*
- typedef void \*(\* **wolfentry\_free\_aligned\_cb\_t**) (void \*context, struct wolfentry\_thread\_context \*thread, void \*ptr)  
*Pointer to special-purpose free-like function, needed only if the memalign pointer in a struct [wolfentry\\_allocator](#) is non-null. Can be same as routine supplied as wolfentry\_free\_cb\_t, or can be a separate routine, e.g. with special handling for pad bytes. Takes extra initial args context and, if !defined(WOLFSENTRY\_SINGLETHREADED), thread arg.*

## Functions

- WOLFSENTRY\_API void \* **wolfentry\_malloc** (WOLFSENTRY\_CONTEXT\_ARGS\_IN, size\_t size)  
*Allocate size bytes using the malloc configured in the wolfSentry context.*
- WOLFSENTRY\_API\_VOID **wolfentry\_free** (WOLFSENTRY\_CONTEXT\_ARGS\_IN, void \*ptr)  
*Free ptr using the free configured in the wolfSentry context.*
- WOLFSENTRY\_API void \* **wolfentry\_realloc** (WOLFSENTRY\_CONTEXT\_ARGS\_IN, void \*ptr, size\_t size)  
*Reallocate ptr to size bytes using the realloc configured in the wolfSentry context.*
- WOLFSENTRY\_API void \* **wolfentry\_memalign** (WOLFSENTRY\_CONTEXT\_ARGS\_IN, size\_t alignment, size\_t size)  
*Allocate size bytes, aligned to alignment, using the memalign configured in the wolfSentry context.*
- WOLFSENTRY\_API\_VOID **wolfentry\_free\_aligned** (WOLFSENTRY\_CONTEXT\_ARGS\_IN, void \*ptr)  
*Free ptr, previously allocated with wolfentry\_memalign(), using the free\_aligned configured in the wolfSentry context.*
- WOLFSENTRY\_API int **\_wolfentry\_get\_n\_mallocs** (void)  
*In library builds with WOLFSENTRY\_MALLOC\_BUILTINS and WOLFSENTRY\_MALLOC\_DEBUG defined, this returns the net number of allocations performed as of time of call. I.e., it returns zero iff all allocations have been freed.*
- WOLFSENTRY\_API struct **wolfentry\_allocator** \* **wolfentry\_get\_allocator** (struct wolfentry\_context \*wolfentry)  
*Return a pointer to the wolfentry\_allocator associated with the supplied wolfentry\_context, mainly for passing to json\_init(), json\_parse(), json\_value\_\*(), and json\_dom\_\*().*

### 8.11.1 Detailed Description

## 8.12 Time Functions and Callbacks

### Data Structures

- struct **wolfentry\_timecbs**  
*Struct for passing shims that abstract the native implementation of time functions.*

### Typedefs

- typedef **wolfentry\_errcode\_t**(\* **wolfentry\_get\_time\_cb\_t**) (void \*context, **wolfentry\_time\_t** \*ts)  
*Pointer to function that returns time denominated in wolfentry\_time\_t. Takes an initial context arg, which can be ignored.*
- typedef **wolfentry\_time\_t**(\* **wolfentry\_diff\_time\_cb\_t**) (**wolfentry\_time\_t** earlier, **wolfentry\_time\_t** later)  
*Pointer to function that subtracts earlier from later, returning the result.*
- typedef **wolfentry\_time\_t**(\* **wolfentry\_add\_time\_cb\_t**) (**wolfentry\_time\_t** start\_time, **wolfentry\_time\_t** time\_interval)  
*Pointer to function that adds two wolfentry\_time\_t times, returning the result.*
- typedef **wolfentry\_errcode\_t**(\* **wolfentry\_to\_epoch\_time\_cb\_t**) (**wolfentry\_time\_t** when, time\_t \*epoch\_secs, long \*epoch\_nsecs)  
*Pointer to function that converts a wolfentry\_time\_t to seconds and nanoseconds since midnight UTC, 1970-Jan-1.*
- typedef **wolfentry\_errcode\_t**(\* **wolfentry\_from\_epoch\_time\_cb\_t**) (time\_t epoch\_secs, long epoch\_nsecs, **wolfentry\_time\_t** \*when)  
*Pointer to function that converts seconds and nanoseconds since midnight UTC, 1970-Jan-1, to a wolfentry\_time\_t.*

- typedef [wolfentry\\_errcode\\_t](#)(\* [wolfentry\\_interval\\_to\\_seconds\\_cb\\_t](#)) ([wolfentry\\_time\\_t](#) howlong, time\_t \*howlong\_secs, long \*howlong\_nsecs)  
*Pointer to function that converts a [wolfentry\\_time\\_t](#) expressing an interval to the corresponding seconds and nanoseconds.*
- typedef [wolfentry\\_errcode\\_t](#)(\* [wolfentry\\_interval\\_from\\_seconds\\_cb\\_t](#)) (time\_t howlong\_secs, long howlong\_nsecs, [wolfentry\\_time\\_t](#) \*howlong)  
*Pointer to function that converts seconds and nanoseconds expressing an interval to the corresponding [wolfentry\\_time\\_t](#).*

## Functions

- WOLFENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_time\\_now\\_plus\\_delta](#) (struct [wolfentry\\_context](#) \*wolfentry, [wolfentry\\_time\\_t](#) td, [wolfentry\\_time\\_t](#) \*res)  
*Generate a [wolfentry\\_time\\_t](#) at a given offset from current time.*
- WOLFENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_time\\_to\\_timespec](#) (struct [wolfentry\\_context](#) \*wolfentry, [wolfentry\\_time\\_t](#) t, struct [timespec](#) \*ts)  
*Convert a [wolfentry\\_time\\_t](#) to a struct [timespec](#).*
- WOLFENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_time\\_now\\_plus\\_delta\\_timespec](#) (struct [wolfentry\\_context](#) \*wolfentry, [wolfentry\\_time\\_t](#) td, struct [timespec](#) \*ts)  
*Generate a struct [timespec](#) at a given offset, supplied as [wolfentry\\_time\\_t](#), from current time.*
- WOLFENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_get\\_time](#) (struct [wolfentry\\_context](#) \*wolfentry, [wolfentry\\_time\\_t](#) \*time\_p)  
*Get current time as [wolfentry\\_time\\_t](#).*
- WOLFENTRY\_API [wolfentry\\_time\\_t](#) [wolfentry\\_diff\\_time](#) (struct [wolfentry\\_context](#) \*wolfentry, [wolfentry\\_time\\_t](#) later, [wolfentry\\_time\\_t](#) earlier)  
*Compute the interval between *later* and *earlier*, using [wolfentry\\_time\\_t](#).*
- WOLFENTRY\_API [wolfentry\\_time\\_t](#) [wolfentry\\_add\\_time](#) (struct [wolfentry\\_context](#) \*wolfentry, [wolfentry\\_time\\_t](#) start\_time, [wolfentry\\_time\\_t](#) time\_interval)  
*Compute the time *time\_interval* after *start\_time*, using [wolfentry\\_time\\_t](#).*
- WOLFENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_to\\_epoch\\_time](#) (struct [wolfentry\\_context](#) \*wolfentry, [wolfentry\\_time\\_t](#) when, time\_t \*epoch\_secs, long \*epoch\_nsecs)  
*Convert a [wolfentry\\_time\\_t](#) to seconds and nanoseconds since 1970-Jan-1 0:00 UTC.*
- WOLFENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_from\\_epoch\\_time](#) (struct [wolfentry\\_context](#) \*wolfentry, time\_t epoch\_secs, long epoch\_nsecs, [wolfentry\\_time\\_t](#) \*when)  
*Convert seconds and nanoseconds since 1970-Jan-1 0:00 UTC to a [wolfentry\\_time\\_t](#).*
- WOLFENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_interval\\_to\\_seconds](#) (struct [wolfentry\\_context](#) \*wolfentry, [wolfentry\\_time\\_t](#) howlong, time\_t \*howlong\_secs, long \*howlong\_nsecs)  
*Convert an interval in [wolfentry\\_time\\_t](#) to seconds and nanoseconds.*
- WOLFENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_interval\\_from\\_seconds](#) (struct [wolfentry\\_context](#) \*wolfentry, time\_t howlong\_secs, long howlong\_nsecs, [wolfentry\\_time\\_t](#) \*howlong)  
*Convert an interval in seconds and nanoseconds to [wolfentry\\_time\\_t](#).*
- WOLFENTRY\_API struct [wolfentry\\_timecbs](#) \* [wolfentry\\_get\\_timecbs](#) (struct [wolfentry\\_context](#) \*wolfentry)  
*Return the active time handlers from the supplied context.*

## 8.12.1 Detailed Description

## 8.13 Semaphore Function Callbacks

### Data Structures

- struct [wolfentry\\_semcbs](#)  
*Struct for passing shims that abstract the native implementation of counting semaphores.*

## Typedefs

- typedef int(\* [sem\\_init\\_cb\\_t](#)) (sem\_t \*sem, int pshared, unsigned int value)
- typedef int(\* [sem\\_post\\_cb\\_t](#)) (sem\_t \*sem)
- typedef int(\* [sem\\_wait\\_cb\\_t](#)) (sem\_t \*sem)
- typedef int(\* [sem\\_timedwait\\_cb\\_t](#)) (sem\_t \*sem, const struct timespec \*abs\_timeout)
- typedef int(\* [sem\\_trywait\\_cb\\_t](#)) (sem\_t \*sem)
- typedef int(\* [sem\\_destroy\\_cb\\_t](#)) (sem\_t \*sem)

### 8.13.1 Detailed Description

### 8.13.2 Typedef Documentation

#### 8.13.2.1 [sem\\_destroy\\_cb\\_t](#)

```
typedef int(* sem_destroy_cb_t) (sem_t *sem)
```

Pointer to function with arguments and semantics of POSIX [sem\\_destroy\(\)](#)

#### 8.13.2.2 [sem\\_init\\_cb\\_t](#)

```
typedef int(* sem_init_cb_t) (sem_t *sem, int pshared, unsigned int value)
```

Pointer to function with arguments and semantics of POSIX [sem\\_init\(\)](#). Currently, `pshared` and `value` are always zero as called by `wolfSentry`, so implementations can ignore them.

#### 8.13.2.3 [sem\\_post\\_cb\\_t](#)

```
typedef int(* sem_post_cb_t) (sem_t *sem)
```

Pointer to function with arguments and semantics of POSIX [sem\\_post\(\)](#)

#### 8.13.2.4 [sem\\_timedwait\\_cb\\_t](#)

```
typedef int(* sem_timedwait_cb_t) (sem_t *sem, const struct timespec *abs_timeout)
```

Pointer to function with arguments and semantics of POSIX [sem\\_timedwait\(\)](#)

#### 8.13.2.5 [sem\\_trywait\\_cb\\_t](#)

```
typedef int(* sem_trywait_cb_t) (sem_t *sem)
```

Pointer to function with arguments and semantics of POSIX [sem\\_trywait\(\)](#)

### 8.13.2.6 sem\_wait\_cb\_t

```
typedef int (* sem_wait_cb_t) (sem_t *sem)
```

Pointer to function with arguments and semantics of POSIX `sem_wait()`

## 8.14 lwIP Callback Activation Functions

### Functions

- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) **wolfentry\_install\_lwip\_filter\_ethernet\_callback** ([WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#), [packet\\_filter\\_event\\_mask\\_t](#) ethernet\_mask)  
*Install wolfSentry callbacks into lwIP for ethernet (layer 2) filtering.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) **wolfentry\_install\_lwip\_filter\_ip\_callbacks** ([WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#), [packet\\_filter\\_event\\_mask\\_t](#) ip\_mask)  
*Install wolfSentry callbacks into lwIP for IPv4/IPv6 (layer 3) filtering.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) **wolfentry\_install\_lwip\_filter\_icmp\_callbacks** ([WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#), [packet\\_filter\\_event\\_mask\\_t](#) icmp\_mask)  
*Install wolfSentry callbacks into lwIP for ICMP filtering.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) **wolfentry\_install\_lwip\_filter\_tcp\_callback** ([WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#), [packet\\_filter\\_event\\_mask\\_t](#) tcp\_mask)  
*Install wolfSentry callbacks into lwIP for TCP (layer 4) filtering.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) **wolfentry\_install\_lwip\_filter\_udp\_callback** ([WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#), [packet\\_filter\\_event\\_mask\\_t](#) udp\_mask)  
*Install wolfSentry callbacks into lwIP for UDP (layer 4) filtering.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) **wolfentry\_install\_lwip\_filter\_callbacks** ([WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#), [packet\\_filter\\_event\\_mask\\_t](#) ethernet\_mask, [packet\\_filter\\_event\\_mask\\_t](#) ip\_mask, [packet\\_filter\\_event\\_mask\\_t](#) icmp\_mask, [packet\\_filter\\_event\\_mask\\_t](#) tcp\_mask, [packet\\_filter\\_event\\_mask\\_t](#) udp\_mask)  
*Install wolfSentry callbacks for all layers/protocols enabled by the supplied masks.*
- [WOLFSENTRY\\_API\\_VOID](#) **wolfentry\_cleanup\_lwip\_filter\_callbacks** ([WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#), void \*arg)  
*Disables any wolfSentry callbacks previously installed in lwIP.*

### 8.14.1 Detailed Description

## Chapter 9

# Data Structure Documentation

### 9.1 JSON\_CALLBACKS Struct Reference

#### Data Fields

- `int(* process )(JSON_TYPE, const unsigned char *, size_t, void *)`

### 9.2 JSON\_CONFIG Struct Reference

#### Data Fields

- `size_t max_total_len`
- `size_t max_total_values`
- `size_t max_number_len`
- `size_t max_string_len`
- `size_t max_key_len`
- `unsigned max_nesting_level`
- `unsigned flags`

### 9.3 JSON\_DOM\_PARSER Struct Reference

#### Data Fields

- [JSON\\_PARSER](#) `parser`
- [JSON\\_VALUE](#) `** path`
- `size_t path_size`
- `size_t path_alloc`
- [JSON\\_VALUE](#) `root`
- [JSON\\_VALUE](#) `key`
- `unsigned flags`
- `unsigned dict_flags`

## 9.4 JSON\_INPUT\_POS Struct Reference

### Data Fields

- `size_t` **offset**
- unsigned `line_number`
- unsigned `column_number`

## 9.5 JSON\_PARSER Struct Reference

### Public Types

- enum `centijson_automaton` {  
`AUTOMATON_MAIN` = 0 ,  
`AUTOMATON_NULL` = 1 ,  
`AUTOMATON_FALSE` = 2 ,  
`AUTOMATON_TRUE` = 3 ,  
`AUTOMATON_NUMBER` = 4 ,  
`AUTOMATON_STRING` = 6 ,  
`AUTOMATON_KEY` = 7 }

### Data Fields

- [JSON\\_CALLBACKS](#) `callbacks`
- [JSON\\_CONFIG](#) `config`
- `void *` `user_data`
- [JSON\\_INPUT\\_POS](#) `pos`
- [JSON\\_INPUT\\_POS](#) `value_pos`
- [JSON\\_INPUT\\_POS](#) `err_pos`
- `int` `errcode`
- `size_t` `value_counter`
- unsigned char \* `nesting_stack`
- `size_t` `nesting_level`
- `size_t` `nesting_stack_size`
- enum `JSON_PARSER::centijson_automaton` `automaton`
- unsigned `state`
- unsigned `substate`
- `uint32_t` `codepoint` [2]
- unsigned char \* `buf`
- `size_t` `buf_used`
- `size_t` `buf_allocated`
- `size_t` `last_cl_offset`

## 9.6 JSON\_VALUE Struct Reference

### Data Fields

- union {  
`uint8_t` `data_bytes` [16]  
`void *` `data_ptrs` [16/sizeof(void \*)]  
} `data`



## 9.7 wolfentry\_allocator Struct Reference

Struct for passing shims that abstract the native implementation of the heap allocator.

```
#include <wolfentry.h>
```

### Data Fields

- `void * context`  
*A user-supplied opaque handle to be passed as the first arg to all callbacks. Can be null.*
- `wolfentry_malloc_cb_t malloc`  
*Required pointer.*
- `wolfentry_free_cb_t free`  
*Required pointer.*
- `wolfentry_realloc_cb_t realloc`  
*Required pointer.*
- `wolfentry_memalign_cb_t memalign`  
*Optional pointer. Required only if a struct `wolfentry_eventconfig` is passed in (e.g. to `wolfentry_init()`) with a `nonzeroroute_private_data_alignment`.*
- `wolfentry_free_aligned_cb_t free_aligned`  
*Optional pointer. Required (and allowed) only if `memalign` pointer is non-null.*

### 9.7.1 Detailed Description

Struct for passing shims that abstract the native implementation of the heap allocator.

## 9.8 wolfentry\_build\_settings Struct Reference

struct for passing the build version and configuration

```
#include <wolfentry_settings.h>
```

### Data Fields

- `uint32_t version`
- `uint32_t config`

### 9.8.1 Detailed Description

struct for passing the build version and configuration

### 9.8.2 Field Documentation

#### 9.8.2.1 config

```
uint32_t wolfentry_build_settings::config
```

Must be initialized to `WOLFENTRY_CONFIG_SIGNATURE`.

### 9.8.2.2 version

```
uint32_t wolfentry_build_settings::version
```

Must be initialized to [WOLFSENTRY\\_VERSION](#).

## 9.9 wolfentry\_data Struct Reference

### Public Member Functions

- [WOLFSENTRY\\_SOCKADDR](#) (128) remote
- [WOLFSENTRY\\_SOCKADDR](#) (128) local

### Data Fields

- [wolfentry\\_route\\_flags\\_t](#) flags
- void \* heap
- int alloctype

## 9.10 wolfentry\_eventconfig Struct Reference

struct for representing event configuration

```
#include <wolfentry.h>
```

### Data Fields

- [size\\_t route\\_private\\_data\\_size](#)  
*bytes to allocate for private use for application data*
- [size\\_t route\\_private\\_data\\_alignment](#)  
*alignment for private data allocation*
- [uint32\\_t max\\_connection\\_count](#)  
*If nonzero, the concurrent connection limit, beyond which additional connection requests are rejected.*
- [wolfentry\\_hitcount\\_t derogatory\\_threshold\\_for\\_penaltybox](#)  
*If nonzero, the threshold at which accumulated derogatory counts (from [WOLFSENTRY\\_ACTION\\_RES\\_↔ DEROGATORY](#) incidents) automatically penalty boxes a route.*
- [wolfentry\\_time\\_t penaltybox\\_duration](#)  
*The duration that a route stays in penalty box status before automatic release. Zero means time-unbounded.*
- [wolfentry\\_time\\_t route\\_idle\\_time\\_for\\_purge](#)  
*The time after the most recent dispatch match for a route to be garbage-collected. Zero means no automatic purge.*
- [wolfentry\\_eventconfig\\_flags\\_t flags](#)  
*Config flags.*
- [wolfentry\\_route\\_flags\\_t route\\_flags\\_to\\_add\\_on\\_insert](#)  
*List of route flags to set on new routes upon insertion.*
- [wolfentry\\_route\\_flags\\_t route\\_flags\\_to\\_clear\\_on\\_insert](#)  
*List of route flags to clear on new routes upon insertion.*
- [wolfentry\\_action\\_res\\_t action\\_res\\_filter\\_bits\\_set](#)  
*List of result flags that must be set at lookup time (dispatch) for referring routes to match.*
- [wolfentry\\_action\\_res\\_t action\\_res\\_filter\\_bits\\_unset](#)  
*List of result flags that must be clear at lookup time (dispatch) for referring routes to match.*
- [wolfentry\\_action\\_res\\_t action\\_res\\_bits\\_to\\_add](#)  
*List of result flags to be set upon match.*
- [wolfentry\\_action\\_res\\_t action\\_res\\_bits\\_to\\_clear](#)  
*List of result flags to be cleared upon match.*

### 9.10.1 Detailed Description

struct for representing event configuration

## 9.11 wolfentry\_host\_platform\_interface Struct Reference

struct for passing shims that abstract native implementations of the heap allocator, time functions, and semaphores

```
#include <wolfentry.h>
```

### Data Fields

- struct [wolfentry\\_build\\_settings](#) caller\_build\_settings
- struct [wolfentry\\_allocator](#) allocator
- struct [wolfentry\\_timecbs](#) timecbs
- struct [wolfentry\\_semcbs](#) semcbs

### 9.11.1 Detailed Description

struct for passing shims that abstract native implementations of the heap allocator, time functions, and semaphores

### 9.11.2 Field Documentation

#### 9.11.2.1 allocator

```
struct wolfentry\_allocator wolfentry_host_platform_interface::allocator
```

Either all-null, or initialized as described for [wolfentry\\_allocator](#).

#### 9.11.2.2 caller\_build\_settings

```
struct wolfentry\_build\_settings wolfentry_host_platform_interface::caller_build_settings
```

Must be initialized as described for [wolfentry\\_build\\_settings](#).

#### 9.11.2.3 semcbs

```
struct wolfentry\_semcbs wolfentry_host_platform_interface::semcbs
```

Either all-null, or initialized as described for [wolfentry\\_semcbs](#).

#### 9.11.2.4 timecbs

```
struct wolfentry\_timecbs wolfentry_host_platform_interface::timecbs
```

Either all-null, or initialized as described for [wolfentry\\_timecbs](#).

## 9.12 wolfentry\_kv\_pair Struct Reference

public structure for passing user-defined values in/out of wolfSentry

```
#include <wolfentry.h>
```

### Data Fields

- int **key\_len**  
*the length of the key, not including the terminating null*
- [wolfentry\\_kv\\_type\\_t](#) **v\_type**  
*the type of value*
- union {
  - uint64\_t **v\_uint**  
*The value when v\_type is WOLFSENTRY\_KV\_UINT*
  - int64\_t **v\_sint**  
*The value when v\_type is WOLFSENTRY\_KV\_SINT*
  - double **v\_float**  
*The value when v\_type is WOLFSENTRY\_KV\_FLOAT*
  - size\_t **string\_len**  
*The length of the value when v\_type is WOLFSENTRY\_KV\_STRING*
  - size\_t **bytes\_len**  
*The length of the value when v\_type is WOLFSENTRY\_KV\_BYTES*
  - [JSON\\_VALUE](#) **v\_json**  
*The value when v\_type is WOLFSENTRY\_KV\_JSON*
- [byte](#) **b** []  
*A flexible-length buffer to hold the key, and for strings and bytes, the data.*

### 9.12.1 Detailed Description

public structure for passing user-defined values in/out of wolfSentry

### 9.12.2 Field Documentation

#### 9.12.2.1 b

```
byte wolfentry_kv_pair::b[]
```

A flexible-length buffer to hold the key, and for strings and bytes, the data.

For atomic values and WOLFSENTRY\_KV\_JSON, this is just the key, with a terminating null at the end. For WOLFSENTRY\_KV\_STRING and WOLFSENTRY\_KV\_BYTES, the value itself appears right after the key with its terminating null.

## 9.13 wolfentry\_route\_endpoint Struct Reference

struct for exporting socket addresses, with fixed-length fields

```
#include <wolfentry.h>
```

**Data Fields**

- [wolfsentry\\_port\\_t](#) **sa\_port**  
*The port number – only treated as a TCP/IP port number if the route has the [WOLFSENTRY\\_ROUTE\\_FLAG\\_TCPLIKE\\_PORT\\_NUMBER](#) flag set.*
- [wolfsentry\\_addr\\_bits\\_t](#) **addr\_len**  
*The number of significant bits in the address. The address data itself is in the parent [wolfsentry\\_route\\_exports](#) struct.*
- [byte](#) **extra\_port\_count**  
*The number of extra ports in the route – not currently supported.*
- [byte](#) **interface**  
*The interface ID of the route.*

**9.13.1 Detailed Description**

struct for exporting socket addresses, with fixed-length fields

**9.14 wolfsentry\_route\_exports Struct Reference**

struct for exporting a route for access by applications

```
#include <wolfsentry.h>
```

**Data Fields**

- const char \* **parent\_event\_label**  
*Label of the parent event, or null if none.*
- int **parent\_event\_label\_len**  
*Length (not including terminating null) of label of the parent event, if any.*
- [wolfsentry\\_route\\_flags\\_t](#) **flags**  
*Current route flags (mutable bits are informational/approximate)*
- [wolfsentry\\_addr\\_family\\_t](#) **sa\_family**  
*Address family for this route.*
- [wolfsentry\\_proto\\_t](#) **sa\_proto**  
*Protocol for this route.*
- struct [wolfsentry\\_route\\_endpoint](#) **remote**  
*Remote socket address for this route.*
- struct [wolfsentry\\_route\\_endpoint](#) **local**  
*Local socket address for this route.*
- const [byte](#) \* **remote\_address**  
*Binary address data for the remote end of this route.*
- const [byte](#) \* **local\_address**  
*Binary address data for the local end of this route.*
- const [wolfsentry\\_port\\_t](#) \* **remote\_extra\_ports**  
*array of extra remote ports that match this route – not yet implemented*
- const [wolfsentry\\_port\\_t](#) \* **local\_extra\_ports**  
*array of extra local ports that match this route – not yet implemented*
- struct [wolfsentry\\_route\\_metadata\\_exports](#) **meta**  
*The current route metadata.*
- void \* **private\_data**  
*The private data segment (application-defined), if any.*
- [size\\_t](#) **private\_data\_size**  
*The size of the private data segment, if any, or zero.*

### 9.14.1 Detailed Description

struct for exporting a route for access by applications

## 9.15 wolfentry\_route\_metadata\_exports Struct Reference

struct for exporting route metadata for access by applications

```
#include <wolfentry.h>
```

### Data Fields

- [wolfentry\\_time\\_t insert\\_time](#)  
*The time the route was inserted.*
- [wolfentry\\_time\\_t last\\_hit\\_time](#)  
*The most recent time the route was matched.*
- [wolfentry\\_time\\_t last\\_penaltybox\\_time](#)  
*The most recent time the route had its [WOLFENTRY\\_ROUTE\\_FLAG\\_PENALTYBOXED](#) flag set.*
- [wolfentry\\_time\\_t purge\\_after](#)  
*The expiration time of the route, if any. Persistent routes have 0 here, and the setting can be modified with [wolfentry\\_route\\_purge\\_time\\_set\(\)](#).*
- [uint16\\_t connection\\_count](#)  
*The current connection count (informational/approximate)*
- [uint16\\_t derogatory\\_count](#)  
*The current derogatory event count (informational/approximate)*
- [uint16\\_t commendable\\_count](#)  
*The current commendable event count (informational/approximate)*
- [wolfentry\\_hitcount\\_t hit\\_count](#)  
*The lifetime match count (informational/approximate, and only maintained if the [WOLFENTRY\\_ROUTE\\_FLAG\\_DONT\\_COUNT\\_HITS](#) flag is clear)*

### 9.15.1 Detailed Description

struct for exporting route metadata for access by applications

## 9.16 wolfentry\_semcbs Struct Reference

Struct for passing shims that abstract the native implementation of counting semaphores.

```
#include <wolfentry.h>
```

### Data Fields

- [sem\\_init\\_cb\\_t](#) **sem\_init**  
*Required pointer.*
- [sem\\_post\\_cb\\_t](#) **sem\_post**  
*Required pointer.*
- [sem\\_wait\\_cb\\_t](#) **sem\_wait**  
*Required pointer.*
- [sem\\_timedwait\\_cb\\_t](#) **sem\_timedwait**  
*Required pointer.*
- [sem\\_trywait\\_cb\\_t](#) **sem\_trywait**  
*Required pointer.*
- [sem\\_destroy\\_cb\\_t](#) **sem\_destroy**  
*Required pointer.*

#### 9.16.1 Detailed Description

Struct for passing shims that abstract the native implementation of counting semaphores.

## 9.17 wolfsentry\_sockaddr Struct Reference

struct for passing socket addresses into `wolfsentry_route_*`() API routines

```
#include <wolfsentry.h>
```

### Data Fields

- [wolfsentry\\_addr\\_family\\_t](#) **sa\_family**  
*Address family number.*
- [wolfsentry\\_proto\\_t](#) **sa\_proto**  
*Protocol number.*
- [wolfsentry\\_port\\_t](#) **sa\_port**  
*Port number.*
- [wolfsentry\\_addr\\_bits\\_t](#) **addr\_len**  
*Significant bits in address.*
- [byte](#) **interface**  
*Interface ID number.*
- [byte](#) **addr []**  
*Binary big-endian address data.*

#### 9.17.1 Detailed Description

struct for passing socket addresses into `wolfsentry_route_*`() API routines

## 9.18 wolfentry\_thread\_context\_public Struct Reference

Right-sized, right-aligned opaque container for thread state.

```
#include <wolfentry_settings.h>
```

### Data Fields

- uint64\_t **opaque** [8]

### 9.18.1 Detailed Description

Right-sized, right-aligned opaque container for thread state.

## 9.19 wolfentry\_timecbs Struct Reference

Struct for passing shims that abstract the native implementation of time functions.

```
#include <wolfentry.h>
```

### Data Fields

- void \* **context**  
*A user-supplied opaque handle to be passed as the first arg to the `get_time` callback. Can be null.*
- [wolfentry\\_get\\_time\\_cb\\_t](#) **get\_time**  
*Required pointer.*
- [wolfentry\\_diff\\_time\\_cb\\_t](#) **diff\_time**  
*Required pointer.*
- [wolfentry\\_add\\_time\\_cb\\_t](#) **add\_time**  
*Required pointer.*
- [wolfentry\\_to\\_epoch\\_time\\_cb\\_t](#) **to\_epoch\_time**  
*Required pointer.*
- [wolfentry\\_from\\_epoch\\_time\\_cb\\_t](#) **from\_epoch\_time**  
*Required pointer.*
- [wolfentry\\_interval\\_to\\_seconds\\_cb\\_t](#) **interval\_to\_seconds**  
*Required pointer.*
- [wolfentry\\_interval\\_from\\_seconds\\_cb\\_t](#) **interval\_from\_seconds**  
*Required pointer.*

### 9.19.1 Detailed Description

Struct for passing shims that abstract the native implementation of time functions.



# Chapter 10

## File Documentation

### 10.1 centijson\_dom.h

```
00001 /*
00002  * centijson_dom.h
00003  *
00004  * Copyright (C) 2022-2023 wolfSSL Inc.
00005  *
00006  * This file is part of wolfSentry.
00007  *
00008  * wolfSentry is free software; you can redistribute it and/or modify
00009  * it under the terms of the GNU General Public License as published by
00010  * the Free Software Foundation; either version 2 of the License, or
00011  * (at your option) any later version.
00012  *
00013  * wolfSentry is distributed in the hope that it will be useful,
00014  * but WITHOUT ANY WARRANTY; without even the implied warranty of
00015  * MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
00016  * GNU General Public License for more details.
00017  *
00018  * You should have received a copy of the GNU General Public License
00019  * along with this program; if not, write to the Free Software
00020  * Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1335, USA
00021  */
00022
00023 /*
00024  * CentiJSON
00025  * <http://github.com/mity/centijson>
00026  *
00027  * Copyright (c) 2018 Martin Mitas
00028  *
00029  * Permission is hereby granted, free of charge, to any person obtaining a
00030  * copy of this software and associated documentation files (the "Software"),
00031  * to deal in the Software without restriction, including without limitation
00032  * the rights to use, copy, modify, merge, publish, distribute, sublicense,
00033  * and/or sell copies of the Software, and to permit persons to whom the
00034  * Software is furnished to do so, subject to the following conditions:
00035  *
00036  * The above copyright notice and this permission notice shall be included in
00037  * all copies or substantial portions of the Software.
00038  *
00039  * THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS
00040  * OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
00041  * FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
00042  * AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
00043  * LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING
00044  * FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS
00045  * IN THE SOFTWARE.
00046  */
00047
00048 #ifndef JSON_DOM_H
00049 #define JSON_DOM_H
00050
00051 #include "wolfsentry/centijson_sax.h"
00052 #include "wolfsentry/centijson_value.h"
00053
00054 #ifdef __cplusplus
00055 extern "C" {
00056 #endif
00057
00058
```

```

00059 /* DOM-specific error codes
00060 *
00061 * The DOM parsing functions can return any from json.h and additionally these.
00062 */
00063 #define JSON_DOM_ERR_DUPKEY (-1000)
00064
00065
00066 /* Flags for json_dom_init()
00067 */
00068
00069 /* Policy how to deal if the JSON contains object with duplicate key: */
00070 #define JSON_DOM_DUPKEY_ABORT 0x0000U
00071 #define JSON_DOM_DUPKEY_USEFIRST 0x0001U
00072 #define JSON_DOM_DUPKEY_USELAST 0x0002U
00073
00074 #define JSON_DOM_DUPKEY_MASK \
00075     (JSON_DOM_DUPKEY_ABORT | JSON_DOM_DUPKEY_USEFIRST | JSON_DOM_DUPKEY_USELAST)
00076
00077 /* When creating JSON_VALUE_DICT (for JSON_OBJECT), use flag JSON_VALUE_DICT_MAINTAINORDER. */
00078 #define JSON_DOM_MAINTAINDICTIONORDER 0x0010U
00079
00080 /* Internal use */
00081 #define JSON_DOM_FLAG_INITED 0x8000U
00082
00083 /* Structure holding parsing state. Do not access it directly.
00084 */
00085 typedef struct JSON_DOM_PARSER {
00086     JSON_PARSER parser;
00087     JSON_VALUE** path;
00088     size_t path_size;
00089     size_t path_alloc;
00090     JSON_VALUE root;
00091     JSON_VALUE key;
00092     unsigned flags;
00093     unsigned dict_flags;
00094 } JSON_DOM_PARSER;
00095
00096
00097 /* Used internally by load_config.c:handle_user_value_clause() */
00098 int json_dom_init_1(
00099     #ifdef WOLFSENTRY
00100     WOLFSENTRY_CONTEXT_ARGS_IN_EX(struct wolfentry_allocator *allocator),
00101     #endif
00102     JSON_DOM_PARSER* dom_parser, unsigned dom_flags);
00103
00104 /* Used internally by load_config.c:handle_user_value_clause() */
00105 int json_dom_process(JSON_TYPE type, const unsigned char* data, size_t data_size, void* user_data);
00106
00107 /* Used internally by load_config.c:handle_user_value_clause() */
00108 int json_dom_fini_aux(JSON_DOM_PARSER* dom_parser, JSON_VALUE* p_root);
00109
00110 int json_dom_clean(JSON_DOM_PARSER* dom_parser);
00111
00112 /* Initialize the DOM parser structure.
00113 *
00114 * The parameter `config` is propagated into json_init().
00115 */
00116 WOLFSENTRY_API int json_dom_init(
00117     #ifdef WOLFSENTRY
00118     WOLFSENTRY_CONTEXT_ARGS_IN_EX(struct wolfentry_allocator *allocator),
00119     #endif
00120     JSON_DOM_PARSER* dom_parser, const JSON_CONFIG* config, unsigned dom_flags);
00121
00122 /* Feed the parser with more input.
00123 */
00124 WOLFSENTRY_API int json_dom_feed(JSON_DOM_PARSER* dom_parser, const unsigned char* input, size_t
size);
00125
00126 /* Finish the parsing and free any resources associated with the parser.
00127 *
00128 * On success, zero is returned and the JSON_VALUE pointed by `p_dom` is initialized
00129 * accordingly to the root of the data in the JSON input (typically array or
00130 * object), and it contains all the data from the JSON input.
00131 *
00132 * On failure, the error code is returned; info about position of the issue in
00133 * the input is filled in the structure pointed by `p_pos` (if `p_pos` is not
00134 * NULL and if it is a parsing kind of error); and the value pointed by `p_dom`
00135 * is initialized to JSON_VALUE_NULL.
00136 */
00137 WOLFSENTRY_API int json_dom_fini(JSON_DOM_PARSER* dom_parser, JSON_VALUE* p_dom, JSON_INPUT_POS*
p_pos);
00138
00139
00140 /* Simple wrapper for json_dom_init() + json_dom_feed() + json_dom_fini(),
00141 * usable when the provided input contains complete JSON document.
00142 */
00143 WOLFSENTRY_API int json_dom_parse(

```

```

00144 #ifdef WOLFSENTRY
00145     WOLFSENTRY_CONTEXT_ARGS_IN_EX(struct wolfentry_allocator *allocator),
00146 #endif
00147     const unsigned char* input, size_t size, const JSON_CONFIG* config,
00148     unsigned dom_flags, JSON_VALUE* p_root, JSON_INPUT_POS* p_pos);
00149
00150
00151 /* Dump recursively all the DOM hierarchy out, via the provided writing
00152  * callback.
00153  *
00154  * The provided writing function must write all the data provided to it
00155  * and return zero to indicate success, or non-zero to indicate an error
00156  * and abort the operation.
00157  *
00158  * Returns zero on success, JSON_ERR_OUTOFMEMORY, or an error the code returned
00159  * from writing callback.
00160  */
00161 #define JSON_DOM_DUMP_MINIMIZE      0x0001 /* Do not indent, do not use no extra whitespace
including new lines. */
00162 #define JSON_DOM_DUMP_FORCECLRF     0x0002 /* Use "\r\n" instead of just "\n". */
00163 #define JSON_DOM_DUMP_INDENTWITHSPACES 0x0004 /* Indent with `tab_width` spaces instead of with
'\t'. */
00164 #define JSON_DOM_DUMP_PREFERDICTORDER 0x0008 /* Prefer original dictionary order, if available. */
00165
00166 WOLFSENTRY_API int json_dom_dump(
00167 #ifdef WOLFSENTRY
00168     WOLFSENTRY_CONTEXT_ARGS_IN_EX(struct wolfentry_allocator *allocator),
00169 #endif
00170     const JSON_VALUE* root,
00171     JSON_DUMP_CALLBACK write_func, void* user_data,
00172     unsigned tab_width, unsigned flags);
00173
00174 WOLFSENTRY_API const char* json_dom_error_str(int err_code);
00175
00176 #ifdef __cplusplus
00177 } /* extern "C" { */
00178 #endif
00179
00180 #endif /* JSON_DOM_H */

```

## 10.2 centijson\_sax.h

```

00001 /*
00002  * centijson_sax.h
00003  *
00004  * Copyright (C) 2021-2023 wolfSSL Inc.
00005  *
00006  * This file is part of wolfSentry.
00007  *
00008  * wolfSentry is free software; you can redistribute it and/or modify
00009  * it under the terms of the GNU General Public License as published by
00010  * the Free Software Foundation; either version 2 of the License, or
00011  * (at your option) any later version.
00012  *
00013  * wolfSentry is distributed in the hope that it will be useful,
00014  * but WITHOUT ANY WARRANTY; without even the implied warranty of
00015  * MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
00016  * GNU General Public License for more details.
00017  *
00018  * You should have received a copy of the GNU General Public License
00019  * along with this program; if not, write to the Free Software
00020  * Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1335, USA
00021  */
00022
00023 /*
00024  * CentiJSON
00025  * <http://github.com/mity/centijson>
00026  *
00027  * Copyright (c) 2018 Martin Mitas
00028  *
00029  * Permission is hereby granted, free of charge, to any person obtaining a
00030  * copy of this software and associated documentation files (the "Software"),
00031  * to deal in the Software without restriction, including without limitation
00032  * the rights to use, copy, modify, merge, publish, distribute, sublicense,
00033  * and/or sell copies of the Software, and to permit persons to whom the
00034  * Software is furnished to do so, subject to the following conditions:
00035  *
00036  * The above copyright notice and this permission notice shall be included in
00037  * all copies or substantial portions of the Software.
00038  *
00039  * THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS
00040  * OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
00041  * FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE

```

```

00042  * AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
00043  * LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING
00044  * FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS
00045  * IN THE SOFTWARE.
00046  */
00047
00048 #ifndef CENTIJSON_SAX_H
00049 #define CENTIJSON_SAX_H
00050
00051 #if !defined(WOLFSENTRY) && !defined(WOLFSENTRY_API)
00052     #define WOLFSENTRY_API
00053 #endif
00054
00055 #ifndef WOLFSENTRY
00056 #include <stdint.h>
00057 #include <sys/types.h>
00058 #endif
00059
00060 #ifdef __cplusplus
00061 extern "C" {
00062 #endif
00063
00064 /* JSON data types.
00065  *
00066  * Note that we distinguish beginning/end of the arrays and objects for
00067  * the purposes of the processing.
00068  */
00069 typedef enum JSON_TYPE {
00070     JSON_NULL,
00071     JSON_FALSE,
00072     JSON_TRUE,
00073     JSON_NUMBER,
00074     JSON_STRING,
00075     JSON_KEY, /* String in the specific role of an object key. */
00076     JSON_ARRAY_BEG,
00077     JSON_ARRAY_END,
00078     JSON_OBJECT_BEG,
00079     JSON_OBJECT_END
00080 } JSON_TYPE;
00081
00082 /* Error codes.
00083  */
00084 #define JSON_ERR_SUCCESS 0
00085 #define JSON_ERR_INTERNAL (-1) /* This should never happen. If you see it, report bug
00086  */
00087 #define JSON_ERR_OUTOFMEMORY (-2)
00088 #define JSON_ERR_SYNTAX (-4) /* Generic syntax error. (More specific error codes
00089  are preferred.) */
00090 #define JSON_ERR_BADCLOSER (-5) /* Mismatch in brackets (e.g. "{" or "[") */
00091 #define JSON_ERR_BADROOTTYPE (-6) /* Root type not allowed by CONFIG::flags. */
00092 #define JSON_ERR_EXPECTEDVALUE (-7) /* Something unexpected where value has to be. */
00093 #define JSON_ERR_EXPECTEDKEY (-8) /* Something unexpected where key has to be. */
00094 #define JSON_ERR_EXPECTEDVALUEORCLOSER (-9) /* Something unexpected where value or array/object
00095  closer has to be. */
00096 #define JSON_ERR_EXPECTEDKEYORCLOSER (-10) /* Something unexpected where key or array/object
00097  closer has to be. */
00098 #define JSON_ERR_EXPECTEDCOLON (-11) /* Something unexpected where colon has to be. */
00099 #define JSON_ERR_EXPECTEDCOMMAORCLOSER (-12) /* Something unexpected where comma or array/object
00100  has to be. */
00101 #define JSON_ERR_EXPECTEDEOF (-13) /* Something unexpected where end-of-file has to be.
00102  */
00103 #define JSON_ERR_MAXTOTALLEN (-14) /* Reached JSON_CONFIG::max_total_len */
00104 #define JSON_ERR_MAXTOTALVALUES (-15) /* Reached JSON_CONFIG::max_total_values */
00105 #define JSON_ERR_MAXNESTINGLEVEL (-16) /* Reached JSON_CONFIG::max_nesting_level */
00106 #define JSON_ERR_MAXNUMBERLEN (-17) /* Reached JSON_CONFIG::max_number_len */
00107 #define JSON_ERR_MAXSTRINGLEN (-18) /* Reached JSON_CONFIG::max_string_len */
00108 #define JSON_ERR_MAXKEYLEN (-19) /* Reached JSON_CONFIG::max_key_len */
00109 #define JSON_ERR_UNCLOSEDSTRING (-20) /* Unclosed string */
00110 #define JSON_ERR_UNESCAPEDCONTROL (-21) /* Unescaped control character (in a string) */
00111 #define JSON_ERR_INVALIDESCAPE (-22) /* Invalid/unknown escape sequence (in a string) */
00112 #define JSON_ERR_INVALIDUTF8 (-23) /* Invalid UTF-8 (in a string) */
00113 #define JSON_ERR_NOT_INITED (-24) /* Attempt to access an uninit JSON_PARSER or
00114  JSON_DOM_PARSER. */
00115
00116 /* Bits for JSON_CONFIG::flags.
00117  */
00118 #define JSON_NONULLASROOT 0x0001U /* Disallow null to be root value */
00119 #define JSON_NOBOOLASROOT 0x0002U /* Disallow false or true to be root value */
00120 #define JSON_NONUMBERASROOT 0x0004U /* Disallow number to be root value */
00121 #define JSON_NOSTRINGASROOT 0x0008U /* Disallow string to be root value */
00122 #define JSON_NOARRAYASROOT 0x0010U /* Disallow array to be root value */
00123 #define JSON_NOOBJECTASROOT 0x0020U /* Disallow object to be root value */
00124 #define JSON_NOSCALARROOT (JSON_NONULLASROOT | JSON_NOBOOLASROOT | \

```

```

00122                                     JSON_NONUMBERASROOT | JSON_NOSTRINGASROOT)
00123 #define JSON_NOVECTORROOT          (JSON_NOARRAYASROOT | JSON_NOOBJECTASROOT)
00124
00125 #define JSON_IGNOREILLUTF8KEY      0x0100U /* Ignore ill-formed UTF-8 (for keys). */
00126 #define JSON_FIXILLUTF8KEY         0x0200U /* Replace ill-formed UTF-8 char with replacement char
00127 (for keys). */
00127 #define JSON_IGNOREILLUTF8VALUE    0x0400U /* Ignore ill-formed UTF-8 (for string values). */
00128 #define JSON_FIXILLUTF8VALUE       0x0800U /* Replace ill-formed UTF-8 char with replacement char
00129 (for string values). */
00129
00130
00131
00132 /* Parser options, passed into json_init().
00133 *
00134 * If NULL is passed to json_init(), default values are used.
00135 */
00136 typedef struct JSON_CONFIG {
00137     size_t max_total_len;          /* zero means no limit; default: 10 MB */
00138     size_t max_total_values;       /* zero means no limit; default: 0 */
00139     size_t max_number_len;         /* zero means no limit; default: 512 */
00140     size_t max_string_len;        /* zero means no limit; default: 65536 */
00141     size_t max_key_len;           /* zero means no limit; default: 512 */
00142     unsigned max_nesting_level;    /* zero means no limit; default: 512 */
00143     unsigned flags;               /* default: 0 */
00144 } JSON_CONFIG;
00145
00146
00147 /* Helper structure describing position in the input.
00148 *
00149 * It is used to specify where in the input a parsing error occurred for
00150 * better diagnostics.
00151 */
00152 typedef struct JSON_INPUT_POS {
00153     size_t offset;
00154     unsigned line_number;
00155     unsigned column_number;
00156 } JSON_INPUT_POS;
00157
00158
00159 /* Callbacks the application has to implement, to process the parsed data.
00160 */
00161 typedef struct JSON_CALLBACKS {
00162     /* Data processing callback. For now (and maybe forever) the only callback.
00163     *
00164     * Note that `data` and `data_size` are set only for JSON_KEY, JSON_STRING
00165     * and JSON_NUMBER. (For the other types the callback always gets NULL and
00166     * 0).
00167     *
00168     * Inside an object, the application is guaranteed to get keys and their
00169     * corresponding values in the alternating fashion (i.e. in the order
00170     * as they are in the JSON input.).
00171     *
00172     * Application can abort the parsing operation by returning a non-zero.
00173     * Note the non-zero return value of the callback is propagated to
00174     * json_feed() and json_fini().
00175     */
00176     int (*process)(JSON_TYPE /*type*/, const unsigned char* /*data*/,
00177                    size_t /*data_size*/, void* /*user_data*/);
00178 } JSON_CALLBACKS;
00179
00180
00181 /* Internal parser state. Use pointer to this structure as an opaque handle.
00182 */
00183 typedef struct JSON_PARSER {
00184 #ifdef WOLFSENTRY
00185     struct wolfentry_allocator *allocator;
00186 #ifdef WOLFSENTRY_THREADSAFE
00187     struct wolfentry_thread_context *thread;
00188 #endif
00189 #endif
00190     JSON_CALLBACKS callbacks;
00191     JSON_CONFIG config;
00192     void* user_data;
00193
00194     JSON_INPUT_POS pos;
00195     JSON_INPUT_POS value_pos;
00196     JSON_INPUT_POS err_pos;
00197
00198     int errcode;
00199
00200     size_t value_counter;
00201
00202     unsigned char* nesting_stack;
00203     size_t nesting_level;
00204     size_t nesting_stack_size;
00205
00206     enum centijson_automaton {

```

```

00207     AUTOMATON_MAIN = 0,
00208     AUTOMATON_NULL = 1,
00209     AUTOMATON_FALSE = 2,
00210     AUTOMATON_TRUE = 3,
00211     AUTOMATON_NUMBER = 4,
00212     AUTOMATON_STRING = 6,
00213     AUTOMATON_KEY = 7
00214 } automaton;
00215
00216 unsigned state;
00217 unsigned substate;
00218
00219 uint32_t codepoint[2];
00220
00221 unsigned char* buf;
00222 size_t buf_used;
00223 size_t buf_allocated;
00224
00225 size_t last_cl_offset; /* Offset of most recently seen '\r' */
00226 } JSON_PARSER;
00227
00228
00229
00230 /* Fill `config` with options used by default.
00231 */
00232 WOLFSENTRY_API_VOID json_default_config(JSON_CONFIG* config);
00233
00234
00235 /* Initialize the parser, associate it with the given callbacks and
00236 * configuration. Returns zero on success, non-zero on an error.
00237 *
00238 * If `config` is NULL, default values are used.
00239 */
00240 WOLFSENTRY_API int json_init(
00241 #ifdef WOLFSENTRY
00242     WOLFSENTRY_CONTEXT_ARGS_IN_EX(struct wolfentry_allocator *allocator),
00243 #endif
00244     JSON_PARSER* parser,
00245     const JSON_CALLBACKS* callbacks,
00246     const JSON_CONFIG* config,
00247     void* user_data);
00248
00249 /* Feed the parser with more input.
00250 *
00251 * Returns zero on success.
00252 *
00253 * If an error occurs it returns non-zero and any attempt to call json_feed()
00254 * again shall just fail with the same error code. Note the application should
00255 * still call json_fini() to release all resources allocated by the parser.
00256 */
00257 WOLFSENTRY_API int json_feed(JSON_PARSER* parser, const unsigned char* input, size_t size);
00258
00259 /* Finish parsing of the document (note it can still call some callbacks); and
00260 * release any resources held by the parser.
00261 *
00262 * Returns zero on success, or non-zero on failure.
00263 *
00264 * If `p_pos` is not NULL, it is filled with info about reached position in the
00265 * input. It can help in diagnostics if the parsing failed.
00266 *
00267 * Note that if the preceding call to json_feed() failed, the error status also
00268 * propagates into json_fini().
00269 *
00270 * Also note this function may still fail even when all preceding calls to
00271 * json_feed() succeeded. This typically happens when the parser was fed with
00272 * an incomplete JSON document.
00273 */
00274 WOLFSENTRY_API int json_fini(JSON_PARSER* parser, JSON_INPUT_POS* p_pos);
00275
00276
00277 /* Simple wrapper function for json_init() + json_feed() + json_fini(), usable
00278 * when the provided input contains complete JSON document.
00279 */
00280 WOLFSENTRY_API int json_parse(
00281 #ifdef WOLFSENTRY
00282     WOLFSENTRY_CONTEXT_ARGS_IN_EX(struct wolfentry_allocator *allocator),
00283 #endif
00284     const unsigned char* input, size_t size,
00285     const JSON_CALLBACKS* callbacks, const JSON_CONFIG* config,
00286     void* user_data, JSON_INPUT_POS* p_pos);
00287
00288
00289 /* Converts error code to human readable error message
00290 */
00291 WOLFSENTRY_API const char* json_error_str(int err_code);
00292
00293 WOLFSENTRY_API const char* json_type_str(JSON_TYPE type);

```

```

00294
00295
00296 /*****
00297  *** Utilities ***
00298  *****/
00299
00300 /* When implementing the callback processing the parsed data, these utilities
00301  * below may come handy.
00302  */
00303
00304 /* Analyze the string holding a JSON number, and analyze whether it can
00305  * fit into integer types.
00306  *
00307  * (Note it says "no" in cases the number string contains any fraction or
00308  * exponent part.)
00309  */
00310 WOLFSENTRY_API int json_analyze_number(const unsigned char* num, size_t num_size,
00311                                       int* p_is_int32_compatible,
00312                                       int* p_is_uint32_compatible,
00313                                       int* p_is_int64_compatible,
00314                                       int* p_is_uint64_compatible);
00315
00316 /* Convert the string holding JSON number to the given C type.
00317  *
00318  * Note the conversion to any of the integer types is undefined unless
00319  * json_analyze_number() says it's fine.
00320  *
00321  * Also note that json_number_to_double() can fail with JSON_ERR_OUTOFMEMORY.
00322  * Hence its prototype differs.
00323  */
00324 WOLFSENTRY_API int32_t json_number_to_int32(const unsigned char* num, size_t num_size);
00325 WOLFSENTRY_API uint32_t json_number_to_uint32(const unsigned char* num, size_t num_size);
00326 WOLFSENTRY_API int64_t json_number_to_int64(const unsigned char* num, size_t num_size);
00327 WOLFSENTRY_API uint64_t json_number_to_uint64(const unsigned char* num, size_t num_size);
00328 WOLFSENTRY_API int json_number_to_double(const unsigned char* num, size_t num_size, double* p_result);
00329
00330
00331 typedef int (*JSON_DUMP_CALLBACK)(const unsigned char* /*str*/, size_t /*size*/, void* /*user_data*/);
00332
00333 /* Helpers for writing numbers and strings in JSON-compatible format.
00334  *
00335  * Note that json_dump_string() assumes the string is a well-formed UTF-8
00336  * string which needs no additional Unicode validation. The function "only"
00337  * handles proper escaping of control characters.
00338  *
00339  * The provided writer callback must write all the data provided to it and
00340  * return zero to indicate success, or non-zero to indicate an error and abort
00341  * the operation.
00342  *
00343  * All these return zero on success, JSON_ERR_OUTOFMEMORY, or an error code
00344  * propagated from the writer callback.
00345  *
00346  * (Given that all the other JSON stuff is trivial to output, the application
00347  * is supposed to implement that manually.)
00348  */
00349 WOLFSENTRY_API int json_dump_int32(int32_t i32, JSON_DUMP_CALLBACK write_func, void* user_data);
00350 WOLFSENTRY_API int json_dump_uint32(uint32_t u32, JSON_DUMP_CALLBACK write_func, void* user_data);
00351 WOLFSENTRY_API int json_dump_int64(int64_t i64, JSON_DUMP_CALLBACK write_func, void* user_data);
00352 WOLFSENTRY_API int json_dump_uint64(uint64_t u64, JSON_DUMP_CALLBACK write_func, void* user_data);
00353 WOLFSENTRY_API int json_dump_double(double dbl, JSON_DUMP_CALLBACK write_func, void* user_data);
00354 WOLFSENTRY_API int json_dump_string(const unsigned char* str, size_t size, JSON_DUMP_CALLBACK
00355   write_func, void* user_data);
00356
00357 #ifdef __cplusplus
00358 } /* extern "C" { */
00359 #endif
00360
00361 #endif /* CENTIJSON_SAX_H */

```

## 10.3 centijson\_value.h

```

00001 /*
00002  * centijson_value.h
00003  *
00004  * Copyright (C) 2022-2023 wolfSSL Inc.
00005  *
00006  * This file is part of wolfSentry.
00007  *
00008  * wolfSentry is free software; you can redistribute it and/or modify
00009  * it under the terms of the GNU General Public License as published by
00010  * the Free Software Foundation; either version 2 of the License, or
00011  * (at your option) any later version.

```

```

00012 *
00013 * wolfSentry is distributed in the hope that it will be useful,
00014 * but WITHOUT ANY WARRANTY; without even the implied warranty of
00015 * MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
00016 * GNU General Public License for more details.
00017 *
00018 * You should have received a copy of the GNU General Public License
00019 * along with this program; if not, write to the Free Software
00020 * Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1335, USA
00021 */
00022
00023 /*
00024 * C Reusables
00025 * <http://github.com/mity/c-reusables>
00026 *
00027 * Copyright (c) 2018 Martin Mitas
00028 *
00029 * Permission is hereby granted, free of charge, to any person obtaining a
00030 * copy of this software and associated documentation files (the "Software"),
00031 * to deal in the Software without restriction, including without limitation
00032 * the rights to use, copy, modify, merge, publish, distribute, sublicense,
00033 * and/or sell copies of the Software, and to permit persons to whom the
00034 * Software is furnished to do so, subject to the following conditions:
00035 *
00036 * The above copyright notice and this permission notice shall be included in
00037 * all copies or substantial portions of the Software.
00038 *
00039 * THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS
00040 * OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
00041 * FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE
00042 * AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER
00043 * LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING
00044 * FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS
00045 * IN THE SOFTWARE.
00046 */
00047
00048 #ifndef CENTIJSON_VALUE_H
00049 #define CENTIJSON_VALUE_H
00050
00051 #ifdef __cplusplus
00052 extern "C" {
00053 #endif
00054
00055 #ifdef WOLFSENTRY
00056 #include "wolfentry.h"
00057 #endif
00058 #ifndef WOLFSENTRY_API
00059 #define WOLFSENTRY_API
00060 #endif
00061
00062 #ifndef WOLFSENTRY
00063 #include <stdint.h>
00064 #endif
00065
00066 /* The value structure.
00067 * Use as opaque.
00068 */
00069 typedef struct JSON_VALUE {
00070     /* We need at least 2 * sizeof(void*). Sixteen bytes covers that on 64-bit
00071     * platforms and it seems as a good compromise allowing to "inline" all
00072     * numeric types as well as short strings; which is good idea: most dict
00073     * keys as well as many string values are in practice quite short. */
00074     union {
00075         uint8_t data_bytes[16];
00076         void *data_ptrs[16 / sizeof(void *)];
00077     } data;
00078 } JSON_VALUE;
00079
00080
00081 /* Value types.
00082 */
00083 typedef enum JSON_VALUE_TYPE {
00084     JSON_VALUE_NULL = 0,
00085     JSON_VALUE_BOOL,
00086     JSON_VALUE_INT32,
00087     JSON_VALUE_UINT32,
00088     JSON_VALUE_INT64,
00089     JSON_VALUE_UINT64,
00090     JSON_VALUE_FLOAT,
00091     JSON_VALUE_DOUBLE,
00092     JSON_VALUE_STRING,
00093     JSON_VALUE_ARRAY,
00094     JSON_VALUE_DICT
00095 } JSON_VALUE_TYPE;
00096
00097
00098 /* Free any resources the value holds.

```



```

00099  * For ARRAY and DICT it is recursive.
00100  */
00101  WOLFSENTRY_API int json_value_fini(
00102  #ifdef WOLFSENTRY
00103      WOLFSENTRY_CONTEXT_ARGS_IN_EX(struct wolfentry_allocator *allocator),
00104  #endif
00105      JSON_VALUE* v);
00106
00107  /* Get value type.
00108  */
00109  WOLFSENTRY_API JSON_VALUE_TYPE json_value_type(const JSON_VALUE* v);
00110
00111  /* Check whether the value is "compatible" with the given type.
00112  *
00113  * This is especially useful for determining whether a numeric value can be
00114  * "casted" to other numeric type. The function does some basic checking
00115  * whether such conversion loses substantial information.
00116  *
00117  * For example, value initialized with init_float(&v, 1.0f) is considered
00118  * compatible with INT32, because 1.0f has zero fraction and 1 fits between
00119  * INT32_MIN and INT32_MAX. Therefore calling int32_value(&v) gets sensible
00120  * result.
00121  */
00122  WOLFSENTRY_API int json_value_is_compatible(const JSON_VALUE* v, JSON_VALUE_TYPE type);
00123
00124  /* Values newly added into array or dictionary are of type VALUE_NULL.
00125  *
00126  * Additionally, for such newly created values, an internal flag is used to
00127  * mark that the value was never explicitly initialized by the application.
00128  *
00129  * This function checks value of the flag, and allows thus the caller to
00130  * distinguish whether the value was just added; or whether the value was
00131  * explicitly initialized as VALUE_NULL with value_init_null().
00132  *
00133  * Caller is supposed to initialize all such newly added value with any of the
00134  * value_init_XXX() functions, and hence reset the flag.
00135  */
00136  WOLFSENTRY_API int json_value_is_new(const JSON_VALUE* v);
00137
00138  /* Simple recursive getter, capable to get a value dwelling deep in the
00139  * hierarchy formed by nested arrays and dictionaries.
00140  *
00141  * Limitations: The function is not capable to deal with object keys which
00142  * contain zero byte '\0', slash '/' or brackets '[' ']' because those are
00143  * interpreted by the function as special characters:
00144  *
00145  * -- '/' delimits dictionary keys (and optionally also array indexes;
00146  *    paths "foo/[4]" and "foo[4]" are treated as equivalent.)
00147  * -- '[' ']' enclose array indexes (for distinguishing from numbered
00148  *    dictionary keys). Note that negative indexes are supported here;
00149  *    '[-1]' refers to the last element in the array, '[-2]' to the element
00150  *    before the last element etc.
00151  * -- '\0' terminates the whole path (as is normal with C strings).
00152  *
00153  * Examples:
00154  *
00155  * (1) value_path(root, "") gets directly the root.
00156  *
00157  * (2) value_path(root, "foo") gets value keyed with 'foo' if root is a
00158  *    dictionary having such value, or NULL otherwise.
00159  *
00160  * (3) value_path(root, "[4]") gets value with index 4 if root is an array
00161  *    having so many members, or NULL otherwise.
00162  *
00163  * (4) value_path(root, "foo[2]/bar/baz[3]") walks deeper and deeper and
00164  *    returns a value stored there assuming these all conditions are true:
00165  *    -- root is dictionary having the key "foo";
00166  *    -- that value is a nested list having the index [2];
00167  *    -- that value is a nested dictionary having the key "bar";
00168  *    -- that value is a nested dictionary having the key "baz";
00169  *    -- and finally, that is a list having the index [3].
00170  *    If any of those is not fulfilled, then NULL is returned.
00171  */
00172  WOLFSENTRY_API JSON_VALUE* json_value_path(JSON_VALUE* root, const char* path);
00173
00174  /* value_build_path() is similar to value_path(); but allows easy populating
00175  * of value hierarchies.
00176  *
00177  * If all values along the path already exist, the behavior is exactly the same
00178  * as value_path().
00179  *
00180  * But when a value corresponding to any component of the path does not exist
00181  * then, instead of returning NULL, new value is added into the parent
00182  * container (assuming the parent existing container has correct type as
00183  * assumed by the path.)
00184  *
00185  * Caller may use empty "[]" to always enforce appending a new value into an

```

```

00186 * array. E.g. value_build_path(root, "multiple_values/[]/name") makes sure the
00187 * root contains an array under the key "multiple_values", and a new dictionary
00188 * is appended at the end of the array. This new dictionary gets a new value
00189 * under the key "name". Assuming the function succeeds, the caller can now be
00190 * sure the "name" is initialized as VALUE_NULL because the new dictionary has
00191 * been just created and added as the last element if the list.
00192 *
00193 * If such new value does not correspond to the last path component, the new
00194 * value gets initialized as the right type so subsequent path component can
00195 * be treated the same way.
00196 *
00197 * If the function creates the value corresponding to the last component of the
00198 * path, it is initialized as VALUE_NULL and the "new flag" is set for it, so
00199 * caller can test this condition with value_is_new().
00200 *
00201 * Returns NULL if the path cannot be resolved because any existing value
00202 * has a type incompatible with the path; if creation of any value along the
00203 * path fails; or if an array index is out of bounds.
00204 */
00205 /* missing implementation */
00206 /* WOLFSENTRY_API JSON_VALUE* json_value_build_path(JSON_VALUE* root, const char* path); */
00207
00208
00209 /*****
00210 *** VALUE_NULL ***
00211 *****/
00212
00213 /* Note it is guaranteed that VALUE_NULL does not need any explicit clean-up;
00214 * i.e. application may avoid calling value_fini().
00215 *
00216 * But it is allowed to. value_fini() for VALUE_NULL is a noop.
00217 */
00218
00219
00220 /* Static initializer.
00221 */
00222 #define JSON_VALUE_NULL_INITIALIZER { { 0,0,0,0,0,0,0,0,0,0,0,0,0,0 } }
00223
00224 WOLFSENTRY_API_VOID json_value_init_null(JSON_VALUE* v);
00225
00226
00227 /*****
00228 *** VALUE_BOOL ***
00229 *****/
00230
00231 WOLFSENTRY_API int json_value_init_bool(JSON_VALUE* v, int b);
00232
00233 WOLFSENTRY_API int json_value_bool(const JSON_VALUE* v);
00234
00235
00236 /*****
00237 *** Numeric types ***
00238 *****/
00239
00240
00241 /* Initializers.
00242 */
00243 WOLFSENTRY_API int json_value_init_int32(
00244 #ifdef WOLFSENTRY
00245     WOLFSENTRY_CONTEXT_ARGS_IN_EX(struct wolfentry_allocator *allocator),
00246 #endif
00247     JSON_VALUE* v, int32_t i32);
00248 WOLFSENTRY_API int json_value_init_uint32(
00249 #ifdef WOLFSENTRY
00250     WOLFSENTRY_CONTEXT_ARGS_IN_EX(struct wolfentry_allocator *allocator),
00251 #endif
00252     JSON_VALUE* v, uint32_t u32);
00253 WOLFSENTRY_API int json_value_init_int64(
00254 #ifdef WOLFSENTRY
00255     WOLFSENTRY_CONTEXT_ARGS_IN_EX(struct wolfentry_allocator *allocator),
00256 #endif
00257     JSON_VALUE* v, int64_t i64);
00258 WOLFSENTRY_API int json_value_init_uint64(
00259 #ifdef WOLFSENTRY
00260     WOLFSENTRY_CONTEXT_ARGS_IN_EX(struct wolfentry_allocator *allocator),
00261 #endif
00262     JSON_VALUE* v, uint64_t u64);
00263 WOLFSENTRY_API int json_value_init_float(
00264 #ifdef WOLFSENTRY
00265     WOLFSENTRY_CONTEXT_ARGS_IN_EX(struct wolfentry_allocator *allocator),
00266 #endif
00267     JSON_VALUE* v, float f);
00268 WOLFSENTRY_API int json_value_init_double(
00269 #ifdef WOLFSENTRY
00270     WOLFSENTRY_CONTEXT_ARGS_IN_EX(struct wolfentry_allocator *allocator),
00271 #endif
00272     JSON_VALUE* v, double d);

```

```

00273
00274 /* Getters.
00275 *
00276 * Note you may use any of the getter function for any numeric value. These
00277 * functions perform required conversions under the hood. The conversion may
00278 * have have the same side/limitations as C casting.
00279 *
00280 * However application may use json_value_is_compatible() to verify whether the
00281 * conversion should provide a reasonable result.
00282 */
00283 WOLFSENTRY_API int32_t json_value_int32(const JSON_VALUE* v);
00284 WOLFSENTRY_API uint32_t json_value_uint32(const JSON_VALUE* v);
00285 WOLFSENTRY_API int64_t json_value_int64(const JSON_VALUE* v);
00286 WOLFSENTRY_API uint64_t json_value_uint64(const JSON_VALUE* v);
00287 WOLFSENTRY_API float json_value_float(const JSON_VALUE* v);
00288 WOLFSENTRY_API double json_value_double(const JSON_VALUE* v);
00289
00290
00291 /*****
00292 *** JSON_VALUE_STRING ***
00293 *****/
00294
00295 /* Note JSON_VALUE_STRING allows to store any sequences of any bytes, even a binary
00296 * data. No particular encoding of the string is assumed. Even zero bytes are
00297 * allowed (but then the caller has to use json_value_init_string_() and specify
00298 * the string length explicitly).
00299 */
00300
00301 /* The function json_value_init_string_() initializes the JSON_VALUE_STRING with any
00302 * sequence of bytes, of any length. It also adds automatically one zero byte
00303 * (not counted in the length of the string).
00304 *
00305 * The function json_value_init_string() is equivalent to calling directly
00306 * json_value_init_string(str, strlen(str)).
00307 *
00308 * The parameter str is allowed to be NULL (then the functions behave the same
00309 * way as if it is points to an empty string).
00310 */
00311 WOLFSENTRY_API int json_value_init_string_(
00312 #ifdef WOLFSENTRY
00313     WOLFSENTRY_CONTEXT_ARGS_IN_EX(struct wolfentry_allocator *allocator),
00314 #endif
00315     JSON_VALUE* v, const unsigned char* str, size_t len);
00316 WOLFSENTRY_API int json_value_init_string(
00317 #ifdef WOLFSENTRY
00318     WOLFSENTRY_CONTEXT_ARGS_IN_EX(struct wolfentry_allocator *allocator),
00319 #endif
00320     JSON_VALUE* v, const unsigned char* str);
00321
00322 /* Get pointer to the internal buffer holding the string. The caller may assume
00323 * the returned string is always zero-terminated.
00324 */
00325 WOLFSENTRY_API const unsigned char* json_value_string(const JSON_VALUE* v);
00326
00327 /* Get length of the string. (The implicit zero terminator does not count.)
00328 */
00329 WOLFSENTRY_API size_t json_value_string_length(const JSON_VALUE* v);
00330
00331 /*****
00332 *** JSON_VALUE_ARRAY ***
00333 *****/
00334
00335 /* Array of values.
00336 *
00337 * Note that any new value added into the array with json_value_array_append() or
00338 * json_value_array_insert() is initially of the type JSON_VALUE_NULL and that it has
00339 * an internal flag marking the value as new (so that json_value_is_new() returns
00340 * non-zero for it). Application is supposed to initialize the newly added
00341 * value by any of the value initialization functions.
00342 *
00343 * WARNING: Modifying contents of an array (i.e. inserting, appending and also
00344 * removing a value) can lead to reallocation of internal array buffer.
00345 * Hence, consider all JSON_VALUE* pointers invalid after modifying the array.
00346 * That includes the return values of json_value_array_get(), json_value_array_get_all(),
00347 * but also preceding calls of json_value_array_append() and json_value_array_insert().
00348 */
00349
00350 WOLFSENTRY_API int json_value_init_array(
00351 #ifdef WOLFSENTRY
00352     WOLFSENTRY_CONTEXT_ARGS_IN_EX(struct wolfentry_allocator *allocator),
00353 #endif
00354     JSON_VALUE* v);
00355
00356 /* Get count of items in the array.
00357 */
00358 WOLFSENTRY_API size_t json_value_array_size(const JSON_VALUE* v);
00359

```

```

00360 /* Get the specified item.
00361 */
00362 WOLFSENTRY_API JSON_VALUE* json_value_array_get(const JSON_VALUE* v, size_t index);
00363
00364 /* Get pointer to internal C array of all items.
00365 */
00366 WOLFSENTRY_API JSON_VALUE* json_value_array_get_all(const JSON_VALUE* v);
00367
00368 /* Append/insert new item.
00369 */
00370 WOLFSENTRY_API JSON_VALUE* json_value_array_append(
00371 #ifdef WOLFSENTRY
00372     WOLFSENTRY_CONTEXT_ARGS_IN_EX(struct wolfentry_allocator *allocator),
00373 #endif
00374     JSON_VALUE* v);
00375 WOLFSENTRY_API JSON_VALUE* json_value_array_insert(
00376 #ifdef WOLFSENTRY
00377     WOLFSENTRY_CONTEXT_ARGS_IN_EX(struct wolfentry_allocator *allocator),
00378 #endif
00379     JSON_VALUE* v, size_t index);
00380
00381 /* Remove an item (or range of items).
00382 */
00383 WOLFSENTRY_API int json_value_array_remove(
00384 #ifdef WOLFSENTRY
00385     WOLFSENTRY_CONTEXT_ARGS_IN_EX(struct wolfentry_allocator *allocator),
00386 #endif
00387     JSON_VALUE* v, size_t index);
00388 WOLFSENTRY_API int json_value_array_remove_range(
00389 #ifdef WOLFSENTRY
00390     WOLFSENTRY_CONTEXT_ARGS_IN_EX(struct wolfentry_allocator *allocator),
00391 #endif
00392     JSON_VALUE* v, size_t index, size_t count);
00393
00394 /* Remove and destroy all members (recursively).
00395 */
00396 WOLFSENTRY_API int json_value_array_clean(
00397 #ifdef WOLFSENTRY
00398     WOLFSENTRY_CONTEXT_ARGS_IN_EX(struct wolfentry_allocator *allocator),
00399 #endif
00400     JSON_VALUE* v);
00401
00402
00403 /*****
00404 *** JSON_VALUE_DICT ***
00405 *****/
00406
00407 /* Dictionary of values. (Internally implemented as red-black tree.)
00408 *
00409 * Note that any new value added into the dictionary is initially of the type
00410 * JSON_VALUE_NULL and that it has an internal flag marking the value as new
00411 * (so that json_value_is_new() returns non-zero for it). Application is supposed
00412 * to initialize the newly added value by any of the value initialization
00413 * functions.
00414 *
00415 * Note that all the functions adding/removing any items may invalidate all
00416 * pointers into the dictionary.
00417 */
00418
00419
00420 /* Flag for init_dict_ex() asking to maintain the order in which the dictionary
00421 * is populated and enabling dict_walk_ordered().
00422 *
00423 * If used, the dictionary consumes more memory.
00424 */
00425 #define JSON_VALUE_DICT_MAINTAINORDER    0x0001
00426
00427 /* Initialize the value as a (empty) dictionary.
00428 *
00429 * json_value_init_dict_ex() allows to specify custom comparer function (may be NULL)
00430 * or flags changing the default behavior of the dictionary.
00431 */
00432 WOLFSENTRY_API int json_value_init_dict(
00433 #ifdef WOLFSENTRY
00434     WOLFSENTRY_CONTEXT_ARGS_IN_EX(struct wolfentry_allocator *allocator),
00435 #endif
00436     JSON_VALUE* v);
00437 WOLFSENTRY_API int json_value_init_dict_ex(
00438 #ifdef WOLFSENTRY
00439     WOLFSENTRY_CONTEXT_ARGS_IN_EX(struct wolfentry_allocator *allocator),
00440 #endif
00441     JSON_VALUE* v,
00442     int (*custom_cmp_func)(const unsigned char* /*key1*/, size_t /*len1*/,
00443                           const unsigned char* /*key2*/, size_t /*len2*/),
00444     unsigned flags);
00445
00446 /* Get flags of the dictionary.

```

```

00447  */
00448 WOLFSENTRY_API unsigned json_value_dict_flags(const JSON_VALUE* v);
00449
00450 /* Get count of items in the dictionary.
00451  */
00452 WOLFSENTRY_API size_t json_value_dict_size(const JSON_VALUE* v);
00453
00454 /* Get all keys.
00455  *
00456  * If the buffer provided by the caller is too small, only subset of keys shall
00457  * be retrieved.
00458  *
00459  * Returns count of retrieved keys.
00460  */
00461 WOLFSENTRY_API size_t json_value_dict_keys_sorted(const JSON_VALUE* v, const JSON_VALUE** buffer,
size_t buffer_size);
00462 WOLFSENTRY_API size_t json_value_dict_keys_ordered(const JSON_VALUE* v, const JSON_VALUE** buffer,
size_t buffer_size);
00463
00464 /* Find an item with the given key, or return NULL if no such item exists.
00465  */
00466 WOLFSENTRY_API JSON_VALUE* json_value_dict_get(const JSON_VALUE* v, const unsigned char* key, size_t
key_len);
00467 WOLFSENTRY_API JSON_VALUE* json_value_dict_get(const JSON_VALUE* v, const unsigned char* key);
00468
00469 /* Add new item with the given key of type JSON_VALUE_NULL.
00470  *
00471  * Returns NULL if the key is already used.
00472  */
00473 WOLFSENTRY_API JSON_VALUE* json_value_dict_add(
00474 #ifdef WOLFSENTRY
    WOLFSENTRY_CONTEXT_ARGS_IN_EX(struct wolfentry_allocator *allocator),
00475 #endif
    JSON_VALUE* v, const unsigned char* key, size_t key_len);
00476 WOLFSENTRY_API JSON_VALUE* json_value_dict_add(
00477 #ifdef WOLFSENTRY
    WOLFSENTRY_CONTEXT_ARGS_IN_EX(struct wolfentry_allocator *allocator),
00478 #endif
    JSON_VALUE* v, const unsigned char* key);
00479
00480 /* This is combined operation of json_value_dict_get() and json_value_dict_add().
00481  *
00482  * Get value of the given key. If no such value exists, new one is added.
00483  * Application can check for such situation with json_value_is_new().
00484  *
00485  * NULL is returned only in an out-of-memory situation.
00486  */
00487 WOLFSENTRY_API JSON_VALUE* json_value_dict_get_or_add(
00488 #ifdef WOLFSENTRY
    WOLFSENTRY_CONTEXT_ARGS_IN_EX(struct wolfentry_allocator *allocator),
00489 #endif
    JSON_VALUE* v, const unsigned char* key, size_t key_len);
00490 WOLFSENTRY_API JSON_VALUE* json_value_dict_get_or_add(
00491 #ifdef WOLFSENTRY
    WOLFSENTRY_CONTEXT_ARGS_IN_EX(struct wolfentry_allocator *allocator),
00492 #endif
    JSON_VALUE* v, const unsigned char* key);
00493
00494 /* Remove and destroy (recursively) the given item from the dictionary.
00495  */
00496 WOLFSENTRY_API int json_value_dict_remove(
00497 #ifdef WOLFSENTRY
    WOLFSENTRY_CONTEXT_ARGS_IN_EX(struct wolfentry_allocator *allocator),
00498 #endif
    JSON_VALUE* v, const unsigned char* key, size_t key_len);
00499 WOLFSENTRY_API int json_value_dict_remove(
00500 #ifdef WOLFSENTRY
    WOLFSENTRY_CONTEXT_ARGS_IN_EX(struct wolfentry_allocator *allocator),
00501 #endif
    JSON_VALUE* v, const unsigned char* key);
00502
00503 /* Walking over all items in the dictionary. The callback function is called
00504  * for every item in the dictionary, providing key and value and propagating
00505  * the user data into it. If the callback returns non-zero, the function
00506  * aborts immediately.
00507  *
00508  * Note dict_walk_ordered() is supported only if DICT_MAINTAINORDER
00509  * flag was used in init_dict().
00510  */
00511 WOLFSENTRY_API int json_value_dict_walk_ordered(const JSON_VALUE* v,
int (*visit_func)(const JSON_VALUE*, JSON_VALUE*, void*), void* ctx);
00512 WOLFSENTRY_API int json_value_dict_walk_sorted(const JSON_VALUE* v,
int (*visit_func)(const JSON_VALUE*, JSON_VALUE*, void*), void* ctx);
00513
00514 /* Remove and destroy all members (recursively).
00515  */
00516 WOLFSENTRY_API int json_value_dict_clean(

```

```

00531 #ifdef WOLFSENTRY
00532     WOLFSENTRY_CONTEXT_ARGS_IN_EX(struct wolfentry_allocator *allocator),
00533 #endif
00534     JSON_VALUE* v);
00535
00536 #ifdef WOLFSENTRY
00537 WOLFSENTRY_API int
00538 json_value_clone(WOLFSENTRY_CONTEXT_ARGS_IN_EX(struct wolfentry_allocator *allocator),
00539                 const JSON_VALUE* node, JSON_VALUE *clone);
00540 #endif
00541
00542 #ifdef __cplusplus
00543 }
00544 #endif
00545
00546 #endif /* CENTIJSON_VALUE_H */

```

## 10.4 wolfentry/wolfentry.h File Reference

The main include file for wolfSentry applications.

```

#include <wolfentry/wolfentry_settings.h>
#include <wolfentry/wolfentry_af.h>
#include <wolfentry/wolfentry_errcodes.h>
#include <wolfentry/centijson_dom.h>
#include <wolfentry/wolfentry_util.h>

```

### Data Structures

- struct [wolfentry\\_allocator](#)  
*Struct for passing shims that abstract the native implementation of the heap allocator.*
- struct [wolfentry\\_timecbs](#)  
*Struct for passing shims that abstract the native implementation of time functions.*
- struct [wolfentry\\_semcbs](#)  
*Struct for passing shims that abstract the native implementation of counting semaphores.*
- struct [wolfentry\\_host\\_platform\\_interface](#)  
*struct for passing shims that abstract native implementations of the heap allocator, time functions, and semaphores*
- struct [wolfentry\\_route\\_endpoint](#)  
*struct for exporting socket addresses, with fixed-length fields*
- struct [wolfentry\\_route\\_metadata\\_exports](#)  
*struct for exporting route metadata for access by applications*
- struct [wolfentry\\_route\\_exports](#)  
*struct for exporting a route for access by applications*
- struct [wolfentry\\_sockaddr](#)  
*struct for passing socket addresses into wolfentry\_route\_\*() API routines*
- struct [wolfentry\\_eventconfig](#)  
*struct for representing event configuration*
- struct [wolfentry\\_kv\\_pair](#)  
*public structure for passing user-defined values in/out of wolfSentry*

## Macros

- **#define WOLFSENTRY\_VERSION\_MAJOR**  
*Macro for major version number of installed headers.*
- **#define WOLFSENTRY\_VERSION\_MINOR**  
*Macro for minor version number of installed headers.*
- **#define WOLFSENTRY\_VERSION\_TINY**  
*Macro for tiny version number of installed headers.*
- **#define WOLFSENTRY\_VERSION\_ENCODE(major, minor, tiny)**  
*Macro to convert a wolfSentry version to a single integer, for comparison to other similarly converted versions.*
- **#define WOLFSENTRY\_VERSION**  
*The version recorded in [wolfsentry.h](#), encoded as an integer.*
- **#define WOLFSENTRY\_VERSION\_GT(major, minor, tiny)**  
*Helper macro that is true if the given version is greater than that in [wolfsentry.h](#).*
- **#define WOLFSENTRY\_VERSION\_GE(major, minor, tiny)**  
*Helper macro that is true if the given version is greater than or equal to that in [wolfsentry.h](#).*
- **#define WOLFSENTRY\_VERSION\_EQ(major, minor, tiny)**  
*Helper macro that is true if the given version equals that in [wolfsentry.h](#).*
- **#define WOLFSENTRY\_VERSION\_LT(major, minor, tiny)**  
*Helper macro that is true if the given version is less than that in [wolfsentry.h](#).*
- **#define WOLFSENTRY\_VERSION\_LE(major, minor, tiny)**  
*Helper macro that is true if the given version is less than or equal to that in [wolfsentry.h](#).*
- **#define WOLFSENTRY\_CONTEXT\_ARGS\_IN**  
*Common context argument generator for use at the beginning of arg lists in function prototypes and definitions. Pair with WOLFSENTRY\_CONTEXT\_ARGS\_OUT in the caller argument list.*
- **#define WOLFSENTRY\_CONTEXT\_ARGS\_IN\_EX(ctx)**  
*Variant of WOLFSENTRY\_CONTEXT\_ARGS\_IN that allows a fully type-qualified context to be supplied explicitly (allowing contexts other than `struct wolfsentry_context`)*
- **#define WOLFSENTRY\_CONTEXT\_ARGS\_IN\_EX4(ctx, thr)**  
*Variant of WOLFSENTRY\_CONTEXT\_ARGS\_IN that allows the identifiers for context and thread pointers to be supplied explicitly.*
- **#define WOLFSENTRY\_CONTEXT\_ELEMENTS**  
*Variant of WOLFSENTRY\_CONTEXT\_ARGS\_IN for constructing structs.*
- **#define WOLFSENTRY\_CONTEXT\_SET\_ELEMENTS(s)**  
*Counterpart to WOLFSENTRY\_CONTEXT\_ELEMENTS to access the wolfsentry context.*
- **#define WOLFSENTRY\_CONTEXT\_GET\_ELEMENTS(s)**  
*Counterpart to WOLFSENTRY\_CONTEXT\_ELEMENTS to access the thread context (exists only if defined ( $\leftrightarrow$  WOLFSENTRY\_THREADSAFE))*
- **#define WOLFSENTRY\_CONTEXT\_ARGS\_OUT**  
*Common context argument generator to use in calls to functions taking WOLFSENTRY\_CONTEXT\_ARGS\_IN*
- **#define WOLFSENTRY\_CONTEXT\_ARGS\_OUT\_EX(ctx)**  
*Variant of WOLFSENTRY\_CONTEXT\_ARGS\_OUT that allows passing an explicitly identified context argument generator to use in calls to functions taking WOLFSENTRY\_CONTEXT\_ARGS\_IN\_EX*
- **#define WOLFSENTRY\_CONTEXT\_ARGS\_OUT\_EX2(x)**  
*Variant of WOLFSENTRY\_CONTEXT\_ARGS\_OUT corresponding to WOLFSENTRY\_CONTEXT\_ELEMENTS*
- **#define WOLFSENTRY\_CONTEXT\_ARGS\_OUT\_EX3(x, y)**  
*Special-purpose variant of WOLFSENTRY\_CONTEXT\_ARGS\_OUT\_EX for accessing context element `y` in structure pointer `x`*
- **#define WOLFSENTRY\_CONTEXT\_ARGS\_OUT\_EX4(x, y)**  
*Special-purpose variant of WOLFSENTRY\_CONTEXT\_ARGS\_OUT that simply expands to `x` or `x, y` depending on WOLFSENTRY\_THREADSAFE*
- **#define WOLFSENTRY\_CONTEXT\_ARGS\_NOT\_USED**



Helper macro for function implementations that need to accept `WOLFSENTRY_CONTEXT_ARGS_IN` for API conformance, but don't actually use the arguments.

- **#define WOLFSENTRY\_CONTEXT\_ARGS\_THREAD\_NOT\_USED**

Helper macro for function implementations that need to accept `WOLFSENTRY_CONTEXT_ARGS_IN` for API conformance, but don't actually use the `thread` argument.

- **#define WOLFSENTRY\_THREAD\_HEADER\_DECLS**
- **#define WOLFSENTRY\_THREAD\_HEADER\_INIT(flags)**

For `WOLFSENTRY_THREADSAFE` applications, this allocates the required thread context on the stack.

- **#define WOLFSENTRY\_THREAD\_HEADER\_INIT\_CHECKED(flags)**

For `WOLFSENTRY_THREADSAFE` applications, this performs the required thread context initialization, with options from its `wolfentry_thread_flags_t` `flags` arg.

- **#define WOLFSENTRY\_THREAD\_HEADER(flags)**

For `WOLFSENTRY_THREADSAFE` applications, this performs the required thread context initialization, with options from its `wolfentry_thread_flags_t` `flags` arg, and returns on failure.

- **#define WOLFSENTRY\_THREAD\_HEADER\_CHECK()**

For `WOLFSENTRY_THREADSAFE` applications, this allocates the required thread context on the stack, and initializes it with options from its `wolfentry_thread_flags_t` `flags` arg.

- **#define WOLFSENTRY\_THREAD\_HEADER\_CHECKED(flags)**

For `WOLFSENTRY_THREADSAFE` applications, checks if thread context initialization succeeded, and returns on failure.

- **#define WOLFSENTRY\_THREAD\_TAILER(flags)**

For `WOLFSENTRY_THREADSAFE` applications, this allocates the required thread context on the stack, and initializes it with options from its `wolfentry_thread_flags_t` `flags` arg, returning on failure.

- **#define WOLFSENTRY\_THREAD\_TAILER\_CHECKED(flags)**

For `WOLFSENTRY_THREADSAFE` applications, this cleans up a thread context allocated with `WOLFSENTRY_THREAD_HEADER*`, with options from its `wolfentry_thread_flags_t` `flags` arg, returning on error.

- **#define WOLFSENTRY\_THREAD\_GET\_ERROR**

For `WOLFSENTRY_THREADSAFE` applications, this evaluates to the most recent result from `WOLFSENTRY_THREAD_HEADER_INIT` or `WOLFSENTRY_THREAD_TAILER()`

- **#define WOLFSENTRY\_ACTION\_RES\_USER\_SHIFT 24U**

Bit shift for user-defined bit span in `wolfentry_action_res_t`.

- **#define WOLFSENTRY\_ACTION\_RES\_USER7 (1U << 31U)**

user-defined result bit #8 of 8. Defined with a macro to retain ISO C compliance on enum range.

- **#define WOLFSENTRY\_ROUTE\_DEFAULT\_POLICY\_MASK (WOLFSENTRY\_ACTION\_RES\_ACCEPT | WOLFSENTRY\_ACTION\_RES\_REJECT | WOLFSENTRY\_ACTION\_RES\_STOP | WOLFSENTRY\_ACTION\_RES\_ERROR)**

Bit mask spanning the bits allowed by `wolfentry_route_table_default_policy_set()`

- **#define WOLFSENTRY\_ROUTE\_WILDCARD\_FLAGS**

Bit mask for the wildcard bits in a `wolfentry_route_flags_t`.

- **#define WOLFSENTRY\_ROUTE\_IMMUTABLE\_FLAGS**

Bit mask for the bits in a `wolfentry_route_flags_t` that can't change after the implicated route has been inserted in the route table.

- **#define WOLFSENTRY\_ROUTE\_INTERNAL\_FLAGS**

- **#define WOLFSENTRY\_SOCKADDR(n)**

- **#define WOLFSENTRY\_LENGTH\_NULL\_TERMINATED**

A macro with a painfully long name that can be passed as a length to routines taking a length argument, to signify that the associated string is null-terminated and its length should be computed on that basis.

- **#define WOLFSENTRY\_KV\_FLAG\_MASK**

A bit mask to retain only the flag bits in a `wolfentry_kv_type_t`.

- **#define WOLFSENTRY\_KV\_KEY\_LEN(kv)**

Evaluates to the length of the key of a `wolfentry_kv_pair`.

- **#define WOLFSENTRY\_KV\_KEY(kv)**

Evaluates to the key of a `wolfentry_kv_pair`.

- **#define WOLFSENTRY\_KV\_TYPE(kv)**



- Evaluates to the type of a [wolfsentry\\_kv\\_pair](#), with flag bits masked out.*
- **#define WOLFSENTRY\_KV\_V\_UINT(kv)**  
*Evaluates to the `uint64_t` value of a [wolfsentry\\_kv\\_pair](#) of type `WOLFSENTRY_KV_UINT`.*
- **#define WOLFSENTRY\_KV\_V\_SINT(kv)**  
*Evaluates to the `int64_t` value of a [wolfsentry\\_kv\\_pair](#) of type `WOLFSENTRY_KV_INT`.*
- **#define WOLFSENTRY\_KV\_V\_FLOAT(kv)**  
*Evaluates to the `double` value of a [wolfsentry\\_kv\\_pair](#) of type `WOLFSENTRY_KV_FLOAT`.*
- **#define WOLFSENTRY\_KV\_V\_STRING\_LEN(kv)**  
*Evaluates to the `size_t` length of the value of a [wolfsentry\\_kv\\_pair](#) of type `WOLFSENTRY_KV_STRING`.*
- **#define WOLFSENTRY\_KV\_V\_STRING(kv)**  
*Evaluates to the `char *` value of a [wolfsentry\\_kv\\_pair](#) of type `WOLFSENTRY_KV_STRING`.*
- **#define WOLFSENTRY\_KV\_V\_BYTES\_LEN(kv)**  
*Evaluates to the `size_t` length of the value of a [wolfsentry\\_kv\\_pair](#) of type `WOLFSENTRY_KV_BYTES`.*
- **#define WOLFSENTRY\_KV\_V\_BYTES(kv)**  
*Evaluates to the `byte *` value of a [wolfsentry\\_kv\\_pair](#) of type `WOLFSENTRY_KV_BYTES`.*
- **#define WOLFSENTRY\_KV\_V\_JSON(kv)**  
*Evaluates to the `JSON_VALUE *` value of a [wolfsentry\\_kv\\_pair](#) of type `WOLFSENTRY_KV_JSON`.*
- **#define WOLFSENTRY\_BASE64\_DECODED\_BUFSPC(buf, len)**  
*Given valid base64 string `buf` of length `len`, evaluates to the exact decoded length.*

## Typedefs

- **typedef void \*(\* [wolfsentry\\_malloc\\_cb\\_t](#))** (void \*context, struct wolfsentry\_thread\_context \*thread, size\_t size)  
*Pointer to malloc-like function. Takes extra initial args `context` and, if `!defined(WOLFSENTRY_SINGLETHREADED)`, `thread` arg.*
- **typedef void(\* [wolfsentry\\_free\\_cb\\_t](#))** (void \*context, struct wolfsentry\_thread\_context \*thread, void \*ptr)  
*Pointer to free-like function. Takes extra initial args `context` and, if `!defined(WOLFSENTRY_SINGLETHREADED)`, `thread` arg.*
- **typedef void \*(\* [wolfsentry\\_realloc\\_cb\\_t](#))** (void \*context, struct wolfsentry\_thread\_context \*thread, void \*ptr, size\_t size)  
*Pointer to realloc-like function. Takes extra initial args `context` and, if `!defined(WOLFSENTRY_SINGLETHREADED)`, `thread` arg.*
- **typedef void \*(\* [wolfsentry\\_memalign\\_cb\\_t](#))** (void \*context, struct wolfsentry\_thread\_context \*thread, size\_t alignment, size\_t size)  
*Pointer to memalign-like function. Takes extra initial args `context` and, if `!defined(WOLFSENTRY_SINGLETHREADED)`, `thread` arg.*
- **typedef void(\* [wolfsentry\\_free\\_aligned\\_cb\\_t](#))** (void \*context, struct wolfsentry\_thread\_context \*thread, void \*ptr)  
*Pointer to special-purpose free-like function, needed only if the `memalign` pointer in a struct [wolfsentry\\_allocator](#) is non-null. Can be same as routine supplied as `wolfsentry_free_cb_t`, or can be a separate routine, e.g. with special handling for pad bytes. Takes extra initial args `context` and, if `!defined(WOLFSENTRY_SINGLETHREADED)`, `thread` arg.*
- **typedef [wolfsentry\\_errcode\\_t](#)(\* [wolfsentry\\_get\\_time\\_cb\\_t](#))** (void \*context, [wolfsentry\\_time\\_t](#) \*ts)  
*Pointer to function that returns time denominated in `wolfsentry_time_t`. Takes an initial context arg, which can be ignored.*
- **typedef [wolfsentry\\_time\\_t](#)(\* [wolfsentry\\_diff\\_time\\_cb\\_t](#))** ([wolfsentry\\_time\\_t](#) earlier, [wolfsentry\\_time\\_t](#) later)  
*Pointer to function that subtracts `earlier` from `later`, returning the result.*
- **typedef [wolfsentry\\_time\\_t](#)(\* [wolfsentry\\_add\\_time\\_cb\\_t](#))** ([wolfsentry\\_time\\_t](#) start\_time, [wolfsentry\\_time\\_t](#) time\_interval)  
*Pointer to function that adds two `wolfsentry_time_t` times, returning the result.*
- **typedef [wolfsentry\\_errcode\\_t](#)(\* [wolfsentry\\_to\\_epoch\\_time\\_cb\\_t](#))** ([wolfsentry\\_time\\_t](#) when, time\_t \*epoch\_secs, long \*epoch\_nsecs)

- Pointer to function that converts a `wolfentry_time_t` to seconds and nanoseconds since midnight UTC, 1970-Jan-1.*
- typedef `wolfentry_errcode_t`(\* `wolfentry_from_epoch_time_cb_t`) (time\_t epoch\_secs, long epoch\_nsecs, `wolfentry_time_t` \*when)  
*Pointer to function that converts seconds and nanoseconds since midnight UTC, 1970-Jan-1, to a `wolfentry_time_t`.*
  - typedef `wolfentry_errcode_t`(\* `wolfentry_interval_to_seconds_cb_t`) (`wolfentry_time_t` howlong, time\_t \*howlong\_secs, long \*howlong\_nsecs)  
*Pointer to function that converts a `wolfentry_time_t` expressing an interval to the corresponding seconds and nanoseconds.*
  - typedef `wolfentry_errcode_t`(\* `wolfentry_interval_from_seconds_cb_t`) (time\_t howlong\_secs, long howlong\_nsecs, `wolfentry_time_t` \*howlong)  
*Pointer to function that converts seconds and nanoseconds expressing an interval to the corresponding `wolfentry_time_t`.*
  - typedef int(\* `sem_init_cb_t`) (sem\_t \*sem, int pshared, unsigned int value)
  - typedef int(\* `sem_post_cb_t`) (sem\_t \*sem)
  - typedef int(\* `sem_wait_cb_t`) (sem\_t \*sem)
  - typedef int(\* `sem_timedwait_cb_t`) (sem\_t \*sem, const struct timespec \*abs\_timeout)
  - typedef int(\* `sem_trywait_cb_t`) (sem\_t \*sem)
  - typedef int(\* `sem_destroy_cb_t`) (sem\_t \*sem)
  - typedef `wolfentry_errcode_t`(\* `wolfentry_action_callback_t`) (`WOLFENTRY_CONTEXT_ARGS_IN`, const struct wolfentry\_action \*action, void \*handler\_arg, void \*caller\_arg, const struct wolfentry\_event \*trigger\_event, `wolfentry_action_type_t` action\_type, const struct wolfentry\_route \*trigger\_route, struct wolfentry\_route\_table \*route\_table, struct wolfentry\_route \*rule\_route, `wolfentry_action_res_t` \*action\_results)  
*A callback that is triggered when an action is taken.*
  - typedef `wolfentry_errcode_t`(\* `wolfentry_make_id_cb_t`) (void \*context, `wolfentry_ent_id_t` \*id)
  - typedef void(\* `wolfentry_cleanup_callback_t`) (`WOLFENTRY_CONTEXT_ARGS_IN`, void \*cleanup\_arg)  
*Function type to pass to `wolfentry_cleanup_push()`*
  - typedef `wolfentry_errcode_t`(\* `wolfentry_addr_family_parser_t`) (`WOLFENTRY_CONTEXT_ARGS_IN`, const char \*addr\_text, int addr\_text\_len, byte \*addr\_internal, `wolfentry_addr_bits_t` \*addr\_internal\_bits)  
*Function type for parsing handler, to pass to `wolfentry_addr_family_handler_install()`*
  - typedef `wolfentry_errcode_t`(\* `wolfentry_addr_family_formatter_t`) (`WOLFENTRY_CONTEXT_ARGS_IN`, const byte \*addr\_internal, unsigned int addr\_internal\_bits, char \*addr\_text, int \*addr\_text\_len)  
*Function type for formatting handler, to pass to `wolfentry_addr_family_handler_install()`*
  - typedef `wolfentry_errcode_t`(\* `wolfentry_kv_validator_t`) (`WOLFENTRY_CONTEXT_ARGS_IN`, struct `wolfentry_kv_pair` \*kv)

## Enumerations

- enum `wolfentry_init_flags_t` {  
    `WOLFENTRY_INIT_FLAG_NONE` ,  
    `WOLFENTRY_INIT_FLAG_LOCK_SHARED_ERROR_CHECKING` }  
*flags to pass to `wolfentry_init_ex()`, to be ORed together.*
- enum `wolfentry_thread_flags_t` {  
    `WOLFENTRY_THREAD_FLAG_NONE` ,  
    `WOLFENTRY_THREAD_FLAG_DEADLINE` ,  
    `WOLFENTRY_THREAD_FLAG_READONLY` }  
*`wolfentry_thread_flags_t` flags are to be ORed together.*

- enum `wolfentry_lock_flags_t` {  
`WOLFENTRY_LOCK_FLAG_NONE` ,  
`WOLFENTRY_LOCK_FLAG_PSHARED` ,  
`WOLFENTRY_LOCK_FLAG_SHARED_ERROR_CHECKING` ,  
`WOLFENTRY_LOCK_FLAG_NONRECURSIVE_MUTEX` ,  
`WOLFENTRY_LOCK_FLAG_NONRECURSIVE_SHARED` ,  
`WOLFENTRY_LOCK_FLAG_GET_RESERVATION_TOO` ,  
`WOLFENTRY_LOCK_FLAG_TRY_RESERVATION_TOO` ,  
`WOLFENTRY_LOCK_FLAG_ABANDON_RESERVATION_TOO` ,  
`WOLFENTRY_LOCK_FLAG_AUTO_DOWNGRADE` ,  
`WOLFENTRY_LOCK_FLAG_RETAIN_SEMAPHORE` }

*flags to pass to `wolfentry_lock_*` () functions, to be OR'd together*

- enum `wolfentry_object_type_t` {  
`WOLFENTRY_OBJECT_TYPE_UNINITED` ,  
`WOLFENTRY_OBJECT_TYPE_TABLE` ,  
`WOLFENTRY_OBJECT_TYPE_ACTION` ,  
`WOLFENTRY_OBJECT_TYPE_EVENT` ,  
`WOLFENTRY_OBJECT_TYPE_ROUTE` ,  
`WOLFENTRY_OBJECT_TYPE_KV` ,  
`WOLFENTRY_OBJECT_TYPE_ADDR_FAMILY_BYNUMBER` ,  
`WOLFENTRY_OBJECT_TYPE_ADDR_FAMILY_BYNAME` }

*enum for communicating the type of an object.*

- enum `wolfentry_action_flags_t` {  
`WOLFENTRY_ACTION_FLAG_NONE` ,  
`WOLFENTRY_ACTION_FLAG_DISABLED` }

*enum for communicating attributes of an action object*

- enum `wolfentry_action_type_t` {  
`WOLFENTRY_ACTION_TYPE_NONE` ,  
`WOLFENTRY_ACTION_TYPE_POST` ,  
`WOLFENTRY_ACTION_TYPE_INSERT` ,  
`WOLFENTRY_ACTION_TYPE_MATCH` ,  
`WOLFENTRY_ACTION_TYPE_UPDATE` ,  
`WOLFENTRY_ACTION_TYPE_DELETE` ,  
`WOLFENTRY_ACTION_TYPE_DECISION` }

*enum communicating (to action handlers and internal logic) what type of action is being evaluated*

- enum `wolfentry_action_res_t` {  
`WOLFENTRY_ACTION_RES_NONE` ,  
`WOLFENTRY_ACTION_RES_ACCEPT` ,  
`WOLFENTRY_ACTION_RES_REJECT` ,  
`WOLFENTRY_ACTION_RES_CONNECT` ,  
`WOLFENTRY_ACTION_RES_DISCONNECT` ,  
`WOLFENTRY_ACTION_RES_DEROGATORY` ,  
`WOLFENTRY_ACTION_RES_COMMENDABLE` ,  
`WOLFENTRY_ACTION_RES_STOP` ,  
`WOLFENTRY_ACTION_RES_DEALLOCATED` ,  
`WOLFENTRY_ACTION_RES_INSERTED` ,  
`WOLFENTRY_ACTION_RES_ERROR` ,  
`WOLFENTRY_ACTION_RES_FALLTHROUGH` ,  
`WOLFENTRY_ACTION_RES_UPDATE` ,  
`WOLFENTRY_ACTION_RES_PORT_RESET` ,  
`WOLFENTRY_ACTION_RES_SENDING` ,  
`WOLFENTRY_ACTION_RES_RECEIVED` ,  
`WOLFENTRY_ACTION_RES_BINDING` ,  
`WOLFENTRY_ACTION_RES_LISTENING` ,  
`WOLFENTRY_ACTION_RES_STOPPED_LISTENING` ,  
`WOLFENTRY_ACTION_RES_CONNECTING_OUT` ,  
`WOLFENTRY_ACTION_RES_CLOSED` ,

```

WOLFSENTRY_ACTION_RES_UNREACHABLE ,
WOLFSENTRY_ACTION_RES_SOCK_ERROR ,
WOLFSENTRY_ACTION_RES_CLOSE_WAIT ,
WOLFSENTRY_ACTION_RES_USER0 ,
WOLFSENTRY_ACTION_RES_USER1 ,
WOLFSENTRY_ACTION_RES_USER2 ,
WOLFSENTRY_ACTION_RES_USER3 ,
WOLFSENTRY_ACTION_RES_USER4 ,
WOLFSENTRY_ACTION_RES_USERS5 ,
WOLFSENTRY_ACTION_RES_USER6 }

```

*bit field used to communicate states and attributes through the evaluation pipeline.*

- enum `wolfentry_route_flags_t` {
 

```

WOLFSENTRY_ROUTE_FLAG_NONE = 0U ,
WOLFSENTRY_ROUTE_FLAG_SA_FAMILY_WILDCARD ,
WOLFSENTRY_ROUTE_FLAG_SA_REMOTE_ADDR_WILDCARD ,
WOLFSENTRY_ROUTE_FLAG_SA_PROTO_WILDCARD ,
WOLFSENTRY_ROUTE_FLAG_SA_LOCAL_PORT_WILDCARD ,
WOLFSENTRY_ROUTE_FLAG_SA_LOCAL_ADDR_WILDCARD ,
WOLFSENTRY_ROUTE_FLAG_SA_REMOTE_PORT_WILDCARD ,
WOLFSENTRY_ROUTE_FLAG_REMOTE_INTERFACE_WILDCARD ,
WOLFSENTRY_ROUTE_FLAG_LOCAL_INTERFACE_WILDCARD ,
WOLFSENTRY_ROUTE_FLAG_PARENT_EVENT_WILDCARD ,
WOLFSENTRY_ROUTE_FLAG_TCPLIKE_PORT_NUMBERS ,
WOLFSENTRY_ROUTE_FLAG_DIRECTION_IN ,
WOLFSENTRY_ROUTE_FLAG_DIRECTION_OUT ,
WOLFSENTRY_ROUTE_FLAG_REMOTE_ADDR_BITMASK ,
WOLFSENTRY_ROUTE_FLAG_LOCAL_ADDR_BITMASK ,
WOLFSENTRY_ROUTE_FLAG_IN_TABLE ,
WOLFSENTRY_ROUTE_FLAG_PENDING_DELETE ,
WOLFSENTRY_ROUTE_FLAG_INSERT_ACTIONS_CALLED ,
WOLFSENTRY_ROUTE_FLAG_DELETE_ACTIONS_CALLED ,
WOLFSENTRY_ROUTE_FLAG_PENALTYBOXED ,
WOLFSENTRY_ROUTE_FLAG_GREENLISTED ,
WOLFSENTRY_ROUTE_FLAG_DONT_COUNT_HITS ,
WOLFSENTRY_ROUTE_FLAG_DONT_COUNT_CURRENT_CONNECTIONS ,
WOLFSENTRY_ROUTE_FLAG_PORT_RESET }

```

*bit field specifying attributes of a route/rule*

- enum `wolfentry_format_flags_t` {
 

```

WOLFSENTRY_FORMAT_FLAG_NONE ,
WOLFSENTRY_FORMAT_FLAG_ALWAYS_NUMERIC }

```

*Macro to instantiate a `wolfentry_sockaddr` with an `addr` field sized to hold `n` bits of address data. Cast to `struct wolfentry_sockaddr` to pass as API argument.*

- enum `wolfentry_event_flags_t` {
 

```

WOLFSENTRY_EVENT_FLAG_NONE ,
WOLFSENTRY_EVENT_FLAG_IS_PARENT_EVENT ,
WOLFSENTRY_EVENT_FLAG_IS_SUBEVENT }

```

*bit field with attribute flags for events*

- enum `wolfentry_eventconfig_flags_t` {
 

```

WOLFSENTRY_EVENTCONFIG_FLAG_NONE ,
WOLFSENTRY_EVENTCONFIG_FLAG_DEROGATORY_THRESHOLD_IGNORE_COMMENDABLE ,
WOLFSENTRY_EVENTCONFIG_FLAG_COMMENDABLE_CLEARS_DEROGATORY ,
WOLFSENTRY_EVENTCONFIG_FLAG_INHIBIT_ACTIONS }

```

*bit field with config flags for events*

- enum `wolfentry_clone_flags_t` {
 

```

WOLFSENTRY_CLONE_FLAG_NONE ,
WOLFSENTRY_CLONE_FLAG_AS_AT_CREATION ,
WOLFSENTRY_CLONE_FLAG_NO_ROUTES }

```

Flags to be OR'd together to control the dynamics of [wolfentry\\_context\\_clone\(\)](#) and other cloning functions.

- enum [wolfentry\\_kv\\_type\\_t](#) {  
**WOLFENTRY\_KV\_NONE** = 0 ,  
**WOLFENTRY\_KV\_NULL** ,  
**WOLFENTRY\_KV\_TRUE** ,  
**WOLFENTRY\_KV\_FALSE** ,  
**WOLFENTRY\_KV\_UINT** ,  
**WOLFENTRY\_KV\_SINT** ,  
**WOLFENTRY\_KV\_FLOAT** ,  
**WOLFENTRY\_KV\_STRING** ,  
**WOLFENTRY\_KV\_BYTES** ,  
**WOLFENTRY\_KV\_JSON** ,  
**WOLFENTRY\_KV\_FLAG\_READONLY** = 1<<30 }

enum to represent the type of a user-defined value

## Functions

- WOLFENTRY\_API struct [wolfentry\\_build\\_settings](#) **wolfentry\_get\_build\_settings** (void)  
Return the [wolfentry\\_build\\_settings](#) of the library as built.
- WOLFENTRY\_API [wolfentry\\_errcode\\_t](#) **wolfentry\_build\_settings\_compatible** (struct [wolfentry\\_build\\_settings](#) caller\_build\_settings)  
Return success if the application and library were built with mutually compatible wolfSentry version and configuration.
- WOLFENTRY\_API [wolfentry\\_errcode\\_t](#) **wolfentry\_init\_thread\_context** (struct [wolfentry\\_thread\\_context](#) \*thread\_context, [wolfentry\\_thread\\_flags\\_t](#) init\_thread\_flags, void \*user\_context)  
Initialize *thread\_context* according to *init\_thread\_flags*, storing *user\_context* for later retrieval with [wolfentry\\_get\\_thread\\_user\\_context\(\)](#).
- WOLFENTRY\_API [wolfentry\\_errcode\\_t](#) **wolfentry\_alloc\_thread\_context** (struct [wolfentry\\_host\\_platform\\_interface](#) \*hpi, struct [wolfentry\\_thread\\_context](#) \*\*thread\_context, [wolfentry\\_thread\\_flags\\_t](#) init\_thread\_flags, void \*user\_context)  
Allocate space for *thread\_context* using the allocator in *hpi*, then call [wolfentry\\_init\\_thread\\_context\(\)](#).
- WOLFENTRY\_API [wolfentry\\_errcode\\_t](#) **wolfentry\_get\_thread\_id** (struct [wolfentry\\_thread\\_context](#) \*thread, [wolfentry\\_thread\\_id\\_t](#) \*id)  
Write the [wolfentry\\_thread\\_id\\_t](#) of *thread* to *id*.
- WOLFENTRY\_API [wolfentry\\_errcode\\_t](#) **wolfentry\_get\_thread\_user\_context** (struct [wolfentry\\_thread\\_context](#) \*thread, void \*\*user\_context)  
Store to *user\_context* the pointer previously passed to [wolfentry\\_init\\_thread\\_context\(\)](#).
- WOLFENTRY\_API [wolfentry\\_errcode\\_t](#) **wolfentry\_get\_thread\_deadline** (struct [wolfentry\\_thread\\_context](#) \*thread, struct timespec \*deadline)  
Store the deadline for *thread* to *deadline*, or if the thread has no deadline set, store [WOLFENTRY\\_DEADLINE\\_NEVER](#) to *deadline->tv\_sec* and *deadline->tv\_nsec*.
- WOLFENTRY\_API [wolfentry\\_errcode\\_t](#) **wolfentry\_get\_thread\_flags** (struct [wolfentry\\_thread\\_context](#) \*thread, [wolfentry\\_thread\\_flags\\_t](#) \*thread\_flags)  
Store the flags of *thread* to *thread\_flags*.
- WOLFENTRY\_API [wolfentry\\_errcode\\_t](#) **wolfentry\_destroy\_thread\_context** (struct [wolfentry\\_thread\\_context](#) \*thread\_context, [wolfentry\\_thread\\_flags\\_t](#) thread\_flags)  
Perform final integrity checking on the thread state, and deallocate its ID.
- WOLFENTRY\_API [wolfentry\\_errcode\\_t](#) **wolfentry\_free\_thread\_context** (struct [wolfentry\\_host\\_platform\\_interface](#) \*hpi, struct [wolfentry\\_thread\\_context](#) \*\*thread\_context, [wolfentry\\_thread\\_flags\\_t](#) thread\_flags)  
Call [wolfentry\\_destroy\\_thread\\_context\(\)](#) on *\*thread\_context*, and if that succeeds, deallocate the thread object previously allocated by [wolfentry\\_alloc\\_thread\\_context\(\)](#).
- WOLFENTRY\_API [wolfentry\\_errcode\\_t](#) **wolfentry\_set\_deadline\_rel\_usec** ([WOLFENTRY\\_CONTEXT\\_ARGS\\_IN](#), int usecs)  
Set the thread deadline to *usecs* in the future. The thread will not wait for a lock beyond that deadline.

- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) **wolfentry\_set\_deadline\_abs** ([WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#), time\_t epoch\_secs, long epoch\_nsecs)  
*Set the thread deadline to the time identified by epoch\_secs and epoch\_nsecs. The thread will not wait for a lock beyond that deadline.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) **wolfentry\_clear\_deadline** ([WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#))  
*Clear any thread deadline previously set. On time-unbounded calls such as [wolfentry\\_lock\\_shared\(\)](#) and [wolfentry\\_lock\\_mutex\(\)](#), the thread will sleep until the lock is available.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) **wolfentry\_set\_thread\_readonly** (struct wolfentry\_thread\_↵ context \*thread\_context)  
*Set the thread state to allow only readonly locks to be gotten, allowing multiple shared locks to be concurrently held. If any mutexes or reservations are currently held, the call will fail.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) **wolfentry\_set\_thread\_readwrite** (struct wolfentry\_thread\_↵ context \*thread\_context)  
*Set the thread state to allow both readonly and mutex locks to be gotten. If multiple shared locks are currently held, the call will fail.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) **wolfentry\_lock\_init** (struct [wolfentry\\_host\\_platform\\_interface](#) \*hpi, struct wolfentry\_thread\_context \*thread, struct wolfentry\_rwlock \*lock, [wolfentry\\_lock\\_flags\\_t](#) flags)  
*This initializes a semaphore lock structure created by the user.*
- WOLFSENTRY\_API size\_t **wolfentry\_lock\_size** (void)
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) **wolfentry\_lock\_alloc** (struct [wolfentry\\_host\\_platform\\_interface](#) \*hpi, struct wolfentry\_thread\_context \*thread, struct wolfentry\_rwlock \*\*lock, [wolfentry\\_lock\\_flags\\_t](#) flags)  
*Allocates and initializes a semaphore lock structure for use with wolfSentry.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) **wolfentry\_lock\_shared** (struct wolfentry\_rwlock \*lock, struct wolfentry\_thread\_context \*thread, [wolfentry\\_lock\\_flags\\_t](#) flags)  
*Requests a shared lock.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) **wolfentry\_lock\_shared\_abstimed** (struct wolfentry\_rwlock \*lock, struct wolfentry\_thread\_context \*thread, const struct timespec \*abs\_timeout, [wolfentry\\_lock\\_flags\\_t](#) flags)  
*Requests a shared lock with an absolute timeout.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) **wolfentry\_lock\_shared\_timed** (struct wolfentry\_rwlock \*lock, struct wolfentry\_thread\_context \*thread, [wolfentry\\_time\\_t](#) max\_wait, [wolfentry\\_lock\\_flags\\_t](#) flags)  
*Requests a shared lock with a relative timeout.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) **wolfentry\_lock\_mutex** (struct wolfentry\_rwlock \*lock, struct wolfentry\_thread\_context \*thread, [wolfentry\\_lock\\_flags\\_t](#) flags)  
*Requests an exclusive lock.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) **wolfentry\_lock\_mutex\_abstimed** (struct wolfentry\_rwlock \*lock, struct wolfentry\_thread\_context \*thread, const struct timespec \*abs\_timeout, [wolfentry\\_lock\\_flags\\_t](#) flags)  
*Requests an exclusive lock with an absolute timeout.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) **wolfentry\_lock\_mutex\_timed** (struct wolfentry\_rwlock \*lock, struct wolfentry\_thread\_context \*thread, [wolfentry\\_time\\_t](#) max\_wait, [wolfentry\\_lock\\_flags\\_t](#) flags)  
*Requests an exclusive lock with a relative timeout.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) **wolfentry\_lock\_mutex2shared** (struct wolfentry\_rwlock \*lock, struct wolfentry\_thread\_context \*thread, [wolfentry\\_lock\\_flags\\_t](#) flags)  
*Downgrade an exclusive lock to a shared lock.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) **wolfentry\_lock\_shared2mutex** (struct wolfentry\_rwlock \*lock, struct wolfentry\_thread\_context \*thread, [wolfentry\\_lock\\_flags\\_t](#) flags)  
*Upgrade a shared lock to an exclusive lock.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) **wolfentry\_lock\_shared2mutex\_abstimed** (struct wolfentry\_↵ rwlock \*lock, struct wolfentry\_thread\_context \*thread, const struct timespec \*abs\_timeout, [wolfentry\\_lock\\_flags\\_t](#) flags)  
*Attempt to upgrade a shared lock to an exclusive lock with an absolute timeout.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) **wolfentry\_lock\_shared2mutex\_timed** (struct wolfentry\_rwlock \*lock, struct wolfentry\_thread\_context \*thread, [wolfentry\\_time\\_t](#) max\_wait, [wolfentry\\_lock\\_flags\\_t](#) flags)  
*Attempt to upgrade a shared lock to an exclusive lock with a relative timeout.*



- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t wolfsentry\\_lock\\_shared2mutex\\_reserve](#) (struct wolfsentry\_rwlock \*lock, struct wolfsentry\_thread\_context \*thread, [wolfsentry\\_lock\\_flags\\_t](#) flags)  
*Attempt to reserve a upgrade of a shared lock to an exclusive lock.*
- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t wolfsentry\\_lock\\_shared2mutex\\_redeem](#) (struct wolfsentry\_rwlock \*lock, struct wolfsentry\_thread\_context \*thread, [wolfsentry\\_lock\\_flags\\_t](#) flags)  
*Redeem a reservation of a lock upgrade from shared to exclusive.*
- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t wolfsentry\\_lock\\_shared2mutex\\_redeem\\_abstimed](#) (struct wolfsentry\_rwlock \*lock, struct wolfsentry\_thread\_context \*thread, const struct timespec \*abs\_timeout, [wolfsentry\\_lock\\_flags\\_t](#) flags)  
*Redeem a reservation of a lock upgrade from shared to exclusive with an absolute timeout.*
- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t wolfsentry\\_lock\\_shared2mutex\\_redeem\\_timed](#) (struct wolfsentry\_rwlock \*lock, struct wolfsentry\_thread\_context \*thread, [wolfsentry\\_time\\_t](#) max\_wait, [wolfsentry\\_lock\\_flags\\_t](#) flags)  
*Redeem a reservation of a lock upgrade from shared to exclusive with a relative timeout.*
- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t wolfsentry\\_lock\\_shared2mutex\\_abandon](#) (struct wolfsentry\_rwlock \*lock, struct wolfsentry\_thread\_context \*thread, [wolfsentry\\_lock\\_flags\\_t](#) flags)  
*Abandon a reservation of a lock upgrade from shared to exclusive.*
- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t wolfsentry\\_lock\\_have\\_shared](#) (struct wolfsentry\_rwlock \*lock, struct wolfsentry\_thread\_context \*thread, [wolfsentry\\_lock\\_flags\\_t](#) flags)  
*Check if the lock is held in shared state.*
- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t wolfsentry\\_lock\\_have\\_mutex](#) (struct wolfsentry\_rwlock \*lock, struct wolfsentry\_thread\_context \*thread, [wolfsentry\\_lock\\_flags\\_t](#) flags)  
*Check if the lock is held in exclusive state.*
- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t wolfsentry\\_lock\\_have\\_either](#) (struct wolfsentry\_rwlock \*lock, struct wolfsentry\_thread\_context \*thread, [wolfsentry\\_lock\\_flags\\_t](#) flags)  
*Check if the lock is held in either shared or exclusive state.*
- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t wolfsentry\\_lock\\_have\\_shared2mutex\\_reservation](#) (struct wolfsentry\_rwlock \*lock, struct wolfsentry\_thread\_context \*thread, [wolfsentry\\_lock\\_flags\\_t](#) flags)  
*Check if an upgrade reservation is held on the lock.*
- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t wolfsentry\\_lock\\_get\\_flags](#) (struct wolfsentry\_rwlock \*lock, struct wolfsentry\_thread\_context \*thread, [wolfsentry\\_lock\\_flags\\_t](#) \*flags)  
*Extract the current flags from the lock.*
- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t wolfsentry\\_lock\\_unlock](#) (struct wolfsentry\_rwlock \*lock, struct wolfsentry\_thread\_context \*thread, [wolfsentry\\_lock\\_flags\\_t](#) flags)  
*Unlock a lock.*
- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t wolfsentry\\_lock\\_destroy](#) (struct wolfsentry\_rwlock \*lock, struct wolfsentry\_thread\_context \*thread, [wolfsentry\\_lock\\_flags\\_t](#) flags)  
*Destroy a lock that was created with [wolfsentry\\_lock\\_init\(\)](#)*
- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t wolfsentry\\_lock\\_free](#) (struct wolfsentry\_rwlock \*\*lock, struct wolfsentry\_thread\_context \*thread, [wolfsentry\\_lock\\_flags\\_t](#) flags)  
*Destroy and free a lock that was created with [wolfsentry\\_lock\\_alloc\(\)](#). The lock's pointer will also be set to NULL.*
- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t wolfsentry\\_time\\_now\\_plus\\_delta](#) (struct wolfsentry\_context \*wolfsentry, [wolfsentry\\_time\\_t](#) td, [wolfsentry\\_time\\_t](#) \*res)  
*Generate a [wolfsentry\\_time\\_t](#) at a given offset from current time.*
- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t wolfsentry\\_time\\_to\\_timespec](#) (struct wolfsentry\_context \*wolfsentry, [wolfsentry\\_time\\_t](#) t, struct timespec \*ts)  
*Convert a [wolfsentry\\_time\\_t](#) to a struct timespec.*
- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t wolfsentry\\_time\\_now\\_plus\\_delta\\_timespec](#) (struct wolfsentry\_context \*wolfsentry, [wolfsentry\\_time\\_t](#) td, struct timespec \*ts)  
*Generate a struct timespec at a given offset, supplied as [wolfsentry\\_time\\_t](#), from current time.*
- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t wolfsentry\\_get\\_time](#) (struct wolfsentry\_context \*wolfsentry, [wolfsentry\\_time\\_t](#) \*time\_p)  
*Get current time as [wolfsentry\\_time\\_t](#).*

- WOLFSENTRY\_API [wolfentry\\_time\\_t](#) **wolfentry\_diff\_time** (struct wolfentry\_context \*wolfentry, [wolfentry\\_time\\_t](#) later, [wolfentry\\_time\\_t](#) earlier)  
*Compute the interval between later and earlier, using [wolfentry\\_time\\_t](#).*
- WOLFSENTRY\_API [wolfentry\\_time\\_t](#) **wolfentry\_add\_time** (struct wolfentry\_context \*wolfentry, [wolfentry\\_time\\_t](#) start\_time, [wolfentry\\_time\\_t](#) time\_interval)  
*Compute the time time\_interval after start\_time, using [wolfentry\\_time\\_t](#).*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) **wolfentry\_to\_epoch\_time** (struct wolfentry\_context \*wolfentry, [wolfentry\\_time\\_t](#) when, time\_t \*epoch\_secs, long \*epoch\_nsecs)  
*Convert a [wolfentry\\_time\\_t](#) to seconds and nanoseconds since 1970-Jan-1 0:00 UTC.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) **wolfentry\_from\_epoch\_time** (struct wolfentry\_context \*wolfentry, time\_t epoch\_secs, long epoch\_nsecs, [wolfentry\\_time\\_t](#) \*when)  
*Convert seconds and nanoseconds since 1970-Jan-1 0:00 UTC to a [wolfentry\\_time\\_t](#).*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) **wolfentry\_interval\_to\_seconds** (struct wolfentry\_context \*wolfentry, [wolfentry\\_time\\_t](#) howlong, time\_t \*howlong\_secs, long \*howlong\_nsecs)  
*Convert an interval in [wolfentry\\_time\\_t](#) to seconds and nanoseconds.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) **wolfentry\_interval\_from\_seconds** (struct wolfentry\_context \*wolfentry, time\_t howlong\_secs, long howlong\_nsecs, [wolfentry\\_time\\_t](#) \*howlong)  
*Convert an interval in seconds and nanoseconds to [wolfentry\\_time\\_t](#).*
- WOLFSENTRY\_API struct [wolfentry\\_timecbs](#) \* **wolfentry\_get\_timecbs** (struct wolfentry\_context \*wolfentry)  
*Return the active time handlers from the supplied context.*
- WOLFSENTRY\_API void \* **wolfentry\_malloc** (WOLFSENTRY\_CONTEXT\_ARGS\_IN, size\_t size)  
*Allocate size bytes using the malloc configured in the wolfSentry context.*
- WOLFSENTRY\_API\_VOID **wolfentry\_free** (WOLFSENTRY\_CONTEXT\_ARGS\_IN, void \*ptr)  
*Free ptr using the free configured in the wolfSentry context.*
- WOLFSENTRY\_API void \* **wolfentry\_realloc** (WOLFSENTRY\_CONTEXT\_ARGS\_IN, void \*ptr, size\_t size)  
*Reallocate ptr to size bytes using the realloc configured in the wolfSentry context.*
- WOLFSENTRY\_API void \* **wolfentry\_memalign** (WOLFSENTRY\_CONTEXT\_ARGS\_IN, size\_t alignment, size\_t size)  
*Allocate size bytes, aligned to alignment, using the memalign configured in the wolfSentry context.*
- WOLFSENTRY\_API\_VOID **wolfentry\_free\_aligned** (WOLFSENTRY\_CONTEXT\_ARGS\_IN, void \*ptr)  
*Free ptr, previously allocated with [wolfentry\\_memalign\(\)](#), using the free\_aligned configured in the wolfSentry context.*
- WOLFSENTRY\_API int **\_wolfentry\_get\_n\_mallocs** (void)  
*In library builds with WOLFSENTRY\_MALLOC\_BUILTINS and WOLFSENTRY\_MALLOC\_DEBUG defined, this returns the net number of allocations performed as of time of call. I.e., it returns zero iff all allocations have been freed.*
- WOLFSENTRY\_API struct [wolfentry\\_allocator](#) \* **wolfentry\_get\_allocator** (struct wolfentry\_context \*wolfentry)  
*Return a pointer to the [wolfentry\\_allocator](#) associated with the supplied wolfentry\_context, mainly for passing to [json\\_init\(\)](#), [json\\_parse\(\)](#), [json\\_value\\_\\*](#)(), and [json\\_dom\\_\\*](#)().*
- WOLFSENTRY\_API const char \* **wolfentry\_action\_res\_assoc\_by\_flag** ([wolfentry\\_action\\_res\\_t](#) res, unsigned int bit)  
*Given a bit number (from 0 to 31), return the name of that bit if set in res, else return a null pointer.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) **wolfentry\_action\_res\_assoc\_by\_name** (const char \*bit\_name, size\_t bit\_name\_len, [wolfentry\\_action\\_res\\_t](#) \*res)  
*Given a bit\_name, set \*res to the corresponding bit number if known, failing which, return ITEM\_NOT\_FOUND.*
- WOLFSENTRY\_API struct [wolfentry\\_host\\_platform\\_interface](#) \* **wolfentry\_get\_hpi** (struct wolfentry\_context \*wolfentry)  
*Return a pointer to the [wolfentry\\_host\\_platform\\_interface](#) associated with the supplied wolfentry\_context, mainly for passing to [wolfentry\\_alloc\\_thread\\_context\(\)](#), [wolfentry\\_free\\_thread\\_context\(\)](#), [wolfentry\\_lock\\_init\(\)](#), and [wolfentry\\_lock\\_alloc\(\)](#).*



- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t](#) [wolfsentry\\_cleanup\\_push](#) ([WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#), [wolfsentry\\_cleanup\\_callback\\_t](#) handler, void \*arg)  
*Register handler to be called at shutdown with arg arg.*
- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t](#) [wolfsentry\\_cleanup\\_pop](#) ([WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#), int execute\_p)  
*Remove the most recently registered and unpoped handler from the cleanup stack, and if execute\_p is nonzero, call it with the arg with which it was registered.*
- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t](#) [wolfsentry\\_cleanup\\_all](#) ([WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#))  
*Iteratively call [wolfsentry\\_cleanup\\_pop\(\)](#), executing each handler as it is popped, passing it the arg with which it was registered.*
- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t](#) [wolfsentry\\_addr\\_family\\_handler\\_install](#) ([WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#), [wolfsentry\\_addr\\_family\\_t](#) family\_bynumber, const char \*family\_byname, int family\_byname\_len, [wolfsentry\\_addr\\_family\\_parser\\_t](#) parser, [wolfsentry\\_addr\\_family\\_formatter\\_t](#) formatter, int max\_addr\_bits)  
*Install handlers for an address family.*
- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t](#) [wolfsentry\\_addr\\_family\\_get\\_parser](#) ([WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#), [wolfsentry\\_addr\\_family\\_t](#) family, [wolfsentry\\_addr\\_family\\_parser\\_t](#) \*parser)  
*Retrieve the parsing handler for an address family.*
- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t](#) [wolfsentry\\_addr\\_family\\_get\\_formatter](#) ([WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#), [wolfsentry\\_addr\\_family\\_t](#) family, [wolfsentry\\_addr\\_family\\_formatter\\_t](#) \*formatter)  
*Retrieve the formatting handler for an address family.*
- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t](#) [wolfsentry\\_addr\\_family\\_handler\\_remove\\_bynumber](#) ([WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#), [wolfsentry\\_addr\\_family\\_t](#) family\_bynumber, [wolfsentry\\_action\\_res\\_t](#) \*action\_results)  
*Remove the handlers for an address family.*
- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t](#) [wolfsentry\\_addr\\_family\\_drop\\_reference](#) ([WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#), struct [wolfsentry\\_addr\\_family\\_bynumber](#) \*family\_bynumber, [wolfsentry\\_action\\_res\\_t](#) \*action\_results)  
*Release an address family record previously returned by [wolfsentry\\_addr\\_family\\_ntop\(\)](#)*
- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t](#) [wolfsentry\\_addr\\_family\\_handler\\_remove\\_byname](#) ([WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#), const char \*family\_byname, int family\_byname\_len, [wolfsentry\\_action\\_res\\_t](#) \*action\_results)  
*Remove the handlers for an address family.*
- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t](#) [wolfsentry\\_addr\\_family\\_pton](#) ([WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#), const char \*family\_name, int family\_name\_len, [wolfsentry\\_addr\\_family\\_t](#) \*family\_number)  
*Look up an address family by name, returning its number.*
- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t](#) [wolfsentry\\_addr\\_family\\_ntop](#) ([WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#), [wolfsentry\\_addr\\_family\\_t](#) family, struct [wolfsentry\\_addr\\_family\\_bynumber](#) \*\*addr\_family, const char \*\*family\_name)  
*Look up an address family by number, returning a pointer to its name. The caller must release `addr_family`, using [wolfsentry\\_addr\\_family\\_drop\\_reference\(\)](#), when done accessing `family_name`.*
- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t](#) [wolfsentry\\_addr\\_family\\_max\\_addr\\_bits](#) ([WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#), [wolfsentry\\_addr\\_family\\_t](#) family, [wolfsentry\\_addr\\_bits\\_t](#) \*bits)  
*Look up the max address size for an address family identified by number.*
- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t](#) [wolfsentry\\_eventconfig\\_init](#) (struct [wolfsentry\\_context](#) \*wolfsentry, struct [wolfsentry\\_eventconfig](#) \*config)  
*Initializes a [wolfsentry\\_eventconfig](#) struct with the defaults from the wolfsentry context. If no wolfsentry context is provided this will initialize to zero.*
- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t](#) [wolfsentry\\_eventconfig\\_check](#) (const struct [wolfsentry\\_eventconfig](#) \*config)  
*Checks the config for self-consistency and validity.*
- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t](#) [wolfsentry\\_init\\_ex](#) (struct [wolfsentry\\_build\\_settings](#) caller\_build\_settings, [WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN\\_EX](#)(const struct [wolfsentry\\_host\\_platform\\_interface](#) \*hpi), const struct [wolfsentry\\_eventconfig](#) \*config, struct [wolfsentry\\_context](#) \*\*wolfsentry, [wolfsentry\\_init\\_flags\\_t](#) flags)  
*Variant of [wolfsentry\\_init\(\)](#) that accepts a `flags` argument, for additional control over configuration.*
- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t](#) [wolfsentry\\_init](#) (struct [wolfsentry\\_build\\_settings](#) caller\_build\_settings, [WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN\\_EX](#)(const struct [wolfsentry\\_host\\_platform\\_interface](#) \*hpi), const struct [wolfsentry\\_eventconfig](#) \*config, struct [wolfsentry\\_context](#) \*\*wolfsentry)

- Allocates and initializes the wolfsentry context.*
- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t wolfsentry\\_defaultconfig\\_get](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, struct [wolfsentry\\_eventconfig](#) \*config)  
*Get the default config from a wolfsentry context.*
  - WOLFSENTRY\_API [wolfsentry\\_errcode\\_t wolfsentry\\_defaultconfig\\_update](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const struct [wolfsentry\\_eventconfig](#) \*config)  
*Updates mutable fields of the default config (all but [wolfsentry\\_eventconfig::route\\_private\\_data\\_size](#) and [wolfsentry\\_eventconfig::route\\_private\\_data\\_alignment](#))*
  - WOLFSENTRY\_API [wolfsentry\\_errcode\\_t wolfsentry\\_context\\_flush](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN)  
*Flushes the route, event, and user value tables from the wolfsentry context.*
  - WOLFSENTRY\_API [wolfsentry\\_errcode\\_t wolfsentry\\_context\\_free](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN\_EX(struct wolfsentry\_context \*\*wolfsentry))  
*Frees the wolfsentry context and the tables within it. The wolfsentry context will be a pointer to NULL upon success.*
  - WOLFSENTRY\_API [wolfsentry\\_errcode\\_t wolfsentry\\_shutdown](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN\_EX(struct wolfsentry\_context \*\*wolfsentry))  
*Shut down wolfSentry, freeing all resources. Gets an exclusive lock on the context, then calls [wolfsentry\\_context\\_free\(\)](#).*
  - WOLFSENTRY\_API [wolfsentry\\_errcode\\_t wolfsentry\\_context\\_inhibit\\_actions](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN)  
*Disable automatic dispatch of actions on the wolfsentry context.*
  - WOLFSENTRY\_API [wolfsentry\\_errcode\\_t wolfsentry\\_context\\_enable\\_actions](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN)  
*Re-enable automatic dispatch of actions on the wolfsentry context.*
  - WOLFSENTRY\_API [wolfsentry\\_errcode\\_t wolfsentry\\_context\\_clone](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, struct wolfsentry\_context \*\*clone, [wolfsentry\\_clone\\_flags\\_t](#) flags)  
*Clones a wolfsentry context.*
  - WOLFSENTRY\_API [wolfsentry\\_errcode\\_t wolfsentry\\_context\\_exchange](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, struct wolfsentry\_context \*wolfsentry2)  
*Swaps information between two wolfsentry contexts.*
  - WOLFSENTRY\_API [wolfsentry\\_errcode\\_t wolfsentry\\_context\\_lock\\_mutex](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN)  
*Calls [wolfsentry\\_lock\\_mutex\(\)](#) on the context.*
  - WOLFSENTRY\_API [wolfsentry\\_errcode\\_t wolfsentry\\_context\\_lock\\_mutex\\_abstimed](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const struct timespec \*abs\_timeout)  
*Calls [wolfsentry\\_lock\\_mutex\\_abstimed\(\)](#) on the context.*
  - WOLFSENTRY\_API [wolfsentry\\_errcode\\_t wolfsentry\\_context\\_lock\\_mutex\\_abstimed\\_ex](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const struct timespec \*abs\_timeout, [wolfsentry\\_lock\\_flags\\_t](#) flags)  
*variant of [wolfsentry\\_context\\_lock\\_mutex\\_abstimed\(\)](#) with a *flags* arg.*
  - WOLFSENTRY\_API [wolfsentry\\_errcode\\_t wolfsentry\\_context\\_lock\\_mutex\\_timed](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, [wolfsentry\\_time\\_t](#) max\_wait)  
*Calls [wolfsentry\\_lock\\_mutex\\_timed\(\)](#) on the context.*
  - WOLFSENTRY\_API [wolfsentry\\_errcode\\_t wolfsentry\\_context\\_lock\\_mutex\\_timed\\_ex](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, [wolfsentry\\_time\\_t](#) max\_wait, [wolfsentry\\_lock\\_flags\\_t](#) flags)  
*variant of [wolfsentry\\_context\\_lock\\_mutex\\_timed\(\)](#) with a *flags* arg.*
  - WOLFSENTRY\_API [wolfsentry\\_errcode\\_t wolfsentry\\_context\\_lock\\_shared](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN)  
*Calls [wolfsentry\\_lock\\_shared\(\)](#) on the context.*
  - WOLFSENTRY\_API [wolfsentry\\_errcode\\_t wolfsentry\\_context\\_lock\\_shared\\_abstimed](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const struct timespec \*abs\_timeout)  
*Calls [wolfsentry\\_lock\\_shared\\_abstimed\(\)](#) on the context.*
  - WOLFSENTRY\_API [wolfsentry\\_errcode\\_t wolfsentry\\_context\\_lock\\_shared\\_with\\_reservation\\_abstimed](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const struct timespec \*abs\_timeout)  
*Calls [wolfsentry\\_lock\\_shared\\_abstimed\(\)](#) on the context, with the [WOLFSENTRY\\_LOCK\\_FLAG\\_GET\\_↔RESERVATION\\_TOO](#) flag.*
  - WOLFSENTRY\_API [wolfsentry\\_errcode\\_t wolfsentry\\_context\\_lock\\_shared\\_timed](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, [wolfsentry\\_time\\_t](#) max\_wait)  
*Calls [wolfsentry\\_lock\\_shared\\_timed\(\)](#) on the context.*

- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t](#) [wolfsentry\\_context\\_lock\\_shared\\_with\\_reservation\\_timed](#) ([WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#), [wolfsentry\\_time\\_t](#) max\_wait)  
Calls [wolfsentry\\_lock\\_shared\\_timed\(\)](#) on the context, with the [WOLFSENTRY\\_LOCK\\_FLAG\\_GET\\_RESERVATION](#)↔  
\_TOO flag.
- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t](#) [wolfsentry\\_context\\_unlock](#) ([WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#))  
Calls [wolfsentry\\_lock\\_unlock\(\)](#) on the context.
- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t](#) [wolfsentry\\_context\\_unlock\\_and\\_abandon\\_reservation](#) ([WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#))  
Calls [wolfsentry\\_lock\\_unlock\(\)](#) on the context, with the [WOLFSENTRY\\_LOCK\\_FLAG\\_ABANDON\\_RESERVATION](#)↔  
\_TOO flag.
- WOLFSENTRY\_API [wolfsentry\\_object\\_type\\_t](#) [wolfsentry\\_get\\_object\\_type](#) (const void \*object)  
Get the object type from a wolfsentry object pointer.
- WOLFSENTRY\_API [wolfsentry\\_ent\\_id\\_t](#) [wolfsentry\\_get\\_object\\_id](#) (const void \*object)  
Get the ID from a wolfsentry object pointer.
- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t](#) [wolfsentry\\_table\\_ent\\_get\\_by\\_id](#) ([WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#), [wolfsentry\\_ent\\_id\\_t](#) id, struct wolfsentry\_table\_header \*\*ent)  
Retrieve an object pointer given its ID. Lock must be obtained before entry, and ent is only valid while lock is held, or if [wolfsentry\\_object\\_checkout\(\)](#) is called for the object.
- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t](#) [wolfsentry\\_object\\_checkout](#) ([WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#), void \*object)  
Increment the refcount for an object, making it safe from deallocation until [wolfsentry\\_object\\_release\(\)](#). Caller must have a context lock on entry.
- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t](#) [wolfsentry\\_object\\_release](#) ([WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#), void \*object, [wolfsentry\\_action\\_res\\_t](#) \*action\_results)  
Decrement the refcount for an object, deallocating it if no references remain. Caller does not need to have a context lock on entry.
- WOLFSENTRY\_API [wolfsentry\\_hitcount\\_t](#) [wolfsentry\\_table\\_n\\_inserts](#) (struct wolfsentry\_table\_header \*table)  
Get the number of inserts into a table.
- WOLFSENTRY\_API [wolfsentry\\_hitcount\\_t](#) [wolfsentry\\_table\\_n\\_deletes](#) (struct wolfsentry\_table\_header \*table)  
Get the number of deletes from a table.
- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t](#) [wolfsentry\\_route\\_check\\_flags\\_sensical](#) ([wolfsentry\\_route\\_flags\\_t](#) flags)  
Check the self-consistency of flags.
- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t](#) [wolfsentry\\_route\\_insert\\_into\\_table](#) ([WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#), struct wolfsentry\_route\_table \*route\_table, void \*caller\_arg, const struct [wolfsentry\\_sockaddr](#) \*remote, const struct [wolfsentry\\_sockaddr](#) \*local, [wolfsentry\\_route\\_flags\\_t](#) flags, const char \*event\_label, int event\_label↔\_len, [wolfsentry\\_ent\\_id\\_t](#) \*id, [wolfsentry\\_action\\_res\\_t](#) \*action\_results)  
Variant of [wolfsentry\\_route\\_insert\(\)](#) that takes an explicit route\_table.
- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t](#) [wolfsentry\\_route\\_insert\\_by\\_exports\\_into\\_table](#) ([WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#), struct wolfsentry\_route\_table \*route\_table, void \*caller\_arg, const struct [wolfsentry\\_route\\_exports](#) \*route↔\_exports, [wolfsentry\\_ent\\_id\\_t](#) \*id, [wolfsentry\\_action\\_res\\_t](#) \*action\_results)  
Variant of [wolfsentry\\_route\\_insert\(\)](#) that accepts the new route as [wolfsentry\\_route\\_exports](#), and takes an explicit route\_table.
- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t](#) [wolfsentry\\_route\\_insert](#) ([WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#), void \*caller\_arg, const struct [wolfsentry\\_sockaddr](#) \*remote, const struct [wolfsentry\\_sockaddr](#) \*local, [wolfsentry\\_route\\_flags\\_t](#) flags, const char \*event\_label, int event\_label\_len, [wolfsentry\\_ent\\_id\\_t](#) \*id, [wolfsentry\\_action\\_res\\_t](#) \*action\_results)  
Insert a route into the route table.
- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t](#) [wolfsentry\\_route\\_insert\\_by\\_exports](#) ([WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#), void \*caller\_arg, const struct [wolfsentry\\_route\\_exports](#) \*route\_exports, [wolfsentry\\_ent\\_id\\_t](#) \*id, [wolfsentry\\_action\\_res\\_t](#) \*action\_results)  
Variant of [wolfsentry\\_route\\_insert\(\)](#) that accepts the new route as [wolfsentry\\_route\\_exports](#).

- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_route\\_insert\\_into\\_table\\_and\\_check\\_out](#) ([WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#), struct [wolfentry\\_route\\_table](#) \*route\_table, void \*caller\_arg, const struct [wolfentry\\_sockaddr](#) \*remote, const struct [wolfentry\\_sockaddr](#) \*local, [wolfentry\\_route\\_flags\\_t](#) flags, const char \*event\_label, int event\_label\_len, struct [wolfentry\\_route](#) \*\*route, [wolfentry\\_action\\_res\\_t](#) \*action\_results)  
 Variant of [wolfentry\\_route\\_insert\(\)](#) that takes an explicit *route\_table*, and returns the inserted route, which the caller must eventually drop using [wolfentry\\_route\\_drop\\_reference\(\)](#) or [wolfentry\\_object\\_release\(\)](#)
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_route\\_insert\\_by\\_exports\\_into\\_table\\_and\\_check\\_out](#) ([WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#), struct [wolfentry\\_route\\_table](#) \*route\_table, void \*caller\_arg, const struct [wolfentry\\_route\\_exports](#) \*route\_exports, struct [wolfentry\\_route](#) \*\*route, [wolfentry\\_action\\_res\\_t](#) \*action\_results)  
 Variant of [wolfentry\\_route\\_insert\(\)](#) that accepts the new route as [wolfentry\\_route\\_exports](#), takes an explicit *route\_table*, and returns the inserted route, which the caller must eventually drop using [wolfentry\\_route\\_drop\\_reference\(\)](#) or [wolfentry\\_object\\_release\(\)](#)
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_route\\_insert\\_and\\_check\\_out](#) ([WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#), void \*caller\_arg, const struct [wolfentry\\_sockaddr](#) \*remote, const struct [wolfentry\\_sockaddr](#) \*local, [wolfentry\\_route\\_flags\\_t](#) flags, const char \*event\_label, int event\_label\_len, struct [wolfentry\\_route](#) \*\*route, [wolfentry\\_action\\_res\\_t](#) \*action\_results)  
 Variant of [wolfentry\\_route\\_insert\(\)](#) that returns the inserted route, which the caller must eventually drop using [wolfentry\\_route\\_drop\\_reference\(\)](#) or [wolfentry\\_object\\_release\(\)](#)
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_route\\_insert\\_by\\_exports\\_and\\_check\\_out](#) ([WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#), void \*caller\_arg, const struct [wolfentry\\_route\\_exports](#) \*route\_exports, struct [wolfentry\\_route](#) \*\*route, [wolfentry\\_action\\_res\\_t](#) \*action\_results)  
 Variant of [wolfentry\\_route\\_insert\(\)](#) that accepts the new route as [wolfentry\\_route\\_exports](#) and returns the inserted route, which the caller must eventually drop using [wolfentry\\_route\\_drop\\_reference\(\)](#) or [wolfentry\\_object\\_release\(\)](#)
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_route\\_delete\\_from\\_table](#) ([WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#), struct [wolfentry\\_route\\_table](#) \*route\_table, void \*caller\_arg, const struct [wolfentry\\_sockaddr](#) \*remote, const struct [wolfentry\\_sockaddr](#) \*local, [wolfentry\\_route\\_flags\\_t](#) flags, const char \*event\_label, int event\_label\_len, [wolfentry\\_action\\_res\\_t](#) \*action\_results, int \*n\_deleted)  
 Variant of [wolfentry\\_route\\_delete\(\)](#) that takes an explicit *route\_table*.
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_route\\_delete](#) ([WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#), void \*caller\_arg, const struct [wolfentry\\_sockaddr](#) \*remote, const struct [wolfentry\\_sockaddr](#) \*local, [wolfentry\\_route\\_flags\\_t](#) flags, const char \*trigger\_label, int trigger\_label\_len, [wolfentry\\_action\\_res\\_t](#) \*action\_results, int \*n\_deleted)  
 Delete route from the route table. The supplied parameters, including the flags, must match the route exactly, else *ITEM\_NOT\_FOUND* will result. To avoid fidgety parameter matching, use [wolfentry\\_route\\_delete\\_by\\_id\(\)](#). The supplied trigger event, if any, is passed to action handlers, and has no bearing on route matching.
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_route\\_delete\\_by\\_id](#) ([WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#), void \*caller\_arg, [wolfentry\\_ent\\_id\\_t](#) id, const char \*trigger\_label, int trigger\_label\_len, [wolfentry\\_action\\_res\\_t](#) \*action\_results)  
 Delete a route from its route table using its ID. The supplied trigger event, if any, is passed to action handlers, and has no bearing on route matching.
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_route\\_get\\_main\\_table](#) ([WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#), struct [wolfentry\\_route\\_table](#) \*\*table)  
 Get a pointer to the internal route table. Caller must have a lock on the context at entry.
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_route\\_table\\_iterate\\_start](#) ([WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#), const struct [wolfentry\\_route\\_table](#) \*table, struct [wolfentry\\_cursor](#) \*\*cursor)  
 Open a cursor to iterate through a routes table. Caller must have a lock on the context at entry.
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_route\\_table\\_iterate\\_seek\\_to\\_head](#) (const struct [wolfentry\\_route\\_table](#) \*table, struct [wolfentry\\_cursor](#) \*cursor)  
 Reset the cursor to the beginning of a table.
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_route\\_table\\_iterate\\_seek\\_to\\_tail](#) (const struct [wolfentry\\_route\\_table](#) \*table, struct [wolfentry\\_cursor](#) \*cursor)  
 Move the cursor to the end of a table.
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_route\\_table\\_iterate\\_current](#) (const struct [wolfentry\\_route\\_table](#) \*table, struct [wolfentry\\_cursor](#) \*cursor, struct [wolfentry\\_route](#) \*\*route)

*Get the current position for the table cursor.*

- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t](#) [wolfsentry\\_route\\_table\\_iterate\\_prev](#) (const struct wolfsentry\_route\_table \*table, struct wolfsentry\_cursor \*cursor, struct wolfsentry\_route \*\*route)

*Get the previous position for the table cursor.*

- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t](#) [wolfsentry\\_route\\_table\\_iterate\\_next](#) (const struct wolfsentry\_route\_table \*table, struct wolfsentry\_cursor \*cursor, struct wolfsentry\_route \*\*route)

*Get the next position for the table cursor.*

- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t](#) [wolfsentry\\_route\\_table\\_iterate\\_end](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const struct wolfsentry\_route\_table \*table, struct wolfsentry\_cursor \*\*cursor)

*Frees the table cursor. Caller must have a lock on the context at entry.*

- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t](#) [wolfsentry\\_route\\_table\\_default\\_policy\\_set](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, struct wolfsentry\_route\_table \*table, [wolfsentry\\_action\\_res\\_t](#) default\_policy)

*Set a table's default policy.*

- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t](#) [wolfsentry\\_route\\_default\\_policy\\_set](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, [wolfsentry\\_action\\_res\\_t](#) default\_policy)

*variant of [wolfsentry\\_route\\_table\\_default\\_policy\\_set\(\)](#) that uses the main route table implicitly, and takes care of context locking.*

- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t](#) [wolfsentry\\_route\\_table\\_default\\_policy\\_get](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, struct wolfsentry\_route\_table \*table, [wolfsentry\\_action\\_res\\_t](#) \*default\_policy)

*Get a table's default policy. Caller must have a lock on the context at entry.*

- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t](#) [wolfsentry\\_route\\_default\\_policy\\_get](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, [wolfsentry\\_action\\_res\\_t](#) \*default\_policy)

*variant of [wolfsentry\\_route\\_table\\_default\\_policy\\_get\(\)](#) that uses the main route table implicitly. Caller must have a lock on the context at entry.*

- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t](#) [wolfsentry\\_route\\_get\\_reference](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const struct wolfsentry\_route\_table \*table, const struct [wolfsentry\\_sockaddr](#) \*remote, const struct [wolfsentry\\_sockaddr](#) \*local, [wolfsentry\\_route\\_flags\\_t](#) flags, const char \*event\_label, int event\_label\_len, int exact\_p, [wolfsentry\\_route\\_flags\\_t](#) \*inexact\_matches, struct wolfsentry\_route \*\*route)

*Increments a reference counter for a route.*

- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t](#) [wolfsentry\\_route\\_drop\\_reference](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, struct wolfsentry\_route \*route, [wolfsentry\\_action\\_res\\_t](#) \*action\_results)

*Decrease a reference counter for a route.*

- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t](#) [wolfsentry\\_route\\_table\\_clear\\_default\\_event](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, struct wolfsentry\_route\_table \*table)

*Clear an event previously set by [wolfsentry\\_route\\_table\\_set\\_default\\_event\(\)](#).*

- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t](#) [wolfsentry\\_route\\_table\\_set\\_default\\_event](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, struct wolfsentry\_route\_table \*table, const char \*event\_label, int event\_label\_len)

*Set an event to be used as a foster parent event for routes with no parent event of their own.*

- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t](#) [wolfsentry\\_route\\_table\\_get\\_default\\_event](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, struct wolfsentry\_route\_table \*table, char \*event\_label, int \*event\_label\_len)

*Get the event, if any, set by [wolfsentry\\_route\\_table\\_set\\_default\\_event\(\)](#)*

- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t](#) [wolfsentry\\_route\\_table\\_fallthrough\\_route\\_get](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, struct wolfsentry\_route\_table \*route\_table, const struct wolfsentry\_route \*\*fallthrough\_route)

*Retrieve the default route in a route table, chiefly to pass to [wolfsentry\\_route\\_update\\_flags\(\)](#).*

- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t](#) [wolfsentry\\_route\\_get\\_addrs](#) (const struct wolfsentry\_route \*route, [wolfsentry\\_addr\\_family\\_t](#) \*af, [wolfsentry\\_addr\\_bits\\_t](#) \*local\_addr\_len, const [byte](#) \*\*local\_addr, [wolfsentry\\_addr\\_bits\\_t](#) \*remote\_addr\_len, const [byte](#) \*\*remote\_addr)

*Extract numeric address family and binary address pointers from a [wolfsentry\\_route](#)*

- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t](#) [wolfsentry\\_route\\_export](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const struct wolfsentry\_route \*route, struct [wolfsentry\\_route\\_exports](#) \*route\_exports)

*Exports a route.*

- WOLFSENTRY\_API const struct wolfsentry\_event \* [wolfsentry\\_route\\_parent\\_event](#) (const struct wolfsentry\_route \*route)



Get a parent event from a given route. Typically used in the `wolfentry_action_callback_t` callback. Note: returned `wolfentry_event` remains valid only as long as the `wolfentry` lock is held (shared or exclusive).

- WOLFENTRY\_API `wolfentry_errcode_t wolfentry_route_event_dispatch_with_table` (WOLFENTRY\_CONTEXT\_ARGS\_IN, struct `wolfentry_route_table` \*route\_table, const struct `wolfentry_sockaddr` \*remote, const struct `wolfentry_sockaddr` \*local, `wolfentry_route_flags_t` flags, const char \*event\_label, int event\_label\_len, void \*caller\_arg, `wolfentry_ent_id_t` \*id, `wolfentry_route_flags_t` \*inexact\_matches, `wolfentry_action_res_t` \*action\_results)

Variant of `wolfentry_route_event_dispatch()` that accepts an explicit `route_table`.

- WOLFENTRY\_API `wolfentry_errcode_t wolfentry_route_event_dispatch` (WOLFENTRY\_CONTEXT\_ARGS\_IN, const struct `wolfentry_sockaddr` \*remote, const struct `wolfentry_sockaddr` \*local, `wolfentry_route_flags_t` flags, const char \*event\_label, int event\_label\_len, void \*caller\_arg, `wolfentry_ent_id_t` \*id, `wolfentry_route_flags_t` \*inexact\_matches, `wolfentry_action_res_t` \*action\_results)

Submit an event into `wolfentry` and pass it through the filters. The `action_results` are cleared on entry, and can be checked to see what actions `wolfentry` took, and what actions the caller should take (most saliently, `WOLFENTRY_ACTION_RES_ACCEPT` or `WOLFENTRY_ACTION_RES_REJECT`). `action_results` can be filtered with constructs like `WOLFENTRY_MASKIN_BITS(action_results, WOLFENTRY_ACTION_RES_REJECT)`

- WOLFENTRY\_API `wolfentry_errcode_t wolfentry_route_event_dispatch_with_table_with_initiated_result` (WOLFENTRY\_CONTEXT\_ARGS\_IN, struct `wolfentry_route_table` \*route\_table, const struct `wolfentry_sockaddr` \*remote, const struct `wolfentry_sockaddr` \*local, `wolfentry_route_flags_t` flags, const char \*event\_label, int event\_label\_len, void \*caller\_arg, `wolfentry_ent_id_t` \*id, `wolfentry_route_flags_t` \*inexact\_matches, `wolfentry_action_res_t` \*action\_results)

Variant of `wolfentry_route_event_dispatch()` that accepts an explicit `route_table`, and doesn't clear `action_results` on entry.

- WOLFENTRY\_API `wolfentry_errcode_t wolfentry_route_event_dispatch_with_initiated_result` (WOLFENTRY\_CONTEXT\_ARGS\_IN, const struct `wolfentry_sockaddr` \*remote, const struct `wolfentry_sockaddr` \*local, `wolfentry_route_flags_t` flags, const char \*event\_label, int event\_label\_len, void \*caller\_arg, `wolfentry_ent_id_t` \*id, `wolfentry_route_flags_t` \*inexact\_matches, `wolfentry_action_res_t` \*action\_results)

Variant of `wolfentry_route_event_dispatch()` that doesn't clear `action_results` on entry.

- WOLFENTRY\_API `wolfentry_errcode_t wolfentry_route_event_dispatch_by_id` (WOLFENTRY\_CONTEXT\_ARGS\_IN, `wolfentry_ent_id_t` id, const char \*event\_label, int event\_label\_len, void \*caller\_arg, `wolfentry_action_res_t` \*action\_results)

Variant of `wolfentry_route_event_dispatch()` that preselects the matched route by ID, mainly for use by application code that tracks ID/session relationships.

- WOLFENTRY\_API `wolfentry_errcode_t wolfentry_route_event_dispatch_by_id_with_initiated_result` (WOLFENTRY\_CONTEXT\_ARGS\_IN, `wolfentry_ent_id_t` id, const char \*event\_label, int event\_label\_len, void \*caller\_arg, `wolfentry_action_res_t` \*action\_results)

Variant of `wolfentry_route_event_dispatch()` that preselects the matched route by ID, and doesn't clear `action_results` on entry, mainly for use by application code that tracks ID/session relationships.

- WOLFENTRY\_API `wolfentry_errcode_t wolfentry_route_event_dispatch_by_route` (WOLFENTRY\_CONTEXT\_ARGS\_IN, struct `wolfentry_route` \*route, const char \*event\_label, int event\_label\_len, void \*caller\_arg, `wolfentry_action_res_t` \*action\_results)

Variant of `wolfentry_route_event_dispatch()` that preselects the matched route by ID, mainly for use by application code that tracks route/session relationships.

- WOLFENTRY\_API `wolfentry_errcode_t wolfentry_route_event_dispatch_by_route_with_initiated_result` (WOLFENTRY\_CONTEXT\_ARGS\_IN, struct `wolfentry_route` \*route, const char \*event\_label, int event\_label\_len, void \*caller\_arg, `wolfentry_action_res_t` \*action\_results)

Variant of `wolfentry_route_event_dispatch()` that preselects the matched route by ID, and doesn't clear `action_results` on entry, mainly for use by application code that tracks route/session relationships.

- WOLFENTRY\_API `wolfentry_errcode_t wolfentry_route_table_max_purgeable_routes_get` (WOLFENTRY\_CONTEXT\_ARGS\_IN, struct `wolfentry_route_table` \*table, `wolfentry_hitcount_t` \*max\_purgeable\_routes)

Retrieve the current limit for ephemeral routes in `table`. Caller must have a lock on the context at entry.

- WOLFENTRY\_API `wolfentry_errcode_t wolfentry_route_table_max_purgeable_routes_set` (WOLFENTRY\_CONTEXT\_ARGS\_IN, struct `wolfentry_route_table` \*table, `wolfentry_hitcount_t` max\_purgeable\_routes)

Set the limit for ephemeral routes in `table`. Caller must have a mutex on the context at entry.

- WOLFENTRY\_API `wolfentry_errcode_t wolfentry_route_table_max_purgeable_idle_time_get` (WOLFENTRY\_CONTEXT\_ARGS\_IN, struct `wolfentry_route_table` \*table, `wolfentry_time_t` \*max\_purgeable\_idle\_time)

- Retrieve the current absolute maximum idle time for a purgeable route (controls forced purges of routes with nonzero [wolfentry\\_route\\_metadata\\_exports.connection\\_count](#)). Caller must have a lock on the context at entry.
- WOLFENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_route\\_table\\_max\\_purgeable\\_idle\\_time\\_set](#) (WOLFENTRY\_CONTEXT\_ARGS\_IN, struct [wolfentry\\_route\\_table](#) \*table, [wolfentry\\_time\\_t](#) max\_purgeable\_idle\_time)

Set the maximum idle time for a purgeable route (controls forced purges of routes with nonzero [wolfentry\\_route\\_metadata\\_exports.connection\\_count](#)). Default is no limit. Caller must have a mutex on the context at entry.

  - WOLFENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_route\\_purge\\_time\\_set](#) (WOLFENTRY\_CONTEXT\_ARGS\_IN, struct [wolfentry\\_route](#) \*route, [wolfentry\\_time\\_t](#) purge\_after)

Set the time after which *route* in *table* is to be subject to automatic purge. 0 sets the route as persistent. Caller must have a mutex on the context at entry.

  - WOLFENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_route\\_stale\\_purge](#) (WOLFENTRY\_CONTEXT\_ARGS\_IN, struct [wolfentry\\_route\\_table](#) \*table, [wolfentry\\_action\\_res\\_t](#) \*action\_results)

Purges all stale (expired) routes from *table*.

  - WOLFENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_route\\_stale\\_purge\\_one](#) (WOLFENTRY\_CONTEXT\_ARGS\_IN, struct [wolfentry\\_route\\_table](#) \*table, [wolfentry\\_action\\_res\\_t](#) \*action\_results)

Variant of [wolfentry\\_route\\_stale\\_purge\(\)](#) that purges at most one stale route, to limit time spent working.

  - WOLFENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_route\\_stale\\_purge\\_one\\_opportunistically](#) (WOLFENTRY\_CONTEXT\_ARGS\_IN, struct [wolfentry\\_route\\_table](#) \*table, [wolfentry\\_action\\_res\\_t](#) \*action\_results)

Variant of [wolfentry\\_route\\_stale\\_purge\(\)](#) that purges at most one stale route, and only if the context lock is uncontended.

  - WOLFENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_route\\_flush\\_table](#) (WOLFENTRY\_CONTEXT\_ARGS\_IN, struct [wolfentry\\_route\\_table](#) \*table, [wolfentry\\_action\\_res\\_t](#) \*action\_results)

Flush routes from a given table.

  - WOLFENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_route\\_bulk\\_clear\\_insert\\_action\\_status](#) (WOLFENTRY\_CONTEXT\_ARGS\_IN, [wolfentry\\_action\\_res\\_t](#) \*action\_results)

Clears the [WOLFENTRY\\_ROUTE\\_FLAG\\_INSERT\\_ACTIONS\\_CALLED](#) flag on all routes in the table.

  - WOLFENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_route\\_bulk\\_insert\\_actions](#) (WOLFENTRY\_CONTEXT\_ARGS\_IN, [wolfentry\\_action\\_res\\_t](#) \*action\_results)

Executes the insert actions for all routes in the table that don't have [WOLFENTRY\\_ROUTE\\_FLAG\\_INSERT\\_ACTIONS\\_CALLED](#) set.

  - WOLFENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_route\\_get\\_private\\_data](#) (WOLFENTRY\_CONTEXT\_ARGS\_IN, struct [wolfentry\\_route](#) \*route, void \*\*private\_data, size\_t \*private\_data\_size)

Gets the private data for a given route.

  - WOLFENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_route\\_get\\_flags](#) (const struct [wolfentry\\_route](#) \*route, [wolfentry\\_route\\_flags\\_t](#) \*flags)

Gets the flags for a route.

  - WOLFENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_route\\_get\\_metadata](#) (const struct [wolfentry\\_route](#) \*route, struct [wolfentry\\_route\\_metadata\\_exports](#) \*metadata)

Gets the metadata for a route.

  - WOLFENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_route\\_reset\\_metadata\\_exports](#) (struct [wolfentry\\_route\\_exports](#) \*route\_exports)

clear metadata counts ([wolfentry\\_route\\_metadata\\_exports::purge\\_after](#), [wolfentry\\_route\\_metadata\\_exports::connection\\_count](#), [wolfentry\\_route\\_metadata\\_exports::derogatory\\_count](#), and [wolfentry\\_route\\_metadata\\_exports::commendable\\_count](#)) in [wolfentry\\_route\\_exports](#) to prepare for use with [wolfentry\\_route\\_insert\\_by\\_exports\(\)](#)

  - WOLFENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_route\\_update\\_flags](#) (WOLFENTRY\_CONTEXT\_ARGS\_IN, struct [wolfentry\\_route](#) \*route, [wolfentry\\_route\\_flags\\_t](#) flags\_to\_set, [wolfentry\\_route\\_flags\\_t](#) flags\_to\_clear, [wolfentry\\_route\\_flags\\_t](#) \*flags\_before, [wolfentry\\_route\\_flags\\_t](#) \*flags\_after, [wolfentry\\_action\\_res\\_t](#) \*action\_results)

Update the route flags.

  - WOLFENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_route\\_increment\\_derogatory\\_count](#) (WOLFENTRY\_CONTEXT\_ARGS\_IN, struct [wolfentry\\_route](#) \*route, int count\_to\_add, int \*new\_derogatory\_count\_ptr)

Increase the derogatory event count of a route.

- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_route\\_increment\\_commendable\\_count](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, struct [wolfentry\\_route](#) \*route, int count\_to\_add, int \*new\_commendable\_count)  
*Increase the commendable event count of a route.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_route\\_reset\\_derogatory\\_count](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, struct [wolfentry\\_route](#) \*route, int \*old\_derogatory\_count\_ptr)  
*Reset the derogatory event count of a route.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_route\\_reset\\_commendable\\_count](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, struct [wolfentry\\_route](#) \*route, int \*old\_commendable\_count\_ptr)  
*Reset the commendable event count of a route.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_route\\_set\\_wildcard](#) (struct [wolfentry\\_route](#) \*route, [wolfentry\\_route\\_flags\\_t](#) wildcards\_to\_set)  
*Set wildcard flags for a route.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_route\\_format\\_address](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, [wolfentry\\_addr\\_family\\_t](#) sa\_family, const [byte](#) \*addr, unsigned int addr\_bits, char \*buf, int \*buflen)  
*Render a binary address in human-readable form to a buffer.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_route\\_flag\\_assoc\\_by\\_flag](#) ([wolfentry\\_route\\_flags\\_t](#) flag, const char \*\*name)  
*Retrieve the name of a route flag, given its numeric value. Note that *flag* must have exactly one bit set, else *ITEM\_NOT\_FOUND* will be returned.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_route\\_flag\\_assoc\\_by\\_name](#) (const char \*name, int len, [wolfentry\\_route\\_flags\\_t](#) \*flag)  
*Retrieve the numeric value of a route flag, given its name.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_route\\_format\\_json](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const struct [wolfentry\\_route](#) \*r, unsigned char \*\*json\_out, size\_t \*json\_out\_len, [wolfentry\\_format\\_flags\\_t](#) flags)  
*Render a route to an output buffer, in JSON format, advancing the output buffer pointer by the length of the rendered output.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_route\\_table\\_dump\\_json\\_start](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const struct [wolfentry\\_route\\_table](#) \*table, struct [wolfentry\\_cursor](#) \*\*cursor, unsigned char \*\*json\_out, size\_t \*json\_out\_len, [wolfentry\\_format\\_flags\\_t](#) flags)  
*Start a rendering loop to export the route table contents as a JSON document that is valid input for [wolfentry\\_config\\_json\\_feed\(\)](#) or [wolfentry\\_config\\_json\\_oneshot\(\)](#), advancing the output buffer pointer by the length of the rendered output, and decrementing *json\_out\_len* by the same amount. Caller must have a shared or exclusive lock on the context at entry.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_route\\_table\\_dump\\_json\\_next](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const struct [wolfentry\\_route\\_table](#) \*table, struct [wolfentry\\_cursor](#) \*cursor, unsigned char \*\*json\_out, size\_t \*json\_out\_len, [wolfentry\\_format\\_flags\\_t](#) flags)  
*Render a route within a loop started with [wolfentry\\_route\\_table\\_dump\\_json\\_start\(\)](#), advancing the output buffer pointer by the length of the rendered output, and decrementing *json\_out\_len* by the same amount.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_route\\_table\\_dump\\_json\\_end](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const struct [wolfentry\\_route\\_table](#) \*table, struct [wolfentry\\_cursor](#) \*\*cursor, unsigned char \*\*json\_out, size\_t \*json\_out\_len, [wolfentry\\_format\\_flags\\_t](#) flags)  
*Finish a rendering loop started with [wolfentry\\_route\\_table\\_dump\\_json\\_start\(\)](#), advancing the output buffer pointer by the length of the rendered output, and decrementing *json\_out\_len* by the same amount.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_route\\_render\\_flags](#) ([wolfentry\\_route\\_flags\\_t](#) flags, FILE \*f)  
*Render route flags in human-readable form to a stream.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_route\\_render](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const struct [wolfentry\\_route](#) \*r, FILE \*f)  
*Renders route information to a file pointer.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_route\\_exports\\_render](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const struct [wolfentry\\_route\\_exports](#) \*r, FILE \*f)  
*Renders route exports information to a file pointer.*



- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t](#) wolfsentry\_action\_insert (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const char \*label, int label\_len, [wolfsentry\\_action\\_flags\\_t](#) flags, [wolfsentry\\_action\\_callback\\_t](#) handler, void \*handler\_arg, [wolfsentry\\_ent\\_id\\_t](#) \*id)  
*Insert a new action into wolfsentry.*
- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t](#) wolfsentry\_action\_delete (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const char \*label, int label\_len, [wolfsentry\\_action\\_res\\_t](#) \*action\_results)  
*Delete an action from wolfsentry.*
- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t](#) wolfsentry\_action\_flush\_all (WOLFSENTRY\_CONTEXT\_ARGS\_IN)  
*Flush all actions from wolfsentry.*
- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t](#) wolfsentry\_action\_get\_reference (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const char \*label, int label\_len, struct wolfsentry\_action \*\*action)  
*Get a reference to an action.*
- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t](#) wolfsentry\_action\_drop\_reference (WOLFSENTRY\_CONTEXT\_ARGS\_IN, struct wolfsentry\_action \*action, [wolfsentry\\_action\\_res\\_t](#) \*action\_results)  
*Drop a reference to an action.*
- WOLFSENTRY\_API const char \* [wolfsentry\\_action\\_get\\_label](#) (const struct wolfsentry\_action \*action)  
*Get the label for an action. This is the internal pointer to the label so should not be freed by the application.*
- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t](#) wolfsentry\_action\_get\_flags (struct wolfsentry\_action \*action, [wolfsentry\\_action\\_flags\\_t](#) \*flags)  
*Get the flags for an action.*
- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t](#) wolfsentry\_action\_update\_flags (struct wolfsentry\_action \*action, [wolfsentry\\_action\\_flags\\_t](#) flags\_to\_set, [wolfsentry\\_action\\_flags\\_t](#) flags\_to\_clear, [wolfsentry\\_action\\_flags\\_t](#) \*flags\_before, [wolfsentry\\_action\\_flags\\_t](#) \*flags\_after)  
*Update the flags for an action.*
- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t](#) wolfsentry\_event\_insert (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const char \*label, int label\_len, [wolfsentry\\_priority\\_t](#) priority, const struct [wolfsentry\\_eventconfig](#) \*config, [wolfsentry\\_event\\_flags\\_t](#) flags, [wolfsentry\\_ent\\_id\\_t](#) \*id)  
*Insert an event into wolfsentry.*
- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t](#) wolfsentry\_event\_delete (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const char \*label, int label\_len, [wolfsentry\\_action\\_res\\_t](#) \*action\_results)  
*Delete an event from wolfsentry.*
- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t](#) wolfsentry\_event\_flush\_all (WOLFSENTRY\_CONTEXT\_ARGS\_IN)  
*Flush all events from wolfsentry.*
- WOLFSENTRY\_API const char \* [wolfsentry\\_event\\_get\\_label](#) (const struct wolfsentry\_event \*event)  
*Get the label for an event. This is the internal pointer to the label so should not be freed by the application.*
- WOLFSENTRY\_API [wolfsentry\\_event\\_flags\\_t](#) wolfsentry\_event\_get\_flags (const struct wolfsentry\_event \*event)  
*Get the flags for an event.*
- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t](#) wolfsentry\_event\_get\_config (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const char \*label, int label\_len, struct [wolfsentry\\_eventconfig](#) \*config)  
*Get the configuration for an event.*
- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t](#) wolfsentry\_event\_update\_config (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const char \*label, int label\_len, const struct [wolfsentry\\_eventconfig](#) \*config)  
*Update the configuration for an event.*
- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t](#) wolfsentry\_event\_get\_reference (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const char \*label, int label\_len, struct wolfsentry\_event \*\*event)  
*Get a reference to an event.*
- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t](#) wolfsentry\_event\_drop\_reference (WOLFSENTRY\_CONTEXT\_ARGS\_IN, struct wolfsentry\_event \*event, [wolfsentry\\_action\\_res\\_t](#) \*action\_results)  
*Drop a reference to an event.*
- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t](#) wolfsentry\_event\_action\_prepend (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const char \*event\_label, int event\_label\_len, [wolfsentry\\_action\\_type\\_t](#) which\_action\_list, const char \*action\_label, int action\_label\_len)

*Prepend an action into an event.*

- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_event\\_action\\_append](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const char \*event\_label, int event\_label\_len, [wolfentry\\_action\\_type\\_t](#) which\_action\_list, const char \*action\_label, int action\_label\_len)

*Append an action into an event.*

- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_event\\_action\\_insert\\_after](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const char \*event\_label, int event\_label\_len, [wolfentry\\_action\\_type\\_t](#) which\_action\_list, const char \*action\_label, int action\_label\_len, const char \*point\_action\_label, int point\_action\_label\_len)

*Insert an action into an event after another action.*

- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_event\\_action\\_delete](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const char \*event\_label, int event\_label\_len, [wolfentry\\_action\\_type\\_t](#) which\_action\_list, const char \*action\_label, int action\_label\_len)

*Delete an action from an event.*

- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_event\\_set\\_aux\\_event](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const char \*event\_label, int event\_label\_len, const char \*aux\_event\_label, int aux\_event\_label\_len)

*Set an auxiliary event for an event.*

- WOLFSENTRY\_API const struct wolfentry\_event \* [wolfentry\\_event\\_get\\_aux\\_event](#) (const struct wolfentry\_event \*event)

*Retrieve an auxiliary event previously set with [wolfentry\\_event\\_set\\_aux\\_event\(\)](#).*

- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_event\\_action\\_list\\_start](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const char \*event\_label, int event\_label\_len, [wolfentry\\_action\\_type\\_t](#) which\_action\_list, struct wolfentry\_action\_list\_ent \*\*cursor)

*Open a cursor for the actions in an event. Caller must have a lock on the context at entry.*

- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_event\\_action\\_list\\_next](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, struct wolfentry\_action\_list\_ent \*\*cursor, const char \*\*action\_label, int \*action\_label\_len)

*Get the next action in an event cursor. Caller must have a lock on the context at entry.*

- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_event\\_action\\_list\\_done](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, struct wolfentry\_action\_list\_ent \*\*cursor)

*End iteration started with [wolfentry\\_event\\_action\\_list\\_start\(\)](#). Caller must have a lock on the context at entry.*

- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_user\\_value\\_set\\_validator](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, [wolfentry\\_kv\\_validator\\_t](#) validator, [wolfentry\\_action\\_res\\_t](#) \*action\_results)

*Install a supplied [wolfentry\\_kv\\_validator\\_t](#) to validate all user values before inserting them into the value table.*

- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_user\\_value\\_set\\_mutability](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const char \*key, int key\_len, int mutable)

*Set the user-defined value with the designated key as readwrite (mutable=1) or readonly (mutable=0). A read-only value cannot be changed or deleted.*

- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_user\\_value\\_get\\_mutability](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const char \*key, int key\_len, int \*mutable)

*Query the mutability of the user-defined value with the designated key. Readonly value cannot be changed or deleted.*

- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_user\\_value\\_get\\_type](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const char \*key, int key\_len, [wolfentry\\_kv\\_type\\_t](#) \*type)

*Returns the type of the value with the designated key, using [WOLFSENTRY\\_KV\\_TYPE\(\)](#).*

- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_user\\_value\\_delete](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const char \*key, int key\_len)

*Deletes the value with the designated key.*

- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_user\\_value\\_store\\_null](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const char \*key, int key\_len, int overwrite\_p)

*Inserts or overwrites a [WOLFSENTRY\\_KV\\_NULL](#) value with the designated key.*

- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_user\\_value\\_store\\_bool](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const char \*key, int key\_len, [wolfentry\\_kv\\_type\\_t](#) value, int overwrite\_p)

*Inserts or overwrites a [WOLFSENTRY\\_KV\\_TRUE](#) or [WOLFSENTRY\\_KV\\_FALSE](#) value with the designated key.*

- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t wolfsentry\\_user\\_value\\_get\\_bool](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const char \*key, int key\_len, [wolfsentry\\_kv\\_type\\_t](#) \*value)  
*Gets a WOLFSENTRY\_KV\_TRUE or WOLFSENTRY\_KV\_FALSE value with the designated key.*
- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t wolfsentry\\_user\\_value\\_store\\_uint](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const char \*key, int key\_len, uint64\_t value, int overwrite\_p)  
*Inserts or overwrites a WOLFSENTRY\_KV\_UINT value with the designated key.*
- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t wolfsentry\\_user\\_value\\_get\\_uint](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const char \*key, int key\_len, uint64\_t \*value)  
*Gets a WOLFSENTRY\_KV\_UINT value with the designated key.*
- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t wolfsentry\\_user\\_value\\_store\\_sint](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const char \*key, int key\_len, int64\_t value, int overwrite\_p)  
*Inserts or overwrites a WOLFSENTRY\_KV\_SINT value with the designated key.*
- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t wolfsentry\\_user\\_value\\_get\\_sint](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const char \*key, int key\_len, int64\_t \*value)  
*Gets a WOLFSENTRY\_KV\_UINT value with the designated key.*
- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t wolfsentry\\_user\\_value\\_store\\_double](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const char \*key, int key\_len, double value, int overwrite\_p)  
*Inserts or overwrites a WOLFSENTRY\_KV\_FLOAT value with the designated key.*
- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t wolfsentry\\_user\\_value\\_get\\_float](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const char \*key, int key\_len, double \*value)  
*Gets a WOLFSENTRY\_KV\_UINT value with the designated key.*
- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t wolfsentry\\_user\\_value\\_store\\_string](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const char \*key, int key\_len, const char \*value, int value\_len, int overwrite\_p)  
*Inserts or overwrites a WOLFSENTRY\_KV\_STRING value with the designated key.*
- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t wolfsentry\\_user\\_value\\_get\\_string](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const char \*key, int key\_len, const char \*\*value, int \*value\_len, struct wolfsentry\_kv\_pair\_internal \*\*user\_value\_record)  
*Gets a WOLFSENTRY\_KV\_STRING value with the designated key.*
- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t wolfsentry\\_user\\_value\\_store\\_bytes](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const char \*key, int key\_len, const byte \*value, int value\_len, int overwrite\_p)  
*Inserts or overwrites a WOLFSENTRY\_KV\_BYTES value with the designated key and a binary-clean value.*
- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t wolfsentry\\_user\\_value\\_store\\_bytes\\_base64](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const char \*key, int key\_len, const char \*value, int value\_len, int overwrite\_p)  
*Inserts or overwrites a WOLFSENTRY\_KV\_BYTES value with the designated key and a base64-encoded value.*
- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t wolfsentry\\_user\\_value\\_get\\_bytes](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const char \*key, int key\_len, const byte \*\*value, int \*value\_len, struct wolfsentry\_kv\_pair\_internal \*\*user\_value\_record)  
*Gets a WOLFSENTRY\_KV\_BYTES value with the designated key.*
- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t wolfsentry\\_user\\_value\\_store\\_json](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const char \*key, int key\_len, JSON\_VALUE \*value, int overwrite\_p)  
*Inserts or overwrites a WOLFSENTRY\_KV\_JSON value with the designated key and a value from json\_dom↔\_parse() (or built up programmatically with the [centijson\\_value.h](#) API).*
- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t wolfsentry\\_user\\_value\\_get\\_json](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, const char \*key, int key\_len, JSON\_VALUE \*\*value, struct wolfsentry\_kv\_pair\_internal \*\*user\_value\_record)  
*Gets a WOLFSENTRY\_KV\_JSON value with the designated key.*
- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t wolfsentry\\_user\\_value\\_release\\_record](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, struct wolfsentry\_kv\_pair\_internal \*\*user\_value\_record)  
*Release a user\_value\_record from [wolfsentry\\_user\\_value\\_get\\_string\(\)](#), [wolfsentry\\_user\\_value\\_get\\_bytes\(\)](#) or [wolfsentry\\_user\\_value\\_get\\_json\(\)](#).*
- WOLFSENTRY\_API [wolfsentry\\_errcode\\_t wolfsentry\\_kv\\_pair\\_export](#) (WOLFSENTRY\_CONTEXT\_ARGS\_IN, struct wolfsentry\_kv\_pair\_internal \*kv, const struct wolfsentry\_kv\_pair \*\*kv\_exports)  
*Extract the struct wolfsentry\_kv\_pair from a struct wolfsentry\_kv\_pair\_internal. Caller must have a shared or exclusive lock on the context.*

- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_kv\\_type\\_to\\_string](#) ([wolfentry\\_kv\\_type\\_t](#) type, const char \*\*out)  
*Return a human-readable rendering of a `wolfentry_kv_type_t`.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_kv\\_render\\_value](#) ([WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#), const struct [wolfentry\\_kv\\_pair](#) \*kv, char \*out, int \*out\_len)  
*Render `kv` in human-readable form to caller-preallocated buffer `out`.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_user\\_values\\_iterate\\_start](#) ([WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#), struct [wolfentry\\_cursor](#) \*\*cursor)  
*Start an iteration loop on the user values table of this context. Caller must have a lock on the context at entry.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_user\\_values\\_iterate\\_seek\\_to\\_head](#) ([WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#), struct [wolfentry\\_cursor](#) \*cursor)  
*Move the cursor to point to the start of the user values table. Caller must have a lock on the context at entry.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_user\\_values\\_iterate\\_seek\\_to\\_tail](#) ([WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#), struct [wolfentry\\_cursor](#) \*cursor)  
*Move the cursor to point to the end of the user values table. Caller must have a lock on the context at entry.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_user\\_values\\_iterate\\_current](#) ([WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#), struct [wolfentry\\_cursor](#) \*cursor, struct [wolfentry\\_kv\\_pair\\_internal](#) \*\*kv)  
*Return the item to which the cursor currently points, without moving the cursor. Caller must have a lock on the context at entry.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_user\\_values\\_iterate\\_prev](#) ([WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#), struct [wolfentry\\_cursor](#) \*cursor, struct [wolfentry\\_kv\\_pair\\_internal](#) \*\*kv)  
*Move the cursor to the previous item, and return it. Caller must have a lock on the context at entry.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_user\\_values\\_iterate\\_next](#) ([WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#), struct [wolfentry\\_cursor](#) \*cursor, struct [wolfentry\\_kv\\_pair\\_internal](#) \*\*kv)  
*Move the cursor to the next item, and return it. Caller must have a lock on the context at entry.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_user\\_values\\_iterate\\_end](#) ([WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#), struct [wolfentry\\_cursor](#) \*\*cursor)  
*End an iteration loop started with [wolfentry\\_user\\_values\\_iterate\\_start\(\)](#). Caller must have a lock on the context at entry.*
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_base64\\_decode](#) (const char \*src, size\_t src\_len, byte \*dest, size\_t \*dest\_spc, int ignore\_junk\_p)  
*Convert base64-encoded input `src` to binary output `dest`, optionally ignoring (with nonzero `ignore_junk_p`) non-base64 characters in `src`.*

### 10.4.1 Detailed Description

The main include file for wolfSentry applications.

Include this file in your application for core wolfSentry capabilities.

## 10.5 wolfentry.h

[Go to the documentation of this file.](#)

```
00001 /*
00002  * wolfentry.h
00003  *
00004  * Copyright (C) 2021-2023 wolfSSL Inc.
00005  *
00006  * This file is part of wolfSentry.
00007  *
00008  * wolfSentry is free software; you can redistribute it and/or modify
00009  * it under the terms of the GNU General Public License as published by
00010  * the Free Software Foundation; either version 2 of the License, or
00011  * (at your option) any later version.
00012  *
```

```

00013  * wolfsentry is distributed in the hope that it will be useful,
00014  * but WITHOUT ANY WARRANTY; without even the implied warranty of
00015  * MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
00016  * GNU General Public License for more details.
00017  *
00018  * You should have received a copy of the GNU General Public License
00019  * along with this program; if not, write to the Free Software
00020  * Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1335, USA
00021  */
00022
00029 #ifndef WOLFSENTRY_H
00030 #define WOLFSENTRY_H
00031
00053 #define WOLFSENTRY_VERSION_MAJOR 1
00055 #define WOLFSENTRY_VERSION_MINOR 6
00057 #define WOLFSENTRY_VERSION_TINY 1
00059 #define WOLFSENTRY_VERSION_ENCODE(major, minor, tiny) (((major) << 16U) | ((minor) << 8U) | (tiny))
00061 #define WOLFSENTRY_VERSION_ENCODE(major, minor, tiny) (WOLFSENTRY_VERSION_MAJOR,
WOLFSENTRY_VERSION_MINOR, WOLFSENTRY_VERSION_TINY)
00063 #define WOLFSENTRY_VERSION_GT(major, minor, tiny) (WOLFSENTRY_VERSION >
WOLFSENTRY_VERSION_ENCODE(major, minor, tiny))
00065 #define WOLFSENTRY_VERSION_GE(major, minor, tiny) (WOLFSENTRY_VERSION >=
WOLFSENTRY_VERSION_ENCODE(major, minor, tiny))
00067 #define WOLFSENTRY_VERSION_EQ(major, minor, tiny) (WOLFSENTRY_VERSION ==
WOLFSENTRY_VERSION_ENCODE(major, minor, tiny))
00069 #define WOLFSENTRY_VERSION_LT(major, minor, tiny) (WOLFSENTRY_VERSION <
WOLFSENTRY_VERSION_ENCODE(major, minor, tiny))
00071 #define WOLFSENTRY_VERSION_LE(major, minor, tiny) (WOLFSENTRY_VERSION <=
WOLFSENTRY_VERSION_ENCODE(major, minor, tiny))
00075 typedef enum {
00076     WOLFSENTRY_INIT_FLAG_NONE = 0,
00077     WOLFSENTRY_INIT_FLAG_LOCK_SHARED_ERROR_CHECKING = 1<<0
00078 } wolfsentry_init_flags_t;
00079
00082 #ifndef WOLFSENTRY
00084 #define WOLFSENTRY /* activate wolfsentry codepaths in CentiJSON headers */
00086 #endif
00087
00088 #include <wolfsentry/wolfsentry_settings.h>
00089 #include <wolfsentry/wolfsentry_af.h>
00090 #include <wolfsentry/wolfsentry_errcodes.h>
00091
00092 struct wolfsentry_allocator;
00093 struct wolfsentry_context;
00094 struct wolfsentry_thread_context;
00095
00100 #ifdef WOLFSENTRY_THREADSAFE
00101
00102 typedef void *(*wolfsentry_malloc_cb_t)(void *context, struct wolfsentry_thread_context *thread,
size_t size);
00104 typedef void *(*wolfsentry_free_cb_t)(void *context, struct wolfsentry_thread_context *thread, void
*ptr);
00108 typedef void *(*wolfsentry_realloc_cb_t)(void *context, struct wolfsentry_thread_context *thread, void
*ptr, size_t size);
00112 typedef void *(*wolfsentry_memalign_cb_t)(void *context, struct wolfsentry_thread_context *thread,
size_t alignment, size_t size);
00116 typedef void *(*wolfsentry_free_aligned_cb_t)(void *context, struct wolfsentry_thread_context *thread,
void *ptr);
00122 #else /* !WOLFSENTRY_THREADSAFE */
00123
00124 typedef void *(*wolfsentry_malloc_cb_t)(void *context, size_t size);
00125 typedef void *(*wolfsentry_free_cb_t)(void *context, void *ptr);
00126 typedef void *(*wolfsentry_realloc_cb_t)(void *context, void *ptr, size_t size);
00127 typedef void *(*wolfsentry_memalign_cb_t)(void *context, size_t alignment, size_t size);
00128 typedef void *(*wolfsentry_free_aligned_cb_t)(void *context, void *ptr);
00129
00130 #endif /* WOLFSENTRY_THREADSAFE */
00131
00133 struct wolfsentry_allocator {
00134     void *context;
00136     wolfsentry_malloc_cb_t malloc;
00138     wolfsentry_free_cb_t free;
00140     wolfsentry_realloc_cb_t realloc;
00142     wolfsentry_memalign_cb_t memalign;
00146     wolfsentry_free_aligned_cb_t free_aligned;
00148 };
00149
00156 typedef wolfsentry_errcode_t (*wolfsentry_get_time_cb_t)(void *context, wolfsentry_time_t *ts);
00159 typedef wolfsentry_time_t (*wolfsentry_diff_time_cb_t)(wolfsentry_time_t earlier, wolfsentry_time_t
later);
00161 typedef wolfsentry_time_t (*wolfsentry_add_time_cb_t)(wolfsentry_time_t start_time, wolfsentry_time_t
time_interval);
00163 typedef wolfsentry_errcode_t (*wolfsentry_to_epoch_time_cb_t)(wolfsentry_time_t when, time_t
*epoch_secs, long *epoch_nsecs);
00165 typedef wolfsentry_errcode_t (*wolfsentry_from_epoch_time_cb_t)(time_t epoch_secs, long epoch_nsecs,
wolfsentry_time_t *when);
00167 typedef wolfsentry_errcode_t (*wolfsentry_interval_to_seconds_cb_t)(wolfsentry_time_t howlong, time_t

```

```

    *howlong_secs, long *howlong_nsecs);
00169 typedef wolfentry_errcode_t (*wolfentry_interval_from_seconds_cb_t)(time_t howlong_secs, long
    howlong_nsecs, wolfentry_time_t *howlong);
00173 struct wolfentry_timecbs {
00174     void *context;
00176     wolfentry_get_time_cb_t get_time;
00178     wolfentry_diff_time_cb_t diff_time;
00180     wolfentry_add_time_cb_t add_time;
00182     wolfentry_to_epoch_time_cb_t to_epoch_time;
00184     wolfentry_from_epoch_time_cb_t from_epoch_time;
00186     wolfentry_interval_to_seconds_cb_t interval_to_seconds;
00188     wolfentry_interval_from_seconds_cb_t interval_from_seconds;
00190 };
00191
00194 #ifdef WOLFSENTRY_THREADSAFE
00195
00200 typedef int (*sem_init_cb_t)(sem_t *sem, int pshared, unsigned int value);
00202 typedef int (*sem_post_cb_t)(sem_t *sem);
00204 typedef int (*sem_wait_cb_t)(sem_t *sem);
00206 typedef int (*sem_timedwait_cb_t)(sem_t *sem, const struct timespec *abs_timeout);
00208 typedef int (*sem_trywait_cb_t)(sem_t *sem);
00210 typedef int (*sem_destroy_cb_t)(sem_t *sem);
00214 struct wolfentry_semcbs {
00215     sem_init_cb_t sem_init;
00217     sem_post_cb_t sem_post;
00219     sem_wait_cb_t sem_wait;
00221     sem_timedwait_cb_t sem_timedwait;
00223     sem_trywait_cb_t sem_trywait;
00225     sem_destroy_cb_t sem_destroy;
00227 };
00228
00231 #endif /* WOLFSENTRY_THREADSAFE */
00232
00238 struct wolfentry_host_platform_interface {
00239     struct wolfentry_build_settings caller_build_settings;
    /* must be first */ 00241     struct wolfentry_allocator allocator;
00243     struct wolfentry_timecbs timecbs;
00245 #ifdef WOLFSENTRY_THREADSAFE
00246     struct wolfentry_semcbs semcbs;
00248 #endif
00249 };
00250
00251 WOLFSENTRY_API struct wolfentry_build_settings wolfentry_get_build_settings(void);
00253 WOLFSENTRY_API wolfentry_errcode_t wolfentry_build_settings_compatible(struct
    wolfentry_build_settings caller_build_settings);
00258 #ifdef WOLFSENTRY_THREADSAFE
00259
00265 typedef enum {
00266     WOLFSENTRY_THREAD_FLAG_NONE = 0,
00268     WOLFSENTRY_THREAD_FLAG_DEADLINE = 1<<0,
00270     WOLFSENTRY_THREAD_FLAG_READONLY = 1<<1
00272 } wolfentry_thread_flags_t;
00273
00274 #define WOLFSENTRY_CONTEXT_ARGS_IN struct wolfentry_context *wolfentry, struct
    wolfentry_thread_context *thread
00276 #define WOLFSENTRY_CONTEXT_ARGS_IN_EX(ctx, struct wolfentry_thread_context *thread
00281 #define WOLFSENTRY_CONTEXT_ARGS_IN_EX4(ctx, thr) struct wolfentry_context *ctx, struct
    wolfentry_thread_context *thr
00283 #define WOLFSENTRY_CONTEXT_ELEMENTS struct wolfentry_context *wolfentry; struct
    wolfentry_thread_context *thread
00285 #define WOLFSENTRY_CONTEXT_SET_ELEMENTS(s) (s).wolfentry = wolfentry; (s).thread = thread
00287 #define WOLFSENTRY_CONTEXT_GET_ELEMENTS(s) (s).wolfentry, (s).thread
00289 #define WOLFSENTRY_CONTEXT_ARGS_OUT wolfentry, thread
00291 #define WOLFSENTRY_CONTEXT_ARGS_OUT_EX(ctx) ctx, thread
00293 #define WOLFSENTRY_CONTEXT_ARGS_OUT_EX2(x) (x)->wolfentry, (x)->thread
00295 #define WOLFSENTRY_CONTEXT_ARGS_OUT_EX3(x, y) (x)->y, (x)->thread
00297 #define WOLFSENTRY_CONTEXT_ARGS_OUT_EX4(x, y) x, y
00299 #define WOLFSENTRY_CONTEXT_ARGS_NOT_USED (void)wolfentry; (void)thread
00301 #define WOLFSENTRY_CONTEXT_ARGS_THREAD_NOT_USED (void)thread
00304 /* note WOLFSENTRY_THREAD_HEADER_DECLS includes final semicolon. */
00305 #define WOLFSENTRY_THREAD_HEADER_DECLS
00306     struct wolfentry_thread_context_public thread_buffer =
00307         WOLFSENTRY_THREAD_CONTEXT_PUBLIC_INITIALIZER;
00308     struct wolfentry_thread_context *thread =
00309         (struct wolfentry_thread_context *)&thread_buffer;
00310     wolfentry_errcode_t _thread_context_ret;
00313 #define WOLFSENTRY_THREAD_HEADER_INIT(flags)
00314     (_thread_context_ret =
00315         wolfentry_init_thread_context(thread, flags, NULL /* user_context */))
00318 #define WOLFSENTRY_THREAD_HEADER_INIT_CHECKED(flags)
00319     do {
00320         _thread_context_ret =
00321             wolfentry_init_thread_context(thread, flags, NULL /* user_context */); \
00322             if (_thread_context_ret < 0)
00323                 return _thread_context_ret;
00324     } while (0)
00327 #define WOLFSENTRY_THREAD_HEADER(flags)

```



```

00328     struct wolfssentry_thread_context_public thread_buffer =
00329         WOLFSENTRY_THREAD_CONTEXT_PUBLIC_INITIALIZER;
00330     struct wolfssentry_thread_context *thread =
00331         (struct wolfssentry_thread_context *)&thread_buffer;
00332     wolfssentry_errcode_t _thread_context_ret =
00333         wolfssentry_init_thread_context(thread, flags, NULL /* user_context */)
00334 #define WOLFSENTRY_THREAD_HEADER_CHECK()
00335     do {
00336         if (_thread_context_ret < 0)
00337             return _thread_context_ret;
00338     } while (0)
00339 #define WOLFSENTRY_THREAD_HEADER_CHECKED(flags)
00340     WOLFSENTRY_THREAD_HEADER(flags);
00341     WOLFSENTRY_THREAD_HEADER_CHECK()
00342 #define WOLFSENTRY_THREAD_TAILER_CHECKED(flags) (_thread_context_ret =
00343     wolfssentry_destroy_thread_context(thread, flags))
00344 #define WOLFSENTRY_THREAD_TAILER_CHECKED(flags) do { WOLFSENTRY_THREAD_TAILER(flags); if
00345     (_thread_context_ret < 0) return _thread_context_ret; } while (0)
00346 #define WOLFSENTRY_THREAD_GET_ERROR _thread_context_ret
00347 typedef enum {
00348     WOLFSENTRY_LOCK_FLAG_NONE = 0,
00349     WOLFSENTRY_LOCK_FLAG_PSHARED = 1<<0,
00350     WOLFSENTRY_LOCK_FLAG_SHARED_ERROR_CHECKING = 1<<1,
00351     WOLFSENTRY_LOCK_FLAG_NONRECURSIVE_MUTEX = 1<<2,
00352     WOLFSENTRY_LOCK_FLAG_NONRECURSIVE_SHARED = 1<<3,
00353     WOLFSENTRY_LOCK_FLAG_GET_RESERVATION_TOO = 1<<4,
00354     WOLFSENTRY_LOCK_FLAG_TRY_RESERVATION_TOO = 1<<5,
00355     WOLFSENTRY_LOCK_FLAG_ABANDON_RESERVATION_TOO = 1<<6,
00356     WOLFSENTRY_LOCK_FLAG_AUTO_DOWNGRADE = 1<<7,
00357     WOLFSENTRY_LOCK_FLAG_RETAIN_SEMAPHORE = 1<<8
00358 } wolfssentry_lock_flags_t;
00359
00360 WOLFSENTRY_API wolfssentry_errcode_t wolfssentry_init_thread_context(struct wolfssentry_thread_context
00361 *thread_context, wolfssentry_thread_flags_t init_thread_flags, void *user_context);
00362 WOLFSENTRY_API wolfssentry_errcode_t wolfssentry_alloc_thread_context(struct
00363 wolfssentry_host_platform_interface *hpi, struct wolfssentry_thread_context **thread_context,
00364 wolfssentry_thread_flags_t init_thread_flags, void *user_context);
00365 WOLFSENTRY_API wolfssentry_errcode_t wolfssentry_get_thread_id(struct wolfssentry_thread_context *thread,
00366 wolfssentry_thread_id_t *id);
00367 WOLFSENTRY_API wolfssentry_errcode_t wolfssentry_get_thread_user_context(struct
00368 wolfssentry_thread_context *thread, void **user_context);
00369 WOLFSENTRY_API wolfssentry_errcode_t wolfssentry_get_thread_deadline(struct wolfssentry_thread_context
00370 *thread, struct timespec *deadline);
00371 WOLFSENTRY_API wolfssentry_errcode_t wolfssentry_get_thread_flags(struct wolfssentry_thread_context
00372 *thread, wolfssentry_thread_flags_t *thread_flags);
00373 WOLFSENTRY_API wolfssentry_errcode_t wolfssentry_destroy_thread_context(struct wolfssentry_thread_context
00374 *thread_context, wolfssentry_thread_flags_t thread_flags);
00375 WOLFSENTRY_API wolfssentry_errcode_t wolfssentry_free_thread_context(struct
00376 wolfssentry_host_platform_interface *hpi, struct wolfssentry_thread_context **thread_context,
00377 wolfssentry_thread_flags_t thread_flags);
00378 WOLFSENTRY_API wolfssentry_errcode_t wolfssentry_set_deadline_rel_usecs(WOLFSENTRY_CONTEXT_ARGS_IN, int
00379 usecs);
00380 WOLFSENTRY_API wolfssentry_errcode_t wolfssentry_set_deadline_abs(WOLFSENTRY_CONTEXT_ARGS_IN, time_t
00381 epoch_secs, long epoch_nsecs);
00382 WOLFSENTRY_API wolfssentry_errcode_t wolfssentry_clear_deadline(WOLFSENTRY_CONTEXT_ARGS_IN);
00383 WOLFSENTRY_API wolfssentry_errcode_t wolfssentry_set_thread_readonly(struct wolfssentry_thread_context
00384 *thread_context);
00385 WOLFSENTRY_API wolfssentry_errcode_t wolfssentry_set_thread_readwrite(struct wolfssentry_thread_context
00386 *thread_context);
00387 struct wolfssentry_rwlock;
00388
00389 WOLFSENTRY_API wolfssentry_errcode_t wolfssentry_lock_init(struct wolfssentry_host_platform_interface
00390 *hpi, struct wolfssentry_thread_context *thread, struct wolfssentry_rwlock *lock,
00391 wolfssentry_lock_flags_t flags);
00392 WOLFSENTRY_API size_t wolfssentry_lock_size(void);
00393 WOLFSENTRY_API wolfssentry_errcode_t wolfssentry_lock_alloc(struct wolfssentry_host_platform_interface
00394 *hpi, struct wolfssentry_thread_context *thread, struct wolfssentry_rwlock **lock,
00395 wolfssentry_lock_flags_t flags);
00396 WOLFSENTRY_API wolfssentry_errcode_t wolfssentry_lock_shared(struct wolfssentry_rwlock *lock, struct
00397 wolfssentry_thread_context *thread, wolfssentry_lock_flags_t flags);
00398 WOLFSENTRY_API wolfssentry_errcode_t wolfssentry_lock_shared_abstimed(struct wolfssentry_rwlock *lock,
00399 struct wolfssentry_thread_context *thread, const struct timespec *abs_timeout, wolfssentry_lock_flags_t
00400 flags);
00401 WOLFSENTRY_API wolfssentry_errcode_t wolfssentry_lock_shared_timed(struct wolfssentry_rwlock *lock,
00402 struct wolfssentry_thread_context *thread, wolfssentry_time_t max_wait, wolfssentry_lock_flags_t flags);
00403 WOLFSENTRY_API wolfssentry_errcode_t wolfssentry_lock_mutex(struct wolfssentry_rwlock *lock, struct
00404 wolfssentry_thread_context *thread, wolfssentry_lock_flags_t flags);
00405 WOLFSENTRY_API wolfssentry_errcode_t wolfssentry_lock_mutex_abstimed(struct wolfssentry_rwlock *lock,
00406 struct wolfssentry_thread_context *thread, const struct timespec *abs_timeout, wolfssentry_lock_flags_t
00407 flags);
00408 WOLFSENTRY_API wolfssentry_errcode_t wolfssentry_lock_mutex_timed(struct wolfssentry_rwlock *lock, struct
00409 wolfssentry_thread_context *thread, wolfssentry_time_t max_wait, wolfssentry_lock_flags_t flags);
00410 WOLFSENTRY_API wolfssentry_errcode_t wolfssentry_lock_mutex2shared(struct wolfssentry_rwlock *lock,
00411 struct wolfssentry_thread_context *thread, wolfssentry_lock_flags_t flags);
00412 WOLFSENTRY_API wolfssentry_errcode_t wolfssentry_lock_shared2mutex(struct wolfssentry_rwlock *lock,
00413 struct wolfssentry_thread_context *thread, wolfssentry_lock_flags_t flags);
00414 WOLFSENTRY_API wolfssentry_errcode_t wolfssentry_lock_shared2mutex_abstimed(struct wolfssentry_rwlock

```

```

    *lock, struct wolfentry_thread_context *thread, const struct timespec *abs_timeout,
    wolfentry_lock_flags_t flags);
00564 WOLFSENTRY_API wolfentry_errcode_t wolfentry_lock_shared2mutex_timed(struct wolfentry_rwlock *lock,
    struct wolfentry_thread_context *thread, wolfentry_time_t max_wait, wolfentry_lock_flags_t flags);
00580 WOLFSENTRY_API wolfentry_errcode_t wolfentry_lock_shared2mutex_reserve(struct wolfentry_rwlock
    *lock, struct wolfentry_thread_context *thread, wolfentry_lock_flags_t flags);
00592 WOLFSENTRY_API wolfentry_errcode_t wolfentry_lock_shared2mutex_redeem(struct wolfentry_rwlock
    *lock, struct wolfentry_thread_context *thread, wolfentry_lock_flags_t flags);
00605 WOLFSENTRY_API wolfentry_errcode_t wolfentry_lock_shared2mutex_redeem_abstimed(struct
    wolfentry_rwlock *lock, struct wolfentry_thread_context *thread, const struct timespec *abs_timeout,
    wolfentry_lock_flags_t flags);
00618 WOLFSENTRY_API wolfentry_errcode_t wolfentry_lock_shared2mutex_redeem_timed(struct wolfentry_rwlock
    *lock, struct wolfentry_thread_context *thread, wolfentry_time_t max_wait, wolfentry_lock_flags_t
    flags);
00630 WOLFSENTRY_API wolfentry_errcode_t wolfentry_lock_shared2mutex_abandon(struct wolfentry_rwlock
    *lock, struct wolfentry_thread_context *thread, wolfentry_lock_flags_t flags);
00644 WOLFSENTRY_API wolfentry_errcode_t wolfentry_lock_have_shared(struct wolfentry_rwlock *lock, struct
    wolfentry_thread_context *thread, wolfentry_lock_flags_t flags);
00658 WOLFSENTRY_API wolfentry_errcode_t wolfentry_lock_have_mutex(struct wolfentry_rwlock *lock, struct
    wolfentry_thread_context *thread, wolfentry_lock_flags_t flags);
00673 WOLFSENTRY_API wolfentry_errcode_t wolfentry_lock_have_either(struct wolfentry_rwlock *lock, struct
    wolfentry_thread_context *thread, wolfentry_lock_flags_t flags);
00686 WOLFSENTRY_API wolfentry_errcode_t wolfentry_lock_have_shared2mutex_reservation(struct
    wolfentry_rwlock *lock, struct wolfentry_thread_context *thread, wolfentry_lock_flags_t flags);
00698 WOLFSENTRY_API wolfentry_errcode_t wolfentry_lock_get_flags(struct wolfentry_rwlock *lock, struct
    wolfentry_thread_context *thread, wolfentry_lock_flags_t *flags);
00710 WOLFSENTRY_API wolfentry_errcode_t wolfentry_lock_unlock(struct wolfentry_rwlock *lock, struct
    wolfentry_thread_context *thread, wolfentry_lock_flags_t flags);
00723 WOLFSENTRY_API wolfentry_errcode_t wolfentry_lock_destroy(struct wolfentry_rwlock *lock, struct
    wolfentry_thread_context *thread, wolfentry_lock_flags_t flags);
00737 WOLFSENTRY_API wolfentry_errcode_t wolfentry_lock_free(struct wolfentry_rwlock **lock, struct
    wolfentry_thread_context *thread, wolfentry_lock_flags_t flags);
00738
00739 #else /* !WOLFSENTRY_THREADSafe */
00740
00741 #define WOLFSENTRY_CONTEXT_ARGS_IN struct wolfentry_context *wolfentry
00742 #define WOLFSENTRY_CONTEXT_ARGS_IN_EX(ctx) ctx
00743 #define WOLFSENTRY_CONTEXT_ELEMENTS struct wolfentry_context *wolfentry
00744 #define WOLFSENTRY_CONTEXT_SET_ELEMENTS(s) (s).wolfentry = wolfentry
00745 #define WOLFSENTRY_CONTEXT_GET_ELEMENTS(s) (s).wolfentry
00746 #define WOLFSENTRY_CONTEXT_ARGS_OUT wolfentry
00747 #define WOLFSENTRY_CONTEXT_ARGS_OUT_EX(ctx) ctx
00748 #define WOLFSENTRY_CONTEXT_ARGS_OUT_EX2(x) (x)->wolfentry
00749 #define WOLFSENTRY_CONTEXT_ARGS_OUT_EX3(x, y) (x)->y
00750 #define WOLFSENTRY_CONTEXT_ARGS_OUT_EX4(x, y) x
00751 #define WOLFSENTRY_CONTEXT_ARGS_NOT_USED (void)wolfentry
00752 #define WOLFSENTRY_CONTEXT_ARGS_THREAD_NOT_USED DO_NOTHING
00753
00754 #define WOLFSENTRY_THREAD_HEADER_DECLS
00755 #define WOLFSENTRY_THREAD_HEADER(flags) DO_NOTHING
00756 #define WOLFSENTRY_THREAD_HEADER_INIT(flags) 0
00757 #define WOLFSENTRY_THREAD_HEADER_INIT_CHECKED(flags) DO_NOTHING
00758 #define WOLFSENTRY_THREAD_HEADER_CHECKED(flags) DO_NOTHING
00759 #define WOLFSENTRY_THREAD_HEADER_CHECK() DO_NOTHING
00760 #define WOLFSENTRY_THREAD_GET_ERROR 0
00761 #define WOLFSENTRY_THREAD_TAILER(flags) 0
00762 #define WOLFSENTRY_THREAD_TAILER_CHECKED(flags) DO_NOTHING
00763
00764 #define wolfentry_lock_init(x, y, z, w) WOLFSENTRY_ERROR_ENCODE(OK)
00765 #define wolfentry_lock_alloc(x, y, z, w) WOLFSENTRY_ERROR_ENCODE(OK)
00766 #define wolfentry_lock_shared(x, y, z) WOLFSENTRY_ERROR_ENCODE(OK)
00767 #define wolfentry_lock_shared_abstimed(x, y, z, w) WOLFSENTRY_ERROR_ENCODE(OK)
00768 #define wolfentry_lock_mutex_timed(x, y, z, w) WOLFSENTRY_ERROR_ENCODE(OK)
00769 #define wolfentry_lock_mutex(x, y, z) WOLFSENTRY_ERROR_ENCODE(OK)
00770 #define wolfentry_lock_mutex_abstimed(x, y, z, w) WOLFSENTRY_ERROR_ENCODE(OK)
00771 #define wolfentry_lock_mutex_timed(x, y, z, w) WOLFSENTRY_ERROR_ENCODE(OK)
00772 #define wolfentry_lock_mutex2shared(x, y, z) WOLFSENTRY_ERROR_ENCODE(OK)
00773 #define wolfentry_lock_shared2mutex(x, y, z) WOLFSENTRY_ERROR_ENCODE(OK)
00774 #define wolfentry_lock_shared2mutex_abstimed(x, y, z, w) WOLFSENTRY_ERROR_ENCODE(OK)
00775 #define wolfentry_lock_shared2mutex_timed(x, y, z, w) WOLFSENTRY_ERROR_ENCODE(OK)
00776 #define wolfentry_lock_shared2mutex_reserve(x, y, z) WOLFSENTRY_ERROR_ENCODE(OK)
00777 #define wolfentry_lock_shared2mutex_redeem(x, y, z) WOLFSENTRY_ERROR_ENCODE(OK)
00778 #define wolfentry_lock_shared2mutex_redeem_abstimed(x, y, z, w) WOLFSENTRY_ERROR_ENCODE(OK)
00779 #define wolfentry_lock_shared2mutex_redeem_timed(x, y, z, w) WOLFSENTRY_ERROR_ENCODE(OK)
00780 #define wolfentry_lock_shared2mutex_abandon(x, y, z) WOLFSENTRY_ERROR_ENCODE(OK)
00781 #define wolfentry_lock_have_shared(x, y, z) WOLFSENTRY_ERROR_ENCODE(OK)
00782 #define wolfentry_lock_have_mutex(x, y, z) WOLFSENTRY_ERROR_ENCODE(OK)
00783 #define wolfentry_lock_have_either(x, y, z) WOLFSENTRY_ERROR_ENCODE(OK)
00784 #define wolfentry_lock_have_shared2mutex_reservation(x, y, z) WOLFSENTRY_ERROR_ENCODE(OK)
00785 #define wolfentry_lock_unlock(x, y, z) WOLFSENTRY_ERROR_ENCODE(OK)
00786 #define wolfentry_lock_destroy(x, y, z) WOLFSENTRY_ERROR_ENCODE(OK)
00787 #define wolfentry_lock_free(x, y, z) WOLFSENTRY_ERROR_ENCODE(OK)
00788
00789 #endif /* WOLFSENTRY_THREADSafe */
00790
00791 typedef enum {
00792     WOLFSENTRY_OBJECT_TYPE_UNINITED = 0,

```



```

00801     WOLFSENTRY_OBJECT_TYPE_TABLE,
00803     WOLFSENTRY_OBJECT_TYPE_ACTION,
00805     WOLFSENTRY_OBJECT_TYPE_EVENT,
00807     WOLFSENTRY_OBJECT_TYPE_ROUTE,
00809     WOLFSENTRY_OBJECT_TYPE_KV,
00811     WOLFSENTRY_OBJECT_TYPE_ADDR_FAMILY_BYNUMBER,
00813     WOLFSENTRY_OBJECT_TYPE_ADDR_FAMILY_BYNAME
00815 } wolfsentry_object_type_t;
00816
00824 typedef enum {
00825     WOLFSENTRY_ACTION_FLAG_NONE          = 0U,
00827     WOLFSENTRY_ACTION_FLAG_DISABLED      = 1U << 0U
00829 } wolfsentry_action_flags_t;
00830
00832 typedef enum {
00833     WOLFSENTRY_ACTION_TYPE_NONE = 0,
00835     WOLFSENTRY_ACTION_TYPE_POST = 1,
00837     WOLFSENTRY_ACTION_TYPE_INSERT = 2,
00839     WOLFSENTRY_ACTION_TYPE_MATCH = 3,
00841     WOLFSENTRY_ACTION_TYPE_UPDATE = 4,
00843     WOLFSENTRY_ACTION_TYPE_DELETE = 5,
00845     WOLFSENTRY_ACTION_TYPE_DECISION = 6
00847 } wolfsentry_action_type_t;
00848
00850 typedef enum {
00851     WOLFSENTRY_ACTION_RES_NONE          = 0U,
00853     WOLFSENTRY_ACTION_RES_ACCEPT        = 1U << 0U,
00855     WOLFSENTRY_ACTION_RES_REJECT        = 1U << 1U,
00857     WOLFSENTRY_ACTION_RES_CONNECT       = 1U << 2U,
00859     WOLFSENTRY_ACTION_RES_DISCONNECT    = 1U << 3U,
00861     WOLFSENTRY_ACTION_RES_DEROGATORY    = 1U << 4U,
00863     WOLFSENTRY_ACTION_RES_COMMENDABLE   = 1U << 5U,
00866     WOLFSENTRY_ACTION_RES_EXCLUDE_REJECT_ROUTES = WOLFSENTRY_ACTION_RES_DEROGATORY |
WOLFSENTRY_ACTION_RES_COMMENDABLE, /* internal use -- overload used by wolfsentry_route_lookup_0() */
00868     WOLFSENTRY_ACTION_RES_STOP          = 1U << 6U,
00870     WOLFSENTRY_ACTION_RES_DEALLOCATED   = 1U << 7U,
00872     WOLFSENTRY_ACTION_RES_INSERTED      = 1U << 8U,
00874     WOLFSENTRY_ACTION_RES_ERROR         = 1U << 9U,
00876     WOLFSENTRY_ACTION_RES_FALLTHROUGH   = 1U << 10U,
00878     WOLFSENTRY_ACTION_RES_UPDATE        = 1U << 11U,
00880     WOLFSENTRY_ACTION_RES_PORT_RESET    = 1U << 12U,
00882     WOLFSENTRY_ACTION_RES_SENDING       = 1U << 13U,
00884     WOLFSENTRY_ACTION_RES_RECEIVED      = 1U << 14U,
00886     WOLFSENTRY_ACTION_RES_BINDING       = 1U << 15U,
00888     WOLFSENTRY_ACTION_RES_LISTENING     = 1U << 16U,
00890     WOLFSENTRY_ACTION_RES_STOPPED_LISTENING = 1U << 17U,
00892     WOLFSENTRY_ACTION_RES_CONNECTING_OUT = 1U << 18U,
00894     WOLFSENTRY_ACTION_RES_CLOSED        = 1U << 19U,
00896     WOLFSENTRY_ACTION_RES_UNREACHABLE    = 1U << 20U,
00898     WOLFSENTRY_ACTION_RES SOCK_ERROR    = 1U << 21U,
00900     WOLFSENTRY_ACTION_RES_CLOSE_WAIT    = 1U << 22U,
00903     WOLFSENTRY_ACTION_RES_RESERVED23    = 1U << 23U,
00905     WOLFSENTRY_ACTION_RES_USER0         = 1U << 24U,
00907     WOLFSENTRY_ACTION_RES_USER1         = 1U << 25U,
00909     WOLFSENTRY_ACTION_RES_USER2         = 1U << 26U,
00911     WOLFSENTRY_ACTION_RES_USER3         = 1U << 27U,
00913     WOLFSENTRY_ACTION_RES_USER4         = 1U << 28U,
00915     WOLFSENTRY_ACTION_RES_USER5         = 1U << 29U,
00917     WOLFSENTRY_ACTION_RES_USER6         = 1U << 30U
00919     /* see macro definition of WOLFSENTRY_ACTION_RES_USER7 below. */
00920
00922 } wolfsentry_action_res_t;
00923
00925 #define WOLFSENTRY_ACTION_RES_USER_BASE WOLFSENTRY_ACTION_RES_USER0
00928 #define WOLFSENTRY_ACTION_RES_USER_SHIFT 24U
00930 #define WOLFSENTRY_ACTION_RES_USER7 (1U << 31U)
00935 struct wolfsentry_table_header;
00936 struct wolfsentry_table_ent_header;
00937 struct wolfsentry_route;
00938 struct wolfsentry_route_table;
00939 struct wolfsentry_event;
00940 struct wolfsentry_event_table;
00941 struct wolfsentry_action;
00942 struct wolfsentry_action_table;
00943 struct wolfsentry_action_list;
00944 struct wolfsentry_action_list_ent;
00945 struct wolfsentry_cursor;
00946
00968 typedef wolfsentry_errcode_t (*wolfsentry_action_callback_t)(
00969     WOLFSENTRY_CONTEXT_ARGS_IN,
00970     const struct wolfsentry_action *action,
00971     void *handler_arg,
00972     void *caller_arg,
00973     const struct wolfsentry_event *trigger_event,
00974     wolfsentry_action_type_t action_type,
00975     const struct wolfsentry_route *trigger_route,
00976     struct wolfsentry_route_table *route_table,

```

```

00977     struct wolfsentry_route *rule_route,
00978     wolfsentry_action_res_t *action_results);
00979
00986 #define WOLFSENTRY_ROUTE_DEFAULT_POLICY_MASK (WOLFSENTRY_ACTION_RES_ACCEPT |
        WOLFSENTRY_ACTION_RES_REJECT | WOLFSENTRY_ACTION_RES_STOP | WOLFSENTRY_ACTION_RES_ERROR)
00990 typedef enum {
00991     WOLFSENTRY_ROUTE_FLAG_NONE = 0U,
00993     /* note the wildcard bits need to be at the start, in order of field
00994      * comparison by wolfsentry_route_key_cmp_1(), due to math in
00995      * wolfsentry_route_lookup_0().
00996      */
00997     WOLFSENTRY_ROUTE_FLAG_SA_FAMILY_WILDCARD = 1U<<0U,
00999     WOLFSENTRY_ROUTE_FLAG_SA_REMOTE_ADDR_WILDCARD = 1U<<1U,
01001     WOLFSENTRY_ROUTE_FLAG_SA_PROTO_WILDCARD = 1U<<2U,
01003     WOLFSENTRY_ROUTE_FLAG_SA_LOCAL_PORT_WILDCARD = 1U<<3U,
01005     WOLFSENTRY_ROUTE_FLAG_SA_LOCAL_ADDR_WILDCARD = 1U<<4U,
01007     WOLFSENTRY_ROUTE_FLAG_SA_REMOTE_PORT_WILDCARD = 1U<<5U,
01009     WOLFSENTRY_ROUTE_FLAG_REMOTE_INTERFACE_WILDCARD = 1U<<6U,
01011     WOLFSENTRY_ROUTE_FLAG_LOCAL_INTERFACE_WILDCARD = 1U<<7U,
01013     WOLFSENTRY_ROUTE_FLAG_PARENT_EVENT_WILDCARD = 1U<<8U,
01015     WOLFSENTRY_ROUTE_FLAG_TCPLIKE_PORT_NUMBERS = 1U<<9U,
01017     WOLFSENTRY_ROUTE_FLAG_DIRECTION_IN = 1U<<10U,
01019     WOLFSENTRY_ROUTE_FLAG_DIRECTION_OUT = 1U<<11U,
01021     WOLFSENTRY_ROUTE_FLAG_REMOTE_ADDR_BITMASK = 1U<<12U,
01023     WOLFSENTRY_ROUTE_FLAG_LOCAL_ADDR_BITMASK = 1U<<13U,
01026     /* immutable above here. */
01027
01028     /* internal use from here... */
01029     WOLFSENTRY_ROUTE_FLAG_IN_TABLE = 1U<<14U,
01031     WOLFSENTRY_ROUTE_FLAG_PENDING_DELETE = 1U<<15U,
01033     WOLFSENTRY_ROUTE_FLAG_INSERT_ACTIONS_CALLED = 1U<<16U,
01035     WOLFSENTRY_ROUTE_FLAG_DELETE_ACTIONS_CALLED = 1U<<17U,
01038     /* ...to here. */
01039
01040     /* mutable below here. */
01041
01042     WOLFSENTRY_ROUTE_FLAG_PENALTYBOXED = 1U<<20U,
01044     WOLFSENTRY_ROUTE_FLAG_GREENLISTED = 1U<<21U,
01046     WOLFSENTRY_ROUTE_FLAG_DONT_COUNT_HITS = 1U<<22U,
01048     WOLFSENTRY_ROUTE_FLAG_DONT_COUNT_CURRENT_CONNECTIONS = 1U<<23U,
01050     WOLFSENTRY_ROUTE_FLAG_PORT_RESET = 1U<<24U
01052 } wolfsentry_route_flags_t;
01053
01054 /* note, _PARENT_EVENT_WILDCARD is excluded because it isn't an intrinsic attribute of network/bus
    traffic. */
01055 #define WOLFSENTRY_ROUTE_WILDCARD_FLAGS
    ((wolfsentry_route_flags_t)WOLFSENTRY_ROUTE_FLAG_PARENT_EVENT_WILDCARD - 1U)
01058 #define WOLFSENTRY_ROUTE_IMMUTABLE_FLAGS ((wolfsentry_route_flags_t)WOLFSENTRY_ROUTE_FLAG_IN_TABLE -
    1U)
01061 #define WOLFSENTRY_ROUTE_INTERNAL_FLAGS ((wolfsentry_route_flags_t) \
01062     (WOLFSENTRY_ROUTE_FLAG_IN_TABLE | \
01063     WOLFSENTRY_ROUTE_FLAG_PENDING_DELETE | \
01064     WOLFSENTRY_ROUTE_FLAG_INSERT_ACTIONS_CALLED | \
01065     WOLFSENTRY_ROUTE_FLAG_DELETE_ACTIONS_CALLED))
01066
01068 #define WOLFSENTRY_ROUTE_FLAG_TRIGGER_WILDCARD WOLFSENTRY_ROUTE_FLAG_PARENT_EVENT_WILDCARD /* xxx
    backward compatibility */
01072 struct wolfsentry_route_endpoint {
01073     wolfsentry_port_t sa_port;
01075     wolfsentry_addr_bits_t addr_len;
01077     byte extra_port_count;
01079     byte interface;
01081 };
01082
01084 struct wolfsentry_route_metadata_exports {
01085     wolfsentry_time_t insert_time;
01087     wolfsentry_time_t last_hit_time;
01089     wolfsentry_time_t last_penaltybox_time;
01091     wolfsentry_time_t purge_after;
01093     uint16_t connection_count;
01095     uint16_t derogatory_count;
01097     uint16_t commendable_count;
01099     wolfsentry_hitcount_t hit_count;
01101 };
01102
01104 struct wolfsentry_route_exports {
01105     const char *parent_event_label;
01107     int parent_event_label_len;
01109     wolfsentry_route_flags_t flags;
01111     wolfsentry_addr_family_t sa_family;
01113     wolfsentry_proto_t sa_proto;
01115     struct wolfsentry_route_endpoint remote;
01117     struct wolfsentry_route_endpoint local;
01119     const byte *remote_address;
01121     const byte *local_address;
01123     const wolfsentry_port_t *remote_extra_ports;
01125     const wolfsentry_port_t *local_extra_ports;

```

```

01127     struct wolfsentry_route_metadata_exports meta;
01129     void *private_data;
01131     size_t private_data_size;
01133 };
01134
01136 struct wolfsentry_sockaddr {
01137     wolfsentry_addr_family_t sa_family;
01139     wolfsentry_proto_t sa_proto;
01141     wolfsentry_port_t sa_port;
01143     wolfsentry_addr_bits_t addr_len;
01145     byte interface;
01147     attr_align_to(4) byte addr[WOLFSENTRY_FLEXIBLE_ARRAY_SIZE];
01149 };
01150
01151 #define WOLFSENTRY_SOCKADDR(n) struct {           \
01152     wolfsentry_addr_family_t sa_family;           \
01153     wolfsentry_proto_t sa_proto;                 \
01154     wolfsentry_port_t sa_port;                   \
01155     wolfsentry_addr_bits_t addr_len;             \
01156     byte interface;                             \
01157     attr_align_to(4) byte addr[WOLFSENTRY_BITS_TO_BYTES(n)]; \
01158 }
01162 typedef enum {
01163     WOLFSENTRY_FORMAT_FLAG_NONE = 0,
01165     WOLFSENTRY_FORMAT_FLAG_ALWAYS_NUMERIC = 1U << 0U
01167 } wolfsentry_format_flags_t;
01168
01176 typedef enum {
01177     WOLFSENTRY_EVENT_FLAG_NONE = 0,
01179     WOLFSENTRY_EVENT_FLAG_IS_PARENT_EVENT = 1U << 0U,
01181     WOLFSENTRY_EVENT_FLAG_IS_SUBEVENT = 1U << 1U
01183 } wolfsentry_event_flags_t;
01184
01186 typedef enum {
01187     WOLFSENTRY_EVENTCONFIG_FLAG_NONE = 0U,
01189     WOLFSENTRY_EVENTCONFIG_FLAG_DEROGATORY_THRESHOLD_IGNORE_COMMENDABLE = 1U << 0U,
01191     WOLFSENTRY_EVENTCONFIG_FLAG_COMMENDABLE_CLEARS_DEROGATORY = 1U << 1U,
01193     WOLFSENTRY_EVENTCONFIG_FLAG_INHIBIT_ACTIONS = 1U << 2U
01195 } wolfsentry_eventconfig_flags_t;
01196
01198 struct wolfsentry_eventconfig {
01199     size_t route_private_data_size;
01201     size_t route_private_data_alignment;
01203     uint32_t max_connection_count;
01205     wolfsentry_hitcount_t derogatory_threshold_for_penaltybox;
01207     wolfsentry_time_t penaltybox_duration;
01209     wolfsentry_time_t route_idle_time_for_purge;
01211     wolfsentry_eventconfig_flags_t flags;
01213     wolfsentry_route_flags_t route_flags_to_add_on_insert;
01215     wolfsentry_route_flags_t route_flags_to_clear_on_insert;
01217     wolfsentry_action_res_t action_res_filter_bits_set;
01219     wolfsentry_action_res_t action_res_filter_bits_unset;
01221     wolfsentry_action_res_t action_res_bits_to_add;
01223     wolfsentry_action_res_t action_res_bits_to_clear;
01225 };
01226
01233 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_time_now_plus_delta(struct wolfsentry_context
01234 *wolfsentry, wolfsentry_time_t td, wolfsentry_time_t *res);
01236 #ifdef WOLFSENTRY_THREADSAFE
01237 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_time_to_timespec(struct wolfsentry_context *wolfsentry,
01238 wolfsentry_time_t t, struct timespec *ts);
01239 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_time_now_plus_delta_timespec(struct wolfsentry_context
01240 *wolfsentry, wolfsentry_time_t td, struct timespec *ts);
01241 #endif
01242
01243 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_get_time(struct wolfsentry_context *wolfsentry,
01244 wolfsentry_time_t *time_p);
01245 WOLFSENTRY_API wolfsentry_time_t wolfsentry_diff_time(struct wolfsentry_context *wolfsentry,
01246 wolfsentry_time_t later, wolfsentry_time_t earlier);
01247 WOLFSENTRY_API wolfsentry_time_t wolfsentry_add_time(struct wolfsentry_context *wolfsentry,
01248 wolfsentry_time_t start_time, wolfsentry_time_t time_interval);
01249 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_to_epoch_time(struct wolfsentry_context *wolfsentry,
01250 wolfsentry_time_t when, time_t *epoch_secs, long *epoch_nsecs);
01251 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_from_epoch_time(struct wolfsentry_context *wolfsentry,
01252 time_t epoch_secs, long epoch_nsecs, wolfsentry_time_t *when);
01253 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_interval_to_seconds(struct wolfsentry_context
01254 *wolfsentry, wolfsentry_time_t howlong, time_t *howlong_secs, long *howlong_nsecs);
01255 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_interval_from_seconds(struct wolfsentry_context
01256 *wolfsentry, time_t howlong_secs, long howlong_nsecs, wolfsentry_time_t *howlong);
01258 WOLFSENTRY_API struct wolfsentry_timecbs *wolfsentry_get_timecbs(struct wolfsentry_context
01259 *wolfsentry);
01266 typedef wolfsentry_errcode_t (*wolfsentry_make_id_cb_t)(void *context, wolfsentry_ent_id_t *id);
01272 WOLFSENTRY_API void *wolfsentry_malloc(WOLFSENTRY_CONTEXT_ARGS_IN, size_t size);
01274 WOLFSENTRY_API void wolfsentry_free(WOLFSENTRY_CONTEXT_ARGS_IN, void *ptr);
01276 WOLFSENTRY_API void *wolfsentry_realloc(WOLFSENTRY_CONTEXT_ARGS_IN, void *ptr, size_t size);
01278 WOLFSENTRY_API void *wolfsentry_memalign(WOLFSENTRY_CONTEXT_ARGS_IN, size_t alignment, size_t size);
01280 WOLFSENTRY_API void wolfsentry_free_aligned(WOLFSENTRY_CONTEXT_ARGS_IN, void *ptr);

```

```

01282 #if (defined(WOLFSENTRY_MALLOC_BUILTINS) && defined(WOLFSENTRY_MALLOC_DEBUG)) ||
    defined(WOLFSENTRY_FOR_DOXYGEN)
01283 WOLFSENTRY_API int _wolfentry_get_n_mallocs(void);
01285 #endif
01286
01287 WOLFSENTRY_API struct wolfentry_allocator *wolfentry_get_allocator(struct wolfentry_context
    *wolfentry);
01292 #if defined(WOLFSENTRY_PROTOCOL_NAMES) || !defined(WOLFSENTRY_NO_JSON)
01296 WOLFSENTRY_API const char *wolfentry_action_res_assoc_by_flag(wolfentry_action_res_t res, unsigned
    int bit);
01298 WOLFSENTRY_API wolfentry_errcode_t wolfentry_action_res_assoc_by_name(const char *bit_name, size_t
    bit_name_len, wolfentry_action_res_t *res);
01301 #endif
01302
01307 WOLFSENTRY_API struct wolfentry_host_platform_interface *wolfentry_get_hpi(struct wolfentry_context
    *wolfentry);
01310 typedef void (*wolfentry_cleanup_callback_t)(
01311     WOLFSENTRY_CONTEXT_ARGS_IN,
01312     void *cleanup_arg);
01315 WOLFSENTRY_API wolfentry_errcode_t wolfentry_cleanup_push(
01316     WOLFSENTRY_CONTEXT_ARGS_IN,
01317     wolfentry_cleanup_callback_t handler,
01318     void *arg);
01321 WOLFSENTRY_API wolfentry_errcode_t wolfentry_cleanup_pop(
01322     WOLFSENTRY_CONTEXT_ARGS_IN,
01323     int execute_p);
01326 WOLFSENTRY_API wolfentry_errcode_t wolfentry_cleanup_all(
01327     WOLFSENTRY_CONTEXT_ARGS_IN);
01336 /* must return _BUFFER_TOO_SMALL and set *addr_internal_bits to an
01337  * accurate value when supplied with a NULL output buf ptr.
01338  * whenever _BUFFER_TOO_SMALL is returned, *addr_*_bits must be set to an
01339  * accurate value.
01340  */
01341 typedef wolfentry_errcode_t (*wolfentry_addr_family_parser_t)(
01342     WOLFSENTRY_CONTEXT_ARGS_IN,
01343     const char *addr_text,
01344     int addr_text_len,
01345     byte *addr_internal,
01346     wolfentry_addr_bits_t *addr_internal_bits);
01349 typedef wolfentry_errcode_t (*wolfentry_addr_family_formatter_t)(
01350     WOLFSENTRY_CONTEXT_ARGS_IN,
01351     const byte *addr_internal,
01352     unsigned int addr_internal_bits,
01353     char *addr_text,
01354     int *addr_text_len);
01357 WOLFSENTRY_API wolfentry_errcode_t wolfentry_addr_family_handler_install(
01358     WOLFSENTRY_CONTEXT_ARGS_IN,
01359     wolfentry_addr_family_t family_bynumber,
01360     const char *family_byname, /* if defined(WOLFSENTRY_PROTOCOL_NAMES), must not be NULL, else
    ignored. */
01361     int family_byname_len,
01362     wolfentry_addr_family_parser_t parser,
01363     wolfentry_addr_family_formatter_t formatter,
01364     int max_addr_bits);
01367 WOLFSENTRY_API wolfentry_errcode_t wolfentry_addr_family_get_parser(
01368     WOLFSENTRY_CONTEXT_ARGS_IN,
01369     wolfentry_addr_family_t family,
01370     wolfentry_addr_family_parser_t *parser);
01373 WOLFSENTRY_API wolfentry_errcode_t wolfentry_addr_family_get_formatter(
01374     WOLFSENTRY_CONTEXT_ARGS_IN,
01375     wolfentry_addr_family_t family,
01376     wolfentry_addr_family_formatter_t *formatter);
01379 WOLFSENTRY_API wolfentry_errcode_t wolfentry_addr_family_handler_remove_bynumber(
01380     WOLFSENTRY_CONTEXT_ARGS_IN,
01381     wolfentry_addr_family_t family_bynumber,
01382     wolfentry_action_res_t *action_results);
01385 struct wolfentry_addr_family_bynumber;
01386
01387 WOLFSENTRY_API wolfentry_errcode_t wolfentry_addr_family_drop_reference(
01388     WOLFSENTRY_CONTEXT_ARGS_IN,
01389     struct wolfentry_addr_family_bynumber *family_bynumber,
01390     wolfentry_action_res_t *action_results);
01393 #ifdef WOLFSENTRY_PROTOCOL_NAMES
01394
01395 WOLFSENTRY_API wolfentry_errcode_t wolfentry_addr_family_handler_remove_byname(
01396     WOLFSENTRY_CONTEXT_ARGS_IN,
01397     const char *family_byname,
01398     int family_byname_len,
01399     wolfentry_action_res_t *action_results);
01402 WOLFSENTRY_API wolfentry_errcode_t wolfentry_addr_family_pton(
01403     WOLFSENTRY_CONTEXT_ARGS_IN,
01404     const char *family_name,
01405     int family_name_len,
01406     wolfentry_addr_family_t *family_number);
01409 WOLFSENTRY_API wolfentry_errcode_t wolfentry_addr_family_ntop(
01410     WOLFSENTRY_CONTEXT_ARGS_IN,
01411     wolfentry_addr_family_t family,

```

```

01412     struct wolfsentry_addr_family_bynumber **addr_family,
01413     const char **family_name);
01416 #endif /* WOLFSENTRY_PROTOCOL_NAMES */
01417
01418 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_addr_family_max_addr_bits(
01419     WOLFSENTRY_CONTEXT_ARGS_IN,
01420     wolfsentry_addr_family_t family,
01421     wolfsentry_addr_bits_t *bits);
01423 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_eventconfig_init(
01424     struct wolfsentry_context *wolfsentry,
01425     struct wolfsentry_eventconfig *config);
01427 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_eventconfig_check(
01428     const struct wolfsentry_eventconfig *config);
01429
01430 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_init_ex(
01431     struct wolfsentry_build_settings caller_build_settings,
01432     WOLFSENTRY_CONTEXT_ARGS_IN_EX(const struct wolfsentry_host_platform_interface *hpi),
01433     const struct wolfsentry_eventconfig *config,
01434     struct wolfsentry_context **wolfsentry,
01435     wolfsentry_init_flags_t flags);
01436 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_init(
01437     struct wolfsentry_build_settings caller_build_settings,
01438     WOLFSENTRY_CONTEXT_ARGS_IN_EX(const struct wolfsentry_host_platform_interface *hpi),
01439     const struct wolfsentry_eventconfig *config,
01440     struct wolfsentry_context **wolfsentry);
01441 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_defaultconfig_get(
01442     WOLFSENTRY_CONTEXT_ARGS_IN,
01443     struct wolfsentry_eventconfig *config);
01444 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_defaultconfig_update(
01445     WOLFSENTRY_CONTEXT_ARGS_IN,
01446     const struct wolfsentry_eventconfig *config);
01447 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_context_flush(WOLFSENTRY_CONTEXT_ARGS_IN);
01448 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_context_free(WOLFSENTRY_CONTEXT_ARGS_IN_EX(struct
    wolfsentry_context **wolfsentry));
01449 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_shutdown(WOLFSENTRY_CONTEXT_ARGS_IN_EX(struct
    wolfsentry_context **wolfsentry));
01450 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_context_inhibit_actions(WOLFSENTRY_CONTEXT_ARGS_IN);
01451 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_context_enable_actions(WOLFSENTRY_CONTEXT_ARGS_IN);
01452
01453 typedef enum {
01454     WOLFSENTRY_CLONE_FLAG_NONE = 0U,
01455     WOLFSENTRY_CLONE_FLAG_AS_AT_CREATION = 1U << 0U,
01456     WOLFSENTRY_CLONE_FLAG_NO_ROUTES = 2U << 0U
01457 } wolfsentry_clone_flags_t;
01458 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_context_clone(WOLFSENTRY_CONTEXT_ARGS_IN, struct
    wolfsentry_context **clone, wolfsentry_clone_flags_t flags);
01459 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_context_exchange(WOLFSENTRY_CONTEXT_ARGS_IN, struct
    wolfsentry_context **wolfsentry2);
01460
01461 #ifdef WOLFSENTRY_THREADSAFE
01462 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_context_lock_mutex(
    WOLFSENTRY_CONTEXT_ARGS_IN);
01463 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_context_lock_mutex_abstimed(
    WOLFSENTRY_CONTEXT_ARGS_IN,
    const struct timespec *abs_timeout);
01464 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_context_lock_mutex_abstimed_ex(
    WOLFSENTRY_CONTEXT_ARGS_IN,
    const struct timespec *abs_timeout,
    wolfsentry_lock_flags_t flags);
01465 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_context_lock_mutex_timed(
    WOLFSENTRY_CONTEXT_ARGS_IN,
    wolfsentry_time_t max_wait);
01466 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_context_lock_mutex_timed_ex(
    WOLFSENTRY_CONTEXT_ARGS_IN,
    wolfsentry_time_t max_wait,
    wolfsentry_lock_flags_t flags);
01467 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_context_lock_shared(
    WOLFSENTRY_CONTEXT_ARGS_IN);
01468 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_context_lock_shared_abstimed(
    WOLFSENTRY_CONTEXT_ARGS_IN,
    const struct timespec *abs_timeout);
01469 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_context_lock_shared_with_reservation_abstimed(
    WOLFSENTRY_CONTEXT_ARGS_IN,
    const struct timespec *abs_timeout);
01470 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_context_lock_shared_timed(
    WOLFSENTRY_CONTEXT_ARGS_IN,
    wolfsentry_time_t max_wait);
01471 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_context_lock_shared_with_reservation_timed(
    WOLFSENTRY_CONTEXT_ARGS_IN,
    wolfsentry_time_t max_wait);
01472 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_context_unlock(
    WOLFSENTRY_CONTEXT_ARGS_IN);
01473 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_context_unlock_and_abandon_reservation(
    WOLFSENTRY_CONTEXT_ARGS_IN);
01474 #else /* !WOLFSENTRY_THREADSAFE */
01475
01476

```

```

01636 #define wolfsentry_context_lock_mutex(x) WOLFSENTRY_ERROR_ENCODE(OK)
01637 #define wolfsentry_context_lock_mutex_abstimed(x, y) WOLFSENTRY_ERROR_ENCODE(OK)
01638 #define wolfsentry_context_lock_mutex_timed(x, y) WOLFSENTRY_ERROR_ENCODE(OK)
01639 #define wolfsentry_context_lock_shared(x) WOLFSENTRY_ERROR_ENCODE(OK)
01640 #define wolfsentry_context_lock_shared_abstimed(x, y) WOLFSENTRY_ERROR_ENCODE(OK)
01641 #define wolfsentry_context_lock_shared_with_reservation_abstimed(x, y) WOLFSENTRY_ERROR_ENCODE(OK)
01642 #define wolfsentry_context_lock_shared_timed(x, y) WOLFSENTRY_ERROR_ENCODE(OK)
01643 #define wolfsentry_context_unlock(x) WOLFSENTRY_ERROR_ENCODE(OK)
01644
01645 #endif /* WOLFSENTRY_THREADSafe */
01646
01649 #define WOLFSENTRY_LENGTH_NULL_TERMINATED (-1)
01663 WOLFSENTRY_API wolfsentry_object_type_t wolfsentry_get_object_type(const void *object);
01664
01672 WOLFSENTRY_API wolfsentry_ent_id_t wolfsentry_get_object_id(const void *object);
01673
01674 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_table_ent_get_by_id(
01675     WOLFSENTRY_CONTEXT_ARGS_IN,
01676     wolfsentry_ent_id_t id,
01677     struct wolfsentry_table_ent_header **ent);
01680 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_object_checkout(WOLFSENTRY_CONTEXT_ARGS_IN, void
*object);
01683 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_object_release(WOLFSENTRY_CONTEXT_ARGS_IN, void
*object, wolfsentry_action_res_t *action_results);
01693 WOLFSENTRY_API wolfsentry_hitcount_t wolfsentry_table_n_inserts(struct wolfsentry_table_header
*table);
01694
01702 WOLFSENTRY_API wolfsentry_hitcount_t wolfsentry_table_n_deletes(struct wolfsentry_table_header
*table);
01703
01710 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_route_check_flags_sensical(
01711     wolfsentry_route_flags_t flags);
01714 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_route_insert_into_table(
01715     WOLFSENTRY_CONTEXT_ARGS_IN,
01716     struct wolfsentry_route_table *route_table,
01717     void *caller_arg, /* passed to action callback(s) as the caller_arg. */
01718     const struct wolfsentry_sockaddr *remote,
01719     const struct wolfsentry_sockaddr *local,
01720     wolfsentry_route_flags_t flags,
01721     const char *event_label,
01722     int event_label_len,
01723     wolfsentry_ent_id_t *id,
01724     wolfsentry_action_res_t *action_results);
01727 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_route_insert_by_exports_into_table(
01728     WOLFSENTRY_CONTEXT_ARGS_IN,
01729     struct wolfsentry_route_table *route_table,
01730     void *caller_arg, /* passed to action callback(s) as the caller_arg. */
01731     const struct wolfsentry_route_exports *route_exports,
01732     wolfsentry_ent_id_t *id,
01733     wolfsentry_action_res_t *action_results);
01752 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_route_insert(
01753     WOLFSENTRY_CONTEXT_ARGS_IN,
01754     void *caller_arg, /* passed to action callback(s) as the caller_arg. */
01755     const struct wolfsentry_sockaddr *remote,
01756     const struct wolfsentry_sockaddr *local,
01757     wolfsentry_route_flags_t flags,
01758     const char *event_label,
01759     int event_label_len,
01760     wolfsentry_ent_id_t *id,
01761     wolfsentry_action_res_t *action_results);
01762
01763 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_route_insert_by_exports(
01764     WOLFSENTRY_CONTEXT_ARGS_IN,
01765     void *caller_arg, /* passed to action callback(s) as the caller_arg. */
01766     const struct wolfsentry_route_exports *route_exports,
01767     wolfsentry_ent_id_t *id,
01768     wolfsentry_action_res_t *action_results);
01771 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_route_insert_into_table_and_check_out(
01772     WOLFSENTRY_CONTEXT_ARGS_IN,
01773     struct wolfsentry_route_table *route_table,
01774     void *caller_arg, /* passed to action callback(s) as the caller_arg. */
01775     const struct wolfsentry_sockaddr *remote,
01776     const struct wolfsentry_sockaddr *local,
01777     wolfsentry_route_flags_t flags,
01778     const char *event_label,
01779     int event_label_len,
01780     struct wolfsentry_route **route,
01781     wolfsentry_action_res_t *action_results);
01784 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_route_insert_by_exports_into_table_and_check_out(
01785     WOLFSENTRY_CONTEXT_ARGS_IN,
01786     struct wolfsentry_route_table *route_table,
01787     void *caller_arg, /* passed to action callback(s) as the caller_arg. */
01788     const struct wolfsentry_route_exports *route_exports,
01789     struct wolfsentry_route **route,
01790     wolfsentry_action_res_t *action_results);
01793 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_route_insert_and_check_out(
01794     WOLFSENTRY_CONTEXT_ARGS_IN,

```

```

01795     void *caller_arg, /* passed to action callback(s) as the caller_arg. */
01796     const struct wolfentry_sockaddr *remote,
01797     const struct wolfentry_sockaddr *local,
01798     wolfentry_route_flags_t flags,
01799     const char *event_label,
01800     int event_label_len,
01801     struct wolfentry_route **route,
01802     wolfentry_action_res_t *action_results);
01803 WOLFENTRY_API wolfentry_errcode_t wolfentry_route_insert_by_exports_and_check_out(
01804     WOLFENTRY_CONTEXT_ARGS_IN,
01805     void *caller_arg, /* passed to action callback(s) as the caller_arg. */
01806     const struct wolfentry_route_exports *route_exports,
01807     struct wolfentry_route **route,
01808     wolfentry_action_res_t *action_results);
01809 WOLFENTRY_API wolfentry_errcode_t wolfentry_route_delete_from_table(
01810     WOLFENTRY_CONTEXT_ARGS_IN,
01811     struct wolfentry_route_table *route_table,
01812     void *caller_arg, /* passed to action callback(s) as the caller_arg. */
01813     const struct wolfentry_sockaddr *remote,
01814     const struct wolfentry_sockaddr *local,
01815     wolfentry_route_flags_t flags,
01816     const char *event_label,
01817     int event_label_len,
01818     wolfentry_action_res_t *action_results,
01819     int *n_deleted);
01820 WOLFENTRY_API wolfentry_errcode_t wolfentry_route_delete(
01821     WOLFENTRY_CONTEXT_ARGS_IN,
01822     void *caller_arg, /* passed to action callback(s) as the caller_arg. */
01823     const struct wolfentry_sockaddr *remote,
01824     const struct wolfentry_sockaddr *local,
01825     wolfentry_route_flags_t flags,
01826     const char *trigger_label,
01827     int trigger_label_len,
01828     wolfentry_action_res_t *action_results,
01829     int *n_deleted);
01830 WOLFENTRY_API wolfentry_errcode_t wolfentry_route_delete_by_id(
01831     WOLFENTRY_CONTEXT_ARGS_IN,
01832     void *caller_arg, /* passed to action callback(s) as the caller_arg. */
01833     wolfentry_ent_id_t id,
01834     const char *trigger_label,
01835     int trigger_label_len,
01836     wolfentry_action_res_t *action_results);
01837 WOLFENTRY_API wolfentry_errcode_t wolfentry_route_get_main_table(
01838     WOLFENTRY_CONTEXT_ARGS_IN,
01839     struct wolfentry_route_table **table);
01840 WOLFENTRY_API wolfentry_errcode_t wolfentry_route_table_iterate_start(
01841     WOLFENTRY_CONTEXT_ARGS_IN,
01842     const struct wolfentry_route_table *table,
01843     struct wolfentry_cursor **cursor);
01844 WOLFENTRY_API wolfentry_errcode_t wolfentry_route_table_iterate_seek_to_head(
01845     const struct wolfentry_route_table *table,
01846     struct wolfentry_cursor *cursor);
01847 WOLFENTRY_API wolfentry_errcode_t wolfentry_route_table_iterate_seek_to_tail(
01848     const struct wolfentry_route_table *table,
01849     struct wolfentry_cursor *cursor);
01850 WOLFENTRY_API wolfentry_errcode_t wolfentry_route_table_iterate_current(
01851     const struct wolfentry_route_table *table,
01852     struct wolfentry_cursor *cursor,
01853     struct wolfentry_route **route);
01854 WOLFENTRY_API wolfentry_errcode_t wolfentry_route_table_iterate_prev(
01855     const struct wolfentry_route_table *table,
01856     struct wolfentry_cursor *cursor,
01857     struct wolfentry_route **route);
01858 WOLFENTRY_API wolfentry_errcode_t wolfentry_route_table_iterate_next(
01859     const struct wolfentry_route_table *table,
01860     struct wolfentry_cursor *cursor,
01861     struct wolfentry_route **route);
01862 WOLFENTRY_API wolfentry_errcode_t wolfentry_route_table_iterate_end(
01863     WOLFENTRY_CONTEXT_ARGS_IN,
01864     const struct wolfentry_route_table *table,
01865     struct wolfentry_cursor **cursor);
01866 WOLFENTRY_API wolfentry_errcode_t wolfentry_route_table_default_policy_set(
01867     WOLFENTRY_CONTEXT_ARGS_IN,
01868     struct wolfentry_route_table *table,
01869     wolfentry_action_res_t default_policy);
01870 WOLFENTRY_API wolfentry_errcode_t wolfentry_route_default_policy_set(

```



```

02005     WOLFSENTRY_CONTEXT_ARGS_IN,
02006     wolfsentry_action_res_t default_policy);
02022 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_route_table_default_policy_get(
02023     WOLFSENTRY_CONTEXT_ARGS_IN,
02024     struct wolfsentry_route_table *table,
02025     wolfsentry_action_res_t *default_policy);
02026
02027 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_route_default_policy_get(
02028     WOLFSENTRY_CONTEXT_ARGS_IN,
02029     wolfsentry_action_res_t *default_policy);
02049 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_route_get_reference(
02050     WOLFSENTRY_CONTEXT_ARGS_IN,
02051     const struct wolfsentry_route_table *table,
02052     const struct wolfsentry_sockaddr *remote,
02053     const struct wolfsentry_sockaddr *local,
02054     wolfsentry_route_flags_t flags,
02055     const char *event_label,
02056     int event_label_len,
02057     int exact_p,
02058     wolfsentry_route_flags_t *inexact_matches,
02059     struct wolfsentry_route **route);
02060
02071 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_route_drop_reference(
02072     WOLFSENTRY_CONTEXT_ARGS_IN,
02073     struct wolfsentry_route *route,
02074     wolfsentry_action_res_t *action_results);
02075
02076 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_route_table_clear_default_event(
02077     WOLFSENTRY_CONTEXT_ARGS_IN,
02078     struct wolfsentry_route_table *table);
02081 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_route_table_set_default_event(
02082     WOLFSENTRY_CONTEXT_ARGS_IN,
02083     struct wolfsentry_route_table *table,
02084     const char *event_label,
02085     int event_label_len);
02088 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_route_table_get_default_event(
02089     WOLFSENTRY_CONTEXT_ARGS_IN,
02090     struct wolfsentry_route_table *table,
02091     char *event_label,
02092     int *event_label_len);
02103 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_route_table_fallthrough_route_get(
02104     WOLFSENTRY_CONTEXT_ARGS_IN,
02105     struct wolfsentry_route_table *route_table,
02106     const struct wolfsentry_route **fallthrough_route);
02107
02116 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_route_get_addrs(
02117     const struct wolfsentry_route *route,
02118     wolfsentry_addr_family_t *af,
02119     wolfsentry_addr_bits_t *local_addr_len,
02120     const byte **local_addr,
02121     wolfsentry_addr_bits_t *remote_addr_len,
02122     const byte **remote_addr);
02123
02139 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_route_export(
02140     WOLFSENTRY_CONTEXT_ARGS_IN,
02141     const struct wolfsentry_route *route,
02142     struct wolfsentry_route_exports *route_exports);
02143
02144 /* returned wolfsentry_event remains valid only as long as the wolfsentry lock
02145  * is held (shared or exclusive), unless the route was obtained via
02146  * wolfsentry_route_get_reference(), in which case it's valid until
02147  * wolfsentry_route_drop_reference()..
02148  */
02158 WOLFSENTRY_API const struct wolfsentry_event *wolfsentry_route_parent_event(const struct
    wolfsentry_route *route);
02159
02160 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_route_event_dispatch_with_table(
02161     WOLFSENTRY_CONTEXT_ARGS_IN,
02162     struct wolfsentry_route_table *route_table,
02163     const struct wolfsentry_sockaddr *remote,
02164     const struct wolfsentry_sockaddr *local,
02165     wolfsentry_route_flags_t flags,
02166     const char *event_label,
02167     int event_label_len,
02168     void *caller_arg, /* passed to action callback(s) as the caller_arg. */
02169     wolfsentry_ent_id_t *id,
02170     wolfsentry_route_flags_t *inexact_matches,
02171     wolfsentry_action_res_t *action_results);
02191 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_route_event_dispatch(
02192     WOLFSENTRY_CONTEXT_ARGS_IN,
02193     const struct wolfsentry_sockaddr *remote,
02194     const struct wolfsentry_sockaddr *local,
02195     wolfsentry_route_flags_t flags,
02196     const char *event_label,
02197     int event_label_len,
02198     void *caller_arg, /* passed to action callback(s). */
02199     wolfsentry_ent_id_t *id,

```



```

02200     wolfsentry_route_flags_t *inexact_matches,
02201     wolfsentry_action_res_t *action_results);
02202
02203 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_route_event_dispatch_with_table_with_initiated_result(
02204     WOLFSENTRY_CONTEXT_ARGS_IN,
02205     struct wolfsentry_route_table *route_table,
02206     const struct wolfsentry_sockaddr *remote,
02207     const struct wolfsentry_sockaddr *local,
02208     wolfsentry_route_flags_t flags,
02209     const char *event_label,
02210     int event_label_len,
02211     void *caller_arg, /* passed to action callback(s) as the caller_arg. */
02212     wolfsentry_ent_id_t *id,
02213     wolfsentry_route_flags_t *inexact_matches,
02214     wolfsentry_action_res_t *action_results);
02215
02216 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_route_event_dispatch_with_initiated_result(
02217     WOLFSENTRY_CONTEXT_ARGS_IN,
02218     const struct wolfsentry_sockaddr *remote,
02219     const struct wolfsentry_sockaddr *local,
02220     wolfsentry_route_flags_t flags,
02221     const char *event_label,
02222     int event_label_len,
02223     void *caller_arg, /* passed to action callback(s). */
02224     wolfsentry_ent_id_t *id,
02225     wolfsentry_route_flags_t *inexact_matches,
02226     wolfsentry_action_res_t *action_results);
02227
02228 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_route_event_dispatch_by_id(
02229     WOLFSENTRY_CONTEXT_ARGS_IN,
02230     wolfsentry_ent_id_t id,
02231     const char *event_label,
02232     int event_label_len,
02233     void *caller_arg, /* passed to action callback(s) as the caller_arg. */
02234     wolfsentry_action_res_t *action_results
02235 );
02236
02237 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_route_event_dispatch_by_id_with_initiated_result(
02238     WOLFSENTRY_CONTEXT_ARGS_IN,
02239     wolfsentry_ent_id_t id,
02240     const char *event_label,
02241     int event_label_len,
02242     void *caller_arg, /* passed to action callback(s) as the caller_arg. */
02243     wolfsentry_action_res_t *action_results
02244 );
02245
02246 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_route_event_dispatch_by_route(
02247     WOLFSENTRY_CONTEXT_ARGS_IN,
02248     struct wolfsentry_route *route,
02249     const char *event_label,
02250     int event_label_len,
02251     void *caller_arg, /* passed to action callback(s) as the caller_arg. */
02252     wolfsentry_action_res_t *action_results
02253 );
02254
02255 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_route_event_dispatch_by_route_with_initiated_result(
02256     WOLFSENTRY_CONTEXT_ARGS_IN,
02257     struct wolfsentry_route *route,
02258     const char *event_label,
02259     int event_label_len,
02260     void *caller_arg, /* passed to action callback(s) as the caller_arg. */
02261     wolfsentry_action_res_t *action_results
02262 );
02263
02264 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_route_table_max_purgeable_routes_get(
02265     WOLFSENTRY_CONTEXT_ARGS_IN,
02266     struct wolfsentry_route_table *table,
02267     wolfsentry_hitcount_t *max_purgeable_routes);
02268
02269 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_route_table_max_purgeable_routes_set(
02270     WOLFSENTRY_CONTEXT_ARGS_IN,
02271     struct wolfsentry_route_table *table,
02272     wolfsentry_hitcount_t max_purgeable_routes);
02273
02274 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_route_table_max_purgeable_idle_time_get(
02275     WOLFSENTRY_CONTEXT_ARGS_IN,
02276     struct wolfsentry_route_table *table,
02277     wolfsentry_time_t *max_purgeable_idle_time);
02278
02279 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_route_table_max_purgeable_idle_time_set(
02280     WOLFSENTRY_CONTEXT_ARGS_IN,
02281     struct wolfsentry_route_table *table,
02282     wolfsentry_time_t max_purgeable_idle_time);
02283
02284 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_route_purge_time_set(
02285     WOLFSENTRY_CONTEXT_ARGS_IN,
02286     struct wolfsentry_route *route,
02287     wolfsentry_time_t purge_after);
02288
02289 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_route_stale_purge(
02290     WOLFSENTRY_CONTEXT_ARGS_IN,
02291     struct wolfsentry_route_table *table,
02292     wolfsentry_action_res_t *action_results);
02293
02294 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_route_stale_purge_one(
02295     WOLFSENTRY_CONTEXT_ARGS_IN,
02296     struct wolfsentry_route_table *table,
02297     wolfsentry_action_res_t *action_results);

```

```

02321 WOLFSENTRY_API wolfentry_errcode_t wolfentry_route_stale_purge_one_opportunistically(
02322     WOLFSENTRY_CONTEXT_ARGS_IN,
02323     struct wolfentry_route_table *table,
02324     wolfentry_action_res_t *action_results);
02337 WOLFSENTRY_API wolfentry_errcode_t wolfentry_route_flush_table(
02338     WOLFSENTRY_CONTEXT_ARGS_IN,
02339     struct wolfentry_route_table *table,
02340     wolfentry_action_res_t *action_results);
02341
02350 WOLFSENTRY_API wolfentry_errcode_t wolfentry_route_bulk_clear_insert_action_status(
02351     WOLFSENTRY_CONTEXT_ARGS_IN,
02352     wolfentry_action_res_t *action_results);
02353
02362 WOLFSENTRY_API wolfentry_errcode_t wolfentry_route_bulk_insert_actions(
02363     WOLFSENTRY_CONTEXT_ARGS_IN,
02364     wolfentry_action_res_t *action_results);
02365
02377 WOLFSENTRY_API wolfentry_errcode_t wolfentry_route_get_private_data(
02378     WOLFSENTRY_CONTEXT_ARGS_IN,
02379     struct wolfentry_route *route,
02380     void **private_data,
02381     size_t *private_data_size);
02382
02391 WOLFSENTRY_API wolfentry_errcode_t wolfentry_route_get_flags(
02392     const struct wolfentry_route *route,
02393     wolfentry_route_flags_t *flags);
02394
02403 WOLFSENTRY_API wolfentry_errcode_t wolfentry_route_get_metadata(
02404     const struct wolfentry_route *route,
02405     struct wolfentry_route_metadata_exports *metadata);
02406
02407 WOLFSENTRY_API wolfentry_errcode_t wolfentry_route_reset_metadata_exports(
02408     struct wolfentry_route_exports *route_exports);
02425 WOLFSENTRY_API wolfentry_errcode_t wolfentry_route_update_flags(
02426     WOLFSENTRY_CONTEXT_ARGS_IN,
02427     struct wolfentry_route *route,
02428     wolfentry_route_flags_t flags_to_set,
02429     wolfentry_route_flags_t flags_to_clear,
02430     wolfentry_route_flags_t *flags_before,
02431     wolfentry_route_flags_t *flags_after,
02432     wolfentry_action_res_t *action_results);
02433
02434 WOLFSENTRY_API wolfentry_errcode_t wolfentry_route_increment_derogatory_count(
02435     WOLFSENTRY_CONTEXT_ARGS_IN,
02436     struct wolfentry_route *route,
02437     int count_to_add,
02438     int *new_derogatory_count_ptr);
02441 WOLFSENTRY_API wolfentry_errcode_t wolfentry_route_increment_commendable_count(
02442     WOLFSENTRY_CONTEXT_ARGS_IN,
02443     struct wolfentry_route *route,
02444     int count_to_add,
02445     int *new_commendable_count);
02448 WOLFSENTRY_API wolfentry_errcode_t wolfentry_route_reset_derogatory_count(
02449     WOLFSENTRY_CONTEXT_ARGS_IN,
02450     struct wolfentry_route *route,
02451     int *old_derogatory_count_ptr);
02454 WOLFSENTRY_API wolfentry_errcode_t wolfentry_route_reset_commendable_count(
02455     WOLFSENTRY_CONTEXT_ARGS_IN,
02456     struct wolfentry_route *route,
02457     int *old_commendable_count_ptr);
02468 WOLFSENTRY_API wolfentry_errcode_t wolfentry_route_set_wildcard(
02469     struct wolfentry_route *route,
02470     wolfentry_route_flags_t wildcards_to_set);
02471
02472 WOLFSENTRY_API wolfentry_errcode_t wolfentry_route_format_address(
02473     WOLFSENTRY_CONTEXT_ARGS_IN,
02474     wolfentry_addr_family_t sa_family,
02475     const byte *addr,
02476     unsigned int addr_bits,
02477     char *buf,
02478     int *buflen);
02481 #if defined(WOLFSENTRY_PROTOCOL_NAMES) || defined(WOLFSENTRY_JSON_DUMP_UTILS) ||
    !defined(WOLFSENTRY_NO_JSON)
02482
02483 WOLFSENTRY_API wolfentry_errcode_t wolfentry_route_flag_assoc_by_flag(
02484     wolfentry_route_flags_t flag,
02485     const char **name);
02488 WOLFSENTRY_API wolfentry_errcode_t wolfentry_route_flag_assoc_by_name(
02489     const char *name,
02490     int len,
02491     wolfentry_route_flags_t *flag);
02494 #endif /* WOLFSENTRY_PROTOCOL_NAMES || WOLFSENTRY_JSON_DUMP_UTILS || !WOLFSENTRY_NO_JSON */
02495
02496 #if !defined(WOLFSENTRY_NO_JSON) || defined(WOLFSENTRY_JSON_DUMP_UTILS)
02497
02498 WOLFSENTRY_API wolfentry_errcode_t wolfentry_route_format_json(
02499     WOLFSENTRY_CONTEXT_ARGS_IN,

```

```

02500     const struct wolfsentry_route *r,
02501     unsigned char **json_out,
02502     size_t *json_out_len,
02503     wolfsentry_format_flags_t flags);
02506 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_route_table_dump_json_start(
02507     WOLFSENTRY_CONTEXT_ARGS_IN,
02508     const struct wolfsentry_route_table *table,
02509     struct wolfsentry_cursor **cursor,
02510     unsigned char **json_out,
02511     size_t *json_out_len,
02512     wolfsentry_format_flags_t flags);
02515 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_route_table_dump_json_next(
02516     WOLFSENTRY_CONTEXT_ARGS_IN,
02517     const struct wolfsentry_route_table *table,
02518     struct wolfsentry_cursor *cursor,
02519     unsigned char **json_out,
02520     size_t *json_out_len,
02521     wolfsentry_format_flags_t flags);
02524 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_route_table_dump_json_end(
02525     WOLFSENTRY_CONTEXT_ARGS_IN,
02526     const struct wolfsentry_route_table *table,
02527     struct wolfsentry_cursor **cursor,
02528     unsigned char **json_out,
02529     size_t *json_out_len,
02530     wolfsentry_format_flags_t flags);
02533 #endif /* !WOLFSENTRY_NO_JSON || WOLFSENTRY_JSON_DUMP_UTILS */
02534
02535 #ifndef WOLFSENTRY_NO_STDIO_STREAMS
02536 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_route_render_flags(wolfsentry_route_flags_t flags, FILE
02537     *f);
02549 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_route_render(WOLFSENTRY_CONTEXT_ARGS_IN, const struct
02550     wolfsentry_route *r, FILE *f);
02560 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_route_exports_render(WOLFSENTRY_CONTEXT_ARGS_IN, const
02561     struct wolfsentry_route_exports *r, FILE *f);
02562 #endif
02562 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_action_insert(
02563     WOLFSENTRY_CONTEXT_ARGS_IN,
02564     const char *label,
02565     int label_len,
02566     wolfsentry_action_flags_t flags,
02567     wolfsentry_action_callback_t handler,
02568     void *handler_arg,
02569     wolfsentry_ent_id_t *id);
02591
02603 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_action_delete(
02604     WOLFSENTRY_CONTEXT_ARGS_IN,
02605     const char *label,
02606     int label_len,
02607     wolfsentry_action_res_t *action_results);
02608
02616 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_action_flush_all(WOLFSENTRY_CONTEXT_ARGS_IN);
02617
02629 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_action_get_reference(
02630     WOLFSENTRY_CONTEXT_ARGS_IN,
02631     const char *label,
02632     int label_len,
02633     struct wolfsentry_action **action);
02634
02645 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_action_drop_reference(
02646     WOLFSENTRY_CONTEXT_ARGS_IN,
02647     struct wolfsentry_action *action,
02648     wolfsentry_action_res_t *action_results);
02649
02657 WOLFSENTRY_API const char *wolfsentry_action_get_label(const struct wolfsentry_action *action);
02658
02667 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_action_get_flags(
02668     struct wolfsentry_action *action,
02669     wolfsentry_action_flags_t *flags);
02670
02682 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_action_update_flags(
02683     struct wolfsentry_action *action,
02684     wolfsentry_action_flags_t flags_to_set,
02685     wolfsentry_action_flags_t flags_to_clear,
02686     wolfsentry_action_flags_t *flags_before,
02687     wolfsentry_action_flags_t *flags_after);
02688
02709 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_event_insert(
02710     WOLFSENTRY_CONTEXT_ARGS_IN,
02711     const char *label,
02712     int label_len,
02713     wolfsentry_priority_t priority,
02714     const struct wolfsentry_eventconfig *config,
02715     wolfsentry_event_flags_t flags,
02716     wolfsentry_ent_id_t *id);
02717
02727 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_event_delete(

```

```
02728     WOLFSENTRY_CONTEXT_ARGS_IN,
02729     const char *label,
02730     int label_len,
02731     wolfentry_action_res_t *action_results);
02732
02740 WOLFSENTRY_API wolfentry_errcode_t wolfentry_event_flush_all(WOLFSENTRY_CONTEXT_ARGS_IN);
02741
02749 WOLFSENTRY_API const char *wolfentry_event_get_label(const struct wolfentry_event *event);
02750
02758 WOLFSENTRY_API wolfentry_event_flags_t wolfentry_event_get_flags(const struct wolfentry_event
    *event);
02759
02771 WOLFSENTRY_API wolfentry_errcode_t wolfentry_event_get_config(
02772     WOLFSENTRY_CONTEXT_ARGS_IN,
02773     const char *label,
02774     int label_len,
02775     struct wolfentry_eventconfig *config);
02776
02788 WOLFSENTRY_API wolfentry_errcode_t wolfentry_event_update_config(
02789     WOLFSENTRY_CONTEXT_ARGS_IN,
02790     const char *label,
02791     int label_len,
02792     const struct wolfentry_eventconfig *config);
02793
02805 WOLFSENTRY_API wolfentry_errcode_t wolfentry_event_get_reference(
02806     WOLFSENTRY_CONTEXT_ARGS_IN,
02807     const char *label,
02808     int label_len,
02809     struct wolfentry_event **event);
02810
02821 WOLFSENTRY_API wolfentry_errcode_t wolfentry_event_drop_reference(
02822     WOLFSENTRY_CONTEXT_ARGS_IN,
02823     struct wolfentry_event *event,
02824     wolfentry_action_res_t *action_results);
02825
02839 WOLFSENTRY_API wolfentry_errcode_t wolfentry_event_action_prepend(
02840     WOLFSENTRY_CONTEXT_ARGS_IN,
02841     const char *event_label,
02842     int event_label_len,
02843     wolfentry_action_type_t which_action_list,
02844     const char *action_label,
02845     int action_label_len);
02846
02860 WOLFSENTRY_API wolfentry_errcode_t wolfentry_event_action_append(
02861     WOLFSENTRY_CONTEXT_ARGS_IN,
02862     const char *event_label,
02863     int event_label_len,
02864     wolfentry_action_type_t which_action_list,
02865     const char *action_label,
02866     int action_label_len);
02867
02883 WOLFSENTRY_API wolfentry_errcode_t wolfentry_event_action_insert_after(
02884     WOLFSENTRY_CONTEXT_ARGS_IN,
02885     const char *event_label,
02886     int event_label_len,
02887     wolfentry_action_type_t which_action_list,
02888     const char *action_label,
02889     int action_label_len,
02890     const char *point_action_label,
02891     int point_action_label_len);
02892
02906 WOLFSENTRY_API wolfentry_errcode_t wolfentry_event_action_delete(
02907     WOLFSENTRY_CONTEXT_ARGS_IN,
02908     const char *event_label,
02909     int event_label_len,
02910     wolfentry_action_type_t which_action_list,
02911     const char *action_label,
02912     int action_label_len);
02913
02926 WOLFSENTRY_API wolfentry_errcode_t wolfentry_event_set_aux_event(
02927     WOLFSENTRY_CONTEXT_ARGS_IN,
02928     const char *event_label,
02929     int event_label_len,
02930     const char *aux_event_label,
02931     int aux_event_label_len);
02932
02933 WOLFSENTRY_API const struct wolfentry_event *wolfentry_event_get_aux_event(
02934     const struct wolfentry_event *event);
02951 WOLFSENTRY_API wolfentry_errcode_t wolfentry_event_action_list_start(
02952     WOLFSENTRY_CONTEXT_ARGS_IN,
02953     const char *event_label,
02954     int event_label_len,
02955     wolfentry_action_type_t which_action_list,
02956     struct wolfentry_action_list_ent **cursor);
02957
02971 WOLFSENTRY_API wolfentry_errcode_t wolfentry_event_action_list_next(
02972     WOLFSENTRY_CONTEXT_ARGS_IN,
```

```

02973     struct wolfsentry_action_list_ent **cursor,
02974     const char **action_label,
02975     int *action_label_len);
02976
02988 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_event_action_list_done(
02989     WOLFSENTRY_CONTEXT_ARGS_IN,
02990     struct wolfsentry_action_list_ent **cursor);
02991
02994 #ifndef WOLFSENTRY_HAVE_JSON_DOM
02995 #include <wolfsentry/centijson_dom.h>
02996 #endif
02997
03003 typedef enum {
03004     WOLFSENTRY_KV_NONE = 0,
03005     WOLFSENTRY_KV_NULL,
03006     WOLFSENTRY_KV_TRUE,
03007     WOLFSENTRY_KV_FALSE,
03008     WOLFSENTRY_KV_UINT,
03009     WOLFSENTRY_KV_SINT,
03010     WOLFSENTRY_KV_FLOAT,
03011     WOLFSENTRY_KV_STRING,
03012     WOLFSENTRY_KV_BYTES,
03013     WOLFSENTRY_KV_JSON,
03014     WOLFSENTRY_KV_FLAG_READONLY = 1<30
03015 } wolfsentry_kv_type_t;
03016
03017 #define WOLFSENTRY_KV_FLAG_MASK WOLFSENTRY_KV_FLAG_READONLY
03021 struct wolfsentry_kv_pair {
03022     int key_len;
03024     wolfsentry_kv_type_t v_type;
03026     union {
03027         uint64_t v_uint;
03029         int64_t v_sint;
03031         double v_float;
03033         size_t string_len;
03035         size_t bytes_len;
03037 #ifndef WOLFSENTRY_HAVE_JSON_DOM
03038         JSON_VALUE v_json;
03039     /* 16 bytes */ 03040 #endif
03041     } a;
03042     byte b[WOLFSENTRY_FLEXIBLE_ARRAY_SIZE];
03047 };
03048
03049 #define WOLFSENTRY_KV_KEY_LEN(kv) ((kv)->key_len)
03051 #define WOLFSENTRY_KV_KEY(kv) ((char *) ((kv)->b))
03053 #define WOLFSENTRY_KV_TYPE(kv) ((uint32_t) (kv)->v_type & ~(uint32_t) WOLFSENTRY_KV_FLAG_MASK)
03055 #define WOLFSENTRY_KV_V_UINT(kv) ((kv)->a.v_uint)
03057 #define WOLFSENTRY_KV_V_SINT(kv) ((kv)->a.v_sint)
03059 #define WOLFSENTRY_KV_V_FLOAT(kv) ((kv)->a.v_float)
03061 #define WOLFSENTRY_KV_V_STRING_LEN(kv) ((kv)->a.string_len)
03063 #define WOLFSENTRY_KV_V_STRING(kv) ((char *) ((kv)->b + (kv)->key_len + 1))
03065 #define WOLFSENTRY_KV_V_BYTES_LEN(kv) ((kv)->a.bytes_len)
03067 #define WOLFSENTRY_KV_V_BYTES(kv) ((kv)->b + (kv)->key_len + 1)
03069 #ifndef WOLFSENTRY_HAVE_JSON_DOM
03070 #define WOLFSENTRY_KV_V_JSON(kv) (&(kv)->a.v_json)
03072 #endif
03073
03074 typedef wolfsentry_errcode_t (*wolfsentry_kv_validator_t)(
03075     WOLFSENTRY_CONTEXT_ARGS_IN,
03076     struct wolfsentry_kv_pair *kv);
03079 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_user_value_set_validator(
03080     WOLFSENTRY_CONTEXT_ARGS_IN,
03081     wolfsentry_kv_validator_t validator,
03082     wolfsentry_action_res_t *action_results);
03085 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_user_value_set_mutability(
03086     WOLFSENTRY_CONTEXT_ARGS_IN,
03087     const char *key,
03088     int key_len,
03089     int mutable);
03092 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_user_value_get_mutability(
03093     WOLFSENTRY_CONTEXT_ARGS_IN,
03094     const char *key,
03095     int key_len,
03096     int *mutable);
03099 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_user_value_get_type(
03100     WOLFSENTRY_CONTEXT_ARGS_IN,
03101     const char *key,
03102     int key_len,
03103     wolfsentry_kv_type_t *type);
03106 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_user_value_delete(
03107     WOLFSENTRY_CONTEXT_ARGS_IN,
03108     const char *key,
03109     int key_len);
03112 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_user_value_store_null(
03113     WOLFSENTRY_CONTEXT_ARGS_IN,
03114     const char *key,
03115     int key_len,

```

```

03116     int overwrite_p);
03119 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_user_value_store_bool(
03120     WOLFSENTRY_CONTEXT_ARGS_IN,
03121     const char *key,
03122     int key_len,
03123     wolfsentry_kv_type_t value,
03124     int overwrite_p);
03127 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_user_value_get_bool(
03128     WOLFSENTRY_CONTEXT_ARGS_IN,
03129     const char *key,
03130     int key_len,
03131     wolfsentry_kv_type_t *value);
03134 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_user_value_store_uint(
03135     WOLFSENTRY_CONTEXT_ARGS_IN,
03136     const char *key,
03137     int key_len,
03138     uint64_t value,
03139     int overwrite_p);
03142 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_user_value_get_uint(
03143     WOLFSENTRY_CONTEXT_ARGS_IN,
03144     const char *key,
03145     int key_len,
03146     uint64_t *value);
03149 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_user_value_store_sint(
03150     WOLFSENTRY_CONTEXT_ARGS_IN,
03151     const char *key,
03152     int key_len,
03153     int64_t value,
03154     int overwrite_p);
03157 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_user_value_get_sint(
03158     WOLFSENTRY_CONTEXT_ARGS_IN,
03159     const char *key,
03160     int key_len,
03161     int64_t *value);
03164 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_user_value_store_double(
03165     WOLFSENTRY_CONTEXT_ARGS_IN,
03166     const char *key,
03167     int key_len,
03168     double value,
03169     int overwrite_p);
03172 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_user_value_get_float(
03173     WOLFSENTRY_CONTEXT_ARGS_IN,
03174     const char *key,
03175     int key_len,
03176     double *value);
03179 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_user_value_store_string(
03180     WOLFSENTRY_CONTEXT_ARGS_IN,
03181     const char *key,
03182     int key_len,
03183     const char *value,
03184     int value_len,
03185     int overwrite_p);
03188 struct wolfsentry_kv_pair_internal;
03189
03196 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_user_value_get_string(
03197     WOLFSENTRY_CONTEXT_ARGS_IN,
03198     const char *key,
03199     int key_len,
03200     const char **value,
03201     int *value_len,
03202     struct wolfsentry_kv_pair_internal **user_value_record);
03203
03204 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_user_value_store_bytes(
03205     WOLFSENTRY_CONTEXT_ARGS_IN,
03206     const char *key,
03207     int key_len,
03208     const byte *value,
03209     int value_len,
03210     int overwrite_p);
03213 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_user_value_store_bytes_base64(
03214     WOLFSENTRY_CONTEXT_ARGS_IN,
03215     const char *key,
03216     int key_len,
03217     const char *value,
03218     int value_len,
03219     int overwrite_p);
03228 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_user_value_get_bytes(
03229     WOLFSENTRY_CONTEXT_ARGS_IN,
03230     const char *key,
03231     int key_len,
03232     const byte **value,
03233     int *value_len,
03234     struct wolfsentry_kv_pair_internal **user_value_record);
03235
03236 #ifndef WOLFSENTRY_HAVE_JSON_DOM
03237 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_user_value_store_json(
03238     WOLFSENTRY_CONTEXT_ARGS_IN,

```

```

03239     const char *key,
03240     int key_len,
03241     JSON_VALUE *value,
03242     int overwrite_p);
03251 WOLFENTRY_API wolfentry_errcode_t wolfentry_user_value_get_json(
03252     WOLFENTRY_CONTEXT_ARGS_IN,
03253     const char *key,
03254     int key_len,
03255     JSON_VALUE **value,
03256     struct wolfentry_kv_pair_internal **user_value_record);
03257 #endif /* WOLFENTRY_HAVE_JSON_DOM */
03258
03259 WOLFENTRY_API wolfentry_errcode_t wolfentry_user_value_release_record(
03260     WOLFENTRY_CONTEXT_ARGS_IN,
03261     struct wolfentry_kv_pair_internal **user_value_record);
03262 WOLFENTRY_API wolfentry_errcode_t wolfentry_kv_pair_export(
03263     WOLFENTRY_CONTEXT_ARGS_IN,
03264     struct wolfentry_kv_pair_internal *kv,
03265     const struct wolfentry_kv_pair **kv_exports);
03270 WOLFENTRY_API wolfentry_errcode_t wolfentry_kv_type_to_string(
03271     wolfentry_kv_type_t type,
03272     const char **out);
03275 WOLFENTRY_API wolfentry_errcode_t wolfentry_kv_render_value(
03276     WOLFENTRY_CONTEXT_ARGS_IN,
03277     const struct wolfentry_kv_pair *kv,
03278     char *out,
03279     int *out_len);
03282 WOLFENTRY_API wolfentry_errcode_t wolfentry_user_values_iterate_start(
03283     WOLFENTRY_CONTEXT_ARGS_IN,
03284     struct wolfentry_cursor **cursor);
03287 WOLFENTRY_API wolfentry_errcode_t wolfentry_user_values_iterate_seek_to_head(
03288     WOLFENTRY_CONTEXT_ARGS_IN,
03289     struct wolfentry_cursor *cursor);
03292 WOLFENTRY_API wolfentry_errcode_t wolfentry_user_values_iterate_seek_to_tail(
03293     WOLFENTRY_CONTEXT_ARGS_IN,
03294     struct wolfentry_cursor *cursor);
03297 WOLFENTRY_API wolfentry_errcode_t wolfentry_user_values_iterate_current(
03298     WOLFENTRY_CONTEXT_ARGS_IN,
03299     struct wolfentry_cursor *cursor,
03300     struct wolfentry_kv_pair_internal **kv);
03303 WOLFENTRY_API wolfentry_errcode_t wolfentry_user_values_iterate_prev(
03304     WOLFENTRY_CONTEXT_ARGS_IN,
03305     struct wolfentry_cursor *cursor,
03306     struct wolfentry_kv_pair_internal **kv);
03309 WOLFENTRY_API wolfentry_errcode_t wolfentry_user_values_iterate_next(
03310     WOLFENTRY_CONTEXT_ARGS_IN,
03311     struct wolfentry_cursor *cursor,
03312     struct wolfentry_kv_pair_internal **kv);
03315 WOLFENTRY_API wolfentry_errcode_t wolfentry_user_values_iterate_end(
03316     WOLFENTRY_CONTEXT_ARGS_IN,
03317     struct wolfentry_cursor **cursor);
03320 #define WOLFENTRY_BASE64_DECODED_BUFSPEC(buf, len) \
03321     (((((len)+3)/4)*3) - ((len) > 1 ? \
03322         ((buf)[(len)-1] == '=' ? \
03323             0) \
03324         - ((len) > 2 ? ((buf)[(len)-2] == '=' ? 0) : 0)) \
03325
03327 WOLFENTRY_API wolfentry_errcode_t wolfentry_base64_decode(
03328     const char *src,
03329     size_t src_len,
03330     byte *dest,
03331     size_t *dest_spc,
03332     int ignore_junk_p);
03337 #ifdef WOLFENTRY_LWIP
03338     #include "wolfentry/wolfentry_lwip.h"
03339 #endif
03340
03341 /* conditionally include wolfentry_util.h last -- none of the above rely on it.
03342 */
03343 #ifndef WOLFENTRY_NO_UTIL_H
03344 #include <wolfentry/wolfentry_util.h>
03345 #endif
03346
03347 #endif /* WOLFENTRY_H */

```

## 10.6 wolfentry/wolfentry\_af.h File Reference

Definitions for address families.

## Macros

- **#define WOLFSENTRY\_AF\_UNSPEC 0**
- **#define WOLFSENTRY\_AF\_UNIX 1**  
*Unix domain sockets.*
- **#define WOLFSENTRY\_AF\_LOCAL 1**  
*POSIX name for WOLFSENTRY\_AF\_UNIX.*
- **#define WOLFSENTRY\_AF\_INET 2**  
*Internet IP Protocol.*
- **#define WOLFSENTRY\_AF\_AX25 3**  
*Amateur Radio AX.25.*
- **#define WOLFSENTRY\_AF\_IPX 4**  
*Novell IPX.*
- **#define WOLFSENTRY\_AF\_APPLETALK 5**  
*AppleTalk DDP.*
- **#define WOLFSENTRY\_AF\_NETROM 6**  
*Amateur Radio NET/ROM.*
- **#define WOLFSENTRY\_AF\_BRIDGE 7**  
*Multiprotocol bridge.*
- **#define WOLFSENTRY\_AF\_ATMPVC 8**  
*ATM PVCs.*
- **#define WOLFSENTRY\_AF\_X25 9**  
*Reserved for X.25 project.*
- **#define WOLFSENTRY\_AF\_INET6 10**  
*IP version 6.*
- **#define WOLFSENTRY\_AF\_ROSE 11**  
*Amateur Radio X.25 PLP.*
- **#define WOLFSENTRY\_AF\_DECnet 12**  
*Reserved for DECnet project.*
- **#define WOLFSENTRY\_AF\_NETBEUI 13**  
*Reserved for 802.2LLC project.*
- **#define WOLFSENTRY\_AF\_SECURITY 14**  
*Security callback pseudo AF.*
- **#define WOLFSENTRY\_AF\_KEY 15**  
*PF\_KEY key management API.*
- **#define WOLFSENTRY\_AF\_NETLINK 16**
- **#define WOLFSENTRY\_AF\_ROUTE WOLFSENTRY\_AF\_NETLINK**  
*Alias to emulate 4.4BSD.*
- **#define WOLFSENTRY\_AF\_PACKET 17**  
*Packet family.*
- **#define WOLFSENTRY\_AF\_ASH 18**  
*Ash.*
- **#define WOLFSENTRY\_AF\_ECONET 19**  
*Acorn Econet.*
- **#define WOLFSENTRY\_AF\_ATMSVC 20**  
*ATM SVCs.*
- **#define WOLFSENTRY\_AF\_RDS 21**  
*RDS sockets.*
- **#define WOLFSENTRY\_AF\_SNA 22**  
*Linux SNA Project (nutters!)*
- **#define WOLFSENTRY\_AF\_IRDA 23**



- IRDA sockets.*
- #define **WOLFSENTRY\_AF\_PPPOX** 24  
*PPPoX sockets.*
- #define **WOLFSENTRY\_AF\_WANPIPE** 25  
*Wanpipe API Sockets.*
- #define **WOLFSENTRY\_AF\_LLC** 26  
*Linux LLC.*
- #define **WOLFSENTRY\_AF\_IB** 27  
*Native InfiniBand address.*
- #define **WOLFSENTRY\_AF\_MPLS** 28  
*MPLS.*
- #define **WOLFSENTRY\_AF\_CAN** 29  
*Controller Area Network.*
- #define **WOLFSENTRY\_AF\_TIPC** 30  
*TIPC sockets.*
- #define **WOLFSENTRY\_AF\_BLUETOOTH** 31  
*Bluetooth sockets.*
- #define **WOLFSENTRY\_AF\_IUCV** 32  
*IUCV sockets.*
- #define **WOLFSENTRY\_AF\_RXRPC** 33  
*RxRPC sockets.*
- #define **WOLFSENTRY\_AF\_ISDN** 34  
*mISDN sockets*
- #define **WOLFSENTRY\_AF\_PHONET** 35  
*Phonet sockets.*
- #define **WOLFSENTRY\_AF\_IEEE802154** 36  
*IEEE802154 sockets.*
- #define **WOLFSENTRY\_AF\_CAIF** 37  
*CAIF sockets.*
- #define **WOLFSENTRY\_AF\_ALG** 38  
*Algorithm sockets.*
- #define **WOLFSENTRY\_AF\_NFC** 39  
*NFC sockets.*
- #define **WOLFSENTRY\_AF\_VSOCK** 40  
*vSockets*
- #define **WOLFSENTRY\_AF\_KCM** 41  
*Kernel Connection Multiplexor.*
- #define **WOLFSENTRY\_AF\_QIPCRTR** 42  
*Qualcomm IPC Router.*
- #define **WOLFSENTRY\_AF\_SMC** 43  
*smc sockets: reserve number for PF\_SMC protocol family that reuses WOLFSENTRY\_AF\_INET address family*
- #define **WOLFSENTRY\_AF\_XDP** 44  
*XDP sockets.*
- #define **WOLFSENTRY\_AF\_BSD\_OFFSET** 100  
*from FreeBSD at commit a56e5ad6, except WOLFSENTRY\_AF\_LINK64, added here.*
- #define **WOLFSENTRY\_AF\_IMPLINK** (**WOLFSENTRY\_AF\_BSD\_OFFSET** + 3)  
*arpanet imp addresses*
- #define **WOLFSENTRY\_AF\_PUP** (**WOLFSENTRY\_AF\_BSD\_OFFSET** + 4)  
*pup protocols: e.g. BSP*
- #define **WOLFSENTRY\_AF\_CHAOS** (**WOLFSENTRY\_AF\_BSD\_OFFSET** + 5)  
*mit CHAOS protocols*

- **#define WOLFSENTRY\_AF\_NETBIOS** ([WOLFSENTRY\\_AF\\_BSD\\_OFFSET](#) + 6)  
*SMB protocols.*
- **#define WOLFSENTRY\_AF\_ISO** ([WOLFSENTRY\\_AF\\_BSD\\_OFFSET](#) + 7)  
*ISO protocols.*
- **#define WOLFSENTRY\_AF\_OSI** [WOLFSENTRY\\_AF\\_ISO](#)
- **#define WOLFSENTRY\_AF\_ECMA** ([WOLFSENTRY\\_AF\\_BSD\\_OFFSET](#) + 8)  
*European computer manufacturers.*
- **#define WOLFSENTRY\_AF\_DATAKIT** ([WOLFSENTRY\\_AF\\_BSD\\_OFFSET](#) + 9)  
*datakit protocols*
- **#define WOLFSENTRY\_AF\_DLI** ([WOLFSENTRY\\_AF\\_BSD\\_OFFSET](#) + 13)  
*DEC Direct data link interface.*
- **#define WOLFSENTRY\_AF\_LAT** ([WOLFSENTRY\\_AF\\_BSD\\_OFFSET](#) + 14)  
*LAT.*
- **#define WOLFSENTRY\_AF\_HYLINK** ([WOLFSENTRY\\_AF\\_BSD\\_OFFSET](#) + 15)  
*NSC Hyperchannel.*
- **#define WOLFSENTRY\_AF\_LINK48** ([WOLFSENTRY\\_AF\\_BSD\\_OFFSET](#) + 18)  
*Link layer interface, explicit EUI-48.*
- **#define WOLFSENTRY\_AF\_LINK** [WOLFSENTRY\\_AF\\_LINK48](#)  
*Link layer interface, implicit EUI-48.*
- **#define WOLFSENTRY\_AF\_LINK64** ([WOLFSENTRY\\_AF\\_BSD\\_OFFSET](#) + 19)  
*Link layer interface, explicit EUI-64.*
- **#define WOLFSENTRY\_AF\_COIP** ([WOLFSENTRY\\_AF\\_BSD\\_OFFSET](#) + 20)  
*connection-oriented IP, aka ST II*
- **#define WOLFSENTRY\_AF\_CNT** ([WOLFSENTRY\\_AF\\_BSD\\_OFFSET](#) + 21)  
*Computer Network Technology.*
- **#define WOLFSENTRY\_AF\_SIP** ([WOLFSENTRY\\_AF\\_BSD\\_OFFSET](#) + 24)  
*Simple Internet Protocol.*
- **#define WOLFSENTRY\_AF\_SLOW** ([WOLFSENTRY\\_AF\\_BSD\\_OFFSET](#) + 33)  
*802.3ad slow protocol*
- **#define WOLFSENTRY\_AF\_SCLUSTER** ([WOLFSENTRY\\_AF\\_BSD\\_OFFSET](#) + 34)  
*Sitara cluster protocol.*
- **#define WOLFSENTRY\_AF\_ARP** ([WOLFSENTRY\\_AF\\_BSD\\_OFFSET](#) + 35)
- **#define WOLFSENTRY\_AF\_IEEE80211** ([WOLFSENTRY\\_AF\\_BSD\\_OFFSET](#) + 37)  
*IEEE 802.11 protocol.*
- **#define WOLFSENTRY\_AF\_INET\_SDP** ([WOLFSENTRY\\_AF\\_BSD\\_OFFSET](#) + 40)  
*OFED Socket Direct Protocol ipv4.*
- **#define WOLFSENTRY\_AF\_INET6\_SDP** ([WOLFSENTRY\\_AF\\_BSD\\_OFFSET](#) + 42)  
*OFED Socket Direct Protocol ipv6.*
- **#define WOLFSENTRY\_AF\_HYPERV** ([WOLFSENTRY\\_AF\\_BSD\\_OFFSET](#) + 43)  
*HyperV sockets.*
- **#define WOLFSENTRY\_AF\_USER\_OFFSET** 256

### 10.6.1 Detailed Description

Definitions for address families.

Included by [wolfentry.h](#).

## 10.7 wolfSentry\_af.h

[Go to the documentation of this file.](#)

```
00001 /*
00002  * wolfSentry_af.h
00003  *
00004  * Copyright (C) 2022-2023 wolfSSL Inc.
00005  *
00006  * This file is part of wolfSentry.
00007  *
00008  * wolfSentry is free software; you can redistribute it and/or modify
00009  * it under the terms of the GNU General Public License as published by
00010  * the Free Software Foundation; either version 2 of the License, or
00011  * (at your option) any later version.
00012  *
00013  * wolfSentry is distributed in the hope that it will be useful,
00014  * but WITHOUT ANY WARRANTY; without even the implied warranty of
00015  * MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
00016  * GNU General Public License for more details.
00017  *
00018  * You should have received a copy of the GNU General Public License
00019  * along with this program; if not, write to the Free Software
00020  * Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1335, USA
00021  */
00022
00029 #ifndef WOLFSENTRY_AF_H
00030 #define WOLFSENTRY_AF_H
00031
00036 /* per Linux kernel 5.12, include/linux/socket.h */
00037
00038 #define WOLFSENTRY_AF_UNSPEC      0
00039 #define WOLFSENTRY_AF_UNIX       1
00040 #define WOLFSENTRY_AF_LOCAL      1
00041 #define WOLFSENTRY_AF_INET       2
00042 #define WOLFSENTRY_AF_AX25       3
00043 #define WOLFSENTRY_AF_IPX        4
00044 #define WOLFSENTRY_AF_APPLETALK  5
00045 #define WOLFSENTRY_AF_NETROM     6
00046 #define WOLFSENTRY_AF_BRIDGE     7
00047 #define WOLFSENTRY_AF_ATMPVC     8
00048 #define WOLFSENTRY_AF_X25        9
00049 #define WOLFSENTRY_AF_INET6     10
00050 #define WOLFSENTRY_AF_ROSE       11
00051 #define WOLFSENTRY_AF_DECnet     12
00052 #define WOLFSENTRY_AF_NETBEUI    13
00053 #define WOLFSENTRY_AF_SECURITY   14
00054 #define WOLFSENTRY_AF_KEY        15
00055 #define WOLFSENTRY_AF_NETLINK    16
00056 #define WOLFSENTRY_AF_ROUTE      WOLFSENTRY_AF_NETLINK
00057 #define WOLFSENTRY_AF_PACKET     17
00058 #define WOLFSENTRY_AF_ASH        18
00059 #define WOLFSENTRY_AF_ECONET     19
00060 #define WOLFSENTRY_AF_ATMSVC     20
00061 #define WOLFSENTRY_AF_RDS        21
00062 #define WOLFSENTRY_AF_SNA        22
00063 #define WOLFSENTRY_AF_IRDA       23
00064 #define WOLFSENTRY_AF_PPPOX      24
00065 #define WOLFSENTRY_AF_WANPIPE    25
00066 #define WOLFSENTRY_AF_LLC        26
00067 #define WOLFSENTRY_AF_IB         27
00068 #define WOLFSENTRY_AF_MPLS       28
00069 #define WOLFSENTRY_AF_CAN        29
00070 #define WOLFSENTRY_AF_TIPC       30
00071 #define WOLFSENTRY_AF_BLUETOOTH  31
00072 #define WOLFSENTRY_AF_IUCV       32
00073 #define WOLFSENTRY_AF_RXRPC      33
00074 #define WOLFSENTRY_AF_ISDN       34
00075 #define WOLFSENTRY_AF_PHONET     35
00076 #define WOLFSENTRY_AF_IEEE802154 36
00077 #define WOLFSENTRY_AF_CAIF       37
00078 #define WOLFSENTRY_AF_ALG        38
00079 #define WOLFSENTRY_AF_NFC        39
00080 #define WOLFSENTRY_AF_VSOCK      40
00081 #define WOLFSENTRY_AF_KCM        41
00082 #define WOLFSENTRY_AF_QIPCRTR    42
00083 #define WOLFSENTRY_AF_SMC        43
00084 #define WOLFSENTRY_AF_XDP        44
00086 #define WOLFSENTRY_AF_BSD_OFFSET 100
00087
00089 #define WOLFSENTRY_AF_IMPLINK    (WOLFSENTRY_AF_BSD_OFFSET + 3)
00090 #define WOLFSENTRY_AF_PUP        (WOLFSENTRY_AF_BSD_OFFSET + 4)
00091 #define WOLFSENTRY_AF_CHAOS      (WOLFSENTRY_AF_BSD_OFFSET + 5)
00092 #define WOLFSENTRY_AF_NETBIOS    (WOLFSENTRY_AF_BSD_OFFSET + 6)
00093 #define WOLFSENTRY_AF_ISO        (WOLFSENTRY_AF_BSD_OFFSET + 7)
00094 #define WOLFSENTRY_AF_OSI        WOLFSENTRY_AF_ISO
```

```

00095 #define WOLFSENTRY_AF_ECMA          (WOLFSENTRY_AF_BSD_OFFSET + 8)
00096 #define WOLFSENTRY_AF_DATAKIT        (WOLFSENTRY_AF_BSD_OFFSET + 9)
00097 #define WOLFSENTRY_AF_DLI            (WOLFSENTRY_AF_BSD_OFFSET + 13)
00098 #define WOLFSENTRY_AF_LAT             (WOLFSENTRY_AF_BSD_OFFSET + 14)
00099 #define WOLFSENTRY_AF_HYLINK         (WOLFSENTRY_AF_BSD_OFFSET + 15)
00100 #define WOLFSENTRY_AF_LINK48         (WOLFSENTRY_AF_BSD_OFFSET + 18)
00101 #define WOLFSENTRY_AF_LINK           WOLFSENTRY_AF_LINK48
00102 #define WOLFSENTRY_AF_LINK64         (WOLFSENTRY_AF_BSD_OFFSET + 19)
00103 #define WOLFSENTRY_AF_COIP           (WOLFSENTRY_AF_BSD_OFFSET + 20)
00104 #define WOLFSENTRY_AF_CNT            (WOLFSENTRY_AF_BSD_OFFSET + 21)
00105 #define WOLFSENTRY_AF_SIP            (WOLFSENTRY_AF_BSD_OFFSET + 24)
00106 #define WOLFSENTRY_AF_SLOW           (WOLFSENTRY_AF_BSD_OFFSET + 33)
00107 #define WOLFSENTRY_AF_SCLUSTER       (WOLFSENTRY_AF_BSD_OFFSET + 34)
00108 #define WOLFSENTRY_AF_ARP            (WOLFSENTRY_AF_BSD_OFFSET + 35)
00109 #define WOLFSENTRY_AF_IEEE80211      (WOLFSENTRY_AF_BSD_OFFSET + 37)
00110 #define WOLFSENTRY_AF_INET_SDP       (WOLFSENTRY_AF_BSD_OFFSET + 40)
00111 #define WOLFSENTRY_AF_INET6_SDP      (WOLFSENTRY_AF_BSD_OFFSET + 42)
00112 #define WOLFSENTRY_AF_HYPERV         (WOLFSENTRY_AF_BSD_OFFSET + 43)
00114 #define WOLFSENTRY_AF_USER_OFFSET 256
00115
00118 #endif /* WOLFSENTRY_AF_H */

```

## 10.8 wolfentry/wolfentry\_errcodes.h File Reference

Definitions for diagnostics.

```
#include <errno.h>
```

### Macros

- **#define WOLFSENTRY\_SOURCE\_ID**

*In each source file in the wolfSentry library, WOLFSENTRY\_SOURCE\_ID is defined to a number that is decoded using `enum wolfentry_source_id`. Application source files that use the below error encoding and rendering macros must also define WOLFSENTRY\_SOURCE\_ID to a number, starting with WOLFSENTRY\_SOURCE\_ID\_USER\_BASE, and can use [wolfentry\\_user\\_source\\_string\\_set\(\)](#) or [WOLFSENTRY\\_REGISTER\\_SOURCE\(\)](#) to arrange for error and warning messages that render the source code file by name.*

- **#define WOLFSENTRY\_ERRCODE\_FMT**

*String-literal macro for formatting `wolfentry_errcode_t` using `printf()`-type functions.*

- **#define WOLFSENTRY\_SOURCE\_ID\_MAX** 127

- **#define WOLFSENTRY\_ERROR\_ID\_MAX** 255

- **#define WOLFSENTRY\_LINE\_NUMBER\_MAX** 65535

- **#define WOLFSENTRY\_ERROR\_DECODE\_ERROR\_CODE(x)**

*Extract the bare error (negative) or success (zero/positive) code from an encoded `wolfentry_errcode_t`*

- **#define WOLFSENTRY\_ERROR\_DECODE\_SOURCE\_ID(x)**

*Extract the bare source file ID from an encoded `wolfentry_errcode_t`*

- **#define WOLFSENTRY\_ERROR\_DECODE\_LINE\_NUMBER(x)**

*Extract the bare source line number from an encoded `wolfentry_errcode_t`*

- **#define WOLFSENTRY\_ERROR\_RECODE(x)**

*Take an encoded `wolfentry_errcode_t` and recode it with the current source ID and line number.*

- **#define WOLFSENTRY\_ERROR\_CODE\_IS(x, name)**

*Take an encoded `wolfentry_errcode_t` `x` and test if its error code matches short-form error name (e.g. `INVALID_ARG`).*

- **#define WOLFSENTRY\_SUCCESS\_CODE\_IS(x, name)**

*Take an encoded `wolfentry_errcode_t` `x` and test if its error code matches short-form success name (e.g. `OK`).*

- **#define WOLFSENTRY\_IS\_FAILURE(x)**

*Evaluates to true if `x` is a `wolfentry_errcode_t` that encodes a failure.*

- **#define WOLFSENTRY\_IS\_SUCCESS(x)**  
*Evaluates to true if `x` is a `wolfentry_errcode_t` that encodes a success.*
- **#define WOLFSENTRY\_ERROR\_FMT**  
*Convenience string-constant macro for formatting a `wolfentry_errcode_t` for rendering by a `printf`-type function.*
- **#define WOLFSENTRY\_ERROR\_FMT\_ARGS(x)**  
*Convenience macro supplying args to match the format directives in `WOLFSENTRY_ERROR_FMT`.*
- **#define WOLFSENTRY\_ERROR\_ENCODE(name)**  
*Compute a `wolfentry_errcode_t` encoding the current source ID and line number, and the designated short-form error name (e.g. `INVALID_ARG`).*
- **#define WOLFSENTRY\_SUCCESS\_ENCODE(x)**  
*Compute a `wolfentry_errcode_t` encoding the current source ID and line number, and the designated short-form success name (e.g. `OK`).*
- **#define WOLFSENTRY\_DEBUG\_CALL\_TRACE**  
*Define to build the library or application to output codepoint and error code info at each return point.*
- **#define WOLFSENTRY\_ERROR\_RETURN(x)**  
*Return a `wolfentry_errcode_t` encoding the current source ID and line number, and the designated short-form error name (e.g. `INVALID_ARG`).*
- **#define WOLFSENTRY\_SUCCESS\_RETURN(x)**  
*Return a `wolfentry_errcode_t` encoding the current source ID and line number, and the designated short-form success name (e.g. `OK`).*
- **#define WOLFSENTRY\_ERROR\_RETURN\_RECODED(x)**  
*Take an encoded `wolfentry_errcode_t`, recode it with the current source ID and line number, and return it.*
- **#define WOLFSENTRY\_ERROR\_REReturn(x)**  
*Return an encoded `wolfentry_errcode_t`.*
- **#define WOLFSENTRY\_RETURN\_VALUE(x)**  
*Return an arbitrary value.*
- **#define WOLFSENTRY\_RETURN\_VOID**  
*Return from a void function.*
- **#define WOLFSENTRY\_SUCCESS\_RETURN\_RECODED(x)**  
*Take an encoded `wolfentry_errcode_t`, recode it with the current source ID and line number, and return it.*
- **#define WOLFSENTRY\_SUCCESS\_REReturn(x)**  
*Return an encoded `wolfentry_errcode_t`.*
- **#define WOLFSENTRY\_UNLOCK\_FOR\_RETURN\_EX(ctx)**
- **#define WOLFSENTRY\_UNLOCK\_FOR\_RETURN()**  
*Unlock a previously locked `wolfentry_context`, and if the unlock fails, return the error.*
- **#define WOLFSENTRY\_UNLOCK\_AND\_UNRESERVE\_FOR\_RETURN\_EX(ctx)**
- **#define WOLFSENTRY\_UNLOCK\_AND\_UNRESERVE\_FOR\_RETURN()**  
*Unlock a previously locked `wolfentry_context`, and abandon a held promotion reservation if any (see `wolfentry_lock_unlock()`), and if the operation fails, return the error.*
- **#define WOLFSENTRY\_MUTEX\_EX(ctx)**  
*Get a mutex on a `wolfentry_context`, evaluating to the resulting `wolfentry_errcode_t`.*
- **#define WOLFSENTRY\_MUTEX\_OR\_RETURN()**
- **#define WOLFSENTRY\_SHARED\_EX(ctx)**  
*Get a mutex on the current context, and on failure, return the `wolfentry_errcode_t`.*
- **#define WOLFSENTRY\_SHARED\_OR\_RETURN()**
- **#define WOLFSENTRY\_PROMOTABLE\_EX(ctx)**  
*Get a shared lock on the current context, and on failure, return the `wolfentry_errcode_t`.*
- **#define WOLFSENTRY\_PROMOTABLE\_OR\_RETURN()**
- **#define WOLFSENTRY\_UNLOCK\_AND\_RETURN(ret)**  
*Get a shared lock with mutex promotion reservation on the current context, and on failure, return the `wolfentry_errcode_t`.*

- **#define WOLFSENTRY\_ERROR\_UNLOCK\_AND\_RETURN(name)**  
*Unlock the current context, and return the supplied `wolfentry_errcode_t`.*
- **#define WOLFSENTRY\_ERROR\_UNLOCK\_AND\_RETURN\_RECODED(x)**  
*Unlock the current context, then take an encoded `wolfentry_errcode_t x`, recode it with the current source ID and line number, and return it.*
- **#define WOLFSENTRY\_ERROR\_UNLOCK\_AND\_RETURN\_EX(ctx, name)**  
*Unlock a previously locked `wolfentry_context ctx`, and return a `wolfentry_errcode_t` encoding the current source ID and line number, and the designated short-form error name (e.g. `INVALID_ARG`).*
- **#define WOLFSENTRY\_ERROR\_UNLOCK\_AND\_RETURN\_RECODED\_EX(ctx, x)**  
*Unlock a previously locked `wolfentry_context ctx`, then take an encoded `wolfentry_errcode_t x`, recode it with the current source ID and line number, and return it.*
- **#define WOLFSENTRY\_ERROR\_UNLOCK\_AND\_RERETURN(x)**  
*Unlock the current context, and return an encoded `wolfentry_errcode_t`.*
- **#define WOLFSENTRY\_ERROR\_RERETURN\_AND\_UNLOCK(y)**  
*Calculate the `wolfentry_errcode_t` return value for an expression `y`, then unlock the current context, and finally, return the encoded `wolfentry_errcode_t`.*
- **#define WOLFSENTRY\_SUCCESS\_UNLOCK\_AND\_RETURN(name)**  
*Unlock the current context, and return a `wolfentry_errcode_t` encoding the current source ID and line number, and the designated short-form success name (e.g. `INVALID_ARG`).*
- **#define WOLFSENTRY\_SUCCESS\_UNLOCK\_AND\_RETURN\_RECODED(x)**  
*Unlock the current context, then take an encoded `wolfentry_errcode_t x`, recode it with the current source ID and line number, and return it.*
- **#define WOLFSENTRY\_SUCCESS\_UNLOCK\_AND\_RERETURN(x)**  
*Unlock the current context, and return an encoded `wolfentry_errcode_t`.*
- **#define WOLFSENTRY\_SUCCESS\_RERETURN\_AND\_UNLOCK(y)**  
*Calculate the `wolfentry_errcode_t` return value for an expression `y`, then unlock the current context, and finally, return the encoded `wolfentry_errcode_t`.*
- **#define WOLFSENTRY\_UNLOCK\_AND\_RETURN\_VALUE(x)**  
*Unlock the current context, and return a value `x`.*
- **#define WOLFSENTRY\_UNLOCK\_AND\_RETURN\_VOID**  
*Unlock the current context, and return void.*
- **#define WOLFSENTRY\_RETURN\_OK**  
*Return a `wolfentry_errcode_t` encoding the current source ID and line number, and the success code `OK`.*
- **#define WOLFSENTRY\_UNLOCK\_AND\_RETURN\_OK**  
*Unlock the current context, and return a `wolfentry_errcode_t` encoding the current source ID and line number, and the success code `OK`.*
- **#define WOLFSENTRY\_RERETURN\_IF\_ERROR(y)**  
*If `wolfentry_errcode_t y` is a failure code, return it.*
- **#define WOLFSENTRY\_UNLOCK\_AND\_RERETURN\_IF\_ERROR(y)**  
*If `wolfentry_errcode_t y` is a failure code, unlock the current context and return the code.*
- **#define WOLFSENTRY\_WARN(fmt, ...)**  
*Render a warning message using `WOLFSENTRY_PRINTF_ERR()`, or if `WOLFSENTRY_NO_STDIO_STREAMS` or `WOLFSENTRY_NO_DIAG_MSGS` is set, `DO_NOTHING`.*
- **#define WOLFSENTRY\_WARN\_ON\_FAILURE(...)**  
*Evaluate the supplied expression, and if the resulting `wolfentry_errcode_t` encodes an error, render the expression and the decoded error using `WOLFSENTRY_PRINTF_ERR()`, but if `WOLFSENTRY_NO_STDIO_STREAMS` or `WOLFSENTRY_NO_DIAG_MSGS` is set, don't render a warning.*
- **#define WOLFSENTRY\_WARN\_ON\_FAILURE\_LIBC(...)**  
*Evaluate the supplied expression, and if it evaluates to a negative value, render the expression and the decoded `errno` using `WOLFSENTRY_PRINTF_ERR()`, but if `WOLFSENTRY_NO_STDIO_STREAMS` or `WOLFSENTRY_NO_DIAG_MSGS` is set, don't render a warning.*
- **#define WOLFSENTRY\_REGISTER\_SOURCE()**  
*Helper macro to call `wolfentry_user_source_string_set()` with appropriate arguments.*
- **#define WOLFSENTRY\_REGISTER\_ERROR(name, msg)**  
*Helper macro to call `wolfentry_user_error_string_set()` with appropriate arguments, given a short-form name and freeform string `msg`.*

## Typedefs

- typedef int32\_t **wolfsentry\_errcode\_t**

*The structured result code type for wolfSentry. It encodes a failure or success code, a source code file ID, and a line number.*

## Enumerations

- enum **wolfsentry\_source\_id** {  
**WOLFSENTRY\_SOURCE\_ID\_UNSET** = 0 ,  
**WOLFSENTRY\_SOURCE\_ID\_ACTIONS\_C** = 1 ,  
**WOLFSENTRY\_SOURCE\_ID\_EVENTS\_C** = 2 ,  
**WOLFSENTRY\_SOURCE\_ID\_WOLFSENTRY\_INTERNAL\_C** = 3 ,  
**WOLFSENTRY\_SOURCE\_ID\_ROUTES\_C** = 4 ,  
**WOLFSENTRY\_SOURCE\_ID\_WOLFSENTRY\_UTIL\_C** = 5 ,  
**WOLFSENTRY\_SOURCE\_ID\_KV\_C** = 6 ,  
**WOLFSENTRY\_SOURCE\_ID\_ADDR\_FAMILIES\_C** = 7 ,  
**WOLFSENTRY\_SOURCE\_ID\_JSON\_LOAD\_CONFIG\_C** = 8 ,  
**WOLFSENTRY\_SOURCE\_ID\_JSON\_JSON\_UTIL\_C** = 9 ,  
**WOLFSENTRY\_SOURCE\_ID\_LWIP\_PACKET\_FILTER\_GLUE\_C** = 10 ,  
**WOLFSENTRY\_SOURCE\_ID\_ACTION\_BUILTINS\_C** = 11 ,  
**WOLFSENTRY\_SOURCE\_ID\_USER\_BASE** = 112 }
- enum **wolfsentry\_error\_id** {  
**WOLFSENTRY\_ERROR\_ID\_OK** = 0 ,  
**WOLFSENTRY\_ERROR\_ID\_NOT\_OK** = -1 ,  
**WOLFSENTRY\_ERROR\_ID\_INTERNAL\_CHECK\_FATAL** = -2 ,  
**WOLFSENTRY\_ERROR\_ID\_SYS\_OP\_FATAL** = -3 ,  
**WOLFSENTRY\_ERROR\_ID\_SYS\_OP\_FAILED** = -4 ,  
**WOLFSENTRY\_ERROR\_ID\_SYS\_RESOURCE\_FAILED** = -5 ,  
**WOLFSENTRY\_ERROR\_ID\_INCOMPATIBLE\_STATE** = -6 ,  
**WOLFSENTRY\_ERROR\_ID\_TIMED\_OUT** = -7 ,  
**WOLFSENTRY\_ERROR\_ID\_INVALID\_ARG** = -8 ,  
**WOLFSENTRY\_ERROR\_ID\_BUSY** = -9 ,  
**WOLFSENTRY\_ERROR\_ID\_INTERRUPTED** = -10 ,  
**WOLFSENTRY\_ERROR\_ID\_NUMERIC\_ARG\_TOO\_BIG** = -11 ,  
**WOLFSENTRY\_ERROR\_ID\_NUMERIC\_ARG\_TOO\_SMALL** = -12 ,  
**WOLFSENTRY\_ERROR\_ID\_STRING\_ARG\_TOO\_LONG** = -13 ,  
**WOLFSENTRY\_ERROR\_ID\_BUFFER\_TOO\_SMALL** = -14 ,  
**WOLFSENTRY\_ERROR\_ID\_IMPLEMENTATION\_MISSING** = -15 ,  
**WOLFSENTRY\_ERROR\_ID\_ITEM\_NOT\_FOUND** = -16 ,  
**WOLFSENTRY\_ERROR\_ID\_ITEM\_ALREADY\_PRESENT** = -17 ,  
**WOLFSENTRY\_ERROR\_ID\_ALREADY\_STOPPED** = -18 ,  
**WOLFSENTRY\_ERROR\_ID\_WRONG\_OBJECT** = -19 ,  
**WOLFSENTRY\_ERROR\_ID\_DATA\_MISSING** = -20 ,  
**WOLFSENTRY\_ERROR\_ID\_NOT\_PERMITTED** = -21 ,  
**WOLFSENTRY\_ERROR\_ID\_ALREADY** = -22 ,  
**WOLFSENTRY\_ERROR\_ID\_CONFIG\_INVALID\_KEY** = -23 ,  
**WOLFSENTRY\_ERROR\_ID\_CONFIG\_INVALID\_VALUE** = -24 ,  
**WOLFSENTRY\_ERROR\_ID\_CONFIG\_OUT\_OF\_SEQUENCE** = -25 ,  
**WOLFSENTRY\_ERROR\_ID\_CONFIG\_UNEXPECTED** = -26 ,  
**WOLFSENTRY\_ERROR\_ID\_CONFIG\_MISPLACED\_KEY** = -27 ,  
**WOLFSENTRY\_ERROR\_ID\_CONFIG\_PARSER** = -28 ,  
**WOLFSENTRY\_ERROR\_ID\_CONFIG\_MISSING\_HANDLER** = -29 ,  
**WOLFSENTRY\_ERROR\_ID\_CONFIG\_JSON\_VALUE\_SIZE** = -30 ,  
**WOLFSENTRY\_ERROR\_ID\_OP\_NOT\_SUPP\_FOR\_PROTO** = -31 ,  
**WOLFSENTRY\_ERROR\_ID\_WRONG\_TYPE** = -32 ,  
**WOLFSENTRY\_ERROR\_ID\_BAD\_VALUE** = -33 ,



```

WOLFSENTRY_ERROR_ID_DEADLOCK_AVERTED = -34 ,
WOLFSENTRY_ERROR_ID_OVERFLOW_AVERTED = -35 ,
WOLFSENTRY_ERROR_ID_LACKING_MUTEX = -36 ,
WOLFSENTRY_ERROR_ID_LACKING_READ_LOCK = -37 ,
WOLFSENTRY_ERROR_ID_LIB_MISMATCH = -38 ,
WOLFSENTRY_ERROR_ID_LIBCONFIG_MISMATCH = -39 ,
WOLFSENTRY_ERROR_ID_IO_FAILED = -40 ,
WOLFSENTRY_ERROR_ID_WRONG_ATTRIBUTES = -41 ,
WOLFSENTRY_ERROR_ID_USER_BASE = -128 ,
WOLFSENTRY_SUCCESS_ID_OK = 0 ,
WOLFSENTRY_SUCCESS_ID_LOCK_OK_AND_GOT_RESV = 1 ,
WOLFSENTRY_SUCCESS_ID_HAVE_MUTEX = 2 ,
WOLFSENTRY_SUCCESS_ID_HAVE_READ_LOCK = 3 ,
WOLFSENTRY_SUCCESS_ID_USED_FALLBACK = 4 ,
WOLFSENTRY_SUCCESS_ID_YES = 5 ,
WOLFSENTRY_SUCCESS_ID_NO = 6 ,
WOLFSENTRY_SUCCESS_ID_ALREADY_OK = 7 ,
WOLFSENTRY_SUCCESS_ID_DEFERRED = 8 ,
WOLFSENTRY_SUCCESS_ID_USER_BASE = 128 }

```

## Functions

- WOLFSENTRY\_API const char \* **wolfentry\_errcode\_source\_string** ([wolfentry\\_errcode\\_t](#) e)  
Return the name of the source code file associated with *wolfentry\_errcode\_t* e, or "unknown user defined source", or "unknown source".
- WOLFSENTRY\_API const char \* **wolfentry\_errcode\_error\_string** ([wolfentry\\_errcode\\_t](#) e)  
Return a description of the failure or success code associated with *wolfentry\_errcode\_t* e, or various "unknown" strings if not known.
- WOLFSENTRY\_API const char \* **wolfentry\_errcode\_error\_name** ([wolfentry\\_errcode\\_t](#) e)  
Return the short name of the failure or success code associated with *wolfentry\_errcode\_t* e, or *wolfentry\_errcode\_error\_string*(e) if not known.
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) **wolfentry\_user\_source\_string\_set** (enum *wolfentry\_errcode\_t* source\_id *wolfentry\_source\_id*, const char \*source\_string)  
Register a source code file so that *wolfentry\_errcode\_source\_string()*, and therefore *WOLFSENTRY\_ERROR\_FMT\_ARGS()* and *WOLFSENTRY\_WARN\_ON\_FAILURE()*, can render it. Note that *source\_string* must be a string constant or otherwise remain valid for the duration of runtime.
- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) **wolfentry\_user\_error\_string\_set** (enum *wolfentry\_errcode\_t* id *wolfentry\_error\_id*, const char \*message\_string)  
Register an error (negative) or success (positive) code, and corresponding message, so that *wolfentry\_errcode\_error\_string()* and therefore *WOLFSENTRY\_ERROR\_FMT\_ARGS()* and *WOLFSENTRY\_WARN\_ON\_FAILURE()*, can render it in human-readable form. Note that *error\_string* must be a string constant or otherwise remain valid for the duration of runtime.

### 10.8.1 Detailed Description

Definitions for diagnostics.

Included by [wolfentry.h](#).



## 10.9 wolfSentry\_errcodes.h

[Go to the documentation of this file.](#)

```

00001 /*
00002  * wolfSentry_errcodes.h
00003  *
00004  * Copyright (C) 2021-2023 wolfSSL Inc.
00005  *
00006  * This file is part of wolfSentry.
00007  *
00008  * wolfSentry is free software; you can redistribute it and/or modify
00009  * it under the terms of the GNU General Public License as published by
00010  * the Free Software Foundation; either version 2 of the License, or
00011  * (at your option) any later version.
00012  *
00013  * wolfSentry is distributed in the hope that it will be useful,
00014  * but WITHOUT ANY WARRANTY; without even the implied warranty of
00015  * MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
00016  * GNU General Public License for more details.
00017  *
00018  * You should have received a copy of the GNU General Public License
00019  * along with this program; if not, write to the Free Software
00020  * Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1335, USA
00021  */
00022
00029 #ifndef WOLFSENTRY_ERRCODES_H
00030 #define WOLFSENTRY_ERRCODES_H
00031
00036 #ifdef WOLFSENTRY_FOR_DOXYGEN
00037 #define WOLFSENTRY_SOURCE_ID
00039 #endif
00040
00041 typedef int32_t wolfSentry_errcode_t;
00042 #ifdef FREERTOS
00043 #define WOLFSENTRY_ERRCODE_FMT "%d"
00044 #elif defined(PRId32)
00045 #define WOLFSENTRY_ERRCODE_FMT "%" PRId32
00046 #else
00047 #define WOLFSENTRY_ERRCODE_FMT "%d"
00049 #endif
00050
00051 /* these must be all-1s */
00052 #define WOLFSENTRY_SOURCE_ID_MAX 127
00053 #define WOLFSENTRY_ERROR_ID_MAX 255
00054 #define WOLFSENTRY_LINE_NUMBER_MAX 65535
00055
00058 #define WOLFSENTRY_ERROR_ENCODE_0(x) (((x) < 0) ?
00059     -(((~(x)) & WOLFSENTRY_ERROR_ID_MAX)
00060       | (((__LINE__ & WOLFSENTRY_LINE_NUMBER_MAX) << 8)
00061         | ((WOLFSENTRY_SOURCE_ID & WOLFSENTRY_SOURCE_ID_MAX) << 24)))
00062     :
00063     (((x) & WOLFSENTRY_ERROR_ID_MAX)
00064       | (((__LINE__ & WOLFSENTRY_LINE_NUMBER_MAX) << 8)
00065         | ((WOLFSENTRY_SOURCE_ID & WOLFSENTRY_SOURCE_ID_MAX) << 24)))
00066
00067 #if defined(__GNUC__) && !defined(__STRICT_ANSI__)
00068 #define WOLFSENTRY_ERROR_ENCODE_1(x) ({
00069     wolfSentry_errcode_t _xret = (x);
00070     wolfSentry_static_assert2(((x) >= -WOLFSENTRY_ERROR_ID_MAX)
00071       && ((x) <= WOLFSENTRY_ERROR_ID_MAX),
00072       "error code must be -"
00073       _q(WOLFSENTRY_ERROR_ID_MAX)
00074       " <= e <= "
00075       _q(WOLFSENTRY_ERROR_ID_MAX) )
00076     wolfSentry_static_assert2(__LINE__ <= WOLFSENTRY_LINE_NUMBER_MAX,
00077       "line number must be 1-" _q(WOLFSENTRY_LINE_NUMBER_MAX) )
00078     wolfSentry_static_assert2((WOLFSENTRY_SOURCE_ID >= 0)
00079       && (WOLFSENTRY_SOURCE_ID <= 0x7f),
00080       "source file ID must be 0-" _q(WOLFSENTRY_SOURCE_ID_MAX) )
00081     WOLFSENTRY_ERROR_ENCODE_0(_xret);
00082 })
00083 #else
00084 #define WOLFSENTRY_ERROR_ENCODE_1(x) WOLFSENTRY_ERROR_ENCODE_0(x)
00085 #endif
00086
00087 #define WOLFSENTRY_ERROR_DECODE_ERROR_CODE_1(x) ((int)(((x) < 0) ? -(~(x) & WOLFSENTRY_ERROR_ID_MAX) :
00088     ((x) & WOLFSENTRY_ERROR_ID_MAX)))
00089 #define WOLFSENTRY_ERROR_DECODE_SOURCE_ID_1(x) ((int)(((x) < 0) ? (((~(x)) >> 24) : ((x) >> 24)))
00090 #define WOLFSENTRY_ERROR_DECODE_LINE_NUMBER_1(x) ((int)(((x) < 0) ? (((~(x)) >> 8) &
00091     WOLFSENTRY_LINE_NUMBER_MAX) : (((x) >> 8) & WOLFSENTRY_LINE_NUMBER_MAX)))
00092
00093 #ifdef WOLFSENTRY_NO_INLINE
00094
00095 #if defined(__GNUC__) && !defined(__STRICT_ANSI__)
00096 #define WOLFSENTRY_ERROR_DECODE_ERROR_CODE(x) ({ wolfSentry_errcode_t _xret = (x);
00097     WOLFSENTRY_ERROR_DECODE_ERROR_CODE_1(_xret); })

```

```

00098 #define WOLFSENTRY_ERROR_DECODE_SOURCE_ID(x) ({ wolfentry_errcode_t _xret = (x);
WOLFSENTRY_ERROR_DECODE_SOURCE_ID_1(_xret); })
00100 #define WOLFSENTRY_ERROR_DECODE_LINE_NUMBER(x) ({ wolfentry_errcode_t _xret = (x);
WOLFSENTRY_ERROR_DECODE_LINE_NUMBER_1(_xret); })
00102 #else
00103 #define WOLFSENTRY_ERROR_DECODE_ERROR_CODE(x) WOLFSENTRY_ERROR_DECODE_ERROR_CODE_1(x)
00104 #define WOLFSENTRY_ERROR_DECODE_SOURCE_ID(x) WOLFSENTRY_ERROR_DECODE_SOURCE_ID_1(x)
00105 #define WOLFSENTRY_ERROR_DECODE_LINE_NUMBER(x) WOLFSENTRY_ERROR_DECODE_LINE_NUMBER_1(x)
00106 #endif
00107
00108 #else
00109
00110 static inline int WOLFSENTRY_ERROR_DECODE_ERROR_CODE(wolfentry_errcode_t x) {
00111     return WOLFSENTRY_ERROR_DECODE_ERROR_CODE_1(x);
00112 }
00113 static inline int WOLFSENTRY_ERROR_DECODE_SOURCE_ID(wolfentry_errcode_t x) {
00114     return WOLFSENTRY_ERROR_DECODE_SOURCE_ID_1(x);
00115 }
00116 static inline int WOLFSENTRY_ERROR_DECODE_LINE_NUMBER(wolfentry_errcode_t x) {
00117     return WOLFSENTRY_ERROR_DECODE_LINE_NUMBER_1(x);
00118 }
00119
00120 #endif
00121
00122 #define WOLFSENTRY_ERROR_RECODE(x) WOLFSENTRY_ERROR_ENCODE_0(WOLFSENTRY_ERROR_DECODE_ERROR_CODE(x))
00124 #define WOLFSENTRY_ERROR_CODE_IS(x, name) (WOLFSENTRY_ERROR_DECODE_ERROR_CODE(x) ==
WOLFSENTRY_ERROR_ID_ ## name)
00126 #define WOLFSENTRY_SUCCESS_CODE_IS(x, name) (WOLFSENTRY_ERROR_DECODE_ERROR_CODE(x) ==
WOLFSENTRY_SUCCESS_ID_ ## name)
00129 #define WOLFSENTRY_IS_FAILURE(x) ((x)<0)
00131 #define WOLFSENTRY_IS_SUCCESS(x) ((x)>=0)
00134 #ifndef WOLFSENTRY_ERROR_STRINGS
00135 #define WOLFSENTRY_ERROR_FMT "code " WOLFSENTRY_ERRCODE_FMT " (%s), src " WOLFSENTRY_ERRCODE_FMT "
(%s), line " WOLFSENTRY_ERRCODE_FMT
00137 #define WOLFSENTRY_ERROR_FMT_ARGS(x) WOLFSENTRY_ERROR_DECODE_ERROR_CODE(x),
wolfentry_errcode_error_string(x), WOLFSENTRY_ERROR_DECODE_SOURCE_ID(x),
wolfentry_errcode_source_string(x), WOLFSENTRY_ERROR_DECODE_LINE_NUMBER(x)
00139 #else
00140 #define WOLFSENTRY_ERROR_FMT "code " WOLFSENTRY_ERRCODE_FMT ", src " WOLFSENTRY_ERRCODE_FMT ", line "
WOLFSENTRY_ERRCODE_FMT
00141 #define WOLFSENTRY_ERROR_FMT_ARGS(x) WOLFSENTRY_ERROR_DECODE_ERROR_CODE(x),
WOLFSENTRY_ERROR_DECODE_SOURCE_ID(x), WOLFSENTRY_ERROR_DECODE_LINE_NUMBER(x)
00142 #endif /* WOLFSENTRY_ERROR_STRINGS */
00143
00144 #define WOLFSENTRY_ERROR_ENCODE(name) WOLFSENTRY_ERROR_ENCODE_0(WOLFSENTRY_ERROR_ID_ ## name)
00146 #define WOLFSENTRY_SUCCESS_ENCODE(x) WOLFSENTRY_ERROR_ENCODE_0(WOLFSENTRY_SUCCESS_ID_ ## x)
00149 #ifndef WOLFSENTRY_FOR_DOXYGEN
00150 #define WOLFSENTRY_DEBUG_CALL_TRACE
00161 #undef WOLFSENTRY_DEBUG_CALL_TRACE
00162 #endif
00163
00164 #if defined(WOLFSENTRY_DEBUG_CALL_TRACE) && !defined(WOLFSENTRY_NO_STDIO_STREAMS)
00165     #define WOLFSENTRY_ERROR_RETURN(x) WOLFSENTRY_ERROR_RETURN_1(WOLFSENTRY_ERROR_ID_ ## x)
00166     #define WOLFSENTRY_SUCCESS_RETURN(x) WOLFSENTRY_ERROR_RETURN_1(WOLFSENTRY_SUCCESS_ID_ ## x)
00167     #if defined(WOLFSENTRY_ERROR_STRINGS) && defined(__GNUC__) && !defined(__STRICT_ANSI__)
00168         #ifdef WOLFSENTRY_CALL_DEPTH_RETURNS_STRING
00169             WOLFSENTRY_API const char *_wolfentry_call_depth(void);
00170             #define _INDENT_FMT "%s"
00171             #define _INDENT_ARGS _wolfentry_call_depth()
00172             #else
00173             WOLFSENTRY_API unsigned int _wolfentry_call_depth(void);
00174             #define _INDENT_FMT "%*s"
00175             #define _INDENT_ARGS _wolfentry_call_depth(), ""
00176             #endif
00177             #define WOLFSENTRY_ERROR_RETURN_1(x) do { const char *_fn = strrchr(__FILE__, '/'); if (_fn) {
++_fn; } else { _fn = __FILE__; } WOLFSENTRY_PRINTF_ERR(_INDENT_FMT "%s L%d %s(): return %d (%s)\n",
_INDENT_ARGS, _fn, _LINE_, _FUNCTION_, x, wolfentry_errcode_error_name(x)); return
WOLFSENTRY_ERROR_ENCODE_1(x); } while (0)
00178             #define WOLFSENTRY_ERROR_RETURN_RECODED(x) do { wolfentry_errcode_t _xret = (x); const char
*_fn = strrchr(__FILE__, '/'); if (_fn) { ++_fn; } else { _fn = __FILE__; }
WOLFSENTRY_PRINTF_ERR(_INDENT_FMT "%s L%d %s(): return-recoded %d (%s)\n", _INDENT_ARGS, _fn,
_LINE_, _FUNCTION_, WOLFSENTRY_ERROR_DECODE_ERROR_CODE(_xret),
wolfentry_errcode_error_name(_xret)); return
WOLFSENTRY_ERROR_ENCODE_0(WOLFSENTRY_ERROR_DECODE_ERROR_CODE(_xret)); } while (0)
00179             #define WOLFSENTRY_ERROR_RERETURN(x) do { wolfentry_errcode_t _xret = (x); const char *_fn =
strrchr(__FILE__, '/'); if (_fn) { ++_fn; } else { _fn = __FILE__; } WOLFSENTRY_PRINTF_ERR(_INDENT_FMT
"%s L%d %s(): rerecord %d (%s)\n", _INDENT_ARGS, _fn, _LINE_, _FUNCTION_,
WOLFSENTRY_ERROR_DECODE_ERROR_CODE(_xret), wolfentry_errcode_error_name(_xret)); return (_xret); }
while (0)
00180             #define WOLFSENTRY_RETURN_VALUE(x) do { const char *_fn = strrchr(__FILE__, '/'); if (_fn) {
++_fn; } else { _fn = __FILE__; } WOLFSENTRY_PRINTF_ERR(_INDENT_FMT "%s L%d %s(): return value\n",
_INDENT_ARGS, _fn, _LINE_, _FUNCTION_); return (x); } while (0)
00181             #define WOLFSENTRY_RETURN_VOID do { const char *_fn = strrchr(__FILE__, '/'); if (_fn) {
++_fn; } else { _fn = __FILE__; } WOLFSENTRY_PRINTF_ERR(_INDENT_FMT "%s L%d %s(): return void\n",
_INDENT_ARGS, _fn, _LINE_, _FUNCTION_); return; } while (0)
00182             #elif defined(WOLFSENTRY_ERROR_STRINGS)
00183             #define WOLFSENTRY_ERROR_RETURN_1(x) do { const char *_fn = strrchr(__FILE__, '/'); if (_fn) {

```

```

++_fn; } else { _fn = __FILE__; } WOLFSENTRY_PRINTF_ERR("%s L%d: return %d (%s)\n", _fn, __LINE__, x,
wolfentry_errcode_error_name(x)); return WOLFSENTRY_ERROR_ENCODE_1(x); } while (0)
00184 #define WOLFSENTRY_ERROR_RETURN_RECODED(x) do { wolfentry_errcode_t _xret = (x); const char
*_fn = strrchr(__FILE__, '/'); if (_fn) { ++_fn; } else { _fn = __FILE__; } WOLFSENTRY_PRINTF_ERR("%s L%d:
L%d: return-recoded %d (%s)\n", _fn, __LINE__, WOLFSENTRY_ERROR_DECODE_ERROR_CODE(_xret),
wolfentry_errcode_error_name(_xret)); return
WOLFSENTRY_ERROR_ENCODE_0(WOLFSENTRY_ERROR_DECODE_ERROR_CODE(_xret)); } while (0)
00185 #define WOLFSENTRY_ERROR_RERETURN(x) do { wolfentry_errcode_t _xret = (x); const char *_fn =
strrchr(__FILE__, '/'); if (_fn) { ++_fn; } else { _fn = __FILE__; } WOLFSENTRY_PRINTF_ERR("%s L%d:
rereturn %d (%s)\n", _fn, __LINE__, WOLFSENTRY_ERROR_DECODE_ERROR_CODE(_xret),
wolfentry_errcode_error_name(_xret)); return (_xret); } while (0)
00186 #define WOLFSENTRY_RETURN_VALUE(x) do { const char *_fn = strrchr(__FILE__, '/'); if (_fn) {
++_fn; } else { _fn = __FILE__; } WOLFSENTRY_PRINTF_ERR("%s L%d: return value\n", _fn, __LINE__);
return (x); } while (0)
00187 #define WOLFSENTRY_RETURN_VOID do { const char *_fn = strrchr(__FILE__, '/'); if (_fn) {
++_fn; } else { _fn = __FILE__; } WOLFSENTRY_PRINTF_ERR("%s L%d: return void\n", _fn, __LINE__);
return; } while (0)
00188 #else
00189 #define WOLFSENTRY_ERROR_RETURN_1(x) do { const char *_fn = strrchr(__FILE__, '/'); if (_fn) {
++_fn; } else { _fn = __FILE__; } WOLFSENTRY_PRINTF_ERR("%s L%d: return %d\n", _fn, __LINE__, x);
return WOLFSENTRY_ERROR_ENCODE_1(x); } while (0)
00190 #define WOLFSENTRY_ERROR_RETURN_RECODED(x) do { wolfentry_errcode_t _xret = (x); const char
*_fn = strrchr(__FILE__, '/'); if (_fn) { ++_fn; } else { _fn = __FILE__; } WOLFSENTRY_PRINTF_ERR("%s
L%d: return-recoded %d\n", _fn, __LINE__, WOLFSENTRY_ERROR_DECODE_ERROR_CODE(_xret)); return
WOLFSENTRY_ERROR_ENCODE_0(WOLFSENTRY_ERROR_DECODE_ERROR_CODE(_xret)); } while (0)
00191 #define WOLFSENTRY_ERROR_RERETURN(x) do { wolfentry_errcode_t _xret = (x); const char *_fn =
strrchr(__FILE__, '/'); if (_fn) { ++_fn; } else { _fn = __FILE__; } WOLFSENTRY_PRINTF_ERR("%s L%d:
rereturn %d\n", _fn, __LINE__, WOLFSENTRY_ERROR_DECODE_ERROR_CODE(_xret)); return (_xret); } while (0)
00192 #define WOLFSENTRY_RETURN_VALUE(x) do { const char *_fn = strrchr(__FILE__, '/'); if (_fn) {
++_fn; } else { _fn = __FILE__; } WOLFSENTRY_PRINTF_ERR("%s L%d: return value\n", _fn, __LINE__);
return (x); } while (0)
00193 #define WOLFSENTRY_RETURN_VOID do { const char *_fn = strrchr(__FILE__, '/'); if (_fn) {
++_fn; } else { _fn = __FILE__; } WOLFSENTRY_PRINTF_ERR("%s L%d: return void\n", _fn, __LINE__);
return; } while (0)
00194 #endif
00195 #else
00196 #define WOLFSENTRY_ERROR_RETURN(x) return WOLFSENTRY_ERROR_ENCODE(x)
00198 #define WOLFSENTRY_SUCCESS_RETURN(x) return WOLFSENTRY_SUCCESS_ENCODE(x)
00200 #define WOLFSENTRY_ERROR_RETURN_RECODED(x) return
WOLFSENTRY_ERROR_ENCODE_0(WOLFSENTRY_ERROR_DECODE_ERROR_CODE(x))
00202 #define WOLFSENTRY_ERROR_RERETURN(x) return (x)
00204 #define WOLFSENTRY_RETURN_VALUE(x) return (x)
00206 #define WOLFSENTRY_RETURN_VOID return
00208 #endif
00209
00210 #define WOLFSENTRY_SUCCESS_RETURN_RECODED(x) WOLFSENTRY_ERROR_RETURN_RECODED(x)
00212 #define WOLFSENTRY_SUCCESS_RERETURN(x) WOLFSENTRY_ERROR_RERETURN(x)
00215 #ifdef WOLFSENTRY_THREADSafe
00216
00217 #define WOLFSENTRY_UNLOCK_FOR_RETURN_EX(ctx) do {
00218     wolfentry_errcode_t _lock_ret;
00219     if ((_lock_ret = wolfentry_context_unlock(ctx, thread)) < 0) { \
00220         WOLFSENTRY_ERROR_RERETURN(_lock_ret);
00221     }
00222 } while (0)
00225 #define WOLFSENTRY_UNLOCK_FOR_RETURN() WOLFSENTRY_UNLOCK_FOR_RETURN_EX(wolfentry)
00228 #define WOLFSENTRY_UNLOCK_AND_UNRESERVE_FOR_RETURN_EX(ctx) do { \
00229     wolfentry_errcode_t _lock_ret;
00230     if ((_lock_ret = wolfentry_context_unlock_and_abandon_reservation(ctx, thread)) < 0) { \
00231         WOLFSENTRY_ERROR_RERETURN(_lock_ret);
00232     }
00233 } while (0)
00236 #define WOLFSENTRY_UNLOCK_AND_UNRESERVE_FOR_RETURN()
WOLFSENTRY_UNLOCK_AND_UNRESERVE_FOR_RETURN_EX(wolfentry)
00239 #define WOLFSENTRY_MUTEX_EX(ctx) wolfentry_context_lock_mutex_abstimed(ctx, thread, NULL)
00242 #define WOLFSENTRY_MUTEX_OR_RETURN() do { \
00243     wolfentry_errcode_t _lock_ret;
00244     if ((_lock_ret = WOLFSENTRY_MUTEX_EX(wolfentry)) < 0) { \
00245         WOLFSENTRY_ERROR_RERETURN(_lock_ret);
00246     } while (0)
00249 #define WOLFSENTRY_SHARED_EX(ctx) wolfentry_context_lock_shared_abstimed(ctx, thread, NULL)
00252 #define WOLFSENTRY_SHARED_OR_RETURN() do { \
00253     wolfentry_errcode_t _lock_ret;
00254     if (thread == NULL)
00255         _lock_ret = WOLFSENTRY_MUTEX_EX(wolfentry);
00256     else
00257         _lock_ret = WOLFSENTRY_SHARED_EX(wolfentry);
00258     WOLFSENTRY_RERETURN_IF_ERROR(_lock_ret);
00259 } while (0)
00262 #define WOLFSENTRY_PROMOTABLE_EX(ctx)
wolfentry_context_lock_shared_with_reservation_abstimed(ctx, thread, NULL)
00265 #define WOLFSENTRY_PROMOTABLE_OR_RETURN() do { \
00266     wolfentry_errcode_t _lock_ret;
00267     if (thread == NULL)
00268         _lock_ret = WOLFSENTRY_MUTEX_EX(wolfentry);
00269     else
00270         _lock_ret = WOLFSENTRY_PROMOTABLE_EX(wolfentry); \

```

```

00271         WOLFSENTRY_RERETURN_IF_ERROR(_lock_ret);           \
00272     } while (0)
00275     #define WOLFSENTRY_UNLOCK_AND_RETURN(ret) do {           \
00276         WOLFSENTRY_UNLOCK_FOR_RETURN();                     \
00277         WOLFSENTRY_ERROR_RERETURN(ret);                      \
00278     } while (0)
00281 #else
00282     #define WOLFSENTRY_UNLOCK_FOR_RETURN() DO_NOTHING
00283     #define WOLFSENTRY_UNLOCK_FOR_RETURN_EX(ctx) DO_NOTHING
00284     #define WOLFSENTRY_MUTEX_EX(ctx) ((void)(ctx), WOLFSENTRY_ERROR_ENCODE(OK))
00285     #define WOLFSENTRY_MUTEX_OR_RETURN() (void)wolfentry
00286     #define WOLFSENTRY_SHARED_EX(ctx) (void)(ctx)
00287     #define WOLFSENTRY_SHARED_OR_RETURN() (void)wolfentry
00288     #define WOLFSENTRY_PROMOTABLE_EX(ctx) (void)(ctx)
00289     #define WOLFSENTRY_PROMOTABLE_OR_RETURN() (void)wolfentry
00290     #define WOLFSENTRY_UNLOCK_AND_RETURN(lock, ret) WOLFSENTRY_ERROR_RERETURN(ret)
00291 #endif
00292
00293 #define WOLFSENTRY_ERROR_UNLOCK_AND_RETURN(name) do { WOLFSENTRY_UNLOCK_FOR_RETURN();
WOLFSENTRY_ERROR_RETURN(name); } while (0)
00295 #define WOLFSENTRY_ERROR_UNLOCK_AND_RETURN_RECODED(x) do { WOLFSENTRY_UNLOCK_FOR_RETURN();
WOLFSENTRY_ERROR_RETURN_RECODED(x); } while (0)
00297 #define WOLFSENTRY_ERROR_UNLOCK_AND_RETURN_EX(ctx, name) do { WOLFSENTRY_UNLOCK_FOR_RETURN_EX(ctx);
WOLFSENTRY_ERROR_RETURN(name); } while (0)
00299 #define WOLFSENTRY_ERROR_UNLOCK_AND_RETURN_RECODED_EX(ctx, x) do {
WOLFSENTRY_UNLOCK_FOR_RETURN_EX(ctx); WOLFSENTRY_ERROR_RETURN_RECODED(x); } while (0)
00301 #define WOLFSENTRY_ERROR_UNLOCK_AND_RERETURN(x) do { WOLFSENTRY_UNLOCK_FOR_RETURN();
WOLFSENTRY_ERROR_RERETURN(x); } while (0)
00303 #define WOLFSENTRY_ERROR_RERETURN_AND_UNLOCK(y) do { wolfentry_errcode_t _yret = (y);
WOLFSENTRY_UNLOCK_FOR_RETURN(); WOLFSENTRY_ERROR_RERETURN(_yret); } while (0)
00306 #define WOLFSENTRY_SUCCESS_UNLOCK_AND_RETURN(name) do { WOLFSENTRY_UNLOCK_FOR_RETURN();
WOLFSENTRY_SUCCESS_RETURN(name); } while (0)
00308 #define WOLFSENTRY_SUCCESS_UNLOCK_AND_RETURN_RECODED(x) do { WOLFSENTRY_UNLOCK_FOR_RETURN();
WOLFSENTRY_SUCCESS_RETURN_RECODED(x); } while (0)
00310 #define WOLFSENTRY_SUCCESS_UNLOCK_AND_RERETURN(x) do { WOLFSENTRY_UNLOCK_FOR_RETURN();
WOLFSENTRY_SUCCESS_RERETURN(x); } while (0)
00312 #define WOLFSENTRY_SUCCESS_RERETURN_AND_UNLOCK(y) do { wolfentry_errcode_t _yret = (y);
WOLFSENTRY_UNLOCK_FOR_RETURN(); WOLFSENTRY_SUCCESS_RERETURN(_yret); } while (0)
00315 #define WOLFSENTRY_UNLOCK_AND_RETURN_VALUE(x) do { WOLFSENTRY_UNLOCK_FOR_RETURN();
WOLFSENTRY_RETURN_VALUE(x); } while (0)
00317 #define WOLFSENTRY_UNLOCK_AND_RETURN_VOID do { WOLFSENTRY_UNLOCK_FOR_RETURN(); WOLFSENTRY_RETURN_VOID;
} while (0)
00320 #define WOLFSENTRY_RETURN_OK WOLFSENTRY_SUCCESS_RETURN(OK)
00322 #define WOLFSENTRY_UNLOCK_AND_RETURN_OK do { WOLFSENTRY_UNLOCK_FOR_RETURN();
WOLFSENTRY_SUCCESS_RETURN(OK); } while (0)
00324 #define WOLFSENTRY_RERETURN_IF_ERROR(y) do { wolfentry_errcode_t _yret = (y); if (_yret < 0)
WOLFSENTRY_ERROR_RERETURN(_yret); } while (0)
00326 #define WOLFSENTRY_UNLOCK_AND_RERETURN_IF_ERROR(y) do { wolfentry_errcode_t _yret = (y); if (_yret <
0) { WOLFSENTRY_UNLOCK_FOR_RETURN(); WOLFSENTRY_ERROR_RERETURN(_yret); } } while (0)
00329 #ifndef WOLFSENTRY_ERROR_STRINGS
00330 WOLFSENTRY_API const char *wolfentry_errcode_source_string(wolfentry_errcode_t e);
00332 WOLFSENTRY_API const char *wolfentry_errcode_error_string(wolfentry_errcode_t e);
00334 WOLFSENTRY_API const char *wolfentry_errcode_error_name(wolfentry_errcode_t e);
00336 #endif
00337
00338 #if !defined(WOLFSENTRY_NO_STDIO_STREAMS) && !defined(WOLFSENTRY_NO_DIAG_MSGS)
00339
00340 #include <errno.h>
00341
00342 #ifdef __STRICT_ANSI__
00343 #define WOLFSENTRY_WARN(fmt,...) WOLFSENTRY_PRINTF_ERR("%s@L%d " fmt, __FILE__, __LINE__, __VA_ARGS__)
00344 #else
00345 #define WOLFSENTRY_WARN(fmt,...) WOLFSENTRY_PRINTF_ERR("%s@L%d " fmt, __FILE__, __LINE__, ##
__VA_ARGS__)
00347 #endif
00348
00349 #define WOLFSENTRY_WARN_ON_FAILURE(...) do { wolfentry_errcode_t _ret = (__VA_ARGS__); if (_ret < 0)
{ WOLFSENTRY_WARN(__VA_ARGS__ ": " WOLFSENTRY_ERROR_FMT "\n", WOLFSENTRY_ERROR_FMT_ARGS(_ret)); }}
while(0)
00351 #define WOLFSENTRY_WARN_ON_FAILURE_LIBC(...) do { if ((__VA_ARGS__) < 0) {
WOLFSENTRY_WARN(__VA_ARGS__ ": %s\n", strerror(errno)); }} while(0)
00354 #else
00355
00356 #define WOLFSENTRY_WARN(fmt,...) DO_NOTHING
00357 #define WOLFSENTRY_WARN_ON_FAILURE(...) do { if ((__VA_ARGS__) < 0) {} } while (0)
00358 #define WOLFSENTRY_WARN_ON_FAILURE_LIBC(...) do { if ((__VA_ARGS__) < 0) {} } while (0)
00359
00360 #endif /* !WOLFSENTRY_NO_STDIO_STREAMS && !WOLFSENTRY_NO_DIAG_MSGS */
00361
00362 #ifdef WOLFSENTRY_CPPCHECK
00363     #undef WOLFSENTRY_ERROR_ENCODE
00364     #define WOLFSENTRY_ERROR_ENCODE(x) 0
00365     #undef WOLFSENTRY_SUCCESS_ENCODE
00366     #define WOLFSENTRY_SUCCESS_ENCODE(x) 0
00367 #endif
00368
00369 enum wolfentry_source_id {

```

```

00370     WOLFSENTRY_SOURCE_ID_UNSET      = 0,
00371     WOLFSENTRY_SOURCE_ID_ACTIONS_C = 1,
00372     WOLFSENTRY_SOURCE_ID_EVENTS_C  = 2,
00373     WOLFSENTRY_SOURCE_ID_WOLFSENTRY_INTERNAL_C = 3,
00374     WOLFSENTRY_SOURCE_ID_ROUTES_C  = 4,
00375     WOLFSENTRY_SOURCE_ID_WOLFSENTRY_UTIL_C = 5,
00376     WOLFSENTRY_SOURCE_ID_KV_C      = 6,
00377     WOLFSENTRY_SOURCE_ID_ADDR_FAMILIES_C = 7,
00378     WOLFSENTRY_SOURCE_ID_JSON_LOAD_CONFIG_C = 8,
00379     WOLFSENTRY_SOURCE_ID_JSON_JSON_UTIL_C = 9,
00380     WOLFSENTRY_SOURCE_ID_LWIP_PACKET_FILTER_GLUE_C = 10,
00381     WOLFSENTRY_SOURCE_ID_ACTION_BUILTINS_C = 11,
00382
00383     WOLFSENTRY_SOURCE_ID_USER_BASE = 112
00384 };
00385
00386 #ifndef WOLFSENTRY_ERROR_STRINGS
00387 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_user_source_string_set(enum wolfsentry_source_id
    wolfsentry_source_id, const char *source_string);
00388 #define WOLFSENTRY_REGISTER_SOURCE() wolfsentry_user_source_string_set(WOLFSENTRY_SOURCE_ID, __FILE__)
00389 #endif
00390
00391 enum wolfsentry_error_id {
00392     WOLFSENTRY_ERROR_ID_OK              = 0,
00393     WOLFSENTRY_ERROR_ID_NOT_OK          = -1,
00394     WOLFSENTRY_ERROR_ID_INTERNAL_CHECK_FATAL = -2,
00395     WOLFSENTRY_ERROR_ID_SYS_OP_FATAL    = -3,
00396     WOLFSENTRY_ERROR_ID_SYS_OP_FAILED   = -4,
00397     WOLFSENTRY_ERROR_ID_SYS_RESOURCE_FAILED = -5,
00398     WOLFSENTRY_ERROR_ID_INCOMPATIBLE_STATE = -6,
00399     WOLFSENTRY_ERROR_ID_TIMED_OUT       = -7,
00400     WOLFSENTRY_ERROR_ID_INVALID_ARG     = -8,
00401     WOLFSENTRY_ERROR_ID_BUSY            = -9,
00402     WOLFSENTRY_ERROR_ID_INTERRUPTED     = -10,
00403     WOLFSENTRY_ERROR_ID_NUMERIC_ARG_TOO_BIG = -11,
00404     WOLFSENTRY_ERROR_ID_NUMERIC_ARG_TOO_SMALL = -12,
00405     WOLFSENTRY_ERROR_ID_STRING_ARG_TOO_LONG = -13,
00406     WOLFSENTRY_ERROR_ID_BUFFER_TOO_SMALL = -14,
00407     WOLFSENTRY_ERROR_ID_IMPLEMENTATION_MISSING = -15,
00408     WOLFSENTRY_ERROR_ID_ITEM_NOT_FOUND   = -16,
00409     WOLFSENTRY_ERROR_ID_ITEM_ALREADY_PRESENT = -17,
00410     WOLFSENTRY_ERROR_ID_ALREADY_STOPPED  = -18,
00411     WOLFSENTRY_ERROR_ID_WRONG_OBJECT     = -19,
00412     WOLFSENTRY_ERROR_ID_DATA_MISSING     = -20,
00413     WOLFSENTRY_ERROR_ID_NOT_PERMITTED    = -21,
00414     WOLFSENTRY_ERROR_ID_ALREADY         = -22,
00415     WOLFSENTRY_ERROR_ID_CONFIG_INVALID_KEY = -23,
00416     WOLFSENTRY_ERROR_ID_CONFIG_INVALID_VALUE = -24,
00417     WOLFSENTRY_ERROR_ID_CONFIG_OUT_OF_SEQUENCE = -25,
00418     WOLFSENTRY_ERROR_ID_CONFIG_UNEXPECTED = -26,
00419     WOLFSENTRY_ERROR_ID_CONFIG_MISPLACED_KEY = -27,
00420     WOLFSENTRY_ERROR_ID_CONFIG_PARSER    = -28,
00421     WOLFSENTRY_ERROR_ID_CONFIG_MISSING_HANDLER = -29,
00422     WOLFSENTRY_ERROR_ID_CONFIG_JSON_VALUE_SIZE = -30,
00423     WOLFSENTRY_ERROR_ID_OP_NOT_SUPP_FOR_PROTO = -31,
00424     WOLFSENTRY_ERROR_ID_WRONG_TYPE       = -32,
00425     WOLFSENTRY_ERROR_ID_BAD_VALUE        = -33,
00426     WOLFSENTRY_ERROR_ID_DEADLOCK_AVERTED = -34,
00427     WOLFSENTRY_ERROR_ID_OVERFLOW_AVERTED = -35,
00428     WOLFSENTRY_ERROR_ID_LACKING_MUTEX    = -36,
00429     WOLFSENTRY_ERROR_ID_LACKING_READ_LOCK = -37,
00430     WOLFSENTRY_ERROR_ID_LIB_MISMATCH     = -38,
00431     WOLFSENTRY_ERROR_ID_LIBCONFIG_MISMATCH = -39,
00432     WOLFSENTRY_ERROR_ID_IO_FAILED        = -40,
00433     WOLFSENTRY_ERROR_ID_WRONG_ATTRIBUTES = -41,
00434
00435     WOLFSENTRY_ERROR_ID_USER_BASE        = -128,
00436
00437     WOLFSENTRY_SUCCESS_ID_OK              = 0,
00438     WOLFSENTRY_SUCCESS_ID_LOCK_OK_AND_GOT_RESV = 1,
00439     WOLFSENTRY_SUCCESS_ID_HAVE_MUTEX      = 2,
00440     WOLFSENTRY_SUCCESS_ID_HAVE_READ_LOCK  = 3,
00441     WOLFSENTRY_SUCCESS_ID_USED_FALLBACK   = 4,
00442     WOLFSENTRY_SUCCESS_ID_YES             = 5,
00443     WOLFSENTRY_SUCCESS_ID_NO              = 6,
00444     WOLFSENTRY_SUCCESS_ID_ALREADY_OK      = 7,
00445     WOLFSENTRY_SUCCESS_ID_DEFERRED        = 8,
00446     WOLFSENTRY_SUCCESS_ID_USER_BASE      = 128
00447 };
00448
00449 #ifndef WOLFSENTRY_ERROR_STRINGS
00450 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_user_error_string_set(enum wolfsentry_error_id
    wolfsentry_error_id, const char *message_string);
00451 #define WOLFSENTRY_REGISTER_ERROR(name, msg) wolfsentry_user_error_string_set(WOLFSENTRY_ERROR_ID_ ##
    name, msg)
00452 #endif
00453

```

```
00460 #endif /* WOLFSENTRY_ERRCODES_H */
```

## 10.10 wolfentry/wolfentry\_json.h File Reference

Types and prototypes for loading/reloading configuration using JSON.

```
#include "wolfentry.h"
#include "centijson_sax.h"
```

### Macros

- `#define WOLFSENTRY`
- `#define WOLFSENTRY_MAX_JSON_NESTING 16`

*Can be overridden.*

### Typedefs

- `typedef uint32_t wolfentry_config_load_flags_t`  
*Type for holding flag bits from [wolfentry\\_config\\_load\\_flags](#).*

### Enumerations

- `enum wolfentry_config_load_flags {`  
`WOLFSENTRY_CONFIG_LOAD_FLAG_NONE ,`  
`WOLFSENTRY_CONFIG_LOAD_FLAG_NO_FLUSH ,`  
`WOLFSENTRY_CONFIG_LOAD_FLAG_DRY_RUN ,`  
`WOLFSENTRY_CONFIG_LOAD_FLAG_LOAD_THEN_COMMIT ,`  
`WOLFSENTRY_CONFIG_LOAD_FLAG_NO_ROUTES_OR_EVENTS ,`  
`WOLFSENTRY_CONFIG_LOAD_FLAG_JSON_DOM_DUPKEY_ABORT ,`  
`WOLFSENTRY_CONFIG_LOAD_FLAG_JSON_DOM_DUPKEY_USEFIRST ,`  
`WOLFSENTRY_CONFIG_LOAD_FLAG_JSON_DOM_DUPKEY_USELAST ,`  
`WOLFSENTRY_CONFIG_LOAD_FLAG_JSON_DOM_MAINTAINDICTIONARY ,`  
`WOLFSENTRY_CONFIG_LOAD_FLAG_FLUSH_ONLY_ROUTES ,`  
`WOLFSENTRY_CONFIG_LOAD_FLAG_FINI }`

*Flags to be OR'd together to communicate options to [wolfentry\\_config\\_json\\_init\(\)](#)*

### Functions

- `WOLFSENTRY_API wolfentry_errcode_t wolfentry_centijson_errcode_translate (wolfentry_errcode_t centijson_errcode)`  
*Convert CentiJSON numeric error code to closest-corresponding wolfSentry error code.*
- `WOLFSENTRY_API wolfentry_errcode_t wolfentry_config_json_init (WOLFSENTRY_CONTEXT_ARGS_IN, wolfentry_config_load_flags_t load_flags, struct wolfentry_json_process_state **jps)`  
*Allocate and initialize a struct wolfentry\_json\_process\_state with the designated load\_flags, to subsequently pass to [wolfentry\\_config\\_json\\_feed\(\)](#).*
- `WOLFSENTRY_API wolfentry_errcode_t wolfentry_config_json_init_ex (WOLFSENTRY_CONTEXT_ARGS_IN, wolfentry_config_load_flags_t load_flags, const JSON_CONFIG *json_config, struct wolfentry_json_process_state **jps)`

Variant of `wolfentry_config_json_init()` with an additional `JSON_CONFIG` argument, `json_↵  
config`, for tailoring of JSON parsing dynamics.

- WOLFENTRY\_API `wolfentry_errcode_t wolfentry_config_json_feed` (struct `wolfentry_json_process_↵  
_state *jps`, const unsigned char \*`json_in`, size\_t `json_in_len`, char \*`err_buf`, size\_t `err_buf_size`)

Pass a segment of JSON configuration into the parsing engine. Segments can be as short or as long as desired, to facilitate incremental read-in.

- WOLFENTRY\_API `wolfentry_errcode_t wolfentry_config_centijson_errcode` (struct `wolfentry_json_↵  
_process_state *jps`, int \*`json_errcode`, const char \*\*`json_errmsg`)

Copy the current error code and/or human-readable error message from a struct `wolfentry_json_↵  
process_state` allocated by `wolfentry_config_json_init()`.

- WOLFENTRY\_API `wolfentry_errcode_t wolfentry_config_json_fini` (struct `wolfentry_json_process_↵  
_state **jps`, char \*`err_buf`, size\_t `err_buf_size`)

To be called when done iterating `wolfentry_config_json_feed()`, completing the configuration load.

- WOLFENTRY\_API `wolfentry_errcode_t wolfentry_config_json_oneshot` (`WOLFENTRY_CONTEXT_ARGS_IN`, const unsigned char \*`json_in`, size\_t `json_in_len`, `wolfentry_config_load_flags_t` `load_flags`, char \*`err_buf`, size\_t `err_buf_size`)

Load a complete JSON configuration from an in-memory buffer.

- WOLFENTRY\_API `wolfentry_errcode_t wolfentry_config_json_oneshot_ex` (`WOLFENTRY_CONTEXT_ARGS_IN`, const unsigned char \*`json_in`, size\_t `json_in_len`, `wolfentry_config_load_flags_t` `load_flags`, const `JSON_CONFIG` \*`json_config`, char \*`err_buf`, size\_t `err_buf_size`)

Variant of `wolfentry_config_json_oneshot()` with an additional `JSON_CONFIG` argument, `json_↵  
config`, for tailoring of JSON parsing dynamics.

### 10.10.1 Detailed Description

Types and prototypes for loading/reloading configuration using JSON.

Include this file in your application for JSON configuration capabilities.

## 10.11 wolfentry\_json.h

[Go to the documentation of this file.](#)

```
00001 /*
00002  * wolfentry_json.h
00003  *
00004  * Copyright (C) 2021-2023 wolfSSL Inc.
00005  *
00006  * This file is part of wolfSentry.
00007  *
00008  * wolfSentry is free software; you can redistribute it and/or modify
00009  * it under the terms of the GNU General Public License as published by
00010  * the Free Software Foundation; either version 2 of the License, or
00011  * (at your option) any later version.
00012  *
00013  * wolfSentry is distributed in the hope that it will be useful,
00014  * but WITHOUT ANY WARRANTY; without even the implied warranty of
00015  * MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
00016  * GNU General Public License for more details.
00017  *
00018  * You should have received a copy of the GNU General Public License
00019  * along with this program; if not, write to the Free Software
00020  * Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1335, USA
00021  */
00022
00029 #ifndef WOLFENTRY_JSON_H
00030 #define WOLFENTRY_JSON_H
00031
00032 #include "wolfentry.h"
00033
00034 #ifndef WOLFENTRY
00035 #define WOLFENTRY
00036 #endif
00037 #include "centijson_sax.h"
```



```

00038
00043 WOLFSENTRY_API wolfentry_errcode_t wolfentry_centijson_errcode_translate(wolfentry_errcode_t
centijson_errcode);
00046 #ifndef WOLFSENTRY_MAX_JSON_NESTING
00047 #define WOLFSENTRY_MAX_JSON_NESTING 16
00049 #endif
00050
00051 typedef uint32_t wolfentry_config_load_flags_t;
00055 enum wolfentry_config_load_flags {
00056     WOLFSENTRY_CONFIG_LOAD_FLAG_NONE = 0U,
00058     WOLFSENTRY_CONFIG_LOAD_FLAG_NO_FLUSH = 1U < 0U,
00060     WOLFSENTRY_CONFIG_LOAD_FLAG_DRY_RUN = 1U < 1U,
00062     WOLFSENTRY_CONFIG_LOAD_FLAG_LOAD_THEN_COMMIT = 1U < 2U,
00064     WOLFSENTRY_CONFIG_LOAD_FLAG_NO_ROUTES_OR_EVENTS = 1U < 3U,
00066     WOLFSENTRY_CONFIG_LOAD_FLAG_JSON_DOM_DUPKEY_ABORT = 1U < 4U,
00068     WOLFSENTRY_CONFIG_LOAD_FLAG_JSON_DOM_DUPKEY_USEFIRST = 1U < 5U,
00070     WOLFSENTRY_CONFIG_LOAD_FLAG_JSON_DOM_DUPKEY_USELAST = 1U < 6U,
00072     WOLFSENTRY_CONFIG_LOAD_FLAG_JSON_DOM_MAINTAININDICTORDER = 1U < 7U,
00074     WOLFSENTRY_CONFIG_LOAD_FLAG_FLUSH_ONLY_ROUTES = 1U < 8U,
00076     WOLFSENTRY_CONFIG_LOAD_FLAG_FINI = 1U < 30U
00078 };
00079
00080 struct wolfentry_json_process_state;
00081
00082 WOLFSENTRY_API wolfentry_errcode_t wolfentry_config_json_init(
00083     WOLFSENTRY_CONTEXT_ARGS_IN,
00084     wolfentry_config_load_flags_t load_flags,
00085     struct wolfentry_json_process_state **jps);
00088 WOLFSENTRY_API wolfentry_errcode_t wolfentry_config_json_init_ex(
00089     WOLFSENTRY_CONTEXT_ARGS_IN,
00090     wolfentry_config_load_flags_t load_flags,
00091     const JSON_CONFIG *json_config,
00092     struct wolfentry_json_process_state **jps);
00095 WOLFSENTRY_API wolfentry_errcode_t wolfentry_config_json_feed(
00096     struct wolfentry_json_process_state *jps,
00097     const unsigned char *json_in,
00098     size_t json_in_len,
00099     char *err_buf,
00100     size_t err_buf_size);
00103 WOLFSENTRY_API wolfentry_errcode_t wolfentry_config_centijson_errcode(struct
wolfentry_json_process_state *jps, int *json_errcode, const char **json_errmsg);
00106 WOLFSENTRY_API wolfentry_errcode_t wolfentry_config_json_fini(
00107     struct wolfentry_json_process_state **jps,
00108     char *err_buf,
00109     size_t err_buf_size);
00112 WOLFSENTRY_API wolfentry_errcode_t wolfentry_config_json_oneshot(
00113     WOLFSENTRY_CONTEXT_ARGS_IN,
00114     const unsigned char *json_in,
00115     size_t json_in_len,
00116     wolfentry_config_load_flags_t load_flags,
00117     char *err_buf,
00118     size_t err_buf_size);
00121 WOLFSENTRY_API wolfentry_errcode_t wolfentry_config_json_oneshot_ex(
00122     WOLFSENTRY_CONTEXT_ARGS_IN,
00123     const unsigned char *json_in,
00124     size_t json_in_len,
00125     wolfentry_config_load_flags_t load_flags,
00126     const JSON_CONFIG *json_config,
00127     char *err_buf,
00128     size_t err_buf_size);
00133 #endif /* WOLFSENTRY_JSON_H */

```

## 10.12 wolfentry/wolfentry\_lwip.h File Reference

Prototypes for lwIP callback installation functions, for use in lwIP applications.

```

#include "lwip/init.h"
#include "lwip/filter.h"

```

### Functions

- WOLFSENTRY\_API [wolfentry\\_errcode\\_t](#) [wolfentry\\_install\\_lwip\\_filter\\_ethernet\\_callback](#) ([WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#), [packet\\_filter\\_event\\_mask\\_t](#) ethernet\_mask)



*Install wolfSentry callbacks into lwIP for ethernet (layer 2) filtering.*

- WOLFSENTRY\_API [wolfSentry\\_errcode\\_t](#) **wolfSentry\_install\_lwip\_filter\_ip\_callbacks** ([WOLFSENTRY\\_CONTEXT\\_ARGS](#), packet\_filter\_event\_mask\_t ip\_mask)

*Install wolfSentry callbacks into lwIP for IPv4/IPv6 (layer 3) filtering.*

- WOLFSENTRY\_API [wolfSentry\\_errcode\\_t](#) **wolfSentry\_install\_lwip\_filter\_icmp\_callbacks** ([WOLFSENTRY\\_CONTEXT\\_ARGS](#), packet\_filter\_event\_mask\_t icmp\_mask)

*Install wolfSentry callbacks into lwIP for ICMP filtering.*

- WOLFSENTRY\_API [wolfSentry\\_errcode\\_t](#) **wolfSentry\_install\_lwip\_filter\_tcp\_callback** ([WOLFSENTRY\\_CONTEXT\\_ARGS](#), packet\_filter\_event\_mask\_t tcp\_mask)

*Install wolfSentry callbacks into lwIP for TCP (layer 4) filtering.*

- WOLFSENTRY\_API [wolfSentry\\_errcode\\_t](#) **wolfSentry\_install\_lwip\_filter\_udp\_callback** ([WOLFSENTRY\\_CONTEXT\\_ARGS](#), packet\_filter\_event\_mask\_t udp\_mask)

*Install wolfSentry callbacks into lwIP for UDP (layer 4) filtering.*

- WOLFSENTRY\_API [wolfSentry\\_errcode\\_t](#) **wolfSentry\_install\_lwip\_filter\_callbacks** ([WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#), packet\_filter\_event\_mask\_t ethernet\_mask, packet\_filter\_event\_mask\_t ip\_mask, packet\_filter\_event\_mask\_t icmp\_mask, packet\_filter\_event\_mask\_t tcp\_mask, packet\_filter\_event\_mask\_t udp\_mask)

*Install wolfSentry callbacks for all layers/protocols enabled by the supplied masks.*

- [WOLFSENTRY\\_API\\_VOID](#) **wolfSentry\_cleanup\_lwip\_filter\_callbacks** ([WOLFSENTRY\\_CONTEXT\\_ARGS\\_IN](#), void \*arg)

*Disables any wolfSentry callbacks previously installed in lwIP.*

### 10.12.1 Detailed Description

Prototypes for lwIP callback installation functions, for use in lwIP applications.

packet\_filter\_event\_mask\_t is passed to lwIP via the callback installation routines, to designate which events are of interest. It is set to a bitwise-OR of values from packet\_filter\_event\_t, defined in src/include/lwip/filter.h in the lwIP source tree after applying lwip/LWIP\_PACKET\_FILTER\_API.patch. The values are:

FILT\_BINDING – Call into wolfSentry (filter) on binding events  
 FILT DISSOCIATE – Call into wolfSentry on socket dissociation events  
 FILT\_LISTENING – Call into wolfSentry at initiation of socket listening  
 FILT\_STOP\_LISTENING – Call into wolfSentry when listening is shut down  
 FILT\_CONNECTING – Call into wolfSentry (filter) when connecting out  
 FILT\_ACCEPTING – Call into wolfSentry (filter) when accepting an inbound connection  
 FILT\_CLOSED – Call into wolfSentry when socket is closed  
 FILT\_REMOTE\_RESET – Call into wolfSentry when a connection was reset by the remote peer  
 FILT\_RECEIVING – Call into wolfSentry (filter) for each regular inbound packet of data  
 FILT\_SENDING – Call into wolfSentry (filter) for each regular outbound packet of data  
 FILT\_ADDR\_UNREACHABLE – Call into wolfSentry when inbound traffic attempts to reach an unknown address  
 FILT\_PORT\_UNREACHABLE – Call into wolfSentry when inbound traffic attempts to reach an unlistened/unbound port  
 FILT\_INBOUND\_ERR – Call into wolfSentry when inbound traffic results in detection of an error by lwIP  
 FILT\_OUTBOUND\_ERR – Call into wolfSentry when outbound traffic results in detection of an error by lwIP

## 10.13 wolfSentry\_lwip.h

[Go to the documentation of this file.](#)

```
00001 /*
00002  * wolfSentry/wolfSentry_lwip.h
00003  *
```

```

00004  * Copyright (C) 2021-2023 wolfSSL Inc.
00005  *
00006  * This file is part of wolfSentry.
00007  *
00008  * wolfSentry is free software; you can redistribute it and/or modify
00009  * it under the terms of the GNU General Public License as published by
00010  * the Free Software Foundation; either version 2 of the License, or
00011  * (at your option) any later version.
00012  *
00013  * wolfSentry is distributed in the hope that it will be useful,
00014  * but WITHOUT ANY WARRANTY; without even the implied warranty of
00015  * MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
00016  * GNU General Public License for more details.
00017  *
00018  * You should have received a copy of the GNU General Public License
00019  * along with this program; if not, write to the Free Software
00020  * Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1335, USA
00021  */
00022
00044 #ifndef WOLFSENTRY_LWIP_H
00045 #define WOLFSENTRY_LWIP_H
00046
00051 #include "lwip/init.h"
00052
00053 #if LWIP_PACKET_FILTER_API
00054
00055 #include "lwip/filter.h"
00056
00057 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_install_lwip_filter_ethernet_callback(
00058     WOLFSENTRY_CONTEXT_ARGS_IN,
00059     packet_filter_event_mask_t ethernet_mask);
00062 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_install_lwip_filter_ip_callbacks(
00063     WOLFSENTRY_CONTEXT_ARGS_IN,
00064     packet_filter_event_mask_t ip_mask);
00067 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_install_lwip_filter_icmp_callbacks(
00068     WOLFSENTRY_CONTEXT_ARGS_IN,
00069     packet_filter_event_mask_t icmp_mask);
00072 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_install_lwip_filter_tcp_callback(
00073     WOLFSENTRY_CONTEXT_ARGS_IN,
00074     packet_filter_event_mask_t tcp_mask);
00077 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_install_lwip_filter_udp_callback(
00078     WOLFSENTRY_CONTEXT_ARGS_IN,
00079     packet_filter_event_mask_t udp_mask);
00082 WOLFSENTRY_API wolfsentry_errcode_t wolfsentry_install_lwip_filter_callbacks(
00083     WOLFSENTRY_CONTEXT_ARGS_IN,
00084     packet_filter_event_mask_t ethernet_mask,
00085     packet_filter_event_mask_t ip_mask,
00086     packet_filter_event_mask_t icmp_mask,
00087     packet_filter_event_mask_t tcp_mask,
00088     packet_filter_event_mask_t udp_mask);
00091 WOLFSENTRY_API_VOID wolfsentry_cleanup_lwip_filter_callbacks(
00092     WOLFSENTRY_CONTEXT_ARGS_IN,
00093     void *arg);
00096 #endif /* LWIP_PACKET_FILTER_API */
00097
00100 #endif /* WOLFSENTRY_LWIP_H */

```

## 10.14 wolfsentry/wolfsentry\_settings.h File Reference

Target- and config-specific settings and abstractions for wolfSentry.

```

#include <wolfsentry/wolfsentry_options.h>
#include <inttypes.h>
#include <stdint.h>
#include <stddef.h>
#include <assert.h>
#include <stdio.h>
#include <string.h>
#include <strings.h>
#include <time.h>

```

## Data Structures

- struct [wolfSentry\\_thread\\_context\\_public](#)  
*Right-sized, right-aligned opaque container for thread state.*
- struct [wolfSentry\\_build\\_settings](#)  
*struct for passing the build version and configuration*

## Macros

- #define **WOLFSENTRY\_USER\_SETTINGS\_FILE** "the\_path"  
*Define to the path of a user settings file to be included, containing extra and override definitions and directives. Can be an absolute or a relative path, subject to a `-I` path supplied to `make` using `EXTRA_CFLAGS`. Include quotes or `<>` around the path.*
- #define **WOLFSENTRY\_NO\_ALLOCA**  
*Build flag to use only implementations that avoid `alloca()`.*
- #define **WOLFSENTRY\_C89**  
*Build flag to use only constructs that are pedantically legal in C89.*
- #define **\_\_attribute\_maybe\_unused\_\_**  
*Attribute abstraction to mark a function or variable (typically a `static`) as possibly unused.*
- #define **DO\_NOTHING**  
*Statement-type abstracted construct that executes no code.*
- #define **WOLFSENTRY\_NO\_INTTYPES\_H**  
*Define to inhibit inclusion of `inttypes.h` (alternative typedefs or include must be supplied with [WOLFSENTRY\\_USER\\_SETTINGS\\_FILE](#)).*
- #define **WOLFSENTRY\_NO\_STDINT\_H**  
*Define to inhibit inclusion of `stdint.h` (alternative typedefs or include must be supplied with [WOLFSENTRY\\_USER\\_SETTINGS\\_FILE](#)).*
- #define **WOLFSENTRY\_PRINTF\_ERR(...)**  
*printf-like macro, expecting a format as first arg, used for rendering warning and error messages. Can be overridden in [WOLFSENTRY\\_USER\\_SETTINGS\\_FILE](#).*
- #define **WOLFSENTRY\_SINGLETHREADED**  
*Define to disable all thread handling and safety in wolfSentry.*
- #define **WOLFSENTRY\_USE\_NONPOSIX\_SEMAPHORES**  
*Define if POSIX semaphore API is not available. If no non-POSIX builtin implementation is present in `wolfSentry_util.c`, then [WOLFSENTRY\\_NO\\_SEM\\_BUILTIN](#) must be set, and the [wolfSentry\\_host\\_platform\\_interface](#) supplied to wolfSentry APIs must include a full semaphore implementation (shim set) in its [wolfSentry\\_semcbs](#) slot.*
- #define **WOLFSENTRY\_USE\_NONPOSIX\_THREADS**  
*Define if POSIX thread API is not available. `WOLFSENTRY_THREAD_INCLUDE`, `WOLFSENTRY_THREAD_ID_T`, and `WOLFSENTRY_THREAD_GET_ID_HANDLER` will need to be supplied in [WOLFSENTRY\\_USER\\_SETTINGS\\_FILE](#).*
- #define **WOLFSENTRY\_NO\_GNU\_ATOMICS**  
*Define if `gnu`-style atomic intrinsics are not available. `WOLFSENTRY_ATOMIC_*()` macro definitions for intrinsics will need to be supplied in [WOLFSENTRY\\_USER\\_SETTINGS\\_FILE](#) (see [wolfSentry\\_util.h](#)).*
- #define **WOLFSENTRY\_NO\_CLOCK\_BUILTIN**  
*If defined, omit built-in time primitives; the [wolfSentry\\_host\\_platform\\_interface](#) supplied to wolfSentry APIs must include implementations of all functions in [wolfSentry\\_timecbs](#).*
- #define **WOLFSENTRY\_NO\_SEM\_BUILTIN**  
*If defined, omit built-in semaphore primitives; the [wolfSentry\\_host\\_platform\\_interface](#) supplied to wolfSentry APIs must include implementations of all functions in [wolfSentry\\_semcbs](#).*
- #define **WOLFSENTRY\_NO\_MALLOC\_BUILTIN**  
*If defined, omit built-in heap allocator primitives; the [wolfSentry\\_host\\_platform\\_interface](#) supplied to wolfSentry APIs must include implementations of all functions in [wolfSentry\\_allocator](#).*
- #define **WOLFSENTRY\_NO\_ERROR\_STRINGS**

If defined, omit APIs for rendering error codes and source code files in human readable form. They will be rendered numerically.

- **#define WOLFSENTRY\_NO\_PROTOCOL\_NAMES**

If defined, omit APIs for rendering error codes and source code files in human readable form. They will be rendered numerically.

- **#define WOLFSENTRY\_NO\_ADDR\_BITMASK\_MATCHING**

If defined, omit support for bitmask matching of addresses, and support only prefix matching.

- **#define WOLFSENTRY\_NO\_IPV6**

If defined, omit support for IPv6.

- **#define WOLFSENTRY\_MAX\_BITMASK\_MATCHED\_AFS**

The maximum number of distinct address families that can use bitmask matching in routes. Default value is 4.

- **#define WOLFSENTRY\_NO\_GETPROTOBY**

Define this to gate out calls to `getprotobyname_r()` and `getservbyname_r()`, necessitating numeric identification of protocols (e.g. 6 for TCP) and services (e.g. 25 for SMTP) in configuration JSON documents.

- **#define WOLFSENTRY\_NO\_POSIX\_MEMALIGN**

Define if `posix_memalign()` is not available.

- **#define WOLFSENTRY\_FLEXIBLE\_ARRAY\_SIZE**

Value appropriate as a size for an array that will be allocated to a variable size. Built-in value usually works.

- **#define SIZET\_FMT**

printf-style format string appropriate for pairing with `size_t`

- **#define WOLFSENTRY\_ENT\_ID\_FMT**

printf-style format string appropriate for pairing with `wolfentry_ent_id_t`

- **#define WOLFSENTRY\_ENT\_ID\_NONE**

always-invalid object ID

- **#define WOLFSENTRY\_HITCOUNT\_FMT**

printf-style format string appropriate for pairing with `wolfentry_hitcount_t`

- **#define \_\_wolfentry\_wur**

abstracted attribute designating that the return value must be checked to avoid a compiler warning

- **#define wolfentry\_static\_assert(c)**

abstracted static assert – `c` must be true, else `c` is printed

- **#define wolfentry\_static\_assert2(c, m)**

abstracted static assert – `c` must be true, else `m` is printed

- **#define WOLFSENTRY\_DEADLINE\_NEVER (-1)**

Value returned in `deadline->tv_sec` and `deadline->tv_nsec` by `wolfentry_get_thread_deadline()` when thread has no deadline set. Not allowed as explicit values passed to `wolfentry_set_deadline_abs()` – use `wolfentry_clear_deadline()` to clear any deadline. Can be overridden with user settings.

- **#define WOLFSENTRY\_DEADLINE\_NOW (-2)**

Value returned in `deadline->tv_sec` and `deadline->tv_nsec` by `wolfentry_get_thread_deadline()` when thread is in non-blocking mode. Not allowed as explicit values passed to `wolfentry_set_deadline_abs()` – use `wolfentry_set_deadline_rel_usecs(WOLFSENTRY_CONTEXT_ARGS_OUT, 0)` to put thread in non-blocking mode. Can be overridden with user settings.

- **#define WOLFSENTRY\_SEMAPHORE\_INCLUDE "the\_path"**

Define to the path of a header file declaring a semaphore API. Can be an absolute or a relative path, subject to a `-I` path supplied to `make` using `EXTRA_CFLAGS`. Include quotes or `<>` around the path.

- **#define WOLFSENTRY\_THREAD\_INCLUDE "the\_path"**

Define to the path of a header file declaring a threading API. Can be an absolute or a relative path, subject to a `-I` path supplied to `make` using `EXTRA_CFLAGS`. Include quotes or `<>` around the path.

- **#define WOLFSENTRY\_THREAD\_ID\_T thread\_id\_type**

Define to the appropriate type analogous to POSIX `pthread_t`.

- **#define WOLFSENTRY\_THREAD\_GET\_ID\_HANDLER pthread\_self\_ish\_function**

Define to the name of a void function analogous to POSIX `pthread_self`, returning a value of type `WOLFSENTRY_THREAD_ID_T`.

- **#define WOLFSENTRY\_THREAD\_NO\_ID 0**

- **#define WOLFSENTRY\_THREAD\_CONTEXT\_PUBLIC\_INITIALIZER** {0}
- **#define WOLFSENTRY\_API\_VOID**  
*Function attribute for declaring/defining public void API functions.*
- **#define WOLFSENTRY\_API**  
*Function attribute for declaring/defining public API functions with return values.*
- **#define WOLFSENTRY\_LOCAL\_VOID**  
*Function attribute for declaring/defining private void functions.*
- **#define WOLFSENTRY\_LOCAL**  
*Function attribute for declaring/defining private functions with return values.*
- **#define WOLFSENTRY\_MAX\_ADDR\_BYTES** 16  
*The maximum size allowed for an address, in bytes. Can be overridden. Note that support for bitmask matching for an address family depends on [WOLFSENTRY\\_MAX\\_ADDR\\_BYTES](#) at least twice the max size of a bare address in that family, as the address and mask are internally stored as a single double-length byte vector. Note also that [WOLFSENTRY\\_MAX\\_ADDR\\_BYTES](#) entails proportional overhead if wolfSentry is built [WOLFSENTRY\\_NO\\_ALLOCA](#) or [WOLFSENTRY\\_C89](#).*
- **#define WOLFSENTRY\_MAX\_ADDR\_BITS** ([WOLFSENTRY\\_MAX\\_ADDR\\_BYTES](#)\*8)  
*The maximum size allowed for an address, in bits. Can be overridden.*
- **#define WOLFSENTRY\_MAX\_LABEL\_BYTES** 32  
*The maximum size allowed for a label, in bytes. Can be overridden.*
- **#define WOLFSENTRY\_BUILTIN\_LABEL\_PREFIX** "%"  
*The prefix string reserved for use in names of built-in actions and events.*
- **#define WOLFSENTRY\_KV\_MAX\_VALUE\_BYTES** 16384  
*The maximum size allowed for scalar user-defined values. Can be overridden.*
- **#define WOLFSENTRY\_CONFIG\_SIGNATURE**  
*Macro to use as the initializer for [wolfSentry\\_build\\_settings.config](#) and [wolfSentry\\_host\\_platform\\_interface.caller\\_build\\_settings](#).*

## Typedefs

- typedef unsigned char **byte**  
*8 bits unsigned*
- typedef uint16\_t **wolfSentry\_addr\_family\_t**  
*integer type for holding address family number*
- typedef uint16\_t **wolfSentry\_proto\_t**  
*integer type for holding protocol number*
- typedef uint16\_t **wolfSentry\_port\_t**  
*integer type for holding port number*
- typedef uint32\_t **wolfSentry\_ent\_id\_t**  
*integer type for holding table entry ID*
- typedef uint16\_t **wolfSentry\_addr\_bits\_t**  
*integer type for address prefix lengths (in bits)*
- typedef uint32\_t **wolfSentry\_hitcount\_t**  
*integer type for holding hit count statistics*
- typedef int64\_t **wolfSentry\_time\_t**  
*integer type for holding absolute and relative times, using microseconds in built-in implementations.*
- typedef uint16\_t **wolfSentry\_priority\_t**  
*integer type for holding event priority (smaller number is higher priority)*

### 10.14.1 Detailed Description

Target- and config-specific settings and abstractions for wolfSentry.

This file is included by [wolfSentry.h](#).

## 10.15 wolfSentry\_settings.h

[Go to the documentation of this file.](#)

```

00001 /*
00002  * wolfSentry_settings.h
00003  *
00004  * Copyright (C) 2022-2023 wolfSSL Inc.
00005  *
00006  * This file is part of wolfSentry.
00007  *
00008  * wolfSentry is free software; you can redistribute it and/or modify
00009  * it under the terms of the GNU General Public License as published by
00010  * the Free Software Foundation; either version 2 of the License, or
00011  * (at your option) any later version.
00012  *
00013  * wolfSentry is distributed in the hope that it will be useful,
00014  * but WITHOUT ANY WARRANTY; without even the implied warranty of
00015  * MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
00016  * GNU General Public License for more details.
00017  *
00018  * You should have received a copy of the GNU General Public License
00019  * along with this program; if not, write to the Free Software
00020  * Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1335, USA
00021  */
00022
00029 #ifndef WOLFSENTRY_SETTINGS_H
00030 #define WOLFSENTRY_SETTINGS_H
00031
00035 #ifdef WOLFSENTRY_FOR_DOXYGEN
00036 #define WOLFSENTRY_USER_SETTINGS_FILE "the_path"
00038 #undef WOLFSENTRY_USER_SETTINGS_FILE
00039 #endif
00040
00041 #ifdef WOLFSENTRY_USER_SETTINGS_FILE
00042     #include WOLFSENTRY_USER_SETTINGS_FILE
00043 #endif
00044
00045 #if !defined(BUILDING_LIBWOLFSENTRY) && !defined(WOLFSENTRY_USER_SETTINGS_FILE)
00046     #include <wolfSentry/wolfSentry_options.h>
00047 #endif
00048
00055 #ifdef WOLFSENTRY_FOR_DOXYGEN
00056 #define WOLFSENTRY_NO_ALLOCA
00057 #undef WOLFSENTRY_NO_ALLOCA
00058 #define WOLFSENTRY_C89
00059 #undef WOLFSENTRY_C89
00060 #endif
00061
00062 #ifdef WOLFSENTRY_C89
00063     #define WOLFSENTRY_NO_INLINE
00064     #ifndef WOLFSENTRY_NO_POSIX_MEMALIGN
00065         #define WOLFSENTRY_NO_POSIX_MEMALIGN
00066     #endif
00067     #define WOLFSENTRY_NO_DESIGNATED_INITIALIZERS
00068     #define WOLFSENTRY_NO_LONG_LONG
00069     #if !defined(WOLFSENTRY_USE_NONPOSIX_SEMAPHORES) && !defined(WOLFSENTRY_SINGLETHREADED)
00070         /* sem_timedwait() was added in POSIX 200112L */
00071         #define WOLFSENTRY_SINGLETHREADED
00072     #endif
00073 #endif
00074
00075 #ifndef __attribute_maybe_unused__
00076 #if defined(__GNUC__)
00077 #define __attribute_maybe_unused__ __attribute__((unused))
00078 #else
00079 #define __attribute_maybe_unused__
00080 #endif
00081 #endif
00082 #endif
00083
00084 #ifdef WOLFSENTRY_NO_INLINE
00086 #define inline __attribute_maybe_unused__
00088 #endif
00089
00090 #ifndef DO_NOTHING
00091 #define DO_NOTHING do {} while (0)
00093 #endif
00094
00097 #ifdef FREERTOS
00098     #include <FreeRTOS.h>
00099     #define WOLFSENTRY_CALL_DEPTH_RETURNS_STRING
00100     #if !defined(WOLFSENTRY_NO_STDIO_STREAMS) && !defined(WOLFSENTRY_PRINTF_ERR)
00101         #define WOLFSENTRY_PRINTF_ERR(...) printf(__VA_ARGS__)
00102     #endif
00103
00104     #define FREERTOS_NANOSECONDS_PER_SECOND 1000000000L

```

```

00105     #define FREERTOS_NANOSECONDS_PER_TICK          (FREERTOS_NANOSECONDS_PER_SECOND / configTICK_RATE_HZ)
00106
00107     #if !defined(SIZE_T_32) && !defined(SIZE_T_64)
00108         /* size_t is "unsigned int" in STM32 FreeRTOS */
00109         #define SIZE_T_32
00110     #endif
00111 #endif
00112
00117 #ifndef WOLFSENTRY_FOR_DOXYGEN
00118 #define WOLFSENTRY_NO_INTTYPES_H
00120 #undef WOLFSENTRY_NO_INTTYPES_H
00121 #endif
00122 #ifndef WOLFSENTRY_NO_INTTYPES_H
00123 #include <inttypes.h>
00124 #endif
00125 #ifndef WOLFSENTRY_FOR_DOXYGEN
00126 #define WOLFSENTRY_NO_STDINT_H
00128 #undef WOLFSENTRY_NO_STDINT_H
00129 #endif
00130 #ifndef WOLFSENTRY_NO_STDINT_H
00131 #include <stdint.h>
00132 #endif
00133
00136 #if !defined(SIZE_T_32) && !defined(SIZE_T_64)
00137     #if defined(__WORDSIZE) && (__WORDSIZE == 64)
00138         #define SIZE_T_64
00139     #elif defined(INTPTR_MAX) && defined(INT64_MAX) && (INTPTR_MAX == INT64_MAX)
00140         #define SIZE_T_64
00141     #elif defined(__WORDSIZE) && (__WORDSIZE == 32)
00142         #define SIZE_T_32
00143     #elif defined(INTPTR_MAX) && defined(INT32_MAX) && (INTPTR_MAX == INT32_MAX)
00144         #define SIZE_T_32
00145     #else
00146         #error "must define SIZE_T_32 or SIZE_T_64 with user settings."
00147     #endif
00148 #elif defined(SIZE_T_32) && defined(SIZE_T_64)
00149     #error "must define SIZE_T_32 xor SIZE_T_64."
00150 #endif
00151
00156 #if !defined(WOLFSENTRY_NO_STDIO_STREAMS) && !defined(WOLFSENTRY_PRINTF_ERR)
00157     #define WOLFSENTRY_PRINTF_ERR(...) fprintf(stderr, __VA_ARGS__)
00159 #endif
00160
00167 #ifndef WOLFSENTRY_FOR_DOXYGEN
00168 #define WOLFSENTRY_SINGLETHREADED
00170 #undef WOLFSENTRY_SINGLETHREADED
00171 #endif
00172
00173 #ifndef WOLFSENTRY_SINGLETHREADED
00174
00176 #define WOLFSENTRY_THREADSAFE
00179 #ifndef WOLFSENTRY_FOR_DOXYGEN
00180
00181 #define WOLFSENTRY_USE_NONPOSIX_SEMAPHORES
00183 #undef WOLFSENTRY_USE_NONPOSIX_SEMAPHORES
00184
00185 #define WOLFSENTRY_USE_NONPOSIX_THREADS
00187 #undef WOLFSENTRY_USE_NONPOSIX_THREADS
00188
00189 #define WOLFSENTRY_NO_GNU_ATOMICS
00191 #undef WOLFSENTRY_NO_GNU_ATOMICS
00192
00193 #endif
00194
00195 #ifndef WOLFSENTRY_USE_NONPOSIX_SEMAPHORES
00196     #if defined(__MACH__) || defined(FREERTOS) || defined(_WIN32)
00197         #define WOLFSENTRY_USE_NONPOSIX_SEMAPHORES
00198     #endif
00199 #endif
00200
00201 #ifndef WOLFSENTRY_USE_NONPOSIX_THREADS
00202     #if defined(FREERTOS) || defined(_WIN32)
00203         #define WOLFSENTRY_USE_NONPOSIX_THREADS
00204     #endif
00205 #endif
00206
00209 #ifndef WOLFSENTRY_USE_NONPOSIX_SEMAPHORES
00210     #define WOLFSENTRY_USE_NATIVE_POSIX_SEMAPHORES
00211 #endif
00212
00213 #ifndef WOLFSENTRY_USE_NONPOSIX_THREADS
00214     #define WOLFSENTRY_USE_NATIVE_POSIX_THREADS
00215 #endif
00216
00217 #ifndef WOLFSENTRY_NO_GNU_ATOMICS
00218     #define WOLFSENTRY_HAVE_GNU_ATOMICS
00219 #endif

```



```

00220
00223 #endif /* !WOLFSENTRY_SINGLETHREADED */
00224
00225 #ifdef WOLFSENTRY_FOR_DOXYGEN
00226
00227 #define WOLFSENTRY_NO_CLOCK_BUILTIN
00229 #undef WOLFSENTRY_NO_CLOCK_BUILTIN
00230
00231 #define WOLFSENTRY_NO_SEM_BUILTIN
00233 #undef WOLFSENTRY_NO_SEM_BUILTIN
00234
00235 #define WOLFSENTRY_NO_MALLOC_BUILTIN
00237 #undef WOLFSENTRY_NO_MALLOC_BUILTIN
00238
00239 #define WOLFSENTRY_NO_ERROR_STRINGS
00241 #undef WOLFSENTRY_NO_ERROR_STRINGS
00242
00243 #define WOLFSENTRY_NO_PROTOCOL_NAMES
00245 #undef WOLFSENTRY_NO_PROTOCOL_NAMES
00246
00247 #define WOLFSENTRY_NO_ADDR_BITMASK_MATCHING
00249 #undef WOLFSENTRY_NO_ADDR_BITMASK_MATCHING
00250
00251 #define WOLFSENTRY_NO_IPV6
00253 #undef WOLFSENTRY_NO_IPV6
00254
00255 #endif /* WOLFSENTRY_FOR_DOXYGEN */
00256
00257 #ifndef WOLFSENTRY_MAX_BITMASK_MATCHED_AFS
00258     #define WOLFSENTRY_MAX_BITMASK_MATCHED_AFS 4
00260 #endif
00261
00264 #ifndef WOLFSENTRY_NO_CLOCK_BUILTIN
00265     #define WOLFSENTRY_CLOCK_BUILTINS
00266 #endif
00267
00268 #ifndef WOLFSENTRY_NO_MALLOC_BUILTIN
00269     #define WOLFSENTRY_MALLOC_BUILTINS
00270 #endif
00271
00272 #ifndef WOLFSENTRY_NO_SEM_BUILTIN
00273     #define WOLFSENTRY_SEM_BUILTINS
00274 #endif
00275
00276 #ifndef WOLFSENTRY_NO_ERROR_STRINGS
00277     #define WOLFSENTRY_ERROR_STRINGS
00278 #endif
00279
00280 #ifndef WOLFSENTRY_NO_PROTOCOL_NAMES
00281     #define WOLFSENTRY_PROTOCOL_NAMES
00282 #endif
00283
00284 #ifndef WOLFSENTRY_NO_JSON_DOM
00285     #define WOLFSENTRY_HAVE_JSON_DOM
00286 #endif
00287
00288 #ifndef WOLFSENTRY_NO_ADDR_BITMASK_MATCHING
00289     #define WOLFSENTRY_ADDR_BITMASK_MATCHING
00290 #endif
00291
00292 #ifndef WOLFSENTRY_NO_IPV6
00293     #define WOLFSENTRY_IPV6
00294 #endif
00295
00298 #if !defined(WOLFSENTRY_NO_GETPROTOBY) && (!defined(__GLIBC__) || !defined(__USE_MISC) ||
defined(WOLFSENTRY_C89))
00299     /* get*by*_r() is non-standard. */
00300     #define WOLFSENTRY_NO_GETPROTOBY
00302 #endif
00303
00310 #if defined(WOLFSENTRY_USE_NATIVE_POSIX_SEMAPHORES) || defined(WOLFSENTRY_CLOCK_BUILTINS) ||
defined(WOLFSENTRY_MALLOC_BUILTINS)
00311 #ifndef _XOPEN_SOURCE
00312 #if __STDC_VERSION__ >= 201112L
00313 #define _XOPEN_SOURCE 700
00314 #elif __STDC_VERSION__ >= 199901L
00315 #define _XOPEN_SOURCE 600
00316 #else
00317 #define _XOPEN_SOURCE 500
00318 #endif /* __STDC_VERSION__ */
00319 #endif
00320 #endif
00321
00322 #if !defined(WOLFSENTRY_NO_POSIX_MEMALIGN) && (!defined(_POSIX_C_SOURCE) || (_POSIX_C_SOURCE <
200112L))
00323     #define WOLFSENTRY_NO_POSIX_MEMALIGN
00325 #endif

```



```

00326
00327 #if defined(__STRICT_ANSI__)
00328 #define WOLFSENTRY_FLEXIBLE_ARRAY_SIZE 1
00329 #elif defined(__GNUC__) && !defined(__clang__)
00330 #define WOLFSENTRY_FLEXIBLE_ARRAY_SIZE
00332 #else
00333 #define WOLFSENTRY_FLEXIBLE_ARRAY_SIZE 0
00334 #endif
00335
00338 #ifndef WOLFSENTRY_NO_TIME_H
00339 #ifndef __USE_POSIX199309
00340 /* glibc needs this for struct timespec with -std=c99 */
00341 #define __USE_POSIX199309
00342 #endif
00343 #endif
00344
00347 #ifdef SIZE_T_32
00348     #define SIZET_FMT "%u"
00349 #elif __STDC_VERSION__ >= 199901L
00350     #define SIZET_FMT "%zu"
00351 #else
00352     #define SIZET_FMT "%lu"
00354 #endif
00355
00356 #ifndef WOLFSENTRY_NO_STDDEF_H
00357 #include <stddef.h>
00358 #endif
00359 #ifndef WOLFSENTRY_NO_ASSERT_H
00360 #include <assert.h>
00361 #endif
00362 #ifndef WOLFSENTRY_NO_STDIO_H
00363 #ifndef __USE_ISOC99
00364 /* kludge to make glibc snprintf() prototype visible even when -std=c89 */
00366 #define __USE_ISOC99
00368 #include <stdio.h>
00369 #undef __USE_ISOC99
00370 #else
00371 #include <stdio.h>
00372 #endif
00373 #endif
00374 #ifndef WOLFSENTRY_NO_STRING_H
00375 #include <string.h>
00376 #endif
00377 #ifndef WOLFSENTRY_NO_STRINGS_H
00378 #include <strings.h>
00379 #endif
00380 #ifndef WOLFSENTRY_NO_TIME_H
00381 #include <time.h>
00382 #endif
00383
00384 typedef unsigned char byte;
00387 typedef uint16_t wolfentry_addr_family_t;
00390 typedef uint16_t wolfentry_proto_t;
00392 typedef uint16_t wolfentry_port_t;
00395 #ifdef WOLFSENTRY_ENT_ID_TYPE
00396 typedef WOLFSENTRY_ENT_ID_TYPE wolfentry_ent_id_t;
00397 #else
00398 typedef uint32_t wolfentry_ent_id_t;
00400 #endif
00401
00402 #ifndef WOLFSENTRY_ENT_ID_FMT
00403     #ifdef PRIu32
00404         #define WOLFSENTRY_ENT_ID_FMT "%" PRIu32
00405     #elif (defined(__WORDSIZE) && (__WORDSIZE == 32)) || \
00406         (defined(INTPTR_MAX) && defined(INT32_MAX) && (INTPTR_MAX == INT32_MAX))
00407         #define WOLFSENTRY_ENT_ID_FMT "%lu"
00408     #else
00409         #define WOLFSENTRY_ENT_ID_FMT "%u"
00411     #endif
00412 #endif
00413
00414 #define WOLFSENTRY_ENT_ID_NONE 0
00416 typedef uint16_t wolfentry_addr_bits_t;
00418 #ifdef WOLFSENTRY_HITCOUNT_TYPE
00419 typedef WOLFSENTRY_HITCOUNT_TYPE wolfentry_hitcount_t;
00420 #else
00421 typedef uint32_t wolfentry_hitcount_t;
00423 #define WOLFSENTRY_HITCOUNT_FMT "%u"
00425 #endif
00426 #ifdef WOLFSENTRY_TIME_TYPE
00427 typedef WOLFSENTRY_TIME_TYPE wolfentry_time_t;
00428 #else
00429 typedef int64_t wolfentry_time_t;
00431 #endif
00432
00433 #ifdef WOLFSENTRY_PRIORITY_TYPE
00434 typedef WOLFSENTRY_PRIORITY_TYPE wolfentry_priority_t;

```

```

00435 #else
00436 typedef uint16_t wolfentry_priority_t;
00437 #endif
00438
00439
00440 #ifndef attr_align_to
00441 #ifdef __GNUC__
00442 #define attr_align_to(x) __attribute__((aligned(x)))
00443 #elif defined(_MSC_VER)
00444 /* disable align warning, we want alignment ! */
00445 #pragma warning(disable: 4324)
00446 #define attr_align_to(x) __declspec(align(x))
00447 #else
00448 #error must supply definition for attr_align_to() macro.
00449 #endif
00450 #endif
00451
00452 #ifndef __wolfentry_wur
00453 #ifdef __wur
00454 #define __wolfentry_wur __wur
00455 #elif defined(__must_check)
00456 #define __wolfentry_wur __must_check
00457 #elif defined(__GNUC__) && (__GNUC__ >= 4)
00458 #define __wolfentry_wur __attribute__((warn_unused_result))
00459 #else
00460 #define __wolfentry_wur
00461 #endif
00462 #endif
00463 #endif
00464
00465 #ifndef wolfentry_static_assert
00466 #if defined(__GNUC__) && defined(static_assert) && !defined(__STRICT_ANSI__)
00467 /* note semicolon included in expansion, so that assert can completely disappear in ISO C builds. */
00468 #define wolfentry_static_assert(c) static_assert(c, #c);
00469 #define wolfentry_static_assert2(c, m) static_assert(c, m);
00470 #else
00471 #define wolfentry_static_assert(c)
00472 #define wolfentry_static_assert2(c, m)
00473 #endif
00474 #endif /* !wolfentry_static_assert */
00475
00476 #if defined(WOLFENTRY_THREADSAFE)
00477
00478 #ifndef WOLFENTRY_DEADLINE_NEVER
00479 #define WOLFENTRY_DEADLINE_NEVER (-1)
00480 #endif
00481 #ifndef WOLFENTRY_DEADLINE_NOW
00482 #define WOLFENTRY_DEADLINE_NOW (-2)
00483 #endif
00484
00485 #ifdef WOLFENTRY_USE_NATIVE_POSIX_SEMAPHORES
00486 #ifdef WOLFENTRY_SEMAPHORE_INCLUDE
00487 #include WOLFENTRY_SEMAPHORE_INCLUDE
00488 #else /* !WOLFENTRY_SEMAPHORE_INCLUDE */
00489 #ifndef __USE_XOPEN2K
00490 /* kludge to force glibc sem_timedwait() prototype visible with -std=c99 */
00491 #define __USE_XOPEN2K
00492 #include <semaphore.h>
00493 #undef __USE_XOPEN2K
00494 #else
00495 #include <semaphore.h>
00496 #endif
00497 #endif /* !WOLFENTRY_SEMAPHORE_INCLUDE */
00498
00499 #elif defined(__MACH__)
00500 #include <dispatch/dispatch.h>
00501 #include <semaphore.h>
00502 #define sem_t dispatch_semaphore_t
00503
00504 #elif defined(FREERTOS)
00505 #include <atomic.h>
00506
00507 #ifdef WOLFENTRY_SEMAPHORE_INCLUDE
00508 #include WOLFENTRY_SEMAPHORE_INCLUDE
00509 #else
00510 #include <semphr.h>
00511 #endif
00512
00513 #define SEM_VALUE_MAX 0x7FFFU
00514
00515 #define sem_t StaticSemaphore_t
00516

```

```

00534 #else
00535
00542 #ifdef WOLFSENTRY_FOR_DOXYGEN
00543 #define WOLFSENTRY_SEMAPHORE_INCLUDE "the_path"
00545 #undef WOLFSENTRY_SEMAPHORE_INCLUDE
00546 #define WOLFSENTRY_THREAD_INCLUDE "the_path"
00548 #undef WOLFSENTRY_THREAD_INCLUDE
00549 #define WOLFSENTRY_THREAD_ID_T thread_id_type
00551 #undef WOLFSENTRY_THREAD_ID_T
00552 #define WOLFSENTRY_THREAD_GET_ID_HANDLER pthread_self_ish_function
00554 #undef WOLFSENTRY_THREAD_GET_ID_HANDLER
00555 #endif
00556
00563 #ifdef WOLFSENTRY_SEMAPHORE_INCLUDE
00564 #include WOLFSENTRY_SEMAPHORE_INCLUDE
00565 #endif
00566
00567 #endif
00568
00569 #ifdef WOLFSENTRY_THREAD_INCLUDE
00570 #include WOLFSENTRY_THREAD_INCLUDE
00571 #elif defined(WOLFSENTRY_USE_NATIVE_POSIX_THREADS)
00572 #include <pthread.h>
00573 #endif
00574 #ifdef WOLFSENTRY_THREAD_ID_T
00575 typedef WOLFSENTRY_THREAD_ID_T wolfsentry_thread_id_t;
00576 #elif defined(WOLFSENTRY_USE_NATIVE_POSIX_THREADS)
00577 typedef pthread_t wolfsentry_thread_id_t;
00578 #elif defined(FREERTOS)
00579 typedef TaskHandle_t wolfsentry_thread_id_t;
00580 #else
00581 #error Must supply WOLFSENTRY_THREAD_ID_T for WOLFSENTRY_THREADSAFE on non-POSIX targets.
00582 #endif
00583 /* note WOLFSENTRY_THREAD_GET_ID_HANDLER must return WOLFSENTRY_THREAD_NO_ID on failure. */
00584 #ifdef WOLFSENTRY_THREAD_GET_ID_HANDLER
00585 #elif defined(WOLFSENTRY_USE_NATIVE_POSIX_THREADS)
00586 #define WOLFSENTRY_THREAD_GET_ID_HANDLER pthread_self
00587 #elif defined(FREERTOS)
00588 #define WOLFSENTRY_THREAD_GET_ID_HANDLER xTaskGetCurrentTaskHandle
00589 #else
00590 #error Must supply WOLFSENTRY_THREAD_GET_ID_HANDLER for WOLFSENTRY_THREADSAFE on non-POSIX
00591 targets.
00592 #endif
00593
00593 struct wolfsentry_thread_context;
00594
00595 /* WOLFSENTRY_THREAD_NO_ID must be zero. */
00596 #define WOLFSENTRY_THREAD_NO_ID 0
00597
00599 struct wolfsentry_thread_context_public {
00600     uint64_t opaque[8];
00601 };
00602
00603 #define WOLFSENTRY_THREAD_CONTEXT_PUBLIC_INITIALIZER {0}
00604 #endif
00605
00614 #ifdef BUILDING_LIBWOLFSENTRY
00615 #if defined(_MSC_VER) || defined(__MINGW32__) || defined(__CYGWIN__) || \
00616     defined(_WIN32_WCE)
00617     #if defined(WOLFSENTRY_DLL)
00618         #define WOLFSENTRY_API_BASE __declspec(dllexport)
00619     #else
00620         #define WOLFSENTRY_API_BASE
00621     #endif
00622     #define WOLFSENTRY_LOCAL_BASE
00623 #elif defined(HAVE_VISIBILITY) && HAVE_VISIBILITY
00624     #define WOLFSENTRY_API_BASE __attribute__((visibility("default")))
00625     #define WOLFSENTRY_LOCAL_BASE __attribute__((visibility("hidden")))
00626 #elif defined(__SUNPRO_C) && (__SUNPRO_C >= 0x550)
00627     #define WOLFSENTRY_API_BASE __global
00628     #define WOLFSENTRY_LOCAL_BASE __hidden
00629 #else
00630     #define WOLFSENTRY_API_BASE
00631     #define WOLFSENTRY_LOCAL_BASE
00632 #endif /* HAVE_VISIBILITY */
00633 #else /* !BUILDING_LIBWOLFSENTRY */
00634 #if defined(_MSC_VER) || defined(__MINGW32__) || defined(__CYGWIN__) || \
00635     defined(_WIN32_WCE)
00636     #if defined(WOLFSENTRY_DLL)
00637         #define WOLFSENTRY_API_BASE __declspec(dllimport)
00638     #else
00639         #define WOLFSENTRY_API_BASE
00640     #endif
00641     #define WOLFSENTRY_LOCAL_BASE
00642 #else
00643     #define WOLFSENTRY_API_BASE
00644     #define WOLFSENTRY_LOCAL_BASE

```

```

00645     #endif
00646 #endif /* !BUILDING_LIBWOLFSENTRY */
00647
00650 #define WOLFSENTRY_API_VOID WOLFSENTRY_API_BASE void
00652 #define WOLFSENTRY_API WOLFSENTRY_API_BASE __wolfentry_wur
00655 #define WOLFSENTRY_LOCAL_VOID WOLFSENTRY_LOCAL_BASE void
00657 #define WOLFSENTRY_LOCAL WOLFSENTRY_LOCAL_BASE __wolfentry_wur
00662 #ifndef WOLFSENTRY_NO_DESIGNATED_INITIALIZERS
00663 #define WOLFSENTRY_HAVE_DESIGNATED_INITIALIZERS
00664 #endif
00665
00666 #ifndef WOLFSENTRY_NO_LONG_LONG
00667 #define WOLFSENTRY_HAVE_LONG_LONG
00668 #endif
00669
00672 #ifndef WOLFSENTRY_MAX_ADDR_BYTES
00673 #define WOLFSENTRY_MAX_ADDR_BYTES 16
00675 #elif WOLFSENTRY_MAX_ADDR_BYTES * 8 > 0xffff
00676 #error WOLFSENTRY_MAX_ADDR_BYTES * 8 must fit in a uint16_t.
00677 #endif
00678
00679 #ifndef WOLFSENTRY_MAX_ADDR_BITS
00680 #define WOLFSENTRY_MAX_ADDR_BITS (WOLFSENTRY_MAX_ADDR_BYTES*8)
00682 #else
00683 #if WOLFSENTRY_MAX_ADDR_BITS > (WOLFSENTRY_MAX_ADDR_BYTES*8)
00684 #error WOLFSENTRY_MAX_ADDR_BITS is too large for given/default WOLFSENTRY_MAX_ADDR_BYTES
00685 #endif
00686 #endif
00687
00688 #ifndef WOLFSENTRY_MAX_LABEL_BYTES
00689 #define WOLFSENTRY_MAX_LABEL_BYTES 32
00691 #elif WOLFSENTRY_MAX_LABEL_BYTES > 0xff
00692 #error WOLFSENTRY_MAX_LABEL_BYTES must fit in a byte.
00693 #endif
00694
00695 #ifndef WOLFSENTRY_BUILTIN_LABEL_PREFIX
00696 #define WOLFSENTRY_BUILTIN_LABEL_PREFIX "%"
00698 #endif
00699
00700 #ifndef WOLFSENTRY_KV_MAX_VALUE_BYTES
00701 #define WOLFSENTRY_KV_MAX_VALUE_BYTES 16384
00703 #endif
00704
00705 #if defined(WOLFSENTRY_ENT_ID_TYPE) || \
00706     defined(WOLFSENTRY_HITCOUNT_TYPE) || \
00707     defined(WOLFSENTRY_TIME_TYPE) || \
00708     defined(WOLFSENTRY_PRIORITY_TYPE) || \
00709     defined(WOLFSENTRY_THREAD_ID_T) || \
00710     defined(SIZE_T_32) || \
00711     defined(SIZE_T_64)
00712 #define WOLFSENTRY_USER_DEFINED_TYPES
00713 #endif
00714
00723 enum wolfentry_build_flags {
00724     WOLFSENTRY_CONFIG_FLAG_ENDIANNESS_ONE = (1U < 0U),
00725     WOLFSENTRY_CONFIG_FLAG_USER_DEFINED_TYPES = (1U < 1U),
00726     WOLFSENTRY_CONFIG_FLAG_THREADSAFE = (1U < 2U),
00727     WOLFSENTRY_CONFIG_FLAG_CLOCK_BUILTINS = (1U < 3U),
00728     WOLFSENTRY_CONFIG_FLAG_MALLOC_BUILTINS = (1U < 4U),
00729     WOLFSENTRY_CONFIG_FLAG_ERROR_STRINGS = (1U < 5U),
00730     WOLFSENTRY_CONFIG_FLAG_PROTOCOL_NAMES = (1U < 6U),
00731     WOLFSENTRY_CONFIG_FLAG_NO_STDIO_STREAMS = (1U < 7U),
00732     WOLFSENTRY_CONFIG_FLAG_NO_JSON = (1U < 8U),
00733     WOLFSENTRY_CONFIG_FLAG_HAVE_JSON_DOM = (1U < 9U),
00734     WOLFSENTRY_CONFIG_FLAG_DEBUG_CALL_TRACE = (1U < 10U),
00735     WOLFSENTRY_CONFIG_FLAG_LWIP = (1U < 11U),
00736     WOLFSENTRY_CONFIG_FLAG_SHORT_ENUMS = (1U < 12U),
00737     WOLFSENTRY_CONFIG_FLAG_ADDR_BITMASKS = (1U < 13U),
00738     WOLFSENTRY_CONFIG_FLAG_MAX = WOLFSENTRY_CONFIG_FLAG_ADDR_BITMASKS,
00739     WOLFSENTRY_CONFIG_FLAG_ENDIANNESS_ZERO = (0U < 31U)
00740 };
00741
00745 struct wolfentry_build_settings {
00746     uint32_t version;
00748     uint32_t config;
00750 };
00751
00752 #if !defined(BUILDING_LIBWOLFSENTRY) || defined(WOLFSENTRY_DEFINE_BUILD_SETTINGS)
00753
00756 #ifndef WOLFSENTRY_USER_DEFINED_TYPES
00757     #define _WOLFSENTRY_CONFIG_FLAG_VALUE_USER_DEFINED_TYPES WOLFSENTRY_CONFIG_FLAG_USER_DEFINED_TYPES
00758 #else
00759     #define _WOLFSENTRY_CONFIG_FLAG_VALUE_USER_DEFINED_TYPES 0
00760 #endif
00761
00762 #ifndef WOLFSENTRY_THREADSAFE
00763     #define _WOLFSENTRY_CONFIG_FLAG_VALUE_THREADSAFE WOLFSENTRY_CONFIG_FLAG_THREADSAFE

```

```
00764 #else
00765     #define _WOLFSENTRY_CONFIG_FLAG_VALUE_THREADSafe 0
00766 #endif
00767
00768 #ifdef WOLFSENTRY_CLOCK_BUILTINS
00769     #define _WOLFSENTRY_CONFIG_FLAG_VALUE_CLOCK_BUILTINS WOLFSENTRY_CONFIG_FLAG_CLOCK_BUILTINS
00770 #else
00771     #define _WOLFSENTRY_CONFIG_FLAG_VALUE_CLOCK_BUILTINS 0
00772 #endif
00773
00774 #ifdef WOLFSENTRY_MALLOC_BUILTINS
00775     #define _WOLFSENTRY_CONFIG_FLAG_VALUE_MALLOC_BUILTINS WOLFSENTRY_CONFIG_FLAG_MALLOC_BUILTINS
00776 #else
00777     #define _WOLFSENTRY_CONFIG_FLAG_VALUE_MALLOC_BUILTINS 0
00778 #endif
00779
00780 #ifdef WOLFSENTRY_ERROR_STRINGS
00781     #define _WOLFSENTRY_CONFIG_FLAG_VALUE_ERROR_STRINGS WOLFSENTRY_CONFIG_FLAG_ERROR_STRINGS
00782 #else
00783     #define _WOLFSENTRY_CONFIG_FLAG_VALUE_ERROR_STRINGS 0
00784 #endif
00785
00786 #ifdef WOLFSENTRY_PROTOCOL_NAMES
00787     #define _WOLFSENTRY_CONFIG_FLAG_VALUE_PROTOCOL_NAMES WOLFSENTRY_CONFIG_FLAG_PROTOCOL_NAMES
00788 #else
00789     #define _WOLFSENTRY_CONFIG_FLAG_VALUE_PROTOCOL_NAMES 0
00790 #endif
00791
00792 #ifdef WOLFSENTRY_NO_STDIO_STREAMS
00793     #define _WOLFSENTRY_CONFIG_FLAG_VALUE_NO_STDIO_STREAMS WOLFSENTRY_CONFIG_FLAG_NO_STDIO_STREAMS
00794 #else
00795     #define _WOLFSENTRY_CONFIG_FLAG_VALUE_NO_STDIO_STREAMS 0
00796 #endif
00797
00798 #ifdef WOLFSENTRY_NO_JSON
00799     #define _WOLFSENTRY_CONFIG_FLAG_VALUE_NO_JSON WOLFSENTRY_CONFIG_FLAG_NO_JSON
00800 #else
00801     #define _WOLFSENTRY_CONFIG_FLAG_VALUE_NO_JSON 0
00802 #endif
00803
00804 #ifdef WOLFSENTRY_HAVE_JSON_DOM
00805     #define _WOLFSENTRY_CONFIG_FLAG_VALUE_HAVE_JSON_DOM WOLFSENTRY_CONFIG_FLAG_HAVE_JSON_DOM
00806 #else
00807     #define _WOLFSENTRY_CONFIG_FLAG_VALUE_HAVE_JSON_DOM 0
00808 #endif
00809
00810 #ifdef WOLFSENTRY_DEBUG_CALL_TRACE
00811     #define _WOLFSENTRY_CONFIG_FLAG_VALUE_DEBUG_CALL_TRACE WOLFSENTRY_CONFIG_FLAG_DEBUG_CALL_TRACE
00812 #else
00813     #define _WOLFSENTRY_CONFIG_FLAG_VALUE_DEBUG_CALL_TRACE 0
00814 #endif
00815
00816 #ifdef WOLFSENTRY_LWIP
00817     #define _WOLFSENTRY_CONFIG_FLAG_VALUE_LWIP WOLFSENTRY_CONFIG_FLAG_LWIP
00818 #else
00819     #define _WOLFSENTRY_CONFIG_FLAG_VALUE_LWIP 0
00820 #endif
00821
00822 /* with compilers that can't evaluate the below expression as a compile-time
00823  * constant, WOLFSENTRY_SHORT_ENUMS can be defined in user settings to 0 or
00824  * 1 to avoid the dependency.
00825  */
00826 #ifdef WOLFSENTRY_SHORT_ENUMS
00827 #if WOLFSENTRY_SHORT_ENUMS == 0
00828     #define _WOLFSENTRY_CONFIG_FLAG_VALUE_SHORT_ENUMS 0
00829 #else
00830     #define _WOLFSENTRY_CONFIG_FLAG_VALUE_SHORT_ENUMS WOLFSENTRY_CONFIG_FLAG_SHORT_ENUMS
00831 #endif
00832 #else
00833     #define _WOLFSENTRY_CONFIG_FLAG_VALUE_SHORT_ENUMS ((sizeof(wolfentry_init_flags_t) < sizeof(int))
? WOLFSENTRY_CONFIG_FLAG_SHORT_ENUMS : 0)
00834 #endif
00835
00836 #ifdef WOLFSENTRY_ADDR_BITMASK_MATCHING
00837     #define _WOLFSENTRY_CONFIG_FLAG_VALUE_ADDR_BITMASKS WOLFSENTRY_CONFIG_FLAG_ADDR_BITMASKS
00838 #else
00839     #define _WOLFSENTRY_CONFIG_FLAG_VALUE_ADDR_BITMASKS 0
00840 #endif
00841
00842 #define WOLFSENTRY_CONFIG_SIGNATURE ( \
00843     WOLFSENTRY_CONFIG_FLAG_ENDIANNESS_ONE | \
00844     _WOLFSENTRY_CONFIG_FLAG_VALUE_USER_DEFINED_TYPES | \
00845     _WOLFSENTRY_CONFIG_FLAG_VALUE_THREADSafe | \
00846     _WOLFSENTRY_CONFIG_FLAG_VALUE_CLOCK_BUILTINS | \
00847     _WOLFSENTRY_CONFIG_FLAG_VALUE_MALLOC_BUILTINS | \
00848     _WOLFSENTRY_CONFIG_FLAG_VALUE_ERROR_STRINGS | \
00849     _WOLFSENTRY_CONFIG_FLAG_VALUE_PROTOCOL_NAMES | \
```

```

00853     _WOLFSENTRY_CONFIG_FLAG_VALUE_NO_STDIO_STREAMS | \
00854     _WOLFSENTRY_CONFIG_FLAG_VALUE_NO_JSON | \
00855     _WOLFSENTRY_CONFIG_FLAG_VALUE_HAVE_JSON_DOM | \
00856     _WOLFSENTRY_CONFIG_FLAG_VALUE_DEBUG_CALL_TRACE | \
00857     _WOLFSENTRY_CONFIG_FLAG_VALUE_LWIP | \
00858     _WOLFSENTRY_CONFIG_FLAG_VALUE_SHORT_ENUMS | \
00859     _WOLFSENTRY_CONFIG_FLAG_VALUE_ADDR_BITMASKS)
00860
00861 static __attribute__((maybe_unused)) struct wolfentry_build_settings wolfentry_build_settings = {
00862 #ifdef WOLFSENTRY_HAVE_DESIGNATED_INITIALIZERS
00863     .version =
00864 #endif
00865     WOLFSENTRY_VERSION,
00866 #ifdef WOLFSENTRY_HAVE_DESIGNATED_INITIALIZERS
00867     .config =
00868 #endif
00869     WOLFSENTRY_CONFIG_SIGNATURE
00870 };
00871 #endif /* !BUILDING_LIBWOLFSENTRY || WOLFSENTRY_DEFINE_BUILD_SETTINGS */
00872
00873 #endif /* WOLFSENTRY_SETTINGS_H */

```

## 10.16 wolfentry/wolfentry\_util.h File Reference

Utility and convenience macros for both internal and application use.

### Macros

- **#define offsetof**(structure, element)  
*Evaluates to the byte offset of element in structure.*
- **#define sizeof\_field**(structure, element)  
*Evaluates to the size in bytes of element in structure.*
- **#define instance\_of\_field**(structure, element)  
*Evaluates to a dummy instance of element in structure, e.g. to be passed to [MAX\\_UINT\\_OF\(\)](#).*
- **#define container\_of**(ptr, container\_type, member\_name)  
*Evaluates to a pointer to the struct of type container\_type within which ptr points to the member named member\_name.*
- **#define length\_of\_array**(x)  
*Evaluates to the number of elements in x, which must be an array.*
- **#define end\_ptr\_of\_array**(x)  
*Evaluates to a pointer to the byte immediately following the end of array x.*
- **#define popcount32**(x)  
*Evaluates to the number of set bits in x.*
- **#define LOG2\_32**(x)  
*Evaluates to the floor of the base 2 logarithm of x, which must be a 32 bit integer.*
- **#define LOG2\_64**(x)  
*Evaluates to the floor of the base 2 logarithm of x, which must be a 64 bit integer.*
- **#define streq**(vs, fs, vs\_len)  
*Evaluates to true iff string vs of length vs\_len (not including a terminating null, if any) equals null-terminated string fs.*
- **#define strcaseeq**(vs, fs, vs\_len)  
*Evaluates to true iff string vs of length vs\_len (not including a terminating null, if any) equals null-terminated string fs, neglecting case distinctions.*
- **#define WOLFSENTRY\_BYTE\_STREAM\_DECLARE\_STACK**(buf, bufsiz)  
*Byte stream helper macro.*
- **#define WOLFSENTRY\_BYTE\_STREAM\_DECLARE\_HEAP**(buf, bufsiz)  
*Byte stream helper macro.*

- **#define WOLFSENTRY\_BYTE\_STREAM\_INIT\_HEAP(buf)**  
*Byte stream helper macro.*
- **#define WOLFSENTRY\_BYTE\_STREAM\_FREE\_HEAP(buf)**  
*Byte stream helper macro.*
- **#define WOLFSENTRY\_BYTE\_STREAM\_RESET(buf)**  
*Byte stream helper macro.*
- **#define WOLFSENTRY\_BYTE\_STREAM\_LEN(buf)**  
*Byte stream helper macro.*
- **#define WOLFSENTRY\_BYTE\_STREAM\_HEAD(buf)**  
*Byte stream helper macro.*
- **#define WOLFSENTRY\_BYTE\_STREAM\_PTR(buf)**  
*Byte stream helper macro.*
- **#define WOLFSENTRY\_BYTE\_STREAM\_SPC(buf)**  
*Byte stream helper macro.*
- **#define MAX\_UINT\_OF(x)**  
*Evaluates to the largest representable unsigned int in a word the size of x.*
- **#define MAX\_SINT\_OF(x)**  
*Evaluates to the largest representable signed int in a word the size of x.*
- **#define WOLFSENTRY\_SET\_BITS(enumint, bits)**  
*Sets the designated bits in enumint.*
- **#define WOLFSENTRY\_CHECK\_BITS(enumint, bits)**  
*Evaluates to true if bits are all set in enumint.*
- **#define WOLFSENTRY\_CLEAR\_BITS(enumint, bits)**  
*Clears the designated bits in enumint.*
- **#define WOLFSENTRY\_MASKIN\_BITS(enumint, bits)**  
*Evaluates to the bits that are set in both enumint and bits.*
- **#define WOLFSENTRY\_MASKOUT\_BITS(enumint, bits)**  
*Evaluates to the bits that are set enumint but not set in bits.*
- **#define WOLFSENTRY\_CLEAR\_ALL\_BITS(enumint)**  
*Clears all bits in enumint.*
- **#define BITS\_PER\_BYTE 8**
- **#define WOLFSENTRY\_BITS\_TO\_BYTES(x)**  
*Evaluates to the number of bytes needed to represent x bits.*
- **#define WOLFSENTRY\_ATOMIC\_INCREMENT(i, x)**  
*Adds x to i thread-safely, returning the sum.*
- **#define WOLFSENTRY\_ATOMIC\_DECREMENT(i, x)**  
*Subtracts x from i thread-safely, returning the difference.*
- **#define WOLFSENTRY\_ATOMIC\_POSTINCREMENT(i, x)**  
*Adds x to i thread-safely, returning the operand i.*
- **#define WOLFSENTRY\_ATOMIC\_POSTDECREMENT(i, x)**  
*Subtracts x from i thread-safely, returning the operand i.*
- **#define WOLFSENTRY\_ATOMIC\_STORE(i, x)**  
*Sets i to x, subject to benign races from other threads.*
- **#define WOLFSENTRY\_ATOMIC\_LOAD(i)**  
*Returns the value of i, subject to benign races from other threads.*
- **#define WOLFSENTRY\_ATOMIC\_CMPXCHG(ptr, expected, desired, weak\_p, success\_memorder, failure\_↵  
\_memorder)**  
*Sets \*ptr to desired and returns true iff \*ptr has the value \*expected, otherwise sets \*expected to the  
actual value of \*ptr and returns false.*
- **#define WOLFSENTRY\_ATOMIC\_INCREMENT\_BY\_ONE(i)**  
*Adds 1 to i thread-safely, returning the sum.*

- `#define WOLFSENTRY_ATOMIC_DECREMENT_BY_ONE(i)`  
*Subtracts 1 from `i` thread-safely, returning the difference.*
- `#define WOLFSENTRY_ATOMIC_TEST_AND_SET(i, expected, intended)`
- `#define WOLFSENTRY_ATOMIC_UPDATE_FLAGS(i, set_i, clear_i, pre_i, post_i)`  
*Sets `i` to `intended` and returns true iff `i` has the value `expected`, otherwise sets `expected` to the actual value of `i` and returns false.*
- `#define WOLFSENTRY_ATOMIC_RESET(i, pre_i)`  
*Sets bits `set_i` in `i`, clears bits `clear_i` in `i`, and sets `pre_i` to the value of `i` before any changes, and `post_i` to the value of `i` after changes.*
- `#define WOLFSENTRY_ATOMIC_INCREMENT_UNSIGNED_SAFELY(i, x, out)`  
*Clears all bits in `i`, saving the previous value of `i` in `pre_i`.*
- `#define WOLFSENTRY_ATOMIC_INCREMENT_UNSIGNED_SAFELY_BY_ONE(i, out)`  
*Adds `x` to unsigned integer `i`, guarding against overflow, saving the sum to `out`. If overflow would occur, error is indicated by saving 0 to `out`, and `i` is left unchanged.*
- `#define WOLFSENTRY_ATOMIC_DECREMENT_UNSIGNED_SAFELY(i, x, out)`  
*Increments unsigned integer `i` by one, guarding against overflow, saving the result to `out`. If overflow would occur, error is indicated by saving 0 to `out`, and `i` is left unchanged.*
- `#define WOLFSENTRY_ATOMIC_DECREMENT_UNSIGNED_SAFELY_BY_ONE(i, out)`  
*Subtracts `x` from unsigned integer `i`, guarding against underflow, saving the difference to `out`. If underflow would occur, error is indicated by saving a max-value integer (all-1s) to `out`, and `i` is left unchanged.*

### 10.16.1 Detailed Description

Utility and convenience macros for both internal and application use.

Included by `wolfentry.h`.

### 10.16.2 Macro Definition Documentation

#### 10.16.2.1 WOLFSENTRY\_ATOMIC\_DECREMENT\_UNSIGNED\_SAFELY

```
#define WOLFSENTRY_ATOMIC_DECREMENT_UNSIGNED_SAFELY(  
    i,  
    x,  
    out )
```

Increments unsigned integer `i` by one, guarding against overflow, saving the result to `out`. If overflow would occur, error is indicated by saving 0 to `out`, and `i` is left unchanged.

<

#### 10.16.2.2 WOLFSENTRY\_ATOMIC\_DECREMENT\_UNSIGNED\_SAFELY\_BY\_ONE

```
#define WOLFSENTRY_ATOMIC_DECREMENT_UNSIGNED_SAFELY_BY_ONE(  
    i,  
    out )
```

Subtracts `x` from unsigned integer `i`, guarding against underflow, saving the difference to `out`. If underflow would occur, error is indicated by saving a max-value integer (all-1s) to `out`, and `i` is left unchanged.

<



**10.16.2.3 WOLFSENTRY\_ATOMIC\_INCREMENT\_UNSIGNED\_SAFELY**

```
#define WOLFSENTRY_ATOMIC_INCREMENT_UNSIGNED_SAFELY(
    i,
    x,
    out )
```

Clears all bits in *i*, saving the previous value of *i* in *pre\_i*.

&lt;

**10.16.2.4 WOLFSENTRY\_ATOMIC\_INCREMENT\_UNSIGNED\_SAFELY\_BY\_ONE**

```
#define WOLFSENTRY_ATOMIC_INCREMENT_UNSIGNED_SAFELY_BY_ONE(
    i,
    out )
```

Adds *x* to unsigned integer *i*, guarding against overflow, saving the sum to *out*. If overflow would occur, error is indicated by saving 0 to *out*, and *i* is left unchanged.

&lt;

**10.16.2.5 WOLFSENTRY\_ATOMIC\_RESET**

```
#define WOLFSENTRY_ATOMIC_RESET(
    i,
    pre_i )
```

Sets bits *set\_i* in *i*, clears bits *clear\_i* in *i*, and sets *pre\_i* to the value of *i* before any changes, and *post\_i* to the value of *i* after changes.

&lt;

**10.16.2.6 WOLFSENTRY\_ATOMIC\_TEST\_AND\_SET**

```
#define WOLFSENTRY_ATOMIC_TEST_AND_SET(
    i,
    expected,
    intended )
```

**Value:**

```
WOLFSENTRY_ATOMIC_CMPXCHG(
    &(i),
    &(expected),
    intended,
    0 /* weak */,
    __ATOMIC_SEQ_CST /* success_memmodel */,
    __ATOMIC_SEQ_CST /* failure_memmodel */);
```

```

/
/
/
/
/
/
```

### 10.16.2.7 WOLFSENTRY\_ATOMIC\_UPDATE\_FLAGS

```
#define WOLFSENTRY_ATOMIC_UPDATE_FLAGS (
    i,
    set_i,
    clear_i,
    pre_i,
    post_i )
```

Sets *i* to intended and returns true iff *i* has the value expected, otherwise sets expected to the actual value of *i* and returns false.

<

## 10.17 wolfentry\_util.h

[Go to the documentation of this file.](#)

```
00001 /*
00002  * wolfentry_util.h
00003  *
00004  * Copyright (C) 2021-2023 wolfSSL Inc.
00005  *
00006  * This file is part of wolfSentry.
00007  *
00008  * wolfSentry is free software; you can redistribute it and/or modify
00009  * it under the terms of the GNU General Public License as published by
00010  * the Free Software Foundation; either version 2 of the License, or
00011  * (at your option) any later version.
00012  *
00013  * wolfSentry is distributed in the hope that it will be useful,
00014  * but WITHOUT ANY WARRANTY; without even the implied warranty of
00015  * MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
00016  * GNU General Public License for more details.
00017  *
00018  * You should have received a copy of the GNU General Public License
00019  * along with this program; if not, write to the Free Software
00020  * Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1335, USA
00021  */
00022
00029 #ifndef WOLFSENTRY_UTIL_H
00030 #define WOLFSENTRY_UTIL_H
00031
00032 #ifndef offsetof
00033 /* gcc and clang define this in stddef.h to use sanitizer-safe builtins. */
00034 #define offsetof(structure, element) ((uintptr_t)&((structure *)0)->element)
00035 #endif
00036 #ifndef sizeof_field
00037 #define sizeof_field(structure, element) sizeof(((structure *)0)->element)
00038 #endif
00039 #ifndef instance_of_field
00040 #define instance_of_field(structure, element) (((structure *)0)->element)
00041 #endif
00042 #ifndef container_of
00043 #define container_of(ptr, container_type, member_name) ((container_type *) (void *) ((byte *) (ptr)) -
    offsetof(container_type, member_name))
00044 #endif
00045 #ifndef length_of_array
00046 #define length_of_array(x) (sizeof (x) / sizeof (x)[0])
00047 #endif
00048 #ifndef end_ptr_of_array
00049 #define end_ptr_of_array(x) (&(x)[length_of_array(x)])
00050 #endif
00051 #ifndef popcount32
00052 #ifdef __GNUC__
00053 #define popcount32(x) __builtin_popcount(x)
00054 #else
00055 #error Must supply binding for popcount32() on non-__GNUC__ targets.
00056 #endif
00057 #endif
00058 #if defined(__GNUC__) && !defined(WOLFSENTRY_NO_BUILTIN_CLZ)
00059 #ifndef LOG2_32
00060 #define LOG2_32(x) (31 - __builtin_clz((unsigned int)(x)))
00061 #endif
00062 #endif
```

```

00071 #endif
00072 #ifndef LOG2_64
00073 #define LOG2_64(x) ((sizeof(unsigned long long) * 8ULL) - (unsigned long
long) __builtin_clzll((unsigned long long) (x)) - 1ULL)
00075 #endif
00076 #endif
00077
00078 #define streq(vs,fs,vs_len) (((vs_len) == strlen(fs)) && (memcmp(vs,fs,vs_len) == 0))
00080 #define strcaseeq(vs,fs,vs_len) (((vs_len) == strlen(fs)) && (strncasecmp(vs,fs,vs_len) == 0))
00083 #define WOLFSENTRY_BYTE_STREAM_DECLARE_STACK(buf, bufsiz) static const size_t buf ## siz = (bufsiz);
unsigned char (buf)[bufsiz], *buf ## _p; size_t buf ## spc
00085 #define WOLFSENTRY_BYTE_STREAM_DECLARE_HEAP(buf, bufsiz) static const size_t buf ## siz = (bufsiz);
unsigned char *(buf), *buf ## _p; size_t buf ## spc
00087 #define WOLFSENTRY_BYTE_STREAM_INIT_HEAP(buf) ((buf) = (unsigned char *)WOLFSENTRY_MALLOC(buf ## siz))
00089 #define WOLFSENTRY_BYTE_STREAM_FREE_HEAP(buf) WOLFSENTRY_FREE(buf)
00091 #define WOLFSENTRY_BYTE_STREAM_RESET(buf) do { (buf ## _p) = (buf); (buf ## spc) = (buf ## siz); }
while (0)
00093 #define WOLFSENTRY_BYTE_STREAM_LEN(buf) ((buf ## siz) - (buf ## spc))
00095 #define WOLFSENTRY_BYTE_STREAM_HEAD(buf) (buf)
00097 #define WOLFSENTRY_BYTE_STREAM_PTR(buf) (&(buf ## _p))
00099 #define WOLFSENTRY_BYTE_STREAM_SPC(buf) (&(buf ## spc))
00102 #define MAX_UINT_OF(x) (((uint64_t)1 < ((sizeof(x) * (uint64_t)BITS_PER_BYTE) - (uint64_t)1)) -
(uint64_t)1) | ((uint64_t)1 < ((sizeof(x) * (uint64_t)BITS_PER_BYTE) - (uint64_t)1)))
00104 #define MAX_SINT_OF(x) ((int64_t) (((uint64_t)1 < ((sizeof(x) * (uint64_t)BITS_PER_BYTE) -
(uint64_t)2)) - (uint64_t)1) | ((uint64_t)1 < ((sizeof(x) * (uint64_t)BITS_PER_BYTE) - (uint64_t)2))))
00107 #define WOLFSENTRY_SET_BITS(enumint, bits) ((enumint) |= (bits))
00109 #define WOLFSENTRY_CHECK_BITS(enumint, bits) (((enumint) & (bits)) == (bits))
00111 #define WOLFSENTRY_CLEAR_BITS(enumint, bits) ((enumint) &= ~(uint32_t)(bits))
00113 #define WOLFSENTRY_MASKIN_BITS(enumint, bits) ((enumint) & (bits))
00115 #define WOLFSENTRY_MASKOUT_BITS(enumint, bits) ((enumint) & ~(uint32_t)(bits))
00117 #define WOLFSENTRY_CLEAR_ALL_BITS(enumint) ((enumint) = 0)
00120 #ifndef BITS_PER_BYTE
00121 #define BITS_PER_BYTE 8
00122 #endif
00123
00124 #define WOLFSENTRY_BITS_TO_BYTES(x) (((x) + 7U) >> 3U)
00127 /* helpers for stringifying the expanded value of a macro argument rather than its literal text: */
00129 #define _qq(x) #x
00130 #define _q(x) _qq(x)
00133 #ifndef WOLFSENTRY_THREADSAFE
00134
00135 #ifdef WOLFSENTRY_HAVE_GNU_ATOMICS
00136
00137 #define WOLFSENTRY_ATOMIC_INCREMENT(i, x) __atomic_add_fetch(&(i),x,__ATOMIC_SEQ_CST)
00139 #define WOLFSENTRY_ATOMIC_DECREMENT(i, x) __atomic_sub_fetch(&(i),x,__ATOMIC_SEQ_CST)
00141 #define WOLFSENTRY_ATOMIC_POSTINCREMENT(i, x) __atomic_fetch_add(&(i),x,__ATOMIC_SEQ_CST)
00143 #define WOLFSENTRY_ATOMIC_POSTDECREMENT(i, x) __atomic_fetch_sub(&(i),x,__ATOMIC_SEQ_CST)
00145 #define WOLFSENTRY_ATOMIC_STORE(i, x) __atomic_store_n(&(i), x, __ATOMIC_RELEASE)
00147 #define WOLFSENTRY_ATOMIC_LOAD(i) __atomic_load_n(&(i), __ATOMIC_CONSUME)
00149 #define WOLFSENTRY_ATOMIC_CMPXCHG(ptr, expected, desired, weak_p, success_memorder, failure_memorder)
__atomic_compare_exchange_n(ptr, expected, desired, weak_p, success_memorder, failure_memorder)
00152 #else
00153
00154 #if !defined(WOLFSENTRY_ATOMIC_INCREMENT) || !defined(WOLFSENTRY_ATOMIC_DECREMENT) || \
00155     !defined(WOLFSENTRY_ATOMIC_POSTINCREMENT) || !defined(WOLFSENTRY_ATOMIC_POSTDECREMENT) || \
00156     !defined(WOLFSENTRY_ATOMIC_STORE) || !defined(WOLFSENTRY_ATOMIC_LOAD) || \
00157     !defined(WOLFSENTRY_ATOMIC_CMPXCHG)
00158 #error Missing required atomic implementation(s)
00159 #endif
00160
00161 #endif /* WOLFSENTRY_HAVE_GNU_ATOMICS */
00162
00163 #define WOLFSENTRY_ATOMIC_INCREMENT_BY_ONE(i) WOLFSENTRY_ATOMIC_INCREMENT(i, 1)
00165 #define WOLFSENTRY_ATOMIC_DECREMENT_BY_ONE(i) WOLFSENTRY_ATOMIC_DECREMENT(i, 1)
00168 /* caution, _TEST_AND_SET() alters arg2 (and returns false) on failure. */
00169 #define WOLFSENTRY_ATOMIC_TEST_AND_SET(i, expected, intended) \
00170     WOLFSENTRY_ATOMIC_CMPXCHG( \
00171         &(i), \
00172         &(expected), \
00173         intended, \
00174         0 /* weak */, \
00175         __ATOMIC_SEQ_CST /* success_memmodel */, \
00176         __ATOMIC_SEQ_CST /* failure_memmodel */); \
00179 #define WOLFSENTRY_ATOMIC_UPDATE_FLAGS(i, set_i, clear_i, pre_i, post_i) \
00180 do { \
00181     *(pre_i) = (i); \
00182     for (;;) { \
00183         *(post_i) = (*(pre_i) | (set_i)) & ~(clear_i); \
00184         if (*(post_i) == *(pre_i)) \
00185             break; \
00186         if (WOLFSENTRY_ATOMIC_CMPXCHG( \
00187             &(i), \
00188             (pre_i), \
00189             *(post_i), \
00190             0 /* weak */, \
00191             __ATOMIC_SEQ_CST /* success_memmodel */, \
00192             __ATOMIC_SEQ_CST /* failure_memmodel */)) \

```

```

00193         break;
00194     }
00195 } while (0)
00198 #define WOLFSENTRY_ATOMIC_RESET(i, pre_i)
00199 do {
00200     *(pre_i) = (i);
00201     for (;;) {
00202         if (*(pre_i) == 0)
00203             break;
00204         if (WOLFSENTRY_ATOMIC_CMPXCHG(
00205             &(i),
00206             (pre_i),
00207             0,
00208             0 /* weak */,
00209             __ATOMIC_SEQ_CST /* success_memmodel */,
00210             __ATOMIC_SEQ_CST /* failure_memmodel */))
00211             break;
00212     }
00213 } while (0)
00216 #define WOLFSENTRY_ATOMIC_INCREMENT_UNSIGNED_SAFELY(i, x, out)
00217 do {
00218     __typeof__(i) _pre_i = (i);
00219     __typeof__(i) _post_i = _pre_i;
00220     for (;;) {
00221         if (MAX_UINT_OF(i) - _pre_i < (x)) {
00222             _post_i = 0;
00223             break;
00224         }
00225         _post_i = (__typeof__(i))(_pre_i + (x));
00226         if (_post_i == _pre_i)
00227             break;
00228         if (WOLFSENTRY_ATOMIC_CMPXCHG(
00229             &(i),
00230             &_pre_i,
00231             _post_i,
00232             0 /* weak */,
00233             __ATOMIC_SEQ_CST /* success_memmodel */,
00234             __ATOMIC_SEQ_CST /* failure_memmodel */))
00235             break;
00236     }
00237     (out) = _post_i;
00238 } while(0)
00241 #define WOLFSENTRY_ATOMIC_INCREMENT_UNSIGNED_SAFELY_BY_ONE(i, out)
00242     WOLFSENTRY_ATOMIC_INCREMENT_UNSIGNED_SAFELY(i, 1U, out)
00245 #define WOLFSENTRY_ATOMIC_DECREMENT_UNSIGNED_SAFELY(i, x, out)
00246 do {
00247     __typeof__(i) _pre_i = (i);
00248     __typeof__(i) _post_i = _pre_i;
00249     for (;;) {
00250         if (_pre_i < (x)) {
00251             _post_i = MAX_UINT_OF(i);
00252             break;
00253         }
00254         _post_i = (__typeof__(i))(_pre_i - (x));
00255         if (_post_i == _pre_i)
00256             break;
00257         if (WOLFSENTRY_ATOMIC_CMPXCHG (
00258             &(i),
00259             &_pre_i,
00260             _post_i,
00261             0 /* weak */,
00262             __ATOMIC_SEQ_CST /* success_memmodel */,
00263             __ATOMIC_SEQ_CST /* failure_memmodel */))
00264             break;
00265     }
00266     (out) = _post_i;
00267 } while(0)
00270 #define WOLFSENTRY_ATOMIC_DECREMENT_UNSIGNED_SAFELY_BY_ONE(i, out)
00271     WOLFSENTRY_ATOMIC_DECREMENT_UNSIGNED_SAFELY(i, 1U, out)
00274 #else /* !WOLFSENTRY_THREADSAFE */
00275
00276 #define WOLFSENTRY_ATOMIC_INCREMENT(i, x) ((i) += (x))
00277 #define WOLFSENTRY_ATOMIC_INCREMENT_BY_ONE(i) (++(i))
00278 #define WOLFSENTRY_ATOMIC_DECREMENT(i, x) ((i) -= (x))
00279 #define WOLFSENTRY_ATOMIC_DECREMENT_BY_ONE(i) (--(i))
00280 #define WOLFSENTRY_ATOMIC_STORE(i, x) ((i)=(x))
00281 #define WOLFSENTRY_ATOMIC_LOAD(i) (i)
00282
00283 #define WOLFSENTRY_ATOMIC_UPDATE_FLAGS(i, set_i, clear_i, pre_i, post_i)
00284 do {
00285     *(pre_i) = (i);
00286     *(post_i) = (*(pre_i) | (set_i)) & ~(clear_i);
00287     if (*(post_i) != *(pre_i))
00288         (i) = *(post_i);
00289 } while (0)
00290
00291 #define WOLFSENTRY_ATOMIC_RESET(i, pre_i) do { *(pre_i) = (i); (i) = 0; } while (0)

```

```

00292
00293 #define WOLFSENTRY_ATOMIC_INCREMENT_UNSIGNED_SAFELY(i, x, out)      \
00294     do {                                                            \
00295         if ((x) > MAX_UINT_OF(i)) || ((MAX_UINT_OF(i) - (i) < (x))) \
00296             (out) = 0U;                                             \
00297         else                                                         \
00298             (out) = (i) = (__typeof__(i))((i) + (x));              \
00299     } while (0)
00300
00301 #define WOLFSENTRY_ATOMIC_INCREMENT_UNSIGNED_SAFELY_BY_ONE(i, out)  \
00302     WOLFSENTRY_ATOMIC_INCREMENT_UNSIGNED_SAFELY(i, 1U, out)
00303
00304 #define WOLFSENTRY_ATOMIC_DECREMENT_UNSIGNED_SAFELY(i, x, out)     \
00305     do {                                                            \
00306         if ((x) > MAX_UINT_OF(i)) || ((i) < (x))                  \
00307             (out) = MAX_UINT_OF(i);                                \
00308         else                                                         \
00309             (out) = (i) = (__typeof__(i))((i) - (x));              \
00310     } while (0)
00311
00312 #define WOLFSENTRY_ATOMIC_DECREMENT_UNSIGNED_SAFELY_BY_ONE(i, out) \
00313     WOLFSENTRY_ATOMIC_DECREMENT_UNSIGNED_SAFELY(i, 1U, out)
00314
00315 #endif /* WOLFSENTRY_THREADSAFE */
00316
00317 #endif /* WOLFSENTRY_UTIL_H */

```

## 10.18 wolfentry/wolfssl\_test.h File Reference

Macros and helper functions for wolfSSL `--enable-wolfentry`.

```

#include <wolfentry/wolfentry_util.h>
#include <wolfentry/wolfentry_json.h>

```

### Data Structures

- struct [wolfentry\\_data](#)

### Macros

- #define **WOLFSENTRY\_CONTEXT\_ARGS\_OUT\_EX**(x) (x)
- #define **WOLFSENTRY\_CONTEXT\_ARGS\_OUT\_EX4**(x, y) (x)
- #define **tcp\_connect**(sockfd, ip, port, udp, sctp, ssl) tcp\_connect\_with\_wolfSentry(sockfd, ip, port, udp, sctp, ssl, wolfentry)

### 10.18.1 Detailed Description

Macros and helper functions for wolfSSL `--enable-wolfentry`.

This file is included by `wolfssl/test.h` when defined(`WOLFSSL_WOLFSENTRY_HOOKS`).

## 10.19 wolfssl\_test.h

[Go to the documentation of this file.](#)

```

00001 /*
00002  * wolfssl_test.h
00003  *
00004  * Copyright (C) 2021-2023 wolfSSL Inc.
00005  *
00006  * This file is part of wolfSentry.
00007  *
00008  * wolfSentry is free software; you can redistribute it and/or modify
00009  * it under the terms of the GNU General Public License as published by
00010  * the Free Software Foundation; either version 2 of the License, or
00011  * (at your option) any later version.
00012  *
00013  * wolfSentry is distributed in the hope that it will be useful,
00014  * but WITHOUT ANY WARRANTY; without even the implied warranty of
00015  * MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
00016  * GNU General Public License for more details.
00017  *
00018  * You should have received a copy of the GNU General Public License
00019  * along with this program; if not, write to the Free Software
00020  * Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1335, USA
00021  */
00022
00029 #ifndef WOLFSENTRY_WOLFSSL_TEST_H
00030 #define WOLFSENTRY_WOLFSSL_TEST_H
00031
00032 #include <wolfentry/wolfentry_util.h>
00033
00034 #if !defined(NO_FILESYSTEM) && !defined(WOLFSENTRY_NO_JSON)
00035 #include <wolfentry/wolfentry_json.h>
00036 #endif
00037
00038 #if defined(WOLFSENTRY_VERSION_GE)
00039 #if WOLFSENTRY_VERSION_GE(0, 8, 0)
00040 #define HAVE_WOLFSENTRY_API_0v8
00041 #endif
00042 #endif
00043
00044 #ifndef HAVE_WOLFSENTRY_API_0v8
00045 #define WOLFSENTRY_CONTEXT_ARGS_OUT_EX(x) (x)
00046 #define WOLFSENTRY_CONTEXT_ARGS_OUT_EX4(x, y) (x)
00047 #endif
00048
00049 struct wolfentry_data {
00050     WOLFSENTRY_SOCKADDR(128) remote;
00051     WOLFSENTRY_SOCKADDR(128) local;
00052     wolfentry_route_flags_t flags;
00053     void *heap;
00054     int alloctype;
00055 };
00056
00057 static void free_wolfentry_data(struct wolfentry_data *data) {
00058     XFREE(data, data->heap, data->alloctype);
00059 }
00060
00061 static struct wolfentry_context *wolfentry = NULL;
00062
00063 static int wolfentry_data_index = -1;
00064
00065 static WC_INLINE int wolfentry_store_endpoints(
00066     WOLFSSL *ssl,
00067     SOCKADDR_IN_T *remote,
00068     SOCKADDR_IN_T *local,
00069     int proto,
00070     wolfentry_route_flags_t flags,
00071     struct wolfentry_data **wolfentry_data_out)
00072 {
00073     struct wolfentry_data *wolfentry_data = (struct wolfentry_data *)XMALLOC(
00074         sizeof *wolfentry_data, NULL, DYNAMIC_TYPE_SOCKADDR);
00075     if (wolfentry_data == NULL)
00076         return WOLFSSL_FAILURE;
00077     wolfentry_data->heap = NULL;
00078     wolfentry_data->alloctype = DYNAMIC_TYPE_SOCKADDR;
00079
00080 #ifdef TEST_IPV6
00081     if ((sizeof wolfentry_data->remote.addr < sizeof remote->sin6_addr) ||
00082         (sizeof wolfentry_data->local.addr < sizeof local->sin6_addr))
00083         return WOLFSSL_FAILURE;
00084     wolfentry_data->remote.sa_family = wolfentry_data->local.sa_family = remote->sin6_family;
00085     wolfentry_data->remote.sa_port = ntohs(remote->sin6_port);
00086     wolfentry_data->local.sa_port = ntohs(local->sin6_port);
00087     if (WOLFSENTRY_MASKIN_BITS(flags, WOLFSENTRY_ROUTE_FLAG_SA_REMOTE_ADDR_WILDCARD)) {

```

```

00089         wolfentry_data->remote.addr_len = 0;
00090         XMEMSET(wolfentry_data->remote.addr, 0, sizeof remote->sin6_addr);
00091     } else {
00092         wolfentry_data->remote.addr_len = sizeof remote->sin6_addr * BITS_PER_BYTE;
00093         XMEMCPY(wolfentry_data->remote.addr, &remote->sin6_addr, sizeof remote->sin6_addr);
00094     }
00095     if (WOLFSENTRY_MASKIN_BITS(flags, WOLFSENTRY_ROUTE_FLAG_SA_LOCAL_ADDR_WILDCARD)) {
00096         wolfentry_data->local.addr_len = 0;
00097         XMEMSET(wolfentry_data->local.addr, 0, sizeof local->sin6_addr);
00098     } else {
00099         wolfentry_data->local.addr_len = sizeof local->sin6_addr * BITS_PER_BYTE;
00100         XMEMCPY(wolfentry_data->local.addr, &local->sin6_addr, sizeof local->sin6_addr);
00101     }
00102 #else
00103     if ((sizeof wolfentry_data->remote.addr < sizeof remote->sin_addr) ||
00104         (sizeof wolfentry_data->local.addr < sizeof local->sin_addr))
00105         return WOLFSSL_FAILURE;
00106     wolfentry_data->remote.sa_family = wolfentry_data->local.sa_family = remote->sin_family;
00107     wolfentry_data->remote.sa_port = ntohs(remote->sin_port);
00108     wolfentry_data->local.sa_port = ntohs(local->sin_port);
00109     if (WOLFSENTRY_MASKIN_BITS(flags, WOLFSENTRY_ROUTE_FLAG_SA_REMOTE_ADDR_WILDCARD)) {
00110         wolfentry_data->remote.addr_len = 0;
00111         XMEMSET(wolfentry_data->remote.addr, 0, sizeof remote->sin_addr);
00112     } else {
00113         wolfentry_data->remote.addr_len = sizeof remote->sin_addr * BITS_PER_BYTE;
00114         XMEMCPY(wolfentry_data->remote.addr, &remote->sin_addr, sizeof remote->sin_addr);
00115     }
00116     if (WOLFSENTRY_MASKIN_BITS(flags, WOLFSENTRY_ROUTE_FLAG_SA_LOCAL_ADDR_WILDCARD)) {
00117         wolfentry_data->local.addr_len = 0;
00118         XMEMSET(wolfentry_data->local.addr, 0, sizeof local->sin_addr);
00119     } else {
00120         wolfentry_data->local.addr_len = sizeof local->sin_addr * BITS_PER_BYTE;
00121         XMEMCPY(wolfentry_data->local.addr, &local->sin_addr, sizeof local->sin_addr);
00122     }
00123 #endif
00124     wolfentry_data->remote.sa_proto = wolfentry_data->local.sa_proto = proto;
00125     wolfentry_data->remote.interface = wolfentry_data->local.interface = 0;
00126     wolfentry_data->flags = flags;
00127
00128     if (wolfSSL_set_ex_data_with_cleanup(
00129         ssl, wolfentry_data_index, wolfentry_data,
00130         (wolfSSL_ex_data_cleanup_routine_t)free_wolfentry_data) !=
00131         WOLFSSL_SUCCESS) {
00132         free_wolfentry_data(wolfentry_data);
00133         return WOLFSSL_FAILURE;
00134     }
00135
00136     if (wolfentry_data_out != NULL)
00137         *wolfentry_data_out = wolfentry_data;
00138
00139     return WOLFSSL_SUCCESS;
00140 }
00141
00142 static int wolfSentry_NetworkFilterCallback(
00143     WOLFSSL *ssl,
00144     struct wolfentry_context *_wolfentry,
00145     wolfSSL_netfilter_decision_t *decision)
00146 {
00147     struct wolfentry_data *data;
00148     char inet_ntop_buf[INET6_ADDRSTRLEN], inet_ntop_buf2[INET6_ADDRSTRLEN];
00149     wolfentry_errcode_t ret;
00150     wolfentry_action_res_t action_results;
00151
00152 #if defined(WOLFSENTRY_THREADSAFE) && defined(HAVE_WOLFSENTRY_API_0v8)
00153     WOLFSENTRY_THREAD_HEADER(WOLFSENTRY_THREAD_FLAG_NONE);
00154     if (WOLFSENTRY_THREAD_GET_ERROR < 0) {
00155         fprintf(stderr, "wolfentry thread init error: "
00156             WOLFSENTRY_ERROR_FMT "\n",
00157             WOLFSENTRY_ERROR_FMT_ARGS(WOLFSENTRY_THREAD_GET_ERROR));
00158         return WOLFSSL_FAILURE;
00159     }
00160 #endif /* WOLFSENTRY_THREADSAFE && HAVE_WOLFSENTRY_API_0v8 */
00161
00162     if ((data = wolfSSL_get_ex_data(ssl, wolfentry_data_index)) == NULL)
00163         return WOLFSSL_FAILURE;
00164
00165     ret = wolfentry_route_event_dispatch(
00166         WOLFSENTRY_CONTEXT_ARGS_OUT_EX(_wolfentry),
00167         (const struct wolfentry_sockaddr *)&data->remote,
00168         (const struct wolfentry_sockaddr *)&data->local,
00169         data->flags,
00170         NULL /* event_label */,
00171         0 /* event_label_len */,
00172         NULL /* caller_context */,
00173         NULL /* id */,
00174         NULL /* inexact_matches */,
00175         &action_results);

```

```

00176
00177     if (ret >= 0) {
00178         if (WOLFSENTRY_MASKIN_BITS(action_results, WOLFSENTRY_ACTION_RES_REJECT))
00179             *decision = WOLFSSL_NETFILTER_REJECT;
00180         else if (WOLFSENTRY_MASKIN_BITS(action_results, WOLFSENTRY_ACTION_RES_ACCEPT))
00181             *decision = WOLFSSL_NETFILTER_ACCEPT;
00182         else
00183             *decision = WOLFSSL_NETFILTER_PASS;
00184     } else {
00185         fprintf(stderr, "wolfSentry_route_event_dispatch error "
00186             WOLFSENTRY_ERROR_FMT "\n", WOLFSENTRY_ERROR_FMT_ARGS(ret));
00187         *decision = WOLFSSL_NETFILTER_PASS;
00188     }
00189
00190     printf("wolfSentry got network filter callback: family=%d proto=%d rport=%d"
00191         " lport=%d raddr=%s laddr=%s interface=%d; decision=%d (%s)\n",
00192         data->remote.sa_family,
00193         data->remote.sa_proto,
00194         data->remote.sa_port,
00195         data->local.sa_port,
00196         inet_ntop(data->remote.sa_family, data->remote.addr, inet_ntop_buf,
00197             sizeof inet_ntop_buf),
00198         inet_ntop(data->local.sa_family, data->local.addr, inet_ntop_buf2,
00199             sizeof inet_ntop_buf2),
00200         data->remote.interface,
00201         *decision,
00202         *decision == WOLFSSL_NETFILTER_REJECT ? "REJECT" :
00203         *decision == WOLFSSL_NETFILTER_ACCEPT ? "ACCEPT" :
00204         *decision == WOLFSSL_NETFILTER_PASS ? "PASS" :
00205         "???");
00206
00207     #if defined(WOLFSENTRY_THREADSAFE) && defined(HAVE_WOLFSENTRY_API_0v8)
00208     ret = WOLFSENTRY_THREAD_TAILER(WOLFSENTRY_THREAD_FLAG_NONE);
00209     if (ret < 0) {
00210         fprintf(stderr, "wolfSentry thread exit error: "
00211             WOLFSENTRY_ERROR_FMT "\n", WOLFSENTRY_ERROR_FMT_ARGS(ret));
00212     }
00213     #endif
00214
00215     return WOLFSSL_SUCCESS;
00216 }
00217
00218 static int wolfSentry_setup(
00219     struct wolfSentry_context **_wolfSentry,
00220     const char *_wolfSentry_config_path,
00221     wolfSentry_route_flags_t route_flags)
00222 {
00223     wolfSentry_errcode_t ret;
00224
00225     #ifndef HAVE_WOLFSENTRY_API_0v8
00226     #ifndef WOLFSENTRY_THREADSAFE
00227         WOLFSENTRY_THREAD_HEADER(WOLFSENTRY_THREAD_FLAG_NONE);
00228         if (WOLFSENTRY_THREAD_GET_ERROR < 0) {
00229             fprintf(stderr, "wolfSentry thread init error: "
00230                 WOLFSENTRY_ERROR_FMT "\n",
00231                 WOLFSENTRY_ERROR_FMT_ARGS(WOLFSENTRY_THREAD_GET_ERROR));
00232             err_sys("unable to initialize wolfSentry thread context");
00233         }
00234     #endif
00235     ret = wolfSentry_init(wolfSentry_build_settings,
00236         WOLFSENTRY_CONTEXT_ARGS_OUT_EX(NULL /* hpi */),
00237         NULL /* default config */,
00238         _wolfSentry);
00239     #else
00240     ret = wolfSentry_init(NULL /* hpi */, NULL /* default config */,
00241         _wolfSentry);
00242     #endif
00243     if (ret < 0) {
00244         fprintf(stderr, "wolfSentry_init() returned " WOLFSENTRY_ERROR_FMT "\n",
00245             WOLFSENTRY_ERROR_FMT_ARGS(ret));
00246         err_sys("unable to initialize wolfSentry");
00247     }
00248
00249     if (wolfSentry_data_index < 0)
00250         wolfSentry_data_index = wolfSSL_get_ex_new_index(0, NULL, NULL, NULL,
00251             NULL);
00252
00253     #if !defined(NO_FILESYSTEM) && !defined(WOLFSENTRY_NO_JSON)
00254     if (_wolfSentry_config_path != NULL) {
00255         unsigned char buf[512];
00256         char err_buf[512];
00257         struct wolfSentry_json_process_state *jps;
00258
00259         FILE *f = fopen(_wolfSentry_config_path, "r");
00260
00261         if (f == NULL) {
00262             fprintf(stderr, "fopen(%s): %s\n", _wolfSentry_config_path, strerror(errno));

```



```

00263         err_sys("unable to open wolfSentry config file");
00264     }
00265
00266     if ((ret = wolfSentry_config_json_init(
00267         WOLFSENTRY_CONTEXT_ARGS_OUT_EX(*_wolfSentry),
00268         WOLFSENTRY_CONFIG_LOAD_FLAG_NONE,
00269         &jps)) < 0) {
00270         fprintf(stderr, "wolfSentry_config_json_init() returned "
00271             WOLFSENTRY_ERROR_FMT "\n",
00272             WOLFSENTRY_ERROR_FMT_ARGS(ret));
00273         err_sys("error while initializing wolfSentry config parser");
00274     }
00275
00276     for (;;) {
00277         size_t n = fread(buf, 1, sizeof buf, f);
00278         if ((n < sizeof buf) && ferror(f)) {
00279             fprintf(stderr, "fread(%s): %s\n", _wolfSentry_config_path, strerror(errno));
00280             err_sys("error while reading wolfSentry config file");
00281         }
00282
00283         ret = wolfSentry_config_json_feed(jps, buf, n, err_buf, sizeof err_buf);
00284         if (ret < 0) {
00285             fprintf(stderr, "%.*s\n", (int)sizeof err_buf, err_buf);
00286             err_sys("error while loading wolfSentry config file");
00287         }
00288         if ((n < sizeof buf) && feof(f))
00289             break;
00290     }
00291     fclose(f);
00292
00293     if ((ret = wolfSentry_config_json_fini(&jps, err_buf, sizeof err_buf)) < 0) {
00294         fprintf(stderr, "%.*s\n", (int)sizeof err_buf, err_buf);
00295         err_sys("error while loading wolfSentry config file");
00296     }
00297 } else
00298 #endif /* !NO_FILESYSTEM && !WOLFSENTRY_NO_JSON */
00299 {
00300     struct wolfSentry_route_table *table;
00301
00302 #ifdef WOLFSENTRY_THREADSAFE
00303     ret = WOLFSENTRY_SHARED_EX(*_wolfSentry);
00304     if (ret < 0) {
00305         fprintf(stderr, "wolfSentry shared lock op failed: "
00306             WOLFSENTRY_ERROR_FMT ".\n",
00307             WOLFSENTRY_ERROR_FMT_ARGS(ret));
00308         return ret;
00309     }
00310 #endif
00311
00312     if ((ret = wolfSentry_route_get_main_table(
00313         WOLFSENTRY_CONTEXT_ARGS_OUT_EX(*_wolfSentry),
00314         &table)) < 0)
00315     {
00316         fprintf(stderr, "wolfSentry_route_get_main_table() returned "
00317             WOLFSENTRY_ERROR_FMT "\n",
00318             WOLFSENTRY_ERROR_FMT_ARGS(ret));
00319 #ifdef WOLFSENTRY_THREADSAFE
00320         WOLFSENTRY_WARN_ON_FAILURE(
00321             wolfSentry_context_unlock(
00322                 WOLFSENTRY_CONTEXT_ARGS_OUT_EX(*_wolfSentry)));
00323 #endif
00324         return ret;
00325     }
00326
00327     if (WOLFSENTRY_MASKIN_BITS(route_flags, WOLFSENTRY_ROUTE_FLAG_DIRECTION_OUT)) {
00328         WOLFSENTRY_SOCKADDR(128) remote, local;
00329         wolfSentry_ent_id_t id;
00330         wolfSentry_action_res_t action_results;
00331
00332         if ((ret = wolfSentry_route_table_default_policy_set(
00333             WOLFSENTRY_CONTEXT_ARGS_OUT_EX(*_wolfSentry),
00334             table,
00335             WOLFSENTRY_ACTION_RES_ACCEPT))
00336             < 0) {
00337             fprintf(stderr,
00338                 "wolfSentry_route_table_default_policy_set() returned "
00339                 WOLFSENTRY_ERROR_FMT "\n",
00340                 WOLFSENTRY_ERROR_FMT_ARGS(ret));
00341 #ifdef WOLFSENTRY_THREADSAFE
00342             WOLFSENTRY_WARN_ON_FAILURE(
00343                 wolfSentry_context_unlock(
00344                     WOLFSENTRY_CONTEXT_ARGS_OUT_EX(*_wolfSentry)));
00345 #endif
00346             return ret;
00347         }
00348     }
00349 }

```

```

00350         XMEMSET(&remote, 0, sizeof remote);
00351         XMEMSET(&local, 0, sizeof local);
00352 #ifdef TEST_IPV6
00353         remote.sa_family = local.sa_family = AF_INET6;
00354         remote.addr_len = 128;
00355         XMEMCPY(remote.addr, "\000\000\000\000\000\000\000\000\000\000\000\000\000\000\000\001",
16);
00356 #else
00357         remote.sa_family = local.sa_family = AF_INET;
00358         remote.addr_len = 32;
00359         XMEMCPY(remote.addr, "\177\000\000\001", 4);
00360 #endif
00361
00362         if ((ret = wolfsentry_route_insert
00363             (WOLFSENTRY_CONTEXT_ARGS_OUT_EX(*_wolfsentry),
00364              NULL /* caller_context */,
00365              (const struct wolfsentry_sockaddr *)&remote,
00366              (const struct wolfsentry_sockaddr *)&local,
00367              route_flags
00368              WOLFSENTRY_ROUTE_FLAG_GREENLISTED
00369              WOLFSENTRY_ROUTE_FLAG_PARENT_EVENT_WILDCARD
00370              WOLFSENTRY_ROUTE_FLAG_REMOTE_INTERFACE_WILDCARD
00371              WOLFSENTRY_ROUTE_FLAG_LOCAL_INTERFACE_WILDCARD
00372              WOLFSENTRY_ROUTE_FLAG_SA_LOCAL_ADDR_WILDCARD
00373              WOLFSENTRY_ROUTE_FLAG_SA_PROTO_WILDCARD
00374              WOLFSENTRY_ROUTE_FLAG_SA_REMOTE_PORT_WILDCARD
00375              WOLFSENTRY_ROUTE_FLAG_SA_LOCAL_PORT_WILDCARD,
00376              0 /* event_label_len */, 0 /* event_label */, &id,
00377              &action_results)) < 0) {
00378             fprintf(stderr, "wolfsentry_route_insert() returned "
00379                 WOLFSENTRY_ERROR_FMT "\n",
00380                 WOLFSENTRY_ERROR_FMT_ARGS(ret));
00381 #ifdef WOLFSENTRY_THREADSAFE
00382             WOLFSENTRY_WARN_ON_FAILURE(
00383                 wolfsentry_context_unlock(
00384                     WOLFSENTRY_CONTEXT_ARGS_OUT_EX(*_wolfsentry)));
00385 #endif
00386             return ret;
00387         }
00388     } else if (WOLFSENTRY_MASKIN_BITS(route_flags, WOLFSENTRY_ROUTE_FLAG_DIRECTION_IN)) {
00389         WOLFSENTRY_SOCKADDR(128) remote, local;
00390         wolfsentry_ent_id_t id;
00391         wolfsentry_action_res_t action_results;
00392
00393         if ((ret = wolfsentry_route_table_default_policy_set(
00394             WOLFSENTRY_CONTEXT_ARGS_OUT_EX(*_wolfsentry), table,
00395             WOLFSENTRY_ACTION_RES_REJECT|WOLFSENTRY_ACTION_RES_STOP))
00396             < 0) {
00397             fprintf(stderr,
00398                 "wolfsentry_route_table_default_policy_set() returned "
00399                 WOLFSENTRY_ERROR_FMT "\n",
00400                 WOLFSENTRY_ERROR_FMT_ARGS(ret));
00401 #ifdef WOLFSENTRY_THREADSAFE
00402             WOLFSENTRY_WARN_ON_FAILURE(
00403                 wolfsentry_context_unlock(
00404                     WOLFSENTRY_CONTEXT_ARGS_OUT_EX(*_wolfsentry)));
00405 #endif
00406             return ret;
00407         }
00408     }
00409     XMEMSET(&remote, 0, sizeof remote);
00410     XMEMSET(&local, 0, sizeof local);
00411 #ifdef TEST_IPV6
00412     remote.sa_family = local.sa_family = AF_INET6;
00413     remote.addr_len = 128;
00414     XMEMCPY(remote.addr, "\000\000\000\000\000\000\000\000\000\000\000\000\000\000\000\001",
16);
00415 #else
00416     remote.sa_family = local.sa_family = AF_INET;
00417     remote.addr_len = 32;
00418     XMEMCPY(remote.addr, "\177\000\000\001", 4);
00419 #endif
00420
00421     if ((ret = wolfsentry_route_insert
00422         (WOLFSENTRY_CONTEXT_ARGS_OUT_EX(*_wolfsentry),
00423          NULL /* caller_context */,
00424          (const struct wolfsentry_sockaddr *)&remote,
00425          (const struct wolfsentry_sockaddr *)&local,
00426          route_flags
00427          WOLFSENTRY_ROUTE_FLAG_GREENLISTED
00428          WOLFSENTRY_ROUTE_FLAG_PARENT_EVENT_WILDCARD
00429          WOLFSENTRY_ROUTE_FLAG_REMOTE_INTERFACE_WILDCARD
00430          WOLFSENTRY_ROUTE_FLAG_LOCAL_INTERFACE_WILDCARD
00431          WOLFSENTRY_ROUTE_FLAG_SA_LOCAL_ADDR_WILDCARD
00432          WOLFSENTRY_ROUTE_FLAG_SA_PROTO_WILDCARD
00433          WOLFSENTRY_ROUTE_FLAG_SA_REMOTE_PORT_WILDCARD
00434          WOLFSENTRY_ROUTE_FLAG_SA_LOCAL_PORT_WILDCARD,

```

```

00435         0 /* event_label_len */, 0 /* event_label */, &id,
00436         &action_results)) < 0) {
00437             fprintf(stderr, "wolfentry_route_insert() returned "
00438                 WOLFSENTRY_ERROR_FMT "\n",
00439                 WOLFSENTRY_ERROR_FMT_ARGS(ret));
00440 #ifdef WOLFSENTRY_THREADSAFE
00441             WOLFSENTRY_WARN_ON_FAILURE(
00442                 wolfentry_context_unlock(
00443                     WOLFSENTRY_CONTEXT_ARGS_OUT_EX(*_wolfentry)));
00444 #endif
00445             return ret;
00446         }
00447     }
00448 #ifdef WOLFSENTRY_THREADSAFE
00449     WOLFSENTRY_WARN_ON_FAILURE(
00450         wolfentry_context_unlock(
00451             WOLFSENTRY_CONTEXT_ARGS_OUT_EX(*_wolfentry)));
00452 #endif
00453 }
00454
00455 #if defined(WOLFSENTRY_THREADSAFE) && defined(HAVE_WOLFSENTRY_API_0v8)
00456     ret = WOLFSENTRY_THREAD_TAILER(WOLFSENTRY_THREAD_FLAG_NONE);
00457     if (ret < 0) {
00458         fprintf(stderr, "wolfentry thread exit error: "
00459             WOLFSENTRY_ERROR_FMT "\n", WOLFSENTRY_ERROR_FMT_ARGS(ret));
00460     }
00461 #endif
00462     return 0;
00463 }
00464
00465 static WC_INLINE int tcp_connect_with_wolfSentry(
00466     SOCKET_T* sockfd,
00467     const char* ip,
00468     word16 port,
00469     int udp,
00470     int sctp,
00471     WOLFSSL* ssl,
00472     struct wolfentry_context *_wolfentry)
00473 {
00474     SOCKADDR_IN_T remote_addr;
00475     struct wolfentry_data *_wolfentry_data;
00476     char inet_ntop_buf[INET6_ADDRSTRLEN], inet_ntop_buf2[INET6_ADDRSTRLEN];
00477     wolfentry_errcode_t ret;
00478     wolfentry_action_res_t action_results;
00479     wolfSSL_netfilter_decision_t decision;
00480
00481     #if defined(WOLFSENTRY_THREADSAFE) && defined(HAVE_WOLFSENTRY_API_0v8)
00482         WOLFSENTRY_THREAD_HEADER(WOLFSENTRY_THREAD_FLAG_NONE);
00483         if (WOLFSENTRY_THREAD_GET_ERROR < 0) {
00484             fprintf(stderr, "wolfentry thread init error: "
00485                 WOLFSENTRY_ERROR_FMT "\n",
00486                 WOLFSENTRY_ERROR_FMT_ARGS(WOLFSENTRY_THREAD_GET_ERROR));
00487             err_sys("unable to initialize wolfSentry thread context");
00488         }
00489     #endif
00490     build_addr(&remote_addr, ip, port, udp, sctp);
00491
00492     {
00493         SOCKADDR_IN_T local_addr;
00494         #ifdef TEST_IPV6
00495             local_addr.sin6_port = 0;
00496         #else
00497             local_addr.sin_port = 0;
00498         #endif
00499         ((struct sockaddr *)&local_addr)->sa_family = ((struct sockaddr *)&remote_addr)->sa_family;
00500
00501         if (wolfentry_store_endpoints(
00502             ssl, &remote_addr, &local_addr,
00503             udp ? IPPROTO_UDP : IPPROTO_TCP,
00504             WOLFSENTRY_ROUTE_FLAG_DIRECTION_OUT |
00505             WOLFSENTRY_ROUTE_FLAG_SA_LOCAL_ADDR_WILDCARD |
00506             WOLFSENTRY_ROUTE_FLAG_SA_LOCAL_PORT_WILDCARD, &wolfentry_data) != WOLFSSL_SUCCESS)
00507             return WOLFSSL_FAILURE;
00508     }
00509
00510     ret = wolfentry_route_event_dispatch(
00511         WOLFSENTRY_CONTEXT_ARGS_OUT_EX(_wolfentry),
00512         (const struct wolfentry_sockaddr *)&wolfentry_data->remote,
00513         (const struct wolfentry_sockaddr *)&wolfentry_data->local,
00514         wolfentry_data->flags,
00515         NULL /* event_label */,
00516         0 /* event_label_len */,
00517         NULL /* caller_context */,
00518         NULL /* id */,
00519         NULL /* inexact_matches */);

```

```

00522         &action_results);
00523
00524     if (ret < 0) {
00525         fprintf(stderr, "wolfsentry_route_event_dispatch error "
00526             WOLFSENTRY_ERROR_FMT "\n", WOLFSENTRY_ERROR_FMT_ARGS(ret));
00527         decision = WOLFSSL_NETFILTER_PASS;
00528     } else {
00529         if (WOLFSENTRY_MASKIN_BITS(action_results, WOLFSENTRY_ACTION_RES_REJECT))
00530             decision = WOLFSSL_NETFILTER_REJECT;
00531         else if (WOLFSENTRY_MASKIN_BITS(action_results, WOLFSENTRY_ACTION_RES_ACCEPT))
00532             decision = WOLFSSL_NETFILTER_ACCEPT;
00533         else
00534             decision = WOLFSSL_NETFILTER_PASS;
00535     }
00536
00537     printf("wolfSentry callin from tcp_connect_with_wolfSentry: family=%d proto=%d rport=%d"
00538         " lport=%d raddr=%s laddr=%s interface=%d; decision=%d (%s)\n",
00539         wolfsentry_data->remote.sa_family,
00540         wolfsentry_data->remote.sa_proto,
00541         wolfsentry_data->remote.sa_port,
00542         wolfsentry_data->local.sa_port,
00543         inet_ntop(wolfsentry_data->remote.sa_family, wolfsentry_data->remote.addr, inet_ntop_buf,
00544             sizeof inet_ntop_buf),
00545         inet_ntop(wolfsentry_data->local.sa_family, wolfsentry_data->local.addr, inet_ntop_buf2,
00546             sizeof inet_ntop_buf2),
00547         wolfsentry_data->remote.interface,
00548         decision,
00549         decision == WOLFSSL_NETFILTER_REJECT ? "REJECT" :
00550         decision == WOLFSSL_NETFILTER_ACCEPT ? "ACCEPT" :
00551         decision == WOLFSSL_NETFILTER_PASS ? "PASS" :
00552         "???");
00553
00554     if (decision == WOLFSSL_NETFILTER_REJECT)
00555         return SOCKET_FILTERED_E;
00556
00557     if (udp) {
00558         wolfSSL_dtls_set_peer(ssl, &remote_addr, sizeof(remote_addr));
00559     }
00560     tcp_socket(sockfd, udp, sctp);
00561
00562     if (!udp) {
00563         if (connect(*sockfd, (const struct sockaddr*)&remote_addr, sizeof(remote_addr)) != 0)
00564             err_sys_with_errno("tcp connect failed");
00565     }
00566
00567 #if defined(WOLFSENTRY_THREADSAFE) && defined(HAVE_WOLFSENTRY_API_0v8)
00568     ret = WOLFSENTRY_THREAD_TAILER(WOLFSENTRY_THREAD_FLAG_NONE);
00569     if (ret < 0) {
00570         fprintf(stderr, "wolfsentry thread exit error: "
00571             WOLFSENTRY_ERROR_FMT "\n", WOLFSENTRY_ERROR_FMT_ARGS(ret));
00572     }
00573 #endif
00574     return WOLFSSL_SUCCESS;
00575 }
00576
00577 #define tcp_connect(sockfd, ip, port, udp, sctp, ssl) \
00578     tcp_connect_with_wolfSentry(sockfd, ip, port, udp, sctp, ssl, wolfsentry)
00579
00580 #endif /* !WOLFSENTRY_WOLFSSL_TEST_H */

```

# Index

## Action Subsystem, [92](#)

- [wolfentry\\_action\\_callback\\_t](#), [94](#)
- [wolfentry\\_action\\_delete](#), [96](#)
- [wolfentry\\_action\\_drop\\_reference](#), [97](#)
- [WOLFSENTRY\\_ACTION\\_FLAG\\_DISABLED](#), [95](#)
- [WOLFSENTRY\\_ACTION\\_FLAG\\_NONE](#), [95](#)
- [wolfentry\\_action\\_flags\\_t](#), [95](#)
- [wolfentry\\_action\\_flush\\_all](#), [97](#)
- [wolfentry\\_action\\_get\\_flags](#), [98](#)
- [wolfentry\\_action\\_get\\_label](#), [98](#)
- [wolfentry\\_action\\_get\\_reference](#), [98](#)
- [wolfentry\\_action\\_insert](#), [99](#)
- [WOLFSENTRY\\_ACTION\\_RES\\_ACCEPT](#), [95](#)
- [WOLFSENTRY\\_ACTION\\_RES\\_BINDING](#), [95](#)
- [WOLFSENTRY\\_ACTION\\_RES\\_CLOSE\\_WAIT](#), [96](#)
- [WOLFSENTRY\\_ACTION\\_RES\\_CLOSED](#), [96](#)
- [WOLFSENTRY\\_ACTION\\_RES\\_COMMENDABLE](#), [95](#)
- [WOLFSENTRY\\_ACTION\\_RES\\_CONNECT](#), [95](#)
- [WOLFSENTRY\\_ACTION\\_RES\\_CONNECTING\\_OUT](#), [96](#)
- [WOLFSENTRY\\_ACTION\\_RES\\_DEALLOCATED](#), [95](#)
- [WOLFSENTRY\\_ACTION\\_RES\\_DEROGATORY](#), [95](#)
- [WOLFSENTRY\\_ACTION\\_RES\\_DISCONNECT](#), [95](#)
- [WOLFSENTRY\\_ACTION\\_RES\\_ERROR](#), [95](#)
- [WOLFSENTRY\\_ACTION\\_RES\\_FALLTHROUGH](#), [95](#)
- [WOLFSENTRY\\_ACTION\\_RES\\_INSERTED](#), [95](#)
- [WOLFSENTRY\\_ACTION\\_RES\\_LISTENING](#), [96](#)
- [WOLFSENTRY\\_ACTION\\_RES\\_NONE](#), [95](#)
- [WOLFSENTRY\\_ACTION\\_RES\\_PORT\\_RESET](#), [95](#)
- [WOLFSENTRY\\_ACTION\\_RES\\_RECEIVED](#), [95](#)
- [WOLFSENTRY\\_ACTION\\_RES\\_REJECT](#), [95](#)
- [WOLFSENTRY\\_ACTION\\_RES\\_SENDING](#), [95](#)
- [WOLFSENTRY\\_ACTION\\_RES\\_SOCKET\\_ERROR](#), [96](#)
- [WOLFSENTRY\\_ACTION\\_RES\\_STOP](#), [95](#)
- [WOLFSENTRY\\_ACTION\\_RES\\_STOPPED\\_LISTENING](#), [96](#)
- [wolfentry\\_action\\_res\\_t](#), [95](#)
- [WOLFSENTRY\\_ACTION\\_RES\\_UNREACHABLE](#), [96](#)
- [WOLFSENTRY\\_ACTION\\_RES\\_UPDATE](#), [95](#)
- [WOLFSENTRY\\_ACTION\\_RES\\_USER0](#), [96](#)
- [WOLFSENTRY\\_ACTION\\_RES\\_USER1](#), [96](#)

- [WOLFSENTRY\\_ACTION\\_RES\\_USER2](#), [96](#)
- [WOLFSENTRY\\_ACTION\\_RES\\_USER3](#), [96](#)
- [WOLFSENTRY\\_ACTION\\_RES\\_USER4](#), [96](#)
- [WOLFSENTRY\\_ACTION\\_RES\\_USER5](#), [96](#)
- [WOLFSENTRY\\_ACTION\\_RES\\_USER6](#), [96](#)
- [WOLFSENTRY\\_ACTION\\_TYPE\\_DECISION](#), [96](#)
- [WOLFSENTRY\\_ACTION\\_TYPE\\_DELETE](#), [96](#)
- [WOLFSENTRY\\_ACTION\\_TYPE\\_INSERT](#), [96](#)
- [WOLFSENTRY\\_ACTION\\_TYPE\\_MATCH](#), [96](#)
- [WOLFSENTRY\\_ACTION\\_TYPE\\_NONE](#), [96](#)
- [WOLFSENTRY\\_ACTION\\_TYPE\\_POST](#), [96](#)
- [wolfentry\\_action\\_type\\_t](#), [96](#)
- [WOLFSENTRY\\_ACTION\\_TYPE\\_UPDATE](#), [96](#)
- [wolfentry\\_action\\_update\\_flags](#), [99](#)

## Address Family Subsystem, [113](#)

- allocator
  - [wolfentry\\_host\\_platform\\_interface](#), [153](#)
- Allocator (Heap) Functions and Callbacks, [144](#)

- [wolfentry\\_kv\\_pair](#), [154](#)

## Building and Initializing wolfSentry for an application on FreeRTOS/IWIP, [7](#)

- caller\_build\_settings
  - [wolfentry\\_host\\_platform\\_interface](#), [153](#)
- config
  - [wolfentry\\_build\\_settings](#), [151](#)

## Configuring wolfSentry using a JSON document, [11](#)

## Core Types and Macros, [51](#)

## Diagnostics, Control Flow Helpers, and Compiler Attribute Helpers, [62](#)

- [WOLFSENTRY\\_DEBUG\\_CALL\\_TRACE](#), [66](#)
- [WOLFSENTRY\\_ERROR\\_UNLOCK\\_AND\\_RETURN](#), [66](#)
- [WOLFSENTRY\\_MUTEX\\_OR\\_RETURN](#), [66](#)
- [WOLFSENTRY\\_PROMOTABLE\\_EX](#), [67](#)
- [WOLFSENTRY\\_PROMOTABLE\\_OR\\_RETURN](#), [67](#)
- [WOLFSENTRY\\_SHARED\\_EX](#), [67](#)
- [WOLFSENTRY\\_SHARED\\_OR\\_RETURN](#), [67](#)
- [WOLFSENTRY\\_UNLOCK\\_AND\\_RETURN](#), [67](#)
- [WOLFSENTRY\\_UNLOCK\\_AND\\_UNRESERVE\\_FOR\\_RETURN](#), [68](#)
- [WOLFSENTRY\\_UNLOCK\\_AND\\_UNRESERVE\\_FOR\\_RETURN\\_EX](#), [68](#)
- [WOLFSENTRY\\_UNLOCK\\_FOR\\_RETURN](#), [68](#)
- [WOLFSENTRY\\_UNLOCK\\_FOR\\_RETURN\\_EX](#), [68](#)

## Event Subsystem, [100](#)

- wolfentry\_event\_action\_append, [103](#)
- wolfentry\_event\_action\_delete, [103](#)
- wolfentry\_event\_action\_insert\_after, [104](#)
- wolfentry\_event\_action\_list\_done, [104](#)
- wolfentry\_event\_action\_list\_next, [105](#)
- wolfentry\_event\_action\_list\_start, [105](#)
- wolfentry\_event\_action\_prepend, [106](#)
- wolfentry\_event\_delete, [106](#)
- wolfentry\_event\_drop\_reference, [107](#)
- WOLFENTRY\_EVENT\_FLAG\_IS\_PARENT\_EVENT, [102](#)
- WOLFENTRY\_EVENT\_FLAG\_IS\_SUBEVENT, [102](#)
- WOLFENTRY\_EVENT\_FLAG\_NONE, [102](#)
- wolfentry\_event\_flags\_t, [102](#)
- wolfentry\_event\_flush\_all, [107](#)
- wolfentry\_event\_get\_config, [108](#)
- wolfentry\_event\_get\_flags, [108](#)
- wolfentry\_event\_get\_label, [108](#)
- wolfentry\_event\_get\_reference, [109](#)
- wolfentry\_event\_insert, [109](#)
- wolfentry\_event\_set\_aux\_event, [110](#)
- wolfentry\_event\_update\_config, [110](#)
- wolfentry\_eventconfig\_check, [112](#)
- WOLFENTRY\_EVENTCONFIG\_FLAG\_COMMENDABLE, [102](#)
- WOLFENTRY\_EVENTCONFIG\_FLAG\_DEROGATORY, [102](#)
- WOLFENTRY\_EVENTCONFIG\_FLAG\_INHIBIT\_ACTIONS, [102](#)
- WOLFENTRY\_EVENTCONFIG\_FLAG\_NONE, [102](#)
- wolfentry\_eventconfig\_flags\_t, [102](#)
- wolfentry\_eventconfig\_init, [112](#)
- JSON\_CALLBACKS, [149](#)
- JSON\_CONFIG, [149](#)
- JSON\_DOM\_PARSER, [149](#)
- JSON\_INPUT\_POS, [150](#)
- JSON\_PARSER, [150](#)
- JSON\_VALUE, [150](#)
- lwIP Callback Activation Functions, [148](#)
- Object Subsystem, [121](#)
  - wolfentry\_get\_object\_id, [122](#)
  - wolfentry\_get\_object\_type, [122](#)
  - WOLFENTRY\_OBJECT\_TYPE\_ACTION, [122](#)
  - WOLFENTRY\_OBJECT\_TYPE\_ADDR\_FAMILY\_BYNAME, [122](#)
  - WOLFENTRY\_OBJECT\_TYPE\_ADDR\_FAMILY\_BYNUMBER, [122](#)
  - WOLFENTRY\_OBJECT\_TYPE\_EVENT, [122](#)
  - WOLFENTRY\_OBJECT\_TYPE\_KV, [122](#)
  - WOLFENTRY\_OBJECT\_TYPE\_ROUTE, [122](#)
  - wolfentry\_object\_type\_t, [121](#)
  - WOLFENTRY\_OBJECT\_TYPE\_TABLE, [122](#)
  - WOLFENTRY\_OBJECT\_TYPE\_UNINITED, [122](#)
  - wolfentry\_table\_n\_deletes, [122](#)
  - wolfentry\_table\_n\_inserts, [123](#)
- Route/Rule Subsystem, [69](#)
  - WOLFENTRY\_FORMAT\_FLAG\_ALWAYS\_NUMERIC, [76](#)
  - WOLFENTRY\_FORMAT\_FLAG\_NONE, [76](#)
  - wolfentry\_format\_flags\_t, [76](#)
  - wolfentry\_route\_bulk\_clear\_insert\_action\_status, [77](#)
  - wolfentry\_route\_bulk\_insert\_actions, [78](#)
  - wolfentry\_route\_delete, [78](#)
  - wolfentry\_route\_delete\_by\_id, [79](#)
  - wolfentry\_route\_drop\_reference, [79](#)
  - wolfentry\_route\_event\_dispatch, [80](#)
  - wolfentry\_route\_export, [80](#)
  - wolfentry\_route\_exports\_render, [81](#)
  - WOLFENTRY\_ROUTE\_FLAG\_DELETE\_ACTIONS\_CALLED, [77](#)
  - WOLFENTRY\_ROUTE\_FLAG\_DIRECTION\_IN, [76](#)
  - WOLFENTRY\_ROUTE\_FLAG\_DIRECTION\_OUT, [77](#)
  - WOLFENTRY\_ROUTE\_FLAG\_DONT\_COUNT\_CURRENT\_CONNECTIONS, [77](#)
  - WOLFENTRY\_ROUTE\_FLAG\_DONT\_COUNT\_HITS, [77](#)
  - WOLFENTRY\_ROUTE\_FLAG\_GREEN, [77](#)
  - WOLFENTRY\_ROUTE\_FLAG\_IGNORE\_COMMENDABLE, [77](#)
  - WOLFENTRY\_ROUTE\_FLAG\_IN\_TABLE, [77](#)
  - WOLFENTRY\_ROUTE\_FLAG\_INSERT\_ACTIONS\_CALLED, [77](#)
  - WOLFENTRY\_ROUTE\_FLAG\_LOCAL\_ADDR\_BITMASK, [77](#)
  - WOLFENTRY\_ROUTE\_FLAG\_LOCAL\_INTERFACE\_WILDCARD, [76](#)
  - WOLFENTRY\_ROUTE\_FLAG\_NONE, [76](#)
  - WOLFENTRY\_ROUTE\_FLAG\_PARENT\_EVENT\_WILDCARD, [76](#)
  - WOLFENTRY\_ROUTE\_FLAG\_PENALTYBOXED, [77](#)
  - WOLFENTRY\_ROUTE\_FLAG\_PENDING\_DELETE, [77](#)
  - WOLFENTRY\_ROUTE\_FLAG\_PORT\_RESET, [77](#)
  - WOLFENTRY\_ROUTE\_FLAG\_REMOTE\_ADDR\_BITMASK, [77](#)
  - WOLFENTRY\_ROUTE\_FLAG\_REMOTE\_INTERFACE\_WILDCARD, [76](#)
  - WOLFENTRY\_ROUTE\_FLAG\_SA\_FAMILY\_WILDCARD, [76](#)
  - WOLFENTRY\_ROUTE\_FLAG\_SA\_LOCAL\_ADDR\_WILDCARD, [76](#)
  - WOLFENTRY\_ROUTE\_FLAG\_SA\_LOCAL\_PORT\_WILDCARD, [76](#)
  - WOLFENTRY\_ROUTE\_FLAG\_SA\_PROTO\_WILDCARD, [76](#)
  - WOLFENTRY\_ROUTE\_FLAG\_SA\_REMOTE\_ADDR\_WILDCARD, [76](#)

- WOLFSENTRY\_ROUTE\_FLAG\_SA\_REMOTE\_PORT\_WILDCARD, 76
- WOLFSENTRY\_ROUTE\_FLAG\_TCPLIKE\_PORT\_NUMBER, 76
- wolfentry\_route\_flags\_t, 76
- wolfentry\_route\_flush\_table, 81
- wolfentry\_route\_get\_addrs, 82
- wolfentry\_route\_get\_flags, 82
- wolfentry\_route\_get\_main\_table, 83
- wolfentry\_route\_get\_metadata, 83
- wolfentry\_route\_get\_private\_data, 83
- wolfentry\_route\_get\_reference, 84
- wolfentry\_route\_insert, 85
- WOLFSENTRY\_ROUTE\_INTERNAL\_FLAGS, 75
- wolfentry\_route\_parent\_event, 85
- wolfentry\_route\_render, 86
- wolfentry\_route\_set\_wildcard, 86
- wolfentry\_route\_stale\_purge, 87
- wolfentry\_route\_table\_default\_policy\_get, 87
- wolfentry\_route\_table\_default\_policy\_set, 87
- wolfentry\_route\_table\_fallthrough\_route\_get, 88
- wolfentry\_route\_table\_iterate\_current, 88
- wolfentry\_route\_table\_iterate\_end, 89
- wolfentry\_route\_table\_iterate\_next, 89
- wolfentry\_route\_table\_iterate\_prev, 90
- wolfentry\_route\_table\_iterate\_seek\_to\_head, 90
- wolfentry\_route\_table\_iterate\_seek\_to\_tail, 90
- wolfentry\_route\_table\_iterate\_start, 91
- wolfentry\_route\_update\_flags, 91
- WOLFSENTRY\_SOCKADDR, 75
- sem\_destroy\_cb\_t
  - Semaphore Function Callbacks, 147
- sem\_init\_cb\_t
  - Semaphore Function Callbacks, 147
- sem\_post\_cb\_t
  - Semaphore Function Callbacks, 147
- sem\_timedwait\_cb\_t
  - Semaphore Function Callbacks, 147
- sem\_trywait\_cb\_t
  - Semaphore Function Callbacks, 147
- sem\_wait\_cb\_t
  - Semaphore Function Callbacks, 147
- Semaphore Function Callbacks, 146
  - sem\_destroy\_cb\_t, 147
  - sem\_init\_cb\_t, 147
  - sem\_post\_cb\_t, 147
  - sem\_timedwait\_cb\_t, 147
  - sem\_trywait\_cb\_t, 147
  - sem\_wait\_cb\_t, 147
- semcbs
  - wolfentry\_host\_platform\_interface, 153
- Startup/Configuration/Shutdown Subsystem, 52
  - WOLFSENTRY\_CLONE\_FLAG\_AS\_AT\_CREATION, 57
  - WOLFSENTRY\_CLONE\_FLAG\_NO\_ROUTES, 57
  - WOLFSENTRY\_CLONE\_FLAG\_NONE, 57
  - wolfentry\_clone\_flags\_t, 56
- WOLFSENTRY\_CONFIG\_LOAD\_FLAG\_DRY\_RUN, 57
- WOLFSENTRY\_CONFIG\_LOAD\_FLAG\_FINI, 57
- WOLFSENTRY\_CONFIG\_LOAD\_FLAG\_FLUSH\_ONLY\_ROUTES, 57
- WOLFSENTRY\_CONFIG\_LOAD\_FLAG\_JSON\_DOM\_DUPKEY\_ABANDON, 57
- WOLFSENTRY\_CONFIG\_LOAD\_FLAG\_JSON\_DOM\_DUPKEY\_USING, 57
- WOLFSENTRY\_CONFIG\_LOAD\_FLAG\_JSON\_DOM\_DUPKEY\_USING\_COPY, 57
- WOLFSENTRY\_CONFIG\_LOAD\_FLAG\_JSON\_DOM\_MAINTAINED, 57
- WOLFSENTRY\_CONFIG\_LOAD\_FLAG\_LOAD\_THEN\_COMMIT, 57
- WOLFSENTRY\_CONFIG\_LOAD\_FLAG\_NO\_FLUSH, 57
- WOLFSENTRY\_CONFIG\_LOAD\_FLAG\_NO\_ROUTES\_OR\_EVENTS, 57
- WOLFSENTRY\_CONFIG\_LOAD\_FLAG\_NONE, 57
- wolfentry\_config\_load\_flags, 57
- wolfentry\_context\_clone, 58
- wolfentry\_context\_enable\_actions, 58
- wolfentry\_context\_exchange, 58
- wolfentry\_context\_flush, 59
- wolfentry\_context\_free, 59
- wolfentry\_context\_inhibit\_actions, 59
- wolfentry\_defaultconfig\_get, 60
- wolfentry\_defaultconfig\_update, 60
- wolfentry\_init, 61
- WOLFSENTRY\_INIT\_FLAG\_LOCK\_SHARED\_ERROR\_CHECKING, 58
- WOLFSENTRY\_INIT\_FLAG\_NONE, 58
- wolfentry\_init\_flags\_t, 57
- wolfentry\_shutdown, 61
- Thread Synchronization Subsystem, 123
  - wolfentry\_lock\_alloc, 130
  - wolfentry\_lock\_destroy, 132
  - WOLFSENTRY\_LOCK\_FLAG\_ABANDON\_RESERVATION\_TOO, 130
  - WOLFSENTRY\_LOCK\_FLAG\_AUTO\_DOWNGRADE, 130
  - WOLFSENTRY\_LOCK\_FLAG\_GET\_RESERVATION\_TOO, 130
  - WOLFSENTRY\_LOCK\_FLAG\_NONE, 130
  - WOLFSENTRY\_LOCK\_FLAG\_NONRECURSIVE\_MUTEX, 130
  - WOLFSENTRY\_LOCK\_FLAG\_NONRECURSIVE\_SHARED, 130
  - WOLFSENTRY\_LOCK\_FLAG\_PSHARED, 130
  - WOLFSENTRY\_LOCK\_FLAG\_RETAIN\_SEMAPHORE, 130
  - WOLFSENTRY\_LOCK\_FLAG\_SHARED\_ERROR\_CHECKING, 130
  - WOLFSENTRY\_LOCK\_FLAG\_TRY\_RESERVATION\_TOO, 130
  - wolfentry\_lock\_flags\_t, 129



- wolfSentry\_lock\_free, [132](#)
- wolfSentry\_lock\_get\_flags, [133](#)
- wolfSentry\_lock\_have\_either, [133](#)
- wolfSentry\_lock\_have\_mutex, [134](#)
- wolfSentry\_lock\_have\_shared, [134](#)
- wolfSentry\_lock\_have\_shared2mutex\_reservation, [135](#)
- wolfSentry\_lock\_init, [135](#)
- wolfSentry\_lock\_mutex, [136](#)
- wolfSentry\_lock\_mutex2shared, [136](#)
- wolfSentry\_lock\_mutex\_abstimed, [137](#)
- wolfSentry\_lock\_mutex\_timed, [137](#)
- wolfSentry\_lock\_shared, [138](#)
- wolfSentry\_lock\_shared2mutex, [138](#)
- wolfSentry\_lock\_shared2mutex\_abandon, [139](#)
- wolfSentry\_lock\_shared2mutex\_abstimed, [139](#)
- wolfSentry\_lock\_shared2mutex\_redeem, [140](#)
- wolfSentry\_lock\_shared2mutex\_redeem\_abstimed, [140](#)
- wolfSentry\_lock\_shared2mutex\_redeem\_timed, [141](#)
- wolfSentry\_lock\_shared2mutex\_reserve, [141](#)
- wolfSentry\_lock\_shared2mutex\_timed, [142](#)
- wolfSentry\_lock\_shared\_abstimed, [142](#)
- wolfSentry\_lock\_shared\_timed, [143](#)
- wolfSentry\_lock\_unlock, [143](#)
- WOLFSENTRY\_THREAD\_FLAG\_DEADLINE, [130](#)
- WOLFSENTRY\_THREAD\_FLAG\_NONE, [130](#)
- WOLFSENTRY\_THREAD\_FLAG\_READONLY, [130](#)
- wolfSentry\_thread\_flags\_t, [130](#)
- WOLFSENTRY\_THREAD\_HEADER, [128](#)
- WOLFSENTRY\_THREAD\_HEADER\_CHECK, [128](#)
- WOLFSENTRY\_THREAD\_HEADER\_CHECKED, [128](#)
- WOLFSENTRY\_THREAD\_HEADER\_DECLS, [129](#)
- WOLFSENTRY\_THREAD\_HEADER\_INIT, [129](#)
- WOLFSENTRY\_THREAD\_HEADER\_INIT\_CHECKED, [129](#)
- WOLFSENTRY\_THREAD\_TAILER, [129](#)
- Time Functions and Callbacks, [145](#)
- timecbcs
  - wolfSentry\_host\_platform\_interface, [153](#)
- User-Defined Value Subsystem, [116](#)
  - wolfSentry\_kv\_validator\_t, [120](#)
  - wolfSentry\_user\_value\_get\_bytes, [120](#)
  - wolfSentry\_user\_value\_get\_json, [120](#)
  - wolfSentry\_user\_value\_get\_string, [120](#)
- version
  - wolfSentry\_build\_settings, [151](#)
- wolfSentry – The Wolfssl Embedded Firewall/IDPS, [1](#)
- wolfSentry Release History and Change Log, [21](#)
- wolfSentry/centijson\_dom.h, [159](#)
- wolfSentry/centijson\_sax.h, [161](#)
- wolfSentry/centijson\_value.h, [165](#)
- wolfSentry/wolfSentry.h, [172](#), [194](#)
- wolfSentry/wolfSentry\_af.h, [213](#), [217](#)
- wolfSentry/wolfSentry\_errcodes.h, [218](#), [223](#)
- wolfSentry/wolfSentry\_json.h, [228](#), [229](#)
- wolfSentry/wolfSentry\_lwip.h, [230](#), [231](#)
- wolfSentry/wolfSentry\_settings.h, [232](#), [236](#)
- wolfSentry/wolfSentry\_util.h, [244](#), [248](#)
- wolfSentry/wolfssl\_test.h, [251](#), [252](#)
- wolfSentry\_action\_callback\_t
  - Action Subsystem, [94](#)
- wolfSentry\_action\_delete
  - Action Subsystem, [96](#)
- wolfSentry\_action\_drop\_reference
  - Action Subsystem, [97](#)
- WOLFSENTRY\_ACTION\_FLAG\_DISABLED
  - Action Subsystem, [95](#)
- WOLFSENTRY\_ACTION\_FLAG\_NONE
  - Action Subsystem, [95](#)
- wolfSentry\_action\_flags\_t
  - Action Subsystem, [95](#)
- wolfSentry\_action\_flush\_all
  - Action Subsystem, [97](#)
- wolfSentry\_action\_get\_flags
  - Action Subsystem, [98](#)
- wolfSentry\_action\_get\_label
  - Action Subsystem, [98](#)
- wolfSentry\_action\_get\_reference
  - Action Subsystem, [98](#)
- wolfSentry\_action\_insert
  - Action Subsystem, [99](#)
- WOLFSENTRY\_ACTION\_RES\_ACCEPT
  - Action Subsystem, [95](#)
- WOLFSENTRY\_ACTION\_RES\_BINDING
  - Action Subsystem, [95](#)
- WOLFSENTRY\_ACTION\_RES\_CLOSE\_WAIT
  - Action Subsystem, [96](#)
- WOLFSENTRY\_ACTION\_RES\_CLOSED
  - Action Subsystem, [96](#)
- WOLFSENTRY\_ACTION\_RES\_COMMENDABLE
  - Action Subsystem, [95](#)
- WOLFSENTRY\_ACTION\_RES\_CONNECT
  - Action Subsystem, [95](#)
- WOLFSENTRY\_ACTION\_RES\_CONNECTING\_OUT
  - Action Subsystem, [96](#)
- WOLFSENTRY\_ACTION\_RES\_DEALLOCATED
  - Action Subsystem, [95](#)
- WOLFSENTRY\_ACTION\_RES\_DEROGATORY
  - Action Subsystem, [95](#)
- WOLFSENTRY\_ACTION\_RES\_DISCONNECT
  - Action Subsystem, [95](#)
- WOLFSENTRY\_ACTION\_RES\_ERROR
  - Action Subsystem, [95](#)
- WOLFSENTRY\_ACTION\_RES\_FALLTHROUGH
  - Action Subsystem, [95](#)
- WOLFSENTRY\_ACTION\_RES\_INSERTED
  - Action Subsystem, [95](#)
- WOLFSENTRY\_ACTION\_RES\_LISTENING
  - Action Subsystem, [96](#)
- WOLFSENTRY\_ACTION\_RES\_NONE



- Action Subsystem, [95](#)
- WOLFSENTRY\_ACTION\_RES\_PORT\_RESET
  - Action Subsystem, [95](#)
- WOLFSENTRY\_ACTION\_RES\_RECEIVED
  - Action Subsystem, [95](#)
- WOLFSENTRY\_ACTION\_RES\_REJECT
  - Action Subsystem, [95](#)
- WOLFSENTRY\_ACTION\_RES\_SENDING
  - Action Subsystem, [95](#)
- WOLFSENTRY\_ACTION\_RES\_SOCK\_ERROR
  - Action Subsystem, [96](#)
- WOLFSENTRY\_ACTION\_RES\_STOP
  - Action Subsystem, [95](#)
- WOLFSENTRY\_ACTION\_RES\_STOPPED\_LISTENING
  - Action Subsystem, [96](#)
- wolfentry\_action\_res\_t
  - Action Subsystem, [95](#)
- WOLFSENTRY\_ACTION\_RES\_UNREACHABLE
  - Action Subsystem, [96](#)
- WOLFSENTRY\_ACTION\_RES\_UPDATE
  - Action Subsystem, [95](#)
- WOLFSENTRY\_ACTION\_RES\_USER0
  - Action Subsystem, [96](#)
- WOLFSENTRY\_ACTION\_RES\_USER1
  - Action Subsystem, [96](#)
- WOLFSENTRY\_ACTION\_RES\_USER2
  - Action Subsystem, [96](#)
- WOLFSENTRY\_ACTION\_RES\_USER3
  - Action Subsystem, [96](#)
- WOLFSENTRY\_ACTION\_RES\_USER4
  - Action Subsystem, [96](#)
- WOLFSENTRY\_ACTION\_RES\_USER5
  - Action Subsystem, [96](#)
- WOLFSENTRY\_ACTION\_RES\_USER6
  - Action Subsystem, [96](#)
- WOLFSENTRY\_ACTION\_TYPE\_DECISION
  - Action Subsystem, [96](#)
- WOLFSENTRY\_ACTION\_TYPE\_DELETE
  - Action Subsystem, [96](#)
- WOLFSENTRY\_ACTION\_TYPE\_INSERT
  - Action Subsystem, [96](#)
- WOLFSENTRY\_ACTION\_TYPE\_MATCH
  - Action Subsystem, [96](#)
- WOLFSENTRY\_ACTION\_TYPE\_NONE
  - Action Subsystem, [96](#)
- WOLFSENTRY\_ACTION\_TYPE\_POST
  - Action Subsystem, [96](#)
- wolfentry\_action\_type\_t
  - Action Subsystem, [96](#)
- WOLFSENTRY\_ACTION\_TYPE\_UPDATE
  - Action Subsystem, [96](#)
- wolfentry\_action\_update\_flags
  - Action Subsystem, [99](#)
- wolfentry\_allocator, [151](#)
- WOLFSENTRY\_ATOMIC\_DECREMENT\_UNSIGNED\_SAFELY
  - wolfentry\_util.h, [246](#)
- WOLFSENTRY\_ATOMIC\_DECREMENT\_UNSIGNED\_SAFELY\_BY\_ONE
  - wolfentry\_util.h, [246](#)
- WOLFSENTRY\_ATOMIC\_INCREMENT\_UNSIGNED\_SAFELY
  - wolfentry\_util.h, [246](#)
- WOLFSENTRY\_ATOMIC\_INCREMENT\_UNSIGNED\_SAFELY\_BY\_ONE
  - wolfentry\_util.h, [247](#)
- WOLFSENTRY\_ATOMIC\_RESET
  - wolfentry\_util.h, [247](#)
- WOLFSENTRY\_ATOMIC\_TEST\_AND\_SET
  - wolfentry\_util.h, [247](#)
- WOLFSENTRY\_ATOMIC\_UPDATE\_FLAGS
  - wolfentry\_util.h, [247](#)
- wolfentry\_build\_settings, [151](#)
  - config, [151](#)
  - version, [151](#)
- WOLFSENTRY\_CLONE\_FLAG\_AS\_AT\_CREATION
  - Startup/Configuration/Shutdown Subsystem, [57](#)
- WOLFSENTRY\_CLONE\_FLAG\_NO\_ROUTES
  - Startup/Configuration/Shutdown Subsystem, [57](#)
- WOLFSENTRY\_CLONE\_FLAG\_NONE
  - Startup/Configuration/Shutdown Subsystem, [57](#)
- wolfentry\_clone\_flags\_t
  - Startup/Configuration/Shutdown Subsystem, [56](#)
- WOLFSENTRY\_CONFIG\_LOAD\_FLAG\_DRY\_RUN
  - Startup/Configuration/Shutdown Subsystem, [57](#)
- WOLFSENTRY\_CONFIG\_LOAD\_FLAG\_FINI
  - Startup/Configuration/Shutdown Subsystem, [57](#)
- WOLFSENTRY\_CONFIG\_LOAD\_FLAG\_FLUSH\_ONLY\_ROUTES
  - Startup/Configuration/Shutdown Subsystem, [57](#)
- WOLFSENTRY\_CONFIG\_LOAD\_FLAG\_JSON\_DOM\_DUPKEY\_ABORT
  - Startup/Configuration/Shutdown Subsystem, [57](#)
- WOLFSENTRY\_CONFIG\_LOAD\_FLAG\_JSON\_DOM\_DUPKEY\_USEFIR
  - Startup/Configuration/Shutdown Subsystem, [57](#)
- WOLFSENTRY\_CONFIG\_LOAD\_FLAG\_JSON\_DOM\_DUPKEY\_USELAS
  - Startup/Configuration/Shutdown Subsystem, [57](#)
- WOLFSENTRY\_CONFIG\_LOAD\_FLAG\_JSON\_DOM\_MAINTAINDICTOP
  - Startup/Configuration/Shutdown Subsystem, [57](#)
- WOLFSENTRY\_CONFIG\_LOAD\_FLAG\_LOAD\_THEN\_COMMIT
  - Startup/Configuration/Shutdown Subsystem, [57](#)
- WOLFSENTRY\_CONFIG\_LOAD\_FLAG\_NO\_FLUSH
  - Startup/Configuration/Shutdown Subsystem, [57](#)
- WOLFSENTRY\_CONFIG\_LOAD\_FLAG\_NO\_ROUTES\_OR\_EVENTS
  - Startup/Configuration/Shutdown Subsystem, [57](#)
- WOLFSENTRY\_CONFIG\_LOAD\_FLAG\_NONE
  - Startup/Configuration/Shutdown Subsystem, [57](#)
- wolfentry\_config\_load\_flags
  - Startup/Configuration/Shutdown Subsystem, [57](#)
- wolfentry\_context\_clone
  - Startup/Configuration/Shutdown Subsystem, [58](#)
- wolfentry\_context\_enable\_actions
  - Startup/Configuration/Shutdown Subsystem, [58](#)
- wolfentry\_context\_exchange
  - Startup/Configuration/Shutdown Subsystem, [58](#)
- wolfentry\_context\_flush
  - Startup/Configuration/Shutdown Subsystem, [59](#)
- wolfentry\_context\_free
  - Startup/Configuration/Shutdown Subsystem, [59](#)
- wolfentry\_context\_inhibit\_actions
  - Startup/Configuration/Shutdown Subsystem, [59](#)
- wolfentry\_data, [152](#)

- WOLFSENTRY\_DEBUG\_CALL\_TRACE
  - Diagnostics, Control Flow Helpers, and Compiler Attribute Helpers, [66](#)
- wolfentry\_defaultconfig\_get
  - Startup/Configuration/Shutdown Subsystem, [60](#)
- wolfentry\_defaultconfig\_update
  - Startup/Configuration/Shutdown Subsystem, [60](#)
- WOLFSENTRY\_ERROR\_UNLOCK\_AND\_RETURN
  - Diagnostics, Control Flow Helpers, and Compiler Attribute Helpers, [66](#)
- wolfentry\_event\_action\_append
  - Event Subsystem, [103](#)
- wolfentry\_event\_action\_delete
  - Event Subsystem, [103](#)
- wolfentry\_event\_action\_insert\_after
  - Event Subsystem, [104](#)
- wolfentry\_event\_action\_list\_done
  - Event Subsystem, [104](#)
- wolfentry\_event\_action\_list\_next
  - Event Subsystem, [105](#)
- wolfentry\_event\_action\_list\_start
  - Event Subsystem, [105](#)
- wolfentry\_event\_action\_prepend
  - Event Subsystem, [106](#)
- wolfentry\_event\_delete
  - Event Subsystem, [106](#)
- wolfentry\_event\_drop\_reference
  - Event Subsystem, [107](#)
- WOLFSENTRY\_EVENT\_FLAG\_IS\_PARENT\_EVENT
  - Event Subsystem, [102](#)
- WOLFSENTRY\_EVENT\_FLAG\_IS\_SUBEVENT
  - Event Subsystem, [102](#)
- WOLFSENTRY\_EVENT\_FLAG\_NONE
  - Event Subsystem, [102](#)
- wolfentry\_event\_flags\_t
  - Event Subsystem, [102](#)
- wolfentry\_event\_flush\_all
  - Event Subsystem, [107](#)
- wolfentry\_event\_get\_config
  - Event Subsystem, [108](#)
- wolfentry\_event\_get\_flags
  - Event Subsystem, [108](#)
- wolfentry\_event\_get\_label
  - Event Subsystem, [108](#)
- wolfentry\_event\_get\_reference
  - Event Subsystem, [109](#)
- wolfentry\_event\_insert
  - Event Subsystem, [109](#)
- wolfentry\_event\_set\_aux\_event
  - Event Subsystem, [110](#)
- wolfentry\_event\_update\_config
  - Event Subsystem, [110](#)
- wolfentry\_eventconfig, [152](#)
- wolfentry\_eventconfig\_check
  - Event Subsystem, [112](#)
- WOLFSENTRY\_EVENTCONFIG\_FLAG\_COMMENDABLE\_CLEAR\_DEROGATORY
  - Event Subsystem, [102](#)
- WOLFSENTRY\_EVENTCONFIG\_FLAG\_DEROGATORY\_THREADS\_IGNORE\_COMMENDABLE
  - Event Subsystem, [102](#)
- Event Subsystem, [102](#)
- WOLFSENTRY\_EVENTCONFIG\_FLAG\_INHIBIT\_ACTIONS
  - Event Subsystem, [102](#)
- WOLFSENTRY\_EVENTCONFIG\_FLAG\_NONE
  - Event Subsystem, [102](#)
- wolfentry\_eventconfig\_flags\_t
  - Event Subsystem, [102](#)
- wolfentry\_eventconfig\_init
  - Event Subsystem, [112](#)
- WOLFSENTRY\_FORMAT\_FLAG\_ALWAYS\_NUMERIC
  - Route/Rule Subsystem, [76](#)
- WOLFSENTRY\_FORMAT\_FLAG\_NONE
  - Route/Rule Subsystem, [76](#)
- wolfentry\_format\_flags\_t
  - Route/Rule Subsystem, [76](#)
- wolfentry\_get\_object\_id
  - Object Subsystem, [122](#)
- wolfentry\_get\_object\_type
  - Object Subsystem, [122](#)
- wolfentry\_host\_platform\_interface, [153](#)
  - allocator, [153](#)
  - caller\_build\_settings, [153](#)
  - semcbs, [153](#)
  - timecbs, [153](#)
- wolfentry\_init
  - Startup/Configuration/Shutdown Subsystem, [61](#)
- WOLFSENTRY\_INIT\_FLAG\_LOCK\_SHARED\_ERROR\_CHECKING
  - Startup/Configuration/Shutdown Subsystem, [58](#)
- WOLFSENTRY\_INIT\_FLAG\_NONE
  - Startup/Configuration/Shutdown Subsystem, [58](#)
- wolfentry\_init\_flags\_t
  - Startup/Configuration/Shutdown Subsystem, [57](#)
- wolfentry\_kv\_pair, [154](#)
  - b, [154](#)
- wolfentry\_kv\_validator\_t
  - User-Defined Value Subsystem, [120](#)
- wolfentry\_lock\_alloc
  - Thread Synchronization Subsystem, [130](#)
- wolfentry\_lock\_destroy
  - Thread Synchronization Subsystem, [132](#)
- WOLFSENTRY\_LOCK\_FLAG\_ABANDON\_RESERVATION\_TOO
  - Thread Synchronization Subsystem, [130](#)
- WOLFSENTRY\_LOCK\_FLAG\_AUTO\_DOWNGRADE
  - Thread Synchronization Subsystem, [130](#)
- WOLFSENTRY\_LOCK\_FLAG\_GET\_RESERVATION\_TOO
  - Thread Synchronization Subsystem, [130](#)
- WOLFSENTRY\_LOCK\_FLAG\_NONE
  - Thread Synchronization Subsystem, [130](#)
- WOLFSENTRY\_LOCK\_FLAG\_NONRECURSIVE\_MUTEX
  - Thread Synchronization Subsystem, [130](#)
- WOLFSENTRY\_LOCK\_FLAG\_NONRECURSIVE\_SHARED
  - Thread Synchronization Subsystem, [130](#)
- WOLFSENTRY\_LOCK\_FLAG\_PSHARED
  - Thread Synchronization Subsystem, [130](#)
- WOLFSENTRY\_LOCK\_FLAG\_RETAIN\_SEMAPHORE
  - Thread Synchronization Subsystem, [130](#)
- WOLFSENTRY\_LOCK\_FLAG\_SHARED\_ERROR\_CHECKING
  - Thread Synchronization Subsystem, [130](#)

- WOLFSENTRY\_LOCK\_FLAG\_TRY\_RESERVATION\_TOO
  - Thread Synchronization Subsystem, [130](#)
- wolfentry\_lock\_flags\_t
  - Thread Synchronization Subsystem, [129](#)
- wolfentry\_lock\_free
  - Thread Synchronization Subsystem, [132](#)
- wolfentry\_lock\_get\_flags
  - Thread Synchronization Subsystem, [133](#)
- wolfentry\_lock\_have\_either
  - Thread Synchronization Subsystem, [133](#)
- wolfentry\_lock\_have\_mutex
  - Thread Synchronization Subsystem, [134](#)
- wolfentry\_lock\_have\_shared
  - Thread Synchronization Subsystem, [134](#)
- wolfentry\_lock\_have\_shared2mutex\_reservation
  - Thread Synchronization Subsystem, [135](#)
- wolfentry\_lock\_init
  - Thread Synchronization Subsystem, [135](#)
- wolfentry\_lock\_mutex
  - Thread Synchronization Subsystem, [136](#)
- wolfentry\_lock\_mutex2shared
  - Thread Synchronization Subsystem, [136](#)
- wolfentry\_lock\_mutex\_abstimed
  - Thread Synchronization Subsystem, [137](#)
- wolfentry\_lock\_mutex\_timed
  - Thread Synchronization Subsystem, [137](#)
- wolfentry\_lock\_shared
  - Thread Synchronization Subsystem, [138](#)
- wolfentry\_lock\_shared2mutex
  - Thread Synchronization Subsystem, [138](#)
- wolfentry\_lock\_shared2mutex\_abandon
  - Thread Synchronization Subsystem, [139](#)
- wolfentry\_lock\_shared2mutex\_abstimed
  - Thread Synchronization Subsystem, [139](#)
- wolfentry\_lock\_shared2mutex\_redeem
  - Thread Synchronization Subsystem, [140](#)
- wolfentry\_lock\_shared2mutex\_redeem\_abstimed
  - Thread Synchronization Subsystem, [140](#)
- wolfentry\_lock\_shared2mutex\_redeem\_timed
  - Thread Synchronization Subsystem, [141](#)
- wolfentry\_lock\_shared2mutex\_reserve
  - Thread Synchronization Subsystem, [141](#)
- wolfentry\_lock\_shared2mutex\_timed
  - Thread Synchronization Subsystem, [142](#)
- wolfentry\_lock\_shared\_abstimed
  - Thread Synchronization Subsystem, [142](#)
- wolfentry\_lock\_shared\_timed
  - Thread Synchronization Subsystem, [143](#)
- wolfentry\_lock\_unlock
  - Thread Synchronization Subsystem, [143](#)
- WOLFSENTRY\_MUTEX\_OR\_RETURN
  - Diagnostics, Control Flow Helpers, and Compiler Attribute Helpers, [66](#)
- WOLFSENTRY\_OBJECT\_TYPE\_ACTION
  - Object Subsystem, [122](#)
- WOLFSENTRY\_OBJECT\_TYPE\_ADDR\_FAMILY\_BYNAME
  - Object Subsystem, [122](#)
- WOLFSENTRY\_OBJECT\_TYPE\_ADDR\_FAMILY\_BYNUMBER
  - Object Subsystem, [122](#)
- WOLFSENTRY\_OBJECT\_TYPE\_EVENT
  - Object Subsystem, [122](#)
- WOLFSENTRY\_OBJECT\_TYPE\_KV
  - Object Subsystem, [122](#)
- WOLFSENTRY\_OBJECT\_TYPE\_ROUTE
  - Object Subsystem, [122](#)
- wolfentry\_object\_type\_t
  - Object Subsystem, [121](#)
- WOLFSENTRY\_OBJECT\_TYPE\_TABLE
  - Object Subsystem, [122](#)
- WOLFSENTRY\_OBJECT\_TYPE\_UNINITED
  - Object Subsystem, [122](#)
- WOLFSENTRY\_PROMOTABLE\_EX
  - Diagnostics, Control Flow Helpers, and Compiler Attribute Helpers, [67](#)
- WOLFSENTRY\_PROMOTABLE\_OR\_RETURN
  - Diagnostics, Control Flow Helpers, and Compiler Attribute Helpers, [67](#)
- wolfentry\_route\_bulk\_clear\_insert\_action\_status
  - Route/Rule Subsystem, [77](#)
- wolfentry\_route\_bulk\_insert\_actions
  - Route/Rule Subsystem, [78](#)
- wolfentry\_route\_delete
  - Route/Rule Subsystem, [78](#)
- wolfentry\_route\_delete\_by\_id
  - Route/Rule Subsystem, [79](#)
- wolfentry\_route\_drop\_reference
  - Route/Rule Subsystem, [79](#)
- wolfentry\_route\_endpoint, [154](#)
- wolfentry\_route\_event\_dispatch
  - Route/Rule Subsystem, [80](#)
- wolfentry\_route\_export
  - Route/Rule Subsystem, [80](#)
- wolfentry\_route\_exports, [155](#)
- wolfentry\_route\_exports\_render
  - Route/Rule Subsystem, [81](#)
- WOLFSENTRY\_ROUTE\_FLAG\_DELETE\_ACTIONS\_CALLED
  - Route/Rule Subsystem, [77](#)
- WOLFSENTRY\_ROUTE\_FLAG\_DIRECTION\_IN
  - Route/Rule Subsystem, [76](#)
- WOLFSENTRY\_ROUTE\_FLAG\_DIRECTION\_OUT
  - Route/Rule Subsystem, [77](#)
- WOLFSENTRY\_ROUTE\_FLAG\_DONT\_COUNT\_CURRENT\_CONNECTIONS
  - Route/Rule Subsystem, [77](#)
- WOLFSENTRY\_ROUTE\_FLAG\_DONT\_COUNT\_HITS
  - Route/Rule Subsystem, [77](#)
- WOLFSENTRY\_ROUTE\_FLAG\_GREENLISTED
  - Route/Rule Subsystem, [77](#)
- WOLFSENTRY\_ROUTE\_FLAG\_IN\_TABLE
  - Route/Rule Subsystem, [77](#)
- WOLFSENTRY\_ROUTE\_FLAG\_INSERT\_ACTIONS\_CALLED
  - Route/Rule Subsystem, [77](#)
- WOLFSENTRY\_ROUTE\_FLAG\_LOCAL\_ADDR\_BITMASK
  - Route/Rule Subsystem, [77](#)
- WOLFSENTRY\_ROUTE\_FLAG\_LOCAL\_INTERFACE\_WILDCARD
  - Route/Rule Subsystem, [76](#)
- WOLFSENTRY\_ROUTE\_FLAG\_NONE

- Route/Rule Subsystem, [76](#)
- WOLFSENTRY\_ROUTE\_FLAG\_PARENT\_EVENT\_WILDCARD
  - Route/Rule Subsystem, [76](#)
- WOLFSENTRY\_ROUTE\_FLAG\_PENALTYBOXED
  - Route/Rule Subsystem, [77](#)
- WOLFSENTRY\_ROUTE\_FLAG\_PENDING\_DELETE
  - Route/Rule Subsystem, [77](#)
- WOLFSENTRY\_ROUTE\_FLAG\_PORT\_RESET
  - Route/Rule Subsystem, [77](#)
- WOLFSENTRY\_ROUTE\_FLAG\_REMOTE\_ADDR\_BITMASK
  - Route/Rule Subsystem, [77](#)
- WOLFSENTRY\_ROUTE\_FLAG\_REMOTE\_INTERFACE\_WILDCARD
  - Route/Rule Subsystem, [76](#)
- WOLFSENTRY\_ROUTE\_FLAG\_SA\_FAMILY\_WILDCARD
  - Route/Rule Subsystem, [76](#)
- WOLFSENTRY\_ROUTE\_FLAG\_SA\_LOCAL\_ADDR\_WILDCARD
  - Route/Rule Subsystem, [76](#)
- WOLFSENTRY\_ROUTE\_FLAG\_SA\_LOCAL\_PORT\_WILDCARD
  - Route/Rule Subsystem, [76](#)
- WOLFSENTRY\_ROUTE\_FLAG\_SA\_PROTO\_WILDCARD
  - Route/Rule Subsystem, [76](#)
- WOLFSENTRY\_ROUTE\_FLAG\_SA\_REMOTE\_ADDR\_WILDCARD
  - Route/Rule Subsystem, [76](#)
- WOLFSENTRY\_ROUTE\_FLAG\_SA\_REMOTE\_PORT\_WILDCARD
  - Route/Rule Subsystem, [76](#)
- WOLFSENTRY\_ROUTE\_FLAG\_TCPLIKE\_PORT\_NUMBERS
  - Route/Rule Subsystem, [76](#)
- wolfentry\_route\_flags\_t
  - Route/Rule Subsystem, [76](#)
- wolfentry\_route\_flush\_table
  - Route/Rule Subsystem, [81](#)
- wolfentry\_route\_get\_addrs
  - Route/Rule Subsystem, [82](#)
- wolfentry\_route\_get\_flags
  - Route/Rule Subsystem, [82](#)
- wolfentry\_route\_get\_main\_table
  - Route/Rule Subsystem, [83](#)
- wolfentry\_route\_get\_metadata
  - Route/Rule Subsystem, [83](#)
- wolfentry\_route\_get\_private\_data
  - Route/Rule Subsystem, [83](#)
- wolfentry\_route\_get\_reference
  - Route/Rule Subsystem, [84](#)
- wolfentry\_route\_insert
  - Route/Rule Subsystem, [85](#)
- WOLFSENTRY\_ROUTE\_INTERNAL\_FLAGS
  - Route/Rule Subsystem, [75](#)
- wolfentry\_route\_metadata\_exports, [156](#)
- wolfentry\_route\_parent\_event
  - Route/Rule Subsystem, [85](#)
- wolfentry\_route\_render
  - Route/Rule Subsystem, [86](#)
- wolfentry\_route\_set\_wildcard
  - Route/Rule Subsystem, [86](#)
- wolfentry\_route\_stale\_purge
  - Route/Rule Subsystem, [87](#)
- wolfentry\_route\_table\_default\_policy\_get
  - Route/Rule Subsystem, [87](#)
- wolfentry\_route\_table\_default\_policy\_set
  - Route/Rule Subsystem, [87](#)
- wolfentry\_route\_table\_fallthrough\_route\_get
  - Route/Rule Subsystem, [88](#)
- wolfentry\_route\_table\_iterate\_current
  - Route/Rule Subsystem, [88](#)
- wolfentry\_route\_table\_iterate\_end
  - Route/Rule Subsystem, [89](#)
- wolfentry\_route\_table\_iterate\_next
  - Route/Rule Subsystem, [89](#)
- wolfentry\_route\_table\_iterate\_prev
  - Route/Rule Subsystem, [90](#)
- wolfentry\_route\_table\_iterate\_seek\_to\_head
  - Route/Rule Subsystem, [90](#)
- wolfentry\_route\_table\_iterate\_seek\_to\_tail
  - Route/Rule Subsystem, [90](#)
- wolfentry\_route\_table\_iterate\_start
  - Route/Rule Subsystem, [91](#)
- wolfentry\_route\_update\_flags
  - Route/Rule Subsystem, [91](#)
- wolfentry\_semcbs, [156](#)
- WOLFSENTRY\_SHARED\_EX
  - Diagnostics, Control Flow Helpers, and Compiler Attribute Helpers, [67](#)
- WOLFSENTRY\_SHARED\_OR\_RETURN
  - Diagnostics, Control Flow Helpers, and Compiler Attribute Helpers, [67](#)
- wolfentry\_shutdown
  - Startup/Configuration/Shutdown Subsystem, [61](#)
- WOLFSENTRY\_SOCKADDR
  - Route/Rule Subsystem, [75](#)
- wolfentry\_sockaddr, [157](#)
- wolfentry\_table\_n\_deletes
  - Object Subsystem, [122](#)
- wolfentry\_table\_n\_inserts
  - Object Subsystem, [123](#)
- wolfentry\_thread\_context\_public, [158](#)
- WOLFSENTRY\_THREAD\_FLAG\_DEADLINE
  - Thread Synchronization Subsystem, [130](#)
- WOLFSENTRY\_THREAD\_FLAG\_NONE
  - Thread Synchronization Subsystem, [130](#)
- WOLFSENTRY\_THREAD\_FLAG\_READONLY
  - Thread Synchronization Subsystem, [130](#)
- wolfentry\_thread\_flags\_t
  - Thread Synchronization Subsystem, [130](#)
- WOLFSENTRY\_THREAD\_HEADER
  - Thread Synchronization Subsystem, [128](#)
- WOLFSENTRY\_THREAD\_HEADER\_CHECK
  - Thread Synchronization Subsystem, [128](#)
- WOLFSENTRY\_THREAD\_HEADER\_CHECKED
  - Thread Synchronization Subsystem, [128](#)
- WOLFSENTRY\_THREAD\_HEADER\_DECLS
  - Thread Synchronization Subsystem, [129](#)
- WOLFSENTRY\_THREAD\_HEADER\_INIT
  - Thread Synchronization Subsystem, [129](#)
- WOLFSENTRY\_THREAD\_HEADER\_INIT\_CHECKED
  - Thread Synchronization Subsystem, [129](#)
- WOLFSENTRY\_THREAD\_TAILER

- Thread Synchronization Subsystem, [129](#)
- wolfentry\_timecbs, [158](#)
- WOLFENTRY\_UNLOCK\_AND\_RETURN
  - Diagnostics, Control Flow Helpers, and Compiler Attribute Helpers, [67](#)
- WOLFENTRY\_UNLOCK\_AND\_UNRESERVE\_FOR\_RETURN
  - Diagnostics, Control Flow Helpers, and Compiler Attribute Helpers, [68](#)
- WOLFENTRY\_UNLOCK\_AND\_UNRESERVE\_FOR\_RETURN\_EX
  - Diagnostics, Control Flow Helpers, and Compiler Attribute Helpers, [68](#)
- WOLFENTRY\_UNLOCK\_FOR\_RETURN
  - Diagnostics, Control Flow Helpers, and Compiler Attribute Helpers, [68](#)
- WOLFENTRY\_UNLOCK\_FOR\_RETURN\_EX
  - Diagnostics, Control Flow Helpers, and Compiler Attribute Helpers, [68](#)
- wolfentry\_user\_value\_get\_bytes
  - User-Defined Value Subsystem, [120](#)
- wolfentry\_user\_value\_get\_json
  - User-Defined Value Subsystem, [120](#)
- wolfentry\_user\_value\_get\_string
  - User-Defined Value Subsystem, [120](#)
- wolfentry\_util.h
  - WOLFENTRY\_ATOMIC\_DECREMENT\_UNSIGNED\_SAFELY, [246](#)
  - WOLFENTRY\_ATOMIC\_DECREMENT\_UNSIGNED\_SAFELY\_BY\_ONE, [246](#)
  - WOLFENTRY\_ATOMIC\_INCREMENT\_UNSIGNED\_SAFELY, [246](#)
  - WOLFENTRY\_ATOMIC\_INCREMENT\_UNSIGNED\_SAFELY\_BY\_ONE, [247](#)
  - WOLFENTRY\_ATOMIC\_RESET, [247](#)
  - WOLFENTRY\_ATOMIC\_TEST\_AND\_SET, [247](#)
  - WOLFENTRY\_ATOMIC\_UPDATE\_FLAGS, [247](#)