

# Настройка SMTP-сервера Postfix

Лабораторная работа №8

---

Авдадаев Джамал Геланиевич

1 декабря 2025

Российский университет дружбы народов, Москва, Россия

## Цель работы

---

Приобретение практических навыков по установке и конфигурированию SMTP-сервера Postfix.

## Ход выполнения

---

# Установка Postfix и настройка firewall

```
Installed:
 postfix-2:3.8.5-8.el10.x86_64          postfix-lmdb-2:3.8.5-8.el10.x86_64          s-nail-14.9.24-12.el10.x86_64

Complete!
[root@server.dgavdadaev.net ~]#
[root@server.dgavdadaev.net ~]# firewall-cmd --add-service=smtp
success
[root@server.dgavdadaev.net ~]# firewall-cmd --add-service=smtp --permanent
success
[root@server.dgavdadaev.net ~]# firewall-cmd --list-services
cockpit dhcp dhcpv6-client dns http https smtp ssh ssh-custom
[root@server.dgavdadaev.net ~]# restorecon -vR /etc
Relabeled /etc/NetworkManager/system-connections/eth1.nmconnection from unconfined_u:object_r:user_tmp_t:s0 to unconfined_u:object_r:NetworkManager_etc_rw_t:s0
[root@server.dgavdadaev.net ~]# systemctl enable postfix.service
Created symlink '/etc/systemd/system/multi-user.target.wants/postfix.service' → '/usr/lib/systemd/system/postfix.service'.
[root@server.dgavdadaev.net ~]# systemctl start postfix.service
[root@server.dgavdadaev.net ~]#
```

Рис. 1: Установка Postfix и настройка firewall

## Настройка myorigin и mydomain

```
virtual_recipient_limit = $default_recipient_limit
virtual_recipient_refill_delay = $default_recipient_refill_delay
virtual_recipient_refill_limit = $default_recipient_refill_limit
virtual_transport = virtual
virtual_transport_rate_delay = $default_transport_rate_delay
virtual_uid_maps =
[root@server.dgavdadaev.net ~]# postconf myorigin
myorigin = $myhostname
[root@server.dgavdadaev.net ~]# postconf mydomain
mydomain = dgavdadaev.net
[root@server.dgavdadaev.net ~]# postconf -e 'myorigin = $mydomain'
[root@server.dgavdadaev.net ~]# postconf myorigin
myorigin = $mydomain
[root@server.dgavdadaev.net ~]# postfix check
[root@server.dgavdadaev.net ~]# systemctl reload postfix.service
[root@server.dgavdadaev.net ~]# █
```

Рис. 2: Изменение параметров myorigin и mydomain

## Продолжение настройки параметров

```
smtp_tls_CAfile = /etc/pki/tls/certs/ca-bundle.crt
smtp_tls_CApath = /etc/pki/tls/certs
smtp_tls_security_level = may
smtpd_tls_cert_file = /etc/pki/tls/certs/postfix.pem
smtpd_tls_key_file = /etc/pki/tls/private/postfix.key
smtpd_tls_security_level = may
unknown_local_recipient_reject_code = 550
[root@server.dgavdadaev.net ~]#
[root@server.dgavdadaev.net ~]# postconf -e 'mydomain = dgavdadaev.net'
[root@server.dgavdadaev.net ~]# postconf inet_protocols
inet_protocols = all
[root@server.dgavdadaev.net ~]# postconf -e 'inet_protocols = ipv4'
[root@server.dgavdadaev.net ~]# postfix check
[root@server.dgavdadaev.net ~]# systemctl reload postfix.service
[root@server.dgavdadaev.net ~]# █
```

Рис. 3: Изменение параметров myorigin и mydomain

# Мониторинг лога и отправка локального письма

```
[root@server.dgavdadaev.net ~]# tail -f /var/log/maillog
Nov 30 10:29:05 server postfix/postfix-script[13316]: refreshing the Postfix mail system
Nov 30 10:29:05 server postfix/master[12470]: reload -- version 3.8.5, configuration /etc/postfix
Nov 30 10:29:05 server postfix/master[12470]: warning: ignoring inet_protocols parameter value change
Nov 30 10:29:05 server postfix/master[12470]: warning: old value: "all", new value: "ipv4"
Nov 30 10:29:05 server postfix/master[12470]: warning: to change inet_protocols, stop and start Postfix
Nov 30 10:30:46 server postfix/pickup[13323]: 0F31520A3C7B: uid=1001 from=<dgavdadaev>
Nov 30 10:30:46 server postfix/cleanup[13579]: 0F31520A3C7B: message-id=<20251130103046.0F31520A3C7B@server.dgavdadaev.net>
Nov 30 10:30:46 server postfix/qmgr[13324]: 0F31520A3C7B: from=<dgavdadaev@dgavdadaev.net>, size=346, nrcpt=1 (queue active)
Nov 30 10:30:46 server postfix/local[13582]: 0F31520A3C7B: to=<dgavdadaev@server.dgavdadaev.net>, relay=local, delay=0.01, delays=0.01/0/0/0, dsn=2.0.0, status=sent (delivered to mailbox)
Nov 30 10:30:46 server postfix/qmgr[13324]: 0F31520A3C7B: removed
```

Рис. 4: Мониторинг лога и отправка локального письма



```
[dgavdadaev@server.dgavdadaev.net ~]$ echo . | mail -s test1 dgavdadaev@server.dgavdadaev.net
[dgavdadaev@server.dgavdadaev.net ~]$
You have new mail in /var/spool/mail/dgavdadaev
[dgavdadaev@server.dgavdadaev.net ~]$ cat /var/spool/mail/dgavdadaev
From dgavdadaev@dgavdadaev.net  Sun Nov 30 10:30:46 2025
Return-Path: <dgavdadaev@dgavdadaev.net>
X-Original-To: dgavdadaev@server.dgavdadaev.net
Delivered-To: dgavdadaev@server.dgavdadaev.net
Received: by server.dgavdadaev.net (Postfix, from userid 1001)
        id 0F31520A3C7B; Sun, 30 Nov 2025 10:30:46 +0000 (UTC)
Date: Sun, 30 Nov 2025 10:30:46 +0000
To: dgavdadaev@server.dgavdadaev.net
Subject: test1
User-Agent: s-nail v14.9.24
Message-Id: <20251130103046.0F31520A3C7B@server.dgavdadaev.net>
From: dgavdadaev@dgavdadaev.net

.

[dgavdadaev@server.dgavdadaev.net ~]$
```

Рис. 5: Мониторинг лога и отправка локального письма

Installed:

```
postfix-2:3.8.5-8.el10.x86_64      postfix-lmdb-2:3.8.5-8.el10.x86_64  
s-nail-14.9.24-12.el10.x86_64
```

Complete!

```
[root@client.dgavdadaev.net ~]# postconf inet_protocols
```

```
inet_protocols = all
```

```
[root@client.dgavdadaev.net ~]# postconf -e 'inet_protocols = ipv4'
```

```
[root@client.dgavdadaev.net ~]# systemctl enable postfix.service
```

```
Created symlink '/etc/systemd/system/multi-user.target.wants/postfix.service' →  
'/usr/lib/systemd/system/postfix.service'.
```

```
[root@client.dgavdadaev.net ~]# systemctl start postfix.service
```

```
[root@client.dgavdadaev.net ~]# █
```

Рис. 6: Установка Postfix и настройка IPv4 на клиенте

## Настройка inet\_interfaces и mynetworks

```
[root@server.dgavdadaev.net ~]#  
[root@server.dgavdadaev.net ~]# postconf -e 'inet_interfaces = all'  
[root@server.dgavdadaev.net ~]# postconf -e 'mynetworks = 127.0.0.0/8, 192.168.0.0/16'  
[root@server.dgavdadaev.net ~]# postfix check  
[root@server.dgavdadaev.net ~]# systemctl reload postfix.service  
[root@server.dgavdadaev.net ~]# systemctl stop postfix.service  
[root@server.dgavdadaev.net ~]# systemctl start postfix.service  
[root@server.dgavdadaev.net ~]# █
```

Рис. 7: Настройка inet\_interfaces и mynetworks

## Успешная доставка после изменения mynetworks

```
Nov 30 10:36:39 server postfix/smtpd[14731]: warning: run-time library vs. compile-time header version mismatch: OpenSSL 3.5.0 may not be compatible with OpenSSL 3.2.0
Nov 30 10:36:39 server postfix/smtpd[14731]: connect from client.dgavdadaev.net[192.168.1.30]
Nov 30 10:36:39 server postfix/smtpd[14731]: 9D11F20A3C63: client=client.dgavdadaev.net[192.168.1.30]
Nov 30 10:36:39 server postfix/cleanup[14735]: 9D11F20A3C63: message-id=<20251130103639.937494130AC2@client.dgavdadaev.net>
Nov 30 10:36:39 server postfix/smtpd[14731]: disconnect from client.dgavdadaev.net[192.168.1.30] ehlo=2 starttls=1 mail=1 rcpt=1 data=1 quit=1 commands=7
Nov 30 10:36:39 server postfix/qmgr[14641]: 9D11F20A3C63: from=<dgavdadaev@client.dgavdadaev.net>, size=575, nrcpt=1 (queue active)
Nov 30 10:36:39 server postfix/local[14736]: 9D11F20A3C63: to=<dgavdadaev@server.dgavdadaev.net>, relay=local, delay=0.01, delays=0/0/0/0, dsn=2.0.0, status=sent (delivered to mailbox)
Nov 30 10:36:39 server postfix/qmgr[14641]: 9D11F20A3C63: removed
```

Рис. 8: Успешная доставка письма после настройки mynetworks

## Письмо, отправленное на доменный адрес без MX

```
From dgavdadaev@client.dgavdadaev.net Sun Nov 30 10:36:39 2025
Return-Path: <dgavdadaev@client.dgavdadaev.net>
X-Original-To: dgavdadaev@server.dgavdadaev.net
Delivered-To: dgavdadaev@server.dgavdadaev.net
Received: from client.dgavdadaev.net (client.dgavdadaev.net [192.168.1.30])
    by server.dgavdadaev.net (Postfix) with ESMTPS id 9D11F20A3C63
    for <dgavdadaev@server.dgavdadaev.net>; Sun, 30 Nov 2025 10:36:39 +0000 (UTC)
Received: by client.dgavdadaev.net (Postfix, from userid 1001)
    id 937494130AC2; Sun, 30 Nov 2025 10:36:39 +0000 (UTC)
Date: Sun, 30 Nov 2025 10:36:39 +0000
To: dgavdadaev@server.dgavdadaev.net
Subject: test1
User-Agent: s-nail v14.9.24
Message-Id: <20251130103639.937494130AC2@client.dgavdadaev.net>
From: dgavdadaev@client.dgavdadaev.net
```

.

Рис. 9: Полученное письмо с клиента перед настройкой MX

## Очередь Postfix при ошибке доставки

```
[dgavdadaev@client.dgavdadaev.net ~]$ echo . | mail -s test2 dgavdadaev@dgavdadaev.net
[dgavdadaev@client.dgavdadaev.net ~]$ postqueue -p
-Queue ID- --Size-- ----Arrival Time---- -Sender/Recipient-----
30E284130A7F      353 Sun Nov 30 10:34:26 dgavdadaev@client.dgavdadaev.net
                (connect to server.dgavdadaev.net[192.168.1.1]:25: Connection refused)
                                dgavdadaev@server.dgavdadaev.net

-- 0 Kbytes in 1 Request.
[dgavdadaev@client.dgavdadaev.net ~]$ █
```

Рис. 10: Очередь сообщений Postfix при ошибке доставки

```
Nov 30 10:37:38 server postfix/smtpd[14731]: connect from client.dgavdadaev.net[192.168.1.30]
Nov 30 10:37:38 server postfix/smtpd[14731]: 2219E20A3C63: client=client.dgavdadaev.net[192.168.1.30]
Nov 30 10:37:38 server postfix/cleanup[14735]: 2219E20A3C63: message-id=<20251130103738.202D54130AC2@client.dgavdadaev.net>
Nov 30 10:37:38 server postfix/qmgr[14641]: 2219E20A3C63: from=<dgavdadaev@client.dgavdadaev.net>, size=561, nrcpt=1 (queue active)
Nov 30 10:37:38 server postfix/smtpd[14731]: disconnect from client.dgavdadaev.net[192.168.1.30] ehlo=2 starttls=1 mail=1 rcpt=1 data=1 q
uit=1 commands=7
Nov 30 10:37:38 server postfix/smtp[14865]: warning: run-time library vs. compile-time header version mismatch: OpenSSL 3.5.0 may not be
compatible with OpenSSL 3.2.0
Nov 30 10:37:38 server postfix/smtp[14865]: 2219E20A3C63: to=<dgavdadaev@dgavdadaev.net>, relay=none, delay=0.01, delays=0/0.01/0/0, dsn=
5.4.6, status=bounced (mail for dgavdadaev.net loops back to myself)
Nov 30 10:37:38 server postfix/cleanup[14735]: 25AF9229D5C3: message-id=<20251130103738.25AF9229D5C3@server.dgavdadaev.net>
Nov 30 10:37:38 server postfix/qmgr[14641]: 25AF9229D5C3: from=<>, size=2589, nrcpt=1 (queue active)
Nov 30 10:37:38 server postfix/bounce[14866]: 2219E20A3C63: sender non-delivery notification: 25AF9229D5C3
Nov 30 10:37:38 server postfix/qmgr[14641]: 2219E20A3C63: removed
Nov 30 10:37:38 server postfix/smtp[14865]: connect to client.dgavdadaev.net[192.168.1.30]:25: No route to host
Nov 30 10:37:38 server postfix/smtp[14865]: 25AF9229D5C3: to=<dgavdadaev@client.dgavdadaev.net>, relay=none, delay=0, delays=0/0/0/0, dsn
=4.4.1, status=deferred (connect to client.dgavdadaev.net[192.168.1.30]:25: No route to host)
```

Рис. 11: Мониторинг maillog при ошибке доставки

## Файл прямой зоны с МХ-записью

```
Open  ▾  +  dgavdadaev.net
/var/named/master/fz

1 $ORIGIN .
2 $TTL 86400      ; 1 day
3 dgavdadaev.net      IN SOA  dgavdadaev.net. server.dgavdadaev.net. (
4                          2025113007 ; serial
5                          86400      ; refresh (1 day)
6                          3600       ; retry (1 hour)
7                          604800     ; expire (1 week)
8                          10800      ; minimum (3 hours)
9                          )
10                     NS      dgavdadaev.net.
11                     A        192.168.1.1
12                     MX 10     mail.dgavdadaev.net.
13 $ORIGIN dgavdadaev.net.
14 $TTL 1200      ; 20 minutes
15 client         A        192.168.1.30
16                DHCID     ( AAEBsxPzpR1LCNUbs3GeP/UYQzT2aXUpiLLYhVp/Wd10
17                pAU= ) ; 1 1 32
18 $TTL 86400      ; 1 day
19 dhcp           A        192.168.1.1
20 ns             A        192.168.1.1
21 server         A        192.168.1.1
22 www            A        192.168.1.1
23 mail           A        192.168.1.1
24
```



```
1 $ORIGIN .
2 $TTL 86400      ; 1 day
3 1.168.192.in-addr.arpa  IN SOA  1.168.192.in-addr.arpa. server.dgavdadaev.net. (
4                                2025113005 ; serial
5                                86400      ; refresh (1 day)
6                                3600       ; retry (1 hour)
7                                604800    ; expire (1 week)
8                                10800     ; minimum (3 hours)
9                                )
10                             NS      1.168.192.in-addr.arpa.
11                             A        192.168.1.1
12                             PTR      server.dgavdadaev.net.
13                             MX 10    mail.dgavdadaev.net.
14 $ORIGIN 1.168.192.in-addr.arpa.
15 1                             PTR      server.dgavdadaev.net.
16                             PTR      ns.dgavdadaev.net.
17                             PTR      dhcp.dgavdadaev.net.
18                             PTR      www.dgavdadaev.net.
19                             PTR      mail.dgavdadaev.net.
20 $TTL 1200      ; 20 minutes
21 30                             PTR      client.dgavdadaev.net.
22                             DHCID    ( AAEBsxPzpR1LCNUbs3GeP/UYQzT2aXUpiLLYhVp/Wd10
23 pAU= ) ; 1 1 32
```

```
Nov 30 10:43:01 server postfix/smtpd[15876]: connect from client.dgavdadaev.net[192.168.1.30]
Nov 30 10:43:01 server postfix/smtpd[15876]: 5A0C720BE081: client=client.dgavdadaev.net[192.168.1.30]
Nov 30 10:43:01 server postfix/cleanup[15880]: 5A0C720BE081: message-id=<20251130104301.583714130A7F@client.dgavdadaev.net>
Nov 30 10:43:01 server postfix/smtpd[15876]: disconnect from client.dgavdadaev.net[192.168.1.30] ehlo=2 starttls=1 mail=1 rcpt=1 data=1 q
uit=1 commands=7
Nov 30 10:43:01 server postfix/qmgr[15696]: 5A0C720BE081: from=<dgavdadaev@client.dgavdadaev.net>, size=561, nrcpt=1 (queue active)
Nov 30 10:43:01 server postfix/local[15881]: 5A0C720BE081: to=<dgavdadaev@dgavdadaev.net>, relay=local, delay=0, delays=0/0/0/0, dsn=2.0.
0, status=sent (delivered to mailbox)
Nov 30 10:43:01 server postfix/qmgr[15696]: 5A0C720BE081: removed
```

Рис. 14: Успешная доставка письма после настройки DNS и Postfix

## Полученное письмо после исправления MX

```
From dgavdadaev@client.dgavdadaev.net Sun Nov 30 10:43:01 2025
Return-Path: <dgavdadaev@client.dgavdadaev.net>
X-Original-To: dgavdadaev@dgavdadaev.net
Delivered-To: dgavdadaev@dgavdadaev.net
Received: from client.dgavdadaev.net (client.dgavdadaev.net [192.168.1.30])
    by server.dgavdadaev.net (Postfix) with ESMTPS id 5A0C720BE081
    for <dgavdadaev@dgavdadaev.net>; Sun, 30 Nov 2025 10:43:01 +0000 (UTC)
Received: by client.dgavdadaev.net (Postfix, from userid 1001)
    id 583714130A7F; Sun, 30 Nov 2025 10:43:01 +0000 (UTC)
Date: Sun, 30 Nov 2025 10:43:01 +0000
To: dgavdadaev@dgavdadaev.net
Subject: test2
User-Agent: s-nail v14.9.24
Message-Id: <20251130104301.583714130A7F@client.dgavdadaev.net>
From: dgavdadaev@client.dgavdadaev.net
```

.

Рис. 15: Полученное письмо test2 после настройки MX

## Итоги

---

- Настроена почтовая система Postfix для локальной сети и доменной доставки
- Реализована отправка писем между клиентом и сервером
- Настроены MX и PTR-записи
- Проверена доставка писем и работа очереди Postfix
- Добавлена автоматизация конфигурации через Vagrant provisioning