

## ABSTRACT

Title of dissertation: Direct measurement of a Feshbach resonance with imaging  
and measuring topology of BECs in a synthetic dimensions

Dina Genkina  
Doctor of Philosophy, 2018

Dissertation directed by: Professor Ian Spielman  
Department of Physics

Direct measurement of a Feshbach resonance with imaging of s-wave  
scattering  
and measuring topology of BECs in a synthetic dimensions lattice

by

Dina Genkina

Dissertation submitted to the Faculty of the Graduate School of the  
University of Maryland, College Park in partial fulfillment  
of the requirements for the degree of  
Doctor of Philosophy  
2018

Advisory Committee:  
Professor Ian Spielman, Chair/Advisor

© Copyright by  
Dina Genkina  
2018



## Chapter 2: Absorption imaging in the presence of strong recoil induced detuning

### 2.1 Near-resonant atom-light interaction

In this section, we will assume the atom can be treated as a two-level system: one with a ground and excited atomic state, with an energy difference of energy difference  $\hbar\omega_0$ . When such an atom, starting in the ground state, is illuminated by a laser beam with frequency  $\hbar\omega_L$ , there are three kinds of transitions that occur: during absorption the atom absorbs a photon from the laser and goes from the ground to the excited state; during stimulated emission, the atom emits a photon into the field of the laser beam and jump from the excited to the ground state; during spontaneous emission, the atom decays to the ground state from the excited state with no help from the laser, emitting into a random vacuum mode. Stimulated emission results in coherent light co-propagating with the laser beam, while spontaneous emission results in light scattering incoherently in any direction. The rate of spontaneous emission from an excited state is given by the natural transition linewidth of the transition  $\Gamma$ .

On timescales short compared to  $1/\Gamma$ , spontaneous emission can be ignored, and an atom undergoes coherent Rabi oscillations between the ground and excited states via cycles of absorption and stimulated emission [1]. Taking  $c_g$  and  $c_e$  to be the time-dependent coefficients multiplying the eigenstate wavefunctions of the ground and excited state respectively, and assuming the atom starts in the ground

state  $c_g(t = 0) = 1$ , the excited state population is given by

$$c_e(t) = -i \frac{\Omega}{\Omega'} \sin\left(\frac{\Omega' t}{2}\right) e^{-i\delta t/2}, \quad (2.1)$$

where  $\Omega$  is the Rabi frequency given by  $\Omega^2 = \frac{\Gamma \lambda_L^3}{h(2\pi)^3} I$ , with  $\lambda_L$  as the laser wavelength,  $h$  as Plank's constant and  $I$  as the laser intensity,  $\Omega' = \sqrt{\Omega^2 + \delta^2}$  is the generalized Rabi frequency and  $\delta = \omega_0 - \omega_L$  is the detuning of the laser from atomic resonance.

In the regime where spontaneous emission cannot be ignored, Rabi oscillations of each individual atom are intermittently interrupted by decay to the ground state. Averaging over an atomic ensemble, on the time scale of a single Rabi oscillation the overall excited state population reaches a steady state, and the rate of spontaneous emission becomes constant. Since during spontaneous emission the ejected photon can go into any vacuum mode, this process can be thought of as the scattering of photons by the atoms. This scattering rate is given by [1]

$$\gamma_{\text{sc}} = \frac{\Gamma}{2} \frac{I/I_{\text{sat}}}{1 + 4(\delta/\Gamma)^2 + I/I_{\text{sat}}}, \quad (2.2)$$

where  $I_{\text{sat}}$  is the saturation intensity. This is the intensity at which the timescale of spontaneous emission matches the Rabi oscillation rate, reducing the capacity for absorption of extra light.

## 2.2 Absorption imaging

Absorption imaging takes advantage of the on-resonant interaction described in the previous section. An on or near-resonant laser beam ( $\delta/\Gamma \ll 1$ ) is shined at the atoms, and the absorbed light acts to create a shadow in the shape of the atoms in the laser beam. This beam with the shadow is then imaged on a camera, in our case a CCD, as depicted in Figure 1a (top). This is called the atom image,




Figure 1: Absorption imaging. (a) Near resonant probe light illuminates the atoms, and the transmitted light (containing a shadow of the atoms) is imaged on the camera. A second image taken with no atoms provides a reference. (b) The probe beam is partially absorbed as it traverses the cloud, and the intensity seen by atoms further along the imaging direction  $e_z$  is lowered. (c) An atomic cloud illuminated by a probe light field absorbs photons from the probe and re-emits them in all directions. This process results in a net acceleration of the cloud in the direction of the probe light as well as diffusive spreading in the transverse directions.

and the intensity distribution over the camera is denoted by  $I_f(x, y)$ , where the subscript f stands for final - the intensity after the light has encountered the atoms. To quantify the 'shadowed out' intensity, after the atoms have left the trap the same laser intensity is shined directly at the camera, as in Figure 1a (bottom). This is called the probe image, and the intensity distribution over the camera is denoted by  $I_0(x, y)$ , where the subscript 0 indicated initial - the intensity before the light had encountered the atoms.

To recover the atom number distribution encountered by the light, consider an atomic cloud with 3D density  $\rho(x, y, z)$ . Since we can only obtain 2D information from the camera, we can only hope to recover a 2D atomic column density  $n(x, y) = \int \rho(x, y, z) dz$ . Focusing in on a single pixel of the camera, we can consider a single value of  $I_0$  and  $I_f$  to recover a local  $n$ . As the laser light propagates through the atomic cloud, the intensity of the light will diminish due to absorption. This

absorption as a function of propagation direction  $z$  can be expressed using the scattering rate equation Eq. 2.2 as the number of photons scattered by the atoms (proportional to the atomic density times the scattering rate) times the photon energy  $\hbar\omega_L$ :

$$\frac{d}{dz} \frac{I(z)}{I_{\text{sat}}} = -\hbar\omega_L \rho(z) \gamma_{sc}(z) = -\rho(z) \sigma_0 \frac{I(z)/I_{\text{sat}}}{1 + 4\delta^2/\Gamma^2 + I(z)/I_{\text{sat}}}, \quad (2.3)$$

where the resonant scattering cross section is  $\sigma_0 = 3\lambda_0^2/2\pi$ , and  $\lambda_0$  is the wavelength associated with atomic resonance.

Integrating both sides of Eq. 2.3, we obtain

$$\sigma_0 n = (1 + 4\delta^2/\Gamma^2) \ln(I_0/I_f) + (I_0 - I_f)/I_{\text{sat}}. \quad (2.4)$$

The quantity  $OD = \ln(I_0/I_f)$  is called the optical depth of the cloud. When the probe intensity  $I_0$  is much smaller than the saturation intensity, the second term in Eq. 2.4 becomes negligible. Assuming further that the probe light is on resonance,  $\delta = 0$ , the atomic column density becomes simply  $\sigma_0 n = OD$ . Figure 1b shows a Gaussian atomic density distribution (top) and the resulting probe intensity as a function of position in the cloud (bottom). The intensity drops from its initial to final value gradually as it traverses the cloud.

However, there is an important effect that the above equations do not account for. Namely, as the atoms absorb light from the probe beam, they also get a momentum kick equal to the momentum of a photon during each collision  $\hbar k_r = h/\lambda_L$  in the direction of propagation. It is true that the absorbed photon will then be re-emitted by the atom, inducing a loss of momentum, but since this happens through the process of spontaneous emission into a random vacuum mode, the average momentum kick acquired this way over many re-emissions will average to zero. On average, each photon absorbed will induce a change in velocity of the atom of  $v_r = \hbar k_r/m$ ,



where  $m$  is the atomic mass, as depicted in Fig. 1c. As the velocity of the atom changes, due to the Doppler effect, the apparent laser frequency will change as well. Therefore, even if the laser light is exactly on-resonant for a stationary atom, it will become off-resonant for longer imaging times, and Eq. 2.3 will acquire a time dependence. For most experiments, this effect is small and can be neglected. However, if the imaging time becomes of order a recoil time  $t_r$ , a time after which the recoil-induced detuning  $\delta$  becomes of order  $\Gamma$ , this effect becomes significant. We explore this effect in the following sections.

## 2.3 Recoil-induced detuning

After absorbing a number of photons  $N$ , an atom will obtain a recoil velocity of  $Nv_r$ . Via the Doppler effect, this will result in a detuning  $\delta = Nk_r v_r$ . This detuning will increase as more atoms are absorbed, and therefore depend on time, making the absorbed intensity also time dependent. We can generalize Eq. 2.3 to include a time dependence on the detuning term and therefore also the intensity:

$$\frac{d}{dz} \frac{I(z, t)}{I_{\text{sat}}} = -\rho(z)\sigma_0 \frac{I(z, t)/I_{\text{sat}}}{1 + 4\delta(z, t)^2/\Gamma^2 + I(z, t)/I_{\text{sat}}}. \quad (2.5)$$

The number of photons absorbed per atom will depend on the intensity lost, up until the current time, at that location. The detuning will therefore be proportional to the total number of photons lost up until time  $t$  at that location, proportional to the absorbed intensity divided by the single photon energy  $\hbar\omega_L$ , divided by the number of atoms that participated in the absorption  $\rho(z)$  times the detuning  $k_r v_r$ :

$$\delta(t, z) = \frac{k_r v_r}{\hbar\omega_L \rho(z)} \int_0^t \frac{dI(z, \tau)}{dz} d\tau. \quad (2.6)$$

These equations are interdependent, and cannot be in general solved analytically.

Figure 2a shows the velocity and detuning as a function of position in space for three different imaging times, calculated numerically. All calculations in this chapter were done for a cloud of  $^{40}\text{K}$  atoms, as that is relevant to our experiment described in the next chapter. The resonant wavelength is  $\lambda_L = 770.11$  nm, the natural linewidth of the transition is  $\Gamma = 6.035$  MHz, the resulting saturation intensity and recoil velocity are  $I_{\text{sat}} = 17.5$  W/m<sup>2</sup> and  $v_r = 0.01297$  m/s.

## 2.4 Perturbative treatment

We can treat these equations perturbatively in time. To first order, we can set the detuning in Eq. 2.5 to  $\delta = 0$ , assume  $I(z)$  is time independent, and plug that into Eq. 2.6 to obtain

$$\delta(t, z) = \frac{k_r v_r}{\hbar \omega_L \rho(z)} \int_0^t -\rho(z) \sigma_0 \frac{I(z)}{1 + I(z)/I_{\text{sat}}} d\tau \quad (2.7)$$

$$= \frac{k_r v_r \sigma_0}{\hbar \omega_L} \frac{I(z)}{1 + I/I_{\text{sat}}} t. \quad (2.8)$$

This can then be recursively plugged into Eq. 2.5 to obtain

$$\frac{d}{dz} \frac{I(z, t)}{I_{\text{sat}}} = -\rho(z) \sigma_0 \frac{I(z, t)/I_{\text{sat}}}{1 + 4 \left( \frac{k_r v_r \sigma_0}{\hbar \omega_L \Gamma} \frac{I(z)}{1 + I/I_{\text{sat}}} \right)^2 t^2 + I(z, t)/I_{\text{sat}}}. \quad (2.9)$$

Integrating both sides of the above equation, we obtain a perturbative equation to second order in time [2]:

$$\sigma_0 n = \ln(I_0/I_f) + \frac{I_0 - I_f}{I_{\text{sat}}} + \frac{(k_r v_r t)^2}{3} \left( \frac{I_{\text{sat}}}{I_f + I_{\text{sat}}} - \frac{I_{\text{sat}}}{I_0 + I_{\text{sat}}} + \ln \left( \frac{I_f + I_{\text{sat}}}{I_0 + I_{\text{sat}}} \right) \right). \quad (2.10)$$

In Fig. 2b, we examine for what imaging times the above perturbative equation, as well as the model that completely ignores recoil induced detuning, is valid. We do this by performing numerical simulations to extract a value for the final intensity  $I_f$




Figure 2: (a) Dependence of velocity and detuning on position simulated for  $^{40}\text{K}$  at three different imaging times and a probe intensity  $I_0 = 0.8I_{\text{sat}}$ . (b) Column densities deduced from optical depths obtained from recoil detuning corrected simulation of on-resonant imaging of  $^{40}\text{K}$  atoms at probe intensity  $I_0 = 0.8I_{\text{sat}}$ . The blue line is the input column density  $\sigma_0 n = 1.6$ . The green line is the high probe intensity corrected column density given by Eq. (2.4). The red line is the column density as expanded to second order in time, Eq. (2.10).

and using Eq. 2.4 and Eq. 2.10 to extract values  $\sigma_0 n$  that would be deduced from experiment. We find that within the recoil time, both analytic expressions start to differ from the true atomic column density by over 5%, and the perturbative model of Eq. 2.10 quickly diverges thereafter.

In the following sections, we describe two versions of numerical simulations that we have performed in order to appropriately extract atomic column densities from experimental data.

## 2.5 Stationary atom model

In order to numerically simulate the imaging process, we assume a Gaussian distribution of atoms along the propagation direction,  $\rho(z) = n/\sqrt{2\pi}w e^{-z^2/(2w^2)}$  –

$z^2/2w^2$ ). The dependence of the result on the choice of cloud width  $w$  is discussed in the next chapter. We divide the cloud into small bins along  $z$ . For the initial version of the simulation, the atoms were assumed to stay within the same bins for the entire duration of the imaging pulse, i.e. the cloud shape remained constant. We then used Eqs. 2.5-2.6 to numerically propagate the probe intensity and detuning as a function of both time and space. The algorithm used is detailed by Alg. 1.

---

**Algorithm 1** Stationary atom model

---

```

 $I[n = 0, t] = I_0$  { $n$  is the bin index,  $t$  is the time index,  $I$  is in units of  $I_{\text{sat}}$ }
 $\delta[n, t = 0] = 0$  {light initially resonant,  $\delta$  in units of  $\Gamma/2$ }
 $H_f = 0$  {Radiant fluence seen by camera after passing through cloud}
for  $t = 0$  to  $t_f$  do {loop over time steps}
  for  $n = 1$  to  $N$  do {loop over bins,  $N$  is total bin number}
     $A = \sigma_0 \rho[n] dz$  { $dz$  is the size of spatial step}
     $B = v_r dt / (\hbar c \rho[n])$  { $dt$  is the size of the time step}
     $I[n, t] = I[n - 1, t] - AI[n - 1, t] / (1 + \delta[n, t - 1]^2 + I[n - 1, t])$  {Eq. (2.5)}
     $\delta[n, t] = \delta[n, t - 1] + B (I[n - 1, t] - I[n, t])$  {Eq. (2.6)}
  end for
   $H_f = H_f + I[N, t] dt$  {collecting total fluence seen by the camera}
end for
 $OD^{\text{sim1}} = -\ln(H_f / I_0 t_f)$ 

```

---

We call the optical depth obtained in this way  $OD^{\text{sim1}}$ , to distinguish it from the simulated optical depth via the method described in the next section.

The validity of this model can be checked by considering limits where the equations are analytically solvable. For short imaging times, the recoil-induced detuning should not contribute to the optical depth, and therefore Eq. 2.4 should become exact. This is seen in Fig. 3a, where the imaging pulse is only 3  $\mu\text{s}$  long and the simulated optical depth (blue dots) agrees with that given by Eq. 2.4 for all intensity regimes.

Even at longer imaging times, the problem can be analytically solved for limits of both high and low intensity compared to the saturation intensity. At intensities  $I \gg I_{\text{sat}}$ , even far detuned atoms will scatter light at their maximum, and we can assume  $\delta^2/\Gamma^2 \ll I/I_{\text{sat}}$ , reducing back to Eq. 2.4. At extremely low intensities,




Figure 3: Optical depth as a function of probe intensity as predicted by the simulation (blue symbols) and by Eq. (2.4) (green curves), for three different imaging times. As expected, the predictions agree in both the high and low intensity limits, and differ for probe intensities comparable to the saturation intensity and longer imaging times.

atoms will scatter very little light and the detuning  $\delta^2/\Gamma^2 \ll 1$ , again reducing back to Eq. 2.4. As seen in Fig. 3 b,c the simulation agrees with the analytic Eq. 2.4 in the limit of both high and low intensities. But, as the imaging time increases, the disagreement due to recoil induced detuning grows.

The simulation allows us to extract both the intensity and the detuning as a function of both time and position. We can use this information to infer the velocity and therefore the displacement of the atoms during the imaging pulse, and check if our assumption that the atoms stay in their original 'bins' during the image pulse is valid. Figure 4a shows the position, deduced by integrating the recoil-induced velocity, as a function of time of the first, middle, and last spatial 'bin' for a probe intensity slightly above saturation,  $I = 1.2I_{\text{sat}}$ . As seen in the figure, not only do the atoms move beyond their 'bins', but also at long imaging times the first atoms (which have absorbed the most light) overtake the last ones. Therefore, the atomic cloud does not maintain shape during the imaging pulse, and our initial assumption




Figure 4: (a) Position of atoms as a function of imaging time for atoms in the first (solid green), middle (dashed red), and last (dotted blue) bins of the simulated density distribution for an initial cloud  $50 \mu\text{m}$  in extent. The probe intensity used in this calculation was  $1.2 I_{\text{sat}}$ , and the column density was  $\sigma_0 n = 1.6$ . (b) The velocity of a single composite atom as a function of probe intensity for various imaging times. Simulation data (dots) and numerical solutions of Eq. (2.11) (lines) are in agreement.

is invalid.

## 2.6 Traveling atom model

To model the recoil-induced detuning effect during the imaging pulse taking into account the potentially significant spatial displacement of the atoms, we performed a second version of our simulation. In this version, we clumped some number of atoms  $N_{\text{ca}}$  into a single composite atom, and then tracked the detuning, velocity and position of each composite atom as a function of imaging time. Tracking individual atoms would be computationally inaccessible for reasonable cloud sizes. The algorithm used is given by Alg. 2.

To check the validity of this version of the simulation, we check the velocity

---

**Algorithm 2** Travelling atom model

---

$z[n] = z_0, \delta[n] = 0$  {initialize position and detuning for each composite atom, labeled by index  $n$ }  
 $O[i] = n$  {make a list of composite atom indexes, ordered by position}  
 $I[n = 0, t] = I_0$  {  $t$  is the time index,  $I$  is in units of  $I_{\text{sat}}$ }  
 $H_f = 0$  {Radiant fluence seen by camera after passing through cloud}  
**for**  $t = 0$  to  $t_f$  **do** {loop over time steps}  
    **for**  $i = 1$  to  $N$  **do** {loop over superatoms}  
         $n = O[i]$  {apply probe intensity to composite atoms in order of appearance}  
         $A = \sigma_0 N_{sa} dz$  {dz is length over which atoms were grouped into single composite atom}  
         $B = v_r dt / (\hbar c N_{sa})$  {dt is the time step}  
         $I[n, t] = I[n - 1, t] - AI[n - 1, t] / (1 + \delta[n]^2 + I[n - 1, t])$  {Eq. (2.5)}  
         $\delta[n] += B (I[n - 1, t] - I[n, t])$  {Eq. (2.6), detuning in units of  $\Gamma/2$ }  
         $z[n] += dt \Gamma \delta / 2k$  { $k$  is the wavenumber,  $\Gamma \delta / 2k$  is the velocity at  $\delta$  detuning}  
    **end for**  
     $O[i] = \text{sort}(n, \text{key} = z[n])$  {sort composite atom indexes by current position}  
     $H_f H_f + I[N, t] dt$  {collecting total fluence seen by the camera}  
**end for**  
 $OD^{\text{sim2}} = -\ln(H_f / I_0 t_f)$

---

of a composite atom as a function of time in an analytically solvable limit. In this case, we take the limit of a single composite atom, such that the intensity seen by the composite atom becomes time independent. This simplifies Eqs. 2.5 and 2.6 to only carry time dependence in the detuning term, and we can then plug Eq. 2.5 into Eq. 2.6 and differentiate both sides with respect to time to obtain

$$\frac{d\delta(t)}{dt} = \frac{\Gamma k_r v_r}{2} \frac{I/I_{\text{sat}}}{1 + 4\delta^2/\Gamma^2 + I/I_{\text{sat}}}. \quad (2.11)$$

Equation (2.11) can be solved numerically, and is in agreement with our simulation, as seen in Fig. 4(b).

We then used this version of the simulation to look at the motion of composite atoms as a function of imaging time in phase space (ie, velocity and position). Some examples of this motion can be seen in Fig. 5. As seen in the figure, the atomic cloud is significantly distorted during the imaging pulse and the atoms perform some

crazy acrobatics.

It remains to check how the atoms' acrobatics affect the resulting optical depth, ie the attenuation of the probe beam. To do this, we compare the optical depths generated by our stationary atom model,  $OD^{\text{sim1}}$ , and by our travelling atom model,  $OD^{\text{sim2}}$ . The results of this comparison are seen in Fig. 6(a). As seen from the figure, the optical depths predicted by the two versions of the simulation are negligibly small -  $|OD^{\text{sim1}} - OD^{\text{sim2}}| / OD^{\text{sim1}} \leq 0.005$ . We also checked the effect of having different initial distributions of atoms in space by varying the initial function  $\rho(z)$  and keeping the total atom number constant. We found the effect of this to be negligible as well. Therefore, to infer atomic column densities from observed optical depths, it is sufficient to use the stationary atom model.

## 2.7 Calibration of saturation intensity

Saturation intensity is an intrinsic property of the atom, so the idea of calibrating it may be confusing. However, there are several experimental parameters that may influence exactly what value of  $I_{\text{sat}}$  is appropriate to use in Eq. 2.5 and 2.6, such as losses in the imaging system and polarization of the probe beam. In addition, we have no direct experimental access to the total radiant fluence (time integral of intensity) seen by the camera. Instead, the light hitting the charge-coupled device (CCD) camera triggers some number of photoelectrons to be registered. The proportionality between the number of photons hitting the camera and the number of photoelectrons it triggers is called the quantum efficiency  $q_e$  of the camera. The number of these photoelectrons, after some electronic gain and noise introduced during the readout process, is then read out as a number of 'counts' registered on each pixel. The camera-dependent factors influencing how the number of counts depends on the number of incoming photons can be convolved with the experimental factors of probe polarization and optical loss into a single calibration of the effective







Figure 5: Phase space evolution of an atomic cloud exposed to probe light with intensity  $\tilde{I}_0 = 1.2$ . We defined  $\Delta v = v - \langle v(t) \rangle$  and  $\Delta z = z - \langle z(t) \rangle$ , subtracting out the center of mass position and velocity of the cloud. The column density  $\sigma_0 n$  is 1.6, and the initial cloud is a Gaussian with a width of 10  $\mu\text{m}$  in (a) and 1  $\mu\text{m}$  in (b). The center of mass velocities  $\langle v \rangle$  are (0, 3.41, 5.26, 6.52, 7.50, 8.32) m/s sequentially, and are the same for both initial cloud widths.




Figure 6: (a) Top. Optical depth as a function of probe intensity for an imaging time  $t = 100 \mu\text{s}$ .  $OD^{(1)}$  and  $OD^{(2)}$  are optical depths predicted from a given column density by Eq. (2.4) and (2.10) respectively. The two versions of simulated optical depth,  $OD^{\text{sim}1}$  (green curve) and  $OD^{\text{sim}2}$  (green dots) are plotted. Bottom. The fractional difference between two versions of the simulated  $OD$ ,  $|OD^{\text{sim}1} - OD^{\text{sim}2}|/OD^{\text{sim}1}$ . (b) The optical depth as a function of probe intensity for three imaging times:  $t = 40 \mu\text{s}$  (cyan),  $t = 75 \mu\text{s}$  (magenta),  $t = 100 \mu\text{s}$  (red). The dots represent experimental data and the lines represent the best fit of simulated data. The optimal fit parameters pictured are a  $\sigma_0 n$  of 1.627(5) and saturation intensity of 29(7) counts/ $\mu\text{s}$ .

saturation intensity in units of 'counts' output by the camera per unit time.

To calibrate this effective  $I_{\text{sat}}$  in camera counts per unit time, we absorption imaged our cloud of  $^{40}\text{K}$  atoms for a range of probe intensities for three different values of imaging time: 40  $\mu\text{s}$ , 100  $\mu\text{s}$ , and 200  $\mu\text{s}$ . We select a small region in the center of the cloud, where we can assume the atomic column density  $\sigma_0 n$ , and the initial probe intensity  $I_0$  to be roughly constant. We then average the values of  $I_0$  and  $I_f$  over this region and plot the final intensity  $I_f$  as a function of  $I_0$ . We then used the optical depth predicted by our simulation  $OD^{\text{sim}}$  and used that to simultaneously fit the three curves with  $I_{\text{sat}}$  and  $\sigma_0 n$  as fit parameters, as shown in Fig. 6(b). As can be seen from the figure, this procedure not only allows us to read off  $I_{\text{sat}}$  in units of camera counts per  $\mu\text{s}$ , but also shows that our simulation accurately reproduces the differences in  $OD$  dependenc on imaging time.

## 2.8 SNR optimization

Using the simulations described in the previous sections, we can create a lookup table of atomic column densities as a function of initial and final probe intensities  $I_0$  and  $I_f$  for any given imaging time. This lookup table can be then used to interpret experimental data and obtain the atom number in regimes where the recoil-induced detuning is significant. This procedure can also be used to propagate photon shot noise into uncertainty in measured atom number.

We consider Poisson distributed photon shot noise, converting into shot noise on photoelectrons triggered inside the CCD. The standard deviation will then be proportional to  $q_e \sqrt{N_p}$ , where  $q_e$  is the quantum efficiency of the camera and  $N_p$  is the photon number. This uncertainty can be then propagated via the lookup table into uncertainty on the measured atomic column density  $\delta_{\sigma_0 n}$ . The signal to noise ratio (SNR) can then be expressed as  $\sigma_0 n / \delta_{\sigma_0 n}$ .

We study the SNR as a function of imaging time and initial probe intensity

for a few different atomic column densities. Some representative data is shown in Fig. 7. As seen in Fig. 7(a), for a wide range of atomic column densities, extending the imaging time beyond 40  $\mu\text{s}$  no longer yields significant improvements in SNR. There is, however, a factor of 1.5 improvement between using an imaging time of 10  $\mu\text{s}$ , where the simple model given by Eq. 2.4 is appropriate, and 40  $\mu\text{s}$ . Therefore, there are significant gains that can be made by going to longer imaging times and making use of the simulated lookup table.

This simulation allowed us to interpret experimental data. For a given imaging time, we created a look-up table of predicted optical depth as a function of probe intensity and atomic column density. We then found the observed optical depth on this table, with the given probe intensity, and inferred the atomic density. The uncertainty in the measured intensities can be propagated through this procedure, and we established optimal imaging parameters to maximize the SNR of this detection scheme. Figure 7(b) illustrates that the optimal initial probe intensity is different for different atom numbers. For low atom numbers,  $\sigma_0 n \approx 0.1$ , a probe intensity of  $I_0 \approx 0.6 I_{\text{sat}}$  is best.




Figure 7: SNR for three different column densities after correcting for recoil induced detuning. (a) SNR as a function of imaging time for a probe intensity of  $I_0 = 5.0 I_{\text{sat}}$  and (b) SNR as a function of probe intensity for an imaging time of  $50 \mu\text{s}$ .

## Bibliography

- [1] H.J. Metcalf and P. van der Straten. *Laser Cooling and Trapping*. Graduate Texts in Contemporary Physics. Springer New York, 1999.
- [2] Lindsey J. LeBlanc. *Exploring many-body physics with ultracold atoms*. PhD thesis, University of Toronto, 2011.
- [3] B. K. Stuhl, H.-I. Lu, L. M. Ayccock, D. Genkina, and I. B. Spielman. Visualizing edge states with an atomic bose gas in the quantum hall regime. *Science*, 349(6255):1514–, Sep 2015.