

Display Direction	Size	Product model	Product description	Resolution ratio	LC Dangle of view	A A distinguish	Module external dimensions	Thickness	Light Strip	Luminance	Interface	Working temperature
Display in landscape	0.5	HG005WS003	0.5 PMOLED I2C interface	48*88	White	6.124*11.244	9*27.6	1.227	PMOLED	200	I2C-14-pin FPC Soldering	-40 ° ~70 °
		HG005WS003-V1	0.5 PMOLED I2C interface	48*88	White	6.124*11.244	9*27.6	1.227	PMOLED	200	I2C-14-PIN FPC Soldering	-40 ° ~70 °
	0.7	HG007FH002	0.71 OLED MIPI/IIC Interface	1920*1080	ALL	9.0087*15.8139	11.88*21.031/18*28	1.25/3.25	OLED	300	MIPI/IIC 48/50PIN TFT	-40 ° ~85 °
	0.96	HG010QS004	0.96 TFT SPI Interface	80*160	ALL	10.8*21.7	14.04*27.95	1.75	1S1P	400	SPI-4 13-pin FPC soldering	-20 ° ~70 °
		HG010SQ005	0.96 PMOLED SPI/IIC interface	64*128	White	10.86*21.74	14*28	1.26	PMOLED	160	SPI-4/IIC 13PIN FPC	-40 ° ~70 °
	1.45	HG015QV007	1.45 TFT SPI Interface	172*320	ALL	17.39*32.35	19.39*36.28	1.5	1S3P	TBD	SPI-4 8PIN FPC	-10 ° ~60 °
	1.7	HG017QV002	1.69 TFT SPI Interface	240*280	ALL	27.972*32.634	30.07*37.43	1.68	1S3P	300	SPI-4 12PIN FPC	-20 ° ~70 °
	1.8	HG018QQ002 (36.75mm)	1.8 TFT SPI Interface	128*160	12 o'clock	28.03*35.04	34*45.83	2.4	1S2P	300	SPI-4 14PIN FPC	-20 ° ~70 °
		HG018QQ002-V1 (50mm)	1.8 TFT SPI Interface	128*160	12 o'clock	28.03*35.04	34*45.83	2.4	1S2P	300	SPI-4 14PIN FPC	-20 ° ~70 °
		HG018QV002	1.83 TFT SPI Interface	240*284	ALL	29.52*34.932	31.395*39.231	2	1S3P	350	SPI-4 12PIN FPC	-20 ° ~70 °
		HG018NH005	1.78 AMOLED QSPI interface	368*448	ALL	28.7*34.94	30.6*37.99	0.65	AMOLED	350	QSPI-4 24PIN BTB	-20 ° ~70 °
	1.9	HG019QQ002	1.92 PMOLED MCU/SPI3-4/I2C interface	128*160	White	28.908*39.34	32.9*46.55	1.22	PMOLED	350	MCU/SPI-4/3/I2C 31PIN FPC	-40 ° ~70 °
		HG019WQ002	1.91 AMOLED MIPI interface	240*536	ALL	19.8*44.22	22.4*51.32	0.753	AMOLED	350	MIPI-1 40PIN BTB	-40 ° ~70 °
	2	HG020QV001 (Semipermeable/Refle)	2.0 TFT QVGA RGB/MCU/SPI interface	240*320	ALL	30.60*40.80	35.8*52.1	2.65	1S4P	260	RGB/MCU/SPI 45PIN FPC	-20 ° ~70 °
		HG020QV003	2.0 TFT QVGA MCU interface	240*320	ALL	30.6*40.8	35.95*49.2	2.22	1S3P	TBD	MCU-16 28PIN FPC	-20 ° ~70 °
		HG020QV006	2.0 TFT QVGA SPI interface	240*320	ALL	30.6*40.8	35.7*51.2	2.4	1S4P	360	SPI-4 14PIN FPC	-20 ° ~70 °
		HG020QV007-V1.2 (PCB)	2.0 TFT QVGA SPI interface + board	240*320	ALL	30.6*40.8	37.1*62	6	1S4P	400	SPI-4 (8-pin)	-20 ° ~70 °
		HG024QV021 (Semipermeable/Refle)	2.4 TFT QVGA RGB/MCU/SPI interface	240*320	ALL	36.72*48.96	42.92*60.26	2.45	6S1P	360	RGB/MCU/SPI 45PIN FPC	-20 ° ~70 °
		HG024QV023	2.4 TFT QVGA SPI interface	240*320	ALL	36.72*48.96	41.32*57.56	2.47	1S4P	TBD	SPI-4 14PIN FPC	-20 ° ~70 °
		HG024QV025 (Semipermeable/Refle)	2.4 TFT QVGA RGB/MCU/SPI interface	240*320	3 o'clock	36.72*48.96	42.92*60.26	2.46	6S1P	350	RGB/MCU/SPI 45PIN FPC	-20 ° ~70 °
		HG024QG002	2.4 AMOLED MIPI/SPI/MUC interface	450*600	ALL	36.72*48.96	38.72*51.56	0.9	AMOLED	800	MIPI-1/SPI-4/MUC 45PIN ZIF	-40 ° ~70 °
	2.5	HG024QG003	2.4 AMOLED MIPI/SPI/MUC interface	450*600	ALL	36.72*48.96	38.68*51.56	0.73	AMOLED	850	MIPI-1/SPI-4/MUC 51PIN ZIF	-40 ° ~70 °
		HG025HV006	2.5 TFT HVGA MCU interface	272*480	ALL	30.19*53.28	33.89*60.32	2.08	5S1P	300	MCU-16 33PIN FPC	-20 ° ~70 °
	2.8	HG025QV002 (Long-Strip Screen)	2.5 TFT HVGA SPI interface	100*310	ALL	18*55.8	21.1*63.6	1.64	1S4P	300	SPI-4 12PIN FPC	-20 ° ~70 °
		HG028QV002	2.8 TFT QVGA RGB/MCU/SPI interface	240*320	12 o'clock	43.20*57.60	46*64.65	2.5	1S4P	TBD	RGB/MCU/SPI 40PIN FPC	-20 ° ~70 °
	2.9	HG028QV008	2.8 TFT QVGA SPI interface	240*320	ALL	43.20*57.60	50*69.2	2.3	1S4P	TBD	SPI-4 18PIN FPC	-20 ° ~70 °
		HG028WQ003	2.8 TFT 240*400 SPI interface	240*400	12 o'clock	36.72*61.2	43*72.3	2.4	1S4P	180	SPI-4 25PIN FPC	-20 ° ~70 °
	3	HG029SC002 (Long-Strip Screen)	2.89 TFT 142*428 SPI interface	142*428	ALL	21.28*64.14	24.38*69.43	1.9	1S4P	350	SPI-4 24PIN FPC	-20 ° ~70 °
		HG030HA004	3.0 TFT 268*800 MIPI interface	268*800	ALL	24.12*72	26.52*78.2	1.58	6S1P	TBD	MIPI-1 31PIN FPC	-20 ° ~70 °
		HG030FW006	2.95 TFT nHD MIPI/SPI/RGB interface	360*640	ALL	36.72*65.28	40.84*73.17	2.05	6S1P	400	MIPI-2/SPI/RGB 40PIN FPC	-20 ° ~70 °
		HG030FW007	2.95 TFT nHD MIPI/RGB interface	360*640	ALL	36.72*65.28	43.04*74.91	2.35	6S1P	500	MIPI-2/RGB565 40PIN FPC	-20 ° ~70 °
		HG030FH006	2.95 AMOLED MIPI interface	1080*1200	ALL	50.112*55.68	52.912*62.58	0.653	AMOLED	300	MIPI-4 39PIN FPC	-40 ° ~70 °
	3.2	HG032QV002	3.2 TFT QVGA RGB/MCU/SPI interface	240*320	ALL	48.6*64.8	55.04*77.50	2.5	6S1P	TBD	RGB/MCU/SPI 40PIN FPC	-20 ° ~70 °
	3.5	HG035HV002	3.5 TFT HVGA MCU/SPI interface	320*480	12 o'clock	48.96*73.44	54.50*83	2.3	1S6P	TBD	MCU/SPI-4 40PIN FPC	-10 ° ~60 °
		HG035HV004	3.5 TFT HVGA MIPI/MCU/SPI interface	320*480	12 o'clock	48.96*73.44	54.50*83	2.35	1S6P	TBD	MIPI/MCU/SPI 40PIN FPC	-20 ° ~70 °
		HG035HV006	3.5 TFT HVGA MIPI interface	320*480	ALL	48.96*73.44	54.50*83	2.3	1S6P	TBD	MIPI-1 14PIN FPC	-20 ° ~70 °
		HG035HV007	3.5 TFT HVGA SPI interface	320*480	12 o'clock	48.96*73.44	54.5*83	2.3	1S6P	700	SPI-4 10PIN FPC	-10 ° ~60 °
		HG035HV008	3.5 TFT HVGA MCU interface	320*480	ALL	48.96*73.44	54.5*83	2.25	1S6P	300	MCU-8 24PIN FPC	-20 ° ~70 °
		HG035HV009	3.5 TFT HVGA MCU interface	320*480	12 o'clock	48.96*73.44	54.5*83	2.2	1S6P	250	MCU 30PIN FPC	-20 ° ~70 °
		HG035HV010	3.5 TFT HVGA SPI interface	320*480	ALL	48.96*73.44	54.5*83	2.25	1S6P	300	SPI-4 10PIN FPC	-20 ° ~70 °
		HG035HV011	3.5 TFT HVGA MIPI interface	320*480	ALL	48.96*73.44	54.5*83	2.2	1S6P	TBD	MIPI-2 24PIN FPC	-20 ° ~70 °
	3.9	HG039SX003	3.92 AMOLED 1080*1240 MIPI interface	1080*1240	ALL	65.448*75.114	67.25*79.87	0.8	AMOLED	500	MIPI-4 38PIN BTB	-40 ° ~70 °
	4	HG040WV006	3.97 TFT WVGA MIPI interface	480*800	ALL	51.84*86.40	57.14*96.85	2.1	8S1P	350	MIPI-2 25PIN FPC	-20 ° ~70 °
		HG040QH005	4.0 TFT 540*1168 MIPI interface	540*1168	ALL	41.99*91.1	43.8*95.4	1.36	5S2P	TBD	MIPI-3 30PIN BTB	-20 ° ~60 °
	4.3	HG043WV009	4.3 TFT WVGA RGB/SPI interface	480*800	ALL	56.16*93.6	60.86*102.57	2.62	5S2P	360	RGB/SPI 50PIN FPC	-20 ° ~70 °
		HG043WV025	4.3 TFT WVGA MIPI interface	480*800	ALL	56.16*93.6	60.86*102.57	2.7	5S2P	500	MIPI-2 30PIN BTB	-20 ° ~70 °
	4.7	HG047HD002	4.7 TFT HD MIPI interface	720*1280	ALL	58.1*103.3	61.1*111.15	1.52	5S2P	300	MIPI-4 25PIN FPC	-20 ° ~70 °
	5	HG050HD012	4.99 TFT HD MIPI interface	720*1280	ALL	62.10*110.40	65.3*119.3	1.7	6S2P	450	MIPI-4 25PIN FPC	-20 ° ~70 °
		HG050HD026	4.99 TFT HD MIPI interface	720*1280	ALL	62.10*110.40	65.3*119.3	1.7	6S2P	430	MIPI-4 40PIN FPC	-20 ° ~70 °
		HG050HD030-V1	4.97 AMOLED HD 3-power MIPI interface	720*1280	ALL	61.88*110.02	64.12*116.72	0.84	AMOLED	300	MIPI-4 39PIN ZIF	-40 ° ~70 °
		HG050HD030-V3	4.97 AMOLED HD with 3-power MIPI interface	720*1280	ALL	61.88*110.02	64.12*116.72	0.84	AMOLED	500	MIPI-4 39PIN ZIF	-40 ° ~70 °
		HG050HD035	4.99 TFT HD MIPI interface	720*1280	ALL	62.10*110.40	65.3*119.3	1.7	6S2P	450	MIPI-4 25PIN FPC	-20 ° ~70 °
		HG050FH008	4.95 TFT FHD MIPI interface	1080*1920	ALL	61.641*109.584	64.7*118.8	1.46	6S2P	400	MIPI-4 25PIN FPC	-20 ° ~70 °
		HG050FH025	4.95 TFT FHD MIPI interface	1080*1920	ALL	61.641*109.584	64.8*118.63	1.46	6S2P	400	MIPI-4 25PIN FPC	-20 ° ~70 °
		HG050FH028	4.97 TFT FHD MIPI interface	1080*1920	ALL	61.884*110.016	64.8*118.63	1.46	6S2P	400	MIPI-4 25PIN FPC	-20 ° ~70 °
		HG050FH029	4.97 TFT FHD MIPI interface	1080*1920	ALL	61.884*110.016	64.8*118.63	1.46	6S2P	400	MIPI-4 39PIN FPC	-20 ° ~70 °
		HG050FH031	4.97 TFT FHD MIPI interface		ALL	61.884*110.016	64.06*116.6	1.7	3S4P	700	MIPI-2/4 25PIN FPC	-20 ° ~70 °
Display in landscape	5.5	HG055HD016	5.46 TFT HD MIPI interface	720*1280	ALL	68.04*120.96	70.65*129.20	1.55	7S2P	400	MIPI-3 30PIN BTB	-20 ° ~70 °
		HG055FH017	5.44 AMOLED FHD display with 3-power MIPI interface	1080*1920	ALL	67.82*120.58	69.74*126.6	0.84	AMOLED	350	MIPI-4 39PIN ZIF	-40 ° ~70 °
		HG055FH018	5.44 AMOLED FHD display with 3-power MIPI interface	1080*1920	ALL	67.82*120.58	69.74*126.6	0.64	AMOLED	350	MIPI-4 39PIN ZIF	-40 ° ~70 °
		HG055FH021	5.44 AMOLED FHD 2-power MIPI interface	1080*1920	ALL	67.82*120.58	69.74*126.6	0.84	AMOLED	350	MIPI-4 25PIN FPC	-40 ° ~70 °
		HG055FH022	5.48 AMOLED FHD display with 5-power MIPI interface	1080*1920	ALL	68.256*121.344	70.356*127.344	0.825	AMOLED	700	MIPI-4 39PIN ZIF	-40 ° ~70 °
		HG055FH023	5.5 TFT FHD MIPI interface	1080*1920	ALL	68.04*120.96	76*136	4.5	4S7P	2000	MIPI-4 40PIN BTB	-20 ° ~70 °
		HG055FH025	5.5 TFT FHD MIPI interface	1080*1920	ALL	68.04*120.96	70.65*129.20	1.62	7S2P	350	MIPI-4 40PIN FPC	-20 ° ~70 °

6	6	HG060HD010	5.99 TFT HD+ MIPI interface	720*1440	ALL	68.04*136.08	70.24*142.59	2.01	7S2P	200min	MIPI-4 30PIN FPC	-10 °~-60 °
		HG060HD012	5.94 TFT HD MIPI interface	720*1280	ALL	73.89*131.52	76.72*139.62	1.95	8S2P	500	MIPI-4 30PIN FPC	-20 °~-70 °
		HG060HD013	5.94 TFT HD MIPI interface	720*1280	ALL	73.89*131.52	76.72*139.62	1.95	7S2P	350	MIPI-4 40PIN FPC	-20 °~-70 °
		HG060FH003	5.99 TFT FHD+ MIPI interface	1080*2160	ALL	68.04*136.08	70.24*142.28	1.69	8S2P	400	MIPI-4 40PIN BTB	-20 °~-70 °
		HG060FH006	5.99 TFT FHD+ MIPI interface	1080*2160	ALL	68.04*136.08	70.24*142.28	2.06	8S2P	TBD	MIPI-4 31PIN FPC	-20 °~-70 °
6.4		HG060FH008	5.99 TFT FHD+ MIPI interface	1080*2160	ALL	68.04*136.08	69.44*141.18	1.38	6S3P	400	MIPI-4 40PIN BTB	-20 °~-70 °
	6.4	HG064FH002	6.39 AMOLED FHD+ display with 5-power MIPI interface	1080*2340	ALL	68.04*147.42	69.84*150.42	1.098	AMOLED	500	MIPI-4 39PIN ZIF	-40 °~-70 °
	6.5	HG065HD007	6.56 TFT HD+ MIPI interface	720*1612	ALL	67.93*152.09	70.23*157.56	1.35	8S2P	480	MIPI-4 40PIN BTB	-20 °~-70 °
	6.7	HG067HD003	6.745 TFT HD+ MIPI interface	720*1600	ALL	70.308*156.24	72.41*161.44	1.36	6S3P	450	MIPI-4 60PIN BTB	-20 °~-70 °
		HG067WQ003 (120Hz)	6.72 TFT FHD+ MIPI interface	1080*2400	ALL	70.08*155.74	71.78*160.12	1.29	6S3P	380	MIPI-4 40PIN BTB	-20 °~-70 °
		HG067WQ005	6.67 AMOLED FHD+ MIPI interface	1080*2400	ALL	154.56*69.552	74.19*169.24	0.47	AMOLED	500~1000	MIPI-4 40PIN BTB	-20 °~-70 °
6.9		HG069HS004-V1	6.86 TFT 480*1280 MIPI interface	480*1280	ALL	60.22*160.59	66.6*181	4.4	3S4P	400	MIPI-4 40PIN ZIF	-20 °~-70 °
		HG069HS005	6.86 TFT 480*1280 MIPI interface	480*1280	ALL	60.22*160.59	66.8*181.2	4.5	3S4P	480	MIPI-4 40PIN ZIF	-20 °~-70 °
		HG069HD002	6.88 TFT HD+ MIPI interface	720*1640	ALL	72.2648*160.0476	72.56*165.35	1.32	6S3P	450	MIPI-4 60PIN BTB	-20 °~-70 °
7		HG070FH002	7.0 AMOLED FHD display with 3-power MIPI interface	1080*1920	ALL	87.1344*154.9056	89.13*160.91	1.01	AMOLED	800~1000	MIPI-4 39PIN ZIF	-40 °~-70 °
		HG070WX003	7.0 TFT WXGA MIPI interface	800*1280	ALL	94.2*150.72	99.8*161.05	2.65	5S4P	350	MIPI-4 40PIN ZIF	-20 °~-70 °
		HG070WX004	7.0 TFT WXGA MIPI interface	800*1280	ALL	94.2*150.72	99.8*161.05	2.65	5S4P	350	MIPI-4 40PIN ZIF	-20 °~-70 °
		HG070WX005	7.0 TFT WXGA MIPI interface	800*1280	ALL	94.2*150.72	99.8*161.05	2.65	3S7P	600	MIPI-4 31PIN ZIF	-20 °~-60 °
		HG070WX008	7.0 TFT WXGA MIPI interface	800*1280	ALL	94.2*150.72	99.8*161.05	2.65	5S4P	350	MIPI-4 31PIN ZIF	-10 °~-50 °
		HG070WX009	7.0 TFT WXGA MIPI interface	800*1280	ALL	94.2*150.72	99.8*161.05	2.65	5S4P	350	MIPI-4 31PIN ZIF	-10 °~-50 °
		HG070WX010	7.0 TFT WXGA MIPI interface	800*1280	ALL	94.2*150.72	99.8*161.05	2.65	5S4P	350	MIPI-4 40PIN ZIF	-10 °~-50 °
		HG070WX011	7.0 TFT WXGA MIPI interface	800*1280	ALL	94.2*150.72	100.56*161.06	2.6	5S4P	300	MIPI-4 40PIN ZIF	0 °~-50 °
		HG070WX012	7.0 TFT WXGA MIPI interface	800*1280	ALL	94.2*150.72	99.75*161	2.37	6S4P	800	MIPI-4 30PIN FPC	-20 °~-70 °
		HG070WX013-V1	7.0 TFT WXGA MIPI interface	800*1280	ALL	94.2*150.72	99.75*161	2.37	6S4P	400	MIPI-4 40PIN FPC	-20 °~-70 °
		HG070WU039	7.0 TFT WUXGA MIPI interface	1200*1920	ALL	94.5*151.2	99.81*161.66	2.2	5S4P	800	MIPI-4 40PIN ZIF	-20 °~-70 °
		HG070WU041	7.0 TFT WUXGA MIPI interface	1200*1920	ALL	94.5*151.2	111*166	3.29	7S8P	1500	MIPI-4 40PIN ZIF	-20 °~-70 °
		HG070WU042	7.0 TFT WUXGA MIPI interface	1200*1920	ALL	94.5*151.2	98.75*160.85	2.1	3S7P	300	MIPI-4 40PIN ZIF	-20 °~-70 °
8		HG080WU008	8.0 TFT WUXGA MIPI interface	1200*1920	ALL	107.64*172.22	114.6*184.1	2.2	3S7P	400	MIPI-4 30PIN ZIF	-10 °~-50 °
		HG080WU009	8.0 TFT WUXGA MIPI interface	1200*1920	ALL	107.64*172.22	114.6*184.1	2.6	3S8P	750	MIPI-4 30PIN ZIF	-10 °~-50 °
		HG080WU039	8.0 TFT WUXGA MIPI interface	1200*1920	ALL	107.64*172.22	114.6*184.1	2.3	3S8P	700	MIPI-4 39PIN ZIF	-10 °~-50 °
		HG080WU040	8.0 TFT WUXGA MIPI interface	1200*1920	ALL	107.64*172.22	114.6*184.1	2.6	8S3P	400	MIPI-4 40PIN ZIF	-10 °~-50 °
		HG080WU042	8.0 TFT WUXGA MIPI interface	1200*1920	ALL	107.64*172.22	113.14*182.42	2.05MAX	9S3P	435	MIPI-4 45PIN ZIF	0 °~-50 °
		HG080WX013	8.0 TFT WXGA MIPI interface	800*1280	ALL	107.64*172.22	114.6*184.1	2.75MAX	3S7P	500	MIPI-4 30PIN FPC	-20 °~-60 °
		HG080WX015	8.0 TFT WXGA MIPI interface	800*1280	ALL	107.64*172.22	114.6*184.1	2.75MAX	3S7P	1000	MIPI-4 30PIN FPC	-20 °~-60 °
		HG080WX032-V1	8.0 TFT WXGA MIPI interface	800*1280	ALL	107.64*172.22	114.66*184.14	2.5	3S7P	250	MIPI-4 31PIN ZIF	-20 °~-60 °
		HG080WX034	8.0 TFT WXGA MIPI interface	800*1280	ALL	107.64*172.22	114.6*184.1	2.75MAX	3S7P	1000	MIPI-4 31PIN ZIF	-20 °~-60 °
		HG080WX037	8.0 TFT WXGA MIPI interface	800*1280	ALL	107.64*172.22	114.6*184.1	2.87	3S8P	450	MIPI-4 30PIN ZIF	0 °~-50 °
		HG080WX038	8.0 TFT WXGA MIPI interface	800*1280	ALL	107.64*172.22	114.6*184.1	2.6	3S8P	500	MIPI-4 31PIN ZIF	-20 °~-60 °
		HG080WX039-V1	8.0 TFT WXGA MIPI interface	800*1280	ALL	107.64*172.22	114.6*184.1	2.6	3S7P	800	MIPI-4 31PIN ZIF	-20 °~-60 °
9.7		HG097QX003	9.7 TFT QXGA EDP interface	2048*1536	ALL	196.608*147.456	208.88*167.12	2.68	TBD	440	EDP-4 51PIN FPC	0 °~-50 °
		HG097QX005	9.7 TFT QXGA MIPI dual-channel interface	1536*2048	ALL	147.456*196.608	154.02*207.83	2.5	6S6P	320	MIPI-8 61PIN ZIF	-10 °~-60 °
10.1		HG101HD009	10.1 TFT HD MIPI interface	720*1280	ALL	125.28*222.72	143*235	4.5	6S7P	400	MIPI-4 30PIN ZIF	-20 °~-70 °
		HG101HD010	10.1 TFT HD MIPI interface	720*1280	ALL	125.28*222.72	142.9*234.9	4.5	6S6P	400	MIPI-4 30PIN FPC	-20 °~-70 °
		HG101WU009	10.1 TFT WUXGA MIPI interface	1200*1920	ALL	135.36*216.58	143*228.7	2.6	8S4P	350	MIPI-4 40PIN ZIF	-10 °~-60 °
		HG101WU010	10.1 TFT WUXGA MIPI interface	1200*1920	ALL	135.36*216.58	143*228.6	2.6	4S8P	800	MIPI-4 40PIN ZIF	-20 °~-60 °
		HG101WU013	10.1 TFT WUXGA MIPI interface	1200*1920	ALL	135.36*216.58	143*228.6	2.6	9S4P	400	MIPI-4 40PIN ZIF	-10 °~-50 °
		HG101WU015	10.1 TFT WUXGA MIPI interface	1200*1920	ALL	135.36*216.58	142.8*228.5	2.65MAX	4S8P	700	MIPI-4 40PIN ZIF	-20 °~-60 °
		HG101WU036	10.1 TFT WUXGA MIPI interface	1200*1920	ALL	135.36*216.58	141.68*226.19	2.1	4S8P	700	MIPI-4 40PIN ZIF	-20 °~-60 °
		HG101WU039	10.1 TFT WUXGA MIPI interface	1200*1920	ALL	135.36*216.58	142.8*228.2	2.25	8S4P	350	MIPI-4 40PIN ZIF	-20 °~-60 °
		HG101WU042	10.1 TFT WUXGA MIPI interface	1200*1920	ALL	135.36*216.58	142.86*228.08	2.26	4S8P	700	MIPI-4 40PIN ZIF	-20 °~-60 °
		HG101WX016	10.1 TFT WXGA MIPI interface	800*1280	ALL	135.36*216.576	142.9*228.5	2.61	8S4P	500	MIPI-4 40PIN ZIF	-20 °~-60 °
		HG101WX025	10.1 TFT WXGA MIPI interface	800*1280	ALL	135.36*216.576	143*228.6	2.65	3S10P	1000	MIPI-4 40PIN ZIF	-20 °~-60 °
		HG101WX047	10.1 TFT WXGA MIPI interface	800*1280	ALL	135.36*216.576	143*228.6	2.7	3S10P	500	MIPI-4 40PIN ZIF	-20 °~-60 °
		HG101WX053	10.1 TFT WXGA MIPI interface	800*1280	ALL	135.36*216.576	143*228.6	2.7	4S8P	250	MIPI-4 31PIN ZIF	-20 °~-60 °
		HG101WX054	10.1 TFT WXGA MIPI interface	800*1280	ALL	135.36*216.576	143*228.6	2.6	4S8P	350	MIPI-4 40PIN ZIF	0 °~-50 °
		HG101WX059	10.1 TFT WXGA MIPI interface	800*1280	ALL	135.36*216.58	143*228.6	2.6	4S8P	350	MIPI-4 40PIN ZIF	0 °~-50 °
		HG101WX060	10.1 TFT WXGA LVDS interface	800*1280	ALL	135.36*216.58	143*228.6	2.5	8S4P	300	LVDS-4 20PIN ZIF	-10 °~-60 °
		HG101WX062	10.1 TFT WXGA LVDS interface	800*1280	ALL	135.36*216.58	143.1*228.55	2.5	5~12V	300	LVDS-4 20PIN ZIF	-10 °~-60 °
10.4		HG104SX002	10.4 TFT SXGA-LVDS interface	960*1280	ALL	158.4*211.2	173.4*228.7	13.77	TBD	900	LVDS-4 50PIN FPC	-40 °~-85 °
10.5		HG105WU002	10.51 TFT WUXGA in cell MIPI interface	1200*1920	ALL	141.48*226.368	146.58*235.37	2.1	9S4P	230	MIPI-4 41PIN ZIF	-10 °~-60 °
11.5		HG115WU002	11.5 TFT WUXGA MIPI interface	1200*2000	ALL	143.1*238.5	166.1*259.1	4.48	6S7P	300	MIPI-4 30PIN ZIF	-20 °~-70 °
12.4		HG124WQ003	2.4 TFT In-cell WQXGA MIPI dual-channel interface	1600*2560	ALL	166.224*265.9584	180.22*279.96	3.075	TBD	500	MIPI-4 46PIN*2 ZIF	-20 °~-60 °
12.95		HG130WU002	12.95 TFT HD+ MIPI interface	1200*1920	ALL	174.312*278.8992	180.1*289.58	2.19	8S6P	350	MIPI-4 51PIN ZIF	-10 °~-60 °
0.42		HG004WS001	0.42 PMOLED SPI/I2C interface	72*40	White	9.196*5.18	12*11	1.25	PMOLED	430	SPI/IIC 16PIN FPC	-40 °~-70 °
0.66		HG007WS003	0.66 PMOLED MCU/SPI/I2C interface	64*48	White	13.415*10.055	18.46*18.1	1.26	PMOLED	110	MCU/SPI-4/I2C (28-pin soldering)	-40 °~-70 °
		HG007WS005	0.66 PMOLED I2C interface	64*48	White	13.42*10.06	18.46*18.1	1.46	PMOLED	110	IIC 16PIN FPC	-40 °~-70 °
0.91		HG009SQ002	0.91 PMOLED I2C interface	128*32	White	22.38*5.58	29*8.8	1.26	PMOLED	120	IIC 14PIN FPC	-40 °~-70 °

0.96	HG010SQ002 (Short row – 20 mm)	0.96 PMOLED MCU/SPI/I2C interface	128*64	White	21.744*10.864	26.7*19.26	1.41	PMOLED	80	MCU/SPI/I2C 30PIN FPC	-40 ~-70 °
	HG010SQ003 (Long row – 40 mm)	0.96 PMOLED MCU/SPI/I2C interface	128*64	White	21.744*10.864	26.7*19.26	1.41	PMOLED	80	MCU/SPI/I2C 30PIN FPC	-40 ~-70 °
	HG010SQ004	0.96 PMOLED Parallel/Serial/I2C Interface	128*64	White	21.740*11.175	26.7*19.26	1.45	PMOLED	100	Parallel/Serial/IIC 30PIN	-20 ~-70 °
	HG010SQ006 (FPC41.6mm)	0.96 PMOLED SPI-4/3 I2C Interface	128*64	White	21.74*11.18	24.7*16.59	1.41	PMOLED	90	SPW/3 IIC 30-PIN Soldering	-40 ~-70 °
1.3	HG010SQ007	0.96 PMOLED SPI-4/3 I2C Interface	128*64	White	21.740*11.175	24.7*16.6	1.3	PMOLED	90	SPW/3 PC 30-PIN Soldering	-20 ~-70 °
	HG013SQ003	1.3 PMOLED MCU/SPI/I2C interface	128*64	White	29.42*14.7	34.5*23	1.41	PMOLED	120	MCU/SPI/I2C 30IN FPC	-40 ~-70 °
1.5	HG013SQ002 (PCB)	1.3 PMOLED + PCB I2C Interface	128*64	White	29.42*14.7	35.5*33.6	3.5	PMOLED	110	IIP 4-pin	-40 ~-70 °
	HG015ME002	1.51 PMOLED MCU/SPI/I2C interface	128*56	White	35.05*15.32	42.04*27.22	1.25	PMOLED	120	MCU/SPI/I2C 24PIN FPC	-40 ~-70 °
1.54	HG015SQ003	1.54 PMOLED MCU/SPI/I2C interface	128*64	White	35.047*17.511	42.04*27.22	1.4	PMOLED	120	MCU/SPI/I2C 24PIN FPC	-40 ~-70 °
	HG015SQ004	1.54 PMOLED MCU/SPI/I2C interface	128*64	White	35.052*17.516	42.04*27.22	1.45	PMOLED	110	MCU/SPI/I2C 24PIN FPC	-40 ~-70 °
	HG015SQ005 (PCB)	1.54 PMOLED + PCB SPI/I2C Interface	128*64	White	35.05*17.52	42.4*38	3.05	PMOLED	120	SPI/I2C (7-pin)	-40 ~-70 °
	HG015SQ006	1.54 PMOLED MCU/SPI/I2C interface	128*64	White	35.05*17.52	39.2*24.2	1.41	PMOLED	120	MCU/SPI/I2C 24PIN FPC	-40 ~-70 °
	HG015SQ007	1.54 PMOLED MCU/SPI/I2C interface	128*64	White	35.052*17.516	42.04*27.22	1.45	PMOLED	110	MCU/SPI/I2C 24PIN FPC	-40 ~-70 °
	HG015SQ008	1.54 PMOLED MCU/SPI/I2C interface	128*64	White	35.052*17.516	42.04*27.22	1.45	PMOLED	110	MCU/SPI/I2C 24PIN FPC	-40 ~-70 °
2	HG020HV002	2.0 TFT HVGA RGB/SPI interface	480*360	ALL	40.82*30.62	43.95*38.8	2.1	1S6P	550	SPI/RGB16Bit 39PIN FPC	-20 ~-70 °
2.3	HG023SC002	2.25 PMOLED (256*96) SPI interface	256*96	White	53*21.7	61.1*16.85	2.06	PMOLED	150	SPI 15PIN FPC	-20 ~-70 °
2.42	HG024SQ002	2.42 PMOLED MCU/SP14/I2C interface	128*64	White	55.01*27.49	60.5*37	1.8	PMOLED	110	MCU/SPI/I2C 24PIN FPC	-40 ~-70 °
	HG024SQ003	2.42 PMOLED MCU/SP14/I2C interface	128*64	White	55.01*27.49	60.5*37	2.01	PMOLED	70	MCU/SPI/I2C 24PIN FPC	-40 ~-70 °
3.12	HG031SC002	3.12 PMOLED MCU/SPI Interface	256*64	White	76.78*19.18	88*27.8	2	PMOLED	80	MCU/SPI 30PIN FPC	-40 ~-70 °
3.2	HG032XG002	3.17 TFT XGA MIPI interface	1024*768	ALL	64.51*48.38	68.41*57.19	2.06	6S2P	1000	MIPI-4 35PIN FPC	-20 ~-70 °
	HG032XG003	3.17 TFT XGA MIPI interface	1024*768	ALL	64.51*48.38	68.41*57.19	2.05	6S2P	400	MIPI-4 35PIN FPC	-20 ~-70 °
3.4	HG034HQ002	3.37 PMOLED 240*128	240*128	White	75.58*40.3	89.52*54.41	2.05	PMOLED	50	MCU/SPI 30PIN FPC	-20 ~-70 °
3.5	HG035QV002	3.5 TFT QVGA TN RGB interface	320*240	6/12 o'clock	70.08*52.56	76.84*63.84	3.25	6S1P	400	RGB-24 54PIN FPC	-20 ~-70 °
	HG035QV003	3.5 TFT QVGA RGB interface	320*240	ALL	70.08*52.56	76.84*63.84	3.2	6S1P	350	RGB-24 54PIN FPC	-20 ~-70 °
	HG035VG002	3.45 TFT VGA 3SPI/RGB	640*480	ALL	70.08*52.56	76.2*63.2	3.07	6S2P	400	3SPI/RGB-24 54PIN FPC	-20 ~-70 °
3.9	HG039WV004	3.9 TFT WVGA RGB interface	800*216	ALL	95.24*24.4	100.4*32.9	2.5	5S2P	750	RGB-24 40-PIN FPC – Top contact connection	-20 ~-70 °
	HG039WV006	3.9 TFT WVGA RGB interface	800*216	ALL	95.24*24.4	100.4*32.9	2.5	5S2P	750	RGB-24 40-pin FPC – Bottom connection	-20 ~-70 °
	HG039HV002	3.9 TFT HVGA RGB interface	480*128	ALL	95.04*25.344	104.4*34.85	2.5	5S2P	800	RGB-24 40PIN FPC	-20 ~-70 °
4	HG040FH002	4.0 TFT FHD MIPI interface	1920*1080	ALL	88.589*49.831	92.890*59.170	2.3	7S3P	450	MIPI-4 25PIN FPC	-20 ~-70 °
4.3	HG043HV001	4.3 TFT HVGA RGB interface	480*272	6 o'clock	95.04*53.86	105.5*67.2	2.95	7S1P	220	RGB-24 40PIN FPC	-20 ~-70 °
	HG043HV002-V1	4.3 TFT HVGA RGB interface	480*272	ALL	95.04*53.86	105.5*67.2	3	7S1P	300	RGB-24 40PIN FPC	-20 ~-70 °
	HG043HV003 (Low 8 bits)	4.3 TFT HVGA RGB interface	480*272	6 o'clock	95.04*53.86	105.5*67.2	3	7S1P	300	RGB-8 40-PIN (Low 8-bit) FPC	-20 ~-70 °
	HG043HV005	4.3 TFT HVGA RGB interface	480*272	6 o'clock	95.04*53.86	105.5*67.2	2.95	7S1P	400	RGB-24 40PIN FPC	-20 ~-70 °
	HG043HV008	4.3 TFT HVGA RGB interface	480*272	ALL	95.04*53.86	105.5*67.2	3	8S2P	1000	RGB-24 40PIN FPC	-30 ~-80 °
	HG043HV009	4.3 TFT HVGA RGB interface	480*272	ALL	95.04*53.86	105.5*67.2	3	7S1P	500	RGB-24 40PIN FPC	-20 ~-70 °
	HG043HV010	4.3 TFT HVGA RGB interface	480*272	12 o'clock	95.04*53.86	105.5*67.2	3	10S1P	500	RGB-24 40PIN FPC	-20 ~-60 °
	HG043HV011	4.3 TFT HVGA RGB interface	480*272	6 o'clock	95.04*53.86	105.5*67.2	2.9	10S1P	500	RGB-24 40PIN FPC	-20 ~-70 °
	HG043HV012	4.3 TFT HVGA RGB interface	480*272	6 o'clock	95.04*53.86	105.5*67.2	3	7S1P	250	RGB-24 40PIN FPC	-20 ~-60 °
	HG043HV022	4.3 TFT HVGA RGB interface	480*272	12 o'clock	95.04*53.86	105.5*67.2	3	8S2P	1000	RGB-24 40PIN FPC	-20 ~-60 °
	HG043HV025	4.3 TFT HVGA RGB interface	480*272	12 o'clock	95.04*53.86	105.5*67.2	3	7S1P	300	RGB-24 40PIN FPC	-20 ~-70 °
	HG043HV026	4.3 TFT HVGA RGB interface	480*272	6 o'clock	95.04*53.86	105.5*67.2	3	7S1P	500	RGB-24 40PIN FPC	-20 ~-70 °
	HG043HV028	4.3 TFT HVGA RGB interface	480*272	ALL	95.04*53.86	105.5*67.2	3	5S2P	500	RGB-24 40PIN FPC	-20 ~-70 °
	HG043HV029	4.3 TFT HVGA RGB interface	480*272	ALL	95.04*53.86	105.5*67.2	7.8max	3S2P	1000	RGB-24 50PIN FPC	-30 ~-85 °
	HG043WV005	4.3 TFT WVGA RGB interface	800*480	ALL	95.04*53.86	105.5*67.2	2.9	5S2P	500	RGB-24 40PIN FPC	-20 ~-70 °
	HG043WV018	4.3 TFT WVGA RGB interface	800*480	ALL	95.04*53.86	105.5*67.2	3	5S2P	350	RGB-24 40PIN FPC	-20 ~-70 °
	HG043WV021	4.3 TFT WVGA RGB interface	800*480	ALL	95.04*53.86	105.5*67.2	2.8	7S2P	1000	RGB-24 40PIN FPC	-20 ~-70 °
	HG043WV022	4.3 TFT WVGA RGB interface	800*480	ALL	95.04*53.86	105.5*67.2	2.8	6S3P	600	RGB-24 40PIN FPC	-20 ~-60 °
	HG043WV023	4.3 TFT WVGA RGB interface	800*480	ALL	95.04*53.86	105.5*67.2	2.8	8S2P	1000	RGB-24 40PIN FPC	-20 ~-70 °
5	HG050VG002	5.0 TFT VGA RGB interface	640*480	12 o'clock	101.57*76.18	117.65*88.43	5.7	TBD	250	RGB-24 50PIN FPC	-20 ~-70 °
	HG050QH005	5.0 AMOELD MIPI interface	960*544	ALL	109.44*62.02	116.54*73.92	1.66	AMOLED	139	MIPI-2 40PIN TBT	-10 ~-60 °
	HG050WV005	5.0 TFT WVGA RGB interface	800*480	ALL	108*64.8	120.8*75.85	3	6S2P	500	RGB-24 40PIN FPC	-20 ~-70 °
	HG050WV008	5.0 TFT WVGA LVDS interface	800*480	ALL	108*64.8	120.8*75.85	3	10S2P	850	LVDS-4 20PIN FPC	-20 ~-70 °
	HG050WV009	5.0 TFT WVGA LVDS interface	800*480	ALL	108*64.8	123.2*79.2	5.89	5S3P	1000	LVDS-4 40-pin FPC connection	-30 ~-85 °
	HG050WV010	5.0 TFT WVGA LVDS interface	800*480	ALL	108*64.8	165.1*99.1	5.89	5S3P	1000	LVDS-4 40-pin FPC connection	-30 ~-85 °
	HG050WV032	5.0 TFT WVGA RGB interface	800*480	6 o'clock	108*64.8	120.8*75.85	3	6S2P	300	RGB-24 40PIN FPC	-20 ~-70 °
	HG050WV033	5.0 TFT WVGA RGB interface	800*480	6 o'clock	108*64.8	120.8*75.85	3	6S3P	450	RGB-24 40PIN FPC	-20 ~-70 °
	HG050WV034	5.0 TFT WVGA RGB interface	800*480	ALL	108*64.8	120.7*75.8	3	6S4P	1000	RGB-24 40PIN FPC	-30 ~-80 °
	HG050WV035	5.0 TFT WVGA RGB interface	800*480	ALL	108*64.8	120.7*75.8	2.9	6S3P	700	RGB-24 40PIN FPC	-30 ~-80 °
	HG050WV036	5.0 TFT WVGA RGB interface	800*480	ALL	108*64.8	120.7*75.8	3	6S3P	500	RGB-24 40PIN FPC	-20 ~-70 °
	HG050WV037	5.0 TFT WVGA RGB interface	800*480	6 o'clock	108*64.8	120.8*75.85	3	5S2P	250	RGB-24 40PIN FPC	-20 ~-60 °
5.5	HG055SV006 (Special Shape)	5.5 TFT WVGA RGB interface	800*480	6 o'clock	118*70	133*80	5	3S6P	1000	RGB-24 60PIN FPC	-20 ~-70 °
	HG056VG003	5.6 TFT VGA RGB interface	640*480	12 o'clock	112.896*84.672	126.5*100	5.7	TBD	350	RGB-18 40PIN FPC	-20 ~-70 °
5.7	HG057VG002	5.7 TFT VGA RGB/LVDS/MIPI interface	640*480	ALL	115.2*86.4	127*98.43	5.85	3S7P	1000	RGB/LVDS/MIPI 60PIN FPC	-20 ~-70 °
	HG057VG003	5.7 TFT VGA/LVDS interface	640*480	ALL	115.2*86.4	127*98.43	7.5	4S7P	1000	LVDS-3 20PIN FPC	-20 ~-70 °
	HG062WV007	6.2-inch TFT WVGA RGB interface	800*480	6 o'clock	137.52*77.232	155.2*88.2	5	3S6P	300	RGB-24 60PIN FPC	-20 ~-70 °

6.2	HG062WS003	6.2 TFT WSVGA LVDS interface	1024*600	ALL	137.472*77.232	155.2*88.2	4.8	3S7P	350	LVDS-4 60PIN FPC	-20 ° ~70 °
	HG062WS005	6.2 TFT WSVGA RGB interface	1024*600	ALL	137.41*77.28	155.22*88.22	5	3S7P	1000	RGB-24 60PIN FPC	-20 ° ~70 °
	HG062WS006	6.2 TFT WSVGA RGB interface	1024*600	ALL	137.41*77.28	155.22*88.22	5	3S7P	1000	RGB-24 50PIN FPC	-30 ° ~80 °
	HG062WS007	6.2 TFT WSVGA RGB interface	1024*600	AKK	137.41*77.28	155.22*88.22	5	3S8P	650	RGB-24 60PIN FPC	-30 ° ~80 °
	HG062WS008	6.2 TFT WSVGA LVDS interface	1024*600	ALL	137.52*77.232	155.22*88.22	5	3S7P	500	LVDS-4 40PIN FPC	-30 ° ~80 °
	HG062WS009	6.2 TFT WSVGA LVDS interface	1024*600	ALL	137.52*77.232	155.22*88.22	5	3S7P	500	LVDS-4 40PIN FPC	-30 ° ~80 °
	HG064XG003	6.4 TFT XGA LVDS interface	1024*768	ALL	129.792*97.344	153.4*122	9.9	TBD	350	LVDS-4 20PIN ZIF	-20 ° ~70 °
	HG064XG004	6.4 TFT XGA LVDS interface	1024*768	ALL	129.792*97.344	153.4*122	9.9	TBD	390	LVDS-4 20PIN ZIF	-20 ° ~70 °
	HG064XG005	6.4 TFT XGA LVDS interface	1024*768	ALL	129.792*97.344	140.75*110.60	5	3S10P	900	LVDS-4 30PIN ZIF	-20 ° ~70 °
	HG065VG002	6.5 TFT VGA RGB interface	640*480	ALL	132.48*99.36	154*121	11MAX	6S2P	1200	RGB-24 40PIN ZIF	-30 ° ~80 °
	HG070WS002	7.0 TFT WSVGA RGB interface	1024*600	6 o'clock	154.2144*85.92	165*100	3.5	3S7P	280	RGB-24 50PIN FPC	-20 ° ~60 °
	HG070WS004	7.0 TFT WSVGA LVDS interface	1024*600	ALL	154.2144*85.92	164.7*99.96	3.5	3S9P	400	LVDS-4 40PIN FPC	-20 ° ~70 °
	HG070WS011 (Edge Trim)	7.0 TFT WSVGA MIPI interface	1024*600	ALL	154.2144*85.92	163.8*97	2.6	3S9P	350	MIPI-4 30PIN FPC	-20 ° ~60 °
	HG070WS013	7.0 TFT WSVGA LVDS interface	1024*600	ALL	154.2144*85.92	164.9*100	3.5	3S10P	500	LVDS-4 40PIN FPC	-20 ° ~70 °
	HG070WS018	7.0 TFT WSVGA LVDS interface	1024*600	ALL	154.2144*85.92	164.9*100	3.2	3S8P	400	LVDS-4 50PIN FPC	-20 ° ~70 °
	HG070WS033	7.0 TFT WSVGA MIPI interface	1024*600	ALL	154.2144*85.92	165*100	3.4	3S7P	400	MIPI-4 30PIN FPC	-10 ° ~50 °
	HG070WS039	7.0 TFT WSVGA LVDS interface	1024*600	6 o'clock	154.2144*85.92	164.9*100	3.5	3S9P	500	LVDS-4 40PIN FPC	-20 ° ~70 °
	HG070WS045	7.0 TFT WSVGA LVDS interface	1024*600	ALL	154.2144*85.92	165*100	3.25	3S9P	300	LVDS-4 40PIN FPC	-20 ° ~70 °
	HG070WS046	7.0 TFT WSVGA LVDS interface	1024*600	ALL	154.2144*85.92	165*100	3.25	3S9P	500	LVDS-4 40PIN FPC	-20 ° ~70 °
	HG070WS047	7.0 TFT WSVGA MIPI interface	1024*600	ALL	154.2144*85.92	165*100	3.5	3S9P	300	MIPI-4 30PIN FPC	-20 ° ~70 °
	HG070WS048 (Gummed)	7.0 TFT WSVGA RGB interface	1024*600	ALL	154.2144*85.92	164.1*99.36	2.55	3S9P	350	RGB-24 50PIN FPC	-20 ° ~60 °
	HG070WS049-V1	7.0 TFT WSVGA LVDS interface	1024*600	ALL	154.2144*85.92	164.9*100	5.5	3S9P	500	LVDS-4 40PIN FPC	-20 ° ~70 °
	HG070WS050	7.0 TFT WSVGA RGB interface	1024*600	6 o'clock	154.2144*85.92	164.9*100	5.5	3S9P	400	RGB-24 50PIN FPC	-20 ° ~70 °
	HG070WS051	7.0 TFT WSVGA MIPI interface	1024*600	ALL	154.2144*85.92	164.9*100	2.8	3S9P	350	MIPI-4 30PIN FPC	-20 ° ~70 °
	HG070WS052	7.0 TFT WSVGA LVDS interface	1024*600	ALL	154.2144*85.92	164.9*100	5.5	3S9P	1000	LVDS-4 40PIN FPC	-30 ° ~80 °
	HG070WS053 (Rubber-Coated)	7.0 TFT WSVGA LVDS interface	1024*600	ALL	154.2144*85.92	165*100	5.5	3S9P	1000	LVDS-4 40PIN FPC	-30 ° ~80 °
7	HG070WS054	7.0 TFT WSVGA RGB interface	1024*600	12 o'clock	154.2144*85.92	165*100	3.5	3S9P	300	RGB-24 50PIN FPC	-20 ° ~60 °
	HG070WS055	7.0 TFT WSVGA RGB interface	1024*600	ALL	154.2144*85.92	164.9*100	3.5	3S9P	550	RGB-24 50PIN FPC	-20 ° ~70 °
	HG070WS056	7.0 TFT WSVGA RGB interface	1024*600	ALL	154.2144*85.92	165*100	3.5	3S9P	500	RGB-24 50PIN FPC	-20 ° ~70 °
	HG070WS057	7.0 TFT WSVGA RGB interface	1024*600	ALL	154.2144*85.92	164.9*100	3.5	3S9P	500	RGB-24 50PIN FPC	-20 ° ~70 °
	HG070WS058	7.0 TFT WSVGA LVDS interface	1024*600	ALL	154.2144*85.92	164.9*100	5.5	3S9P	1000	LVDS-4 40PIN FPC	-30 ° ~85 °
	HG070WS059 (Rubber-Coated)	7.0 TFT WSVGA LVDS interface	1024*600	ALL	154.2144*85.92	164.9*100	5.5	3S9P	500	LVDS-4 40PIN FPC	-20 ° ~70 °
	HG070WS060	7.0 TFT WSVGA MIPI interface – High-current LED	1024*600	ALL	154.2144*85.92	165*100	5.5	3S9P	1000	MIPI-4 30PIN FPC	-20 ° ~70 °
	HG070WS061	7.0 TFT WSVGA MIPI interface	1024*600	ALL	154.2144*85.92	164.86*99.96	3.5	4S7P	500	MIPI-4 40PIN ZIF	-10 ° ~60 °
	HG070WS062	7.0 TFT WSVGA MIPI interface	1024*600	ALL	154.2144*85.92	165*100	3.2	3S6P	300	MIPI-4 40PIN ZIF	-20 ° ~70 °
	HG070WS063	7.0 TFT WSVGA MIPI interface	1024*600	ALL	154.2144*85.92	164.86*99.96	3.5	3S9P	500	LVDS-4 30PIN FPC	-10 ° ~60 °
	HG070WS065	7.0 TFT WSVGA MIPI interface	1024*600	ALL	154.2144*85.92	164*97	2.6	3S9P	400	MIPI-4 30PIN ZIF	-10 ° ~60 °
	HG070WS066	7.0 TFT WSVGA LVDS interface	1024*600	ALL	154.2144*85.92	165.75*105.39	3.4	3S6P	350	LVDS-4 40PIN FPC	-20 ° ~70 °
	HG070WS067	7.0 TFT WSVGA LVDS interface	1024*600	ALL	154.2144*85.92	165*100	3.3	3S9P	300	LVDS-4 40PIN FPC	-20 ° ~70 °
	HG070WS068	7.0 TFT WSVGA RGB interface	1024*600	6 o'clock	154.2144*85.92	164.86*99.96	3.5	3S9P	500	RGB-24 50PIN FPC	-10 ° ~50 °
	HG070WS069	7.0 TFT WSVGA RGB interface	1024*600	ALL	154.2144*85.92	165*100	3.2	3S9P	1000	RGB-24 50PIN FPC	-10 ° ~60 °
	HG070WV002	7.0 TFT WVGA RGB interface	800*480	ALL	152.4*91.44	166.6*105.8	10.5MAX	6S3P	1000	RGB-24 50PIN FPC	-30 ° ~85 °
	HG070WV003	7.0 TFT WVGA LVDS interface	800*480	ALL	152.4*91.44	165.82*104.95	9.65MAX	6S3P	1000	LVDS-4 40PIN FPC	-30 ° ~85 °
	HG070WV013	7.0 TFT WVGA RGB interface	800*480	6 o'clock	154.08*85.92	165*100	3.5	7S3P	300	RGB-24 40PIN FPC	-20 ° ~60 °
	HG070WV020	7.0 TFT WVGA RGB interface	800*480	6 o'clock	153.84*85.63	164.9*99.6	3.5	3S9P	800	RGB-24 50PIN FPC	-20 ° ~60 °
	HG070WV025	7.0 TFT WVGA RGB interface	800*480	6 o'clock	154.08*85.92	164.9*100	5.7	3S7P	350	RGB-24 50PIN FPC	-20 ° ~70 °
	HG070WV031	7.0 TFT WVGA RGB interface	800*480	6 o'clock	154.08*85.92	164.86*99.96	3.5	3S9P	800	RGB-24 50PIN FPC	-20 ° ~60 °
	HG070WV035	7.0 TFT WVGA RGB interface	800*480	12 o'clock	154.08*85.92	164.9*100	5.5	3S9P	800	RGB-24 50PIN FPC	-20 ° ~60 °
	HG070WV036	7.0 TFT WVGA RGB interface	800*480	12 o'clock	154.08*85.92	164.9*100	5.7	3S9P	300	RGB-24 50PIN FPC	-20 ° ~70 °
	HG070WV037	7.0 TFT WVGA RGB interface	800*480	6 o'clock	154.08*85.92	164.9*100	3.5	3S9P	300	RGB-24 50PIN FPC	-20 ° ~70 °
	HG070WV047	7.0 TFT WVGA RGB interface	800*480	12 o'clock	154.08*85.92	164.9*100	5.7	3S9P	500	RGB-24 50PIN FPC	-30 ° ~85 °
	HG070WV048	7.0 TFT WVGA RGB interface	800*480	12 o'clock	154.08*85.92	164.9*100	5.7	3S9P	400	RGB-24 50PIN FPC	-20 ° ~60 °
	HG070WV049	7.0 TFT WVGA RGB interface	800*480	6 o'clock	154.08*85.92	164.9*100	3.25	3S9P	600	RGB-24 50PIN FPC	-20 ° ~70 °
	HG070WV050	7.0 TFT WVGA RGB interface	800*480	12 o'clock	154.08*85.92	164.9*100	2.8	3S6P	250	RGB-24 50PIN FPC	-20 ° ~70 °
	HG070WV051	7.0 TFT WVGA RGB interface	800*480	12 o'clock	154.21*85.92	165*100	3.35	3S6P	250	RGB-24 50PIN FPC	-20 ° ~70 °
	HG070WV052	7.0 TFT WVGA RGB interface	800*480	6 o'clock	154.08*85.92	164.86*99.96	3.5	3S9P	300	RGB-24 50PIN FPC	-20 ° ~70 °
8	HG080WV029	8.0 TFT SVGA RGB interface	800*480	6 o'clock	176.64*99.36	192.8*117	6.3	3S10P	500	RGB 50PIN FPC	-20 ° ~70 °
	HG080SV003	8.0 TFT SVGA RGB interface	800*600	12 o'clock	162*121.5	183*141	5.6	3S9P	250	RGB-24 50PIN FPC	-20 ° ~70 °
	HG080SV005	8.0 TFT SVGA RGB interface	800*600	ALL	162*121.5	183*141	3.5	3S9P	350	RGB-24 50PIN FPC	-20 ° ~70 °
	HG080XG003-V1	8.0 TFT XGA LVDS interface	1024*768	ALL	162.05*121.54	174*136	2.7	3S11P	350	LVDS-4 40PIN FPC	-10 ° ~60 °
	HG080XG005	8.0 TFT XGA LVDS interface	1024*768	ALL	162.05*121.54	174.5*135.6	2.8	3S11P	350	LVDS-4 40PIN FPC	-10 ° ~60 °
	HG080XG006	8.0 TFT XGA LVDS interface	1024*768	ALL	162.05*121.54	182.9*141	5.5	6S6P	800	LVDS-4 40PIN FPC	-20 ° ~70 °
	HG080HD002	8.0 TFT HD720 LVDS interface	1280*720	ALL	176.64*99.36	192.8*116.9	6.4	8S3P	800	LVDS-4 30PIN FPC	-35 ° ~80 °
	HG080WX009-V1	8.0 TFT WXGA LVDS interface	1280*800	ALL	172.22*107.64	181.65*118.75	2.25	6S6P	350	LVDS-4 40PIN I-PEX	-20 ° ~70 °
	HG080WX036	8.0 TFT WXGA LVDS interface	1280*800	ALL	172.22*107.64	181.25*118.75	3.95	6S6P	500	LVDS-4 40PIN ZIF	-20 ° ~70 °
	HG080WU036	8.0 TFT WUXGA LVDS dual-channel interface	1920*1200	ALL	172.224*107.64	119.8*181.7	5.5	6S6P	1000	LVDS-8 45PIN ZIF	-30 ° ~80 °
	HG080WU041	8.0 TFT WUXGA LVDS dual-channel interface	1920*1200	ALL	172.224*107.64	178.21*118.85	4.7	9S4P	1000~2000	LVDS-8 45PIN ZIF	-20 ° ~70 °

Portrait display	8.4	HG080QS002	8.0 Folding AMOLED 2K+ MIPI interface	2480*1860	ALL	162.688*122.016	165.89*126.12	0.8	AMOLED	430	MIPI-4 40PIN BTB	-40 ~-70.°
		HG080QS003	8.0 Flexible AMOLED 2K+ MIPI interface	2480*1860	ALL	162.688*122.016	165.688*125.416	0.36	AMOLED	430	MIPI-4 40PIN BTB	-40 ~-70.°
		HG084XG002	8.4 TFT XGA LVDS interface	1024*768	ALL	170.5*127.87	184.5*143	7.25	10S3P	1200	LVDS-4 40PIN FPC	-30 ~-85.°
		HG088HS006	8.8 TFT 1280*480 LVDS interface	1280*480	ALL	209.28*78.48	229.7*98.13	4.6	8S3P	500	LVDS-4 60PIN FPC	-20 ~-70.°
	8.9	HG089WQ003	8.9 TFT WQXGA MIPI dual-channel interface	2560*1600	ALL	190*120	204.26*134.46	3	8S5P	1200	MIPI-8 51PIN ZIF	0 ~-50.°
	9	HG090WV002	9.0 TFT SVGA RGB interface	800*480	6 o'clock	198*111.696	210.7*126.4	5	3S9P	200	RGB-24 50PIN	-10 ~-60.°
		HG090HD001	9.0 TFT HD720 LVDS interface	1280*720	ALL	198.912*111.888	210.71*127.71	4.9	6S7P	400	LVDS-4 60PIN FPC	-20 ~-70.°
		HG090HD002	9.0 TFT HD720 LVDS interface	1280*720	ALL	198.912*111.888	210.7*126.5	5.2	6S7P	380	LVDS-4 60PIN FPC	-20 ~-70.°
		HG090HD004	9.0 TFT HD720 LVDS interface	1280*720	ALL	198.72*111.78	212.2*127.5	7.6	9S3P	1000	LVDS-4 40PIN FPC	-30 ~-85.°
		HG090HD005	9.0 TFT HD720 LVDS interface	1280*720	ALL	198.91*111.86	210.7*126.5	4.98	6S9P	550	LVDS-4 60PIN FPC	-30 ~-80.°
		HG090WS008	9.0 TFT WSVGA LVDS interface	1024*600	6 o'clock	196.608*114.15	210.7*126.5	3.5	3S8P	230	LVDS-4 40PIN FPC	-20 ~-60.°
		HG090WS011	9.0 TFT WSVGA LVDS interface	1024*600	ALL	196.608*114.15	211.1*126.5	5	6S7P	450	LVDS-4 60PIN FPC	-20 ~-70.°
		HG090WS012	9.0 TFT WSVGA MIPI interface	1024*600	ALL	196.62*114.16	210.7*126.5	4.9	6S7P	450	MIPI-4 30PIN FPC	-20 ~-70.°
	9.7	HG097XG006	9.7 TFT XGA LVDS interface	1024*768	ALL	196.61*147.46	210.16*164.25	5.1	6S6P	300	LVDS-3 30PIN I-PEX	-20 ~-70.°
		HG097XG007-V1	9.7 TFT XGA LVDS interface	1024*768	ALL	196.61*147.46	210.6*164.15	2.8	6S6P	350	LVDS-3 30PIN I-PEX	-20 ~-70.°
		HG097XG009	9.7 TFT XGA LVDS interface	1024*768	6 o'clock	198.3*149.1	210.2*164.2	5	7S5P	300	LVDS-4 40PIN ZIF	0 ~-50.°
		HG097XG010	9.7 TFT XGA LVDS interface	1024*768	ALL	196.61*147.46	210.2*164.2	5	3S12P	350	LVDS-4 40PIN ZIF	-20 ~-70.°
		HG097XG011	9.7 TFT XGA LVDS interface	1024*768	ALL	196.608*147.456	210.1*164.15	2.85	6S6P	350	LVDS-3 30PIN ZIF	-20 ~-70.°
		HG097XG012	9.7 TFT XGA LVDS interface	1024*768	3 o'clock	196.608*147.456	210.21*164.25	3	6S6P	300	LVDS-3 30PIN ZIF	-10 ~-60.°
		HG097XG013	9.7 TFT XGA LVDS interface	1024*768	ALL	196.608*147.456	210.9*164.95	3.15	6S6P	350	LVDS-3 30PIN ZIF	-20 ~-70.°
	10.1	HG101WS039	10.1 TFT WSVGA LVDS interface	1024*600	ALL	222.72*125.28	235*143	2.8	3S12P	260	LVDS-4 40PIN FPC	-10 ~-50.°
		HG101WS040	10.1 TFT WSVGA LVDS interface	1024*600	6 o'clock	222.72*125.28	235*143	2.9	3S9P	230	LVDS-4 40PIN FPC	-20 ~-60.°
		HG101WS042	10.1 TFT WSVGA LVDS interface	1024*600	6 o'clock	222.72*125.28	235*143	2.8	3S8P	180	LVDS-4 40PIN FPC	-20 ~-70.°
		HG101WS043	10.1 TFT WSVGA MIPI interface	1024*600	6 o'clock	222.72*125.28	234.9*143	5	6S7P	1000	MIPI-4 30PIN FPC	-20 ~-70.°
		HG101WS045-V1	10.1 TFT WSVGA RGB interface	1024*600	ALL	222.72*125.28	225*143	5	6S7P	550	RGB-24 50PIN FPC	-20 ~-60.°
		HG101WS046	10.1 TFT WSVGA LVDS interface	1024*600	ALL	222.72*125.28	235*143	5	6S7P	1000	LVDS-4 40PIN FPC	-10 ~-50.°
		HG101HD005	10.1 TFT HD720 LVDS interface	1280*720	ALL	224.64*126.36	235*143	4.3	6S7P	400	LVDS-4 60PIN FPC	-20 ~-70.°
		HG101HD008	10.1 TFT HD720 LVDS interface	1280*720	ALL	224.64*126.36	235*143	2.9	3S9P	400	LVDS-4 40PIN FPC	-20 ~-60.°
		HG101HD011	10.1 TFT HD720 LVDS interface	1280*720	ALL	223.68*125.82	233.9*141.4	6.47	8S4P	1000	LVDS-4 50PIN ZIF	-30 ~-85.°
		HG101WX008	10.1 TFT WXGA LVDS interface	1280*800	ALL	216.96*135.60	229.02*148.66	2.41	3S13P	1000	LVDS-4 40PIN ZIF	0 ~-50.°
		HG101WX010	10.1 TFT WXGA LVDS interface	1280*800	ALL	216.96*135.60	229.46*149.10	4.7	6S6P	1000	LVDS-4 40PIN ZIF	-20 ~-70.°
		HG101WX012	10.1 TFT WXGA LVDS interface	1280*800	ALL	216.96*135.60	229.46*149.10	4.7	4S8P	1000	LVDS-4 40PIN ZIF	-20 ~-70.°
		HG101WX019	10.1 TFT WXGA LVDS interface	1280*800	ALL	216.96*135.60	229.5*149.1	2.48	6S6P	450	LVDS-4 40PIN I-PEX	-20 ~-70.°
		HG101WX021	10.1 TFT WXGA LVDS interface	1280*800	ALL	216.96*135.60	229.5*149.1	4.8	6S6P	1000	LVDS-4 40PIN I-PEX	-20 ~-70.°
		HG101WX026	10.1 TFT WXGA LVDS interface	1280*800	ALL	216.96*135.60	229.46*149.20	3.76	12V boost	300	LVDS-3 40PIN ZIF	-20 ~-60.°
		HG101WX041	10.1 TFT WXGA LVDS interface	1280*800	ALL	216.96*135.60	228.2*148.85	2.8	12V boost	430	LVDS-4 40PIN I-PEX	-20 ~-70.°
		HG101WX049	10.1 TFT WXGA EDP interface	1280*800	ALL	216.96*135.60	228.3*149.05	2.4	12V boost	300	EDP-1 30PIN I-PEX	-20 ~-60.°
		HG101WX061	10.1 TFT WXGA LVDS interface	1280*800	ALL	216.96*135.60	229.46*148.1	2.8Max	12V boost	350	LVDS-4 40PIN ZIF	-20 ~-70.°
		HG101WX063	10.1 TFT WXGA LVDS interface	1280*800	ALL	216.96*135.60	229.46*149.10	4.7	9S4P	1000	LVDS-4 40PIN ZIF	-20 ~-70.°
		HG101FH005	10.1 TFT FHD LVDS dual-channel interface	1920*1080	ALL	223.488*125.712	237.69*142.7	7.2	8S4P	1100	LVDS-8 50PIN ZIF	-40 ~-85.°
		HG101WU032-V1	10.1 TFT WUXGA MIPI interface	1920*1200	ALL	216.81*135.5	228.3*149.05	2.7	8S6P	400	MIPI-4 34PIN ZIF	-20 ~-70.°
		HG101WU035	10.1 TFT WUXGA EDP interface	1920*1200	ALL	216.81*135.5	228.22*148.32	5.35	12V boost	410	EDP-2 30PIN I-PEX	-20 ~-60.°
		HG101WU040	10.1 TFT WUXGA EDP interface	1920*1200	ALL	216.81*135.5	228.3*149.05	2.7	7S7P	400	EDP-2 30PIN I-PEX	-20 ~-70.°
		HG101WU063	10.1 TFT WUXGA LVDS dual-channel interface	1920*1200	ALL	216.81*135.5	229.46*149.10	4.8	6S6P	1500	LVDS-8 45PIN ZIF	-20 ~-70.°
		HG101WU065	10.1 TFT WUXGA MIPI interface	1920*1200	ALL	216.81*135.5	228.3*149.05	2.7	8S6P	400	MIPI-4 34PIN ZIF	-20 ~-70.°
		HG101WU066	10.1 TFT WUXGA LVDS dual-channel interface	1920*1200	ALL	216.81*135.5	229.46*149.10	4.8	6S6P	1000	LVDS-8 45PIN ZIF	-20 ~-70.°
		HG101WU067	10.1 TFT WUXGA LVDS dual-channel interface	1920*1200	ALL	216.81*135.5	228.5*149.3	4.58	9S4P	1000	LVDS-8 45PIN ZIF	-20 ~-70.°
		HG101WU068	10.1 TFT WUXGA EDP interface	1920*1200	ALL	216.81*135.5	229.2*149.8	4.5	9S5P	1000	EDP-2 30PIN I-PEX	-20 ~-70.°
		HG101WU071	10.1 TFT WUXGA LVDS dual-channel interface	1920*1200	ALL	217.44*135.9	228.5*149.3	5.08	9S4P	1000	LVDS-8 45PIN ZIF	-20 ~-70.°
		HG101WU072-V1	10.1 TFT WUXGA LVDS dual-channel interface	1920*1200	ALL	216.81*135.5	228.5*149.3	4.58	9S4P	1000	LVDS-8 45PIN ZIF	-20 ~-70.°
		HG101WU073	10.1 TFT WUXGA EDP interface	1920*1200	ALL	216.58*135.36	228.1*148.9	2.8	10S6P	1000	EDP-2 30PIN I-PEX	-20 ~-70.°
		HG101WU074	10.1 TFT WUXGA MIPI interface	1920*1200	ALL	216.08*135.5	228.56*149.06	4.5	9S4P	1000	MIPI-4 34PIN ZIF	-40 ~-80.°
		HG101WU075	10.1 TFT WUXGA LVDS dual-channel interface	1920*1200	ALL	217.728*136.08	229.46*149.10	4.8	10S4P	1000	LVDS-8 45PIN ZIF	-30 ~-80.°
		HG101WU076	10.1 TFT WUXGA LVDS dual-channel interface	1920*1200	ALL	217.728*136.08	225.13*148.34	2.8	4S16P	1000	LVDS-8 45PIN ZIF	-40 ~-80.°
		HG101WU078	10.1 TFT WUXGA LVDS dual-channel interface	1920*1200	ALL	216.8064*125.504	228.3*149	2.5	7S7P	500	LVDS-8 45PIN ZIF	-20 ~-70.°
		HG101WU079	10.1 TFT WUXGA LVDS dual-channel interface	1920*1200	ALL	216.81*135.5	228.5*149.3	4.58	6S6P	1000	LVDS-8 45PIN ZIF	-20 ~-70.°
		HG101WU080	10.1 TFT WUXGA EDP interface	1920*1200	ALL	217.728*136.08	228.2*149	2.35	12V boost	1000	EDP-2 30PIN I-PEX	-40 ~-70.°
		HG101WQ004	10.1 TFT WQXGA EDP interface	2560*1600	ALL	216.576*135.36	221.85*145.15	2	8S6P	400	EDP-4 40PIN I-PEX	-40 ~-50.°
		HG101WQ005	10.1 TFT WQXGA MIPI dual-channel interface	2560*1600	ALL	216.576*135.36	221.85*145.15	2	8S6P	400	MIPI-8 40PIN ZIF	0 ~-50.°
		HG101WQ006	10.1 TFT WQXGA MIPI dual-channel interface	2560*1600	ALL	216.576*135.36	228.66*148.3	4.56	10S4P	1000	MIPI-8 40PIN ZIF	-20 ~-70.°
	10.25	HG103WS006	10.25 TFT HD480 LVDS interface	1280*480	ALL	243.84*91.44	258.6*107	6.32	9S3P	1000	LVDS-4 60PIN FPC	-30 ~-85.°
		HG103HD002	10.25 TFT FHD720 LVDS dual-channel interface	1920*720	ALL	243.648*91.368	265.2*109.8	5.6	9S4P	500	LVDS-8 50PIN FPC	-20 ~-70.°
	10.4	HG104VG002	10.4 TFT VGA/LVDS interface	640*480	12 o'clock	211.2*158.4	230*180.2	10.5	24V boost	1200~1500	LVDS-4 20PIN FI-S	-20 ~-70.°
		HG104SV004	10.4 TFT SVGA RGB interface	800*600	12 o'clock	211.2*158.4	228.5*175.5	5	3S12P	400	RGB-24 60PIN FPC	-20 ~-60.°
		HG104SV005	10.4 TFT SVGA RGB interface	800*600	12 o'clock	211.2*158.4	228.5*175.5	5	3S12P	400	RGB-24 60PIN FPC	-20 ~-60.°
		HG104SV006	10.4 TFT SVGA LVDS interface	800*600	12 o'clock	211.2*158.4	236*176.9	5.6	6S4P	350	LVDS-4 20PIN FI-S	-20 ~-70.°
		HG104SV007	10.4 TFT SVGA RGB interface	800*600	6 o'clock	211.2*158.4	228.5*175.5	6	3S12P	350	RGB-24 60PIN FPC	-20 ~-70.°

		HG104XG003	10.4 TFT XGA LVDS interface	1024*768	ALL	210.43*157.82	238.6*175.8	7.47	8S4P	600	LVDS-4 30PIN F-I-S	-30 °~-80 °
		HG104XG004	10.4 TFT XGA LVDS interface	1024*768	ALL	210.43*157.82	238.6*175.8	7.47	11S4P	1000	LVDS-4 30PIN F-I-S	-30 °~-80 °
		HG104XG007	10.4 TFT XGA LVDS interface	1024*768	ALL	210.43*157.82	225.9*174.6	8	8S4P	800	LVDS-4 60PIN FPC	-30 °~-80 °
		HG104XG008	10.4 TFT XGA LVDS interface	1024*768	ALL	210.43*157.82	225.9*174.3	8	11S4P	1000	LVDS-4 30PIN F-I-S	-30 °~-80 °
11.2		HG112WQ002	11.2 AMOLED WQXGA MIPI dual-channel interface	2560*1536	ALL	244.22*146.53	249.22*154.08	0.96	AMOLED	450~600	MIPI-8 51PIN ZIF	-40 °~-70 °
11.5		HG115WQ001	11.5 AMOLED WQXGA MIPI dual-channel interface	2560*1600	ALL	247.68*154.80	251.58*159.94	1.8	AMOLED	350	MIPI-8 61PIN ZIF	-20 °~-70 °
11.6		HG116FH010	11.6 TFT FHD backlit display with EDP interface	1920*1080	ALL	256.32*144.18	267.72*164.42	5.85	10S4P	500	EDP-2 30PIN I-PEX	-20 °~-50 °
		HG116FH014	11.6 TFT FHD backlit display with EDP interface	1920*1080	ALL	256.32*144.18	263.4*157.52	2.6	9S5P	250	EDP-2 30PIN I-PEX	-20 °~-70 °
		HG116FH014-V1	11.6 TFT FHD backlit display with EDP interface	1920*1080	ALL	256.32*144.18	263.46*157.28	2.8	8S5P	250	EDP-2 30PIN I-PEX	0 °~-50 °
		HG116FH015	11.6 TFT FHD backlit EDP interface	1920*1080	ALL	256.32*144.18	267.72*164.42	5.75	10S5P	1000	EDP-2 30PIN I-PEX	-20 °~-70 °
		HG116FH016	11.6 TFT FHD backlit display with EDP interface	1920*1080	ALL	256.32*144.18	267.72*164.42	6.1	10S4P	500	EDP-2 30PIN I-PEX	-20 °~-70 °
12.1		HG121SV002	12.1 TFT SVGA LVDS interface	800*600	6 o'clock	246*184.5	279*209	5.73~9	9S2P	400	LVDS-4 20PIN F-I-S	-20 °~-70 °
		HG121XG001	12.1 TFT XGA LVDS interface	1024*768	ALL	245.76*184.32	260.5*204	6.7	TBD	500	LVDS-4 20PIN F-I-S	-20 °~-70 °
		HG121XG002	12.1 TFT XGA LVDS interface	1024*768	ALL	245.76*184.32	260.5*204	6.05~7.2	11S4P	600	LVDS-4 20PIN F-I-S	-30 °~70 °
		HG121XG003	12.1 TFT XGA LVDS interface	1024*768	ALL	245.76*184.32	260.5*204	6.05~7.2	12S4P	1000	LVDS-4 20PIN F-I-S	-30 °~70 °
		HG121XG005	12.1 TFT XGA LVDS interface	1024*768	ALL	245.76*184.32	260.5*204	6.7~8.7	12V boost	500	LVDS-4 20PIN F-I-S	-20 °~-70 °
		HG121XG006	12.1 TFT XGA LVDS interface	1024*768	6 o'clock	245.76*184.32	279*209	6~9	12V boost	350	LVDS-4 20PIN F-I-S	-20 °~-70 °
		HG121WX001	12.1 TFT WXGA LVDS interface	1280*800	ALL	261.12*163.2	278.0*184.0	9.29	TBD	300	LVDS-4 30PIN F-I-S	-30 °~-85 °
		HG121WX003	12.1 TFT WXGA LVDS interface	1280*800	ALL	261.12*163.2	278.0*184.0	7.1~10.2	9S4P	900	LVDS-4 40PIN ZIF	-30 °~-80 °
		HG121WX006	12.1 TFT WXGA LVDS interface	1280*800	ALL	261.12*163.2	278.0*184.0	7.1~10	12V boost	1000	LVDS-4 30PIN F-I-S	-30 °~-80 °
		HG121WX009	12.1 TFT WXGA LVDS interface	1280*800	ALL	261.12*163.2	278*184	6.63	8S6P	750	LVDS-4 30PIN ZIF	-20 °~-70 °
		HG121WX010	12.1 TFT WXGA LVDS interface	1280*800	ALL	261.12*163.2	276.6*179.5	5.7	8S6P	600	LVDS-4 40PIN ZIF	-10 °~-60 °
		HG121WX011	12.1 TFT WXGA LVDS interface	1280*800	ALL	261.12*163.2	277.7*180.6	6~7.5	8S6P	1000	LVDS-4 40PIN ZIF	-10 °~-60 °
		HG121WX012	12.1 TFT WXGA MIPI interface	1280*800	ALL	261.12*163.20	267.61*174.98	4.03	6S10P	600	MIPI-4 30PIN ZIF	-20 °~-70 °
		HG123HD008-V1	12.3 TFT FHD720 LVDS dual-channel interface	1920*720	ALL	292.032*109.512	308.7*127.2	6.2~10.3	TBD	900	LVDS-8 50PIN FPC	-30 °~-85 °
		HG123HD009	12.3 TFT FHD720 LVDS dual-channel interface	1920*720	ALL	292.032*109.512	306.3*125.3	7	8S6P	700	LVDS-8 50PIN ZIF	-30 °~-85 °
		HG123HD010	12.3 TFT FHD720 LVDS dual-channel interface	1920*720	ALL	292.03*109.51	310.03*128.03	6.52	8S6P	600	LVDS-8 50PIN ZIF	-20 °~-70 °
		HG123HD011	12.3 TFT FHD720 LVDS dual-channel interface	1920*720	ALL	292.032*109.512	310*128	6.5~10.65	9S6P	1000	LVDS-8 50PIN ZIF	-30 °~-80 °
		HG123HD012	12.3 TFT FHD720 LVDS dual-channel interface	1920*720	ALL	292.032*109.512	309.5*127	5.8~10	8S6P	700	LVDS-8 50PIN ZIF	-20 °~-70 °
12.5		HG125FH002	12.5 TFT FHD direct-sequential EDP interface	1920*1080	ALL	276.48*155.52	282.4*179.32	2.3	9S3P	300	EDP-2 30PIN I-PEX	0 °~-50 °
12.6		HG126WQ001	12.6 AMOLED WQXGA MIPI dual-channel interface	2560*1600	ALL	271.4112 * 169.632	275.41*175.23	0.902	AMOLED	400	MIPI-4 51PIN*2 ZIF	-40 °~-70 °
		HG126WQ002	12.6 AMOLED WQXGA MIPI dual-channel interface	2560*1600	ALL	271.4112 * 169.632	275.411*175.232	1.01	AMOLED	600	MIPI-4 51PIN*2 ZIF	-40 °~-70 °
12.8		HG128FH002	12.8 TFT FHD LVDS dual-channel interface	1920*1080	ALL	283.392*159.408	294*175	5~12	9S7P	650	LVDS-8 50PIN ZIF	-20 °~-70 °
		HG128FH003	12.8 TFT FHD LVDS dual-channel interface	1920*1080	ALL	283.392*159.408	294.4*175	6.5	12S4P	700	LVDS-8 50PIN ZIF	-30 °~-85 °
13.3		HG133FH016	13.3 TFT FHD backlit display with EDP interface	1920*1080	ALL	293.76*165.24	307.6*183.05	5.5	9S6P	600	EDP-2 30PIN I-PEX	-20 °~-70 °
		HG133FH017-V1	13.3 TFT FHD direct-sequential EDP interface	1920*1080	ALL	293.76*165.24	300.26*187.45	2.4	9S4P	300	EDP-2 30PIN I-PEX	0 °~-50 °
		HG133FH019	13.3 TFT FHD On-Cell Back-Folded EDP Interface	1920*1080	ALL	293.76*165.24	300.26*177.47	3	8S4P	250	EDP-2 40PIN I-PEX	0 °~-50 °
		HG133FH020	13.3 TFT FHD backlit display with EDP interface	1920*1080	ALL	293.76*165.24	307.6*183.85	5.5	9S6P	1000	EDP-2 30PIN I-PEX	-20 °~-70 °
		HG133FH021	13.3 TFT FHD backlit display with EDP interface	1920*1080	ALL	293.76*165.24	300.26*177.39	2.5	8S7P	250	EDP-2 30PIN I-PEX	0 °~-50 °
		HG133FH022	13.3 AMOLED FHD back-curved display with EDP interface	1920*1080	ALL	293.76*165.24	297.46*183.99	1.254	AMOLED	400	EDP-2 30PIN I-PEX	-40 °~-70 °
		HG133FH023	13.3 TFT FHD direct-sequential EDP interface	1920*1080	ALL	293.76*165.24	300.26*188.25	2.4	9S4P	300	EDP-2 30PIN I-PEX	0 °~-50 °
		HG133FH025	13.3 TFT FHD backlit display with EDP interface	1920*1080	ALL	293.76*165.24	300.2*178.3	2.8	10S6P	500	EDP-2 30PIN I-PEX	-20 °~-70 °
		HG133FH027	13.3 TFT FHD backlit display with EDP interface	1920*1080	ALL	293.76*165.24	307.6*183.05	5.5	10S5P	1000	EDP-2 30PIN I-PEX	-20 °~-70 °
		HG133FH028	13.3 TFT FHD backlit display with EDP interface	1920*1080	ALL	293.76*165.24	300.26*177.39	2.6	9S4P	260	EDP-2 30PIN I-PEX	0 °~-50 °
13.6		HG133WQ005	13.3 TFT FHD backlit display with EDP interface	2560*1600	ALL	286.08*178.8	289.58*186.5	1.85	7S12P	500	EDP-2 40PIN I-PEX	0 °~-50 °
		HG136WQ003	13.3 TFT WQXGA backlit display with EDP interface	2560*1600	ALL	286.464*179.04	292.52*189.79	2.8	8S6P	200	EDP-4 30PIN I-PEX	0 °~-50 °
14.0		HG140FH005	13.92 TFT FHD backlit display with EDP interface	1920*1080	ALL	308.16*173.34	317.52*186.76	4.9	8S6P	1000	EDP-2 30PIN I-PEX	-30 °~-80 °
		HG140FH006	13.97 TFT FHD direct-sequential EDP interface	1920*1080	ALL	309.312*173.988	315.81*196.98	2.95	6S9P	650	EDP-2 30PIN I-PEX	0 °~-50 °
		HG140FH007	13.92 TFT FHD backlit display with EDP interface	1920*1080	ALL	308.16*173.34	317.46*186.7	5.15	8S6P	1000	EDP-4 30PIN I-PEX	-30 °~-80 °
		HG140FH008	14.0 TFT FHD direct-sequential EDP interface	1920*1080	ALL	309.3*173.99	315.9*186.05	3	9S4P	250	EDP-2 30PIN I-PEX	0 °~-50 °
		HG140QF002	14.0 TFT QFHD Direct-Output EDP Interface	3840*2160	ALL	309.312*173.99	315.01*195.67	2.3	10S8P	500	EDP-4 40PIN I-PEX	0 °~-50 °
15		HG150XG005	15.0 TFT XGA LVDS interface	1024*768	6 o'clock	304.128*228.096	326.5*253.5	10	TBD	350	LVDS-4 20PIN F-I-S	-0 °~-65 °
		HG150XG006	15.0 TFT XGA LVDS interface	1024*768	12 o'clock	304.128*228.096	326.5*253.5	10	TBD	300	LVDS-4 20PIN F-I-S	-20 °~-70 °
		HG150XG008	15.0 TFT XGA LVDS interface	1024*768	ALL	304.1*228.1	326.5*253.5	10.8	TBD	2000	LVDS-4 20PIN F-I-S	-30 °~-70 °
		HG150XG009	15.0 TFT XGA LVDS interface	1024*768	ALL	304.1*228.1	326.5*253.5	13.25	TBD	1800	LVDS-4 20PIN F-I-S	-30 °~-70 °
		HG150UG002	15.0 1600*1200 LVDS interface	1600*1200	ALL	304.8*228.6	317.4*242	5.9	10S4P	500	LVDS-8 40PIN I-PEX	-20 °~-70 °
		HG156FH012	15.6 TFT FHD direct-sequential EDP interface	1920*1080	ALL	344.16*193.59	350.66*216.25	3.05	10S4P	800	EDP-2 30PIN I-PEX	-20 °~-70 °
		HG156FH013	15.6 TFT FHD backlit display with LVDS dual-channel interface	1920*1080	ALL	344.16*193.59	363.80*215.90	9.7	12V boost	1000	LVDS-8 30PIN F-I-X	-30 °~-85 °
		HG156FH014	15.6 TFT FHD direct-mount screw hole – EDP interface	1920*1080	ALL	344.16*193.59	359.5*223.8	3.2	10S4P	250	EDP-2 30PIN I-PEX	0 °~-50 °
		HG156FH015	15.6 TFT FHD direct-sequential EDP interface	1920*1080	ALL	344.16*193.59	350.66*216.25	3.05	8S8P	500	EDP-2 30PIN I-PEX	0 °~-50 °
		HG156FH018	15.6 TFT FHD direct-sequential EDP interface	1920*1080	ALL	344.16*193.59	359.5*223.8	3.2	9S6P	300	EDP-2 30PIN I-PEX	0 °~-50 °
		HG156FH020	15.6 TFT FHD backlit display with LVDS dual-channel interface	1920*1080	ALL	344.16*193.59	363.7*215.7	12	12S4P	850	LVDS-8 50PIN ZIF	-30 °~-85 °
		HG156FH021	15.6 TFT FHD direct-sequential EDP interface	1920*1080	ALL	344.16*193.59	359.4*211.7	5.5	10S10P	1200	EDP-2 30PIN I-PEX	-20 °~-70 °
		HG156FH022	15.6 TFT FHD direct-sequential EDP interface	1920*1080	ALL	344.16*193.59	350.66*216.15	3	8S5P	300	EDP-2 30PIN I-PEX	0 °~-50 °
		HG156FH023	15.6 TFT FHD backlit display with LVDS dual-channel interface	1920*1080	ALL	344.16*193.59	351.86*206.33	3.2	9S6P	250	LVDS-8 40PIN I-PEX	-20 °~-70 °
		HG156FH025	15.6 TFT FHD direct-sequential EDP interface	1920*1080	ALL	344.16*193.59	359.6*221.83	5.35	10S6P	1000	EDP-2 30PIN I-PEX	0 °~-50 °
		HG156FH026-V1	15.6 TFT FHD backlit display with EDP interface	1920*1080	ALL	344.16*193.59	350.66*205.24	3	4S18P	1000	EDP-2 30PIN I-PEX	-30 °~-70 °

Rectangular Display	15.6	HG156FH027	15.6 TFT FHD backlit display with EDP interface	1920*1080	ALL	344.16*193.59	350.66*205.78	2.89	10S6P	800	EDP-2 30PIN I-PEX	0 °~50 °	
		HG156FH028	15.6 TFT FHD backlit display with EDP interface	1920*1080	ALL	344.16*193.59	360*212.3	6.4	10S6P	1000	EDP-2 30PIN I-PEX	0 °~50 °	
		HG156FH029	15.6 TFT FHD direct-sequential EDP interface	1920*1080	ALL	344.16*193.59	350.66*205.24	3	4S16P	700	EDP-2 30PIN I-PEX	0 °~50 °	
		HG156FH030	15.6 AMOLED FHD direct-connection EDP interface	1920*1080	ALL	344.21*193.62	347.92*212.77	1.245	AMOLED	400	EDP-2 30PIN I-PEX	-40 °~70 °	
		HG156FH031	15.6 TFT FHD backlit display with LVDS dual-channel interface	1920*1080	ALL	344.16*193.59	360*212.3	5.7	11S6P	1000	LVDS-8 40PIN I-PEX	0 °~50 °	
		HG156FH033	15.6 TFT FHD backlit display with EDP interface	1920*1080	ALL	344.16*193.59	360*214.19	5.7	10S6P	1000	EDP-2 30PIN I-PEX	-20 °~70 °	
		HG156FH035	15.6 TFT FHD backlit display with LVDS dual-channel interface	1920*1080	ALL	344.16*193.59	351.86*206.33	3.2	9S6P	250	LVDS-8 40PIN I-PEX	0 °~50 °	
		HG156FH036	15.6 TFT FHD backlit display with EDP interface	1920*1080	ALL	344.16*193.59	351.74*205.69	2.84	11S6P	450	EDP-2 51PIN I-PEX	0 °~50 °	
		HG156FH037	15.6 TFT FHD backlit display with EDP interface	1920*1080	ALL	344.16*193.59	350.66*205.25	3	11S5P	500	EDP-2 30PIN I-PEX	0 °~50 °	
		HG156FH038	15.6 TFT FHD backlit display with LVDS dual-channel interface	1920*1080	ALL	345.6*194.4	363.8*215.9	8.1	10S4P	500	LVDS-8 40PIN I-PEX	-20 °~70 °	
		HG156FH039	15.6 TFT FHD backlit display with EDP interface	1920*1080	ALL	344.16*193.59	350.66*205.24	3	9S6P	250	EDP-2 30PIN I-PEX	0 °~50 °	
	HG156WQ002	15.6 TFT WQHD EDP interface	2560*1440	ALL	344.2176*193.6224	350.66*216.14	3.2	10S5P	300	EDP-4 40PIN I-PEX	0 °~50 °		
	16	HG160WQ002	16.0 TFT WQXGA backlit display with EDP interface	2560*1600	ALL	344.68*215.42	349.68*224.42	2.45	12S6	500	EDP-4 40PIN I-PEX	0 °~50 °	
		HG160WQ004	16.0 TFT WQXGA backlit display with EDP interface	2560*1600	ALL	344.68*215.42	349.68*224.42	2.45	10S8P	500	EDP-4 40PIN I-PEX	0 °~50 °	
		HG160WQ006	16.0 TFT WQXGA backlit display with EDP interface	2560*1600	ALL	344.6784*215.424	349.68*224.42	2.45	11S8P	500	EDP-4 40PIN I-PEX	0 °~50 °	
	17	HG170SX003	17.0 TFT SXGA LVDS dual-channel interface	1280*1024	ALL	337.920*270.336	358.5*296.5	8.7	12S4P	250	LVDS-8 30PIN FI-X	-20 °~60 °	
		HG170SX004	17.0 TFT SXGA LVDS dual-channel interface	1280*1024	ALL	337.920*270.336	358.5*296.5	8.7	12S4P	500	LVDS-8 30PIN FI-X	-20 °~70 °	
		HG170SX006	17.0 TFT SXGA LVDS dual-channel interface	1280*1024	6/12 o'clock	337.920*270.336	358.5*296.5	10.3	9S4P	250	LVDS-8 30PIN FI-X	-20 °~60 °	
		HG170SX007	17.0 TFT SXGA LVDS dual-channel interface	1280*1024	ALL	337.920*270.336	358.5*296.5	12.45	10S4P	800	LVDS-8 30PIN FI-X	-30 °~85 °	
	17.3	HG173FH002-V0	17.3 TFT FHD direct-sequential EDP interface	1920*1080	ALL	381.89*214.81	389.95*227.07	3	5S16P	1000	EDP-2 30PIN I-PEX	-20 °~70 °	
		HG173FH003	17.3 TFT FHD backlit display with EDP interface	1920*1080	ALL	381.89*214.81	389.89*227.61	3.2	8S12P	480	EDP-2 45PIN ZIF	0 °~50 °	
		HG173FH005	17.3 TFT FHD direct-sequential EDP interface	1920*1080	ALL	381.888*214.812	389.888*238.312	5	5S16P	500	EDP-2 30PIN I-PEX	0 °~50 °	
		HG173WQ002	17.3TFT WQHD direct-attached EDP interface	2560*1440	ALL	381.8496*214.7904	389.89*227.01	3.5	10S6P	400	EDP-4 40PIN I-PEX	-20 °~50 °	
	18.5	HG185HD002	18.5 TFT HD LVDS interface	1366*768	ALL	409.8* 230.4	430*254	9.5	16S4P*2	1100	LVDS-4 30PIN FI-X	0 °~50 °	
		HG185FH005	18.5 TFT FHD EDP interface	1920*1080	ALL	408.96*230.04	430.4*254.6	13.5	9S6P	400	EDP-2 40PIN I-PEX	-20 °~70 °	
		HG185FH006	18.5 TFT FHD LVDS dual-channel interface	1920*1080	ALL	408.96*230.04	430.4*254.6	13.75	4S16P	500	LVDS-8 30PIN FI-X	-30 °~80 °	
		HG185FH007	18.5 TFT FHD LVDS dual-channel interface	1920*1080	ALL	408.96*230.04	417.96*243.84	3.2	9S11P	300	LVDS-8 30PIN FI-X	0 °~50 °	
	19	HG190SX002	19.0 TFT SXGA LVDS dual-channel interface	1280*1024	ALL	374.784*299.8272	396*324	12.5	TBD	800	LVDS-8 30PIN FI-S	-20 °~70 °	
		HG190SX003	19.0 TFT SXGA LVDS dual-channel interface	1280*1024	ALL	376.32*301.056	396*323.6	11.5	TBD	1000	LVDS-8 30PIN FI-X	-15 °~65 °	
		HG190SX005	19.0 TFT SXGA LVDS dual-channel interface	1280*1024	ALL	374.784*299.8272	396*324	9.9	4S11P	450	LVDS-8 30PIN DF14	-20 °~70 °	
	21.5	HG215FH002	21.5 TFT FHD LVDS dual-channel interface	1920*1080	ALL	476.64*268.11	496.6*292.2	8.2	15S3P	1000	LVDS-8 30PIN FI-X	0 °~50 °	
		HG215FH008	21.5 TFT FHD LVDS dual-channel interface	1920*1080	ALL	476.064*267.786	495.6*292.2	10.7	24S3P	500	LVDS-8 30PIN FI-X	0 °~50 °	
		HG215FH009	21.5 TFT FHD LVDS dual-channel interface	1920*1080	ALL	476.64*268.11	495.6*292.2	10.7	15S4P	300	LVDS-8 30PIN FI-X	-10 °~50 °	
		HG215FH010	21.5 TFT FHD LVDS dual-channel interface	1920*1080	ALL	476.64*268.11	495.6*292.2	10.7	17S4P	500	LVDS-8 30PIN FI-X	-20 °~80 °	
		HG215FH011	21.5 TFT FHD LVDS dual-channel interface	1920*1080	ALL	476.64*268.11	495.6*292.2	10.7	16S3P	1000	LVDS-8 30PIN FI-X	-20 °~70 °	
		HG215FH012	21.5 TFT FHD LVDS dual-channel interface	1920*1080	ALL	476.64*268.11	495.6*292.2	9	18S4P	250	LVDS-8 30PIN FI-X	-5 °~45 °	
	23	HG230FH002	23.0 TFT FHD LVDS dual-channel interface	1920*1080	ALL	509.184*286.4	533.2*312	10.5	TBD	300	LVDS-8 30PIN FI-X	0 °~50 °	
	23.8	HG238FH002	23.8 TFT FHD LVDS dual-channel interface	1920*1080	ALL	527.04*296.46	535*313	12.45	20S4P	250	LVDS-8 30PIN FI-X	0 °~50 °	
		HG238FH005	23.8 TFT FHD LVDS dual-channel interface	1920*1080	ALL	527.04*296.46	543*317.4	11.1	16S4P	550	LVDS-8 30PIN FI-X	0 °~50 °	
		HG238FH006	23.0 TFT FHD LVDS dual-channel interface	1920*1080	ALL	527.04*296.46	536.69*310.41	3.6	5S23P	260	LVDS-8 30PIN FI-X	0 °~50 °	
	27	HG270FH002	27.0 TFT FHD LVDS dual-channel interface	1920*1080	ALL	601.29*340.15	630*368.2	13	17S7P	500	LVDS-8 30PIN FI-X	0 °~50 °	
		HG270QF002	27.0 TFT QFHD EDP interface	3840*2160	ALL	596.74*335.66	621.8*360.6	13.5	18S4P	250	EDP-4 30PIN I-PEX	0 °~50 °	
	32	HG320FH002	32.0 TFT FHD LVDS dual-channel interface	1920*1080	ALL	698.4*392.85	716.2*415.05	8.95	20S6P	400	LVDS-8 51PIN UJU	0 °~50 °	
	43	HG430FH002	43.0 TFT FHD LVDS dual-channel interface	1920*1080	ALL	940.896*529.254	961*549.2	14.1	24S4P	800	LVDS-8 51PIN UJC	0 °~50 °	
		HG430FH005	43.0 TFT FHD LVDS dual-channel interface	1920*1080	ALL	940.896*529.254	961.7*550.1	11.7	24V boost	400	LVDS-8 51PIN UJC	0 °~50 °	
	49	HG490FH002	48.5 TFT FHD LVDS dual-channel interface	1920*1080	ALL	1073.8*604	1090.4*621.3	27.355	23S4P	400	LVDS-8 51PIN UJC	0 °~50 °	
	55	HG550FH007	55 TFT FHD LVDS dual-channel interface	1920*1080	ALL	1209.6*680.4	1230.4*706.8	14.1	26S4P	400	LVDS-8 51PIN UJU	0 °~50 °	
		HG550QF005	55 TFT QFHD LVDS dual-channel interface	3840*2160	ALL	1209.6*680.4	1232.8*703.6	17	18S4P	800	LVDS-8 51PIN ZIF	0 °~50 °	
	Square display	0.85	HG008SQ002	0.85 TFT 128*128 SPI interface	128*128	ALL	15.2064*15.2064	17.58*20.82	1.46	1S1P	260	SPI-4 12-pin FPC soldering	-20 °~70 °
		4	HG040HS002	4.0 TFT 480*480 MIPI interface	480*480	ALL	71.86*70.18	74.66*76.54	2.1	4S2P	350	MIPI-2 30PIN FPC	-20 °~60 °
HG040HS003			4.0 TFT 480*480 MIPI interface	480*480	ALL	71.86*70.18	74.66*76.54	2.1	4S2P	350	MIPI-2 30PIN FPC	-20 °~60 °	
HG040HS005			4.0 TFT 480*480 RGB interface	480*480	ALL	71.86*70.18	74.66*76.54	2.1	4S2P	350	RGB-18 40PIN FPC	-20 °~60 °	
HG040HD003			3.95 TFT 720*720 MIPI interface	720*720	ALL	71.928*71.928	74.83*78.98	1.95	5S2P	300	MIPI-4 30PIN FPC	-20 °~70 °	
5		HG050VQ003	5.0 640*640 RGB/MIPI interface	640*640	ALL	89.28*89.28	94.68*97.83	2.24	5S4P	500	RGB/MIPI 61PIN ZIF	-30 °~80 °	
		HG050WS002	4.97 TFT 600*600 MIPI interface	600*600	ALL	89.28*89.28	95.08*99.50	2.7	3S6P	900	MIPI-4 40PIN FPC	-20 °~70 °	
5.6		HG056VQ002	5.6 TFT 640*644 LVDS interface	640*644	ALL	101.3*101.3	119.7*116.8	14~24.3	5S4P	1000	LVDS-4 40PIN FPC	-30 °~80 °	
8.5		HG085PA003 (with stud)	8.5 TFT 736*744 LVDS interface	736*744	ALL	152*152	173.7*173.8	16~26.3	6S5P	1000	LVDS-4 60PIN FPC	-30 °~80 °	
Round Screen		1.09	HG011QV002	1.09 TFT 240*240 SPI interface	240*240	ALL	27.79*32.4	30.59*32.98	1.65	1S2P	350	SPI-4 8PIN FPC	-20 °~70 °
	1.19	HG012HV002	1.19 AMOLED 390*390 MIPI interface	390*390	ALL	30.42*30.42	33.22*33.75	0.95	AMOLED	1000	MIPI-1 20PIN	-20 °~70 °	
	1.54	HG015HS003	1.54 AMOLDE 480*480 QSPI Interface	480*480	ALL	41.52*41.54	39.52*39.12	0.2	AMOLED	1000	QSPI 24PIN	-20 °~70 °	
	1.60	HG016HV002	1.6 TFT 400*400 SPI interface	400*400	ALL	39.84*39.84	42.94*45.89	1.6	1S3P	340	SPI 14PIN FPC	-20 °~70 °	
	1.60	HG016HV003	1.6 TFT (400*400) with QSPI interface	400*400	ALL	39.84*39.84	42.94 × 45.87	1.05	1S2P	TBD	QSPI 21PIN FPC	-20 °~70 °	
	1.73	HG017EG002	1.73 AMOLED 466*466 MIPI interface	466*466	ALL	43.76*43.76	46.35*45.63	0.78	AMOLED	700	MIPI-2 24PIN BTB	-10 °~60 °	
	1.8	HG018HV002	1.8 TFT 360*360 SPI interface	360*360	ALL	45.68*45.68	47.99*49.86	1.96	1S3P	350	SPI-4 15PIN FPC	-20 °~70 °	
	2.1	HG021HS002	2.1 TFT 480*480 RGB interface	480*480	ALL	53.28*53.28	56.18*59	2.35	1S4P	300	RGB-18 40PIN FPC	-20 °~70 °	
	2.8	HG028HS003	2.76 TFT 480*480 SPI/RGB interface	480*480	ALL	70.13*70.13	73.33*76.82	2.2	1S4P	300	SPI-3/RGB-18 40PIN FPC	-20 °~70 °	
		HG028HS005	2.76 TFT 480*480 MIPI interface	480*480	ALL	70.128*10.128	73.03*76.48	2.3	1S4P	700	MIPI-2 30PIN FPC	-20 °~70 °	

		HG028HS006-V1	2.76 TFT 480×480 MIPI interface	480*480	ALL	70.128*10.128	73.03*76.48	2.3	1S4P	300	MIPI-2 30PIN FPC	-20 ~-70 °
	3.4	HG034SV003	3.4 TFT 800*800 LVDS interface	800*800	ALL	87.6*87.6	94.9*96.95	2.4	4S2P	240	LVDS-4 30PIN FPC	-20 ~-70 °
		HG034SV004	3.4 TFT 800*800 MIPI Interface	800*800	ALL	87.6*87.6	96.6*99.79	3.8	5S2P	1500	MIPI-4 30PIN FPC	-20 ~-70 °
	3.5	HG035SV002 (Blade Screen)	3.54 TFT 844×640 RGB interface	800*640	ALL	90°72	97.6*83.79	4.05	6S2P	800	RGB-24 40PIN FPC	-20 ~-70 °
		HG035SV003 (Blade Screen)	3.54 TFT SPI/RGB Interface	844*640	ALL	90°72	97.6*83.8	4	6S2P	800	SPI-2/RGB-24 40PIN FPC	-20 ~-70 °
	4.0	HG040HH005	4.0 TFT 720×720 MIPI interface	720*720	ALL	101.52*101.52	107.6*111.87	3.8	5S2P	1000	MIPI-4 30PIN FPC	-20 ~-70 °
		HG040HH006	4.0 TFT 720×720 MIPI interface	720*720	ALL	101.52*101.52	106.81*110.27	2.25	4S2P	450	MIPI-4 30PIN FPC	-20 ~-70 °
		HG040HH007	4.0 TFT 720×720 MIPI interface	720*720	ALL	101.52*101.52	105.5*109.87	2.25	4S2P	500	MIPI-4 30PIN FPC	-20 ~-70 °
5		HG050QZ002	5.0 TFT 1080×1080 MIPI interface	1080*1080	ALL	127.008*127.008	136.531*132.208	1.98	6S1P	350	MIPI-4 50PIN BTB	-20 ~-60 °
Serial Dispalpy	2.4	HG3224T124_011N_A01	2.4-inch module + Serial Port Board	320*240	12 o'clock	48.96*36.72	74.42*44.02	7.95	TBD	300	4-PIN serial port	-20 ~-70 °
	2.8	HG3224T128_011N_A01	2.8-inch module + Serial Port Board	320*240	12 o'clock	57.6*43.2	85°51.24	5.9	TBD	300	4-PIN serial port	-20 ~-70 °
	4.3	HG4827X543-011R	4.3-inch module + Serial Port Board + Resistive Touchscreen	480*272	ALL	95.04*53.86	120°74	6.2	TBD	300	4-PIN serial port	-20 ~-70 °
		HG4827X543-011C	4.3-inch module + Serial Port Board + Capacitive Touchscreen	480*272	ALL	95.04*53.86	120°74	6.6	TBD	300	4-PIN serial port	-20 ~-70 °
		HG4827X543-11N	4.3-inch module + Serial Port Board	480*272	ALL	95.04*53.86	120°74	5	TBD	300	4-PIN serial port	-20 ~-70 °
		HG043HV006PZ02	4.3-inch TN display screen + Serial Port Board	480*272	12 o'clock	95.04*53.86	105.5°67.2	2.95	7S1P	300	4-PIN serial port	-20 ~-70 °
		HG8048X343_011C_I	4.3-inch + Serial Port Board	800*480	ALL	95.04*53.86	120°74	7	TBD	300	4-PIN serial port	-20 ~-70 °
	7	HG070YTD02C	7-inch + Serial Port Board	800*480	6 o'clock	154.1*85.9	194.4°105.20	11.3~17.5	TBD	300	4-PIN serial port	-20 ~-70 °
Special Model	8	HG080STD02C	8-inch + Serial Port Board	800*600	6 o'clock	162°121.5	199.4°148.8	7.6~16.9	TBD	300	4-PIN serial port	-20 ~-70 °
		HG-G16080SYG-01	FPC with thermistor; 0.55 mm LCD with attached heating plate	160*80	6 o'clock	38.38°23.18	49.9°35.6	5.75	2S2P	/	26-pin soldering	-40 ~-70 °
		HG-GB12864SBS-09	Module: Low-temperature LCD with rear backlight + PCB -- -30°C	128°64	6 o'clock	66.52°33.24	93°70	12	TBD	/	20-pin pin location	-30 ~-80 °
	3.2	HG032WV001	3.2/480×800 IPS display with heating pad – wide-temperature compatible product	480*800	ALL	41.76°69.6	47.8°80.7	3.3	7S1P	500min	RGB-24 45PIN FPC	-40 ~-70 °
	10.1	HG101WX019T03	The shielding effect of the 250-mesh industrial-grade electromagnetic shielding film is 50-6	1200*800	ALL	216.96°135.60	229.5°149.1	5.01	6S6P	450	LVDS-4 40PIN I-PEX	-20 ~-70 °