Result 1 (clipped subpath vertex). [Interval clipping, coordinate retraction]
Let n, a and m be natural numbers. Assume $a + m \leq n$ (`h`). Let v be a vertex in $\{0, \ldots, m + 1 - 1\}$. Then

$$c_{a,m}(a + v) = v.$$

Result 2 (clipping preserves order). [Interval clipping, monotonicity]
Let n, a and m be natural numbers. Let u and v be vertices in $\{0, \ldots, n + 1 - 1\}$. Assume $u \leq v$ (`ordered`). Then

$$c_{a,m}(u) \leq c_{a,m}(v).$$

Result 3 (clipped interval support). [Interval clipping, surviving interval support]
Let I be a type. Let n, a and m be natural numbers. Assume $a + m \leq n$ (`h`). Let L be a family of ordered interval labels indexed by I on vertices 0 through n. Let i be an element of I. Assume i belongs to $L|_{[a,a+m]}$ (`survives`). Let v be a vertex in $\{0, \ldots, m + 1 - 1\}$. Then

$$c_{a,m}(L.\mathrm{lower}(i)) \leq v \text{ and } v \leq c_{a,m}(L.\mathrm{upper}(i)) \text{ if and only if } i \text{ belongs to } L_{a+v}.$$

LLM-assisted statements and proofs (gpt-6, 2026-11-07). See PROVENANCE.md. Clipping uses truncated natural subtraction. These results establish interval support coordinates, not restriction of a basis.