National Information Technology Development Agency

Folio Administrator Guide

People and roles, settings, monitoring, deployment and troubleshooting

National Information Technology Development Agency · Office of the Director-General/CEO · DGO Digital Operations

Document	Folio Administrator Guide
Reference	NITDA-FOLIO-HO-2.3
Version	1.0
Date	20 October 2026
Classification	Internal
Built from	Repository dgoeaa/ECM_DOCS_DEV, commit c6e49d73
Build	v2026.10.20-1 (Workspace and Portal packages)
Register of record	Version 1.12.87: 0 open, 122 closed

Contents

8 · Administrator guide 3

8.1 Who administers what 3

8.2 People and access 3

8.3 Server-side settings: Flow Configuration 4

8.4 Monitoring 5

8.5 Deploying a new Workspace build 5

8.6 Security operations 6

8.7 Test data 6

8.8 Related procedures 7

10 · Troubleshooting 8

10.1 Cannot sign in 8

10.2 Data does not load after sign-in 8

10.3 "NITDA Folio could not start" 10

10.4 401s in run history that nobody caused 10

10.5 A flow change is refused 10

10.6 Limits and design notes at commissioning 10

8 · Administrator guide

> **Status:** handbook chapter, 2026-10-10. It carries steps, and owns none: tenant procedures are owned by `docs/deployment/RUNBOOK.md` and `PLATFORM_ACCESS_RUNBOOK.md`.

For **System Administrators** and **User Administrators** of the Workspace, and for whoever looks after its SharePoint lists, flows and hosting. Day-to-day use of the screens is in the User guide.

8.1 Who administers what

Role	Can
System Administrator (`systemAdmin`)	Everything, including granting System Administrator
User Administrator (`userAdmin`)	Add, change and disable people; assign roles (not System Administrator); view audit; open Administration, User Administration, System Health, Operator HUD and Admin Suite
Flow owner (dgsregistry@nitda.gov.ng)	Owns the Power Automate flows and their connections; needed to read run history or apply packages
SharePoint site owner	Edits lists directly (for example `Flow Configuration`)

8.2 People and access

Add a person

1. **Administration › User Administration › add**.
2. Fill in at least: full name, work e-mail (it must be the address they receive mail at), directorate, department, **role** (see the table below), status **active**.
3. Save. They can sign in at once with their e-mail and a code.

If the person…	Give them
registers, classifies and assigns incoming correspondence	**Operator**
leads a directorate and approves or dispatches	**Director**
reviews and decides at executive level	**Executive**
only needs to see their own assigned work	**Read-only Viewer**
manages people	**User Administrator**

If the person…	Give them
administers the whole platform	**System Administrator** (only another System Administrator can grant it)

What each role can open is in Data model §4.7. What each role **receives** is decided by the server: Operators, Executives and administrators get every record; others get their own tasks only.

Change or remove access

- Change the role, or set the status to **disabled** and give a reason. A disabled person's next request is refused (401). Their open sign-in proof stops working at that request.
- Statuses: `staged` (prepared, not yet allowed), `active`, `disabled`, `unregistered`. Only `active` works.
- Every change made through the screen is written to `DGO_AuditLog` by the USER_ADMIN service. (The USER_ADMIN package does not write `DGO_UserRoleHistory`.)

The form's fields: full name, e-mail, phone, job title, directorate, department, unit, role, persona, access scope, pilot cohort, status and, when disabling, a reason.

Direct list edits

`DGO_UserDirectory` can be edited in SharePoint, but the USER_ADMIN service applies the checks: valid role and status values, no duplicate e-mail, and only a System Administrator granting System Administrator. A direct edit skips them and writes no audit row. Prefer the screen.

8.3 Server-side settings: `Flow Configuration`

The SharePoint list `Flow Configuration` (activity-tracking site) holds settings the flows read at run time. `Title` is the key, `ConfigValue` the value. Change it to change behaviour without changing a flow.

Key	Read by	Effect
`IDENTITY_PROOF_REQUIRED`	every internal service (11 packages)	`true`: a valid sign-in proof is required. **Keep it `true` in production.**
`ALLOWED_ORIGIN…` (any key starting so)	17 packages	Origins the flows name in their CORS reply (the gateway answers `*` regardless; see ITEM-56)
`NOTIFY_…`, `NOTIFY_REGISTRY_TO`	notification sends	Who receives registry notices
`DATASET_<NAME>_SITE_URL`, `DATASET_<NAME>_LIST_ID`	FETCH_ALL and others	Where the intake register, briefs, meetings, projects, approvals and registry files live
`ENVIRONMENT_CODE`	identification	`prd`, `uat` or `dev` (non-production references start with Z)

Key	Read by	Effect
`STATUS_REQUIRE_VERIFICATION`	Portal STATUS	Whether tracking a submission needs a verified e-mail
`OPENROUTER_API_KEY`	AI document processing	The AI provider key (AI is off at go-live). Restrict who can read the list.

Change one value at a time, note the old value, and check the next run of the flows that read it.

8.4 Monitoring

Daily check	Where	Healthy
Failed runs	Power Automate › My flows › flow › Run history (kept 28 days)	No `Failed` run, or each one explained
Mail actually sent	SharePoint `Portal Outbox Receipts`	A receipt for each notice
Run records	SharePoint `Portal Flow Telemetry`	No error outcomes
Scans picked up	Run history of `Folio_Incoming_Correspondence_Scan_Processing_Flow`	Runs each minute; a file → a record
Sweep	Run history of `AUTO_SCHEDULED_SWEEP`	Runs on schedule

In the Workspace (System Administrator):

- **System Health** (`#/diagnostics`): runtime checks (booted, routes, services configured, last data load), collections, the endpoint table and readiness panels.
- **Endpoint Console** (via Administration): a **probe** sends each read service a request **without a sign-in proof**. With sign-in enforced, **401 is the healthy answer**: the service is up and refusing anonymous calls. A non-JSON answer means the service was not reached at all.
- **Operator HUD**: integration health at a glance.
- **Admin Suite**: the service estate, flow catalogue, live checks, commissioning and audit trail.

8.5 Deploying a new Workspace build

You receive `FOLIO-WORKSPACE-v<version>-upload-to-site-root.zip` privately from the platform team, for example `FOLIO-WORKSPACE-v2026.10.20-1-upload-to-site-root.zip`. The version in its name is the build's identity: use the newest you were sent, and never mix files from two versions.

1. Unzip it on your computer.
2. Upload **all** its contents to the root of `folio-platform.page.gd`, replacing what is there. Make sure the hidden file `.htaccess` is uploaded; some file managers hide files starting with a dot.

3. In a private window, open the site, sign in, and wait about 20 seconds: the Command Center shows counts.
4. Open your profile (top right). It reads **Build v...**: check it is the version in the zip's name. If it shows an older version, the upload did not replace every file.
5. Tell the platform team which version is deployed, so they delete the private copy.

Because of `.htaccess`, browsers fetch the new files on their next load. Users do not need to clear anything. (Before 2026-10-09 the host kept JavaScript for 30 days, and a browser holding old files could sign in but never load data. If someone still sees that, clearing the site's data once fixes it.)

The Portal zip goes to the Portal host (`CG/` folder) and the Mailer file to the Mailer, the same way.

Rollback: upload the previous zip. The flows are not affected.

8.6 Security operations

Task	How
A signed address leaked	Regenerate that flow's trigger key in Power Automate. The platform team runs `npm run config:drift` (it reports the change) and `npm run config:rebuild`; you deploy the new zip. The old address stops working at once. See `docs/architecture/ROTATION_REGISTER.md`.
Remove someone's access now	Set their status to `disabled`.
A proof must stop working before its 4 hours	Set `Consumed` to yes on their row in `DGO_SessionProofs`, or disable the person.
Handling build zips	They contain signed addresses. Send them privately, delete them after deployment, and never commit them.
Hosting	The Workspace and Portal are on folio-platform.page.gd and folio-portal.page.gd. The host's browser check runs once every 6 hours per browser and drops a `#/` part of a link on that first visit; Folio's e-mails link to `/acknowledge.html` and query addresses (`?TaskID=`), which survive it.

8.7 Test data

Commissioning creates test rows. The owner approved their removal (2026-10-08, MANUAL-2). The platform team removes them after the last commissioning test, and records the reference sequence counter's starting value (`Portal Sequence Counters`). When you create test data yourself, give it a recognisable name (for example a `ZTEST` prefix) and tell the platform team.

8.8 Related procedures

Need	Document
Every cutover step, standing procedures	`docs/deployment/RUNBOOK.md`
Access setup and checks	`docs/deployment/PLATFORM_ACCESS_RUNBOOK.md`
Portal operations	`docs/deployment/DOCUMENT_PORTAL_LIVE_OPERATIONS.md`
The Central Administration Centre	`docs/admin-centre/`
RBAC in depth	`docs/architecture/AUTH_RBAC_GUIDE.md`

10 · Troubleshooting

Start from evidence, not from a guess. For any fault, establish in this order:

1. **Did the request reach the flow?** Look in the flow's run history. No run means the browser never sent it, or the gateway refused it before a run started.
2. **What did the flow receive and answer?** Open the run: the trigger's headers and body, each action's inputs and outputs, the Response action's status.
3. **What did the browser record?** Use the command in §10.2.
4. **Reproduce with the real code**, changing one thing at a time.

10.1 Cannot sign in

Symptom	Cause	Fix
No code e-mail	Junk folder; mistyped address	Check junk; retype the address. A code is mailed only to an active Folio user, so a mistyped or unregistered address gets no e-mail.
The code is refused	Mistyped or expired code; or the address is not **active** in `DGO_UserDirectory` (OTP_VERIFY checks the code and the directory)	Request a new code. If it is still refused, an administrator checks the person's row: `Email` exactly as typed, `Status` = `active`.
Refused after several tries	Five wrong attempts	Request a new code
Asked to sign in again	The proof lasts 4 hours, and ends when the tab closes	Sign in again

10.2 Data does not load after sign-in

Symptom: the Workspace opens but every count is 0, and ⟳ says "The registry could not be reached".

Step 1: did FETCH_ALL run? Open the run history of `IP_FETCH_ALL_BOOTSTRAP` at the time of the sign-in.

What you find	Means	Go to
No run	The browser never sent the request	Step 2
A run answering **200**	The data was sent; the browser did not take it in, or was looked at before it arrived (it takes about 20 seconds)	Wait and recheck; then Step 2

What you find	Means	Go to
A run answering **401**, body `{"action":"fetchAll"}` only, no `X-Correlation-Id`	That was the **Endpoint Console probe**, not a data load. Expected.	Ignore it
A run answering **401** with `payload`, `requestId` and `X-Correlation-Id`	A real load whose proof was missing, expired, or whose person is not active	Check the person's directory row; sign in again
A run answering **500**	The flow failed	Open the failed action

Step 2: what did the browser record? In the affected browser, sign in, wait 30 seconds, press F12, open **Console**, paste this and press Enter. It prints no token. It runs one read-only data load and reports each stage, waiting up to 2 minutes.

```
(async()=>{const o=
{booted:!!window.__DGO_BOOTED__,secure:isSecureContext,href:location.origin};const
step=async(n,f,ms=60000)=>{const t=performance.now();try{const v=await
Promise.race([f(),new Promise((_,j)=>setTimeout(()=>j(new Error('no answer after
'+ms/1000+'s')),ms))]);o[n]={ok:true,ms:Math.round(performance.now()-t),v};}catch(e){o[n]=
{ok:false,ms:Math.round(performance.now()-t),error:(e&&e.name)+': '+
(e&&e.message)};}};const {State}=await
import('/core/state.js');o.loading=!!State.get().runtime?.loading;o.lastLoad=State.get().r
untime?.lastLoad||null;await step('auth',async()=>{const a=await
import('/core/auth.js');const i=await a.ensureAuthenticated('diagnostic');return
{role:i&&i.role};});await step('url',async()=>{const d=await import('/core/data-
client.js');const u=d.resolveUrl('FETCH_ALL');return {configured:!!u,host:u?new
URL(u).host:''};});await step('request',async()=>{const {FetchManager}=await
import('/core/fetch-manager.js');const r=await FetchManager.fetch('FETCH_ALL',
{force:true,requestedAt:new Date().toISOString()},
{force:true,cacheNamespace:'FETCH_ALL'});const d=r.data?.data||r.data||{};return
{source:r.source,docs:(d.docs||[]).length,tasks:(d.tasks||
[]).length};},120000);console.log(JSON.stringify(o,null,1));return o})()
```

Output	Means
`booted: false`	Start-up stopped after drawing the screen. Clear the site's data (padlock › Site settings › Delete data) and reload.
`auth` not ok	No valid sign-in: sign in again
`url` not ok	The build has no FETCH_ALL address: redeploy the build
`request` not ok	Read the error; check FETCH_ALL's run history at that time
all ok, with document and task counts	The service works. Press ⟳.

What it was on 2026-10-09. The deployed build, flows and account all worked: a clean browser received the data. The owner's browsers held JavaScript files cached for 30 days from earlier builds (the host's default), and sent no data request after signing in. After the site's data was cleared, every load succeeded. The root `.htaccess` now makes browsers revalidate every page, script and stylesheet, so a redeploy cannot leave a browser on old files.

10.3 "NITDA Folio could not start"

The start-up watchdog in `index.html` shows this if start-up has not finished within 15 seconds. Since build `5b9f7ed` it pauses while the sign-in box waits for you, so it should only appear for a real failure. Press **Try again**. If it repeats, open **Technical details** and send the failing file names to IT support.

10.4 401s in run history that nobody caused

Bodies of exactly `{"action":"<action>"}` with only a `Content-Type` header come from the **Endpoint Console probe** (System Health › Administration). The probe carries no proof on purpose. 401 is its healthy result.

10.5 A flow change is refused

`npm run flows:update -- apply` refuses, before writing, any package that would give a flow more than **500 actions** or contain an expression longer than **8,192 characters**: the tenant would reject either. Split the work into its own flow (as USER_ADMIN was) or shorten the expression.

10.6 Limits and design notes at commissioning

Facts read from the code, configuration and live flows, checked again at commissioning on 2026-10-19. Every item the register tracks is closed (`npm run outstanding`: 0 open); what remains here are design limits and notes for operators.

Gap	Effect	Tracked
AI analysis off	AI buttons say unavailable	ITEM-88, resolved by decision
Writes are not de-duplicated by the server, except in DYNAMIC_ACTIONS	The Workspace waits 90 s for a write and never repeats one itself (2026-10-10), so it creates no duplicate; a person pressing Assign twice still could	G-04 obligation 6
FETCH_ALL reads the newest 500 documents and 500 tasks	Older records are not on the dashboards; use Lookup	Design limit

Gap	Effect	Tracked
FETCH_ALL's role-catalogue check is a constant `true`	`DGO_RoleCatalogue` is read but decides nothing; data scope comes from the role and persona	Not in the register (scope is enforced; the catalogue check is redundant)
A link opens the Command Center instead of the screen it names	The host's browser check (first visit in 6 hours) dropped the `#/` part of the link	Open the link again; links Folio sends use `/acknowledge.html` or `?TaskID=`, which survive it (release 41)
`docs/PLATFORM.md` §4 names some superseded flows (for example `IP_FETCH_ALL__EXTENDED_ENDPOINT` for FETCH_ALL)	Readers of that page get a stale picture	Regenerate from current registers; the build ledger is current