

MSDS Report

Sample Description
& Model

Li-ion Rechargeable Battery (18650)

Applicant

EVERWIN TECH CO., LIMITED

Address

BLDG1, MEILAN INDUSTRIAL PARK, DALANG
ROAD(S), LONGHUA, SHENZHEN, CHINA

No.: MZIGAJZN26910719
Code: ne8hb1l



www.ponytest.com

Hotline: 400-819-5688

北京实验室: 010-52818118
青岛实验室: 0532-88796996
天津实验室: 022-27340730

长春实验室: 0431-85156996
大连实验室: 0411-84650820
深圳实验室: 0371-68310670

上海实验室: 021-64851999
宁波实验室: 0574-87716499
杭州实验室: 0571-87210096

厦门实验室: 0592-26050888
广州实验室: 020-86224310
武汉实验室: 027-83997127

Material Safety Data Sheet

Reference to ST/SG/AC.10/30/Rev.5 (GHS)

Section 1 - Chemical Product and Company Identification

Chemical product identification

Sample Description: Li-ion Rechargeable Battery

Sample Model: 18650

Recommended Uses: Power Bank

Restrictions on use: N/A

Supplier name: EVERWIN TECH CO., LIMITED

Address: BLDG1, MEILAN INDUSTRIAL PARK, DALANG
ROAD(S), LONGHUA, SHENZHEN, CHINA

Phone number: 86-755-81752844

FAX: 86-755-81752840

E-mail: sales01@ewtbattery.com

Emergency phone number: 0755-81752844

Section 2 - Hazards Identification

Emergency overview: This product is an article which contains a chemical substance. Safety information is given for exposure to the article as sold. Intended use of the product should not result in exposure to the chemical substance. This is a battery.

In case of rupture: the below hazards exist.

CAS# 7440-50-8

Classification according to GHS

Specific target organ toxicity, single exposure; Respiratory tract irritation (3)

Specific target organ toxicity, repeated exposure (1) (liver)

Hazardous to the aquatic environment, long-term hazard (3)

Label elements

Hazard pictogram(s):



Signal word:

Danger

Hazard statement(s):

H335 May cause respiratory irritation



Pony Testing International Group

H372 Causes damage to organs through prolonged or repeated exposure (liver)

H412 Harmful to aquatic life with long lasting effects

Precautionary statement(s):
Prevention:

P271 Use only outdoors or in a well-ventilated area.

P260 Do not breathe dust.

P264 Wash skin and clothing thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P273 Avoid release to the environment.

Response:

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER or doctor, if you feel unwell.

Storage

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

Disposal:

P501 Contents or container handling to approved waste treatment plants.

CAS# 7429-90-5
Classification according to GHS

Specific target organ toxicity, repeated exposure (1) (Lung)

Hazardous to the aquatic environment, long-term hazard (4)

Label elements
Hazard pictogram(s):

Signal word:

Danger

Hazard statement(s):

H372 Causes damage to organs through prolonged or repeated exposure (Lung)

H413 May cause long lasting harmful effects to aquatic life

Precautionary statement(s):
Prevention:

P260 Do not breathe dust.

P264 Wash skin and clothing thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P273 Avoid release to the environment.

Response:

P314 Get medical advice if you feel unwell.

www.ponytest.com ☎Hotline 400-819-5688

北京实验室: 010-82018118	长春实验室: 0431-83150808	上海实验室: 021-64451999	深圳实验室: 0755-26059999
青岛实验室: 0532-86706966	哈尔滨实验室: 0451-88104261	宁波实验室: 0574-87716499	广州实验室: 020-89224110
天津实验室: 022-27360720	大连实验室: 0411-84658620	杭州实验室: 0571-87219896	武汉实验室: 027-87997127
南通实验室: 0591-6684186	郑州实验室: 0371-64358670	惠州实验室: 0512-62997900	厦门实验室: 0592-5568848

Storage

None.

Disposal:

P501 Contents handling to approved waste treatment plants.

Other hazards
Physical and chemical hazards: See Section 10

Human health hazards: See Section 11

Environmental hazards: See Section 12

Section 3 – Composition/Information on Ingredients

Chemical characterization: Mixture

Chemical Composition	CAS No.	EC#	Weight (%)
Cobalt lithium manganese nickel oxide	182442-95-1	---	40
Graphite	7782-42-5	231-955-3	18
Phosphate(1-), hexafluoro-, lithium	21324-40-3	244-334-7	18
Copper	7440-50-8	231-159-6	10
Aluminum	7429-90-5	231-072-3	5
Polyvinyl chloride resin	9002-86-2	---	2

Section 4 - First Aid Measures

Description of first aid measures
General information No special measures required.

After eye contact

Flush eyes with plenty of water for several minutes while holding eyelids open. Get medical attention if irritation persists.

After skin contact

Remove contaminated clothing and shoes. Immediately wash with water and soap and rinse thoroughly. Wash clothing and shoes before reuse. If irritation occurs, get medical attention.

After inhalation

Remove victim to fresh area. Administer artificial respiration if breathing is difficult. Seek

medical attention.

After swallowing

Do not induce vomiting. Get medical attention.

Personal protective equipment for first-aid responders: No data available.

Most important symptoms/effects, acute and delayed: No data available.

Indication of immediate medical attention and special treatment needed: No data available.

Section 5 - Fire Fighting Measures

Suitable extinguishing media:

Use extinguishing agent suitable for local conditions and the surrounding environment .
Such as dry powder , CO₂.

Unsuitable extinguishing media:

No data available.

Specific Hazards arising from the chemical:

Special hazards arising from the substance or mixture

Battery may burst and release hazardous decomposition products when exposed to a fire situation. Lithium ion batteries contain flammable electrolyte that may vent, ignite and produce sparks when subjected to high temperature(>150°C(302°F)), when damaged or abused (e.g. mechanical damage or electrical overcharging); may burn rapidly with flare-burning effect; may ignite other batteries in clothes proximity.

Specific protective actions for fire-fighters:

Protective equipment: Wear self-contained respirator. Wear fully protective impervious suit.

Section 6 - Accidental Release Measures

Personal precautions:

Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation

Protective equipment:

No data available.

Emergency procedures:

Remove ignition sources, evacuate area. Sweep up using a method that does not generate dust. Collect as much of the spilled material as possible, placed the spilled material into a suitable disposal container. Keep spilled material out of sewers, ditches and bodies of water.

Environmental precautions:

Do not allow material to be released to the environment without proper governmental permits.

Methods and materials for containment and cleaning up:

All waste must refer to the United Nations, the national and local regulations for disposal.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Section 7 - Handling and Storage

Precautions for safe handling:

Consumption of food and beverage should be avoided in work areas.

Wash hands with soap and water before eating, drinking.

Ground containers when transferring liquid to prevent static accumulation and discharge.

Information about fire and explosion protection

Batteries may explode or cause burns, if disassembled, crushed or exposed to fire or high temperatures. Do not short or install with incorrect polarity.

Conditions for safe storage, including any incompatibilities:

Requirements to be met by storerooms and receptacles

Store in a cool, dry, well-ventilated place.

Information about storage in one common storage facility

Keep away from heat, avoiding the long time of sunlight.

Further information about storage conditions

Keep container tightly sealed.

Specific and use

No data available.

Section 8 - Exposure Controls/Personal Protection

Control parameters

CAS No.	ACGIH	NIOSH	OSHA
182442-95-1	N/A	N/A	N/A
7782-42-5	TLV-TWA 2mg/m ³	REL-TWA 2.5mg/m ³	PEL-TWA 15mppcf PEL-TWA 20mppcf
21324-40-3	N/A	N/A	N/A



7440-50-8	TLV-TWA 0.2mg/m ³ TLV-TWA 1mg/m ³	REL-TWA 1mg/m ³ REL-TWA 0.1mg/m ³	PEL-TWA 0.1mg/m ³ PEL-TWA 1mg/m ³
7429-90-5	TLV-TWA 10mg/m ³ TLV-TWA 5mg/m ³	REL-TWA 2mg/m ³ REL-TWA 5mg/m ³ REL-TWA 10mg/m ³	PEL-TWA 5mg/m ³ PEL-TWA 15mg/m ³
9002-86-2	N/A	N/A	N/A

Appropriate engineering controls:

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Remove all soiled and contaminated clothing immediately.

Wash hands before breaks and at the end of work.

Personal Protective Equipment

Respiratory protection: Wear suitable protective mask in order to reduce the respiratory system. A large number of leakage, wear chemical protective clothing, including self-contained breathing apparatus.

Hand Protection: Wear appropriate protective gloves to reduce skin contact.

Eyes Protection: Wear safety goggles or eye protection combined with respiratory protection.

Skin and Body Protection: Working environment required, wear suitable protective clothing to minimize contact with skin. The type of protective equipment must be according to the concentration and the content of certain hazardous substances in the workplace.

Section 9 - Physical and Chemical Properties

Information on basic physical and chemical properties

Colour:	Blue.
Physical State:	Cylindrical.
Odour:	Not available.
Odour threshold:	Not available.
pH:	Not available.
Melting point/freezing point:	Not available.
Initial boiling point and boiling range:	Not available.
Flash Point:	Not available.
Evaporation rate:	Not available.
Flammability (solid, gas):	Not available.



Pony Testing International Group

Explosion Limits (vol% in air):	Not available.
Vapour pressure, kPa at 20°C:	Not available.
Vapor density:	Not available.
Density/Relative density (water = 1):	Not available.
Solubility(ies):	Not available.
Partition coefficient: n-octanol/water:	Not available.
Auto-ignition temperature:	Not available.
Decomposition temperature:	Not available.
Viscosity:	Not available.
Other information:	
Voltage	3.7V
Electric capacity	1600mAh
Electric Energy	9.62Wh

Section 10 - Stability and Reactivity

Reactivity: No data available.

Chemical stability: Stable.

Possibility of hazardous reactions: No data available.

Conditions to Avoid: Flames, sparks, and other sources of ignition, incompatible materials.

Incompatibilities materials: Oxidizing agents, acid, base.

Hazardous decomposition products: Carbon monoxide, carbon dioxide, lithium oxide fumes.

Section 11 - Toxicological Information

Acute Toxicity:

CAS No.	LC50/LD50
182442-95-1	No data available.
7782-42-5	No data available.
21324-40-3	No data available.
7440-50-8	No data available.
7429-90-5	No data available.
9002-86-2	No data available.



Pony Testing International Group

Report No. : MZIGAJZN26910719 Date: 01.01.2019 Page 8 of 11

Skin corrosion/irritation: No data available.
Serious eye damage/irritation: No data available.
Respiratory or Skin sensitization: No data available.
Germ Cell mutagenicity: No data available.
Carcinogenicity: No data available.
Reproductive toxicity: No data available.
Specific target organ toxicity-Single exposure: No data available.
Specific target organ toxicity-Repeated exposure: No data available.
Aspiration hazard: No data available.
Information on the likely routes of exposure: No data available.
Eye: No data available.
Skin: No data available.
Ingestion: No data available.
Inhalation: No data available.

Section 12 - Ecological Information

Ecological Toxicity: No data available.
Persistence and degradability: No data available.
Bioaccumulative Potential: No data available.
Mobility in Soil: No data available.
Other adverse effects: No data available.

Section 13 - Disposal Considerations

Disposal methods:
Recommendation:
 Consult state, local or national regulations to ensure proper disposal.

Uncleaned packaging
Recommendation: Disposal must be made according to official regulations.

Section 14 - Transport Information

UN Number	
IATA	UN3480
IMDG	UN3480

UN Proper shipping name	
IATA	Lithium ion batteries
IMDG	LITHIUM ION BATTERIES
Transport hazard class(es)	
IATA	9
IMDG	9
Packing group	
IATA	N/A
IMDG	N/A
Packaging Sign	
IATA	N/A
IMDG	N/A
Environmental hazards	
Marine pollutant:	No
Special precautions for user	Not applicable.

Transport Information: The Li-ion Rechargeable Battery (18650) has passed the test UN38.3, according to the report ID: MZIBSGTA50530521.

According to the Packing Instruction 965 section II of IATA DGR 60th Edition for transportation.

According to the special provision 188 of IMDG (37-14). The products are not subject to dangerous goods.

Separate batteries to prevent short-circuiting, and they should be packed in strong package during transport. Lithium cell or battery should incorporate a safety venting device or be designed to prevent a violent rupture under normal transport conditions. Keep away from high temperature and open flames.

Transport Fashion: By air, by sea.

Section 15 - Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture

CAS No.	TSCA	IECSC	DSL/NDL	EINECS/ ELINCS/ NLP
182442-95-1	Listed	Listed	Listed DSL	Listed
7782-42-5	Listed	Listed	Listed DSL	Listed
21324-40-3	Listed	Listed	Listed DSL	Listed

21324-40-3	Listed	Listed	Listed DSL	Listed
7440-50-8	Listed	Listed	Listed DSL	Listed
7429-90-5	Listed	Listed	Listed DSL	Listed
9002-86-2	Listed	Listed	Listed DSL	Listed

Section 16 - Other Information

Issue Time: 2016-01-01

Issue Department: Technical department

Modification record:

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Other Information:

CAS: (Chemical Abstracts Service);

EC: (European Commission);

ACGIH: (American Conference of Governmental Industrial Hygienists);

NIOSH: (US National Institute for Occupational Safety and Health);

OSHA: (US Occupational Safety and Health);

TLV: (Threshold Limit Value)

TWA: (Time Weighted Average);

STEL: (Short Term Exposure Limit);

PEL: (Permissible Exposure Level);

REL: (Recommended Exposure Limit);

PC-STEL: (Permissible concentration-time weighted average);

PC-TWA: (Permissible concentration-short time exposure limit);

LC50: (Lethal concentration, 50 percent kill);

LD50: (Lethal dose, 50 percent kill);

IARC: (International Agency for Research on Cancer);

EC50: (Median effective concentration);

BCF: (Bioconcentration Factor);

BOD: (Biochemical oxygen demand);

NOEC: (No observed effect concentration);

NTP: (US National Toxicology Program);

RTECS: (Registry of Toxic Effects of Chemical Substances);

IATA: (International Air Transport Association);



Pony Testing International Group

IMDG: (International Maritime Dangerous Goods);

TDG: (Recommendations on the TRANSPORT OF DANGEROUS GOODS Model Regulations);

TOC: (Total Organic Carbon);

TSCA: (Toxic Substances Control Act of USA);

DSL: (the Domestic Substances List of Canada);

NDSL: (the Non-domestic Substances List of Canada)

End of report