NAND gate example

Mark W. Coffey
Department of Physics
Colorado School of Mines
Golden, CO 80401

December 13, 2015

We'd like to consider how to set up an Ising model that encodes this logical operation. Take

$$H_f = \sum_{j} h_j \sigma_j^z + \sum_{i < j} J_{ij} \sigma_i^z \sigma_j^z,$$

where h_j are the field parameters and J_{ij} the spin couplings. Choose logical 1 (true) to be represented by spin up $|\uparrow\rangle$ (or s=+1) and logical 0 (false) by spin down $|\downarrow\rangle$ (or s=-1). We'll confirm the following encoding for the NAND gate:

$$\begin{array}{c|cc} h_j & J_{ij} \\ \hline h_A = -1 & J_{AB} = 1 \\ h_B = -1 & J_{AC} = 2 \\ h_C = -2 & J_{BC} = 2 \\ \hline \end{array}$$

A	В	С	Energy	
$\overline{\downarrow}$	\downarrow	\downarrow	9	
\downarrow	\downarrow	\uparrow	-3	
\downarrow	\uparrow	\downarrow	1	
\downarrow	\uparrow	\uparrow	-3	So we see that the ground state energy of -3 corresponds
\uparrow	\downarrow	\downarrow	1	
\uparrow	\downarrow	\uparrow	-3	
\uparrow	\uparrow	\downarrow	-3	
	<u> </u>	\uparrow	1	

to the entries of the truth table for NAND.




Figure 1: Graphical representation of the Hamiltonian implementing the logic of a NAND gate. Each of the vertices is a spin and the number inside is the field value on that spin; each edge is the coupling value between the respective vertices. Each ground state of this Hamiltonian enforces the logic C=NOT(AND(A,B)).

This example begs the question of how to obtain the h_j and J_{ij} parameters for a given problem. When the operation in question is a logic gate, two avenues seem to be available:

- (a) Use integer programming to solve for these parameter values. This will not be computationally advantageous in general, but ok for small or specialized problems.
- (b) For this special case of a logic gate (by far not the typical application of adiabatic quantum computing), one can write mathematical formulas encoding the output of the gate, and then translate that to a quadratic objective function for the Ising model.

We as a group need to elaborate and explore both of these approaches.

Consider method (a) for the NAND gate. Writing out the problem Hamiltonian in detail,

$$H_f = h_1 \sigma_1^z + h_2 \sigma_2^z + h_3 \sigma_3^z + J_{12} \sigma_1^z \sigma_2^z + J_{13} \sigma_1^z \sigma_3^z + J_{23} \sigma_2^z \sigma_3^z.$$

We have 6 parameters in total: 3 h's and 3 J's. Suppose that we wish the ground state energy to be k. Then from the truth table encoded by spins, we have the 4 conditions

$$-h_1 - h_2 + h_3 + J_{12} - J_{13} - J_{23} = k,$$

$$-h_1 + h_2 + h_3 - J_{12} - J_{13} + J_{23} = k,$$

$$h_1 - h_2 + h_3 - J_{12} + J_{13} - J_{23} = k,$$

$$h_1 + h_2 - h_3 + J_{12} - J_{13} - J_{23} = k.$$

The other four conditions are inequalities since we demand that they yield an energy strictly greater than k. Thinking in terms of an integer programming problem, we replace the condition > k with $\ge k+1$ and get

$$-h_1 - h_2 - h_3 + J_{12} + J_{13} + J_{23} \ge k + 1,$$

$$-h_1 + h_2 - h_3 - J_{12} + J_{13} - J_{23} \ge k + 1,$$

$$h_1 - h_2 - h_3 - J_{12} - J_{13} + J_{23} \ge k + 1,$$

$$h_1 + h_2 + h_3 + J_{12} + J_{13} + J_{23} \ge k + 1.$$

If we just solve the 4 equalities, we have the reduced relations

$$h_3 = h_1 + h_2$$
, $J_{12} = h_3 - k$, $J_{13} = h_2 - k$, and $J_{23} = h_1 - k$.

It's easily confirmed that these relations are satisfied as above when k = -3.

In general when there are N spins in the Ising Hamiltonian, there are N h parameters and N(N-1)/2 J parameters, for a total of $N(N+1)/2 = \binom{N+1}{2}$. There are 2^N conditions, so that this method is limited to small problems.