

Quantum Key Distribution:

Bridging Theoretical Security Proofs,
Practical Attacks, and Error Correction
for Quantum-Augmented Networks

Nitin Jha
Abhishek Parakh
Mahadevan Subramaniam

Contents

Executive Summary	1
1 Introduction & QKD Landscape	4
1.1 Protocol Taxonomy	4
1.1.1 Uncertainty Principle-Based Protocols (BB84)	5
1.1.2 Hybrid Architecture: The Three-Stage Protocol	5
1.1.3 Continuous-Variable (CV) QKD	5
1.1.4 Twin-Field QKD	6
1.1.5 Device-Independent (DI) QKD	6
2 Attacks on QKD Systems	7
2.1 Photon Number Splitting (PNS) Attack	7
2.2 Trojan Horse Attack	8
2.3 Jamming Attacks	9
3 Security Proofs & Error Correction	11
3.1 Security Paradigms in QKD	11
3.1.1 Unconditional Security	11
3.1.2 Finite-Key Security	11
3.1.3 Composable Security	12
3.2 Major Security Proofs	12
3.3 Quantum Error Correction Codes	14
3.3.1 Landmark Codes	14
3.3.2 Recent Experimental Breakthroughs	15
Conclusion	18

Executive Summary

The Quantum Security Imperative

Quantum Key Distribution (QKD) has emerged as one of the most promising cryptographic frameworks of the post-quantum era. By grounding security in the immutable laws of quantum mechanics rather than the assumed hardness of mathematical problems, QKD offers information-theoretic security that no increase in classical or quantum computing power can undermine. This whitepaper synthesizes and distills the key findings of a comprehensive academic review of QKD protocols, their attack surfaces, and the error-correction codes that make them practical.

What This Whitepaper Covers

This whitepaper covers five core themes drawn from the academic review:

1. **QKD Protocols** — From the foundational BB84 scheme to modern Twin-Field and Device-Independent variants, we survey the protocol landscape and its trade-offs.
2. **Practical Attack Vectors** — We examine three critical classes of attacks: Photon Number Splitting (PNS), Trojan Horse, and Jamming attacks, highlighting both theoretical models and recent experimental demonstrations.
3. **Security Proofs** — We outline the mathematical frameworks—unconditional, finite-key, and composable security—that underpin QKD's security guarantees.
4. **Quantum Error Correction Codes (QECCs)** — From three-qubit repetition codes to topological surface codes, we review the codes that protect quantum states against noise and decoherence.

5. **Quantum-Augmented Networks (QuANets)** — We discuss how all of the above directly informs the design and deployment of hybrid classical-quantum network infrastructure.

Key Takeaways

The gap between idealized QKD theory and practical deployment remains a central challenge. Real-world photon sources, noisy channels, and side-channel vulnerabilities each erode the theoretical guarantees. Decoy-state methods, optical isolators, and measurement-device-independent architectures represent the current frontier of defense. Meanwhile, Quantum Error Correction Codes are no longer abstract constructs—recent superconducting and trapped-ion implementations have demonstrated logical qubits surpassing the “break-even” coherence point, a milestone for fault-tolerant quantum communication.

1 Introduction & QKD Landscape

The need for private communication has driven cryptographic innovation for centuries. Today, classical public-key cryptography—including RSA, elliptic curves, and Diffie-Hellman—faces an existential threat from quantum computers capable of running Shor’s algorithm. Quantum Key Distribution (QKD) addresses this threat by replacing computational hardness assumptions with the physical laws of quantum mechanics.

Core Principle of QKD

Alice and Bob exchange quantum states over an unauthenticated channel, then use an authenticated classical channel to reconcile measurements. Any eavesdropping attempt by Eve inevitably disturbs the quantum states, raising the observed error rate. If it exceeds a threshold, the key is discarded and the protocol restarts. Because QKD’s security arises from physics rather than computational assumptions, retrospective cryptanalysis is impossible.

The no-cloning theorem is the cornerstone of this security: unknown quantum states cannot be duplicated without disturbance, ensuring that any interception by a third party leaves a detectable signature.

1.1 Protocol Taxonomy

QKD protocols fall into two primary families, which are further extended by modern variants optimized for range and practical deployability.

1.1.1 Uncertainty Principle-Based Protocols (BB84)

The BB84 protocol, proposed by Bennett and Brassard in 1984, is the foundational QKD scheme. Alice encodes bits using two non-commuting bases (rectilinear and diagonal), transmits them to Bob, and they compare bases over a classical channel, discarding mismatched measurements. Any eavesdropper measuring in the wrong basis introduces detectable errors.

Key strength: Proven information-theoretic security under ideal conditions with strong supporting mathematical proofs.

Key weakness: Practical photon sources emit multi-photon pulses, opening the door to Photon Number Splitting (PNS) attacks. Decoy-state methods mitigate this at the cost of reduced key rates.

Performance: Early BB84 experiments achieved 1.9 Mb/s over 10 km; recent work reports 13.72 Mb/s at 2 dB loss, and up to 107 Mb/s over a 37-core fiber—though still orders of magnitude below classical key exchange rates exceeding 0.75 Gb/s.

1.1.2 Hybrid Architecture: The Three-Stage Protocol

Proposed by Dr. Subhash Kak in 2006, the three-stage protocol is based on double-lock cryptography. Alice and Bob each apply commutative unitary (rotation) transformations to quantum states across three transmission stages, enabling *Quantum Secure Direct Communication* (QSDC)—messages are transmitted directly without pre-establishing a secret key.

Key strength: Bidirectional eavesdropper checks; direct message transmission without prior key exchange; multi-photon resilience.

Key weakness: Susceptible to Trojan Horse and side-channel attacks that exploit the bidirectional channel.

1.1.3 Continuous-Variable (CV) QKD

CV-QKD encodes information in the quadrature components of coherent states rather than discrete photon polarization. Alice prepares Gaussian-modulated coherent states; Bob measures using homodyne or heterodyne detection.

Key strength: High secret-key rates compatible with existing telecom lasers and fiber infrastructure.

Key weakness: Local oscillator side-channels, including LO intensity and phase manipulation, pose a significant threat. Generally limited to metropolitan distances.

1.1.4 Twin-Field QKD

Twin-Field QKD surpasses the repeater-less key rate bound by having Alice and Bob send faint, phase-encoded pulses to an untrusted middle relay (Charlie). A single detection event at Charlie, after interference on a beam splitter, is sufficient to generate a raw bit. This means the key rate scales with $\sqrt{\eta}$ (the square root of channel transmittance) rather than η , dramatically extending viable range.

Key strength: Beats the repeater-less distance limit; untrusted relay neutralizes detector-side attacks.

Key weakness: Demands precise phase stabilization and tight synchronization; sensitive to reference-frame drift.

1.1.5 Device-Independent (DI) QKD

DI-QKD treats all hardware as uncharacterized black boxes. Security is certified solely through observed violations of Bell inequalities—if a loophole-free Bell violation is observed, the laws of quantum mechanics guarantee that no eavesdropper could have predicted the measurement outcomes.

Key strength: Security from Bell-violation alone; no device modeling assumptions; resilient to internal side-channels.

Key weakness: Demands high detection efficiency, near-perfect isolation, and strong random number generation; short distances and modest rates with current technology.

Protocol Comparison at a Glance

BB84: Simple, proven, limited by PNS at distance.

Three-Stage: Direct communication, vulnerable to Trojan Horse.

CV-QKD: High rate, LO side-channels, metro-scale only.

Twin-Field: Long range, $\sqrt{\eta}$ scaling, complex phase control.

DI-QKD: Device-agnostic security, demanding hardware requirements.

2 Attacks on QKD Systems

The gap between theoretical QKD security and practical implementation is exploited by a growing class of sophisticated attacks. Attacks on quantum networks fall into three broad categories: *Individual* (Eve attacks each qubit independently), *Collective* (Eve applies a joint strategy across many qubits), and *Coherent* (Eve performs arbitrary quantum operations across the entire transmission). We focus on three classes of practically relevant attacks supported by experimental evidence.

2.1 Photon Number Splitting (PNS) Attack

The PNS attack exploits the fact that practical QKD systems use weak coherent pulse (WCP) sources, which occasionally emit multi-photon pulses. A coherent state with mean photon number μ has a Poissonian photon number distribution:

$$P(n) = e^{-\mu} \frac{\mu^n}{n!}$$

When a pulse contains $n \geq 2$ photons, Eve can split off one photon, store it in a quantum memory, and forward the rest to Bob via a lossless channel—introducing zero detectable errors. Later, once Alice announces basis choices over the classical channel, Eve measures her stored photon and recovers the raw key bit.

PNS Attack: Key Findings from Experimental and Simulation Studies

- **Ideal PNS (Mailloux et al., 2016):** Simulation shows Eve gains 100% of raw key bits. Decoy-state protocols detect the attack with statistical confidence $P < 0.001$.

- **Hypothesis-testing detection (2022):** A Gaussian-fluctuation test statistic can detect standard PNS attacks at the 5% significance level, but subtler variants that leave overall statistics nearly unchanged can evade detection.
- **Beamsplitter-Based Attack (Liu et al., 2011):** A modified PNS attack using a beamsplitter—requiring no ability to isolate individual photons—achieved Eve-Alice mutual information as high as 0.92 while QBER remained at the normal 6.5% threshold.
- **SPRINT-PNS (Ashkenazy et al., 2024):** Using three-level quantum systems in the Λ configuration, Eve can gain over 60% of information for photon bursts with $\mu \geq 1.5$, suggesting near-ideal PNS attacks are feasible with current technology.
- **Joint-PNS on Semi-Quantum QKD (Shang et al., 2022):** Two joint-PNS attack variants achieve bidirectional photon-blocking rates above 88%, exploiting high channel loss to remain covert.

Primary countermeasures: Decoy-state protocols, photon-number-resolving detectors, hypothesis-testing-based statistical monitoring, and integrating PNS detection into finite-key analyses.

2.2 Trojan Horse Attack

In a Trojan Horse attack, Eve exploits the quantum channel not by intercepting Alice’s transmitted photons, but by *injecting* light pulses into Alice’s or Bob’s apparatus while the channel is active. By analyzing the backscattered signal, Eve can infer the internal state of Alice’s encoding device—effectively reading the key without touching the forward-traveling qubits.

The theoretical maximum information Eve can gain from a Trojan Horse injection using a coherent state of amplitude α is bounded by:

$$I_{\text{Eve}}^{\text{Trojan}}(|\alpha|^2) \approx \frac{1}{\ln(2)|\alpha|^2} + \mathcal{O}(|\alpha|^4)$$

Trojan Horse Attack: Key Findings

- **Gisin et al. (2006):** Experimental demonstration using OTDR and OFDR techniques. Allowing just 0.1 back-scattered photons enables Eve to gain up to 0.135 bits per qubit. Randomizing Alice’s phase settings reduces Eve’s gain by a factor of ≈ 1.44 .
- **Yang et al. (2015):** Trojan Horse attack on the BKM07 semi-quantum protocol, injecting a fake photon at the same wavelength to extract key bits undetected. Defense: wavelength filters and a 50/50 beam splitter.
- **Sushchev et al. (2024):** At 1800 nm, Eve’s mean photon number per pulse rises to 9×10^{-4} , implying $\approx 1\%$ potential key leakage—far higher than at the standard 1550 nm wavelength.
- **Vinay & Kok (2018):** Gaussian attack states show that coherent states are optimal for Trojan Horse attacks even under thermal noise. The secret key rate reaches zero if the distinguishability Δ exceeds a threshold.
- **Jain et al. (2014):** Wavelength-dependent vulnerabilities in isolators and SPADs reveal a 30 dB reduction in isolation at 1300 nm versus 1500 nm. Bright pulses exceeding 4×10^6 photons can bypass all protections.

Primary countermeasures: Narrow-band optical filters, optical isolators, active phase randomization, monitoring reflected light intensity, and MDI/DI-QKD architectures that eliminate device-side trust.

2.3 Jamming Attacks

A jamming attack is a Denial-of-Service (DoS) strategy in which Eve introduces sufficient noise into the quantum channel to force a QBER above the abort threshold, preventing Alice and Bob from generating a usable key. Under a depolarizing noise injection with probability p , the channel fidelity degrades as:

$$F = 1 - \frac{p}{2}$$

and the induced QBER becomes:

$$\text{QBER}_{\text{induced}} = 1 - \cos^2(\beta)$$

where β is the polarization rotation angle induced by the jamming field.

Jamming Attack: Key Findings

- **Daschner et al. (2019) — Faraday Jamming:** An external magnetic field rotates photon polarization by $\beta = VB_0L$ (Verdet constant times field strength times fiber length). A rotation of $\beta = 16^\circ$ increases QBER by 7.6%, effectively halting key exchange in standard telecom fiber.
- **Boche et al. (2017) — Arbitrarily Varying Wiretap Channels:** A formal model proves that if a channel is “symmetrizable,” its deterministic secrecy capacity is zero—the jammer can force silence. Remarkably, two channels with zero secrecy capacity can be *super-activated* when combined.
- **Boche et al. (2019) — Simultaneous Classical-Quantum Jamming:** Extension to simultaneous classical and quantum communication under active jamming, with super-activation of capacity for arbitrarily varying quantum channels.
- **Simmons et al. (2023) — Free-Space & Satellite Jamming:** Direct Line-of-Sight blinding of SPADs can be mitigated (≈ 20 dB improvement in signal-to-interference ratio) using SPAD arrays. Non-Line-of-Sight reflective jamming off satellites, however, remains an open and largely unsolved problem.

Primary countermeasures: Spatial filtering with SPAD arrays; frequency-hopping; real-time QBER monitoring with adaptive routing; MDI-QKD; and robust coding schemes.

3 Security Proofs & Error Correction

3.1 Security Paradigms in QKD

QKD's security guarantees are formalized through three increasingly demanding paradigms, each suited to different operational contexts.

3.1.1 Unconditional Security

Unconditional (or information-theoretic) security ensures that Eve's probability of successfully estimating any subset K^* of the key is negligible regardless of her computational resources. The standard measure is *trace distance*: the distance between the actual key distribution ρ_{KE} and an ideal uniform distribution $\rho_U \otimes \rho_E$:

$$d = \frac{1}{2} \|\rho_{KE} - \rho_U \otimes \rho_E\|_1 \leq \varepsilon$$

When $d \leq \varepsilon$, Eve's success probability in guessing the key is bounded by $\frac{1}{2^n} + \varepsilon$.

Important Caveat

The trace distance criterion, while standard, can **overestimate** the actual security level—particularly in finite-key and Known-Plaintext Attack scenarios. Achieving true unconditional security requires significantly smaller ε values than often assumed.

3.1.2 Finite-Key Security

Asymptotic security proofs assume infinite key lengths. In practice, only finite-length keys are exchanged, introducing statistical fluctuations that must be carefully bounded. Bunandar et al. (2020) developed a numerical framework using

semi-definite programs (SDPs) to compute finite-key rates via smooth min-entropy, achieving composable security:

$$R = p_{\text{succ}} [1 - h(e_{\text{bit}}) - h(e_{\text{phase}})]$$

This framework has been applied to BB84 with detector asymmetries, the B92 protocol, and Twin-Field QKD.

3.1.3 Composable Security

Composable security ensures that keys generated by QKD remain secure even when used in larger cryptographic systems or combined with other protocols. Ben-Or et al. (2005) established that protocols like BB84 achieve composable security by proving indistinguishability between the real key state and an ideal key state:

$$\|\rho_{\text{qkd}} - \rho_{\text{ideal}}\|_1 \leq \varepsilon$$

This is the gold standard for cryptographic security in deployed systems.

3.2 Major Security Proofs

Lo-Chau Security Proof (1999)

Alice and Bob distill near-perfect EPR pairs from noisy entangled states using quantum error correction (entanglement distillation). The fidelity of the distilled state to the ideal EPR pair is bounded:

$$F(\rho_{ABE}, |\Phi^+\rangle^{\otimes m} \otimes \rho_E) \geq 1 - \varepsilon_f$$

This connects QKD security directly to entanglement distillation and provides security against all *coherent* attacks. A key limitation: distillation may fail with low probability in finite-data scenarios.

Shor-Preskill Security Proof (2000) --- BB84

This landmark proof reinterprets BB84 as an entanglement-based protocol, then shows that Calderbank-Shor-Steane (CSS) quantum error correction codes can simultaneously correct bit errors (in the Z basis) and phase errors (in the X basis). The final key rate is:

$$R = 1 - h(e_b) - h(e_p)$$

Security holds whenever $h(e_b) + h(e_p) < 1$. The proof's use of CSS codes creates a direct and explicit bridge to quantum error correction machinery.

Composable Security for CV-QKD (Leverrier, 2015)

Using the postselection technique or de Finetti's theorem to reduce general attacks to collective attacks, the composable finite-key rate for CV-QKD with Gaussian modulation is:

$$R \approx 1 - h(e_{\text{bit}}) - h(e_{\text{phase}})$$

Gaussian attacks are confirmed to be asymptotically optimal under this framework. Finite-size rates converge to asymptotic values for sufficiently large n .

Security Proof for the Three-Stage Protocol (Chan et al.)

The three-stage protocol is shown resilient against Intercept-Resend (IR), PNS, and Man-in-the-Middle (MIM) attacks for coherent states with mean photon number $N > 1$. The secure key rate is:

$$K = R[1 - h(Q)] - f \cdot \Delta P_e$$

where Q is the QBER and ΔP_e is Eve's induced error probability. Sensitivity to amplification attacks and multi-transmission photon loss remain open challenges.

3.3 Quantum Error Correction Codes

Quantum Error Correction (QEC) is essential to any practical QKD deployment. Unlike classical coding, QEC must contend with the no-cloning theorem (prohibiting direct data duplication) and must correct not just bit flips but also phase flips and their combinations. A quantum error correction code is characterized as $Q: [[n, k, d]]$ —encoding k logical qubits into n physical qubits with distance d (correcting up to $\lfloor (d-1)/2 \rfloor$ errors).

The principal error types in quantum communication are:

- **Coherent errors:** Miscalibrated gates causing systematic rotation errors.
- **Decoherence:** Environment coupling that destroys quantum coherence.
- **Photon loss:** Modeled by Beer-Lambert exponential decay $P_{\text{loss}} = 1 - e^{-\lambda L}$.
- **NISQ errors:** Gate infidelity, finite coherence times (T_1 , T_2), and readout errors in near-term quantum hardware.

3.3.1 Landmark Codes

- **3-Qubit Repetition Code** $[[3, 1, 3]]$: Encodes one logical qubit into three physical qubits. Corrects a single bit-flip error via ancilla-based syndrome measurement. No phase-flip protection.
- **5-Qubit Perfect Code** $[[5, 1, 3]]$: The smallest code capable of correcting an arbitrary single-qubit error (bit-flip, phase-flip, or combined). Uses stabilizer formalism with generators in the set $\{XZZXI, IXZZX, XIXZZ, ZXIXZ\}$.
- **7-Qubit Steane Code** $[[7, 1, 3]]$: A CSS code built from the classical $[7, 4, 3]$ Hamming code. Corrects any single-qubit bit-flip or phase-flip error. Foundational for fault-tolerant quantum computing.
- **9-Qubit Shor Code** $[[9, 1, 3]]$: The first QECC to correct arbitrary single-qubit errors by combining a 3-qubit bit-flip repetition code with a phase-flip encoding. A concatenated code that remains conceptually foundational.
- **CSS Codes (General)**: A family of codes constructed from two classical linear codes C_1 and C_2 with $C_2^\perp \subseteq C_1$. Bit-flip errors are detected by the parity check matrix of C_1 ; phase-flip errors by $C_2^\perp$. This is the code family underlying the Shor-Preskill proof.

3.3.2 Recent Experimental Breakthroughs

State-of-the-Art QECC Implementations

- **Binomial Bosonic Codes (Michael et al., 2016):** A novel class of error correcting codes for bosonic modes (e.g., microwave cavities), protecting against photon loss, gain, and dephasing using Fock state superpositions. Uncorrectable error rate scales as κ^L for L photon-loss events.
- **3-Qubit Code in Superconducting Qubits (Reed et al., 2012):** Experimental realization of bit-flip and phase-flip correction using transmon qubits. Process fidelity reached 76% with first-order insensitivity to errors. Toffoli gate achieved 85% fidelity.
- **Distance-3 Surface Code (Cai et al., 2021):** Nine data qubits + eight auxiliary qubits implement a topological surface code with QEC cycle time of $1.1 \mu\text{s}$. Logical error rate $\varepsilon_L \propto p^2$, achieving second-order fault tolerance. Logical coherence time $T_2 \approx 18.2 \mu\text{s}$.
- **GKP code beyond break-even (Sivak et al., 2023):** A Gottesman-Kitaev-Preskill bosonic encoding in superconducting circuits achieved logical coherence times $T_X = T_Z = 2.20 \text{ ms}$, surpassing the best physical qubit in the system by a factor of $G = 2.27$. Reinforcement learning was used to optimize QEC parameters in real time.
- **Steane QEC in Trapped Ions (Postler et al., 2024):** Fault-tolerant Steane syndrome extraction using transversal CNOT gates on a 7-qubit color code. Outperformed flag-based QEC approaches, particularly in the regime dominated by two-qubit gate errors.

Conclusion & Implications for Quantum-Augmented Networks

Quantum-Augmented Networks (QuANets)

Quantum-Augmented Networks (QuANets) represent a practical near-term path to global-scale quantum-secured communications. Rather than requiring a fully quantum internet, QuANets integrate quantum components *strategically* within classical network infrastructure: quantum resources (qubit channels, single-photon detectors, quantum memories) are reserved for high-value, private traffic, while classical infrastructure carries the bulk of communications.

Every design decision in a QuANet—from hardware selection to routing policy—must be informed by the security analysis reviewed in this whitepaper.

Key Implications for QuANet Design

1. Hardware-Layer Security

Trojan Horse and PNS attacks demand that quantum gateways and switches incorporate optical isolators, narrow-band filters, real-time reflectometry, and decoy-state intensity monitoring. Passive security assumptions are insufficient—active, instrumented monitoring of side-channel leakage is mandatory at every node arbitrating between classical and quantum paths.

2. Denial-of-Service Resilience

QuANets are inherently exposed to both quantum jamming (polarization rotation, SPAD blinding) and classical DoS attacks. Real-time QBER monitoring, adaptive routing logic (diverting quantum payloads to backup paths or falling back to classical encryption when QBER thresholds are exceeded), and SPAD array receivers for free-space links are essential operational requirements.

3. Error Correction at the Network Layer

In QuANets, quantum channels may co-propagate with classical WDM traffic in a single fiber, increasing crosstalk and error rates beyond those of dedicated QKD links. Surface codes with distance $d \geq 3$, fault-tolerant syndrome extraction, and adaptive (ML-assisted) QEC parameter tuning will be necessary to reach “break-even” logical qubit coherence under realistic network conditions.

4. Security Proof Alignment with Routing Policy

The characterization of channel symmetrizability (zero deterministic secrecy capacity) directly informs QuANet routing: links determined to be symmetrizable under active jamming must be excluded from quantum payload routing or relegated to classical fallback. Security proofs must be applied at the network control plane, not just the physical layer.

Open Research Challenges

Despite significant progress, several critical gaps remain:

- **Unified attack models:** No current framework simultaneously models PNS, Trojan Horse, and jamming attacks with realistic, finite-key bounds. Most experimental demonstrations address these threats in isolation.
- **Non-Gaussian probe analysis:** Trojan Horse security analyses are largely restricted to Gaussian attack states. Non-Gaussian probes may achieve higher information gain than current bounds suggest.
- **QECC integration into QKD networks:** Most QECC demonstrations use idealized noise models. Tailoring codes to real QKD network error profiles—including side-channel and adversarial errors—remains largely unexplored.
- **Satellite and free-space jamming:** Reflective non-line-of-sight jamming of satellite QKD links has no effective countermeasure. This is a critical gap for global-scale quantum communication.
- **ML-guided attacks and defenses:** Adversarially adaptive jamming using neural network feedback represents an emerging frontier with no established formal defense framework.

Final Remarks

The transition from theoretical QKD security proofs to deployed, resilient quantum-augmented networks is neither automatic nor straightforward. The laws of quantum mechanics offer genuinely unprecedented cryptographic guarantees—but realizing those guarantees in practice demands rigorous co-design of protocols, hardware, error correction, and network architecture. This whitepaper has traced the full chain from foundational protocol design through practical attack vectors, security proof frameworks, and error correction breakthroughs to the emerging QuANet paradigm.

The literature is clear: information-theoretic security is achievable, but only when theoretical ideals are matched by rigorous engineering at every layer of the stack.

Bibliography

Ben-Or, Michael et al.

“The universal composable security of quantum key distribution.”

In: (2005), pp. 386–406.

Bennett, Charles H. and Gilles Brassard.

“An update on quantum cryptography.”

In: *Advances in Cryptology – CRYPTO ’84* (1984), pp. 475–480.

Boche, Holger et al.

“Classical-quantum arbitrarily varying wiretap channel: Secret message transmission under jamming attacks.”

In: *Journal of Mathematical Physics* 58.10 (2017).

Devitt, Simon J., William J. Munro, and Kae Nemoto.

“Quantum error correction for beginners.”

In: *Reports on Progress in Physics* 76.7 (2013), p. 076001.

Gisin, Nicolas et al.

“Quantum cryptography.”

In: *Reviews of Modern Physics* 74 (2002), pp. 145–195.

— “Trojan-horse attacks on quantum-key-distribution systems.”

In: *Physical Review A* 73 (2006), p. 022320.

Jha, Nitin, Abhishek Parakh, and Mahadevan Subramaniam.

“Joint encryption and error correction for secure quantum communication.”

In: *Scientific Reports* 14 (2024), p. 24542.

Lo, Hoi-Kwong and Hoi Fung Chau.

“Unconditional security of quantum key distribution over arbitrarily long distances.”

In: *Science* 283 (1999), pp. 2050–2056.

Lucamarini, Marco et al.

“Overcoming the rate–distance limit of quantum key distribution without quantum repeaters.”

In: *Nature* 557 (2018), pp. 400–403.

Mailloux, Laurence O. et al.

“Using modeling and simulation to study photon number splitting attacks.”

In: *IEEE Access* 4 (2016), pp. 2188–2197.

Scarani, V. et al.

“The security of practical quantum key distribution.”

In: *Reviews of Modern Physics* 81 (2009), p. 1301.

Shor, Peter W. and John Preskill.

“Simple proof of security of the BB84 quantum key distribution protocol.”

In: *Physical Review Letters* 85 (2000), p. 441.

Sivak, V. V. et al.

“Real-time quantum error correction beyond break-even.”

In: *Nature* 616 (2023), pp. 50–55.

Xu, Feihu et al.

“Secure quantum key distribution with realistic devices.”

In: *Reviews of Modern Physics* 92.2 (2020), p. 025002.

