

The entire code repository can be found at <https://github.com/dgsaf/hpc-assignment-4>.

## Contents

<b>1</b>	<b>Interpretation</b>	<b>2</b>
<b>2</b>	<b>Development</b>	<b>4</b>
2.1	Bash For Loop . . . . .	4
2.2	xargs Command . . . . .	4
<b>3</b>	<b>Execution</b>	<b>5</b>
3.1	SNR Plot . . . . .	5
3.2	Workflow DAG . . . . .	5
<b>4</b>	<b>Analysis</b>	<b>7</b>

## List of Figures

1	SNR Plot . . . . .	5
2	Workflow DAG . . . . .	6

## List of Tables

# 1 Interpretation

The count process is presented in [Listing 4](#).

```

48 process count {
49   input:
50   path(files) from files_ch.collect()
51
52   output:
53   file("results.csv") into counted_ch
54
55   container = ""
56
57   shell:
58   '''
59   echo "seed,ncores,nsrc" > results.csv
60   files=$(ls table*.csv)
61   for f in ${files[@]}; do
62     seed_cores=$(echo ${f} | tr '_' ' ' | awk '{print $2 " " $3}')
63     seed=${seed_cores[0]}
64     cores=${seed_cores[1]}
65     nsrc=$(echo "$(cat ${f} | wc -l) - 1" | bc -l)
66     echo "${seed},${cores},${nsrc}" >> results.csv
67   done
68   '''
69 }

```

Listing 1: The process *process* count in *nextflow/main.nf*.

- i. `echo "seed,ncores,nsrc" > results.csv`

The output of the left hand side (SNR seed, number of cores used and number of sources counted) which would normally be sent to `stdout` is redirected to the destination specified on the right hand side (in this case, a file called `results.csv`) creating/overwriting the file in the process.

- ii. `echo "${seed},${cores},${nsrc}" >> results.csv`

Similar to the effect of `>` above, except that this operator appends to the file, rather than overwriting it.

- iii. `cat ${f} | wc -l`

The output of the left hand (normally send to `stdout`) is *piped* to input of the right hand side; that is, the input of `wc -l` is taken from the output of `cat ${f}`. This effect of this command is to count the number of lines in the file with filepath `${f}`.

- iv. `$(<command>)` and `$((<command>))`

Wrapping a shell command with a single pair of parentheses, `(<command>)` executes that command in a sub-shell - prefixing this with a dollar sign captures the final output of that subshell `$(<command>)`. However if the result of this is a list of whitespace-delimited strings, wrapping this in a further set of parentheses, `$((<command>))`, will capture the output as an array variable.

- v. `$(ls table*.csv)`

The effect of `ls table*.csv` is to list all files in the current directory which start with `table` and end with `.csv`. The effect of `$(ls table*.csv)` is to capture this list of matching files as a string. Specifically, it collects the files containing tables of counted sources for all combinations of `seed` and `cores`.

vi. `echo ${f}`

The effect of this command is to output (to `stdout`) the string-value of the variable `f`. Specifically, this outputs the filepath of a specific file, which is taken from the list of tables described above, and will be of the form `table_<seeds>_<cores>.csv`.

vii. `tr '._' ' '`

The effect of this command is, for a given input, to translate all instances of the characters `_` and `.` into whitespace. Specifically this transforms `table_<seeds>_<cores>.csv` into `table <seeds> <cores> csv`.

viii. `awk '{print $2 " " $3}'`

The effect of this command is, for a given input consisting of lines (delimited by `\n`) containing records (delimited by whitespace), to print the second record, followed by a white space, followed by the third record, for each line in the input. Specifically, this transforms `table <seeds> <cores> csv` into `<seeds> <cores>`.

ix. `cat ${f}`

x. `wc -l`

xi. `echo "$(cat ${f} | wc -l)-1" | bc -l`

## 2 Development

```
72 counted_ch.into{counted_for_ch; counted_xargs_ch}
```

*Listing 2: The channel `counted_ch` is duplicated, with one for each of `process plot_for`, and `process plot_xargs`, in `nextflow/main.nf`.*

### 2.1 Bash For Loop

```
75 process plot_for {
76   input:
77   path(table) from counted_for_ch
78
79   output:
80   file("*.png") into final_for_ch
81
82   cpus 4
83
84   shell:
85   '''
86   ncores_set=$(awk -F, '{if (NR != 1) {print $2}}' !{table} | sort | uniq)
87
88   for ncores in $ncores_set ; do
89     python !{projectDir}/plot_completeness.py \
90       --infile !{table} --outfile plot_for_${ncores}.png --cores $ncores
91   done
92   '''
93 }
```

*Listing 3: The process `process plot_for` in `nextflow/main.nf`.*

### 2.2 xargs Command

```
96 process plot_xargs {
97   input:
98   path(table) from counted_xargs_ch
99
100  output:
101  file("*.png") into final_xargs_ch
102
103  cpus 4
104
105  shell:
106  '''
107  ncores_set=$(awk -F, '{if (NR != 1) {print $2}}' !{table} | sort | uniq)
108
109  printf '%s ' $ncores_set | xargs -n1 -P4 -I ncores -d ' ' \
110  python !{projectDir}/plot_completeness.py \
111  --infile !{table} --outfile plot_xargs_ncores.png --cores ncores
112  '''
113 }
```

*Listing 4: The process `process plot_for` in `nextflow/main.nf`.*

### 3 Execution

#### 3.1 SNR Plot




Figure 1: The Signal-to-Noise Ratio (SNR) is presented for a range of seed SNR values. This figure was produced by `process plot_for`, for the case of `cores = 1`. No difference was observed between this plot and any of the other plots produced for any value of `cores`, nor whether if `process plot_for` or if `process plot_xargs` were used.

#### 3.2 Workflow DAG




Figure 2: The Directed Acyclic Graph (DAG) of the workflow is presented. Note that the *combine* operator (below *Channel.of*) appears to have been cropped out by the tool producing the DAG.

## 4 Analysis