

[Getting started](#)[Layout](#)[Content](#)[Reboot](#)[Typography](#)[Code](#)[Images](#)[Tables](#)[Figures](#)[Components](#)[Utilities](#)[Extend](#)[Migration](#)[About](#)

Tables

Documentation and examples for opt-in styling of tables (given their prevalent use in JavaScript plugins) with Bootstrap.



Adobe Creative Cloud for
Teams starting at \$33.99
per month.
ads via Carbon

Examples

Due to the widespread use of tables across third-party widgets like calendars and date pickers, we've designed our tables to be **opt-in**. Just add the base class `.table` to any `<table>`, then extend with custom styles or our various included modifier classes.

Using the most basic table markup, here's how `.table`-based tables look in Bootstrap. **All table styles are inherited in Bootstrap 4**, meaning any nested tables will be styled in the same manner as the parent.

#	First	Last	Handle
1	Mark	Otto	@mdo
2	Jacob	Thornton	@fat
3	Larry	the Bird	@twitter

Copy

```

<table class="table">
  <thead>
    <tr>
      <th scope="col">#</th>
      <th scope="col">First</th>
      <th scope="col">Last</th>
      <th scope="col">Handle</th>
    </tr>
  </thead>
  <tbody>
    <tr>
      <th scope="row">1</th>
      <td>Mark</td>
      <td>Otto</td>
      <td>@mdo</td>
    </tr>
    <tr>
      <th scope="row">2</th>
      <td>Jacob</td>
      <td>Thornton</td>
      <td>@fat</td>
    </tr>
    <tr>
      <th scope="row">3</th>
      <td>Larry</td>
      <td>the Bird</td>
      <td>@twitter</td>
    </tr>
  </tbody>
</table>

```

You can also invert the colors—with light text on dark backgrounds—with `.table-dark`.

#	First	Last	Handle
1	Mark	Otto	@mdo
2	Jacob	Thornton	@fat
3	Larry	the Bird	@twitter

Copy

```

<table class="table table-dark">
  <thead>
    <tr>
      <th scope="col">#</th>
      <th scope="col">First</th>
      <th scope="col">Last</th>
      <th scope="col">Handle</th>
    </tr>
  </thead>
  <tbody>
    <tr>
      <th scope="row">1</th>
      <td>Mark</td>
      <td>Otto</td>
      <td>@mdo</td>
    </tr>
    <tr>
      <th scope="row">2</th>
      <td>Jacob</td>
      <td>Thornton</td>
      <td>@fat</td>
    </tr>
    <tr>
      <th scope="row">3</th>
      <td>Larry</td>
      <td>the Bird</td>
      <td>@twitter</td>
    </tr>
  </tbody>
</table>

```

Table head options

Similar to tables and dark tables, use the modifier classes `.thead-light` or `.thead-dark` to make `<thead>`s appear light or dark gray.

#	First	Last	Handle
1	Mark	Otto	@mdo
2	Jacob	Thornton	@fat
3	Larry	the Bird	@twitter
#	First	Last	Handle
1	Mark	Otto	@mdo
2	Jacob	Thornton	@fat
3	Larry	the Bird	@twitter

```

<table class="table">
  <thead class="thead-dark">
    <tr>
      <th scope="col">#</th>
      <th scope="col">First</th>
      <th scope="col">Last</th>
      <th scope="col">Handle</th>
    </tr>
  </thead>
  <tbody>
    <tr>
      <th scope="row">1</th>
      <td>Mark</td>
      <td>Otto</td>
      <td>@mdo</td>
    </tr>
    <tr>
      <th scope="row">2</th>
      <td>Jacob</td>
      <td>Thornton</td>
      <td>@fat</td>
    </tr>
    <tr>
      <th scope="row">3</th>
      <td>Larry</td>
      <td>the Bird</td>
      <td>@twitter</td>
    </tr>
  </tbody>
</table>

```


```

<table class="table">
  <thead class="thead-light">
    <tr>
      <th scope="col">#</th>
      <th scope="col">First</th>
      <th scope="col">Last</th>
      <th scope="col">Handle</th>
    </tr>
  </thead>
  <tbody>
    <tr>
      <th scope="row">1</th>
      <td>Mark</td>
      <td>Otto</td>
      <td>@mdo</td>
    </tr>
    <tr>
      <th scope="row">2</th>
      <td>Jacob</td>
      <td>Thornton</td>
      <td>@fat</td>
    </tr>
    <tr>
      <th scope="row">3</th>
      <td>Larry</td>
      <td>the Bird</td>
      <td>@twitter</td>
    </tr>
  </tbody>
</table>

```

Striped rows

Use `.table-striped` to add zebra-striping to any table row within the `<tbody>`.



#	First	Last	Handle
1	Mark	Otto	@mdo
2	Jacob	Thornton	@fat
3	Larry	the Bird	@twitter

Copy

```
<table class="table table-striped">
  <thead>
    <tr>
      <th scope="col">#</th>
      <th scope="col">First</th>
      <th scope="col">Last</th>
      <th scope="col">Handle</th>
    </tr>
  </thead>
  <tbody>
    <tr>
      <th scope="row">1</th>
      <td>Mark</td>
      <td>Otto</td>
      <td>@mdo</td>
    </tr>
    <tr>
      <th scope="row">2</th>
      <td>Jacob</td>
      <td>Thornton</td>
      <td>@fat</td>
    </tr>
    <tr>
      <th scope="row">3</th>
      <td>Larry</td>
      <td>the Bird</td>
      <td>@twitter</td>
    </tr>
  </tbody>
</table>
```

#	First	Last	Handle
1	Mark	Otto	@mdo
2	Jacob	Thornton	@fat
3	Larry	the Bird	@twitter

Copy

```

<table class="table table-striped table-dark">
  <thead>
    <tr>
      <th scope="col">#</th>
      <th scope="col">First</th>
      <th scope="col">Last</th>
      <th scope="col">Handle</th>
    </tr>
  </thead>
  <tbody>
    <tr>
      <th scope="row">1</th>
      <td>Mark</td>
      <td>Otto</td>
      <td>@mdo</td>
    </tr>
    <tr>
      <th scope="row">2</th>
      <td>Jacob</td>
      <td>Thornton</td>
      <td>@fat</td>
    </tr>
    <tr>
      <th scope="row">3</th>
      <td>Larry</td>
      <td>the Bird</td>
      <td>@twitter</td>
    </tr>
  </tbody>
</table>

```

Bordered table

Add `.table-bordered` for borders on all sides of the table and cells.

#	First	Last	Handle
1	Mark	Otto	@mdo
2	Jacob	Thornton	@fat
3	Larry the Bird		@twitter

Copy

```
<table class="table table-bordered">
  <thead>
    <tr>
      <th scope="col">#</th>
      <th scope="col">First</th>
      <th scope="col">Last</th>
      <th scope="col">Handle</th>
    </tr>
  </thead>
  <tbody>
    <tr>
      <th scope="row">1</th>
      <td>Mark</td>
      <td>Otto</td>
      <td>@mdo</td>
    </tr>
    <tr>
      <th scope="row">2</th>
      <td>Jacob</td>
      <td>Thornton</td>
      <td>@fat</td>
    </tr>
    <tr>
      <th scope="row">3</th>
      <td colspan="2">Larry the Bird</td>
      <td>@twitter</td>
    </tr>
  </tbody>
</table>
```

#	First	Last	Handle
1	Mark	Otto	@mdo
2	Jacob	Thornton	@fat
3	Larry the Bird		@twitter

```

<table class="table table-bordered table-dark">
  <thead>
    <tr>
      <th scope="col">#</th>
      <th scope="col">First</th>
      <th scope="col">Last</th>
      <th scope="col">Handle</th>
    </tr>
  </thead>
  <tbody>
    <tr>
      <th scope="row">1</th>
      <td>Mark</td>
      <td>Otto</td>
      <td>@mdo</td>
    </tr>
    <tr>
      <th scope="row">2</th>
      <td>Jacob</td>
      <td>Thornton</td>
      <td>@fat</td>
    </tr>
    <tr>
      <th scope="row">3</th>
      <td colspan="2">Larry the Bird</td>
      <td>@twitter</td>
    </tr>
  </tbody>
</table>

```

Borderless table

Add `.table-borderless` for a table without borders.

#	First	Last	Handle
1	Mark	Otto	@mdo
2	Jacob	Thornton	@fat
3	Larry the Bird		@twitter

Copy


```

<table class="table table-borderless">
  <thead>
    <tr>
      <th scope="col">#</th>
      <th scope="col">First</th>
      <th scope="col">Last</th>
      <th scope="col">Handle</th>
    </tr>
  </thead>
  <tbody>
    <tr>
      <th scope="row">1</th>
      <td>Mark</td>
      <td>Otto</td>
      <td>@mdo</td>
    </tr>
    <tr>
      <th scope="row">2</th>
      <td>Jacob</td>
      <td>Thornton</td>
      <td>@fat</td>
    </tr>
    <tr>
      <th scope="row">3</th>
      <td colspan="2">Larry the Bird</td>
      <td>@twitter</td>
    </tr>
  </tbody>
</table>

```

`.table-borderless` can also be used on dark tables.

#	First	Last	Handle
1	Mark	Otto	@mdo
2	Jacob	Thornton	@fat
3	Larry the Bird		@twitter

Copy

```

<table class="table table-borderless table-dark">
  <thead>
    <tr>
      <th scope="col">#</th>
      <th scope="col">First</th>
      <th scope="col">Last</th>
      <th scope="col">Handle</th>
    </tr>
  </thead>
  <tbody>
    <tr>
      <th scope="row">1</th>
      <td>Mark</td>
      <td>Otto</td>
      <td>@mdo</td>
    </tr>
    <tr>
      <th scope="row">2</th>
      <td>Jacob</td>
      <td>Thornton</td>
      <td>@fat</td>
    </tr>
    <tr>
      <th scope="row">3</th>
      <td colspan="2">Larry the Bird</td>
      <td>@twitter</td>
    </tr>
  </tbody>
</table>

```

Hoverable rows

Add `.table-hover` to enable a hover state on table rows within a `<tbody>`.

#	First	Last	Handle
1	Mark	Otto	@mdo
2	Jacob	Thornton	@fat
3	Larry the Bird		@twitter

Copy

```
<table class="table table-hover">
  <thead>
    <tr>
      <th scope="col">#</th>
      <th scope="col">First</th>
      <th scope="col">Last</th>
      <th scope="col">Handle</th>
    </tr>
  </thead>
  <tbody>
    <tr>
      <th scope="row">1</th>
      <td>Mark</td>
      <td>Otto</td>
      <td>@mdo</td>
    </tr>
    <tr>
      <th scope="row">2</th>
      <td>Jacob</td>
      <td>Thornton</td>
      <td>@fat</td>
    </tr>
    <tr>
      <th scope="row">3</th>
      <td colspan="2">Larry the Bird</td>
      <td>@twitter</td>
    </tr>
  </tbody>
</table>
```

#	First	Last	Handle
1	Mark	Otto	@mdo
2	Jacob	Thornton	@fat
3	Larry the Bird		@twitter

```

<table class="table table-hover table-dark">
  <thead>
    <tr>
      <th scope="col">#</th>
      <th scope="col">First</th>
      <th scope="col">Last</th>
      <th scope="col">Handle</th>
    </tr>
  </thead>
  <tbody>
    <tr>
      <th scope="row">1</th>
      <td>Mark</td>
      <td>Otto</td>
      <td>@mdo</td>
    </tr>
    <tr>
      <th scope="row">2</th>
      <td>Jacob</td>
      <td>Thornton</td>
      <td>@fat</td>
    </tr>
    <tr>
      <th scope="row">3</th>
      <td colspan="2">Larry the Bird</td>
      <td>@twitter</td>
    </tr>
  </tbody>
</table>

```

Small table

Add `.table-sm` to make tables more compact by cutting cell padding in half.

#	First	Last	Handle
1	Mark	Otto	@mdo
2	Jacob	Thornton	@fat
3	Larry the Bird		@twitter

Copy

```
<table class="table table-sm">
  <thead>
    <tr>
      <th scope="col">#</th>
      <th scope="col">First</th>
      <th scope="col">Last</th>
      <th scope="col">Handle</th>
    </tr>
  </thead>
  <tbody>
    <tr>
      <th scope="row">1</th>
      <td>Mark</td>
      <td>Otto</td>
      <td>@mdo</td>
    </tr>
    <tr>
      <th scope="row">2</th>
      <td>Jacob</td>
      <td>Thornton</td>
      <td>@fat</td>
    </tr>
    <tr>
      <th scope="row">3</th>
      <td colspan="2">Larry the Bird</td>
      <td>@twitter</td>
    </tr>
  </tbody>
</table>
```

#	First	Last	Handle
1	Mark	Otto	@mdo
2	Jacob	Thornton	@fat
3	Larry the Bird		@twitter

```
<table class="table table-sm table-dark">
  <thead>
    <tr>
      <th scope="col">#</th>
      <th scope="col">First</th>
      <th scope="col">Last</th>
      <th scope="col">Handle</th>
    </tr>
  </thead>
  <tbody>
    <tr>
      <th scope="row">1</th>
      <td>Mark</td>
      <td>Otto</td>
      <td>@mdo</td>
    </tr>
    <tr>
      <th scope="row">2</th>
      <td>Jacob</td>
      <td>Thornton</td>
      <td>@fat</td>
    </tr>
    <tr>
      <th scope="row">3</th>
      <td colspan="2">Larry the Bird</td>
      <td>@twitter</td>
    </tr>
  </tbody>
</table>
```

Contextual classes

Use contextual classes to color table rows or individual cells.

Class	Heading	Heading
Active	Cell	Cell
Default	Cell	Cell
Primary	Cell	Cell
Secondary	Cell	Cell
Success	Cell	Cell
Danger	Cell	Cell
Warning	Cell	Cell
Info	Cell	Cell
Light	Cell	Cell
Dark	Cell	Cell

```
<!-- On rows -->
<tr class="table-active">...</tr>

<tr class="table-primary">...</tr>
<tr class="table-secondary">...</tr>
<tr class="table-success">...</tr>
<tr class="table-danger">...</tr>
<tr class="table-warning">...</tr>
<tr class="table-info">...</tr>
<tr class="table-light">...</tr>
<tr class="table-dark">...</tr>

<!-- On cells (`td` or `th`) -->
<tr>
  <td class="table-active">...</td>

  <td class="table-primary">...</td>
  <td class="table-secondary">...</td>
  <td class="table-success">...</td>
  <td class="table-danger">...</td>
  <td class="table-warning">...</td>
  <td class="table-info">...</td>
  <td class="table-light">...</td>
  <td class="table-dark">...</td>
</tr>
```

Regular table background variants are not available with the dark table, however, you may use [text or background utilities](#) to achieve similar styles.

#	Heading	Heading
1	Cell	Cell
2	Cell	Cell
3	Cell	Cell
4	Cell	Cell
5	Cell	Cell
6	Cell	Cell
7	Cell	Cell
8	Cell	Cell
9	Cell	Cell

```

<!-- On rows -->
<tr class="bg-primary">...</tr>
<tr class="bg-success">...</tr>
<tr class="bg-warning">...</tr>
<tr class="bg-danger">...</tr>
<tr class="bg-info">...</tr>

<!-- On cells (`td` or `th`) -->
<tr>
  <td class="bg-primary">...</td>
  <td class="bg-success">...</td>
  <td class="bg-warning">...</td>
  <td class="bg-danger">...</td>
  <td class="bg-info">...</td>
</tr>

```

Conveying meaning to assistive technologies

Using color to add meaning only provides a visual indication, which will not be conveyed to users of assistive technologies – such as screen readers. Ensure that information denoted by the color is either obvious from the content itself (e.g. the visible text), or is included through alternative means, such as additional text hidden with the `.sr-only` class.

Create responsive tables by wrapping any `.table` with `.table-responsive{-sm|-md|-lg|-xl}`, making the table scroll horizontally at each `max-width` breakpoint of up to (but not including) 576px, 768px, 992px, and 1120px, respectively.

Note that since browsers do not currently support [range context queries](#), we work around the limitations of [min- and max- prefixes](#) and viewports with fractional widths (which can occur under certain conditions on high-dpi devices, for instance) by using values with higher precision for these comparisons.

Captions

A `<caption>` functions like a heading for a table. It helps users with screen readers to find a table and understand what it's about and decide if they want to read it.

#	First	Last	Handle
1	Mark	Otto	@mdo
2	Jacob	Thornton	@fat
3	Larry	the Bird	@twitter

List of users

Copy


```

<table class="table">
  <caption>List of users</caption>
  <thead>
    <tr>
      <th scope="col">#</th>
      <th scope="col">First</th>
      <th scope="col">Last</th>
      <th scope="col">Handle</th>
    </tr>
  </thead>
  <tbody>
    <tr>
      <th scope="row">1</th>
      <td>Mark</td>
      <td>Otto</td>
      <td>@mdo</td>
    </tr>
    <tr>
      <th scope="row">2</th>
      <td>Jacob</td>
      <td>Thornton</td>
      <td>@fat</td>
    </tr>
    <tr>
      <th scope="row">3</th>
      <td>Larry</td>
      <td>the Bird</td>
      <td>@twitter</td>
    </tr>
  </tbody>
</table>

```

Responsive tables

Responsive tables allow tables to be scrolled horizontally with ease. Make any table responsive across all viewports by wrapping a `.table` with `.table-responsive`. Or, pick a maximum breakpoint with which to have a responsive table up to by using `.table-responsive{-sm|-md|-lg|-xl}`.

Vertical clipping/truncation

Responsive tables make use of `overflow-y: hidden`, which clips off any content that goes beyond the bottom or top edges of the table. In particular, this can clip off dropdown menus and other third-party widgets.

Always responsive

Across every breakpoint, use `.table-responsive` for horizontally scrolling tables.

#	Heading	Heading	Heading	Heading	Heading	Heading	Heading
1	Cell	Cell	Cell	Cell	Cell	Cell	Cell
2	Cell	Cell	Cell	Cell	Cell	Cell	Cell
3	Cell	Cell	Cell	Cell	Cell	Cell	Cell

```
<div class="table-responsive">
  <table class="table">
    ...
  </table>
</div>
```

Breakpoint specific

Use `.table-responsive{-sm|-md|-lg|-xl}` as needed to create responsive tables up to a particular breakpoint. From that breakpoint and up, the table will behave normally and not scroll horizontally.

These tables may appear broken until their responsive styles apply at specific viewport widths.

[illegible]

```
<div class="table-responsive-sm">
  <table class="table">
    ...
  </table>
</div>
```

Copy

[illegible]

```
<div class="table-responsive-md">
  <table class="table">
    ...
  </table>
</div>
```

Copy

[illegible]

```
<div class="table-responsive-lg">
  <table class="table">
    ...
  </table>
</div>
```

Copy

#	Heading	Heading	Heading	Heading	Heading	Heading	Heading
1	Cell	Cell	Cell	Cell	Cell	Cell	Cell
2	Cell	Cell	Cell	Cell	Cell	Cell	Cell
3	Cell	Cell	Cell	Cell	Cell	Cell	Cell

< >

```
<div class="table-responsive-xl">
  <table class="table">
    ...
  </table>
</div>
```

Copy