

## [Getting started](#)

## [Layout](#)

## [Content](#)

## [Components](#)

### [Alerts](#)

### [Badge](#)

### [Breadcrumb](#)

### [Buttons](#)

### [Button group](#)

### [Card](#)

### [Carousel](#)

### [Collapse](#)

### [Dropdowns](#)

### [Forms](#)

### [Input group](#)

### [Jumbotron](#)

### [List group](#)

### [Media object](#)

### [Modal](#)

### [Navs](#)

### [Navbar](#)

### [Pagination](#)

## [Popovers](#)

### [Progress](#)

### [Scrollspy](#)

### [Spinners](#)

### [Toasts](#)

### [Tooltips](#)

## [Utilities](#)


## [Extend](#)

## [Migration](#)

## [About](#)

# Popovers

Documentation and examples for adding Bootstrap popovers, like those found in iOS, to any element on your site.



Limited time offer: Get 10 free Adobe Stock images.

ads via Carbon

## Overview

Things to know when using the popover plugin:

- Popovers rely on the 3rd party library [Popper.js](#) for positioning. You must include [popper.min.js](#) before bootstrap.js or use [bootstrap.bundle.min.js](#) / [bootstrap.bundle.js](#) which contains Popper.js in order for popovers to work!
- Popovers require the [tooltip plugin](#) as a dependency.
- If you're building our JavaScript from source, it [requires util.js](#).
- Popovers are opt-in for performance reasons, so **you must initialize them yourself**.
- Zero-length `title` and `content` values will never show a popover.
- Specify `container: 'body'` to avoid rendering problems in more complex components (like our input groups, button groups, etc).
- Triggering popovers on hidden elements will not work.
- Popovers for `.disabled` or `disabled` elements must be triggered on a wrapper element.
- When triggered from anchors that wrap across multiple lines, popovers will be centered between the anchors' overall width. Use `.text-nowrap` on your `<a>`s to avoid this behavior.
- Popovers must be hidden before their corresponding elements have been removed from the DOM.
- Popovers can be triggered thanks to an element inside a shadow DOM.

The animation effect of this component is dependent on the `prefers-reduced-motion` media query. See the [reduced motion section of our accessibility documentation](#).

Keep reading to see how popovers work with some examples.

## Example: Enable popovers everywhere

One way to initialize all popovers on a page would be to select them by their `data-toggle` attribute:

```
$(function () {  
  $('[data-toggle="popover"]').popover()  
})
```

Copy

## Example: Using the `container` option

When you have some styles on a parent element that interfere with a popover, you'll want to specify a custom `container` so that the popover's HTML appears within that element instead.

```
$(function () {  
  $('.example-popover').popover({  
    container: 'body'  
  })  
})
```

Copy

## Example

Click to toggle popover

```
<button type="button" class="btn btn-lg btn-danger" data-toggle="popover"  
title="Popover title" data-content="And here's some amazing content. It's very  
engaging. Right?">Click to toggle popover</button>
```

Copy

## Four directions

Four options are available: top, right, bottom, and left aligned.

Popover on top

Popover on right

Popover on bottom

Popover on left

```
<button type="button" class="btn btn-secondary" data-container="body" data-  
toggle="popover" data-placement="top" data-content="Vivamus sagittis lacus vel  
augue laoreet rutrum faucibus.">
```

```
  Popover on top  
</button>
```

```
<button type="button" class="btn btn-secondary" data-container="body" data-  
toggle="popover" data-placement="right" data-content="Vivamus sagittis lacus vel  
augue laoreet rutrum faucibus.">
```

```
  Popover on right  
</button>
```

```
<button type="button" class="btn btn-secondary" data-container="body" data-  
toggle="popover" data-placement="bottom" data-content="Vivamus  
sagittis lacus vel augue laoreet rutrum faucibus.">
```

```
  Popover on bottom  
</button>
```

```
<button type="button" class="btn btn-secondary" data-container="body" data-  
toggle="popover" data-placement="left" data-content="Vivamus sagittis lacus vel  
augue laoreet rutrum faucibus.">
```

```
  Popover on left  
</button>
```

Copy

## Dismiss on next click

Use the `focus` trigger to dismiss popovers on the user's next click of a different element than the toggle element.

## Specific markup required for dismiss-on-next-click

For proper cross-browser and cross-platform behavior, you must use the `<a>` tag, *not* the `<button>` tag, and you also must include a `tabindex` attribute.

Dismissible popover

```
<a tabindex="0" class="btn btn-lg btn-danger" role="button" data-toggle="popover" data-trigger="focus" title="Dismissible popover" data-content="And here's some amazing content. It's very engaging. Right?">Dismissible popover</a>
```

Copy

```
$('.popover-dismiss').popover({  
  trigger: 'focus'  
})
```

Copy

## Disabled elements

Elements with the `disabled` attribute aren't interactive, meaning users cannot hover or click them to trigger a popover (or tooltip). As a workaround, you'll want to trigger the popover from a wrapper `<div>` or `<span>` and override the `pointer-events` on the disabled element.

For disabled popover triggers, you may also prefer `data-trigger="hover"` so that the popover appears as immediate visual feedback to your users as they may not expect to *click* on a disabled element.

Disabled button

```
<span class="d-inline-block" data-toggle="popover" data-content="Disabled popover">  
  <button class="btn btn-primary" style="pointer-events: none;" type="button" disabled>Disabled button</button>  
</span>
```

Copy

## Usage

Enable popovers via JavaScript:

```
$('#example').popover(options)
```

Copy

## Making popovers work for keyboard and assistive technology users

To allow keyboard users to activate your popovers, you should only add them to HTML elements that are traditionally keyboard-focusable and interactive (such as links or form controls). Although arbitrary HTML elements (such as `<span>`s) can be made focusable by adding the `tabindex="0"` attribute, this will add potentially annoying and confusing tab stops on non-interactive elements for keyboard users, and most assistive technologies

currently do not announce the popover’s content in this situation. Additionally, do not rely solely on `hover` as the trigger for your popovers, as this will make them impossible to trigger for keyboard users.

While you can insert rich, structured HTML in popovers with the `html` option, we strongly recommend that you avoid adding an excessive amount of content. The way popovers currently work is that, once displayed, their content is tied to the trigger element with the `aria-describedby` attribute. As a result, the entirety of the popover’s content will be announced to assistive technology users as one long, uninterrupted stream.

Additionally, while it is possible to also include interactive controls (such as form elements or links) in your popover (by adding these elements to the `whiteList` or allowed attributes and tags), be aware that currently the popover does not manage keyboard focus order. When a keyboard user opens a popover, focus remains on the triggering element, and as the popover usually does not immediately follow the trigger in the document’s structure, there is no guarantee that moving forward/pressing `TAB` will move a keyboard user into the popover itself. In short, simply adding interactive controls to a popover is likely to make these controls unreachable/unusable for keyboard users and users of assistive technologies, or at the very least make for an illogical overall focus order. In these cases, consider using a modal dialog instead.

## Options

Options can be passed via data attributes or JavaScript. For data attributes, append the option name to `data-`, as in `data-animation=""`.

Note that for security reasons the `sanitize`, `sanitizeFn` and `whiteList` options cannot be supplied using data attributes.

Name	Type	Default	Description
animation	boolean	true	Apply a CSS fade transition to the popover
container	string   element   false	false	Appends the popover to a specific element. Example: <code>container: 'body'</code> . This option is particularly useful in that it allows you to position the popover in the flow of the document near the triggering element - which will prevent the popover from floating away from the triggering element during a window resize.

Name	Type	Default	Description
content	string   element   function	"	<p>Default content value if <b>data-content</b> attribute isn't present.</p> <p>If a function is given, it will be called with its <b>this</b> reference set to the element that the popover is attached to.</p>
delay	number   object	0	<p>Delay showing and hiding the popover (ms) - does not apply to manual trigger type</p> <p>If a number is supplied, delay is applied to both hide/show</p> <p>Object structure is: <b>delay</b>: {  <b>"show"</b>: 500,  <b>"hide"</b>: 100 }</p>
html	boolean	false	<p>Insert HTML into the popover. If false, jQuery's <b>text</b> method will be used to insert content into the DOM. Use text if you're worried about XSS attacks.</p>

Name	Type	Default	Description
placement	string   function	'right'	<p>How to position the popover - auto   top   bottom   left   right.</p> <p>When <b>auto</b> is specified, it will dynamically reorient the popover.</p> <p>When a function is used to determine the placement, it is called with the popover DOM node as its first argument and the triggering element DOM node as its second. The <b>this</b> context is set to the popover instance.</p>
selector	string   false	false	<p>If a selector is provided, popover objects will be delegated to the specified targets. In practice, this is used to enable dynamic HTML content to have popovers added. See <a href="#">this</a> and <a href="#">an informative example</a>.</p>

Name	Type	Default	Description
template	string	'<div class="popover" role="tooltip"><div class="arrow"></div><h3 class="popover-header"></h3><div class="popover-body"></div></div>'	<p>Base HTML to use when creating the popover.</p> <p>The popover's <b>title</b> will be injected into the <b>.popover-header</b>.</p> <p>The popover's <b>content</b> will be injected into the <b>.popover-body</b>.</p> <p><b>.arrow</b> will become the popover's arrow.</p> <p>The outermost wrapper element should have the <b>.popover</b> class.</p>
title	string   element   function	''	<p>Default title value if <b>title</b> attribute isn't present.</p> <p>If a function is given, it will be called with its <b>this</b> reference set to the element that the popover is attached to.</p>
trigger	string	'click'	<p>How popover is triggered - click   hover   focus   manual. You may pass multiple triggers; separate them with a space. <b>manual</b> cannot be combined with any other trigger.</p>

Name	Type	Default	Description
offset	number   string	0	Offset of the popover relative to its target. For more information refer to Popper.js's <a href="#">offset docs</a> .
fallbackPlacement	string   array	'flip'	Allow to specify which position Popper will use on fallback. For more information refer to Popper.js's <a href="#">behavior docs</a>
boundary	string   element	'scrollParent'	Overflow constraint boundary of the popover. Accepts the values of <code>'viewport'</code> , <code>'window'</code> , <code>'scrollParent'</code> , or an HTMLElement reference (JavaScript only). For more information refer to Popper.js's <a href="#">preventOverflow docs</a> .
sanitize	boolean	true	Enable or disable the sanitization. If activated <code>'template'</code> , <code>'content'</code> and <code>'title'</code> options will be sanitized.
whitelist	object	<a href="#">Default value</a>	Object which contains allowed attributes and tags



Name	Type	Default	Description
sanitizeFn	null   function	null	Here you can supply your own sanitize function. This can be useful if you prefer to use a dedicated library to perform sanitization.
popperConfig	null   object	null	To change Bootstrap's default Popper.js config, see <a href="#">Popper.js's configuration</a>

### Data attributes for individual popovers

Options for individual popovers can alternatively be specified through the use of data attributes, as explained above.

## Methods

### Asynchronous methods and transitions

All API methods are **asynchronous** and start a **transition**. They return to the caller as soon as the transition is started but **before it ends**. In addition, a method call on a **transitioning component will be ignored**.

[See our JavaScript documentation for more information.](#)

### `$().popover(options)`

Initializes popovers for an element collection.

### `.popover('show')`

Reveals an element's popover. **Returns to the caller before the popover has actually been shown** (i.e. before the `shown.bs.popover` event occurs). This is considered a "manual" triggering of the popover. Popovers whose title and content are both zero-length are never displayed.

```
$('#element').popover('show')
```

Copy

### `.popover('hide')`

Hides an element's popover. **Returns to the caller before the popover has actually been hidden** (i.e. before the `hidden.bs.popover` event occurs). This is considered a "manual" triggering of the popover.

```
$('#element').popover('hide')
```

Copy

### `.popover('toggle')`

Toggles an element's popover. **Returns to the caller before the popover has actually been shown or hidden** (i.e. before the `shown.bs.popover` or `hidden.bs.popover` event occurs). This is considered a "manual" triggering of the popover.

```
$('#element').popover('toggle')
```

Copy

### `.popover('dispose')`

Hides and destroys an element's popover. Popovers that use delegation (which are created using [the selector option](#)) cannot be individually destroyed on descendant trigger elements.

```
$('#element').popover('dispose')
```

Copy

### `.popover('enable')`

Gives an element's popover the ability to be shown. **Popovers are enabled by default.**

```
$('#element').popover('enable')
```

Copy

### `.popover('disable')`

Removes the ability for an element's popover to be shown. The popover will only be able to be shown if it is re-enabled.

```
$('#element').popover('disable')
```

Copy

### `.popover('toggleEnabled')`

Toggles the ability for an element's popover to be shown or hidden.

```
$('#element').popover('toggleEnabled')
```

Copy

### `.popover('update')`

Updates the position of an element's popover.

```
$('#element').popover('update')
```

Copy

## Events

Event Type	Description
show.bs.popover	This event fires immediately when the <code>show</code> instance method is called.
shown.bs.popover	This event is fired when the popover has been made visible to the user (will wait for CSS transitions to complete).

Event Type	Description
hide.bs.popover	This event is fired immediately when the <code>hide</code> instance method has been called.
hidden.bs.popover	This event is fired when the popover has finished being hidden from the user (will wait for CSS transitions to complete).
inserted.bs.popover	This event is fired after the <code>show.bs.popover</code> event when the popover template has been added to the DOM.

[Copy](#)

```
$('#myPopover').on('hidden.bs.popover', function () {  
  // do something...  
})
```