

IT APP. SEC. LAB FILE

To- Dr. Gopal Rawat

Name- Dhairya Jain Sap ID- 500105432 Batch- CSF-B1

Aim- XSS attack

To do the following:

- Perform XSS attack on DVWA.
- Perform the attack under low, medium, and high security scenario.

Metasploitable ipaddress-

```
metasploitable 2 [Running] - Oracle VM VirtualBox
                                                                                               X
To access official Ubuntu documentation, please visit:
http://help.ubuntu.com/
No mail.
inet6 addr: fe80::a00:27ff:fe78:f6e4/64 Scope:Link
             UP BROADCAST RUNNING MULTICAST MTU:1500 Metric:1
RX packets:55 errors:0 dropped:0 overruns:0 frame:0
             TX packets:66 errors:0 dropped:0 overruns:0 rame:0
TX packets:66 errors:0 dropped:0 overruns:0 carrier:0
collisions:0 txqueuelen:1000
RX bytes:12575 (12.2 KB) TX bytes:7030 (6.8 KB)
Base address:0xd020 Memory:f0200000-f0220000
             Link encap:Local Loopback
             inet addr:127.0.0.1 Mask:255.0.0.0 inet6 addr: ::1/128 Scope:Host
             UP LOOPBACK RUNNING MTU:16436 Metric:1
             RX packets:92 errors:0 dropped:0 overruns:0 frame:0
TX packets:92 errors:0 dropped:0 overruns:0 carrier:0
             collisions:0 txqueuelen:0
RX bytes:19393 (18.9 KB) TX bytes:19393 (18.9 KB)
msfadmin@metasploitable:~$
```

1. Reflected XSS:


Low level-

Source code-

```
Peflected XSS Source

| Population | Popula
```


Normally trying a string in name section



Java script code for xss-



capturing cookies-



• Medium level-

Source code-

Normally trying a string in name section-

Vulnerability: Reflected Cross Site Scri What's your name? Submit Hello reflected

Java script code for xss-

In medium level we use capital CR and P in script(sCRiPt)to preform task because script function is sanitised-



capturing cookies-



• High level

Source code-

Normally trying a string in name section-



Java script code for xss-

Not found any way to exploit high security level because it is sanitizing all the html tags-




2. Stored XSS:


• Low level-

Source code-

Genuine string-




Java script code for xss-





Cookie hijacking-



Medium level-

Source code-

```
O 各 192.168.0.113/dvwa/vulnerabilities/view_source.php?id=xss_s&security=medium
if(isset($_POST['btnSign']))
  $message = trim($_POST['mtxMessage']);
          = trim($_POST['txtName']);
  // Sanitize message input
  $message = trim(strip_tags(addslashes($message)));
  $message = mysql_real_escape_string($message);
  $message = htmlspecialchars($message);
  // Sanitize name input
  $name = str_replace('<script>', '', $name);
  $name = mysql_real_escape_string($name);
  $query = "INSERT INTO guestbook (comment,name) VALUES ('$message','$name');";
  $result = mysql_query($query) or die('' . mysql_error() . '' );
}
?>
Compare
```

Since medium is sanitizing message input for all script tags, html special character we cant do cross site using message input so we have to try if for name input


But there are two problems in name input

- 1. Sanitized for script command so we have to use some other command
- 2. Input length is 10 only so we have to inspect and increase the length of name input

Original size and length-


Double click and edit the size and length to 100-

Now doing cross site scripting-





Capturing cookie-




• High level-

Source code-

```
O & 192.168.0.113/dvwa/vulnerabilities/view_source.php?id=xss_s&security=high
                                                                            ∃ ☆
                                                                                    \equiv
Stored XSS Source
<?php
if(isset($_POST['btnSign']))
   $message = trim($_POST['mtxMessage']);
          = trim($_POST['txtName']);
   $name
   // Sanitize message input
   $message = stripslashes($message);
   $message = mysql_real_escape_string($message);
   $message = htmlspecialchars($message);
   // Sanitize name input
   $name = stripslashes($name);
   $name = mysql_real_escape_string($name);
  $name = htmlspecialchars($name);
   $query = "INSERT INTO guestbook (comment,name) VALUES ('$message','$name');";
   $result = mysql_query($query) or die('' . mysql_error() . '' );
```

We cant preform any xss attack on high level because it is sanitizing both the message and name input for script tag as well as for html special character and mysql escape string

Trying for xss-




3. Dom based XSS-

preformed in mutillidae

Low level-

XSS Script for dom-







Medium level-

XSS script-




Capturing cookie-




ОК

High level-

XSS Script-











Trying xss on some other sites


https://xss-game.appspot.com/level1

level1 (reflected)






Trying to capture cookie-




Level2 (stored)











Level 3 (url)







Level 4 (timer)


3'**alert());//






Level 5 (dom)






XSS Challenges
Stage #1
Notes (for all stages): * NEVER DO ANY ATTACKS EXCEPT XSS. * DO NOT USE ANY AUTOMATED SCANNER (AppScan, WebInspect, WVS,) * Some stages may fit only IE.
What you have to do: Inject the following JavaScript command: alert(document.domain);
Hint:
Search: <script>alert("XSS")</script>
xss-quiz.int21h.jp says
xss
ОК







Next site- https://sudo.co.il/xss/


Level0-

```
<script>alert("XSS")</script Subscribe!</pre>
```

Thank you for subscription! Email added to mailing list!



Level1-



Capturing cookie-

```
"><script>alert(document.cc|"> Subscribe!
```

Thank you for subscription!

Email "><script>alert(document.cookie)</script> added to mailing list!

```
sudo.co.il says
_ga=GA1.3.846819183.1711030687;
_gid=GA1.3.1163119461.1711030687; _gat=1;
_ga_8S7MMPCHJR=GS1.3.1711041473.3.1.1711041678.0.0.0

OK
```