

Task 1: Accessing the Router Admin Panel



Task 2: Current Network Configurations

Network Setting Value	
IPv4 Address	192.168.29.245
Subnet Mask	255.255.255.0
Default Gateway	192.168.29.1

Task 3 — Static IP Test + Internet Access + DHCP Revert

Internet Protocol Version 4 (TCP/IPv4) Properties

General

You can get IP settings assigned automatically if your network supports this capability. Otherwise, you need to ask your network administrator for the appropriate IP settings.

☐ Obtain an IP address automatically

☒ Use the following IP address:

IP address:	192 . 168 . 29 . 50
Subnet mask:	255 . 255 . 255 . 0
Default gateway:	192 . 168 . 29 . 1

☐ Obtain DNS server address automatically

☒ Use the following DNS server addresses:

Preferred DNS server:	. . .
Alternate DNS server:	. . .

☐ Validate settings upon exit

Advanced...

OK Cancel

Static IP Configuration:

IP Address: 192.168.29.50

Subnet Mask: 255.255.255.0

Default Gateway: 192.168.29.1

Task 4: DHCP Range

**DHCP Range: 192.168.29.0 to
192.168.29.255**

DHCP automatically assigns IP addresses to devices on the network.

If two devices are assigned the same IP address, an IP address conflict can occur.

This can cause connectivity problems for one or both devices.