

RAM Reseating Procedure

Step 1- shutdown the pc

i switched off the computer and disconnected the power cable before opening the cabinet

Step 2 – Open the Cabinet

I removed the side panel of the desktop cabinet and located the RAM slots on the motherboard.

Step 3 – Remove the RAM

I released the clips on both sides of the RAM slot and carefully removed the RAM module.

Step 4 – Inspect the RAM

I checked the RAM module and slot for dust, damage or any visible problem.

Step 5 – Re-insert the RAM

I aligned the notch on the RAM module with the slot and pressed it down evenly until the clips locked into place.

Step 6 – Test the PC

I reconnected the power cable and started the PC to check whether it booted normally.

Observation:

No physical damage was observed. Reseating the RAM can

help resolve problems caused by a loose or improperly seated memory module.

GPU Troubleshooting Checklist

1. Identify the Symptom

I would check whether the monitor shows no display, flickering, artifacts, or other display problems.

2. Check the Display Connection

I would check that the HDMI/DisplayPort cable is properly connected to the GPU and monitor.

3. Check the GPU Power Connection

I would make sure the required PCIe power cable is properly connected to the graphics card.

4. Check the GPU Installation

I would switch off and unplug the PC, then check that the GPU is properly seated in the PCIe slot.

5. Check the Driver

I would check Device Manager for any GPU

warning or error and verify that the graphics driver is installed correctly.

6. Test the GPU

I would restart the PC and test the display with a suitable application or game to confirm that the GPU is working normally.

Conclusion:

This checklist helps identify whether the problem is related to the display connection, GPU power, physical installation, or driver.

Storage Drive Troubleshooting

Step 1 – Disconnect the Drive

I switched off the PC and disconnected the power before disconnecting the SATA or NVMe storage drive.

Step 2 – Check the Storage Detection

Before reconnecting the drive, I checked the BIOS to see whether the storage device was detected.

Observation Before Reconnecting:

The storage drive was not detected in the BIOS, so the system could not find the drive.

Step 3 – Reconnect the Drive

I securely reconnected the SATA cable and power cable for a SATA drive. For an NVMe drive, I checked that the module was properly seated in its M.2 slot.

Step 4 – Check BIOS Again

After reconnecting the drive, I entered the BIOS and checked the storage information again.

Observation After Reconnecting:

The storage drive was detected correctly after the connection was restored.

Step 5 – Check the System

I restarted the PC and checked whether the operating system could access the storage drive normally.

Conclusion:

A loose or disconnected storage connection can prevent the BIOS and operating system from detecting the drive. Reconnecting the drive properly can resolve this type of problem.

Troubleshooting a PC That Randomly Restarts

I would check the **RAM first** because faulty or improperly seated RAM can cause system instability, crashes, and unexpected restarts.

Step 1 – Power Off the PC

I would shut down the PC and disconnect the power cable before checking the RAM.

Step 2 – Check the RAM Installation

I would open the cabinet and make sure the RAM modules are properly seated in their slots.

Step 3 – Reseat the RAM

I would remove and carefully re-insert the RAM module to make sure it has a proper connection.

Step 4 – Test the RAM

If there are multiple RAM modules, I would test them one at a time to help identify a faulty module.

Step 5 – Check the PC

I would start the computer and observe whether the random restarting problem continues.

Conclusion:

If the PC becomes stable after checking and reseating the RAM, the problem may have been caused by a loose or faulty RAM module. If the problem continues, I would then investigate the GPU and storage components.