

Review and Practice

Task 1: Create a Home WiFi Network

I created a new project in Cisco Packet Tracer and named it **HomeWiFiNetwork.pkt**. I used three PCs and one wireless router for the network.

Devices Used:

- 1 Wireless Router
- 3 PCs
- Network cables

Steps:

1. Open Cisco Packet Tracer.
2. Create a new project.
3. Add one wireless router to the workspace.
4. Add three PCs.
5. Connect the PCs to the wireless router using appropriate connections.
6. Arrange the devices properly to make a small home network.
7. Save the project as **HomeWiFiNetwork.pkt**

Configure Static IP Addresses

I assigned static IP addresses to all three PCs. All PCs are on the same subnet so they can communicate with each other.

IP Configuration

Device	Ip address	Subnet mask	Default gateway
Pc1	192.168.10.2	255.255.255.0	192.168.10.1
Pc2	192.168.29.3	255.255.255.0	192.168.10.1
Pc3	192.168.29.4	255.255.255.0	192.168.10.1
Wireless router	192.168.29.1	255.255.255.0	-

Steps:

1. Click on PC1.
2. Open **Desktop** → **IP Configuration**.
3. Select **Static**.
4. Enter the IP address, subnet mask and default gateway.
5. Repeat the same steps for PC2 and PC3.
6. Make sure all three PCs are using the same subnet

Test Network Connectivity

After configuring the IP addresses, I tested the connectivity between the PCs and the router.

Steps:

1. Open PC1 and go to **Desktop** → **Command Prompt**.

2. Type the following command:

```
ping 192.168.10.3
```

3. Test PC1 with PC3:

```
ping 192.168.10.4
```

4. Test PC1 with the router:

```
ping 192.168.10.1
```

5. Repeat the test from the other PCs.

If the configuration is correct, the ping should receive replies from the other devices.

Documentation of the Network

I documented the complete process of creating and configuring the small network.

Steps Completed:

1. Created a new Cisco Packet Tracer project.
2. Added one wireless router and three PCs.
3. Connected the devices properly.
4. Configured static IP addresses.
5. Set the subnet mask as **255.255.255.0**.
6. Set the default gateway as **192.168.10.1**.
7. Tested connectivity using the ping command.
8. Verified that the PCs can communicate with each other and the router.
9. Took screenshots of the topology and IP configuration.
10. Added all screenshots and steps to this assignment.

Conclusion

This practical helped me understand how to create a small network in Cisco Packet Tracer. I learned how to connect devices, assign static IP addresses, configure the default gateway and test connectivity using the ping command.