```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <!-- Responsive Web Design: viewport tag makes the page fit phone screens -->
  <meta name="viewport" content="width=device-width, initial-scale=1">
  <title>ColdChain Monitor</title>

  <!-- Bootstrap 5 via CDN (Module 2: Introduction to Bootstrap 5) -->
  <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/css/bootstrap.min.css" rel="stylesheet">
  <!-- Our own CSS -->
  <link rel="stylesheet" href="style.css">
</head>
<body>

  <!-- Semantic tag: header -->
  <header class="bg-navy text-white">
    <div class="container d-flex flex-wrap justify-content-between align-items-center py-3 gap-2">
      <h1 class="h3 mb-0">ColdChain Monitor</h1>
      <nav>
        <button id="navDashboard" class="btn btn-light btn-sm">Dashboard</button>
        <button id="navAlerts" class="btn btn-outline-light btn-sm">
          Alerts <span id="alertCount" class="badge bg-danger">0</span>
        </button>
      </nav>
    </div>
  </header>

  <!-- Semantic tag: main -->
  <main class="container my-4">

    <!-- Message area (shows success / error text) -->
    <div id="message" class="d-none" role="status"></div>

    <!-- ========== SCREEN 1: DASHBOARD ========== -->
    <section id="dashboardSection">
      <h2 class="h4 mb-3">Shipment Monitoring</h2>

      <!-- Summary cards (Bootstrap grid: row + col) -->
      <div class="row g-3 mb-4">
        <div class="col-12 col-md-4">
          <div class="card summary-card">
            <div class="card-body">
              <p class="mb-0 text-muted">Total shipments</p>
              <p id="totalShipments" class="fs-2 fw-bold mb-0">0</p>
            </div>
          </div>
        </div>
        <div class="col-12 col-md-4">
          <div class="card summary-card warn">
            <div class="card-body">
              <p class="mb-0 text-muted">Shipments with violations</p>
              <p id="violationCount" class="fs-2 fw-bold mb-0">0</p>
            </div>
          </div>
        </div>
        <div class="col-12 col-md-4">
          <div class="card summary-card danger">
            <div class="card-body">
              <p class="mb-0 text-muted">Unresolved alerts</p>
              <p id="unresolvedCount" class="fs-2 fw-bold mb-0">0</p>
            </div>
          </div>
        </div>
      </div>

      <!-- Search and filter -->
      <div class="row g-2 mb-3">
        <div class="col-12 col-md-8">
          <label for="searchInput" class="visually-hidden">Search shipments</label>
```

```
          <input id="searchInput" type="text" class="form-control" placeholder="Search by shipment ID or
            cargo type">
        </div>
        <div class="col-12 col-md-4">
          <label for="statusFilter" class="visually-hidden">Filter by status</label>
          <select id="statusFilter" class="form-select">
            <option value="all">All conditions</option>
            <option value="normal">Normal</option>
            <option value="warning">Warning</option>
            <option value="critical">Critical</option>
          </select>
        </div>
      </div>

      <!-- Shipment table (table-responsive lets it scroll on phones) -->
      <div class="table-responsive">
        <table class="table table-bordered align-middle bg-white">
          <thead class="table-dark">
            <tr>
              <th>ID</th>
              <th>Cargo</th>
              <th>Route</th>
              <th>Safe range</th>
              <th>Latest</th>
              <th>Status</th>
              <th>Details</th>
            </tr>
          </thead>
          <tbody id="shipmentBody"></tbody>
        </table>
      </div>
    </section>

    <!-- ========== SCREEN 2: SHIPMENT DETAILS ========== -->
    <section id="detailsSection" class="d-none">
      <button id="backBtn" class="btn btn-outline-secondary btn-sm mb-3">Back to dashboard</button>

      <div class="d-flex flex-wrap align-items-center gap-2 mb-2">
        <h2 id="detailTitle" class="h4 mb-0"></h2>
        <span id="detailBadge"></span>
      </div>
      <p id="detailInfo" class="text-muted"></p>

      <!-- Form: add a simulated reading (Forms & Validation) -->
      <form id="readingForm" class="row g-2 mb-4" novalidate>
        <div class="col-12 col-md-4">
          <label for="tempInput" class="form-label">New temperature reading (°C)</label>
          <input id="tempInput" type="text" class="form-control" placeholder="Example: 6.5">
          <div id="tempError" class="invalid-feedback"></div>
        </div>
        <div class="col-12 col-md-4 d-flex align-items-end">
          <button type="submit" class="btn btn-primary">Add reading</button>
        </div>
      </form>

      <h3 class="h5">Temperature history</h3>
      <div class="table-responsive">
        <table class="table table-bordered bg-white">
          <thead class="table-dark">
            <tr><th>Time</th><th>Temperature</th><th>Status</th></tr>
          </thead>
          <tbody id="historyBody"></tbody>
        </table>
      </div>
    </section>

    <!-- ========== SCREEN 3: ALERTS ========== -->
    <section id="alertsSection" class="d-none">
      <h2 class="h4 mb-3">Temperature Alerts</h2>

```

```
      <div class="mb-3 col-12 col-md-4">
        <label for="alertFilter" class="form-label">Show alerts</label>
        <select id="alertFilter" class="form-select">
          <option value="all">All</option>
          <option value="Active">Active</option>
          <option value="Acknowledged">Acknowledged</option>
          <option value="Resolved">Resolved</option>
        </select>
      </div>

      <div id="alertList" class="list-group"></div>
    </section>

  </main>

  <!-- Semantic tag: footer -->
  <footer class="container pb-4 text-muted small">
    Readings are simulated sample data.
    <button id="resetBtn" class="btn btn-link btn-sm p-0">Reset sample data</button>
  </footer>

  <script src="script.js"></script>
</body>
</html>
```