

Design and Implementation of a Secure Smart Locker System with QR-Based Authentication and Real-Time Analytics

Dhanisha Sethupathy
Department of Computer Science and Engineering
Vellore Institute of Technology
Chennai, India
dhanisha.sethupathy2023@vitstudent.ac.in

Abstract—E-commerce growth is accelerating the last mile delivery process considerably. This is primarily understood to mean high rates of delivery errors and security risks when using a standard courier company to deliver at the point of sale. The individual does not need to wait for long as the courier the parcels down at the right place. The smart locker holds the parcel until the person who owns it opens the smart locker using thumb impression or OTP. Delivery agents and end customers each have individual portals for streamlining workflow according to their roles. The Entrance Security System features a dual QR code authentication mechanism. The system generates a token for each delivery ID based on UUID4 logic. The expiry can be set for such tokens. The cheque code isn't a stationary pin and cannot also be faked. The Physical Lockers architecture consists of a physical locker system that relies on an SQLite database to record physical locker state and allow state transitions. Supplementing a robust validation layer for mobile formats in India showing up on an Audit Trail on every transaction that takes place ensures the continued functioning of the data and total visibility of every operation that takes place. The integrated Real-Time Analytics Dashboard results confirm that this data-driven mechanism reduces parcel “dwell time” and improves locker utilization (which has excellent clarity) that is scalable and cost-effective for the operation of parcel deliveries.

Index Terms—Smart Locker, IoT, QR Code Authentication, Last-Mile Delivery, Real-time Analytics, E-commerce Logistics.

I. INTRODUCTION

Without a doubt, e-commerce has seen a dramatic change globally in the past decade, creating a post-pandemic digital-first scenario. Robotics and automatic sorting centers have automated the first-mile and middle-mile logistics of digital stores. However, the last mile is still a challenge. Last-mile cargo delivery refers to the last leg of the journey of a parcel. Nearly 53% of total shipping costs are accounted by this section and it also is one of the main contributors to vehicular pollution in the cities.

In many developing nations like India, the situation is worsened by complicated addressing systems, high population density and widespread issues of failed delivery attempts or FDA. If a delivery fails due to the receiver's unavailability, the consortium must usually cover reverse logistics costs. This includes ultimately returning the product to the seller in case deliveries are not completed. Returning the shipment from the

destination back to the source. Apart from profit margins and customer experience, there is also the problem of having to attempt delivery multiple times.

A. Motivation

This research is motivated by the ability to use the Internet of Things (IoT) in a mobile first approach and authentication. Conventional staffed parcel shops or basic electronic locker solutions present a significant challenge to operations such as:

- 1) **Credential Vulnerability:** Static PIN system are identifiable to shoulder surfing attack. It might also turn into social engineering. Locker reset is manual so if your pin gets compromised locker gets compromised.
- 2) **Hardware Rigidity:** Standard lockers utilize a costly hardware console that is proprietary. The manufacturers will eye on “decoupled” systems where the users smartphone is the interface and this is the system which lowers the BOM (Bill of Material) cost.
- 3) **Data Silos:** Modern systems operate in partitions and lack analytical capabilities. Logistics managers are unable to predict locker saturation or optimize courier routes based on availability.
- 4) **Standardization Gaps:** A sizeable number of our users are based in India and we do not do the phone number validation (it should be 10 digits and start with a prefix between 6 and 9) which is causing notifications to fail, parcels to get stuck, and lockers not seeing a good turnover.

B. Problem Statement

Parcel delivery process does not have a commonly available secure and automated framework which can perform the handover phase. That is, it will asynchronously handover package from agent to customer. All this can happen without physical supervision. Problem in this paper refers to the design of a software defined secure locker architecture using cryptographically unique QR codes for managing the states of the locker, authenticating user persona in real time, as well as providing audit ready trace for every transaction.

C. Technical Contributions

This paper details the development of a comprehensive Secure Locker System. The primary technical contributions include:

- **Role-Specific Tri-Portal Architecture:** The architecture design of a decoupled system that comprises an E-commerce Portal (creation), an Agent Portal (deposit), and a Customer Portal (collection), strictly isolating the three with each other.
- **Asymmetric QR Authentication:** A system of dual tokens with UUID4 unique string for delivery id mapping implementation. This means that the agent depositing the parcel cannot use their code to retrieve it. The locker will not be available to customer until agent checks the deposit.
- **Dynamic State Machine Logic:** Users will be unable to book a locker at the same time, preventing race conditions and more. Available, Depositing, Occupied and Pickup, Available states will all be transferred in the database.
- **Advanced Real-Time Analytics:** A stand-alone engine that's deployed by logistics service providers to calculate KPIs like Average Dwell Time, Completion Velocity, Peak Hour Utilisation for optimal resource.
- **Automated Expiration & Cleanup:** Our QR codes will be expired after 168 hours (7 days) which is a logical expiration system in place. Parcels that are not collected will automatically alert users to clear locker spaces.

D. Paper Organization

A systematic arrangement beginning with a theoretical background and ending in practical implementation provides the logical flow. Review of studies on IoT in logistics and on QR security in critical section II. The Database design and the authentication algorithm are presented in Section III of proposed methodology. Section IV provides the implementation details. This section spotlights the software stack and the workflows contributing to portals. Section V will conduct performance evaluation of proposed system on various test cases and real life situations. Section VI will conclude the paper IoT level hardware connectivity future works and results SMS-gateway engineering.

II. RELATED WORK

The launch of the automated parcel locker (APL) system encompasses a range of fields such as IoT, cryptography and operating methods. The review of literature in this chapter addresses this transition from mechanization to smart or data-driven systems.

A. Evolution of Authentication Mechanisms

Many years ago, it was impossible to access storage units without keys or a PIN pad. Nonetheless, Alghfeli et al. [1] reported that methods based on the conventional principle are at risk of social engineering and hardware tampering. Their work on public transport management systems relates well

to logistics. Results show dynamic QR code authentication provides a 40% improvement in access time over manual entry.

The incorporation of QR codes for e-commerce logistics was explored by Lakshmi et al. [4]. Researchers say that although static QR codes can simply be clicked and duplicated through a camera, these “handshake-based” tokens, which make the QR code invalid after use, are stronger against replay attacks. The two-token system proposed in our work (of Agent and Customer) provides the digital proof of the custody at every transition.

B. IoT Architectures for Smart Storage

The smart locker architecture is shifting from localised controller architecture to cloud networking architecture. The common implementation of a communication protocol, proof of authentication in an IoT-based locker system using WSN for university campus by Wu et al. [3]. The study implemented a Central Command Center that can control multiple locker nodes and we've enhanced that into a tri-portal web architecture.

Ferreira et al. [6] further evaluate the communication latency between IoT edge devices and cloud backends. The primary challenge in distributed architected locker networks is to maintain state synchronicity. To achieve this, we use atomic SQL transactions such that the physical state of the locker and its digital twin in the database always remain consistent even during peak concurrency.

C. Last-Mile Logistics and Operational Efficiency

The last-mile delivery has been affected by smart lockers which cost cushion impact social researchers. In a systematic review on the urban delivery failure rates Michalakopoulou et al. [7] found that the automated lockers could reduce the cost of “failed delivery” by 30%. However, they pointed out that locker owners do not have the above real-time analytics.

To bridge the gap, we have integrated with the live analytics engine. In contrast to the “SmartBox” development suggested by Nonthaputha et al. [8] which concentrates on physical-handling system for hardware, our proposal is oriented towards data. The logistics can optimize the best courier routing and locker placements based on data from our system by looking at metrics like ‘Locker Turnover Rate’ and ‘Peak Usage Hours’.

D. Security and Data Validation Frameworks

Security features in smart lockers are not only physical, but also ensure integrity. Prasad et al. [5] observed that input not validated forms a common entry point for SQL injection in the case of log software. Their research advocated for strict regex-based filtering of user metadata.

In terms of their regional implementations, Rosmi et al. [2] looked at the use of automated notification systems such as via messaging apps to reduce parcel “dwell time.” They have concluded that the efficacy of these systems depends fully on the accuracy of the contact data. Our project caters the needs of this niche by implementing a strict 10-digit Indian mobile number validation, making sure that the important collection QR is sent to a valid and correct collection QR.

E. Comparison with Extant Systems

Table II summarizes the differences between our proposed Secure Locker System and the systems described in recent literature.

TABLE I
COMPARATIVE ANALYSIS OF SMART LOCKER SYSTEMS

Feature	Wu [3]	Prasad [5]	Rosmi [2]	Proposed
QR Auth	Yes	Yes	No	Yes (Dual)
Real-time Analytics	No	No	Yes	Yes
Role-based Portals	Partial	No	No	Yes (Tri)
Input Validation	No	Yes	No	Yes
State Management	Basic	Basic	Advanced	FSM Logic

The thorough review of the related work shows that while certain features of smart lockers such as QR code or IoT exist in the literature, there is an absence of a comprehensive, secure and analytical driven framework to cover the entire delivery lifecycle.

F. Identified Research Gaps

This paper fills four important research gaps stemming from a review of the existing literature on APL, despite the increased interest in APL research:

- 1) **Fragmentation of User Interfaces:** Presently available research such as those by Wu et al. [3] and Nonthaputha et al. [8] emphasize on only one ‘User-Locker’ interaction. A tri-portal framework that allows the *Ecommerce Provider* (Data Entry), the *Delivery Agent* (Deposit), and the *Customer* (Pickup) to simultaneously fulfil their respective security and functional demands does not seem to exist.
- 2) **Asymmetric Authentication Scenarios:** Although authentication through QR codes is often suggested [4][5], it seems like the method used by most systems is symmetric, for example, the same token is given to both agent and customer. This results in a security gap, allowing a delivery agent to potentially re-enter a locker after a parcel has been dropped off but before it is picked up. Our study shows that *Asymmetric QR Pairs* need to be implemented to enforce strict chain of custody.
- 3) **Neglect of Regional Data Integrity:** Most of the IoT locker prototypes do not take into account the GIGO principle for user metadata. In India, logistics context, the leading cause of failure of notification is incorrect phone number formatting. The locker allocation logic of existing literature does not incorporate any local validation layers (e.g., 10-digit Indian prefixing).
- 4) **Absence of Integrated Operational Analytics:** Michalakopoulou et al. [7] present a theoretical efficiency of lockers while there are few implementations that allow direct telemetry provision (Peak Hour Analysis, Completion Velocity and Dwell Time) to the system administrator. Most systems function as ‘black boxes’: they hold parcels, but nothing else of value.

III. PROPOSED METHODOLOGY AND ARCHITECTURE

The suggested scheme has been designed as a multi-tier, decoupled architecture to conduct asynchronous logistics events. The methodology describes a virtual state machine that synchronizes a logical machine to the locker hardware through middleware.

A. System Architecture Overview

Architecture is splitted into 3 main layers which are *Application Layer* (User Interfaces), *Service Layer* (Logic and Authentication) and *Data Layer* (Persistence and State Maintenance)

- 1) **Application Layer:** There are three distinct portals for different roles. The foundation of the administrative office from which deliveries are initiated is the *Ecommerce Portal*. The *Agent Portal* allows couriers to scan deposit codes from a mobile-friendly interface. The **Customer Portal** enables final parcel retrieval through dedicated collection tokens.
- 2) **Service Layer (The Control Engine):** The core business logic is managed in this layer. UUID4 generation, Indian mobile number validation regex and locker allocation algorithm which picks the first available node from the pool.
- 3) **Data Layer:** SQLite a relational database helps in persistence delivery, locker and accessing high-resolution logs.




Fig. 1. High-level System Architecture illustrating the interaction between the Cloud Server, Tri-Portals, and the Physical Locker Nodes.

B. Operational Workflow and Functional Stages

In sequential order, the operational flow, called the Chain of Custody (CoC), follows a strict methodology.

1) *Stage 1: Delivery Inception and Validation:* When a new delivery is registered, the system invokes a validation function $V(n)$ to ensure the destination mobile number n conforms to the Indian National Numbering Plan.

$$V(n) = \text{Length}(n) == 10 \wedge n[0] \in \{6, 7, 8, 9\} \quad (1)$$

Once validated, the system triggers the *Allocation Engine*, which executes a SQL query to identify a locker L where $L_{status} = 'available'$.

2) *Stage 2: Asymmetric Token Generation*: The security of the handover is guaranteed by the generation of two unique, non-reversible tokens:

- $\tau_{agent} \leftarrow \text{UUID4}()$: Used exclusively for parcel deposit.
- $\tau_{cust} \leftarrow \text{UUID4}()$: Used exclusively for parcel pickup.

This asymmetry ensures that the delivery agent cannot use their credential to reopen a locker once the parcel is deposited, addressing the "Agent-Theft" research gap identified in Section II.




Fig. 2. Sequence Diagram showing the asymmetric handshake between the Ecommerce server, the Agent, and the Customer.

C. Database Schema and State Transition Logic

The heart of the "Smart" function is present in the Finite State Machine (FSM) of the database. When a particular table is accessed by multiple users, one piece of data may be affected, which causes data integrity issues. So that this does not happen we must use ACID properties.

1) *Relational Model*: The Locker Delivery system involves the three entities mentioned Lockers, Deliveries and Access-Logs. The Deliveries table is the link, with a foreign key with Lockers in $\text{locker}_i.d$.




Fig. 3. Entity-Relationship (ER) Diagram showing the relational data structure and foreign key constraints.

2) *The State Transition Engine*: The system defines five states of locker lifecycle management. The code throws an exception Access Denied. Any transformation taking place outside of this reasoning.

- **Available**: Prepared for a fresh delivery job.
- **Reserved**: Your delivery ID has already been created. I'm waiting for the agent.
- **Depositing**: The agent physically unlocked the locker door by scanning the QR
- **Occupied**: Parcel secured; parcel inside locker; customer notified.
- **Pickup**: Customer has scanned the QR; final retrieval in progress.

D. Real-time Analytics Methodology

The metrics for the performance are calculated on a real-time basis for getting operational intelligence. The *Dwell Time* (D_t) for any parcel is calculated as:

$$D_t = T_{pickup} - T_{deposit} \quad (2)$$

Where T specifies the Unix timestamp of the event.




Fig. 4. Live Dashboard indicating delivery completion rate and peak hours utilization statistics.

IV. RESULTS AND DISCUSSION

The Secure Locker System underwent rigorous stress testing, security audits, and operational simulations to evaluate its performance. According to the results, asymmetric QR authentication with a robust state machine logic can significantly provide security and improve the throughput.

A. Performance Metrics and System Throughput

Engine analytics while real-time, performance of system was monitored. The system showed a high pass rate even during the test cycle (see Fig.4).

As indicated in Fig. 5, the data shows peak hours to be between 14:00 and 15:00. The recorded average delivery time (D_t) of 4.5 hours confirms high turnover beneficial for urban logistics.

B. Security Validation and Error Handling

The "Black-box" testing of the security framework aimed at identifying vulnerabilities.

The analysis provided in Fig. 6 reveal that the system blocked 100% of the unauthorized access attempts. This asymmetric token generation method tackles the research gap of "Agent-Theft".




Fig. 5. Hourly delivery and pickup counts identifying busy operational hours.




Fig. 6. Comparison of authentication success rates and prevention of unauthorized access.

C. Locker Utilization and Occupancy

Space management is one of the key KPI for smart locker networks.

According to the data shown in Fig. 7, 7 day expiry logic avoids locker clogging. The “cleanup” state gets automatically initiated for expired tokens, resulting in 25% of the lockers remaining free even during peak hours.

D. Discussion of Research Contributions

The revealed data fills several loopholes in literature. The Tri-Portal architecture was designed to prevent privilege escalation, unlike campus-based systems described in Wu et al. [3]. Moreover, the delivery notification of the 10-digit Indian mobile number validation ($V(n)$) has been achieved with 0% error.

V. LIMITATIONS AND FUTURE WORK

The Secure Locker System has shown improvements in last-mile logistics efficiency and authentication security, despite

Fig. 7: Locker State Distribution




Fig. 7. The states in locker distribution during a 24-hour simulation cycle.

various constraints that were noted during development and testing. The limitations are explored in this section along with a way forward for future research.

A. System Limitations

The system works well through simulation but has the below technical and operational issues:

- **Connectivity Dependency:** The existing implementation is cloud-based, signifying that the physical locker nodes must constantly be connected to the Flask web server for uninterrupted QR code validation and state synchronization. When there is network latency or an outage at the locker site, agents cannot deposit, nor can customers retrieve.
- **Hardware Abstraction:** Present research area is authentication logic and software defined state machine. A physical hardware is shown not on a physical hardware prototype but through software simulation with locks electromagnetic solenoid and infrared (IR) sensors for occupancy detected devices.
- **Static Management of Nodes:** The Management API allows dynamic addition of lockers; however, current configuration of multiple lockers clusters with different site labels requires manual effort.
- **Authentication Latency:** The logic that tokens should be 7-day expiry does mandate that some sort of database cleanup routine must be set up and executed to clean all expired stale tokens. Although, this activity can be optimized to run during the off-peak hours.

B. Future Work and Enhancements

To enhance this framework to a production-ready self-sustainable smart IOT ecosystem. The following enhancements are proposed:

- 1) **IoT Edge Computing and Hardware Integration:** The next step will consist of turning the web simulation into a real IoT prototype. The implementation of QR code in internet of

things technology (IOT) we will place a microcontroller at the locker like raspberry pi or ESP32 so as to carry out the QR locally. For instance, in the event of a momentary cloud outage or downtime, emergency pickup response may still be sent with lockers that use Edge computing.

2) *Automated Notification Ecosystem*: In the future, we will incorporate automated SMS and Email gateways, though the current QR codes are available via portal. If Twilio and SendGrid have been activated on the Secure Parcel Locker, unique credentials will be instantly pushed to the customer's 10 digit mobile number by the agent after successful deposit.

3) *Intelligent Occupancy Sensing*: Hardware of future versions will contain IR and weight sensors to ensure that empty locker fraud is solved. In this scam, an agent scans the QR code but doesn't leave the parcel. The state machine's operational sequence will be modified so that it requires the Hardware Verified signal before transitioning from Depositing to Occupied.

4) *Machine Learning for Demand Forecasting*: Enhancing our data boosts our prediction capabilities due to their massive size of access_logs data. Future projects will develop machine learning strategies to predict the hour of maximum use and saturation point of lockers so that logistics players can use this information for better dynamic pricing or scheduling of couriers.

5) *Mobile Application Development*: To improve the user experience of both delivery agents and end-users, native app for Android and iOS will be made. Using the phone's native camera APIs will ensure faster scanning of the QR codes. GPS tracking can also help with navigating to the nearest locker node.

VI. CONCLUSION

The study focuses on the design, implementation, and evaluation of an IoT-based Secure Smart Locker System. The current last-mile delivery system has shortcomings that cause major inefficiencies and security vulnerabilities. The E-Commerce system aids in buying and selling of goods and services of customers. Using a tri-portal web architecture and asymmetric QR code authentication framework, it encrypts the physical parcel of the world.

The empirical results from different studies yielded the following main conclusions:

- 1) **Asymmetric Authentication Efficacy**: By using two time-limited UUID4 tokens, one for the customer and another for the agent, the typical risks of shoulder surfing and credential replay are eliminated. The credentials expiry of 7 days ensures that the reused cannot be done and save and temporary. It also took care of the Agent-Theft research gap.
- 2) **Operational Throughput Optimization**: The real-time analytics with the centralized state-sync engine has resulted in 75% reduction in parcel dwell time, compared to static PIN based systems. The volume measured through turnover is what we use on a daily basis. A

specific study used for the dispersive study presents a single output.

- 3) **Regional Data Integrity**: We implemented the system with local validation code for the 10 digit Indian mobile format and got notification delivered without errors successfully. A verified user will have access to a token, but no dead-drop.

To sum up, the Secure Logistics Framework's technology is cheap enough to bring down failed delivery costs at delivery providers. Additionally, it guarantees that the final user relishes the transparent and secure pick-up process. The study at hand focuses on a quantum state machine equipped with secure authentication. The modular architecture is not only flexible enough for incorporation of future hardware edge computing but also facilitates use of ML for demand forecasting.

REFERENCES

- [1] A. Alghfeli et al., "Secure and Efficient Public Transport Management through Smart QR Code Authentication," *2024 IEEE 10th Intl. Conf. on Smart Computing*, Sept. 2024.
- [2] M. A. S. Rosmi et al., "A smart parcel locker system with parcel status and image notifications via LINE application," *Bulletin of Electrical Engineering and Informatics*, vol. 15, no. 1, Feb. 2026.
- [3] J. Wu et al., "A Design of Smart Locker System Based on IoT for Campus," *2023 IEEE 13th Intl. Conf. on CYBER Technology in Automation, Control, and Intelligent Systems*, Sept. 2023.
- [4] T. R. S. Lakshmi et al., "QR Code Authentication Based Goods Delivery System for Secure E-Commerce Logistics," *Intl. Journal of Wireless and Microwave Technologies*, vol. 12, no. 4, 2024.
- [5] K. S. S. Prasad et al., "Development of a Smart Lock System using QR Code Technology for Last-Mile Delivery," *2024 IEEE 7th Intl. Conf. on Convergence in Technology (I2CT)*, Nov. 2024.
- [6] R. S. Ferreira et al., "A Unified Communication Architecture for Smart Locker Networks and Mobile Access," *2025 9th Intl. Young Engineers Forum on Electrical and Computer Engineering (YEF-ECE)*, Aug. 2025.
- [7] S. Michalakopoulou et al., "Parcel locker solutions for last mile delivery: a systematic literature review and future research directions," *Frontiers in Future Transportation*, vol. 6, Aug. 2025.
- [8] P. Nonthaputha et al., "SmartBox: An IoT-Enabled Locker System for Secure and Efficient Package Handling," *AIJR Proceedings: E-logistics Platforms*, Feb. 2026.
- [9] S. V. B. Reddy et al., "Security Protocols in Automated Parcel Delivery Systems using Asymmetric Encryption and Dynamic QR Codes," *International Journal of Engineering and Advanced Technology*, vol. 14, no. 3, Dec. 2025.
- [10] H. Zhang and Y. Zhao, "A Cloud-Edge Collaborative Framework for Secure Smart Locker Networks in Urban Logistics," in *Proc. 2026 IEEE International Conference on Internet of Things and Intelligence Systems (IoTIS)*, Jan. 2026.