

Use-case flow - UC-01 Create Anonymous Wellness Account

Problem Statement #14 - Healthcare & Telemedicine - Corporate Mental Wellness & Counseling Platform

Primary actor: Corporate Employee

Secondary actors: Corporate Identity Provider

Goal: Get the employee an account that proves they are entitled to the benefit, while leaving the counselling side of the system with nothing but a pseudo-ID.

Trigger: The employee opens the portal for the first time and chooses 'Create account'.

Preconditions

1. The employer has enrolled in the programme and its directory feed is reachable.
2. The employee holds valid corporate credentials.
3. No wellness account exists yet for this employee.

Postconditions (success)

1. A pseudo-ID in the format WEL-XXXXXXX has been generated at random and issued.
2. The mapping between the employee and the pseudo-ID is stored encrypted, in the identity store rather than with counselling data (NFR-002).
3. The employee can take an assessment and book sessions.
4. No counselling-side record created by this use case carries a corporate identifier (FR-001).

Postcondition (failure): No account, no pseudo-ID and no mapping row exist, and the employee is told the verification did not succeed.

Main success scenario

1. The employee chooses 'Create account'.
2. The system hands the employee to the Corporate Identity Provider to sign in.
3. The employee authenticates with their corporate credentials.
4. The identity provider returns a signed assertion confirming current employment («include» UC-13).
5. The system checks that no wellness account already exists for that assertion.
6. The system generates a random pseudo-ID («include» UC-08) and confirms it is not already in use.
7. The system writes the mapping to the identity store, encrypted.
8. The system drops the corporate identifiers from the session and keeps only the pseudo-ID.
9. The system shows the employee their pseudo-ID and explains that this is the only thing a therapist will ever see.
10. The use case ends successfully.

Alternate flows

4a. The person is not a current employee

- 4a1. The identity provider returns no assertion, or one marking the account as inactive.
- 4a2. The system refuses registration and shows the employer's benefits contact.
- 4a3. Nothing is written to either store and the use case ends.

5a. An account already exists

- 5a1. The system finds a mapping for that assertion.
- 5a2. The system signs the employee into the existing account instead of issuing a second pseudo-ID.
- 5a3. The use case ends successfully, with the pseudo-ID unchanged.

7a. The mapping cannot be written

- 7a1. The identity store rejects the write or times out.
- 7a2. The system discards the generated pseudo-ID so no orphan identifier is left behind, and asks the employee to try again.

Notes

- Steps 3 and 4 are the only point in the whole system where a corporate identity is handled. Everything after step 8 works on the pseudo-ID.
- The pseudo-ID is random rather than a hash of the employee ID, so nobody can recompute it from a directory export.