	ELogo
(echic	TAILS SECOND TEMPER SECURIC SET ON STUDENT REPORT TEMPER SECURIC SECOND SECO
< C	CSEON LEWER CS. OTHER TOTAL TO
5.5	TAILS CSEDAN TEMPETECTICS TO A TEMPETECTIC SEDAN TEMPETECTICS TO A
Z E	PAILS STORY AND THE STORY STORY STORY STORY STORY STORY STORY
.6	DHANUSH JADHAV
.v. CS	DHANUSH JADHAV NOII Number AND
	TEMPS IECH-USEU4U
EV	
Titl	PERIMENT CAD COLOR OF THE PROPERTY OF THE PROP
C	CHOCOLATE JAR SELDO TEMPETED STEELD OF THE SELDON STEELD S
SEOD	ATT. Selection Store The Store
SE	Description No. 1987 Control of the
	You are given an integer array of size N, representing jars of chocolates. Three students A, B, and C respectively, will pick chocolates one by one from each chocolate jar, till the jar is empty, and then repeat the same with the rest of the jars. Your task
10	is to fine and return an integer value representing the total number of chocolates that student A will have, after all the
RATE	chocolates have been picked from all the jars.
	Note: Once a jar is done A will start taking the chocolates from the new jar.
OAO	input Format:
:040°	input1: An integer value N representing the number of jars.
	input2: An integer array representing the quantity of chocolates in each jar.
Lech.	Output Format:
Lech.	Return an integer value representing the total number of chocolates that student A will have, after all the chocolates are picked.
	Example:
XO TES	Input:
	3
Ċ	10 20 30
ch'.Ce	Output:
	21
,R ^{<}	Explanation:
EMP	Jar 1: 10 chocolates -> A-4, B-3,C-3
	Jar 2: 20 chocolates -> A-7, B-7, C-6
	Jar 3: 30 chocolates -> A-10, B-10,C-10
	so A gets a total of 4+7+10=21 chocolates. Source Code: THE REPORT OF THE PROPERTY OF THE PR
S	Source Code:
	A SECTION OF THE SECT
	TEM, SLICE VOLK, STARTER START

```
def total_chocolates_for_A(chocolates):
    total_chocolates_A = 0

# Iterate through each jar
for jar in chocolates:
    # Full cycles where A gets 1 chocolate per cycle
    total_chocolates_A += jar // 3

# If there are leftover chocolates and A gets 1 more
    if jar % 3 >= 1:
        total_chocolates_A += 1

return total_chocolates_A
jar=int(input())
chocolates=list(map(int,input(). split ()))
print(total_chocolates_for_A(chocolates))

RESULT

RESULT

S/5 Test Cases Passed | 100 %
```