Java Institute for Advanced Technology • Unit: Object Oriented Design Patterns II (JIAT/OODP II) • JIAT/OODP II /EX/01

SMARTCITY360 MANAGEMENT PLATFORM

Technical Design Pattern Implementation & Comprehensive Architectural Assessment Report

Industrial Context: UrbanTech Solutions • Target City: Metropolis Neo-Prime

TABLE OF CONTENTS

1. Executive Summary & Scenario Overview

2. Part A — Dynamic Security Wrappers for Data Streams (Decorator Pattern)

2.1 Identification & Architectural Justification

2.2 Mechanism of Flexible & Layered Enhancement

[Figure 2.1 — UML Class Diagram: Dynamic Security Decorator Architecture]

2.3 Long-Term Evaluation: Reusability, Extensibility & Anti-Pattern Mitigation

2.4 Object Wrapping Pipeline Flowchart & Source Code Architecture

[Figure 2.2 — Data Stream Dynamic Wrapping Pipeline Execution Flowchart]

[Listing 2.1 — Production Source Code Screenshot: EncryptionDecorator.java]

3. Part B — Hierarchical Structure of Smart Zones (Composite Pattern)

3.1 Identification & Architectural Justification

3.2 UML Class Diagram & Mechanism of the Hierarchical Composition

[Figure 3.1 — UML Class Diagram: Hierarchical Smart Zones Composite Pattern]

3.3 Evaluation: Scalability & Growing Infrastructure Management

3.4 Hierarchical Urban Zone Topography & Source Code Architecture

[Figure 3.2 — Hierarchical Urban Zone Topography & Object Composition Hierarchy]

[Listing 3.1 — Production Source Code Screenshot: ZoneComposite.java]

4. Part C — Escalation of Citizen Complaints (Chain of Responsibility Pattern)

4.1 Identification & Architectural Justification

4.2 Mechanism of Decoupled Request Handling

[Figure 4.1 — UML Class Diagram: Multi-Tier Complaint Escalation Chain]

4.3 Evaluation of Flexibility, Traceability, Benefits & Trade-offs

4.4 Multi-Tier Escalation Flowchart & Source Code Architecture

[Figure 4.2 — Dynamic Citizen Complaint Escalation Workflow & Decision Flowchart]

[Listing 4.1 — Production Source Code Screenshot: ComplaintHandler.java]

5. Part D — Efficient Management of Smart Street Lights (Flyweight Pattern)

5.1 Identification & Architectural Justification

5.2 Handling Shared Intrinsic vs Unique Extrinsic State

[Figure 5.1 — UML Class Diagram: Smart Streetlight Flyweight Pattern Architecture]

5.3 Quantitative Memory & Performance Impact Analysis (72.2% Analytical Layout Reduction)
5.4 JVM Memory Pool Architecture Diagram & Source Code Architecture
[Figure 5.2 — JVM Heap Memory Allocation: Flyweight Pool vs Unoptimized Graph]
[Listing 5.1 — Production Source Code Screenshot: StreetlightProfileFactory.java]

6. Part E — Interpreting City Policies Defined in DSL (Interpreter Pattern)
6.1 Identification & Architectural Justification
6.2 UML Class Diagram & Mechanism of the DSL Interpreter Pattern
[Figure 6.1 — UML Class Diagram: Municipal Policy DSL Grammar & Interpreter]
6.3 Critical Assessment: Rule Updates, Extensibility & Security
6.4 Abstract Syntax Tree (AST) & Source Code Architecture
[Figure 6.2 — Abstract Syntax Tree (AST) Decomposition & Evaluation Flowchart]
[Listing 6.1 — Production Source Code Screenshot: DslPolicyParser.java]

7. Part F — Final Project Demonstration, VIVA Defense & Video Outline
7.1 Overall System Architecture & Multi-Tier Enterprise Design
[Figure 7.1 — End-to-End SmartCity360 Multi-Tier Enterprise Platform Architecture]
[Figure 7.2 — SmartCity360 Comprehensive System Use Case Diagram]
[Figure 7.3 — Architectural Package Structure & Component Interaction Diagram]
[Figure 7.4 — SmartCity360 Relational Database Entity-Relationship Diagram (ERD)]
7.2 Key Architectural Choices & Anti-Pattern Defense Matrix
7.3 Empirical Automated Test Execution Results (35/35 Tests Passing - 100%)
7.4 Final Submission Deliverables Verification

8. Conclusion & Academic References

9. Appendix A — Comprehensive Source Code Implementation Screenshot Catalog
9.1 Part A: Data Stream Security Wrappers Source Code Screenshots (Decorator Pattern)
9.2 Part B: Hierarchical Smart Zones Source Code Screenshots (Composite Pattern)
9.3 Part C: Citizen Grievance Escalation Source Code Screenshots (Chain of Responsibility Pattern)
9.4 Part D: Smart Streetlight Memory Optimization Source Code Screenshots (Flyweight Pattern)
9.5 Part E: Municipal Policy DSL Grammar Source Code Screenshots (Interpreter Pattern)

LIST OF ARCHITECTURAL FIGURES & DIAGRAMS

This technical assessment report incorporates 14 dedicated architectural diagrams, UML class models, behavioral sequence workflows, and system enterprise designs mapped directly to the assessment rubric. Each architectural figure is embedded within its designated system specification section below:

Figure ID	Diagram Title & Description	Rubric Mapping	Report Location
Figure 2.1	UML Class Diagram — Dynamic Security Decorator Pattern Architecture	Part A.2	Section 2.2

Figure ID	Diagram Title & Description	Rubric Mapping	Report Location
Figure 2.2	Data Stream Dynamic Wrapping Pipeline & Execution Flowchart	Part A.4 (Highlights)	Section 2.4
Figure 3.1	UML Class Diagram — Hierarchical Smart Zones Composite Pattern	Part B.2 (Mandatory)	Section 3.2
Figure 3.2	Hierarchical Urban Zone Topography & Object Composition Hierarchy	Part B.4 (Highlights)	Section 3.4
Figure 4.1	UML Class Diagram — Multi-Tier Complaint Escalation Chain of Responsibility	Part C.2	Section 4.2
Figure 4.2	Citizen Complaint Dynamic Escalation Workflow & Decision Flowchart	Part C.4 (Highlights)	Section 4.4
Figure 5.1	UML Class Diagram — Smart Streetlight Flyweight Pattern Architecture	Part D.2	Section 5.2
Figure 5.2	JVM Heap Memory Allocation: Flyweight Shared Pool vs Unoptimized Heap Graph	Part D.4 (Highlights)	Section 5.4
Figure 6.1	UML Class Diagram — Municipal Policy DSL Grammar & Interpreter Pattern	Part E.2 (Mandatory)	Section 6.2
Figure 6.2	Abstract Syntax Tree (AST) Decomposition & Boolean Evaluation Flowchart	Part E.4 (Highlights)	Section 6.4
Figure 7.1	End-to-End SmartCity360 Multi-Tier Enterprise Platform Architecture Diagram	Part F.1	Section 7.1
Figure 7.2	SmartCity360 Comprehensive System Use Case Diagram	Part F.1 (Use Cases)	Section 7.1
Figure 7.3	Architectural Package Structure & Subsystem Component Interaction Diagram	Part F.1 (Components)	Section 7.1
Figure 7.4	SmartCity360 Relational Database Entity-Relationship Diagram (ERD)	Part F.1 (Persistence)	Section 7.1

LIST OF SOURCE CODE IMPLEMENTATION SCREENSHOT PLACEMENTS

In accordance with Part F.3 of the assessment specification, production source code architecture is formally documented through dedicated pattern listings and the comprehensive source catalog in Appendix A. The complete, compilable production source code is packaged in the accompanying project repository archive:

Listing ID	Pattern / Subsystem Title	Primary Target Source File Path	Report Location
Listing 2.1	Dynamic Security Decorator Pattern	backend/src/main/java/com/smartcity/pattern/decorator/EncryptionDecorator.java	Section 2.4 & App. A.1
Listing 3.1	Hierarchical Smart Zones (Composite Pattern)	backend/src/main/java/com/smartcity/pattern/composite/ZoneComposite.java	Section 3.4 & App. A.2
Listing 4.1	Citizen Grievance Escalation (Chain of Responsibility)	backend/src/main/java/com/smartcity/pattern/chain/ComplaintHandler.java	Section 4.4 & App. A.3
Listing 5.1	Smart Streetlight Memory Optimization (Flyweight Pattern)	backend/src/main/java/com/smartcity/pattern/flyweight/StreetlightProfileFactory.java	Section 5.4 & App. A.4
Listing 6.1	Municipal Policy DSL Mini-Language (Interpreter Pattern)	backend/src/main/java/com/smartcity/pattern/interpreter/DslPolicyParser.java	Section 6.4 & App. A.5

1. EXECUTIVE SUMMARY & SCENARIO OVERVIEW

As part of my final assessment for Object Oriented Design Patterns II (JIAT/OODP II /EX/01), I have designed, audited, and implemented the core enterprise architectural components for SmartCity360, a digital municipal operating platform developed under UrbanTech Solutions for the municipal administration of Metropolis Neo-Prime. Modern cities are complex, highly interconnected cyber-physical systems that integrate thousands of IoT sensors, distributed utility grids, municipal regulations, and citizen services.

When analyzing the initial system requirements, it became clear that conventional procedural programming and rigid inheritance hierarchies would inevitably cause critical system failures: tight coupling, severe memory bloat, high garbage collection latency, and unmaintainable conditional branching. To overcome these engineering challenges, I systematically applied five core Gang of Four (GoF) design patterns:

1. The Decorator Pattern (Structural): Designed to dynamically attach and detach data transformation and security layers onto high-frequency energy meter telemetry streams without altering the underlying polling engine. The processing pipeline strictly applies GZIP compression prior to AES-256-GCM encryption, complemented by an outer HMAC-SHA256 authentication tag for shared-secret perimeter verification and tamper detection.
2. **The Composite Pattern (Structural):** Applied to organize nested municipal zones (City, Districts, Streets, Buildings) into a unified tree structure, enabling uniform broadcasting of administrative

commands (such as SHUTDOWN_POWER and RESTORE_POWER via a type-safe ZoneCommand abstraction) and recursive energy aggregation.

3. **The Chain of Responsibility Pattern (Behavioral):** Employed to route citizen grievances through a decoupled, multi-tiered escalation pipeline (Validation Triage, Local Staff, Area Supervisors, City Manager, and Terminal Fallback). Critically, unclassified or missing severities are safely intercepted by a triage handler and never defaulted to LOW.
4. The Flyweight Pattern (Structural): Implemented to optimize the heap memory footprint of 25,000 smart LED streetlights by sharing immutable hardware profiles across instances via a thread-safe ConcurrentHashMap cache. Based on the 288-byte naive object and 80-byte context assumptions in FlyweightBenchmark.java, the implementation achieves an analytical 72.2% memory layout reduction, significantly mitigating young-generation allocation pressure.
5. The Interpreter Pattern (Behavioral): Designed to parse and evaluate municipal environmental ordinances written in a Domain-Specific Language (DSL) via a recursive-descent parser and restricted Abstract Syntax Tree (AST) evaluation environment, executing in microseconds while reducing the attack surface compared to general-purpose scripting engines by restricting evaluation to controlled Boolean threshold expressions with strict token and depth limits.

This report documents my complete architectural reasoning, algorithmic derivations, quantitative memory calculations, anti-pattern mitigation analysis, and empirical test evidence (35/35 automated tests passing). In accordance with academic guidelines, key illustrative architectural code snippets are presented below, with the complete compilable codebase packaged in the accompanying project source archive.

2. Part A — Dynamic Security Wrappers for Data Streams

> Scenario Description: SmartCity360 continuously ingests high-frequency telemetry streams from distributed energy meters across municipal power grids. The transmission channel requires varying security protocols: Payload Encryption (AES-256-GCM) for data confidentiality and tamper detection across public backhauls; Cryptographic Authentication (HMAC-SHA256 authentication tags) to verify shared-secret authenticity and detect payload tampering; and Stream Compression (GZIP) to minimize network bandwidth consumption across constrained cellular IoT links. These capabilities must be dynamically configurable and composable at runtime on a per-stream basis on a per-stream basis without altering the underlying energy meter polling engine.

2.1 A.1 Identification & Architectural Justification

> Selected Design Pattern: Decorator Design Pattern (Structural GoF Pattern; Gamma et al., 1994)

When evaluating the requirements for securing data streams in SmartCity360, I selected the Decorator Pattern (Structural GoF) as the most appropriate architectural solution.

My Architectural Justifications:

1. Prevention of Combinatorial Class Explosion:

In evaluating stream security architectures, I analyzed the structural consequences of using traditional static class inheritance to attach security features (Compression, Encryption, and Authentication) to the core energy telemetry stream. When each optional feature can be independently enabled or disabled, the total number of possible runtime feature combinations is:

> Total Feature Combinations = 2^N

With N = 3 optional features, there are 2^3 = 8 distinct runtime feature combinations: (1) PlainStream, (2) CompressedStream, (3) EncryptedStream, (4) AuthenticatedStream, (5) CompressedEncryptedStream, (6) CompressedAuthenticatedStream, (7) EncryptedAuthenticatedStream, and (8) CompressedEncryptedAuthenticatedStream.

Under a static inheritance architecture, supporting every combination requires authoring and maintaining 2^N separate, concrete subclasses. If the municipality subsequently introduces a fourth transformation layer (such as AnonymizedStream for data privacy compliance), the required subclasses expand exponentially to 2^4 = 16 subclasses, and a fifth feature would require 32 subclasses. This exponential class explosion severely compromises maintainability, creates pervasive code duplication, and violates the Single Responsibility Principle.

In contrast, the Decorator pattern decouples class authoring complexity from runtime combinatorial flexibility. Rather than creating subclasses for combinations, the Decorator pattern requires authoring only N reusable concrete decorator classes (CompressionDecorator, EncryptionDecorator, and AuthenticationDecorator), alongside 1 uniform component interface (StreamData) and 1 abstract decorator base (StreamDataDecorator). The developer authors and maintains a linear number of classes—O(N)—which clients can dynamically assemble into any of the 2^N possible feature combinations at runtime through object composition. Thus, the pattern does not eliminate the 2^N runtime combinations; rather, it allows all 2^N combinations to be realized with only O(N) classes.

2. Strict Adherence to the Open/Closed Principle (OCP) (Martin, 2008):

The core energy telemetry ingestion class (EnergyStreamData) remains completely closed for modification. Whenever security standards evolve, I can introduce new transformation layers simply by creating new decorator classes without altering a single line of existing production code.

3. Dynamic Runtime Composition vs Compile-Time Rigidity:

Inheritance permanently binds functionality at compile time. In a smart city environment, network conditions and security alert levels change dynamically. With the Decorator pattern, municipal operators can dynamically compose, wrap, or unwrap optional transformation layers on an active data stream at runtime—adapting instantaneously to threat escalations (e.g., selectively enabling encryption across untrusted WAN links) or cellular bandwidth constraints (e.g., enabling compression on metered cellular backhaul)—while strictly preserving the required cryptographic pipeline ordering (Compression -> Encryption -> Authentication).

2.2 A.2 Flexible & Layered Enhancement Mechanism

To achieve flexible and layered enhancements, I structured the Decorator implementation around recursive object aggregation, strict interface conformance, and a mathematically sound transformation pipeline:

1. Unified Component Contract (StreamData Interface):

I defined a common interface, StreamData, implemented by both the concrete core component (EnergyStreamData) and the abstract wrapper base (StreamDataDecorator). The interface establishes four fundamental operations:

- **getData():** Returns the processed string payload (or Base64 envelope).
- **getPayloadBytes():** Returns the raw byte array of the current transformation stage.
- getPayloadSize(): Returns the exact payload byte length, with strict invariant getPayloadSize() == getPayloadBytes().length.
- **getDescription():** Returns the human-readable pipeline description.

2. Recursive Aggregation ('HAS-A' Relationship):

The abstract StreamDataDecorator maintains a protected reference to another StreamData instance:

```
public abstract class StreamDataDecorator implements StreamData {
    protected final StreamData wrappee;
    public StreamDataDecorator(StreamData wrappee) {
        this.wrappee = wrappee;
```

Because StreamDataDecorator implements StreamData while simultaneously holding a StreamData reference, any decorator can wrap either the core component or another decorator. This allows nesting decorators to an arbitrary depth at runtime:

```
StreamData stream = new EnergyStreamData("STR-101", 230.5, 14.2, 3.27);
stream = new CompressionDecorator(stream);
stream = new EncryptionDecorator(stream, secretKey);
stream = new AuthenticationDecorator(stream, hmacKey);
```

3. Correct Cryptographic & Compression Pipeline Ordering:

A critical engineering rule in data transmission is that Compression Must Precede Encryption. Encrypted ciphertext produced by strong ciphers such as AES-256-GCM exhibits near-maximum Shannon entropy, appearing as uniform pseudorandom noise. Lossless compression algorithms (such as DEFLATE/GZIP) depend on detecting repeating byte patterns and statistical redundancy; attempting to compress ciphertext yields zero compression or even slight byte expansion due to format headers. Therefore, my pipeline strictly compresses raw structured JSON telemetry first, and then encrypts the compressed byte array.

4. Authenticated Encryption with Associated Data (AEAD) & Outer HMAC (Dworkin, 2007; Krawczyk et al., 1997):

In SmartCity360, EncryptionDecorator utilizes the AES-256-GCM (Galois/Counter Mode) authenticated encryption algorithm. Under GCM mode, the cipher provides both confidentiality and data integrity: each encryption pass generates a unique 12-byte initialization vector (IV) via SecureRandom and computes a 128-bit authentication tag appended to the ciphertext. Tampering with either the ciphertext or the IV causes Cipher.doFinal() to throw an AEADBadTagException during decryption, verifying cryptographic integrity natively at the cipher level.

Why an additional outer HMAC-SHA256 layer is implemented in AuthenticationDecorator:

• Cryptographic Key Separation: The system establishes two independent secret keys: a 256-bit symmetric cipher key (STREAM_AES_KEY) for payload confidentiality, and an independent HMAC secret key (STREAM_HMAC_KEY) for perimeter gateway authentication. This separation ensures that compromise of perimeter verification credentials does not compromise the private decryption key.

• Data Covered by HMAC Authentication Tag: When AuthenticationDecorator wraps EncryptionDecorator, Mac.getInstance("HmacSHA256") computes the authentication tag over wrappee.getData(), which represents the complete transport JSON envelope: {"cipher":"AES-256-GCM","iv":"<ivB64>","tagLength":128,"ciphertext":"<ciphertextB64>"}
Crucially, the HMAC authentication tag covers the IV, cipher parameters, and the full ciphertext (which embeds the 128-bit GCM tag). Any alteration to transport framing, IV, or ciphertext is caught at the outer authentication tag boundary.

• Encrypt-then-MAC Verification Order & DoS Defense: On the receiving side, processing follows the strict Encrypt-then-MAC paradigm in reverse. Perimeter gateways and edge routers verify the outer HMAC authentication tag first using MessageDigest.isEqual(). If the HMAC authentication tag is invalid (due to transmission corruption, an unauthorized sender lacking the shared secret key, or tampered metadata), the packet is rejected and dropped immediately at the network perimeter. (Note: HMAC provides message integrity and origin authentication between parties that possess the shared secret; it does not provide asymmetric digital signature non-repudiation). This shields internal services from computationally intensive AES-GCM decryption cycles and protects against denial-of-service (DoS) packet floods.

• Architectural Trade-off: It must be emphasized that an outer HMAC is not universally mandatory for all AES-GCM deployments, since GCM mode already detects payload tampering. Here, the outer HMAC serves a specific operational purpose: enabling perimeter gateway authentication and early packet filtering without distributing the private AES decryption keys to perimeter routing nodes.




Figure 2.1: *UML Class Diagram — Dynamic Security Decorator Pattern Architecture — Structural hierarchy depicting component interface, concrete component, abstract decorator aggregation, and specialized encryption/compression/authentication wrapper classes.*

2.3 A.3 Long-Term Evaluation: Reusability, Extensibility & Anti-Pattern Mitigation

1. Long-Term Reusability Benefits:

- **Orthogonal Separation of Concerns:** In my implementation, stream compression logic resides strictly inside CompressionDecorator, AES-256-GCM encryption inside EncryptionDecorator, and cryptographic signing inside AuthenticationDecorator. None of the decorators have compile-time dependencies on each other.
- **Mix-and-Match Composability:** Different municipal sensors have radically different transmission priorities. High-voltage power grid substations require [Compression -> Encryption -> Authentication]; low-power environmental air quality sensors on isolated networks require only [Compression]; public analytic feeds require only [Authentication]. By isolating responsibilities into single-purpose decorators, all configurations reuse the exact same classes without code duplication.

2. System Extensibility:

- **Forward Compatibility:** If municipal regulations mandate Post-Quantum Cryptography (e.g., Kyber-1024 or Dilithium) in the future, developers only need to write a new decorator class extending

StreamDataDecorator. The core polling engine, telemetry models, and database ingestion pipelines remain completely untouched, ensuring zero regression risk.

3. Empirical Compression Analysis vs Theoretical Claims:

In initial theoretical discussions, flat claims of '55% compression' were cited. My empirical testing reveals the actual dynamics of GZIP stream compression:

- **Single Small Packet (72 bytes JSON):** GZIP produces 92 bytes due to mandatory 10-byte gzip header, 8-byte CRC-32 trailer, and block framing. Small single IoT packets incur a slight framing overhead.
- **Batched Telemetry Stream (1 KB to 64 KB):** When telemetry readings are buffered into realistic operational batches (e.g., 20 to 100 consecutive readings), GZIP achieves 65% to 75% bandwidth reduction because repeating JSON keys ('streamId', 'voltage', 'current', 'powerKw') are compressed efficiently.

Documenting this threshold distinction ensures engineering integrity and realistic network capacity planning.

4. Mitigation of Object-Oriented Anti-Patterns:

- Spaghetti Code: Eliminates deeply nested conditional blocks such as 'if (isCompressed) { ... } else if (isEncrypted) { ... }' inside telemetry controllers.
- **God Object:** Prevents the creation of a bloated StreamManager class that attempts to poll meters, authenticate tokens, encrypt bytes, and compress packets in a single file.
- **Copy-Paste Programming:** Eradicates duplicate encryption and hashing logic across different meter ingestion handlers.
- **Long Method:** Breaks down complex transformation pipelines into cohesive methods of fewer than 20 lines distributed across discrete decorator classes.
- **Tight Coupling:** Client controllers interact exclusively with the StreamData interface, remaining completely decoupled from concrete transformation algorithms.

2.4 Architectural Implementation Highlights & Source Code Architecture




Figure 2.2: *Data Stream Dynamic Wrapping Pipeline & Execution Flowchart — Sequential runtime execution pipeline demonstrating compression-before-encryption ordering and outer HMAC authentication tagging.*

EncryptionDecorator.java

```java
public class EncryptionDecorator extends StreamDataDecorator {  16 usages  Dhanushka Maduranga

    public EncryptionDecorator(StreamData wrappee) {  9 usages  Dhanushka Maduranga
        this(wrappee, resolveDefaultKey());
    }

    public EncryptionDecorator(StreamData wrappee, byte[] keyBytes) {  5 usages  Dhanushka Maduranga
        super(wrappee);
        if (keyBytes == null || keyBytes.length != 32) {
            throw new IllegalArgumentException("AES-256 requires exactly 32-byte key");
        }
        this.keyBytes = keyBytes.clone();
        byte[] input = wrappee.getPayloadBytes();
        this.ivBytes = new byte[GCM_IV_LENGTH];
        new SecureRandom().nextBytes(this.ivBytes);

        try {
            SecretKey secretKey = new SecretKeySpec(this.keyBytes,  algorithm: "AES");
            Cipher cipher = Cipher.getInstance( transformation: "AES/GCM/NoPadding");
            GCMParameterSpec spec = new GCMParameterSpec(GCM_TAG_LENGTH, this.ivBytes);
            cipher.init(Cipher.ENCRYPT_MODE, secretKey, spec);
            this.ciphertextBytes = cipher.doFinal(input);
        } catch (GeneralSecurityException e) {
            throw new RuntimeException("AES-GCM encryption failed", e);
        }

        String ivB64 = Base64.getEncoder().encodeToString(this.ivBytes);
        String cipherB64 = Base64.getEncoder().encodeToString(this.ciphertextBytes);
        this.encryptedJson = "{\"cipher\":\"AES-256-GCM\",\"iv\":\"" + ivB64
                + "\",\"tagLength\":" + GCM_TAG_LENGTH
                + ",\"ciphertext\":\"" + cipherB64 + "\"}";
    }
```

Listing 2.1: *Production Source Code Implementation Screenshot — Dynamic Security Decorator Pattern — backend/src/main/java/com/smartcity/pattern/decorator/EncryptionDecorator.java*

3. Part B — Hierarchical Structure of Smart Zones

> **Scenario Description:** *City zones (city -> district -> street -> building) need to be represented hierarchically so that operations commands like 'shutdown power' or 'report usage' can be applied uniformly at any level of the municipal topography.*

3.1 B.1 Identification & Architectural Justification

> Selected Design Pattern: Composite Design Pattern (Structural GoF Pattern; Gamma et al., 1994)

When designing the structural representation for the municipal boundaries of Metropolis Neo-Prime, I selected the Composite Design Pattern (Structural GoF) as the most appropriate architectural solution.

My Architectural Justifications:

1. Uniformity of Leaf and Composite Treatment:

The municipal zoning model represents a classic 'part-whole' hierarchy: a City is composed of Districts, Districts are composed of Streets, and Streets are composed of individual Buildings. The Composite pattern allows client code to treat leaf objects (BuildingLeaf) and composite containers (ZoneComposite) identically through a single abstract component interface (ZoneComponent).

2. Elimination of Type-Checking and Spaghetti Recursion (Martin, 2008):

Without the Composite pattern, client controllers would need to traverse nested collections using explicit instanceof type checking:

```
    if (zone instanceof City) { ... }
    else if (zone instanceof District) { ... }
    else if (zone instanceof Building) { ... }
```

This creates rigid, error-prone spaghetti code. With the Composite pattern, the client simply executes:

```
    zoneComponent.executeCommand(ZoneCommand.SHUTDOWN_POWER);
```

Polymorphic dynamic dispatch takes care of recursively navigating the tree structure automatically, decoupling the invoker from the structural depth of the city.

3.2 B.2 UML Class Diagram & Mechanism of the Hierarchical Composition

In my implementation, the Composite pattern is organized into three distinct structural roles as illustrated in the accompanying UML Class Diagram:

1. Abstract Component (ZoneComponent):

Declares the common interface for all elements in the municipal tree, including operational methods (executeCommand, getPowerConsumption, getTotalPowerConsumption, getStatus) and child management contracts (add, remove, getChildren).

2. Type-Safe Command Abstraction (ZoneCommand Enum):

Instead of passing unrestricted strings (which cause silent failures when misspelled, e.g. 'shutDownPower'), I encapsulated valid operations in a robust Java enum:

```
    public enum ZoneCommand {
        SHUTDOWN_POWER,
        RESTORE_POWER,
        EMERGENCY_ISOLATE
```

3. Leaf Component (BuildingLeaf):

Represents terminal nodes in the hierarchy that have no children. A BuildingLeaf contains concrete hardware relay state (status = ONLINE/OFFLINE, baselinePowerKw, and current powerConsumptionKw).

When executeCommand(ZoneCommand.SHUTDOWN_POWER) is called on a leaf:

- Its status updates to OFFLINE.
- Its current power consumption drops to 0.0 kW.

When executeCommand(ZoneCommand.RESTORE_POWER) is called:

- Its status restores to ONLINE.
- Its power consumption restores to its rated baseline (baselinePowerKw).

4. Composite Component (ZoneComposite):

Represents non-terminal container nodes (City, District, Street). It maintains a collection of child components (List<ZoneComponent>). When executeCommand() is invoked on a ZoneComposite, it iterates over its children and recursively delegates the command to each child:

```
public void executeCommand(ZoneCommand command) {
    for (ZoneComponent child : children) {
        child.executeCommand(command);
```

This recursive composition enables administrative commands to cascade smoothly down through arbitrary depths of the urban hierarchy.




Figure 3.1: *UML Class Diagram — Hierarchical Smart Zones Composite Pattern — Formal structural class diagram demonstrating recursive composition, uniform client interface, and polymorphic command delegation across urban zones.*

3.3 B.3 Evaluation: Scalability & Growing Infrastructure Management

1. Cascading Command Execution Across Complex Topographies:

When executeCommand(ZoneCommand.SHUTDOWN_POWER) is dispatched to a top-level City composite:

- The City composite iterates through its child collection and invokes executeCommand on each District.
- Each District propagates the call to its contained Streets.
- Each Street cascades the call to its terminal BuildingLeaf components.
- Each BuildingLeaf disconnects its local power relays and terminates power draw.

The entire traversal executes via depth-first recursion in O(M) time (where M is the total number of nodes in the sub-tree), with zero awareness of tree depth required by the invoker.

2. Open/Closed Principle for Urban Growth:

As Metropolis Neo-Prime expands:

- New suburban districts, smart industrial corridors, or solar micro-grids can be inserted anywhere in the hierarchy without changing a single line of client execution logic.
- Adding new specialized composite types (e.g., MetroTransitComposite) requires only extending ZoneComponent, leaving existing classes untouched.

3. Aggregate Telemetry Rollup Calculations:

Municipal operations teams require aggregate real-time power consumption analytics across nested urban boundaries. In the codebase, getPowerConsumption() is the primary polymorphic operation declared in ZoneComponent. Leaf nodes (BuildingLeaf) implement getPowerConsumption() to return their active local power consumption (this.currentPowerKw). Composite nodes (ZoneComposite) implement getPowerConsumption() to iterate over their children and compute the recursive aggregate:

```
@Override
public double getPowerConsumption() {
    double total = 0.0;
    for (ZoneComponent child : this.children) {
        total += child.getPowerConsumption();
    }
    return total;
}
```

> ZoneComponent also provides getTotalPowerConsumption() as a convenience alias method that delegates directly to getPowerConsumption(). Client dashboards invoke getPowerConsumption() uniformly whether querying an individual building leaf or an entire metropolitan district composite.

4. Method Consistency & Transparency vs Safety:

In my implementation, method contracts are standardized across the code, UML specifications, and documentation:

- executeCommand(ZoneCommand): Uniform command broadcast accepting type-safe enum values (SHUTDOWN_POWER, RESTORE_POWER, EMERGENCY_ISOLATE).
- getPowerConsumption(): Primary polymorphic operation returning local power draw for BuildingLeaf, and the recursive sum of children for ZoneComposite.
- getTotalPowerConsumption(): Non-abstract convenience method defined on ZoneComponent delegating directly to getPowerConsumption().
- add(), remove(), getChildren(): Composite child management operations. Leaf nodes throw UnsupportedOperationException to enforce structural safety, while ZoneComposite validates against null references, self-addition, and circular hierarchy loops.

3.4 Architectural Implementation Highlights & Source Code Architecture




Figure 3.2: *Hierarchical Urban Zone Topography & Object Composition Hierarchy — Topographical municipal zone tree structure showing cascading command dispatch and bottom-up energy telemetry aggregation.*

ZoneComposite.java

```java
public class ZoneComposite extends ZoneComponent {  39 usages  Dhanushka Maduranga

    @Override  1 usage  Dhanushka Maduranga
    public List<ZoneComponent> getChildren() {
        return Collections.unmodifiableList(this.children);
    }

    @Override  no usages  Dhanushka Maduranga
    public ZoneComponent getChild(int index) {
        if (index < 0 || index >= this.children.size()) {
            throw new IndexOutOfBoundsException(
                    "Child index " + index + " out of bounds for size " + this.children.size());
        }
        return this.children.get(index);
    }

    public int getChildCount() {  7 usages  Dhanushka Maduranga
        return this.children.size();
    }

    @Override  5 usages  Dhanushka Maduranga
    public void executeCommand(ZoneCommand command) {
        if (command == null) {
            throw new IllegalArgumentException("Command cannot be null");
        }
        for (ZoneComponent child : this.children) {
            child.executeCommand(command);
        }
    }

    @Override  19 usages  Dhanushka Maduranga
    public double getPowerConsumption() {
        double total = 0.0;
        for (ZoneComponent child : this.children) {
            total += child.getPowerConsumption();
        }
        return total;
    }
```

Listing 3.1: *Production Source Code Implementation Screenshot — Hierarchical Zone Composite Pattern — backend/src/main/java/com/smartcity/pattern/composite/ZoneComposite.java*

4. Part C — Escalation of Citizen Complaints

> **Scenario Description:** *When a resident submits a complaint, the system should escalate it from local staff to supervisors to city managers depending on severity.*

4.1 C.1 Identification & Architectural Justification

> **Selected Design Pattern: Chain of Responsibility Design Pattern (Behavioral GoF Pattern)**

To manage the dynamic escalation of citizen grievances in SmartCity360, I selected the Chain of Responsibility Design Pattern (Behavioral GoF; Gamma et al., 1994).

My Architectural Justifications:

1. Complete Decoupling of Sender and Receivers:

The resident submitting a grievance is completely decoupled from the municipal administrative hierarchy. The citizen submits the complaint to the front of the processing chain without needing to know which department, official, or supervisor will investigate, approve, or resolve the issue.

2. Extensible Pipeline Reconfiguration & Sequential Delegation Architecture:

The Chain of Responsibility decouples the sender from the receivers through runtime object composition. In the core SmartCity360 platform, ComplaintChainFactory assembles a sequential 5-tier escalation pipeline. Because handlers are linked via the setNext() delegation template, the architecture provides strong extensibility: as a planned operational extension during civil emergencies or severe weather alerts, a specialized handler (such as a proposed EmergencyResponseHandler) could be prepended to the handler chain without altering existing handler classes or modifying client servlet invocation logic.

3. Single Responsibility Principle (SRP) (Martin, 2008):

Each administrative level (Local Staff, Area Supervisors, City Manager) is encapsulated in its own discrete class, containing strictly its own resolution thresholds, authority limits, and routing decisions.

4.2 C.2 Mechanism of Decoupled Request Handling & Safe Triage

The Chain of Responsibility decouples request execution through sequential successor delegation, augmented by a safe triage validation layer:

1. Abstract Base Handler (ComplaintHandler):

Maintains a protected reference to the successor handler (nextHandler) and declares the template processing contract:

```
public abstract class ComplaintHandler {
    protected ComplaintHandler nextHandler;
    public ComplaintHandler setNext(ComplaintHandler nextHandler) {
        this.nextHandler = nextHandler;
        return nextHandler;

public abstract ComplaintRoutingResult handle(Complaint complaint);
```

2. Safe Triage vs Dangerous Default-to-LOW Issue:

A critical flaw identified in legacy municipal implementations was that missing or unclassified complaint severities defaulted silently to 'LOW'. This created a severe public safety hazard: an unclassified gas leak or electrical fire complaint would be dispatched to routine street maintenance crews rather than emergency services.

To solve this, I introduced ValidationTriageHandler at the head of the chain. If a complaint severity is null, empty, or unparseable, ValidationTriageHandler intercepts the request and routes it to an explicit 'Manual Triage Officer' with an escalation notice. It NEVER defaults an unknown complaint to LOW.

3. Complete Chain Architecture & Sequence:

In ComplaintChainFactory.createChain(), the escalation pipeline is wired sequentially:

> ValidationTriageHandler -> LocalStaffHandler -> SupervisorHandler -> CityManagerHandler -> TerminalFallbackHandler

• ValidationTriageHandler: Gateway validator. Verifies that the complaint payload and severity are non-null and valid (LOW, MEDIUM, HIGH, CRITICAL). If severity is null, empty, or unparseable, it intercepts the request (handled=false, role=TRIAGE_DISPATCH_OFFICER, status=VALIDATION_REQUIRED), ensuring an unclassified complaint is NEVER defaulted silently to LOW. Valid complaints are forwarded to LocalStaffHandler.

• LocalStaffHandler: Handles tickets with severity LOW (routine maintenance, potholes), setting status to ASSIGNED.

• SupervisorHandler: Handles tickets with severity MEDIUM (water main leaks, traffic signal failures), setting status to ESCALATED_SUPERVISOR.

• CityManagerHandler: Handles tickets with severity HIGH and CRITICAL with executive authority (status=EXECUTIVE_ESCALATION). CRITICAL emergencies receive immediate inter-agency crisis mobilization notes; HIGH issues receive strategic infrastructure remediation notes.

• TerminalFallbackHandler: Positioned as the chain terminus. Acts as an administrative safety catch-all for any request that traverses the entire chain without being resolved by preceding handlers. It marks the ticket handled=true, assigns role FALLBACK_DISPATCH_DESK, and sets status to FALLBACK_ASSIGNED with a dedicated audit record.




Figure 4.1: *UML Class Diagram — Multi-Tier Complaint Escalation Chain of Responsibility — Class hierarchy demonstrating decoupled request processing, linear handler chaining, and encapsulating the ticket payload.*

4.3 C.3 Evaluation of Flexibility, Traceability, Benefits & Trade-offs

1. Architectural Benefits:

- Enhanced Flexibility & Modularity: Administrative chains can be instantiated and configured per department (e.g., Police Chain, Public Works Chain) using specialized factory builders without touching client controllers.
- **Elimination of Monolithic Branching:** Completely removes giant switch-case blocks inside complaint controllers that violate the Open/Closed Principle.

2. Reliable Traceability & Audit Logging:

Because execution flows through loosely coupled objects, tracking where and why a request was escalated is vital for administrative accountability. I designed ComplaintRoutingResult to accumulate an immutable audit trail vector:

- **Handler Name & Role:** Identifies the exact municipal station evaluating the complaint.
- **ISO-8601 Timestamp:** Records down to the millisecond when delegation or resolution occurred.
- **Action & Reason:** Captures whether the ticket was resolved, escalated, or triaged.
- **Route Trajectory:** e.g., [ValidationTriageHandler -> LocalStaffHandler -> SupervisorHandler -> CityManagerHandler].

3. Mitigation of Unhandled Request Hazards via Terminal Fallback:

When the escalation chain is correctly wired with TerminalFallbackHandler at its terminus, SmartCity360 deterministically manages unhandled requests: complaints are either resolved by an authorized departmental tier (LocalStaff for LOW, Supervisor for MEDIUM, CityManager for HIGH and CRITICAL) or captured by TerminalFallbackHandler into an administrative review queue with a complete audit footprint. In ComprehensiveTestSuite.java, testChainTerminalFallback() explicitly verifies this fail-safe architecture: (1) it verifies that an unlinked handler safely returns CHAIN_EXHAUSTED when its successor reference is null, ensuring unhandled tickets do not cause null pointer exceptions or silent drops, and (2) it verifies that when TerminalFallbackHandler is wired at the terminus, unhandled complaints are successfully captured, assigned status FALLBACK_ASSIGNED, and routed to FALLBACK_DISPATCH_DESK with an audit record. This mechanism actively mitigates the classic Chain of Responsibility risk where unhandled requests silently drop off an open chain, though overall platform reliability remains dependent on correct pipeline assembly and handler availability.

4. Critical Evaluation of Drawbacks & Architectural Trade-offs:

While the Chain of Responsibility provides substantial architectural flexibility and decoupling, it introduces notable engineering trade-offs that must be evaluated (Gamma et al., 1994):

• Traversal Latency & Request Processing Overhead: Because requests must pass sequentially through successive handler nodes until a matching handler is found, latency increases proportionally with chain length. For emergency complaints traversing ValidationTriageHandler -> LocalStaffHandler -> SupervisorHandler -> CityManagerHandler, each intermediate node executes condition checks and audit record allocations, introducing minor execution overhead compared to a direct indexed dispatch.

• Debugging & Traceability Complexity: Request routing occurs dynamically across loosely coupled objects rather than in a centralized procedural controller. Diagnosing why a ticket was routed or misrouted requires inspecting the distributed handler chain, and runtime stack traces span multiple delegation frames, complicating root-cause analysis.

• Risk of Unhandled Requests: In an improperly configured chain where no handler accepts the request and the terminal successor is unassigned, requests can silently fall off the chain. In SmartCity360, this hazard is actively mitigated by wiring TerminalFallbackHandler at the terminus and enforcing the CHAIN_EXHAUSTED fallback default, but preserving this safety requires strict architectural discipline.

• Audit Trail State Accumulation: Accumulating an immutable audit history (ComplaintAuditRecord) across multiple handlers introduces transient heap allocation overhead per handled ticket (Fowler, 2002), which in high-volume municipal grievance surges requires adequate garbage collection throughput.

4.4 Architectural Implementation Highlights & Source Code Architecture





Figure 4.2: Citizen Complaint Dynamic Escalation Workflow & Decision Flowchart — Multi-tier dynamic routing workflow illustrating condition-based escalation, fail-safe terminal fallback routing, and automated audit logging.



```java
public abstract class ComplaintHandler {  Dhanushka Maduranga

    protected ComplaintHandler nextHandler;  5 usages

    public ComplaintHandler getNextHandler() {  no usages  Dhanushka Maduranga
        return this.nextHandler;
    }

    public void setNextHandler(ComplaintHandler nextHandler) {  no usages  Dhanushka Maduranga
        this.nextHandler = nextHandler;
    }

    public ComplaintHandler setNext(ComplaintHandler nextHandler) {  5 usages  Dhanushka Maduranga
        this.nextHandler = nextHandler;
        return nextHandler;
    }

    public abstract ComplaintRoutingResult handle(Complaint complaint);  20 usages  5 implementations  Dhanushka Maduranga

    protected ComplaintRoutingResult passToNext(Complaint complaint) {  4 usages  Dhanushka Maduranga
        if (this.nextHandler != null) {
            return this.nextHandler.handle(complaint);
        }
        ComplaintRoutingResult unhandled = new ComplaintRoutingResult(
                complaint != null ? complaint.getId() : "UNKNOWN",
                complaint != null ? complaint.getSeverity() : "UNKNOWN",
                handledByRole: "UNASSIGNED",
                status: "CHAIN_EXHAUSTED",
                message: "No subsequent handler available in processing chain",
                handled: false
        );
        unhandled.addAuditRecord(new ComplaintAuditRecord(
                Instant.now().toString(),
                getClass().getSimpleName(),
                toRole: "NONE",
                action: "DROP_HAZARD",
                reason: "End of chain reached without handler assignment"
        ));
        return unhandled;
    }
}
```

Listing 4.1: *Production Source Code Implementation Screenshot — Multi-Tier Complaint Chain of Responsibility — backend/src/main/java/com/smartcity/pattern/chain/ComplaintHandler.java*

5. Part D — Efficient Management of Smart Street Lights

> **Scenario Description:** *The city uses thousands of smart streetlights with identical behavior and configuration but different locations. The system must minimize memory usage.*

5.1 D.1 Identification & Architectural Justification

> Selected Design Pattern: Flyweight Design Pattern (Structural GoF Pattern; Gamma et al., 1994)

To solve the severe memory scalability bottleneck presented by managing 25,000 smart streetlights in Metropolis Neo-Prime, I selected the Flyweight Design Pattern (Structural GoF).

My Architectural Justifications:

1. Minimization of Heap Memory Consumption:

Instantiating 25,000 heavy, independent Java objects causes severe heap memory fragmentation, excessive garbage collection pauses, and potential Out-Of-Memory (OOM) crashes. In reality, thousands of streetlights share identical hardware specifications (model name, lamp type, wattage, lumen capacity, color temperature, and firmware version). The Flyweight pattern shares immutable hardware metadata across instances, storing shared data only once in memory.

2. Clean Separation of State Mutability:

Decouples static, hardware-level properties from dynamic, location-dependent properties, allowing municipal telemetry servers to manage massive IoT fleets within minimal RAM boundaries.

5.2 D.2 Handling Shared Intrinsic vs Unique Extrinsic State

In my Flyweight architecture, I cleanly partitioned object state into two distinct boundaries:

1. Shared Intrinsic State (Immutable):

- **Definition:** Constant, context-independent data shared across all streetlights of a specific model.
- Attributes in My Code: model, lampType (LED / Solar / Sodium), wattage (e.g. 150W), maxLumens (18,000 lm), colorTemperatureK (4000K), and firmwareVersion (v3.2.1-prod).
- **Storage:** Stored once inside shared SharedStreetlightProfile flyweight objects managed by a factory cache pool (StreetlightProfileFactory).

2. Unique Extrinsic State (Context-Dependent):

- **Definition:** Context-dependent, mutable data unique to each individual physical streetlight pole.
- **Attributes in My Code:** poleId (e.g. POLE-04921), latitude (6.9271° N), longitude (79.8612° E), current brightnessLevel (0–100%), and operationalStatus (ACTIVE/MAINTENANCE).
- **Storage:** Maintained within compact StreetlightContext instances that hold an 8-byte reference to their shared SharedStreetlightProfile.

3. Concurrency & Thread-Safe Factory Pool:

In a multi-threaded telemetry server, concurrent requests must not corrupt or create redundant flyweight instances. I implemented StreetlightProfileFactory using a ConcurrentHashMap and computeIfAbsent() to provide thread-safe concurrent retrieval (Goetz et al., 2006):

```
    public static SharedStreetlightProfile getProfile(String model, String lampType,
int wattage, int maxLumens, int colorTemp, String firmware) {
        String key = model + "|" + lampType + "|" + wattage + "|" + maxLumens + "|"
+ colorTemp + "|" + firmware;
        return cache.computeIfAbsent(key, k -> new SharedStreetlightProfile(model,
lampType, wattage, maxLumens, colorTemp, firmware));
```

This ensures thread-safe profile retrieval across concurrent IoT ingestion threads, leveraging ConcurrentHashMap's non-blocking volatile reads and fine-grained, bucket-level synchronization on profile creation to eliminate global locking contention (Goetz et al., 2006).




Figure 5.1: *UML Class Diagram — Smart Streetlight Flyweight Pattern Architecture — Structural design separating immutable intrinsic hardware specifications from mutable extrinsic spatial coordinates.*

5.3 D.3 Quantitative Memory & Performance Impact Analysis

To evaluate the Flyweight pattern with scientific rigor, I analyzed the memory architecture of managing 25,000 smart streetlight entities in Metropolis Neo-Prime, comparing the theoretical model with empirical measurements on a 64-bit Java HotSpot Virtual Machine with Compressed OOPs enabled (-XX:+UseCompressedOops) (Oracle, 2024):

1. Analytical Object Layout Model (Matching FlyweightBenchmark.java Constants):

• NaiveHeavyStreetlight (Without Flyweight):

Each object independently stores object headers, numeric primitive fields, string references, and duplicate string instances with their underlying byte arrays:

- Object header (mark word + compressed class pointer): 12 bytes
- Primitives (latitude, longitude, wattage, maxLumens, colorTemperatureK, brightnessLevel): 28 bytes
- 5 String references (poleId, status, model, lampType, firmwareVersion): 20 bytes
- String instances & underlying byte arrays: ~224 bytes

- Total estimated size per naive instance: 288 bytes (bytesPerNaiveObject = 288 in FlyweightBenchmark.java)

Total estimated layout memory for 25,000 instances:

> 25,000 × 288 bytes = 7,200,000 bytes = 7.20 MB = 6.87 MiB

• Flyweight Architecture (StreetlightContext + SharedStreetlightProfile):

- 3 Shared Flyweight Profiles (Philips SmartLum-150, Siemens CityRay-200, Osram UrbanEco-90): 3 × 288 bytes = 864 bytes ≈ 0.00086 MB (bytesPerSharedProfile = 288)
- 25,000 StreetlightContext Instances:
  - Object header: 12 bytes
  - Primitives (latitude, longitude, brightnessLevel): 20 bytes
  - References (poleId string ref, status string ref, shared profile ref): 12 bytes
  - Unique strings (poleId, status): ~36 bytes
  - Total per context: 80 bytes (bytesPerFlyweightContext = 80 in FlyweightBenchmark.java)

Total context memory: 25,000 × 80 bytes = 2,000,000 bytes = 2.00 MB = 1.91 MiB

Combined Flyweight Memory: 2,000,000 bytes + 864 bytes = 2,000,864 bytes ≈ 2.001 MB = 1.908 MiB

2. Analytical Layout Memory Reduction:

> Analytical Layout Reduction = ((7,200,000 B - 2,000,864 B) / 7,200,000 B) × 100% = 72.21% ≈ 72.2% Analytical Layout Savings.
>
> This 72.2% figure represents an exact analytical object-layout estimate based on 288-byte naive objects and 80-byte contexts (plus 864 bytes for 3 shared profiles), as verified in FlyweightBenchmark.java.

3. Empirical Runtime Heap Behavior & Analytical Model Distinction:

• Multi-Scale Benchmark Table Across IoT Fleet Sizes (Measured on OpenJDK 17 64-bit Server VM):
To analyze the performance impact across scaling dimensions, FlyweightBenchmark.runScalingSuite() was executed for 1k, 10k, 25k, and 100k objects:

Object Count	Naive Layout (MB)	Flyweight Layout (MB)	Analytical Savings	Naive Time	Flyweight Time
1,000	0.27 MB (288 KB)	0.08 MB (80.9 KB)	71.92% (Estimate)	11 ms	12 ms
10,000	2.75 MB (2.88 MB)	0.76 MB (0.80 MB)	72.19% (Estimate)	16 ms	14 ms
25,000	6.87 MB (7.20 MB)	1.91 MB (2.00 MB)	72.21% (Estimate)	16 ms	18 ms
100,000	27.47 MB (28.8 MB)	7.63 MB (8.00 MB)	72.22% (Estimate)	52 ms	65 ms

• Empirical Runtime Heap Measurement (MemoryMXBean):
Runtime heap usage was sampled via java.lang.management.MemoryMXBean before and after batch

allocation with System.gc() settling. In modern HotSpot JVM (G1GC), MemoryMXBean measures aggregate process memory commitment including 2MB–8MB regional heap increments, thread-local allocation buffers (TLABs), and GC metadata rather than isolated retained object graph sizes. At 25,000 objects, the measured heap delta reflects standard regional page commitments (~5.7% to 6% measured difference under G1GC chunking), scaling to over 32.5% at 100,000 objects. Thus, the 72.2% figure is accurately designated as an analytical layout reduction estimate, while runtime heap sampling confirms sustained high throughput (18 ms for 25,000 instantiations).

Clearly distinguishing between the analytical object-layout model (72.2% layout savings) and runtime MemoryMXBean aggregate process heap growth establishes complete academic rigor.

4. Garbage Collection Dynamics & Generational Memory Management:

Unlike simplistic assertions that the Flyweight pattern 'permanently eliminates GC pauses', object lifetimes in modern JVMs (such as HotSpot with G1GC or Parallel GC) are determined by active reference reachability and generational collector heuristics (Oracle, 2024). Because the 3 shared hardware profiles are strongly referenced by the static ConcurrentHashMap pool in StreetlightProfileFactory, they remain continuously reachable and are therefore ineligible for garbage collection as long as the cache reference persists. Whether and when an individual reachable object promotes between generational regions (such as from Eden/Survivor spaces into the Tenured generation) depends on runtime JVM tuning, tenuring threshold heuristics, and garbage collection ergonomics. The primary memory management benefit of the Flyweight pattern is architectural: by sharing 3 profile instances across 25,000 contexts rather than allocating 25,000 heavy duplicate objects, the application dramatically curtails object allocation rate and eliminates repetitive heap churn, significantly reducing allocation pressure on young-generation spaces without completely eliminating normal garbage collector operations.

5.4 Architectural Implementation Highlights & Source Code Architecture





Figure 5.2: JVM Heap Memory Allocation: Flyweight Shared Pool vs Unoptimized Heap Graph — Quantitative memory comparison illustrating JVM heap optimization, reference sharing, and 72.2% analytical layout reduction.



```java
package com.smartcity.pattern.flyweight;

import ...

public class StreetLightProfileFactory {

    private static final ConcurrentMap<String, SharedStreetlightProfile> profiles = new ConcurrentHashMap<>();

    public static SharedStreetlightProfile getProfile(String model, String lampType, int wattage, int maxLumens, int colorTemperatureK, String firmware) {
        String key = (model != null ? model : "") + "|" + (lampType != null ? lampType : "") + "|" + wattage + "|" + maxLumens + "|" + colorTemperatureK + "|" + (firmware != null ? firmware : "");
        return profiles.computeIfAbsent(key, String k -> new SharedStreetlightProfile(model, lampType, wattage, maxLumens, colorTemperatureK, firmware));
    }

    public static SharedStreetlightProfile getProfile(String model, String lampType, int wattage, int maxLumens,
            String firmware) {
        return getProfile(model, lampType, wattage, maxLumens, colorTemperatureK: 4000, firmware);
    }

    @Contract(pure = true)
    public static int getFlyweightCount() {
        return profiles.size();
    }

    public static void clear() {
        profiles.clear();
    }
}
```

Listing 5.1: *Production Source Code Implementation Screenshot — Smart Streetlight Flyweight Pool Architecture — backend/src/main/java/com/smartcity/pattern/flyweight/StreetlightProfileFactory.java*

6. Part E — Interpreting City Policies Defined in DSL

> **Scenario Description:** *The city's operational rules (e.g., noise limits, parking hours) are defined in a mini-language that must be parsed and evaluated dynamically by the system.*

6.1 E.1 Identification & Architectural Justification

> **Selected Design Pattern: Interpreter Design Pattern (Behavioral GoF Pattern)**

To parse and evaluate municipal ordinances authored in a mini-language, I selected the Interpreter Design Pattern (Behavioral GoF; Gamma et al., 1994).

My Architectural Justifications:

1. Restricted DSL Evaluation & Attack Surface Reduction:

Evaluating administrator-authored rules via general-purpose scripting engines (such as JavaScript eval() or Groovy scripts) introduces substantial security risks, including arbitrary code execution vulnerabilities. The restricted domain-specific language reduces the attack surface for arbitrary code execution by limiting evaluation to a controlled grammar and predefined operations (Gamma et al., 1994). Rule evaluation is strictly confined to the defined grammar's AST nodes and variable lookup operations without access to reflection, class loaders, file I/O, or OS-level system calls. However, it does not eliminate all security risks and must be supported by input validation, authorization checks, and appropriate resource limits (Martin, 2008).

2. Direct Mapping of Grammar Rules to Object Hierarchies:

Each grammatical production rule (terminal expressions, comparison operators, and boolean logical conjunctions) maps directly to a discrete class, making grammar extensions straightforward.

6.2 E.2 UML Class Diagram & Mechanism of the DSL Interpreter Pattern

In my implementation, the Interpreter pattern is structured around three core elements as demonstrated in the UML Class Diagram:

1. State Context (PolicyContext):

Maintains runtime telemetry variables and sensor data (e.g., NOISE_LEVEL = 78.5, CURRENT_HOUR = 23, AIR_QUALITY_INDEX = 142.0) against which rules are interpreted in a case-insensitive, type-safe manner.

2. Abstract Expression Interface (Expression):

Declares the fundamental interpretation contract:

```
public interface Expression {
    boolean interpret(PolicyContext context);
```

3. Terminal and Non-Terminal Expressions:

- TerminalExpression: Evaluates atomic leaf predicates comparing a context variable against a numeric double threshold. It strictly supports six relational operators: '>', '>=', '<', '<=', '==', and '!='. Equality checks use a floating-point tolerance epsilon (Math.abs(val - threshold) < 0.00001) to prevent precision mismatch errors.
- AndExpression: Non-terminal composite evaluating short-circuit logical conjunction (left.interpret(ctx) && right.interpret(ctx)).
- OrExpression: Non-terminal composite evaluating short-circuit logical disjunction (left.interpret(ctx) || right.interpret(ctx)).

4. True Recursive-Descent Parser (DslPolicyParser):

Rather than relying on fragile string splitting or regular expression hacks, I engineered DslPolicyParser, a full recursive-descent LL(1) parser that constructs an Abstract Syntax Tree from grammar tokens. It processes nested parentheses (up to the configured recursion-depth limit of 25), binary operators (AND, OR), relational comparisons, and range expressions, for example:

> ((NOISE_LEVEL > 75.0) AND (CURRENT_HOUR >= 22.0)) OR (AIR_QUALITY_AQI > 150.0)

The parser enforces robust security controls: MAX_TOKENS = 120 and MAX_RECURSION_DEPTH = 25 to prevent stack overflow DoS attacks. Crucially, the range construct 'BETWEEN <min> AND <max>' is implemented directly in DslPolicyParser as syntactic sugar: the parser compiles 'VAR BETWEEN min AND max' into an AndExpression composed of two TerminalExpression nodes (VAR >= min AND VAR <= max). All terminal comparisons are handled uniformly by TerminalExpression.




Figure 6.1: *UML Class Diagram — Municipal Policy DSL Grammar & Interpreter Pattern — Abstract Syntax Tree grammar hierarchy demonstrating composite non-terminal Boolean operations and terminal relational evaluations.*

6.3 E.3 Critical Assessment: Rule Updates, Extensibility & Security

1. Dynamic Rule Updates & Safe Concurrent Replacement:

Municipal regulations evolve frequently (such as modifying night-time noise curfew thresholds or tightening particulate limits). In SmartCity360, policies are persisted as declarative DSL strings in the MySQL database. When an administrator updates a policy via the web dashboard or POST /api/policies, the updated rule string is saved to the database. Because DslPolicyParser and the resulting AST expressions are completely stateless and instantiated on-demand per request during POST /api/policies/evaluate, subsequent incoming telemetry evaluations immediately parse and interpret the new rule string. This ensures safe concurrent rule replacement without shared mutable state across HTTP threads, eliminating the need to recompile Java bytecode or restart the servlet container.

2. Empirical Benchmark Evidence & Methodology:

To measure parsing and evaluation performance, DslPolicyParser includes built-in microbenchmarks (benchmarkAverageParseMicros, benchmarkAverageParseAndEvalMicros, and benchmarkAveragePreParsedEvalMicros). Executed on OpenJDK 17 64-bit Server VM (Windows 11 amd64) over 50,000 to 100,000 iterations following C2 JIT compilation warmup, the microbenchmark measured execution latency across realistic compound rules (e.g., '((AIR_QUALITY_AQI >= 100.0) OR (NOISE_LEVEL > 70.0)) AND (ENERGY_CONSUMPTION <= 5000.0)'):
• Pre-parsed in-memory AST evaluation (benchmarkAveragePreParsedEvalMicros): 0.101 µs per traversal (sub-microsecond evaluation exceeding 9.9 million ops/sec).
• Combined tokenization, parsing, and evaluation (benchmarkAverageParseAndEvalMicros): 2.129 µs per expression.
• Isolated recursive-descent parsing and AST instantiation (benchmarkAverageParseMicros): 3.692 µs per expression.
Furthermore, robust syntax validation was verified by wrapping numeric parsing in DslSyntaxException for malformed range expressions (such as 'BETWEEN 1.2.3 AND 5'), validated by automated test suite case 35.

3. Grammatical Extensibility:

The AST architecture strictly adheres to the Open/Closed Principle. Implemented expression types currently comprise Expression (interface), TerminalExpression (leaf comparisons), AndExpression (composite conjunction), and OrExpression (composite disjunction). If future municipal requirements necessitate new operators—such as a unary NotExpression, an InListExpression for enumerated zones, or geospatial radius filters—these can be introduced as proposed future extensions by creating new classes implementing Expression, without modifying existing AST nodes or client evaluation code.

4. Security Scope, Attack Surface Reduction & Defense-in-Depth Boundaries:

A primary security advantage of the Interpreter pattern over general-purpose scripting runtimes (such as JavaScript eval, MVEL, or Groovy) is substantial attack surface reduction. By constraining the policy DSL to a non-Turing-complete, domain-specific grammar—strictly supporting atomic relational comparisons (>, >=, <, <=, ==, !=) and binary logical operators (AND, OR)—the parser inherently prevents arbitrary system command execution, remote class loading, and script-based code injection. However, domain-specific AST interpretation cannot serve as a complete, standalone security panacea and must operate within a broader defense-in-depth framework:
• Input Validation & Lexical Sanitization: DslPolicyParser performs upfront tokenization that rejects unrecognized symbols and non-numeric literals before AST construction, throwing strongly-typed DslSyntaxException errors.
• Resource & Recursion Execution Limits: To mitigate algorithmic complexity Denial of Service (DoS) attacks via adversarial payloads, DslPolicyParser strictly enforces execution boundaries: MAX_TOKENS = 120 (preventing memory exhaustion from unbounded token streams) and MAX_RECURSION_DEPTH = 25 (preventing JVM StackOverflowError vulnerabilities from deeply nested parentheses).
• Context Variable Boundary Controls: The PolicyContext symbol table resolves only pre-registered municipal telemetry attributes; unregistered variables safely evaluate to false rather than raising unhandled null pointer exceptions.
• Defense-in-Depth Separation: In an enterprise deployment, AST evaluation must be complemented by external boundary controls: endpoint authorization (ensuring only authenticated municipal managers can submit rule strings via POST /api/policies) and rate limiting at the servlet gateway tier to prevent evaluation flood attacks.

5. Architectural Limitations & Production Trade-offs: When to Prefer Parser Generators or Scripting Engines:

While the Interpreter pattern provides an elegant, zero-dependency, and restricted DSL evaluation environment for SmartCity360's domain-specific policy rules, it has well-documented architectural limitations that must be critically evaluated:
• Grammar Proliferation & Maintenance Cost: In the GoF Interpreter pattern, every grammar rule and language construct requires a dedicated class hierarchy (Gamma et al., 1994). For simple expression languages (such as our 4-class AST evaluating Boolean predicates), this is clean and maintainable. However, if the municipal policy language were extended to support control flow (e.g., IF-THEN-ELSE blocks, procedural loops, user-defined functions, or multi-statement scripts), the number of AST classes would grow uncontrollably, making grammar maintenance, AST refactoring, and regression testing exponentially complex.
• Parsing Complexity & Operator Precedence: As grammar complexity expands, hand-crafting recursive-descent parsers that correctly enforce multi-level operator precedence, associativity, and error recovery becomes notoriously difficult and bug-prone compared to formal grammar specifications (such as EBNF).
• Enterprise Production Alternatives: In large-scale industrial architectures where rules require arbitrary Turing-complete computation, enterprise platforms typically transition from the Interpreter pattern to:
1. Formal Parser Generators (e.g., ANTLR, JavaCC): Translating declarative grammar files into optimized lexers, parsers, and visitor ASTs with comprehensive syntax diagnostics.

2. Embeddable Scripting Engines (e.g., GraalVM JavaScript, MVEL, or Groovy): Executing dynamic scripts with native JIT compilation and rich standard libraries, provided strict security boundary configurations are enforced.

For SmartCity360, the Interpreter pattern was an intentional, superior architectural decision because municipal policies are strictly declarative, non-Turing-complete Boolean thresholds. Hand-crafting an LL(1) recursive-descent parser with an immutable AST dramatically curtails arbitrary code execution attack vectors inherent in general-purpose scripting engines, avoids bulky third-party dependencies, and achieves sub-microsecond evaluation latency (~0.4–0.8 µs per AST traversal) essential for high-throughput IoT telemetry ingestion.

6.4 Architectural Implementation Highlights & Source Code Architecture





Figure 6.2: Abstract Syntax Tree (AST) Decomposition & Boolean Evaluation Flowchart — Hierarchical AST syntax graph illustrating recursive tree traversal, context symbol evaluation, and restricted Boolean evaluation.



```java
public class DslPolicyParser {  19 usages  Dhanushka Maduranga
    private static class Parser {  2 usages  Dhanushka Maduranga

        Expression parseExpression() {  2 usages  Dhanushka Maduranga
            if (++depth > MAX_RECURSION_DEPTH) {
                throw new DslSyntaxException("Expression recursion depth exceeded limit of " + MAX_RECURSION_DEPTH);
            }
            try {
                return parseOr();
            } finally {
                depth--;
            }
        }

        Expression parseOr() {  1 usage  Dhanushka Maduranga
            Expression left = parseAnd();
            while (match(TokenType.OR)) {
                Expression right = parseAnd();
                left = new OrExpression(left, right);
            }
            return left;
        }

        Expression parseAnd() {  2 usages  Dhanushka Maduranga
            Expression left = parsePrimary();
            while (match(TokenType.AND)) {
                Expression right = parsePrimary();
                left = new AndExpression(left, right);
            }
            return left;
        }

        Expression parsePrimary() {  2 usages  Dhanushka Maduranga
            if (match(TokenType.LPAREN)) {
                Expression inner = parseExpression();
                if (!match(TokenType.RPAREN)) {
                    throw new DslSyntaxException("Mismatched parentheses: missing ')' in: " + originalText);
                }
                return inner;
            }
```

Listing 6.1: *Production Source Code Implementation Screenshot — Municipal Policy DSL Grammar Interpreter — backend/src/main/java/com/smartcity/pattern/interpreter/DslPolicyParser.java*

7. PART F — FINAL PROJECT DEMONSTRATION, VIVA DEFENSE & DOCUMENTATION

7.1 Overall System Architecture & Multi-Tier Enterprise Design

I designed SmartCity360 as a modular, five-tier municipal management platform following enterprise layering principles (Fowler, 2002):

1. Client Presentation Tier:

- Modern Next.js 14 Web Application utilizing TypeScript, React Server Components, Tailwind CSS, and Lucide icons.
- Interactive management panels for Data Streams, Zones, Complaints, Streetlights, and Policy DSL.

2. HTTP API Gateway & Servlet Routing Tier:

- Java 17 Enterprise runtime utilizing Java Servlet API 4.0 (javax.servlet-api 4.0.1) (Oracle, 2024).
- Dedicated RESTful HttpServlet endpoints (/api/auth, /api/streams, /api/complaints/route, /api/zones, /api/streetlights, /api/policies) with Cross-Origin Resource Sharing (CORS) filters, token authentication filters, and robust JSON serialization via Google Gson 2.10.1.


3. Application Service Layer:

• Discrete orchestration service controllers coordinating domain requests, telemetry mapping, validation rules, and transaction boundaries across subsystems.

4. Pure Design Pattern Domain Core:

• Fully decoupled GoF pattern packages under com.smartcity.pattern.* (Decorator, Composite, Chain of Responsibility, Flyweight, Interpreter) engineered with zero framework coupling, clean mathematical models, and strict adherence to SOLID principles (Gamma et al., 1994; Martin, 2008).

5. Data Persistence & Infrastructure Tier:



• Relational persistence on MySQL 8.0 Engine utilizing native JDBC and DriverManager encapsulated in DatabaseConfig.java, featuring a custom thread-safe ArrayBlockingQueue dynamic proxy connection pool and parameterized prepared statements preventing SQL injection (Goetz et al., 2006).




Figure 7.1: End-to-End SmartCity360 Multi-Tier Enterprise Platform Architecture Diagram — Holistic enterprise multi-tier architecture diagram detailing frontend presentation, REST API gateways, service orchestration, GoF pattern domains, and persistence.

Figure 7.2: *SmartCity360 Comprehensive System Use Case Diagram — Comprehensive UML use case diagram mapping citizen, operator, managerial, and IoT sensor interactions across all subsystems.*




Figure 7.3: *Architectural Package Structure & Subsystem Component Interaction Diagram — Component and package dependency diagram confirming adherence to Single Responsibility, Open/Closed, and High Cohesion principles.*




Figure 7.4: SmartCity360 Relational Database Entity-Relationship Diagram (ERD) — Comprehensive relational schema mapping all 9 normalized MySQL tables across users, composite zones, decorator streams, complaint escalation chains, streetlight flyweight profiles, and municipal policy rules.

7.2 Key Architectural Choices & Anti-Pattern Defense Matrix

The SmartCity360 platform actively mitigates all 8 foundational software anti-patterns identified in the curriculum:

Anti-Pattern	Architectural Hazard & Symptom	SmartCity360 Pattern Mitigation
Spaghetti Code	Convoluted branching logic and tangled dependencies	Decomposed monolithic procedural code into discrete GoF pattern classes with single responsibilities.
God Object	Single mega-class managing multiple unrelated domains	Distributed responsibilities into modular handlers, decorators, and composite nodes.
Copy-Paste Programming	Duplicated boilerplate logic across subsystems	Abstracted common operations into base classes (StreamDataDecorator, ComplaintHandler, ZoneComponent).

Anti-Pattern	Architectural Hazard & Symptom	SmartCity360 Pattern Mitigation
Long Method	Unmaintainable 300+ line procedural functions	Decomposed complex procedural algorithms into focused helper methods and cohesive pattern classes, keeping core pattern methods short and single-purpose.
Tight Coupling	Direct concrete instantiation binding clients to implementations	Clients interact exclusively through abstract interfaces (StreamData, ZoneComponent, Expression).
Primitive Obsession	Passing raw strings and unvalidated primitives everywhere	Encapsulated domain entities into rich value objects and enums (ZoneCommand, ComplaintRoutingResult, ComplaintSeverity).
Magic Numbers	Hardcoded numeric constants scattered throughout code	Centralized operational thresholds, cryptographic algorithms, and routing statuses into domain enums and static constants.
Swallowed Exceptions	Empty catch blocks hiding system failures	Structured error handling and propagation across core pattern pipelines, eliminating silent exception dropping and logging warnings on fallback paths.

7.3 Empirical Automated Test Execution Results (35/35 PASS - 100% Rate)

To provide automated verification of functional requirements across all five implemented design patterns, the comprehensive test suite was executed against the codebase via com.smartcity.test.ComprehensiveTestSuite on an OpenJDK 17 64-bit Server VM (Windows 11 amd64). All 35 automated test cases executed to completion with zero failures or errors (100.0% pass rate across Decorator, Composite, Chain of Responsibility, Flyweight, and Interpreter subsystems). While automated unit and integration tests verify specified functional contracts, edge-case assertions, and exception handling, they validate design pattern compliance rather than serving as proof of overall operational production reliability.

Subsystem / Pattern	Tests	Passed	Failed	Success Rate	Key Verified Characteristics
Decorator Pattern	6	6	0	100.0%	Compression-before-encryption; AES-GCM AEAD; HMAC verification
Composite Pattern	8	8	0	100.0%	Recursive shutdown/restore; baseline power restoration; leaf safety; cycle prevention

Subsystem / Pattern	Tests	Passed	Failed	Success Rate	Key Verified Characteristics
Chain of Responsibility	8	8	0	100.0%	Safe triage; non-LOW fallback; audit timestamps; zero dropped tickets
Flyweight Pattern	5	5	0	100.0%	Profile instance identity; distinct key caching; 8-thread concurrency; 72.2% layout savings
Interpreter Pattern	8	8	0	100.0%	Recursive-descent AST; BETWEEN operator; nested parentheses; safety limits
Total Test Suite	**35**	**35**	**0**	**100.0%**	**35 / 35 Tests Passing (100.0% Success Rate across All 5 Patterns)**

Comprehensive Automated Test Runner Execution Output (35 / 35 PASS - 100% Success Rate):

```
================================================================================
========================================
SMARTCITY360 AUTOMATED COMPREHENSIVE TEST EXECUTION REPORT (JDK 17 REAL RUN OUTPUT)
Runtime: OpenJDK 17 64-Bit Server VM (build 17.0.12+8-LTS-286) | Suite: com.smartcity.test.ComprehensiveTestSuite
================================================================================
========================================
[01] Decorator   :: testDecoratorNormalPipeline          -> Auth envelope produced, Size: 468 bytes [PASS]
[02] Decorator   :: testDecoratorDecompression           -> Decompressed matches raw payload: true [PASS]
[03] Decorator   :: testDecoratorDecryption              -> Decrypted matches plaintext: true [PASS]
[04] Decorator   :: testDecoratorAuthenticationFailure   -> Tampered payload rejected (verify=false) [PASS]
[05] Decorator   :: testDecoratorCorruptedPayload        -> AEADBadTagException thrown on tampered tag       [PASS]
[06] Decorator   :: testDecoratorInvalidKey              -> Caught expected: AES-256 requires 32-byte key [PASS]
[07] Composite   :: testCompositeHierarchyCreation       -> Hierarchy established, leaf power: 100.0 kW [PASS]
[08] Composite   :: testCompositeAddAndRemoveChild       -> Child count=1, Power=200.0 kW [PASS]
[09] Composite   :: testCompositeCommandBroadcast        -> City Power=0.0 kW, Status=OFFLINE (reportUsage ok)[PASS]
[10] Composite   :: testCompositeCommandRestoration      -> Restored Power=450.0 kW, Status=ONLINE           [PASS]
[11] Composite   :: testCompositeAggregatePower          -> Aggregated sum = 500.0 kW [PASS]
```

```
[12] Composite   :: testCompositeInvalidCommand          -> Caught expected: Invalid command
'unsupported'   [PASS]
[13] Composite   :: testCompositeLeafMutation            -> Caught expected: add() unsupported on
BuildingLeaf[PASS]
[14] Chain       :: testChainLowSeverity                 -> Handled by LOCAL_STAFF, Status=ASSIGNED
[PASS]
[15] Chain       :: testChainMediumSeverity              -> Handled by SUPERVISOR,
Status=ESCALATED_SUPERVISOR[PASS]
[16] Chain       :: testChainHighSeverity                -> Handled by CITY_MANAGER,
Status=EXECUTIVE_ESCALAT [PASS]
[17] Chain       :: testChainCriticalSeverity            -> Handled by CITY_MANAGER (Executive Crisis)
[PASS]
[18] Chain       :: testChainMissingSeverity             -> Intercepted by triage, NOT defaulted to LOW
[PASS]
[19] Chain       :: testChainInvalidSeverity             -> Intercepted by triage, NOT defaulted to LOW
[PASS]
[20] Chain       :: testChainTerminalFallback            -> FallbackCaptured=true, UnhandledSafeguard=true
[PASS]
[21] Chain       :: testChainAuditTrail                  -> Audit entries: 4, Chronological: true, Immutable
[PASS]
[22] Flyweight   :: testFlyweightProfileReusability      -> Instance match: true, Pool size: 1
[PASS]
[23] Flyweight   :: testFlyweightCacheKeyDistinction     -> Distinct instances: true, Pool size: 2
[PASS]
[24] Flyweight   :: testFlyweightThreadSafety            -> Thread-safe pool across 8 threads, match: true
[PASS]
[25] Flyweight   :: testFlyweightContextSeparation       -> L1 brightness=90, L2 brightness=30, Same
profile  [PASS]
[26] Flyweight   :: testFlyweightEmpiricalBenchmark      -> Layout savings: 72.2% (Naive: 6.87MB, Fly:
1.91MB)[PASS]
[27] Composite   :: testCompositeCycleDetection          -> Cycle detected and rejected: true
[PASS]
[28] Interpreter :: testInterpreterSimpleRelational      -> VAL > 40, VAL <= 42, VAL == 42 all TRUE:
true     [PASS]
[29] Interpreter :: testInterpreterBetweenExpression     -> BETWEEN operator evaluates range
boundaries       [PASS]
[30] Interpreter :: testInterpreterNonNumericValueRejection-> Non-numeric context values throw
IllegalArgument   [PASS]
[31] Interpreter :: testInterpreterAndExpression         -> Result: true for AST: (NOISE >= 70.0 AND
HOUR > 22[PASS]
[32] Interpreter :: testInterpreterOrExpression          -> Result: true for AST: (AIR > 150.0 OR NOISE >
85.0[PASS]
[33] Interpreter :: testInterpreterParentheses           -> Nested parentheses AST evaluated: true
[PASS]
```

[34] Interpreter :: testInterpreterMissingVariable -> Missing variable returns false safely: true [PASS]
[35] Interpreter :: testInterpreterMalformedSyntax -> DslSyntaxException caught for all malformed cases [PASS]
==========
SUMMARY: 35 / 35 TESTS PASSED (100.0% PASS RATE) | EXECUTION TIME: 46 ms
==========

Empirical Measurement Methodology & Reproducible Analysis Notes:
• Decorator Telemetry Framing vs. Bulk Stream Compression: In testDecoratorNormalPipeline, an isolated 72-byte JSON energy telemetry packet produces a 468-byte cryptographic envelope. This expansion is governed by mandatory security overhead: AES-GCM Initialization Vector (12 bytes), AEAD authentication tag (16 bytes), Base64 payload encoding (+33%), HMAC-SHA256 authentication tag (64 hex characters), and GZIP stream header/trailer framing (~20 bytes). While GZIP introduces framing overhead on isolated micro-payloads under 100 bytes, on continuous batched telemetry streams (>1 KB) GZIP achieves a 60–80% compression ratio, substantially reducing network egress costs.
• Interpreter Microbenchmark Methodology: Benchmarking in DslPolicyParser measures execution latency across 2,000 iterations following initial C2 JIT compilation warmup loops. This separates one-time compilation overhead from steady-state AST traversal, confirming sub-microsecond evaluation (~0.4–0.8 µs per AST) and ~6.0–6.7 µs total parse-and-eval latency.
• Fail-Safe Terminal Fallback Verification: testChainTerminalFallback explicitly exercises both conditions: verifying that an unlinked handler safely returns CHAIN_EXHAUSTED without throwing NullPointerException, and confirming that wiring TerminalFallbackHandler at the chain terminus reliably captures unhandled complaints into FALLBACK_DISPATCH_DESK with status FALLBACK_ASSIGNED and an audit record.

7.4 Final Submission Deliverables Verification

In accordance with Section 5 of the assessment specification (Part F) (Java Institute for Advanced Technology, 2026), the three mandatory deliverables have been prepared, audited, and formatted for direct submission to the Java Institute Student Portal:

Requirement	Portal Section	Artifact File	Verification Scope

Requirement	Portal Section	Artifact File	Verification Scope
Item 5.a: Project Documentation	Project Document (PDF Format)	SmartCity360_OODP_II_Final_Submission.pdf	This report contains the five required pattern analyses, complete 13-figure architectural and behavioral diagram catalogue (including the core vector diagrams corresponding to each pattern subsystem), implementation highlights, automated test evidence, and academic references.
Item 5.b: Project Source Code	Project File (ZIP Archive)	SmartCity360_Source_Code.zip	Complete source archive containing the backend Java pattern implementations, frontend, database resources, and test runners. Upload the ZIP separately from this report.
Item 5.c: Demonstration Video	Demonstration Video (MP4 Format (10–15 min))	SmartCity360_Demonstration_Video.mp4	Formal 12-minute 45-second demonstration video (1080p MP4, H.264/AAC) showcasing the implemented system, live Jakarta servlet endpoints, Next.js frontend, and 35/35 test suite execution in full accordance with Part F requirements and SmartCity360_Demo_Script.md.
Companion: VIVA & Video Guide	Student Reference (PDF & Markdown)	SmartCity360_Viva_and_Presentation_Guide.pdf	Optional preparation material containing model viva questions and a 10–15-minute recording script; it is not a substitute for the required MP4.

1. Project Documentation (Project Document): Final academic report in PDF format uploaded to the Project Document section.

2. Project Source Code (Project File): Complete, compilable source code archive in ZIP format uploaded to the Project File section.

---

3. Demonstration Video (Demonstration Video): A 10–15-minute recorded video in MP4 format uploaded to the Demonstration Video section.

8. CONCLUSION & ACADEMIC REFERENCES

8.1 Comprehensive Architectural Synthesis & Pattern Synergy

The SmartCity360 municipal platform demonstrates the practical application of Gang of Four object-oriented design patterns in engineering scalable, resilient, and modular smart city infrastructure. Rather than treating design patterns as academic abstractions, each pattern was selected to solve a distinct, high-impact architectural challenge:

1. Structural Decorator Pattern (Data Streams): Solved the combinatorial class explosion problem inherent in subclassing, allowing dynamic composition of compression (GZIP), authenticated encryption (AES-256-GCM), and outer HMAC-SHA256 message authentication and integrity verification over telemetry streams.
2. Structural Composite Pattern (Smart Zones): Established a unified, hierarchical tree topography enabling municipal commands (power shutdown, load shedding, emergency isolation) to cascade seamlessly across cities, districts, streets, and building leaves in O(M) time while preventing circular reference cycles via proactive cycle validation.
3. Behavioral Chain of Responsibility Pattern (Citizen Grievances): Decoupled complaint submission from administrative resolution, implementing safe validation triage, deterministic multi-tier routing (LocalStaff for LOW, Supervisor for MEDIUM, CityManager for HIGH and CRITICAL), and an audit-backed TerminalFallbackHandler that, when correctly configured at the chain terminus, reliably traps unhandled complaints to mitigate request drop hazards.
4. Structural Flyweight Pattern (Smart Streetlights): Optimized JVM heap consumption across 25,000 smart streetlights by externalizing extrinsic coordinates and sharing immutable hardware profiles via a thread-safe ConcurrentHashMap pool, achieving an analytical 72.2% layout reduction based on the benchmark model and mitigating young-generation allocation pressure.
5. Behavioral Interpreter Pattern (Municipal DSL Policies): Provided an in-memory, restricted recursive-descent LL(1) parser evaluating complex Boolean environmental regulations in sub-microsecond latency (~0.4–0.8 μs per AST traversal) while mitigating code injection risks and avoiding servlet container restarts.

8.2 Critical Limitations & Future System Enhancements

While the architecture achieves complete functional correctness verified by 35/35 automated unit and integration tests (100% pass rate), several production trade-offs provide avenues for future municipal enhancements:

• AST Grammar Evolution: If municipal policy rules expand to require procedural loops, time-series window aggregations, or external API queries, the GoF Interpreter pattern should be migrated to a formal parser generator (such as ANTLR) or an embeddable sandboxed scripting engine (GraalVM).

• Distributed Cluster Coordination: Currently, the Flyweight pool and Composite hierarchies operate as in-memory JVM structures. In a multi-node horizontal cluster, shared profiles and zone state should be synchronized via distributed in-memory datagrids (such as Hazelcast or Redis) with local caching.
• Cryptographic Identity: While HMAC-SHA256 provides robust message authentication between symmetric key holders, future perimeter gateways could implement asymmetric ECDSA digital signatures to achieve absolute sender non-repudiation across heterogeneous IoT hardware vendors.

Academic References & Literature:

- Dworkin, M. (2007). Recommendation for Block Cipher Modes of Operation: Galois/Counter Mode (GCM) and GMAC. NIST Special Publication 800-38D. National Institute of Standards and Technology.
- Fowler, M. (2002). Patterns of Enterprise Application Architecture. Addison-Wesley.
- Gamma, E., Helm, R., Johnson, R., & Vlissides, J. (1994). Design Patterns: Elements of Reusable Object-Oriented Software. Addison-Wesley.
- Goetz, B., Peierls, T., Bloch, J., Bowbeer, J., Holmes, D., & Lea, D. (2006). Java Concurrency in Practice. Addison-Wesley.

• Krawczyk, H., Bellare, M., & Canetti, R. (1997). HMAC: Keyed-Hashing for Message Authentication. RFC 2104. Internet Engineering Task Force (IETF).

• Martin, R. C. (2008). Clean Code: A Handbook of Agile Software Craftsmanship. Prentice Hall.

• Coward, D. (2017). Java Servlet Specification, Version 4.0 (JSR 369). Oracle Corporation & Eclipse Foundation.

• Dworkin, M. (2007). Recommendation for Block Cipher Modes of Operation: Galois/Counter Mode (GCM) and GMAC. NIST Special Publication 800-38D. National Institute of Standards and Technology.
• Fowler, M. (2002). Patterns of Enterprise Application Architecture. Addison-Wesley.
• Gamma, E., Helm, R., Johnson, R., & Vlissides, J. (1994). Design Patterns: Elements of Reusable Object-Oriented Software. Addison-Wesley.
• Goetz, B., Peierls, T., Bloch, J., Bowbeer, J., Holmes, D., & Lea, D. (2006). Java Concurrency in Practice. Addison-Wesley.
• Krawczyk, H., Bellare, M., & Canetti, R. (1997). HMAC: Keyed-Hashing for Message Authentication. RFC 2104. Internet Engineering Task Force (IETF).
• Martin, R. C. (2008). Clean Code: A Handbook of Agile Software Craftsmanship. Prentice Hall.

• Oracle Corporation. (2024). Java SE 17 Developer Documentation & HotSpot Virtual Machine Memory Management Guide. Oracle America, Inc.
• Java Institute for Advanced Technology. (2026). Object Oriented Design Patterns - II Lecture Notes & Academic Syllabus. Department of Examinations.


- Java Institute for Advanced Technology. (2026). Object Oriented Design Patterns - II Lecture Notes & Academic Syllabus. Department of Examinations.

9. APPENDIX A — COMPREHENSIVE SOURCE CODE IMPLEMENTATION SCREENSHOT CATALOG

This appendix provides a structured, formal catalog of all production source code files developed for the SmartCity360 municipal platform. In compliance with Part F.3 of the assessment specification ('prepare comprehensive project documentation, including working code to illustrate the design and functionality of your application'), each pattern's source files are mapped with their exact repository paths, architectural roles, and formal implementation references. The complete, compilable source files are packaged in the project repository and cataloged below:

9.1 Part A: Dynamic Security Wrappers for Data Streams (Decorator Pattern)

Package: com.smartcity.pattern.decorator



Screenshot A.1.1: *StreamData.java — Component Interface — Defines uniform telemetry payload contract (getData(), getPayloadBytes(), getPayloadSize()).*

EnergyStreamData.java

```java
package com.smartcity.pattern.decorator;

import java.nio.charset.StandardCharsets;

public class EnergyStreamData implements StreamData {  11 usages  Dhanushka Maduranga

    private final String streamId;  2 usages
    private final String payload;  3 usages
    private final byte[] payloadBytes;  3 usages

    @Contract(pure = true)
    public EnergyStreamData(String streamId, double voltage, double currentAmps, double powerKw) {  12 usages  Dhanushka Maduranga
        this.streamId = streamId;
        this.payload = "{\"streamId\":\"" + streamId + "\",\"voltage\":" + voltage + ",\"currentAmps\":" + currentAmps
                + ",\"powerKw\":" + powerKw + "}";
        this.payloadBytes = this.payload.getBytes(StandardCharsets.UTF_8);
    }

    @Override  19 usages  Dhanushka Maduranga
    public String getData() {
        return this.payload;
    }

    @Override  3 usages  Dhanushka Maduranga
    public byte[] getPayloadBytes() {
        return this.payloadBytes.clone();
    }

    @Override  14 usages  Dhanushka Maduranga
    public int getPayloadSize() {
        return this.payloadBytes.length;
    }

    @Override  Dhanushka Maduranga
    public String getDescription() {
        return "Energy Stream (" + this.streamId + ")";
    }
}
```

Screenshot A.1.2: *EnergyStreamData.java — Concrete Component — Ingests raw smart energy meter readings and stores unencrypted payload.*

StreamDataDecorator.java

```java
package com.smartcity.pattern.decorator;

public abstract class StreamDataDecorator implements StreamData {  3 usages  3 inheritors  Dhanushka Maduranga

    protected final StreamData wrappee;  10 usages

    @Contract(value = "null -> fail", pure = true)
    public StreamDataDecorator(StreamData wrappee) {  6 usages  Dhanushka Maduranga
        if (wrappee == null) {
            throw new IllegalArgumentException("Wrappee component cannot be null");
        }
        this.wrappee = wrappee;
    }

    public StreamData getWrappee() {  2 usages  Dhanushka Maduranga
        return this.wrappee;
    }

    @Override  19 usages  3 overrides  Dhanushka Maduranga
    public String getData() {
        return this.wrappee.getData();
    }

    @Override  3 usages  3 overrides  Dhanushka Maduranga
    public byte[] getPayloadBytes() {
        return this.wrappee.getPayloadBytes();
    }

    @Override  14 usages  3 overrides  Dhanushka Maduranga
    public int getPayloadSize() {
        return this.wrappee.getPayloadSize();
    }

    @Override  3 overrides  Dhanushka Maduranga
    public String getDescription() {
        return this.wrappee.getDescription();
    }
}
```

Screenshot A.1.3: *StreamDataDecorator.java — Abstract Decorator — Holds protected wrappedStream reference and delegates calls.*

EncryptionDecorator.java

```
12  public class EncryptionDecorator extends StreamDataDecorator {  16 usages  Dhanushka Maduranga
42
43      public EncryptionDecorator(StreamData wrappee) {  9 usages  Dhanushka Maduranga
44          this(wrappee, resolveDefaultKey());
45      }
46
47      public EncryptionDecorator(StreamData wrappee, byte[] keyBytes) {  5 usages  Dhanushka Maduranga
48          super(wrappee);
49          if (keyBytes == null || keyBytes.length != 32) {
50              throw new IllegalArgumentException("AES-256 requires exactly 32-byte key");
51          }
52          this.keyBytes = keyBytes.clone();
53          byte[] input = wrappee.getPayloadBytes();
54          this.ivBytes = new byte[GCM_IV_LENGTH];
55          new SecureRandom().nextBytes(this.ivBytes);
56
57          try {
58              SecretKey secretKey = new SecretKeySpec(this.keyBytes,  algorithm: "AES");
59              Cipher cipher = Cipher.getInstance( transformation: "AES/GCM/NoPadding");
60              GCMParameterSpec spec = new GCMParameterSpec(GCM_TAG_LENGTH, this.ivBytes);
61              cipher.init(Cipher.ENCRYPT_MODE, secretKey, spec);
62              this.ciphertextBytes = cipher.doFinal(input);
63          } catch (GeneralSecurityException e) {
64              throw new RuntimeException("AES-GCM encryption failed", e);
65          }
66
67          String ivB64 = Base64.getEncoder().encodeToString(this.ivBytes);
68          String cipherB64 = Base64.getEncoder().encodeToString(this.ciphertextBytes);
69          this.encryptedJson = "{\"cipher\":\"AES-256-GCM\",\"iv\":\"" + ivB64
70                  + "\",\"tagLength\":" + GCM_TAG_LENGTH
71                  + ",\"ciphertext\":\"" + cipherB64 + "\"}";
72      }
```

Screenshot A.1.4: *EncryptionDecorator.java — Concrete Decorator — 256-bit AES-GCM AEAD encryption engine with secure IV generation.*

CompressionDecorator.java

```java
package com.smartcity.pattern.decorator;

import java.io.ByteArrayInputStream;
import java.io.ByteArrayOutputStream;
import java.io.IOException;
import java.nio.charset.StandardCharsets;
import java.util.Base64;
import java.util.zip.GZIPInputStream;
import java.util.zip.GZIPOutputStream;

public class CompressionDecorator extends StreamDataDecorator {  16 usages  Dhanushka Maduranga

    private final String compressedJson;
    private final byte[] compressedBytes;
    private final int originalSize;
    private final int compressedSize;

    public CompressionDecorator(StreamData wrappee) {  5 usages  Dhanushka Maduranga
        super(wrappee);
        byte[] input = wrappee.getPayloadBytes();
        this.originalSize = input.length;
        this.compressedBytes = compressBytes(input);
        this.compressedSize = this.compressedBytes.length;
        String b64 = Base64.getEncoder().encodeToString(this.compressedBytes);
        this.compressedJson = "{\"format\":\"GZIP\",\"originalBytes\":" + this.originalSize
                + ",\"compressedBytes\":" + this.compressedSize
                + ",\"data\":\"" + b64 + "\"}";
    }

    private static byte[] compressBytes(byte[] data) {
        try {
            ByteArrayOutputStream baos = new ByteArrayOutputStream();
            try (GZIPOutputStream gzip = new GZIPOutputStream(baos)) {
                gzip.write(data);
                gzip.finish();
            }
            return baos.toByteArray();
        } catch (IOException e) {
            throw new RuntimeException("GZIP compression failure", e);
```

Screenshot A.1.5: *CompressionDecorator.java — Concrete Decorator — GZIP compression wrapper applied prior to ciphering.*

AuthenticationDecorator.java

```java
package com.smartcity.pattern.decorator;

import javax.crypto.Mac;
import javax.crypto.spec.SecretKeySpec;
import java.nio.charset.StandardCharsets;
import java.security.GeneralSecurityException;
import java.security.MessageDigest;
import java.util.Base64;

public class AuthenticationDecorator extends StreamDataDecorator {  16 usages  Dhanushka Maduranga

    private static final byte[] FALLBACK_HMAC_KEY = "SmartCity360-Gateway-Hmac-Secret-Key-2026".get

    public static byte[] resolveDefaultKey() {  5 usages  Dhanushka Maduranga
        String envKey = System.getenv("STREAM_HMAC_KEY");
        if (envKey != null && !envKey.trim().isEmpty()) {
            return envKey.trim().getBytes(StandardCharsets.UTF_8);
        }
        return FALLBACK_HMAC_KEY;
    }

    private final String authenticatedJson;
    private final String signatureBase64;
    private final byte[] hmacKey;

    public AuthenticationDecorator(StreamData wrappee) {  5 usages  Dhanushka Maduranga
        this(wrappee, resolveDefaultKey());
    }

    public AuthenticationDecorator(StreamData wrappee, byte[] hmacKey) {  5 usages  Dhanushka Maduranga
        super(wrappee);
        if (hmacKey == null || hmacKey.length == 0) {
            throw new IllegalArgumentException("HMAC key cannot be empty");
        }
        this.hmacKey = hmacKey.clone();
        String innerData = wrappee.getData();
        this.signatureBase64 = sign(innerData, this.hmacKey);
        this.authenticatedJson = "{\"auth\":\"HMAC-SHA256\",\"keyId\":\"GW-KEY-01\",\"signature\":\
                + this.signatureBase64 + "\",\"payload\":" + innerData + "}";
```

Screenshot A.1.6: *AuthenticationDecorator.java — Concrete Decorator — HMAC-SHA256 authenticity signature generator and perimeter verifier.*

9.2 Part B: Hierarchical Structure of Smart Zones (Composite Pattern)

> **Package: com.smartcity.pattern.composite**

ZoneComponent.java

```java
package com.smartcity.pattern.composite;

import java.util.List;

public abstract class ZoneComponent {  16 usages  Dhanushka Maduranga

    protected final String id;
    protected final String name;
    protected final String type;

    public ZoneComponent(String id, String name, String type) {  5 usages  Dhanushka Maduranga
        if (id == null || id.trim().isEmpty()) {
            throw new IllegalArgumentException("ZoneComponent id cannot be null or empty");
        }
        if (name == null || name.trim().isEmpty()) {
            throw new IllegalArgumentException("ZoneComponent name cannot be null or empty");
        }
        this.id = id;
        this.name = name;
        this.type = type != null ? type : "GENERIC";
    }

    public String getId() {  5 usages  Dhanushka Maduranga
        return id;
    }

    public String getName() {  5 usages  Dhanushka Maduranga
        return name;
    }

    public String getType() {  5 usages  Dhanushka Maduranga
        return type;
    }

    public abstract void executeCommand(ZoneCommand command);  5 usages  Dhanushka Maduranga

    public void executeCommand(String command) {  5 usages  Dhanushka Maduranga
```

Screenshot A.2.1: *ZoneComponent.java — Component Interface — Declares uniform operations for leaves and composite zones.*

BuildingLeaf.java

```java
package com.smartcity.pattern.composite;

public class BuildingLeaf extends ZoneComponent {  16 usages  Dhanushka Maduranga

    private final double baselinePowerKw;
    private double currentPowerKw;
    private String status;

    public BuildingLeaf(String id, String name, double powerUsageKw) {  5 usages  Dhanushka Maduranga
        super(id, name, "BUILDING");
        if (powerUsageKw < 0) {
            throw new IllegalArgumentException("Power consumption cannot be negative");
        }
        this.baselinePowerKw = powerUsageKw;
        this.currentPowerKw = powerUsageKw;
        this.status = "ONLINE";
    }

    @Override
    public void executeCommand(ZoneCommand command) {  5 usages  Dhanushka Maduranga
        if (command == null) {
            throw new IllegalArgumentException("Command cannot be null");
        }
        switch (command) {
            case SHUTDOWN_POWER:
                this.status = "OFFLINE";
                this.currentPowerKw = 0.0;
                break;
            case RESTORE_POWER:
                this.status = "ONLINE";
                this.currentPowerKw = this.baselinePowerKw;
                break;
            case EMERGENCY_ISOLATE:
                this.status = "ISOLATED";
                this.currentPowerKw = 0.0;
                break;
        }
    }

```

Screenshot A.2.2: *BuildingLeaf.java — Leaf Component — Represents atomic smart buildings / assets; safe leaf enforcement.*

ZoneComposite.java

```
public class ZoneComposite extends ZoneComponent {  39 usages  Dhanushka Maduranga

    @Override  1 usage  Dhanushka Maduranga
    public List<ZoneComponent> getChildren() {
        return Collections.unmodifiableList(this.children);
    }

    @Override  no usages  Dhanushka Maduranga
    public ZoneComponent getChild(int index) {
        if (index < 0 || index >= this.children.size()) {
            throw new IndexOutOfBoundsException(
                    "Child index " + index + " out of bounds for size " + this.children.size());
        }
        return this.children.get(index);
    }

    public int getChildCount() {  7 usages  Dhanushka Maduranga
        return this.children.size();
    }

    @Override  5 usages  Dhanushka Maduranga
    public void executeCommand(ZoneCommand command) {
        if (command == null) {
            throw new IllegalArgumentException("Command cannot be null");
        }
        for (ZoneComponent child : this.children) {
            child.executeCommand(command);
        }
    }

    @Override  19 usages  Dhanushka Maduranga
    public double getPowerConsumption() {
        double total = 0.0;
        for (ZoneComponent child : this.children) {
            total += child.getPowerConsumption();
        }
        return total;
    }
```

Screenshot A.2.3: *ZoneComposite.java — Composite Container — Maintains child components with recursive command broadcasting and power rollup.*

ZoneCommand.java

```java
package com.smartcity.pattern.composite;

public enum ZoneCommand {  16 usages  Dhanushka Maduranga
    SHUTDOWN_POWER("shutdownPower"),
    RESTORE_POWER("restorePower"),
    EMERGENCY_ISOLATE("emergencyIsolate");

    private final String commandName;

    ZoneCommand(String commandName) {
        this.commandName = commandName;
    }

    public String getCommandName() {  5 usages  Dhanushka Maduranga
        return commandName;
    }

    public static ZoneCommand fromString(String text) {  5 usages  Dhanushka Maduranga
        if (text == null || text.trim().isEmpty()) {
            throw new IllegalArgumentException("Command cannot be null or empty");
        }
        String clean = text.trim();
        for (ZoneCommand cmd : values()) {
            if (cmd.name().equalsIgnoreCase(clean) || cmd.commandName.equalsIgnoreCase(clean)) {
                return cmd;
            }
        }
        throw new IllegalArgumentException("Invalid or unsupported zone command: '" + text + "'. Su
    }
}

```

Screenshot A.2.4: *ZoneCommand.java — Command Abstraction — Type-safe enum for municipal command broadcasting.*

9.3 Part C: Escalation of Citizen Complaints (Chain of Responsibility Pattern)

> **Package: com.smartcity.pattern.chain**

ComplaintHandler.java

```java

public abstract class ComplaintHandler {  Dhanushka Maduranga

    protected ComplaintHandler nextHandler;  5 usages

    public ComplaintHandler getNextHandler() {  no usages  Dhanushka Maduranga
        return this.nextHandler;
    }

    public void setNextHandler(ComplaintHandler nextHandler) {  no usages  Dhanushka Maduranga
        this.nextHandler = nextHandler;
    }

    public ComplaintHandler setNext(ComplaintHandler nextHandler) {  5 usages  Dhanushka Maduranga
        this.nextHandler = nextHandler;
        return nextHandler;
    }

    public abstract ComplaintRoutingResult handle(Complaint complaint);  20 usages  5 implementations  Dhanushka Maduranga

    protected ComplaintRoutingResult passToNext(Complaint complaint) {  4 usages  Dhanushka Maduranga
        if (this.nextHandler != null) {
            return this.nextHandler.handle(complaint);
        }
        ComplaintRoutingResult unhandled = new ComplaintRoutingResult(
                complaint != null ? complaint.getId() : "UNKNOWN",
                complaint != null ? complaint.getSeverity() : "UNKNOWN",
                handledByRole: "UNASSIGNED",
                status: "CHAIN_EXHAUSTED",
                message: "No subsequent handler available in processing chain",
                handled: false
        );
        unhandled.addAuditRecord(new ComplaintAuditRecord(
                Instant.now().toString(),
                getClass().getSimpleName(),
                toRole: "NONE",
                action: "DROP_HAZARD",
                reason: "End of chain reached without handler assignment"
        ));
        return unhandled;
    }
}
```

Screenshot A.3.1: *ComplaintHandler.java — Abstract Base Handler — Maintains protected successor reference and handleRequest() delegation template.*

LocalStaffHandler.java

```java
package com.smartcity.pattern.chain;

import com.smartcity.model.Complaint;

import java.time.Instant;

public class LocalStaffHandler extends ComplaintHandler {  16 usages  Dhanushka Maduranga

    @Override
    public ComplaintRoutingResult handle(Complaint complaint) {  5 usages  Dhanushka Maduranga
        ComplaintSeverity severity = ComplaintSeverity.parse(complaint.getSeverity());

        if (severity == ComplaintSeverity.LOW) {
            complaint.setCurrentHandlerRole("LOCAL_STAFF");
            complaint.setStatus("ASSIGNED");
            ComplaintRoutingResult result = new ComplaintRoutingResult(
                    complaint.getId(),
                    "LOW",
                    "LOCAL_STAFF",
                    "ASSIGNED",
                    "Assigned to Local Staff for routine field inspection and resolution",
                    true
            );
            result.addAuditRecord(new ComplaintAuditRecord(
                    Instant.now().toString(),
                    "ENTRY_GATEWAY",
                    "LOCAL_STAFF",
                    "ROUTED_LOW",
                    "Resolved at Tier 1 local operations level"
            ));
            return result;
        }

        ComplaintRoutingResult nextResult = passToNext(complaint);
        nextResult.addAuditRecord(new ComplaintAuditRecord(
                Instant.now().toString(),
                "LOCAL_STAFF",
                "SUPERVISOR",
                "ESCALATE_TIER2",
```

Screenshot A.3.2: *LocalStaffHandler.java — Concrete Handler 1 — Dispatches LOW severity municipal maintenance issues.*

SupervisorHandler.java

```java
package com.smartcity.pattern.chain;

import com.smartcity.model.Complaint;

import java.time.Instant;

public class SupervisorHandler extends ComplaintHandler {  16 usages  Dhanushka Maduranga

    @Override
    public ComplaintRoutingResult handle(Complaint complaint) {  5 usages  Dhanushka Maduranga
        ComplaintSeverity severity = ComplaintSeverity.parse(complaint.getSeverity());

        if (severity == ComplaintSeverity.MEDIUM) {
            complaint.setCurrentHandlerRole("SUPERVISOR");
            complaint.setStatus("ESCALATED");
            ComplaintRoutingResult result = new ComplaintRoutingResult(
                    complaint.getId(),
                    "MEDIUM",
                    "SUPERVISOR",
                    "ESCALATED_SUPERVISOR",
                    "Escalated to District Supervisor for departmental resource coordination",
                    true
            );
            result.addAuditRecord(new ComplaintAuditRecord(
                    Instant.now().toString(),
                    "LOCAL_STAFF",
                    "SUPERVISOR",
                    "ROUTED_MEDIUM",
                    "Resolved at Tier 2 supervisor management level"
            ));
            return result;
        }

        ComplaintRoutingResult nextResult = passToNext(complaint);
        nextResult.addAuditRecord(new ComplaintAuditRecord(
                Instant.now().toString(),
                "SUPERVISOR",
                "CITY_MANAGER",
                "ESCALATE_TIER3",
```

Screenshot A.3.3: *SupervisorHandler.java — Concrete Handler 2 — Resolves MEDIUM severity municipal issues within operational SLAs.*

CityManagerHandler.java

```java
package com.smartcity.pattern.chain;

import com.smartcity.model.Complaint;

import java.time.Instant;

public class CityManagerHandler extends ComplaintHandler {  16 usages  Dhanushka Maduranga

    @Override
    public ComplaintRoutingResult handle(Complaint complaint) {  5 usages  Dhanushka Maduranga
        ComplaintSeverity severity = ComplaintSeverity.parse(complaint.getSeverity());

        if (severity == ComplaintSeverity.HIGH || severity == ComplaintSeverity.CRITICAL) {
            complaint.setCurrentHandlerRole("CITY_MANAGER");
            complaint.setStatus("ESCALATED_EMERGENCY");
            String actionNote = severity == ComplaintSeverity.CRITICAL
                    ? "Emergency executive declaration dispatched to City Manager for immediate int
                    : "Escalated to City Manager for strategic infrastructure remediation";

            ComplaintRoutingResult result = new ComplaintRoutingResult(
                    complaint.getId(),
                    severity.name(),
                    "CITY_MANAGER",
                    "EXECUTIVE_ESCALATION",
                    actionNote,
                    true
            );
            result.addAuditRecord(new ComplaintAuditRecord(
                    Instant.now().toString(),
                    "SUPERVISOR",
                    "CITY_MANAGER",
                    "ROUTED_" + severity.name(),
                    "Resolved at Tier 3 municipal executive leadership"
            ));
            return result;
        }

        return passToNext(complaint);
    }
```

Screenshot A.3.4: CityManagerHandler.java — Concrete Handler 3 — Authorizes HIGH and CRITICAL municipal emergencies with executive authority.

TerminalFallbackHandler.java

```java
package com.smartcity.pattern.chain;

import com.smartcity.model.Complaint;

import java.time.Instant;

public class TerminalFallbackHandler extends ComplaintHandler {  16 usages  Dhanushka Maduranga

    @Override
    public ComplaintRoutingResult handle(Complaint complaint) {  5 usages  Dhanushka Maduranga
        String cid = complaint != null ? complaint.getId() : "UNKNOWN";
        String sev = complaint != null && complaint.getSeverity() != null ? complaint.getSeverity()

        if (complaint != null) {
            complaint.setCurrentHandlerRole("FALLBACK_DISPATCH_DESK");
            complaint.setStatus("TERMINAL_FALLBACK_HELD");
        }

        ComplaintRoutingResult fallback = new ComplaintRoutingResult(
                cid,
                sev,
                "FALLBACK_DISPATCH_DESK",
                "FALLBACK_ASSIGNED",
                "Captured by terminal fallback handler to prevent drop hazard. Enqueued for special
                true
        );
        fallback.addAuditRecord(new ComplaintAuditRecord(
                Instant.now().toString(),
                "CHAIN_TERMINUS",
                "FALLBACK_DISPATCH_DESK",
                "TERMINAL_RESCUE",
                "Guaranteed processing: complaint prevented from falling off chain"
        ));
        return fallback;
    }
}

```

Screenshot A.3.5: TerminalFallbackHandler.java — Terminal Fallback Handler — Safely captures requests that remain unhandled after traversing preceding handlers, enqueuing them for dispatch review without drop hazards.

ComplaintChainFactory.java

```java
package com.smartcity.pattern.chain;

public class ComplaintChainFactory {  16 usages  Dhanushka Maduranga

    public static ComplaintHandler createChain() {  5 usages  Dhanushka Maduranga
        ComplaintHandler triage = new ValidationTriageHandler();
        ComplaintHandler localStaff = new LocalStaffHandler();
        ComplaintHandler supervisor = new SupervisorHandler();
        ComplaintHandler cityManager = new CityManagerHandler();
        ComplaintHandler fallback = new TerminalFallbackHandler();

        triage.setNext(localStaff);
        localStaff.setNext(supervisor);
        supervisor.setNext(cityManager);
        cityManager.setNext(fallback);

        return triage;
    }
}
```

Screenshot A.3.6: *ComplaintChainFactory.java — Assembly Factory — Instantiates and wires the complete handler chain sequentially.*

9.4 Part D: Efficient Management of Smart Street Lights (Flyweight Pattern)

Package: com.smartcity.pattern.flyweight

SharedStreetlightProfile.java

```java
package com.smartcity.pattern.flyweight;

public final class SharedStreetlightProfile {  16 usages  Dhanushka Maduranga

    private final String model;
    private final String lampType;
    private final int wattage;
    private final int maxLumens;
    private final int colorTemperatureK;
    private final String firmwareVersion;

    public SharedStreetlightProfile(String model, String lampType, int wattage, int maxLumens, int
        if (model == null || model.trim().isEmpty()) {
            throw new IllegalArgumentException("Model cannot be null or empty");
        }
        this.model = model;
        this.lampType = lampType != null ? lampType : "LED";
        this.wattage = wattage;
        this.maxLumens = maxLumens;
        this.colorTemperatureK = colorTemperatureK;
        this.firmwareVersion = firmwareVersion != null ? firmwareVersion : "v1.0";
    }

    public String getModel() {  5 usages  Dhanushka Maduranga
        return model;
    }

    public String getLampType() {  5 usages  Dhanushka Maduranga
        return lampType;
    }

    public int getWattage() {  5 usages  Dhanushka Maduranga
        return wattage;
    }

    public int getMaxLumens() {  5 usages  Dhanushka Maduranga
        return maxLumens;
    }

```

Screenshot A.4.1: *SharedStreetlightProfile.java — Intrinsic Flyweight — Immutable hardware specification shared across 25,000 streetlights.*

StreetlightProfileFactory.java

```java
package com.smartcity.pattern.flyweight;

import ...

public class StreetlightProfileFactory {  25 usages  Dhanushka Maduranga

    private static final ConcurrentMap<String, SharedStreetlightProfile> profiles = new ConcurrentHashMap<>();  3 usages

    public static SharedStreetlightProfile getProfile(String model, String lampType, int wattage, int maxLumens, int colorTemperatureK, String firmware) {  17 usages  Dhanushka Maduranga
        String key = (model != null ? model : "") + "|" + (lampType != null ? lampType : "") + "|" + wattage + "|" + maxLumens + "|" + colorTemperatureK + "|" + (firmware != null ? firmware : "");
        return profiles.computeIfAbsent(key, String k -> new SharedStreetlightProfile(model, lampType, wattage, maxLumens, colorTemperatureK, firmware));
    }

    public static SharedStreetlightProfile getProfile(String model, String lampType, int wattage, int maxLumens,  no usages  Dhanushka Maduranga
            String firmware) {
        return getProfile(model, lampType, wattage, maxLumens, colorTemperatureK: 4000, firmware);
    }

    @ContractJure = true)
    public static int getFlyweightCount() {  0 usages  Dhanushka Maduranga
        return profiles.size();
    }

    public static void clear() {  4 usages  Dhanushka Maduranga
        profiles.clear();
    }
}
```

Screenshot A.4.2: *StreetlightProfileFactory.java — Thread-Safe Factory Pool — Manages static ConcurrentHashMap cache via computeIfAbsent.*

StreetlightContext.java

```java
package com.smartcity.pattern.flyweight;

public class StreetlightContext {  16 usages  Dhanushka Maduranga

    private final String poleId;
    private final double latitude;
    private final double longitude;
    private int brightnessLevel;
    private String operationalStatus;
    private final SharedStreetlightProfile profile;

    public StreetlightContext(String poleId, double latitude, double longitude, SharedStreetlightPr
        if (poleId == null || poleId.trim().isEmpty()) {
            throw new IllegalArgumentException("Pole ID cannot be null or empty");
        }
        if (profile == null) {
            throw new IllegalArgumentException("Shared profile cannot be null");
        }
        this.poleId = poleId;
        this.latitude = latitude;
        this.longitude = longitude;
        this.profile = profile;
        this.brightnessLevel = 0;
        this.operationalStatus = "ACTIVE";
    }

    public void setBrightnessLevel(int level) {  5 usages  Dhanushka Maduranga
        this.brightnessLevel = Math.max(0, Math.min(100, level));
    }

    public void setOperationalStatus(String status) {  5 usages  Dhanushka Maduranga
        this.operationalStatus = status != null ? status : "ACTIVE";
    }

    public String display() {  5 usages  Dhanushka Maduranga
        return this.profile.render(poleId, latitude, longitude, brightnessLevel, operationalStatus)
    }

    public String getPoleId() {  5 usages  Dhanushka Maduranga
```

Screenshot A.4.3: *StreetlightContext.java — Extrinsic Context — Lightweight object holding per-device state (GPS latitude/longitude, brightness, status).*

FlyweightBenchmark.java

```
    }

    public static BenchmarkResult runBenchmark(int count) {  5 usages  Dhanushka Maduranga
        BenchmarkResult res = new BenchmarkResult();
        res.objectCount = count;
        res.jvmInfo = System.getProperty("java.vm.name") + " v" + System.getProperty("java.version")
                + " (" + System.getProperty("os.name") + " " + System.getProperty("os.arch") + ")";

        String[] models = {"Philips SmartLum-150", "Siemens CityRay-200", "Osram UrbanEco-90"};
        String[] types = {"LED", "Solar-LED", "High-Efficiency LED"};
        int[] wattages = {150, 200, 90};
        int[] lumens = {18000, 24000, 11000};
        int[] temps = {4000, 5000, 3000};
        String firmware = "v3.2.1-prod";

        int bytesPerNaiveObject = 288;
        int bytesPerFlyweightContext = 80;
        int bytesPerSharedProfile = 288;
        res.naiveEstimatedBytes = (long) count * bytesPerNaiveObject;
        res.flyweightEstimatedBytes = ((long) count * bytesPerFlyweightContext) + ( * bytesPerShare
        res.savingsPercent = ((double) (res.naiveEstimatedBytes - res.flyweightEstimatedBytes) / re

        MemoryMXBean mem = ManagementFactory.getMemoryMXBean();

        // 1. Measure Naive Heavy allocation in isolation
        settleGc();
        long memBeforeNaive = mem.getHeapMemoryUsage().getUsed();
        long t0 = System.currentTimeMillis();
        NaiveHeavyStreetlight[] naiveArray = new NaiveHeavyStreetlight[count];
        for (int i = 0; i < count; i++) {
            int idx = i % 3;
            naiveArray[i] = new NaiveHeavyStreetlight(
                    "POLE-" + String.format("%06d", i),
                    6.9271 + (i * 0.0001),
                    79.8612 + (i * 0.0001),
                    models[idx], types[idx], wattages[idx], lumens[idx], temps[idx], firmware
            );
        }
        res.naiveTimeMs = System.currentTimeMillis() - t0;
```

Screenshot A.4.4: FlyweightBenchmark.java — Memory Measurement Engine — Evaluates analytical object layout estimation and runtime heap usage via MemoryMXBean (72.2% reduction on 25,000 objects).

9.5 Part E: Interpreting City Policies Defined in DSL (Interpreter Pattern)

Package: com.smartcity.pattern.interpreter

Expression.java

```
package com.smartcity.pattern.interpreter;

public interface Expression {  16 usages  Dhanushka Maduranga
    boolean interpret(PolicyContext context);
}

```

Screenshot A.5.1: *Expression.java — Abstract Expression Interface — Declares boolean interpret(PolicyContext context) contract.*

TerminalExpression.java

```java
package com.smartcity.pattern.interpreter;

import java.util.Set;

public class TerminalExpression implements Expression {  16 usages  Dhanushka Maduranga

    private static final Set<String> VALID_OPERATORS = Set.of(">", ">=", "<", "<=", "==", "!=");
    private final String variable;
    private final String operator;
    private final double threshold;

    public TerminalExpression(String variable, String operator, double threshold) {  5 usages  Dhanushk
        if (variable == null || variable.trim().isEmpty()) {
            throw new IllegalArgumentException("Variable name cannot be null or empty");
        }
        if (operator == null || !VALID_OPERATORS.contains(operator.trim())) {
            throw new IllegalArgumentException("Invalid comparison operator: '" + operator + "'. Su
        }
        this.variable = variable.trim();
        this.operator = operator.trim();
        this.threshold = threshold;
    }

    public String getVariable() {  5 usages  Dhanushka Maduranga
        return variable;
    }

    public String getOperator() {  5 usages  Dhanushka Maduranga
        return operator;
    }

    public double getThreshold() {  5 usages  Dhanushka Maduranga
        return threshold;
    }

    @Override
    public boolean interpret(PolicyContext context) {  5 usages  Dhanushka Maduranga
        if (context == null || !context.has(this.variable)) {
            return false;
```

Screenshot A.5.2: TerminalExpression.java — Terminal Expression — Evaluates atomic relational predicates (>, >=, <, <=, ==, !=) against context telemetry.

AndExpression.java

```java
package com.smartcity.pattern.interpreter;

public class AndExpression implements Expression {  16 usages  Dhanushka Maduranga

    private final Expression left;
    private final Expression right;

    public AndExpression(Expression left, Expression right) {  5 usages  Dhanushka Maduranga
        if (left == null || right == null) {
            throw new IllegalArgumentException("Sub-expressions in AndExpression cannot be null");
        }
        this.left = left;
        this.right = right;
    }

    public Expression getLeft() {  5 usages  Dhanushka Maduranga
        return left;
    }

    public Expression getRight() {  5 usages  Dhanushka Maduranga
        return right;
    }

    @Override
    public boolean interpret(PolicyContext context) {  5 usages  Dhanushka Maduranga
        return this.left.interpret(context) && this.right.interpret(context);
    }

    @Override
    public String toString() {  5 usages  Dhanushka Maduranga
        return "(" + left + " AND " + right + ")";
    }
}
```

Screenshot A.5.3: *AndExpression.java — Non-Terminal Expression — Evaluates binary logical AND between two sub-expressions.*

OrExpression.java

```java
package com.smartcity.pattern.interpreter;

public class OrExpression implements Expression {  16 usages  Dhanushka Maduranga

    private final Expression left;
    private final Expression right;

    public OrExpression(Expression left, Expression right) {  5 usages  Dhanushka Maduranga
        if (left == null || right == null) {
            throw new IllegalArgumentException("Sub-expressions in OrExpression cannot be null");
        }
        this.left = left;
        this.right = right;
    }


    public Expression getLeft() {  5 usages  Dhanushka Maduranga
        return left;
    }

    public Expression getRight() {  5 usages  Dhanushka Maduranga
        return right;
    }

    @Override
    public boolean interpret(PolicyContext context) {  5 usages  Dhanushka Maduranga
        return this.left.interpret(context) || this.right.interpret(context);
    }

    @Override
    public String toString() {  5 usages  Dhanushka Maduranga
        return "(" + left + " OR " + right + ")";
    }
}
```

Screenshot A.5.4: *OrExpression.java — Non-Terminal Expression — Evaluates binary logical OR between two sub-expressions.*



```java
public class DslPolicyParser {  19 usages  Dhanushka Maduranga
    private static class Parser {  2 usages  Dhanushka Maduranga

        Expression parseExpression() {  2 usages  Dhanushka Maduranga
            if (++depth > MAX_RECURSION_DEPTH) {
                throw new DslSyntaxException("Expression recursion depth exceeded limit of " + MAX_RECURSION_DEPTH);
            }
            try {
                return parseOr();
            } finally {
                depth--;
            }
        }

        Expression parseOr() {  1 usage  Dhanushka Maduranga
            Expression left = parseAnd();
            while (match(TokenType.OR)) {
                Expression right = parseAnd();
                left = new OrExpression(left, right);
            }
            return left;
        }

        Expression parseAnd() {  2 usages  Dhanushka Maduranga
            Expression left = parsePrimary();
            while (match(TokenType.AND)) {
                Expression right = parsePrimary();
                left = new AndExpression(left, right);
            }
            return left;
        }

        Expression parsePrimary() {  2 usages  Dhanushka Maduranga
            if (match(TokenType.LPAREN)) {
                Expression inner = parseExpression();
                if (!match(TokenType.RPAREN)) {
                    throw new DslSyntaxException("Mismatched parentheses: missing ')' in: " + originalText);
                }
                return inner;
            }
```

Screenshot A.5.5: *DslPolicyParser.java — Recursive-Descent Parser — Parses raw DSL strings into recursive AST with token & depth security limits.*

PolicyContext.java

```java
package com.smartcity.pattern.interpreter;

import java.util.HashMap;
import java.util.Map;

public class PolicyContext {  16 usages  Dhanushka Maduranga

    private final Map<String, Object> variables = new HashMap<>();

    public void set(String key, Object value) {  5 usages  Dhanushka Maduranga
        if (key != null) {
            variables.put(key.trim().toUpperCase(), value);
        }
    }

    public Object get(String key) {  5 usages  Dhanushka Maduranga
        if (key == null) return null;
        return variables.get(key.trim().toUpperCase());
    }

    public double getDouble(String key) {  5 usages  Dhanushka Maduranga
        Object val = get(key);
        if (val == null) {
            return 0.0;
        }
        if (val instanceof Number) {
            return ((Number) val).doubleValue();
        }
        if (val instanceof String) {
            try {
                return Double.parseDouble(((String) val).trim());
            } catch (NumberFormatException e) {
                throw new IllegalArgumentException("Variable '" + key + "' value '" + val + "' canno
            }
        }
        throw new IllegalArgumentException("Variable '" + key + "' has unsupported non-numeric type
    }

    public boolean has(String key) {  5 usages  Dhanushka Maduranga
```

Screenshot A.5.6: *PolicyContext.java — State Context — Stores runtime telemetry variable values (e.g. NOISE_LEVEL, AIR_QUALITY, TIME_HOUR).*