

Randoms :-

## What is a Random Number?

Random number does NOT mean a different number every time. Random means something that can not be predicted logically.

## Pseudo Random and

True Random:-

### Pseudo Random:-

Computers work on programs, and programs are definitive set of instructions. So it means there must be some algorithm to generate a random number as well.

If there is a program to generate random number it can be predicted, thus it is not truly random.

Random numbers generated through a generation algorithm are called pseudo random.

### True Random:-

## Can we make truly random numbers?

Yes. In order to generate a truly random number on our computers we need to get the random data from some outside source. This outside source is generally our keystrokes, mouse movements, data on network etc.

We do not need truly random numbers, unless its related to security (e.g. encryption keys) or the basis of application is the randomness (e.g. Digital roulette wheels).

.....

.....

Generate Random

Number: -

NumPy offers the "random" module to work with random numbers.

Example:-

1)Generate a random integer from 0 to 100:

```
from numpy import random
x = random.randint(100)                                ##randint for generating
random integers
print(x)
,,,,,,,,,,,,,o/p is [it will produce random integer with all posible values of
integer 100]
```

## 2)Generate Random Float

The random module's "rand()" method returns a random float between 0 and 1.

### Example

Generate a random float from 0 to 1:

```
from numpy import random
x = random.rand()
print(x)
```

o/p is [it will produce random float with all possible values of float]

[illegible]

Array: -

## 1)Integers

Example:-

```
from numpy import random
x=random.randint(100, size=(5))          ###it will produce 5 random integers
from 100 by chance with equal chance to all 100
print(x)
```

Example:-

```
from numpy import random
x = random.randint(100, size=(3, 5))          ###it will produce 3 rows & 5
columns random integers from 100 integers by chance with equal chance to all 100
print(x)
print(x)
```

The "rand()" method also allows you to specify the shape of the array.

Example:-

```
from numpy import random
x = random.rand(5)
print(x)
```

\* ) Example

```
from numpy import random
x = random.rand(3, 5)
print(x)
```

,,,,,,,,,,,,,,  
 ,,,,,,,,,,,,,,

## Generate Random Number From

Given Array:-

The "choice()" method allows you to generate a random value based on an array of values.

The "choice()" method takes an array as a parameter and randomly returns one of the values.

### Example

- \*)Return one of the values in an array:

```
from numpy import random
```

```
x = random.choice([3, 5, 7, 9])
```

```
number from specified array [3,5,7,9]
```

```
print(x)
```

```
###it will genrate random
```

The "choice()" method also allows you to return an array of values.

Add a size parameter to specify the shape of the array.

### Example

\*)Generate a 2-D array that consists of the values in the array parameter (3, 5, 7, and 9):

```
from numpy import random
```

```
x = random.choice([3, 5, 7, 9], size=(3, 5))
```

number in 3 rows & 5 column from array [3,5,7,9]

```
print(x)
```

###It will generate random

```

,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
```

Random Data Distribution:-

## What is Data Distribution?

Data Distribution is a list of all possible values, and how often each value occurs. Such lists are important when working with statistics and data science.

The "random" module offer methods that returns randomly generated data distributions.

Random Distribution:-

A random distribution is a set of random numbers that follow a certain probability density function.

Probability Density Function:-

A function that describes a continuous probability. i.e. probability of all values in an array.

\*We can generate random numbers based on defined probabilities using the "choice()" method of the random module.

\*The probability is set by a number between 0 and 1, where 0 (0% chance of occurrence, it will never come in output) means that the value will never occur and 1 (100% chance of occurrence, it will come always comes in input) means that the value will always occur.

\*)Generate a 1-D array containing 100 values, where each value has to be 3, 5, 7 or 9.

The probability for the value to be 5 is set to be 0.3                      ##30% chance of occurrence

```
The probability for the value to be 7 is set to be 0.6      ##60% chance of
occurrence
```

The probability for the value to be 9 is set to be 0                      ##0% chance of occurrence, this is bcz summing of all probability should be 1 or 100%(i.e.,  
10+30+60=100))

```
x = random.choice([3, 5, 7, 9], p=[0.1, 0.3, 0.6, 0.0], size=(10))
```

```
print(x)
```

```

,,,,,,,,,,,,,exact o/p can't predicted [5 3 3 5 5 3 7 5 7 7] this is for only
understandind purpose if we execute again we got different result

```

The sum of all probability numbers should be 1. or 100%

Even if you run the example above 100 times, the value 9 will never occur.

### Example

Same example as above, but return a 2-D array with 3 rows, each containing 5 values.

```
x = random.choice([3, 5, 7, 9], p=[0.1, 0.3, 0.6, 0.0], size=(3, 5))
```

```
print(x)
```

[illegible][illegible]

### Random Permutations:-

read the permutation & combination notebook file before starting this

### Random Permutations of Elements:-

A permutation refers to an arrangement of elements. e.g. [3, 2, 1] is a permutation of [1, 2, 3] and vice-versa.

The NumPy "Random" module provides two methods for this: "shuffle()" and "permutation()".

### 1)Shuffling Arrays:-

Shuffle means changing arrangement of elements in-place. i.e. in the array itself.

Example:-

Randomly shuffle elements of following array:

```
from numpy import random
import numpy as np
arr = np.array([1, 2, 3, 4, 5])
print(random.shuffle(arr))                                     ##it changes to original
array
,,,,,,,,,,,,,,,,,,,,,,,,,,,,,o/p is [4 2 1 5 3],it is not same for every time
```

The "shuffle()" method makes "changes to the original array".

## 2) Generating Permutation of Arrays

### Example

Generate a random permutation of elements of following array:

```
from numpy import random
import numpy as np
arr = np.array([1, 2, 3, 4, 5])
print(random.permutation(arr))          ##it leaves original array
un changed
,,,,,,,,,,,,,,,,,,,,,,,,,,,,,o/p is [5 4 3 2 1],it is not same for every time
```

The "permutation()" method returns a re-arranged array (and leaves the original array un-changed).

### Application of Random Numbers:-

\*Randomness has many uses in science, art, statistics, cryptography, gaming, gambling, and other fields.

\*Random numbers are important for computer encryption, lotteries, scientific modelling, and gambling.

\*Current methods of generating random numbers can produce predictable results.

\*Most cryptographic applications require random numbers, for example: key generation. nonces.

\*salts in certain signature schemes, including ECDSA, RSASSA-PSS(These are the Digital Signature).(In cryptography, a salt is random data that is used as an additional input to a one-way function that hashes data, a password or passphrase. Salts are used to safeguard passwords in storage. ... Cryptographic salts are broadly used in many modern computer systems, from Unix system credentials to Internet security.)

[illegible]

[illegible]