1. Objective

Insert sample records into all seven tables. Insert parent records before child records so that foreign keys work.

2. SQL Sample Data

```
INSERT INTO Passenger VALUES
(1,'Aarav Sharma','aarav@example.com','9876500001','P100001'),
(2,'Diya Kumar','diya@example.com','9876500002','P100002'),
(3,'Rahul Menon','rahul@example.com','9876500003','P100003'),
(4,'Meera Iyer','meera@example.com','9876500004','P100004'),
(5,'Arjun Rao','arjun@example.com','9876500005','P100005'),
(6,'Sara Khan','sara@example.com','9876500006','P100006');

INSERT INTO Airport VALUES
(1,'Kempegowda International Airport','Bengaluru','India','BLR'),
(2,'Chennai International Airport','Chennai','India','MAA'),
(3,'Indira Gandhi International Airport','Delhi','India','DEL'),
(4,'Chhatrapati Shivaji Maharaj International Airport','Mumbai','India','BOM');

INSERT INTO Aircraft VALUES
(1,'A320',180,'Airbus'),(2,'B737-800',189,'Boeing');

INSERT INTO Seat VALUES
(101,1,'1A','Business'),(102,1,'2A','Business'),
(103,1,'10A','Economy'),(104,1,'10B','Economy'),
(105,1,'11A','Economy'),(201,2,'1A','Business'),
(202,2,'10A','Economy'),(203,2,'10B','Economy'),
(204,2,'11A','Economy');

INSERT INTO Flight VALUES
(1001,'AI101',1,1,2,'2026-11-01 08:00:00','2026-11-01 09:15:00','Scheduled'),
(1002,'AI202',2,2,3,'2026-11-01 11:00:00','2026-11-01 13:45:00','Scheduled'),
(1003,'AI303',1,3,4,'2026-11-02 16:00:00','2026-11-02 18:10:00','Delayed'),
(1004,'AI404',2,4,1,'2026-11-03 07:30:00','2026-11-03 09:15:00','Scheduled');

INSERT INTO Booking VALUES
(5001,1,1001,103,'2026-10-20','Confirmed'),
(5002,2,1001,104,'2026-10-21','Confirmed'),
(5003,3,1002,202,'2026-10-21','Confirmed'),
(5004,4,1002,203,'2026-10-22','Pending'),
(5005,5,1003,105,'2026-10-22','Confirmed'),
(5006,6,1004,202,'2026-10-23','Confirmed');

INSERT INTO Payment VALUES
(9001,5001,4500.00,'2026-10-20','UPI','Paid'),
(9002,5002,4500.00,'2026-10-21','Card','Paid'),
(9003,5003,6200.00,'2026-10-21','Net Banking','Paid'),
(9004,5004,6200.00,'2026-10-22','UPI','Pending'),
(9005,5005,7800.00,'2026-10-22','Card','Paid'),
(9006,5006,5200.00,'2026-10-23','UPI','Paid');
```

3. Check Record Counts

```
SELECT 'Passenger' AS Table_Name, COUNT(*) AS Total FROM Passenger\nUNION ALL SELECT 'Airport', COUNT(*)
FROM Airport\nUNION ALL SELECT 'Aircraft', COUNT(*) FROM Aircraft\nUNION ALL SELECT 'Seat', COUNT(*)
FROM Seat\nUNION ALL SELECT 'Flight', COUNT(*) FROM Flight\nUNION ALL SELECT 'Booking', COUNT(*) FROM
Booking\nUNION ALL SELECT 'Payment', COUNT(*) FROM Payment;
```

Table	Expected records
Passenger	6
Airport	4
Aircraft	2
Seat	9
Flight	4
Booking	6
Payment	6

4. View Bookings

```
SELECT Booking_ID, Passenger_ID, Flight_ID, Seat_ID, Booking_Status\nFROM Booking ORDER BY Booking_ID;
```

Booking_ID	Passenger_ID	Flight_ID	Seat_ID	Booking_Status
5001	1	1001	103	Confirmed
5002	2	1001	104	Confirmed
5003	3	1002	202	Confirmed
5004	4	1002	203	Pending

Booking_ID	Passenger_ID	Flight_ID	Seat_ID	Booking_Status
5005	5	1003	105	Confirmed
5006	6	1004	202	Confirmed

5. Integrity Check

```
SELECT Flight_ID, Seat_ID, COUNT(*) AS Total\nFROM Booking GROUP BY Flight_ID, Seat_ID\nHAVING COUNT(*)
> 1;
```

Expected output: no rows. The query checks that no seat is booked more than once on the same flight.

6. Conclusion

The sample records cover all tables and support the SQL examples in the next assignments.