


A Star-Inspired Framework for Transforming Nuclear Waste at the Source

A Conceptual Direction for Next-Generation Nuclear Waste Neutralization

Conceptual three-layer waste-transformation architecture



Conceptual White Paper

Prepared by Anup J. Dharangutti | August 2026

This document is a conceptual research framework, not a reactor design, operating procedure, safety case, or claim of demonstrated technology.

Abstract

Long-lived radioactive waste is a consequence of nuclear fission, with a small fraction of spent-fuel inventory accounting for a disproportionately large share of long-term radiotoxicity and stewardship burden. This paper proposes a conceptual framework inspired by the way stars transform nuclei: rather than treating long-lived radionuclides solely as materials to be isolated, selected nuclei would be partitioned, recycled, transmuted, and finally immobilized in durable wasteforms. The framework combines three layers: (1) recovery and recycling of transuranic actinides, (2) targeted transmutation of selected long-lived actinides and fission products using fast-spectrum systems and/or accelerator-driven systems, and (3) immobilization of residual radionuclides in highly durable ceramic, glass, or glass-ceramic matrices. The proposal is not a claim that radioactive waste can be made to disappear, nor that all nuclides can be economically transmuted. Its central proposition is narrower: a future integrated fuel-cycle architecture could potentially convert a larger share of the long-lived inventory into shorter-lived or stable products while reducing the burden placed on final disposal. Established partitioning-and-transmutation research supports the scientific basis for this direction, while major challenges remain in separation chemistry, fuel and target materials, neutron economy, accelerator reliability, nuclear data, economics, safeguards, and final disposal. The paper therefore presents a research roadmap rather than a deployment claim.

Keywords: nuclear waste; transmutation; stellar nucleosynthesis; partitioning; actinide recycling; fast reactors; accelerator-driven systems; long-lived fission products; Synroc; vitrification; waste immobilization.

Core proposition. Move the endpoint of nuclear-waste management from “store everything that remains radioactive” toward “transform what is technically and economically transformable, then immobilize and dispose of the irreducible residue.”

Contents

1. Introduction
2. Stellar Processes as Conceptual Inspiration
3. The Three-Layer Framework
4. Layer 1 - Partitioning and Actinide Recycling
5. Layer 2 - Targeted Transmutation
6. Layer 3 - Durable Waste Immobilization
7. Integrated System Architecture
8. Research and Development Roadmap
9. Technical Constraints and Open Questions
10. Expected Impact and Evaluation Metrics
11. Conclusion
- References

1. Introduction

1.1 The problem

Spent nuclear fuel and high-level radioactive waste contain a mixture of short-lived fission products, long-lived fission products, plutonium and other transuranic elements. The long-lived fraction drives much of the extended stewardship challenge. Partitioning and transmutation (P&T) has consequently been studied as a complement or alternative pathway within advanced fuel cycles. OECD Nuclear Energy Agency assessments describe P&T as a route that can reduce the long-lived inventory and radiotoxicity of waste, while emphasizing substantial technical and systems-level requirements. [1-4]

The key distinction in this paper is between disposal and transformation. Geological disposal remains an essential reference strategy for long-lived waste. Transmutation does not remove the need for a final disposal concept; instead, it can change the composition, quantity, and time profile of the material that ultimately needs disposal. [4]

1.2 Why a star-inspired framing?

Stars provide a useful conceptual metaphor because stellar evolution demonstrates that nuclei can be transformed through a diversity of nuclear pathways. Fusion, neutron capture, photodisintegration and explosive nucleosynthesis are astrophysical phenomena governed by nuclear reaction physics. The proposal does not attempt to reproduce stellar interiors. It asks a more practical question: which underlying classes of nuclear reactions can be engineered on Earth, at useful scale, to transform selected waste isotopes?

This framing is therefore inspirational rather than literal. The engineering system remains a reactor, accelerator, fuel-cycle and materials system operating under terrestrial constraints.

2. Stellar Processes as Conceptual Inspiration

2.1 Nuclear transformation in stars

Stellar environments transform nuclei through reactions whose rates depend on temperature, density, neutron/proton availability, nuclear cross sections and decay pathways. The s-process and r-process, for example, involve neutron captures over very different flux and timescale regimes. The general lesson is that nuclear identity is a dynamic variable when an appropriate reaction environment is supplied.

For waste management, the analogous engineering resource is not stellar temperature but controllable particle flux: neutrons, charged particles and, in specialized systems, high-energy spallation products.

2.2 Earth-based analogues

Fast-spectrum reactors can provide high-energy neutron environments in which selected actinides have significant fission opportunities. Accelerator-driven systems can use a high-power proton beam striking a spallation target to generate neutrons and drive a subcritical multiplying assembly. Long-lived fission products can also be investigated as transmutation targets, but their optimal reaction pathways and overall system value are isotope-specific. [2-4]

3. The Three-Layer Framework

3.1 Layer 1 - Partition and recycle

Separate the chemically and radiologically important long-lived actinides from material destined for disposal, then recycle them through an appropriate fast-spectrum fuel cycle or dedicated transmutation system.

3.2 Layer 2 - Target and transform

Use engineered neutron fields and suitable reactor/accelerator configurations to convert selected nuclides through fission, neutron capture or other useful reaction channels.

3.3 Layer 3 - Immobilize the residue

After repeated recycle and transmutation, convert the remaining material into a durable wasteform, such as a tailored ceramic, glass, or glass-ceramic, and route it to an appropriate disposal pathway. Modern Synroc research illustrates how multiphase ceramics and glass-ceramics can be engineered for high durability and difficult waste chemistries. [5-7]

Research logic: from stellar inspiration to engineered nuclear reactions




Figure 1. Conceptual mapping from astrophysical nuclear transformation to terrestrial engineering objectives.

4. Layer 1 - Partitioning and Actinide Recycling

4.1 Partitioning

The first engineering task is selective recovery of transuranic elements and other target nuclides from spent fuel or reprocessing streams. Candidate approaches include aqueous solvent extraction and pyrochemical methods. The feasibility question is not simply chemical separation performance; it also includes radiolysis, waste secondary streams, process losses, worker dose, safeguards, criticality safety, and compatibility with recycled fuel fabrication. [1,3,9]

4.2 Fast-spectrum recycling

Fast reactors are attractive because the neutron spectrum can support fission of isotopes that are less readily consumed in thermal systems. Repeated recycling can therefore shift actinide inventories toward fission

products. OECD/NEA analyses identify fast reactors and ADS concepts as important options in advanced P&T strategies. [2,3]

4.3 What this layer can realistically achieve

The strongest defensible statement is not that actinides can simply be “removed” in one pass. A practical closed fuel cycle requires repeated separation, fabrication, irradiation, cooling and reprocessing. Losses at every step create an irreducible tail. The value of the layer is cumulative reduction of the transuranic inventory that would otherwise enter final disposal.

5. Layer 2 - Targeted Transmutation

5.1 Candidate isotopes

Important long-lived fission-product targets commonly discussed in P&T include technetium-99 and iodine-129, together with other isotopes such as selenium-79 and zirconium-93 depending on fuel-cycle assumptions and nuclear data. Actinides including plutonium, neptunium, americium and curium are also central targets. [1-4]

5.2 Reaction classes

Reaction class	Potential role	Main constraint
Fission	Destroys heavy actinide nucleus; creates lighter products	Produces a new distribution of radioactive products and energy
Neutron capture	Can move a long-lived isotope toward a shorter-lived or stable daughter	Requires favorable cross sections and pathway; capture may create another long-lived nuclide
(n,2n) / threshold reactions	Can redirect isotope inventories in selected neutron-energy regimes	Highly isotope- and spectrum-dependent; competing channels matter
Spallation neutron production	Supplies intense neutron fields for ADS	High-power accelerator, target heat removal, materials damage and reliability

5.3 Accelerator-driven systems

ADS concepts couple a high-power accelerator and spallation target to a subcritical core or blanket. Their appeal for transmutation is flexibility in neutron production and the ability to operate a multiplying system below criticality. Their disadvantages include accelerator reliability, target/window lifetime, heat removal, neutron economy, maintenance and cost. The OECD/NEA literature explicitly treats these as major R&D topics rather than solved engineering details. [3,8,9]

5.4 Why isotope-specific modelling matters

A generic statement that “neutrons shorten waste life” is insufficient. For each isotope, a systems study must follow the full reaction network, including capture, fission, decay, daughter production and secondary activation. The correct objective is therefore an optimized inventory trajectory, not maximization of raw neutron exposure.

6. Layer 3 - Durable Waste Immobilization

6.1 Why immobilization remains necessary

Transmutation changes the nuclear composition but does not eliminate the need for containment. The residual inventory must be converted into a form with predictable chemical durability, radiation tolerance, thermal behavior and mechanical integrity. The wasteform is an engineered barrier; it does not replace the broader disposal system.

6.2 Ceramic, glass and glass-ceramic options

Borosilicate vitrification is an established route for many high-level waste streams. Synroc and related ceramic/glass-ceramic approaches provide alternative or complementary wasteforms, especially for challenging compositions. ANSTO describes Synroc as a platform spanning ceramic, glass and glass-ceramic forms, with recent work extending to difficult sulphate-bearing wastes. [5-7]

6.3 Design criterion

The target should be a measurable wasteform performance envelope: low dissolution rate, retention of radionuclides under repository-relevant conditions, tolerance to self-irradiation, resistance to thermal and chemical degradation, manageable volume, and compatibility with canister and geological disposal systems.

7. Integrated System Architecture

The framework is best viewed as a closed-loop architecture rather than three isolated technologies. Separation produces target streams; target streams become recycled fuels or transmutation targets; irradiation creates new products and heat; cooling and chemical processing enable another cycle; and the residual stream is immobilized. The architecture should be optimized against a multi-objective function that includes radiotoxic inventory, mass and volume of final waste, energy balance, separations losses, secondary waste, cost, proliferation resistance and repository burden.

Stage	Primary output	Key metric	Failure/uncertainty
Partitioning	Separated target streams	Recovery + decontamination factors	Separation losses / secondary waste
Recycle	Actinide-bearing fuel/targets	Fission/transmutation rate per cycle	Fuel performance / fabrication complexity
Transmutation	Reduced long-lived inventory	Net radiotoxicity and hazard trajectory	Nuclear data / neutron economy
Immobilization	Disposal-ready wasteform	Leach rate + radiation durability	Long-term materials behavior
Disposal	Contained residual inventory	Repository dose/risk performance	Geosphere + engineered barrier uncertainty

8. Research and Development Roadmap

Step	Work package	Purpose
1	Inventory mapping	Build isotope-by-isotope mass and radiotoxicity inventories for representative reactor fuels and cooling times.
2	Nuclear reaction modelling	Quantify reaction networks, cross sections, neutron-spectrum

		sensitivity, daughter products and burnup pathways.
3	Partitioning flowsheets	Compare aqueous and pyrochemical separations with explicit accounting of losses, secondary waste and safeguards.
4	Transmutation experiments	Use irradiation and benchmark experiments to validate the most promising isotope-specific reaction pathways.
5	Fuel/target materials	Develop fuels, targets, cladding, spallation windows and structural materials able to tolerate high dose and thermal cycling.
6	Integrated demonstration	Evaluate coupled fast-reactor/ADS and recycling flowsheets at pilot or demonstration scale.
7	Wasteform qualification	Test ceramic/glass/glass-ceramic forms under repository-relevant chemical, radiation and thermal conditions.
8	Systems assessment	Compare the complete architecture with once-through fuel cycles and alternative waste-management strategies using transparent lifecycle metrics.

9. Technical Constraints and Open Questions

Energy and economics: Transmutation consumes infrastructure, fuel-cycle capacity and potentially substantial accelerator power. The architecture must show that its waste-management benefits justify its additional energy and capital requirements.

Neutron economy: Every neutron used on an unwanted capture channel can reduce transmutation efficiency. Spectrum tailoring and target placement are therefore central design variables.

Nuclear data: Accurate reaction cross sections and fission yields are necessary for credible predictions, particularly for rare isotopes and high-energy neutron spectra.

Materials: High flux produces displacement damage, helium/hydrogen production, swelling, embrittlement and corrosion. Accelerator targets and structural components may be lifetime-limiting.

Secondary waste: Chemical separation and reactor operation generate secondary waste streams. A valid comparison must track the entire system, not only the original spent-fuel inventory.

Safeguards and proliferation resistance: Partitioning and recycling of plutonium and minor actinides create safeguards requirements that must be designed into the architecture from the beginning.

Final disposal: Even an aggressively optimized P&T system is expected to leave residual radionuclides and activated materials. Disposal therefore remains a necessary endpoint for the residual inventory.

10. Expected Impact and Evaluation Metrics

The framework should be judged quantitatively. A credible future demonstration should report at least the following metrics:

- Fraction of transuranic mass removed from the final disposal stream
- Reduction in long-lived radiotoxic inventory as a function of time
- Mass and volume of final disposal forms per unit electrical energy generated
- Number of recycle/transmutation passes required and losses per pass
- Secondary radioactive waste generated by separation and fuel fabrication
- Net energy consumption and parasitic power
- Fuel/target and accelerator component lifetime
- Wasteform durability under repository-relevant conditions
- Lifecycle cost and infrastructure burden
- Safeguards, security and proliferation-resistance performance

A particularly important metric is not a single “years of radioactivity” number, because different isotopes and dose pathways behave differently. A better approach is to publish time-dependent curves of radiotoxicity, heat load, activity and repository-relevant dose metrics under clearly stated assumptions. OECD/NEA assessments emphasize this systems-level perspective. [1-4]

11. Conclusion

This white paper proposes a star-inspired conceptual direction for transforming nuclear waste at the source. Its novelty is not the invention of partitioning, fast reactors, ADS, or durable wasteforms individually; all are established areas of nuclear research. The conceptual contribution is the deliberate integration of these elements into a single three-layer objective: recover what can be recycled, transmute what can be usefully transformed, and immobilize the irreducible residue in an engineered disposal-ready form.

The scientific case is strongest when the framework is stated conservatively. Nuclear waste cannot simply be made to vanish. Transmutation creates daughter products, consumes infrastructure and may be inefficient for some isotopes. Geological disposal remains an important reference endpoint for residual long-lived waste. The opportunity is instead to reduce the quantity and long-lived radiotoxic burden of the final waste stream, potentially moving more of the problem toward timescales that are easier to manage with engineered and institutional systems.

The next step is therefore not a claim of deployment but a disciplined isotope-by-isotope systems study. If such modelling demonstrates a favorable combination of transmutation efficiency, energy balance, economic performance, safeguards, materials lifetime and wasteform durability, the framework could provide a rational basis for experimental programs and future demonstration systems.

References

[1] OECD Nuclear Energy Agency (NEA). Actinide and Fission Product Partitioning and Transmutation: Status and Assessment Report. NEA, 1999.

[2] OECD Nuclear Energy Agency (NEA). Fuels and Materials for Transmutation: A Status Report. NEA No. 5419, 2005.

[3] OECD Nuclear Energy Agency (NEA). Accelerator-driven Systems (ADS) and Fast Reactors (FR) in Advanced Nuclear Fuel Cycles: A Comparative Study. NEA, 2002.

[4] OECD Nuclear Energy Agency (NEA). Physics and Safety of Transmutation Systems: A Status Report. NEA No. 6090, 2006.

[5] Gregg, D. J., Farzana, R., Dayal, P., Holmes, R. L., & Triani, G. Synroc technology: perspectives and current status (review). Journal of the American Ceramic Society, 103(10), 5424-5441, 2020. DOI: 10.1111/jace.17322.

[6] ANSTO. ANSTO Synroc Waste Treatment Technology and facility documentation. Australian Nuclear Science and Technology Organisation. Accessed 2026.

[7] ANSTO. ANSTO advances solution for challenging sulphate-bearing radioactive wastes. 31 July 2026.

[8] International Atomic Energy Agency (IAEA). Radioactive Waste Management: material on transmutation of long-lived technetium-99, iodine-129 and actinides. IAEA publication series.

[9] OECD Nuclear Energy Agency (NEA). Working Party on Scientific Issues in Partitioning and Transmutation (WPPT): scope and activities, including accelerator reliability, target performance, chemical partitioning and nuclear data.

Scientific positioning note: Numerical claims in this paper are deliberately presented as system-level objectives or ranges supported by published P&T literature rather than as guaranteed performance. Any deployment decision would require detailed reactor physics, fuel-cycle, materials, safety, economics, safeguards and repository assessments.