

HARDWARE-NATIVE CAPABILITIES

App-like access to secure device capabilities

MULTIMODAL PHYSICAL AUTHENTICATION

The smartphone body as an intelligent authentication surface

Anup Jayant Dharangutti

dharangutti.in

Open Innovation / Engineering Concept Paper

Version 2.0 • September 2026

Executive Summary

This paper proposes three independently implementable concepts for future smartphones. Their common philosophy is to treat the **physical device itself as a programmable computing resource**, rather than limiting innovation to the display and application layer.

Core thesis

The future smartphone can combine programmable mechanical interaction, hardware-native secure capabilities and distributed physical sensing to create capabilities that conventional rigid touchscreen devices cannot easily provide.

The concepts are architectural directions, not finished product specifications. Multiple implementation paths are intentionally left open.

1. Design Philosophy

A future smartphone can be viewed as four interacting layers: **physical structure** → **hardware capabilities** → **operating system** → **applications**. These concepts explore what becomes possible when the first two layers are deliberately designed as programmable computing resources.

Design principle: exploit capabilities that the physical device already possesses—or can be engineered to possess—and expose them through clean software abstractions.

2. Concept 1 — Programmable Flex Interaction

Foldable phones introduce a mechanical degree of freedom that conventional smartphones do not have. Instead of using the hinge only to fold and unfold the device, the hinge region could become a **controlled flexible input zone**.

2.1 From Foldable Mechanism to Input Device

When unfolded, the phone remains substantially flat for normal use. A deliberately applied small flex can be sensed and interpreted as an input: **physical flex** → **sensing** → **tactile confirmation** → **software event**.

New input dimension: controlled mechanical deformation becomes a programmable input channel.

2.2 Gesture Vocabulary

Physical gesture	Possible software meaning
Slight flex	Select / activate
Flex left	Previous item / tool
Flex right	Next item / tool
Double flex	Confirm / special action
Flex and hold	Continuous control
Increasing flex	Analog parameter

2.3 Tactile Click

A flex gesture should provide unambiguous feedback. A click-like response could come from controlled mechanical resistance, a hinge detent, haptic actuation, or a combination—similar in user perception to a mouse button or physical switch.

2.4 Application Examples

Drawing: flex magnitude could control brush size or tool selection.

Music: left/right flex could navigate tracks.

Camera: flex could control zoom or exposure.

Gaming: flex could become an application-specific control.

Architectural proposition: the physical geometry of a foldable smartphone becomes a programmable input API.

3. Concept 2 — Hardware-Native Capability Architecture

A smartphone manufacturer that controls significant portions of hardware, firmware, secure processing and operating-system integration can implement selected functions deeper than the conventional application layer.

3.1 App-Like Interface, Hardware-Native Function

The user can still experience a capability as an application or One UI service. Internally, however, security-critical functionality can be implemented as a hardware-backed primitive.

Example: Digital Car Key

User interface: app-like

Underlying capability: secure hardware + firmware + manufacturer capability layer

Critical credential operations: protected execution environment

3.2 Capability Layer

Potential capabilities include digital vehicle keys, secure access credentials, identity credentials, payment credentials, enterprise authentication, home access, UWB-based secure proximity and specialized device-to-device authentication.

3.3 Principle

App-like access to hardware-native capabilities. Applications become interfaces to trusted capabilities rather than necessarily containing the complete implementation themselves.

3.4 Engineering Space

Some functions may benefit from secure hardware storage; others from hardware acceleration, trusted execution, dedicated connectivity or specialized sensors. The objective is to identify where hardware-level implementation provides a security, reliability, latency or power advantage.

4. Concept 3 — Multimodal Physical Authentication Surface

The human hand naturally contacts a phone during ordinary use. Rather than requiring the user to deliberately place a finger on one sensor every time authentication is required, the phone could potentially recognize the person interacting with it through a distributed sensing architecture.

Core insight

A natural grip contains information about the hand: contact locations, geometry, pressure, movement and potentially biometric characteristics. A future smartphone could electronically sense selected aspects of that interaction.

4.1 Distributed Sensing Surface

The back and sides of the phone could contain distributed sensing elements—conceptually a non-visual sensing fabric or “biometric pixels.” These need not be conventional fingerprint sensors.

Possible sensing families: capacitive/contact, optical or infrared, time-of-flight / LiDAR-like, pressure/force, electrical/impedance, or combinations of future technologies.

4.2 Two-Tier Sensing Architecture

Mode	Purpose	Sensing strategy
Passive / low power	Interaction awareness	Minimal sensing; owner/trusted/unfamiliar classification
Active authentication	High-confidence verification	Stronger optical/ToF/LiDAR-like/biometric or multimodal scan
Fallback	Maximum assurance	Fingerprint / face / PIN / password

Power principle: high-resolution sensing can be event-driven. Expensive sensing need not operate continuously if strong authentication is only required at particular moments.

5. Sensor Fusion and Security Intelligence

No individual sensing technology needs to solve the complete problem. Multiple signals can be combined in a secure sensor-fusion engine.

Contact pattern + grip geometry + pressure + optical/ToF information + biometric characteristics
→ **secure sensor fusion** → **confidence** → **authentication policy**

5.1 Confidence-Based Authentication

High confidence could permit frictionless authentication; medium confidence could invoke a stronger biometric check; low confidence could require a PIN/password.

5.2 Trusted Secondary Users

Real devices are often handled by people other than the owner. A family member may answer a call or view photographs. The system could distinguish **owner**, **trusted secondary user**, **known occasional user** and **unrecognized user**, with user-controlled permissions.

5.3 Device Interaction Security History

The same sensing infrastructure could create a privacy-preserving history: *08:42 — Owner; 09:17 — Trusted secondary user; 14:06 — Unrecognized interaction*. The objective is not to record video or retain raw biometric data.

Potential security feature — Device Chain-of-Custody Awareness

The phone could identify unusual physical interaction while the owner was absent, its frequency, and whether the interaction pattern was familiar or unfamiliar.

6. Privacy-by-Architecture

Raw sensing → secure local processing → derived identity / event → minimal retained information

Potential principles include local processing wherever practical; secure hardware for sensitive biometric operations; applications receiving authentication results rather than raw biometric signals; encrypted interaction history; and explicit user control over trusted users and retention.

7. Unified Future Smartphone Architecture

Layer	Future capabilities
Physical device	Flexible hinge, distributed sensing surface, specialized sensors
Secure hardware	Biometric processing, credentials, device identity
Manufacturer capability layer	Hardware-native services and secure APIs
Operating system	Flex-input API, authentication framework, capability APIs, security intelligence
Applications	Context-specific experiences built on those primitives

8. Engineering Solution Space

The concepts intentionally leave room for multiple technical implementations. The capability and architecture are defined first; engineering can then optimize the implementation.

Flex system: hinge mechanics, compliant structures, strain/position sensing, haptics, durability, calibration and accidental-input rejection.

Authentication surface: distributed sensor arrays, optical/IR, ToF/LiDAR-like sensing, capacitive methods, pressure, electrical/impedance sensing and sensor fusion.

Security: secure execution, hardware-backed keys, anti-spoofing, event integrity, privacy controls and policy enforcement.

Power: event-driven sensing, low-duty-cycle monitoring, hardware wake-up paths and adaptive sensor selection.

Software: standardized APIs, permission models, application-specific interpretation, authentication policy and user-visible controls.

9. Key Engineering Questions

Mechanical: What flex range is safe and repeatable? How can a tactile click be produced without compromising display or hinge life?

Sensing: What signal provides the best discrimination per watt? Can natural grip variations be handled without excessive false rejection?

Security: How should spoofing, replay and sensor attacks be prevented? What confidence is sufficient for each operation?

Privacy: What information should be retained, for how long, and who can access it?

Manufacturing: Can distributed sensing elements be integrated into future chassis materials at acceptable cost?

10. Potential Benefits

New physical interaction

Foldable geometry becomes an input channel rather than only a mechanical feature.

Lower-friction authentication

The device can potentially authenticate naturally without repeatedly demanding an explicit biometric gesture.

Hardware-software differentiation

Manufacturer-controlled hardware can expose secure capabilities through clean OS interfaces.

Device security intelligence

The phone can potentially understand who has interacted with it and recognize unusual patterns.

11. Open Innovation Position

These concepts are intentionally presented as open engineering ideas. The author does not claim that every underlying sensor, component or implementation is unprecedented. Similar technologies, research or implementations may already exist and should be evaluated as relevant prior art or related work.

The purpose of publication is to document the proposed architectural combinations and invite engineers, researchers, manufacturers, universities, startups and developers to evaluate, critique, improve or implement them.

Open invitation

The concepts may be extended, challenged, redesigned or implemented using better technologies as they become available. The objective is engineering exploration rather than a claim to a finished product.

12. Conclusion

The next generation of smartphones may not be defined solely by faster processors, better cameras or larger displays. A deeper evolution may occur when the **physical smartphone becomes part of the computing interface**.

A foldable can become a programmable physical controller. A manufacturer-controlled hardware capability layer can provide secure functions beneath app-like experiences. A distributed sensing surface can allow the device to recognize natural interaction and potentially develop a new class of security awareness.

“The future smartphone should not merely be a computer behind a touchscreen. The phone itself should become an intelligent, programmable physical interface.”

Open Innovation & Prior Art Statement

This paper presents independent engineering concepts for open discussion and development. It does not represent a claim that the underlying technologies are new in isolation, nor does it constitute a patentability, legal or technical certification. The concepts are hypotheses and architectural proposals for further investigation.

Author

Anup Jayant Dharangutti

Independent engineering / open innovation
dharangutti.in

Version 2.0 • September 2026

Suggested citation

Dharangutti, Anup Jayant. *Future Smartphone Architecture: Three Open Engineering Concepts for the Next Generation of Mobile Computing*. Open Innovation Concept Paper, Version 2.0, September 2026.