EXERCISE – 8

Question: Execute and display the results of the following Nmap service version and OS detection commands in Kali Linux Operating System:

1. Detect the version of services running
2. Aggressive scan
3. Detect operating system of the target

Aim

To execute and display the results of Nmap service version and OS detection commands in Kali Linux.

1. DETECT VERSION OF SERVICES

Command:

nmap -sV 127.0.0.1

Use: The -sV option is used to detect the version of services running on the target.

```
┌──(dharani㉿kali)-[~]
└─$ nmap -sV 127.0.0.1
Starting Nmap 7.99 ( https://nmap.org ) at 2026-10-07 09:43 +0530
Nmap scan report for localhost (127.0.0.1)
Host is up (0.0000040s latency).
All 1000 scanned ports on localhost (127.0.0.1) are in ignored states.
Not shown: 1000 closed tcp ports (reset)

Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 0.59 seconds
```

2. AGGRESSIVE SCAN

Command:

nmap -A 127.0.0.1

Use: The -A option performs an aggressive scan including service, OS, and other detection.

```
┌──(dharani㉿kali)-[~]
└─$ nmap -A 127.0.0.1
Starting Nmap 7.99 ( https://nmap.org ) at 2026-10-07 09:45 +0530
Nmap scan report for localhost (127.0.0.1)
Host is up (0.000071s latency).
All 1000 scanned ports on localhost (127.0.0.1) are in ignored states.
Not shown: 1000 closed tcp ports (reset)
Too many fingerprints match this host to give specific OS details
Network Distance: 0 hops

OS and Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 2.20 seconds
```

3. DETECT OPERATING SYSTEM

Command:

sudo nmap -O 127.0.0.1

Use: The -O option is used to detect the operating system of the target.



Result

Thus, the Nmap service version detection, aggressive scan, and operating system detection commands were successfully executed in Kali Linux, and the results were displayed.