RAJALAKSHMI ENGINEERING COLLEGE

Dharanipriyn S 251801056-2025-AIDS

Started on	Monday, 24 August 2026, 3:58 PM
State	Finished
Completed on	Monday, 24 August 2026, 3:59 PM
Time taken	53 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Given an array of N integer, we have to maximize the sum of arr[i] * i, where i is the index of the element (i = 0, 1, 2, ..., N).Write an algorithm based on Greedy technique with a Complexity O(nlogn).

Input Format:

First line specifies the number of elements-n

The next n lines contain the array elements.

Output Format:

Maximum Array Sum to be printed.

Sample Input:

5

2 5 3 4 0

Sample output:

40

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>
#include <stdlib.h>

int compare(const void *a, const void *b)
{
    int x = *(int *)a;
    int y = *(int *)b;

    if (x < y)
        return -1;
    else if (x > y)
        return 1;
    else
        return 0;
}

int main()
{
    int n, i;
    long long sum = 0;
    int a[100000];

    scanf("%d", &n);

    for (i = 0; i < n; i++)
    {
        scanf("%d", &a[i]);
    }

    qsort(a, n, sizeof(int), compare);

    for (i = 0; i < n; i++)
    {
        sum += (long long)a[i] * i;
    }

    printf("%lld", sum);

    return 0;
}
```

	Input	Expected	Got	
✔	5 2 5 3 4 0	40	40	✔
✔	10 2 2 2 4 4 3 3 5 5 5	191	191	✔
✔	2 45 3	45	45	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course