

```

mysql> -- =====
mysql>
mysql> -- Allow function creation (needed if binary logging is on)
mysql> SET GLOBAL log_bin_trust_function_creators = 1;
Query OK, 0 rows affected, 1 warning (0.01 sec)

mysql>
mysql> DELIMITER //
mysql>
mysql> CREATE FUNCTION CustomerLevel(p_CREDITLIMIT INT) RETURNS VARCHAR(10)
    -> DETERMINISTIC
    -> BEGIN
    ->     DECLARE lvl VARCHAR(10);
    ->     IF p_CREDITLIMIT > 50000 THEN
    ->         SET lvl = 'PLATINUM';
    ->     ELSEIF (p_CREDITLIMIT <= 50000 AND p_CREDITLIMIT >= 10000) THEN
    ->         SET lvl = 'GOLD';
    ->     ELSEIF p_CREDITLIMIT < 10000 THEN
    ->         SET lvl = 'SILVER';
    ->     END IF;
    ->     RETURN (lvl);
    -> END //
Query OK, 0 rows affected (0.01 sec)

mysql>
mysql> DELIMITER ;
mysql>
mysql> -- Test Problem 1
mysql> SELECT CNAME, CustomerLevel(CREDITLIMIT) FROM customer ORDER BY CNAME;
+-----+-----+
| CNAME | CustomerLevel(CREDITLIMIT) |
+-----+-----+
| DINESH | GOLD |
| NAGENDRA | PLATINUM |
| RAJA | GOLD |
| RAMU | SILVER |
+-----+-----+
4 rows in set (0.01 sec)

```

```

mysql> -- =====
mysql>
mysql> -- Set recursion depth (required for recursive procedures)
mysql> SET @@GLOBAL.max_sp_recursion_depth = 255;
Query OK, 0 rows affected (0.01 sec)

mysql> SET @@session.max_sp_recursion_depth = 255;
Query OK, 0 rows affected (0.00 sec)

mysql>
mysql> DELIMITER $$
mysql>
mysql> CREATE PROCEDURE factorial(IN n INT, OUT fact INT)
-> BEGIN
->     DECLARE temp_fact INT;
->     IF n = 1 THEN
->         SET fact = 1;
->     ELSE
->         CALL factorial(n - 1, temp_fact);
->         SET fact = n * temp_fact;
->     END IF;
-> END$$
Query OK, 0 rows affected (0.01 sec)

mysql>
mysql> DELIMITER ;
mysql>
mysql> -- Test Problem 2
mysql> CALL factorial(5, @fact);
Query OK, 0 rows affected (0.00 sec)

mysql> SELECT @fact;
+-----+
| @fact |
+-----+
|   120 |
+-----+
1 row in set (0.00 sec)

```