

```

mysql> -----
mysql> DELIMITER $$
mysql>
mysql> CREATE PROCEDURE build_email_list (INOUT email_list VARCHAR(4000))
-> BEGIN
->     DECLARE v_finished INTEGER DEFAULT 0;
->     DECLARE v_email VARCHAR(100) DEFAULT "";
->
->     -- Cursor to fetch all emails from employees table
->     DECLARE email_cursor CURSOR FOR
->         SELECT email FROM employees;
->
->     -- Handler to detect when there are no more rows to fetch
->     DECLARE CONTINUE HANDLER FOR NOT FOUND SET v_finished = 1;
->
->     OPEN email_cursor;
->
->     get_email: LOOP
->         FETCH email_cursor INTO v_email;
->         IF v_finished = 1 THEN
->             LEAVE get_email;
->         END IF;
->         SET email_list = CONCAT(v_email, ";", email_list);
->     END LOOP get_email;
->
->     CLOSE email_cursor;
-> END$$
Query OK, 0 rows affected (0.01 sec)

mysql>
mysql> DELIMITER ;
mysql>

```

```

-> DECLARE CONTINUE HANDLER FOR NOT FOUND SET v_finished = 1;
->
-> OPEN email_cursor;
->
-> get_email: LOOP
->     FETCH email_cursor INTO v_email;
->     IF v_finished = 1 THEN
->         LEAVE get_email;
->     END IF;
->     SET email_list = CONCAT(v_email, ";", email_list);
-> END LOOP get_email;
->
-> CLOSE email_cursor;
-> END$$
Query OK, 0 rows affected (0.01 sec)

mysql>
mysql> DELIMITER ;
mysql>
mysql> -- =====
mysql> -- CALL the procedure
mysql> -- =====
mysql> SET @email_list = "";
Query OK, 0 rows affected (0.00 sec)

mysql> CALL build_email_list(@email_list);
Query OK, 0 rows affected (0.01 sec)

mysql>
mysql> SELECT @email_list;
+-----+
| @email_list |
+-----+
| pharry@warnerbros.com;kclark@deconics.com;stony@marvel.com; |
+-----+
1 row in set (0.00 sec)

mysql> |

```