

```

mysql>
mysql>
mysql> -- =====
mysql> -- TRIGGER: before_student_update
mysql> -- =====
mysql> DELIMITER //
mysql>
mysql> CREATE TRIGGER before_student_update
    -> BEFORE UPDATE ON student
    -> FOR EACH ROW
    -> BEGIN
    ->     INSERT INTO student_audit
    ->     SET action      = 'update',
    ->         student_id  = OLD.id,
    ->         lastname    = OLD.name,
    ->         changedat   = NOW();
    -> END //
Query OK, 0 rows affected (0.01 sec)

mysql>
mysql> DELIMITER ;
mysql>
mysql>
mysql> -- =====
mysql> -- TEST: Update a student record
mysql> -- =====
mysql> UPDATE student SET name = 'tony_stark_c' WHERE id = 3;
Query OK, 1 row affected (0.01 sec)
Rows matched: 1  Changed: 1  Warnings: 0

mysql>
mysql> -- Check the audit log
mysql> SELECT * FROM student_audit;
+----+-----+-----+-----+-----+
| id | student_id | lastname | changedat | action |
+----+-----+-----+-----+-----+
| 1  |          3 | tony stark | 2026-08-28 19:57:50 | update |
+----+-----+-----+-----+-----+
1 row in set (0.00 sec)

```