

Database changed

mysql>

mysql> -- -----

mysql> -- 1. REPLACE() - Replaces all occurrences of a substring

mysql> -- -----

mysql> SELECT REPLACE('Welcome to MySQL World', 'World', 'Tutorial') AS Replace_Result;

Replace_Result
Welcome to MySQL Tutorial

1 row in set (0.00 sec)

mysql>

mysql> -- -----

mysql> -- 2. REPEAT() - Repeats a string a specified number of times

mysql> -- -----

mysql> SELECT REPEAT('SQL', 3) AS Repeat_Result;

Repeat_Result
SQLSQLSQL

1 row in set (0.00 sec)

mysql>

mysql> -- -----

mysql> -- 3. REVERSE() - Reverses the order of characters in a string

mysql> -- -----

mysql> SELECT REVERSE('MySQL') AS Reverse_Result;

Reverse_Result
LQSyM

1 row in set (0.00 sec)

```

mysql>
mysql> -- -----
mysql> -- 4. RIGHT() - Extracts characters from the right side
mysql> -- -----
mysql> SELECT RIGHT('Database Management', 10) AS Right_Result;
+-----+
| Right_Result |
+-----+
| Management  |
+-----+
1 row in set (0.00 sec)

mysql>
mysql> -- -----
mysql> -- 5. LEFT() - Extracts characters from the left side
mysql> -- -----
mysql> SELECT LEFT('Database Management', 8) AS Left_Result;
+-----+
| Left_Result |
+-----+
| Database    |
+-----+
1 row in set (0.00 sec)

mysql>
mysql> -- -----
mysql> -- 6. RPAD() - Pads a string on the right to a given length
mysql> -- -----
mysql> SELECT RPAD('MySQL', 10, '*') AS Rpad_Result;
+-----+
| Rpad_Result |
+-----+
| MySQL***** |
+-----+
1 row in set (0.00 sec)

```

```
mysql>
mysql> -- -----
mysql> -- 7. LPAD() - Pads a string on the left to a given length
mysql> -- -----
mysql> SELECT LPAD('MySQL', 10, '*') AS Lpad_Result;
+-----+
| Lpad_Result |
+-----+
| *****MySQL |
+-----+
1 row in set (0.00 sec)

mysql>
mysql> -- -----
mysql> -- 8. ASCII() - Returns ASCII value of leftmost character
mysql> -- -----
mysql> SELECT ASCII('A') AS Ascii_Result;
+-----+
| Ascii_Result |
+-----+
|          65 |
+-----+
1 row in set (0.00 sec)

mysql>
mysql> -- -----
mysql> -- 9. BIN() - Returns binary representation of a number
mysql> -- -----
mysql> SELECT BIN(15) AS Bin_Result;
+-----+
| Bin_Result |
+-----+
| 1111      |
+-----+
1 row in set (0.00 sec)

mysql>
mysql> -- -----
mysql> -- 10. OCT() - Returns octal representation of a number
mysql> -- -----
mysql> SELECT OCT(15) AS Oct_Result;
+-----+
| Oct_Result |
+-----+
| 17         |
+-----+
1 row in set (0.00 sec)

mysql>
mysql> -- -----
mysql> -- ALL FUNCTIONS TOGETHER IN A SINGLE RESULT (for one-shot demo)
mysql> -- -----
mysql> SELECT
--> REPLACE('Welcome to MySQL World', 'World', 'Tutorial') AS Replace_Result,
--> REPEAT('SQL', 3) AS Repeat_Result,
--> REVERSE('MySQL') AS Reverse_Result,
--> RIGHT('Database Management', 10) AS Right_Result,
--> LEFT('Database Management', 8) AS Left_Result,
--> RPAD('MySQL', 10, '*') AS Rpad_Result,
--> LPAD('MySQL', 10, '*') AS Lpad_Result,
--> ASCII('A') AS Ascii_Result,
--> BIN(15) AS Bin_Result,
--> OCT(15) AS Oct_Result;
+-----+-----+-----+-----+-----+-----+-----+-----+-----+
| Replace_Result | Repeat_Result | Reverse_Result | Right_Result | Left_Result | Rpad_Result | Lpad_Result | Ascii_Result | Bin_Result | Oct_Resu |
+-----+-----+-----+-----+-----+-----+-----+-----+-----+
| Welcome to MySQL Tutorial | SQLSQLSQL | LQSyM | Management | Database | MySQL***** | *****MySQL | 65 | 1111 | 17 |
+-----+-----+-----+-----+-----+-----+-----+-----+-----+
1 row in set (0.00 sec)
```