

```

mysql> CREATE FUNCTION IncomeLevel(monthly_value INT)
-> RETURNS VARCHAR(20)
-> DETERMINISTIC
-> BEGIN
->     DECLARE income_level VARCHAR(20);
->
->     CASE
->         WHEN monthly_value <= 4000 THEN
->             SET income_level = 'Low Income';
->
->         WHEN monthly_value <= 5000 THEN
->             SET income_level = 'Avg Income';
->
->         ELSE
->             SET income_level = 'High Income';
->     END CASE;
->
->     RETURN income_level;
-> END //

```

Query OK, 0 rows affected (0.01 sec)

```

mysql>
mysql> DELIMITER ;
mysql> SELECT IncomeLevel(3000);
+-----+
| IncomeLevel(3000) |
+-----+
| Low Income        |
+-----+
1 row in set (0.00 sec)

```

```

mysql>
mysql> SELECT IncomeLevel(4500);
+-----+
| IncomeLevel(4500) |
+-----+
| Avg Income        |
+-----+
1 row in set (0.00 sec)

```

```

mysql>
mysql> SELECT IncomeLevel(5300);
+-----+
| IncomeLevel(5300) |
+-----+
| High Income       |
+-----+
1 row in set (0.00 sec)

```

```

mysql>
mysql> CREATE FUNCTION CALCINCOME2(starting_value INT)
-> RETURNS INT
-> DETERMINISTIC
-> BEGIN
->     DECLARE income INT;
->
->     SET income = 0;
->
->     label1: LOOP
->
->         SET income = income + starting_value;
->
->         IF income < 4000 THEN
->             ITERATE label1;
->         END IF;
->
->         LEAVE label1;
->
->     END LOOP label1;
->
->     RETURN income;
-> END //

```

Query OK, 0 rows affected (0.00 sec)

```

mysql>
mysql> DELIMITER ;
mysql>
mysql>
mysql> -- =====
mysql> -- TEST PROGRAM 2
mysql> -- =====
mysql>
mysql> SELECT CALCINCOME2(2100);

```

```

+-----+
| CALCINCOME2(2100) |
+-----+
|           4200    |
+-----+

```

1 row in set (0.00 sec)